Spacial Thalassa ClimaSys

Catalogue 2021

Universal Enclosures

More than 60 years protecting your equipment

se.com/enclosures

Life Is On Schneider Electric

Life Is On

Contents

Overview 4

Services / Software / General Information 8
Selection Guide (Reference overview) 10

Spacial

1 Steel Industrial Boxes 30
2 Steel wall-mounting enclosures 42
3 Steel floor-standing enclosures 80
4 Stainless-Steel Industrial Boxes 122
5 Stainless steel wall-mounting enclosures 134
6 Stainless steel floor-standing enclosures 146

Thalassa

7 Insulating boxes 156
8 Insulating wall-mounting enclosures 186
9 Insulating floor-standing enclosures 204

Accessories

10 Accessories 238

Applicative and customised solutions

11 Applicative and customised solutions 324

ClimaSys

12 Thermal management system 536

Technical guides

13 Technical guides and spare parts 622

Index

14 Index of references 658

Green Premium™

The Green Premium program stands for our commitment to deliver customer valued sustainable performance. It has been upgraded with recognized environmental claims and extended to cover all o ers including Products, Services and Solutions.

More than 75% of our product sales of ouer superior transparency on the material content, regulatory information and environmental impact of ourproducts:

- RoHS compliance
- REACh substance information
- Industry leading # of PEP's*
- Circularity instructions

*PEP: Product Environmental Profile (i.e. Environmental Product Declaration)

CO_2 and P&L impact through… Resource Performance

Green Premium brings improved resource e ciency throughout an asset's lifecycle. This includes e cient use of energy and natural resources, along with the minimization of CO_2 emissions.

Cost of ownership optimization through… Circular Performance

We're helping our customers optimize the total cost of ownership of their assets. To do this, we provide IoT-enabled solutions, as well as upgrade, repair, retrofi t, and remanufacture services.

Peace of mind through… Well-being Performance

Green Premium products are RoHS and REACh compliant. We're going beyond regulatory compliance with step-by-step substitution of certain materials and substances from our products.

Improved sales through… Differentiation

Green Premium delivers strong value propositions through third-party labels and services. By collaborating with third-party organizations we can support our customers in meeting their sustainability goals such as green buildingcertifications.

Discover what we mean by green
Check your products!

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

How to define an enclosures solution?

Invariables

Switchgear and Controlgear are the cornerstone of all electrical system. Industry, infrastructure, building, energy, transport, every segment. The correct enclosure and thermal management selection is crucial to guaranty the targeted performance. Safeguards of equipment installed inside and consequently, service continuity.



The correct selection of an enclosure and thermal solution

Many influences must be considered when defining an enclosure system. They may be grouped in three groups:

- **Protection (Equipment and people)**
- **Thermal management**
- **Solution profitability**

The environment and the enclosure

The table below is only indicative and not binding. It shows, in a general concept, the optimized performance of the Universal Enclosures ranges according to de environment conditions taking into account technical and commercial criteria:

■■■ **Very recommended**
■ **Recommended**
- **Not recommended**

Environment	Enclosure material						
	Steel	Steel Heavy Duty	Stainless steel 304L	Stainless steel 316L	Stainless steel 316L Paint	Polyester	Polyester Heavy Duty
Indoor clean environment [1]	■■■	■	■	■	■	■	■
Hard cleaning process [2]	-	-	■■■	■■■	-	-	-
Outdoor (no public access)	-	■■■	■	■	■	■■■	■■■
Outdoor (public access)	-	■	■	■	■	■	■■■
Harsh chemicals	-	■	■■■	■■■	■■■	■■■	■■■
Solar radiation	-	■■■	-	■ [4]	■ [4]	■■■	■■■
Sand storm	-	-	■■■	■■■	-	■	■
Temperature > 40ºC [3]	■■■	■■■	■■■	■■■	■■■	■■■	■■■
Temperature < 5ºC [3]	■■■	■■■	■■■	■■■	■■■	■■■	■■■
Salty environment	-	-	-	■■■	■■■	■■■	■■■
Sea water splashes	-	-	-	■■■	■■■	■■■	■■■
Humidity > 70% [3]	-	■■■	■■■	■■■	■■■	■■■	■■■
Impact	■■■	■■■	■■■	■■■	■■■	■■■	■■■
Vandalism	-	■■■	■	■	■	■	■■■
Burglary	-	■■■	■	■	■	■	■■■
Strong pollution	■	■■■	■■■	■■■	■■■	■■■	■■■
Vibration (Marine application)	■■■	-	■■■	■■■	■■■	■■■	-
Seismic	■■■	-	-	-	-	-	-
Electro Magnetic Interference	■■■	-	-	-	-	-	-

[1] Not considering F&B process
[2] e.g. F&B process
[3] Always using ClimaSys solutions
[4] Marine solar plants

Thermal management

Thermal management system must guaranty the temperature and humidity controlled inside the enclosure.
The correct solution must be based on a robust process starting on the environment diagnostic, going to the parameters calculations and defining the best architecture (Enclosures + Equipment installed + Thermal solution).
ClimaSys is the definitive solution based on ClimaSys DT / EffiClima / ProClima.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Schneider Electric

Our Universal Enclosures ranges, solutions for each application

Spacial

Metal enclosures and boxes

From our small boxes to large suitable floor-standing enclosures, with the Spacial range you can find the perfect fit for your applications. Our extensive range of easy-to-use accessories helps you save time during your projects. Select between steel or stainless steel to better suit the installation environment. In our stainless steel offer you can find the optimal solution where cleanliness is required, or for highly corrosive environments.

Thalassa

Insulating enclosures

Working in difficult environments can, without the right protection, expose your installation to chemical or aggressive substances. Developed to efficiently protect it; Our Thalassa offer, from boxes to floor-standing enclosures, made in fibreglassreinforced polyester, resists in hard conditions and outdoor applications. Our Thalassa industrial boxes in ABS or polycarbonate are strong, easy to install and designed to be used in highly demanding environments.

ClimaSys



Thermal management

Preserving and keeping the right temperature inside your enclosure is vital for maximising the lifetime of your installed devices. With our ClimaSys offer you can find the right solution, be it Ventilation, Cooling or Heating, including control units for temperature, humidity and much more.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Industry and Infrastructure Offer

A material for every environment

Steel

Indoor non-clean industrial environment
The industrial environment in mechanical plants is especially demanding as regards the protection of electric and electronic components against dust, splashing with oil and impacts. This environment therefore requires a range that is suited to the applications and easy to implement.
- Standard range, for industry.
- E.M.C. just available for WM (S3HF)
- Range of ATEX enclosures, for potentially explosive atmospheres.

Solution:
The Spacial range in steel
(wall-mounting, monobloc and suitable floor-standing enclosures).

304L - 316L stainless steel

Demanding industrial environment
Food and beverage, pharmaceutical, petrochemical and infrastructure industries are particularly demanding in terms of hygiene and resistance to corrosion. With two grades of stainless steel:
- 304L stainless steel:
  Resistance to corrosion and cleanability
  (often used in food production environments).
- 316L stainless steel, also known as "marine stainless steel":
  Very high resistance to corrosion (saline or chlorinated environment).

Solution:
The Spacial range in stainless steel
(wall-mounting, monobloc and suitable floor-standing enclosures).

Insulating polyester and plastic materials (ABS, polycarbonate)



Infrastructures and industrial environments
Outdoor infrastructures and electrical installations are exposed to direct sunlight, rain, saline mist, extreme temperatures, oil splashes, chemical and corrosive agents.zt.
- Standard range, for industry and infrastructures.

Solution:
The Thalassa range
(boxes, wall-mounting and floor-standing enclosures).

Heavy Duty materials

Severe outdoor environments, generally requested by OEMs, telecom, water treatment and transportation
Polyester Heavy Duty is suitable for outdoor public areas thanks to its multiple virtues:
- pressure and shock resistant (IEC 61439-5: 2010),
- anti-posting thanks to its special ribbed-surface door,
- insulated (ready to be Class II according to IEC 61439-1: 2011).

Steel Heavy Duty enclosures are designed for outdoor private areas:
- they are engineered to resist aggressive environments (anti-corrosion certification class C4H, ISO 12944:1999).

Solution:
The Thalassa PHD and Spacial S3HD and SFHD ranges
(wall-mounting and floor-standing).

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Selection tools

www.se.com

Our web site allows you to access all the Schneider Electric products in just two clicks with direct links to:
- A complete library of technical documents, catalogues, FAQs brochures, etc.
- Certificates.
- 2D and 3D drawings.
- Selection Guides from the e-catalogue.
- Product discovery sites.

You may also find illustrated overviews, news to which you can subscribe, a list of country contacts and more useful information.

Digital Offer

ProClima

Find the best thermal solution for your enclosure
Select and calculate your thermal management requirements, according to the environment and the electrical/electronic devices installed inside the enclosure.

EffiClima

Create a complete and accurate tracking report of thermal conditions
EffiClima software translates data into a report on temperature, humidity, and dew point. It provides security for your enclosures by monitoring and controlling the entire application environment directly.



Digital Rules

Find the accessories that suit your enclosure
The digital rules allow you to select the best components from the current product range. There will be no risk of mistake, since product and accessory selection take place automatically, saving you time and money.

Spacial.conf

Get your enclosure pre-engineered for your special needs
Spacial.conf software gives you total autonomy to configure and quote enclosures with services (cut-outs, painting, accessory mounting) in less than 3 minutes. Spacial.conf is designed for convenient, error-free, and time-saving orders.

Have a smartphone or a tablet? Scan this

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

The customised solutions

Over 60 years of experience, knowledge and expertise to have the best enclosure solution that meets your needs.

Two offer levels to cover your different requirements

Configured:

the enriched standard offer

Feasibility automatically guaranteed by the configurator software Spacial.conf, which gives you autonomy and flexibility to quickly define your customized enclosure.

Delivery date information.

Specific:

the co-developed offer

Special dimensions, accessories and logistic needs.
You participate to the whole development process of your "Tailor-made" solution.

According to co-developed specifications.

	Steel	configured for Stailes steel boxes	Insulating material
Boxes	● ○	○	● ○
Wall-mounting	● ○	● ○	● ○
Compact floor-standing	● ○	● ○	● ○
Modular floor-standing	● ○	● ○	● ○

● Configured offers

○ Specific offers

Time saving
Delivered with cut-outs and painting:
no waste of time

Logistics
Flexible management of your logistic option (scheduled delivery service for on-going orders), Special packaging

Installation simplified
Enclosures delivered with cut-outs:
you don't need special tools

Ergonomic design
Customized project dedicate to your personal concern

Life time increased
Cut-outs done before painting guarantees better anti-corrosion/ sealing, Painting service for better protection

Quality improved
No burrs on edges of cut-outs, Guaranteed machining tolerances

Aesthetics
Large choice of colours, External surfaces with no scratches

Higher performances
Adapted thermal management, Upgraded stainless steel type

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Steel industrial boxes

Metallic junction boxes SDB IP55, low cover models

External dimensions (mm)			Models without knock-outs	Models with knock-outs, n° of drill holes, knock-outs and group			Internal dimensions (mm)			Plain mounting plate	Weight (kg)
Height (A)	Width (B)	Depth (C)	References	References	Height (A)	Width (B)	D	E	F	References	
85	85	49	**NSYDBN88**	**NSYDB88M**	1 n° 1	1 n° 1	58	58	-		0.18
105	105	49	**NSYDBN1010**	**NSYDB1010M**	2 n° 1	1 n° 1	76	76	-		0.25
155	105	61	**NSYDBN1510**	**NSYDB1510M**	3 n° 1	1 n° 1	124	74	56	**NSYPMD1510**	0.38
206	156	83	**NSYDBN2015**	**NSYDB2015M**	3 n° 2	2 n° 2	172	122	78	**NSYPMD2015**	1.00
256	206	93	**NSYDBN2520**	-	-	-	220	170	88	**NSYPMD2520**	1.5
307	257	116	**NSYDBN3025**	-	-	-	268	218	110	**NSYPMD3025**	3.3

Metallic modular boxes

External dimensions (mm)			SBM
Height	Width	Depth	References
150	150	80	**NSYSBM15158**
150	150	120	**NSYSBM151512**
150	200	80	**NSYSBM15208**
150	200	120	**NSYSBM152012**
150	300	80	**NSYSBM15308**
150	300	120	**NSYSBM153012**
150	400	80	**NSYSBM15408**
150	400	120	**NSYSBM154012**
200	200	80	**NSYSBM20208**
200	200	120	**NSYSBM202012**
200	300	80	**NSYSBM20308**
200	300	120	**NSYSBM203012**
200	400	80	**NSYSBM20408**
200	400	120	**NSYSBM204012**
200	500	80	**NSYSBM20508**
200	500	120	**NSYSBM205012**
200	600	80	**NSYSBM20608**
200	600	120	**NSYSBM206012**
200	800	120	**NSYSBM208012**
300	300	120	**NSYSBM303012**
300	400	120	**NSYSBM304012**
300	500	120	**NSYSBM305012**
300	600	120	**NSYSBM306012**
300	800	120	**NSYSBM308012**
400	400	120	**NSYSBM404012**
400	500	120	**NSYSBM405012**
400	600	120	**NSYSBM406012**
400	800	120	**NSYSBM408012**

Accessories and mounting plates for metallic modular boxes:
All informations about accessories and mounting plate on page 38

Spacial SBX Flat boxes

Dimensions (mm)			SBX	
Height	Width	Depth	References	
150	150	80	**NSYSBX15158**	New
150	300	80	**NSYSBX15308**	New
200	200	80	**NSYSBX20208**	New
200	300	80	**NSYSBX20308**	New
200	400	120	**NSYSBX204012**	New
300	300	120	**NSYSBX303012**	New

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Insulating industrial boxes

Universal boxes with IP66

										Universal boxes with IP66			
										ABS IP66 IK07		PC-UL IP66 IK08	
										Opaque cover	Made of polycarbonate		Transparent cover
Overall external dimensions			Overall internal dimensions										
Height (mm)	Width (mm)	Depth (mm)	Height (mm)	Width (mm)	Depth (mm)	Body (mm)	Cover (mm)	Minor pack.	Cover screw	References	References	References	References
74	74	54	65	65	47	37	10	5	Metal	**NSYTBS775**	-	**NSYTBP775**	-
89	89	54	80	80	47	37	10	5	Metal	**NSYTBS885**	-	**NSYTBP885**	-
116	74	62	105	65	55	45	10	5	Metal	**NSYTBS1176**	-	**NSYTBP1176**	-
116	74	94	105	65	85	45	40	3	Metal	**NSYTBS1179H**	-	-	-
116	116	62	105	105	55	45	10	5	Plastic	**NSYTBS11116**	-	**NSYTBP11116**	-
138	116	133	105	105	125	45	80	2	Plastic	**NSYTBS111113H**	-	-	-
164	93	72	125	80	65	45	20	2	Plastic	**NSYTBS1397**	**NSYTBS1397T**	**NSYTBP1397**	**NSYTBP1397T**
192	121	87	150	105	80	60	20	2	Plastic	**NSYTBS16128**	**NSYTBS16128T**	**NSYTBP16128**	**NSYTBP16128T**
192	121	87	175	105	80	60	20	2	Plastic	**NSYTBS19128**	**NSYTBS19128T**	**NSYTBP19128**	**NSYTBP19128T**
192	121	105	175	105	100	60	40	2	Plastic	**NSYTBS191210H**	**NSYTBS191210HT**	**NSYTBP191210H**	**NSYTBP191210HT**
192	164	87	175	150	80	60	20	1	Plastic	**NSYTBS19168**	**NSYTBS19168T**	**NSYTBP19168**	**NSYTBP19168T**
192	164	105	175	150	100	60	40	1	Plastic	**NSYTBS191610H**	**NSYTBS191610HT**	**NSYTBP191610H**	**NSYTBP191610HT**
241	194	87	225	175	80	60	20	1	Plastic	**NSYTBS24198**	**NSYTBS24198T**	**NSYTBP24198**	**NSYTBP24198T**
241	194	107	225	175	100	80	20	1	Plastic	**NSYTBS241910**	**NSYTBS241910T**	**NSYTBP241910**	**NSYTBP241910T**
241	194	107	225	175	100	60	40	1	Plastic	**NSYTBS241910H**	**NSYTBS241910HT**	**NSYTBP241910H**	**NSYTBP241910HT**
241	194	127	225	175	120	80	40	1	Plastic	**NSYTBS241912H**	**NSYTBS241912HT**	**NSYTBP241912H**	**NSYTBP241912HT**
291	241	88	275	225	80	60	20	1	Plastic	**NSYTBS29248**	**NSYTBS29248T**	**NSYTBP29248**	**NSYTBP29248T**
291	241	128	275	225	120	100	20	1	Plastic	**NSYTBS292412**	**NSYTBS292412T**	**NSYTBP292412**	**NSYTBP292412T**
291	241	128	275	225	120	60	60	1	Plastic	**NSYTBS292412H**	**NSYTBS292412HT**	**NSYTBP292412H**	**NSYTBP292412HT**
291	241	168	275	225	160	100	60	1	Plastic	**NSYTBS292416H**	**NSYTBS292416HT**	**NSYTBP292416H**	**NSYTBP292416HT**
341	291	128	325	275	120	100	20	1	Plastic	**NSYTBS342912**	**NSYTBS342912T**	**NSYTBP342912**	**NSYTBP342912T**
341	291	168	325	275	160	100	60	1	Plastic	**NSYTBS342916H**	**NSYTBS342916HT**	**NSYTBP342916H**	**NSYTBP342916HT**

Accessories and mounting plates for universal boxes with IP66:
All informations about accessories and mounting plate on page 162

Universal boxes with IP66

			Complete box					
Dimensions			Transparent cover		Opaque cover		Polyester cover	
Height (mm)	Width (mm)	Depth (mm)	References		References		References	
180	270	180	**NSYPLS1827G**		**NSYPLSC1827G**		**NSYPLSP1827G**	
270	270	180	**NSYPLS2727G**		**NSYPLSC2727G**		**NSYPLSP2727G**	
270	270	230	**NSYPLS2727AG**		**NSYPLSC2727AG**		-	
270	360	180	**NSYPLS2736G**		**NSYPLSC2736G**		**NSYPLSP2736G**	
270	360	230	**NSYPLS2736AG**		**NSYPLSC2736AG**		-	
270	540	180	**NSYPLS2754G**		**NSYPLSC2754G**		**NSYPLSP2754G**	
270	540	230	**NSYPLS2754AG**		**NSYPLSC2754AG**		-	
360	360	180	**NSYPLS3636G**		**NSYPLSC3636G**		**NSYPLSP3636G**	
360	540	180	**NSYPLS3654G**		**NSYPLSC3654G**		**NSYPLSP3654G**	
360	540	230	**NSYPLS3654AG**		**NSYPLSC3654AG**		-	
360	720	230	**NSYPLS3672AG**		**NSYPLSC3672AG**		-	
540	540	180	**NSYPLS5454G**		**NSYPLSC5454G**		**NSYPLSP5454G**	
540	540	230	**NSYPLS5454AG**		**NSYPLSC5454AG**		-	
540	720	230	**NSYPLS5472AG**		**NSYPLSC5472AG**		-	

Accessories and mounting plates for modular boxes:
All informations about accessories and mounting plate on page 176

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

S3D Steel wall-mounting enclosures

Dimensions [1]						Door			Mounting plates		
Height (mm)	Width (mm)	Depth (mm)	Doors	IP	Weight (kg) [2]	Plain without mounting plate	Plain with mounting plate	Glazed without mounting plate	Plain	Silkscreened [3]	Microperforated
300	200	150	1	66	3.02	**NSYS3D3215**	**NSYS3D3215P**	-	**NSYMM32**	-	**NSYMF32**
300	250	150	1	66	3.48	**NSYS3D32515**	**NSYS3D32515P**	**NSYS3D32515T**	**NSYMM3025**	-	-
300	300	150	1	66	3.90	**NSYS3D3315**	**NSYS3D3315P**	**NSYS3D3315T**	**NSYMM33**	-	**NSYMF33**
300	300	200	1	66	4.50	**NSYS3D3320**	**NSYS3D3320P**	**NSYS3D3320T**	**NSYMM33**	-	**NSYMF33**
300	400	150	1	66	4.82	**NSYS3D3415**	**NSYS3D3415P**	**NSYS3D3415T**	**NSYMM43**	**NSYMS43**	**NSYMF43**
300	400	200	1	66	5.60	**NSYS3D3420**	**NSYS3D3420P**	**NSYS3D3420T**	**NSYMM43**	**NSYMS43**	**NSYMF43**
400	300	150	1	66	4.90	**NSYS3D4315**	**NSYS3D4315P**	**NSYS3D4315T**	**NSYMM43**	**NSYMS43**	**NSYMF43**
400	300	200	1	66	5.00	**NSYS3D4320**	**NSYS3D4320P**	**NSYS3D4320T**	**NSYMM43**	**NSYMS43**	**NSYMF43**
400	400	200	1	66	6.50	**NSYS3D4420**	**NSYS3D4420P**	**NSYS3D4420T**	**NSYMM44**	**NSYMS44**	**NSYMF44**
400	600	200	1	66	10.50	**NSYS3D4620**	**NSYS3D4620P**	**NSYS3D4620T**	**NSYMM64**	**NSYMS64**	**NSYMF64**
400	600	250	1	66	12.00	**NSYS3D4625**	**NSYS3D4625P**	**NSYS3D4625T**	**NSYMM64**	**NSYMS64**	**NSYMF64**
500	300	200	1	66	7.50	**NSYS3D5320**	**NSYS3D5320P**	**NSYS3D5320T**	**NSYMM53**	**NSYMS53**	**NSYMF53**
500	400	200	1	66	9.30	**NSYS3D5420**	**NSYS3D5420P**	**NSYS3D5420T**	**NSYMM54**	**NSYMS54**	**NSYMF54**
500	400	250	1	66	10.20	**NSYS3D5425**	**NSYS3D5425P**	**NSYS3D5425T**	**NSYMM54**	**NSYMS54**	**NSYMF54**
500	500	200	1	66	11.18	**NSYS3D5520**	**NSYS3D5520P**	**NSYS3D5520T**	**NSYMM55**	**NSYMS55**	**NSYMF55**
500	500	250	1	66	12.06	**NSYS3D5525**	**NSYS3D5525P**	**NSYS3D5525T**	**NSYMM55**	**NSYMS55**	**NSYMF55**
600	400	200	1	66	11.00	**NSYS3D6420**	**NSYS3D6420P**	**NSYS3D6420T**	**NSYMM64**	**NSYMS64**	**NSYMF64**
600	400	250	1	66	12.00	**NSYS3D6425**	**NSYS3D6425P**	**NSYS3D6425T**	**NSYMM64**	**NSYMS64**	**NSYMF64**
600	500	250	1	66	16.20	**NSYS3D6525**	**NSYS3D6525P**	**NSYS3D6525T**	**NSYMM65**	-	**NSYMF65**
600	600	200	1	66	14.00	**NSYS3D6620**	**NSYS3D6620P**	**NSYS3D6620T**	**NSYMM66**	**NSYMS66**	**NSYMF66**
600	600	250	1	66	15.00	**NSYS3D6625**	**NSYS3D6625P**	**NSYS3D6625T**	**NSYMM66**	**NSYMS66**	**NSYMF66**
600	600	300	1	66	17.00	**NSYS3D6630**	**NSYS3D6630P**	**NSYS3D6630T**	**NSYMM66**	**NSYMS66**	**NSYMF66**
600	600	400	1	66	19.00	**NSYS3D6640**	**NSYS3D6640P**	**NSYS3D6640T**	**NSYMM66**	**NSYMS66**	**NSYMF66**
600	800	300	1	66	25.50	**NSYS3D6830**	**NSYS3D6830P**	**NSYS3D6830T**	**NSYMM86**	**NSYMS86**	**NSYMF86**
700	500	250	1	66	15.00	**NSYS3D7525**	**NSYS3D7525P**	**NSYS3D7525T**	**NSYMM75**	**NSYMS75**	**NSYMF75**
800	600	200	1	66	21.00	**NSYS3D8620**	**NSYS3D8620P**	**NSYS3D8620T**	**NSYMM86**	**NSYMS86**	**NSYMF86**
800	600	250	1	66	23.00	**NSYS3D8625**	**NSYS3D8625P**	**NSYS3D8625T**	**NSYMM86**	**NSYMS86**	**NSYMF86**
800	600	300	1	66	25.00	**NSYS3D8630**	**NSYS3D8630P**	**NSYS3D8630T**	**NSYMM86**	**NSYMS86**	**NSYMF86**
800	600	400	1	66	29.00	**NSYS3D8640**	**NSYS3D8640P**	**NSYS3D8640T**	**NSYMM86**	**NSYMS86**	**NSYMF86**
800	800	250	1	66	30.00	**NSYS3D8825**	**NSYS3D8825P**	**NSYS3D8825T**	**NSYMM88**	-	**NSYMF88**
800	800	300	1	66	32.00	**NSYS3D8830**	**NSYS3D8830P**	**NSYS3D8830T**	**NSYMM88**	-	**NSYMF88**
800	1000	300	1	66	38.00	**NSYS3D81030**	**NSYS3D81030P**	-	**NSYMM108**	-	**NSYMF108**
800	1000	300	2	55	43.50	**NSYS3D81030D**	**NSYS3D81030DP**	-	**NSYMM108**	-	**NSYMF108**
800	1200	300	2	55	46.00	**NSYS3D81230D**	**NSYS3D81230DP**	-	**NSYMM128**	-	**NSYMF128**
1000	600	250	1	66	28.00	**NSYS3D10625**	**NSYS3D10625P**	**NSYS3D10625T**	**NSYMM106**	-	**NSYMF106**
1000	600	300	1	66	30.60	**NSYS3D10630**	**NSYS3D10630P**	**NSYS3D10630T**	**NSYMM106**	-	**NSYMF106**
1000	600	400	1	66	33.00	**NSYS3D10640**	**NSYS3D10640P**	**NSYS3D10640T**	**NSYMM106**	-	**NSYMF106**
1000	800	250	1	66	35.00	**NSYS3D10825**	**NSYS3D10825P**	**NSYS3D10825T**	**NSYMM108**	-	**NSYMF108**
1000	800	300	1	66	38.00	**NSYS3D10830**	**NSYS3D10830P**	**NSYS3D10830T**	**NSYMM108**	-	**NSYMF108**
1000	800	400	1	66	42.00	**NSYS3D10840**	**NSYS3D10840P**	**NSYS3D10840T**	**NSYMM108**	-	**NSYMF108**
1000	1000	300	1	66	46.00	**NSYS3D101030**	**NSYS3D101030P**	**NSYS3D101030T**	**NSYMM1010**	-	**NSYMF1010**
1000	1000	300	2	55	46.00	**NSYS3D101030D**	**NSYS3D101030DP**	**NSYS3D101030DT**	**NSYMM1010**	-	**NSYMF1010**
1000	1200	300	2	55	53.00	**NSYS3D101230D**	**NSYS3D101230DP**	-	**NSYMM1210**	-	**NSYMF1210**
1000	1200	400	2	55	60.00	**NSYS3D101240D**	**NSYS3D101240DP**	-	**NSYMM1210**	-	**NSYMF1210**
1200	600	300	1	66	37.00	**NSYS3D12630**	**NSYS3D12630P**	**NSYS3D12630T**	**NSYMM126**	-	**NSYMF126**
1200	600	400	1	66	42.00	**NSYS3D12640**	**NSYS3D12640P**	**NSYS3D12640T**	**NSYMM126**	-	**NSYMF126**
1200	800	300	1	66	45.00	**NSYS3D12830**	**NSYS3D12830P**	**NSYS3D12830T**	**NSYMM128**	-	**NSYMF128**
1200	800	400	1	66	49.00	**NSYS3D12840**	**NSYS3D12840P**	**NSYS3D12840T**	**NSYMM128**	-	**NSYMF128**
1200	1000	300	1	66	53.00	**NSYS3D121030**	**NSYS3D121030P**	**NSYS3D121030T**	**NSYMM1210**	-	**NSYMF1210**
1200	1000	300	2	55	54.00	**NSYS3D121030D**	**NSYS3D121030DP**	**NSYS3D121030DT**	**NSYMM1210**	-	**NSYMF1210**
1200	1000	400	2	55	61.00	**NSYS3D121040D**	**NSYS3D121040DP**	-	**NSYMM1210**	-	**NSYMF1210**
1200	1200	300	2	55	64.00	**NSYS3D121230D**	**NSYS3D121230DP**	-	**NSYMM1212**	-	2x **NSYMF126** [4]
1200	1200	400	2	55	90.00	**NSYS3D121240D**	**NSYS3D121240DP**	-	**NSYMM1212**	-	2x **NSYMF126** [4]
1400	1000	300	2	55	80.00	**NSYS3D141030D**	**NSYS3D141030DP**	-	**NSYMM1410**	-	-

[1] For other dimensions, see our application offer, page 14.
[2] Enclosure without mounting plate.
[3] In inverted use, the marking is inverted.
[4] Order **NSYCRNGSDR** for double mounting of the mounting plates
[5] Order nuts ref. **NSYAMCSF**. Steel siderail ref. **NSYMDVR12**.
[6] When width ≥ 1000 mm ref. **NSYEMR** is mandatory (see on page 74).
[7] Possible assembling to ref. **NSYDLM84** or **NSYDLM112**.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

			Modular mounting plate				Cross rails	
								
Telequick	Bakelite	Module	Modular chassis DLM Steel	Modular chassis DLA Insulated	DIN rail chassis	Typ	Aluminium vertical rails [5]	Door cross rails
NSYMR32	**NSYMB32**	-	**-**	**-**	**-**	-	**NSYMDVR3**	**-**
NSYMR3025	**NSYMB3025**	-	**-**	**-**	**-**	-	**NSYMDVR3**	**-**
NSYMR33	**NSYMB33**	-	**-**	**-**	**NSYMD33**	B	**NSYMDVR3**	**-**
NSYMR33	**NSYMB33**	-	**-**	**-**	**NSYMD33**	B	**NSYMDVR3**	**-**
NSYMR34	**NSYMB43**	-	**-**	**-**	**-**	-	**NSYMDVR3**	**-**
NSYMR34	**NSYMB43**	-	**-**	**-**	**-**	-	**NSYMDVR3**	**-**
NSYMR43	**NSYMB43**	24	**NSYDLM24**	**-**	**NSYMD43**	B	**NSYMDVR4**	**-**
NSYMR43	**NSYMB43**	24	**NSYDLM24**	**NSYDLA24G**	**NSYMD43**	B	**NSYMDVR4**	**-**
NSYMR44	**-**	-	**-**	**-**	**-**	-	**NSYMDVR4**	**NSYTFPCRN4**
NSYMR46	**NSYMB64**	-	**-**	**-**	**-**	-	**NSYMDVR4**	**NSYTFPCRN6**
NSYMR46	**NSYMB64**	-	**-**	**-**	**-**	-	**NSYMDVR4**	**NSYTFPCRN6**
NSYMR53	**-**	-	**-**	**-**	**-**	-	**NSYMDVR5**	**-**
NSYMR54	**NSYMB54**	48	**NSYDLM48**	**NSYDLA48G**	**NSYMD54**	B	**NSYMDVR5**	**NSYTFPCRN4**
NSYMR54	**NSYMB54**	48	**NSYDLM48**	**-**	**NSYMD54**	B	**NSYMDVR5**	**NSYTFPCRN4**
NSYMR55	**-**	-	**-**	**-**	**-**	-	**NSYMDVR5**	**NSYTFPCRN5**
NSYMR55	**-**	-	**-**	**-**	**-**	-	**NSYMDVR5**	**NSYTFPCRN5**
NSYMR64	**NSYMB64**	48	**NSYDLM48P**	**NSYDLA48PG**	**NSYMD64**	B	**NSYMDVR6**	**NSYTFPCRN4**
NSYMR64	**NSYMB64**	48	**NSYDLM48P**	**NSYDLA48PG**	**NSYMD64**	B	**NSYMDVR6**	**NSYTFPCRN4**
NSYMR65	**NSYMB65**	-	**-**	**-**	**-**	-	**NSYMDVR6**	**-**
NSYMR66	**-**	84	**NSYDLM84P**	**-**	**NSYMD66**	A	**NSYMDVR6**	**NSYTFPCRN6**
NSYMR66	**-**	84	**NSYDLM84P**	**-**	**NSYMD66**	A	**NSYMDVR6**	**NSYTFPCRN6**
NSYMR66	**-**	84	**NSYDLM84P**	**-**	**NSYMD66**	A	**NSYMDVR6**	**NSYTFPCRN6**
NSYMR66	**-**	84	**NSYDLM84P**	**-**	**NSYMD66**	A	**NSYMDVR6**	**NSYTFPCRN6**
NSYMR68	**NSYMB86**	-	**-**	**-**	**NSYMD86**	A	**NSYMDVR6**	**NSYTFPCRN8**
NSYMR75	**NSYMB75**	66	**NSYDLM66**	**NSYDLA66G**	**NSYMD75**	B	**NSYMDVR7**	**NSYTFPCRN5**
NSYMR86	**NSYMB86**	84 [7]	**NSYDLM84**	**NSYDLA84G / NSYDLA112G**	**NSYMD86**	A	**NSYMDVR8**	**NSYTFPCRN6**
NSYMR86	**NSYMB86**	112 [7]	**NSYDLM112**	**NSYDLA84G / NSYDLA112G**	**NSYMD86**	A	**NSYMDVR8**	**NSYTFPCRN6**
NSYMR86	**NSYMB86**	112 [7]	**NSYDLM112**	**NSYDLA84G / NSYDLA112G**	**NSYMD86**	A	**NSYMDVR8**	**NSYTFPCRN6**
NSYMR86	**NSYMB86**	112 [7]	**NSYDLM112**	**NSYDLA84G / NSYDLA112G**	**NSYMD86**	A	**NSYMDVR8**	**NSYTFPCRN6**
NSYMR88	**-**	-	**-**	**-**	**-**	-	**NSYMDVR8**	**NSYTFPCRN8**
NSYMR88	**-**	-	**-**	**-**	**-**	-	**NSYMDVR8**	**NSYTFPCRN8**
NSYMR810	**NSYMB108**	-	**-**	**-**	**-**	-	**NSYMDVR8**	**NSYTFPCRN10**
NSYMR810	**NSYMB108**	-	**-**	**-**	**-**	-	**NSYMDVR8**	**-**
2x **NSYMR86** [4]	2x **NSYMB86** [4]	-	**-**	**-**	2x **NSYMD86** [4]	A	**NSYMDVR8**	**-**
NSYMR106	**NSYMB106**	168	**NSYDLM168**	**-**	**-**	-	**NSYMDVR10**	**NSYTFPCRN6**
NSYMR106	**NSYMB106**	168	**NSYDLM168**	**-**	**-**	-	**NSYMDVR10**	**NSYTFPCRN6**
NSYMR106	**NSYMB106**	168	**NSYDLM168**	**-**	**-**	-	**NSYMDVR10**	**NSYTFPCRN6**
NSYMR108	**NSYMB108**	234	**NSYDLM240**	**NSYDLA234G**	**NSYMD108**	A	**NSYMDVR10**	**NSYTFPCRN8**
NSYMR108	**NSYMB108**	234	**NSYDLM240**	**NSYDLA234G**	**NSYMD108**	A	**NSYMDVR10**	**NSYTFPCRN8**
NSYMR108	**NSYMB108**	234	**NSYDLM240**	**NSYDLA234G**	**NSYMD108**	A	**NSYMDVR10**	**NSYTFPCRN8**
NSYMR1012 [6]	**-**	-	**-**	**-**	**-**	-	**NSYMDVR10**	**NSYTFPCRN10**
NSYMR1012 [6]	**-**	-	**-**	**-**	**-**	-	**NSYMDVR10**	**-**
NSYMR1012 [6]	**NSYMB1210**	-	**-**	**-**	**-**	-	**NSYMDVR10**	**-**
NSYMR1012 [6]	**NSYMB1210**	-	**-**	**-**	**-**	-	**NSYMDVR10**	**-**
-	**-**	-	**-**	**-**	**-**	-	**NSYMDVR12**	**-**
-	**-**	-	**-**	**-**	**-**	-	**NSYMDVR12**	**-**
NSYMR128	**-**	-	**-**	**-**	**NSYMD128**	A	**NSYMDVR12**	**NSYTFPCRN8**
NSYMR128	**-**	-	**-**	**-**	**NSYMD128**	A	**NSYMDVR12**	**NSYTFPCRN8**
NSYMR1210 [6]	**NSYMB1210**	-	**-**	**-**	**-**	-	**NSYMDVR12**	**NSYTFPCRN10**
NSYMR1210 [6]	**NSYMB1210**	-	**-**	**-**	**-**	-	**NSYMDVR12**	**-**
NSYMR1210 [6]	**NSYMB1210**	-	**-**	**-**	**-**	-	**NSYMDVR12**	**-**
2x **NSYMR126** [4]	**-**	-	**-**	**-**	**-**	-	**NSYMDVR12**	**-**
2x **NSYMR126** [4]	**-**	-	**-**	**-**	**-**	-	**NSYMDVR12**	**-**
NSYMR1410 [6]	**-**	-	**-**	**-**	**-**	-	**-**	**-**

Wall fixing lugs: Page 51
Steel: **NSYAEFPFSC**
Stainless steel: **NSYAEFPFXSC**

Reinforcement for heavy loads: Page 51
NSYAEFAHLBSC
Locking accessories: Page 58

Door accessories: Page 300
Clip-on nuts: Page 270
Self-tapping screw: **NSYS13M5HS** / Page 271

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Applicative and customised solutions

					Basic enclosures Empty application enclosures		Basic enclosures 19" enclosure with glazed door (Plain door, please consult us.)					
Dimensions			Doors	IP	S3DB terminal enclosures	S3DM modular enclosures with glazed door	VDM steel enclosures with 19" swing rack	No. of U	1-body 19" fixed rack	No. of U	2 parts with 19" fixed rack	No. of U
Height (mm)	Width (mm)	Depth (mm)										
200	300	150	1	66	-	-	-	-	-	-	-	-
250	300	150	1	66	**NSYS3DB25315**	-	-	-	-	-	-	-
250	400	150	1	66	**NSYS3DB25415**	-	-	-	-	-	-	-
250	500	150	1	66	**NSYS3DB25515**	-	-	-	-	-	-	-
300	300	150	1	66	**NSYS3DB3315**	-	-	-	-	-	-	-
300	300	170	1	66	-	-	-	-	-	-	-	-
300	400	150	1	66	**NSYS3DB3415**	-	-	-	-	-	-	-
300	400	170	1	66	-	-	-	-	-	-	-	-
300	500	150	1	66	**NSYS3DB3515**	-	-	-	-	-	-	-
300	500	200	1	66	-	-	-	-	-	-	-	-
300	600	150	1	66	**NSYS3DB3615**	-	-	-	-	-	-	-
300	600	400	1	66	-	-	**NSYVDM4U4P**	4	**NSYVDM5U4F**	5	**NSYVD2M5U4**	5
300	600	500	1	66	-	-	-	-	-	-	**NSYVD2M5U5**	5
400	300	150	1	66	**NSYS3DB4315**	**NSYS3DM4315T**	-	-	-	-	-	-
400	300	170	1	66	-	-	-	-	-	-	-	-
400	600	400	1	66	-	-	**NSYVDM7U4P**	7	**NSYVDM8U4F**	8	**NSYVD2M8U4**	8
400	600	500	1	66	-	-	-	-	-	-	**NSYVD2M8U5**	8
400	800	150	1	66	**NSYS3DB4815**	-	-	-	-	-	-	-
500	400	150	1	66	**NSYS3DB5415**	**NSYS3DM5415T**	-	-	-	-	-	-
500	600	400	1	66	-	-	**NSYVDM9U4P**	9	**NSYVDM10U4F**	10	**NSYVD2M10U4**	10
500	600	500	1	66	-	-	-	-	-	-	**NSYVD2M10U5**	10
600	400	150	1	66	**NSYS3DB6415**	**NSYS3DM6415T**	-	-	-	-	-	-
600	600	150	1	66	-	**NSYS3DM6615T**	-	-	-	-	-	-
700	500	150	1	66	-	-	-	-	-	-	-	-
700	500	150	1	66	-	**NSYS3DM7515T**	-	-	-	-	-	-
700	600	400	1	66	-	-	**NSYVDM13U4P**	13	**NSYVDM14U4F**	14	**NSYVD2M14U4**	14
700	600	500	1	66	-	-	-	-	-	-	**NSYVD2M14U5**	14
800	600	150	1	66	-	-	-	-	-	-	-	-
800	600	150	1	66	-	**NSYS3DM8615T**	-	-	-	-	-	-
800	600	400	1	66	-	-	**NSYVDM16U4P**	16	**NSYVDM17U4F**	17	**NSYVD2M17U4**	17
800	600	500	1	66	-	-	-	-	-	-	**NSYVD2M17U5**	17
1000	600	150	1	66	-	**NSYS3DM10615T**	-	-	-	-	-	-
1000	800	150	1	66	-	**NSYS3DM10815T**	-	-	-	-	-	-
Details					see page 327	see page 330	see page 453		see page 453		see page 453	

Wall fixing lugs: Page 51
Steel: **NSYAEFPFSC**
Stainless steel: **NSYAEFPFXSC**

Reinforcement for heavy loads: Page 51
NSYAEFAHLBSC
Locking accessories: Page 58

Door accessories: Page 300
Clip-on nuts: Page 270
Self-tapping screw: **NSYS13M5HS** / Page 271

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Accessories Electricitydistribution		Accessories Automatism			
Modular mounting chassis (metallic)	No. of modul	DIN rail support and DIN rail	Plain mounting plate	Telequick mounting plate	Aluminium vertical rails
-	-	NSYAMRD2030	NSYMM32	-	-
-	-	NSYAMRD2530	NSYMM3025	-	-
-	-	NSYAMRD2540	NSYMM2540	-	-
-	-	NSYAMRD2550	NSYMM2550	-	-
-	-	NSYAMRD3030	NSYMM33	NSYMR33	NSYMDVR3
-	-	NSYAMRD3030	NSYMM33	NSYMR33	-
-	-	NSYAMRD3040	NSYMM43	NSYMR34	NSYMDVR3
-	-	NSYAMRD3040	NSYMM43	NSYMR34	-
-	-	NSYAMRD3050	NSYMM53	-	NSYMDVR3
-	-	NSYAMRD3050	NSYMM53	-	NSYMDVR3
-	-	NSYAMRD36	NSYMM36	-	NSYMDVR3
-	-	NSYAMRD36	NSYMM36	-	NSYMDVR3
-	-	NSYAMRD36	NSYMM36	-	NSYMDVR3
NSYDLM24	24	NSYAMRD43	NSYMM43	NSYMR43	NSYMDVR4
-	-	NSYAMRD43	NSYMM43	NSYMR43	-
-	-	-	NSYMM64	NSYMR46	NSYMDVR4
-	-	NSYAMRD48	NSYMM64	NSYMR46	NSYMDVR4
-	-	NSYAMRD54	NSYMM48	-	NSYMDVR4
NSYDLM48	48	-	NSYMM54	NSYMR54	NSYMDVR5
-	-	-	NSYMM65	-	NSYMDVR5
-	-	-	NSYMM65	-	NSYMDVR5
NSYDLM48P	48	NSYAMRD64	NSYMM64	NSYMR64	NSYMDVR6
NSYDLM84P	84	-	NSYMM66	NSYMR66	NSYMDVR6
NSYDLM66	66	-	NSYMM75	NSYMR75	NSYMDVR7
NSYDLM88	88	-	NSYMM75	NSYMR75	NSYMDVR7
-	-	-	NSYMM76	NSYMR76	NSYMDVR7
-	-	-	NSYMM76	NSYMR76	NSYMDVR7
NSYDLM84	84	-	NSYMM86	NSYMR86	NSYMDVR8
NSYDLM112	112	-	NSYMM86	NSYMR86	NSYMDVR8
-	-	-	NSYMM86	NSYMR86	NSYMDVR8
-	-	-	NSYMM86	NSYMR86	NSYMDVR8
NSYDLM168	168	-	NSYMM106	NSYMR106	NSYMDVR10
NSYDLM240	234	-	NSYMM108	NSYMR108	NSYMDVR10
see page 331			see page 240	see page 240	see page 244

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

SM Steel floor-standing enclosures

Dimensions				Enclosures			Plinth (H 100 mm)	
								
Height (mm)	Width (mm)	Depth (mm)	Doors	Plain door, without mounting plate	Plain door, with mounting plate	Transparent door, without mounting plate	Front kit (corners + front panels)	Side panels, 2 u.
1200	800	300	1	NSYSM12830	NSYSM12830P	-	NSYSPF8100	NSYSPS3100
1200	1000	300	2	NSYSM1210302D	NSYSM1210302DP	-	NSYSPF10100	NSYSPS3100
1200	1200	400	2	NSYSM1212402D	NSYSM1212402DP	-	NSYSPF12100	NSYSPS4100
1400	600	300	1	NSYSM14630	NSYSM14630P	-	NSYSPF6100	NSYSPS3100
1400	600	400	1	NSYSM14640	NSYSM14640P	-	NSYSPF6100	NSYSPS4100
1400	800	300	1	NSYSM14830	NSYSM14830P	-	NSYSPF8100	NSYSPS3100
1400	800	400	1	NSYSM14840	NSYSM14840P	NSYSM14840T	NSYSPF8100	NSYSPS4100
1400	1000	400	2	NSYSM1410402D	NSYSM1410402DP	-	NSYSPF10100	NSYSPS4100
1400	1200	400	2	NSYSM1412402D	NSYSM1412402DP	-	NSYSPF12100	NSYSPS4100
1600	600	300	1	NSYSM16630	NSYSM16630P	-	NSYSPF6100	NSYSPS3100
1600	600	400	1	NSYSM16640	NSYSM16640P	NSYSM16640T	NSYSPF6100	NSYSPS4100
1600	800	300	1	NSYSM16830	NSYSM16830P	NSYSM16830T	NSYSPF8100	NSYSPS3100
1600	800	400	1	NSYSM16840	NSYSM16840P	NSYSM16840T	NSYSPF8100	NSYSPS4100
1600	1000	300	2	NSYSM1610302D	NSYSM1610302DP	-	NSYSPF10100	NSYSPS3100
1600	1000	400	2	NSYSM1610402D	NSYSM1610402DP	-	NSYSPF10100	NSYSPS4100
1600	1200	300	2	NSYSM1612302D	NSYSM1612302DP	-	NSYSPF12100	NSYSPS3100
1600	1200	400	2	NSYSM1612402D	NSYSM1612402DP	-	NSYSPF12100	NSYSPS4100
1800	600	300	1	NSYSM18630	NSYSM18630P	-	NSYSPF6100	NSYSPS3100
1800	600	400	1	NSYSM18640	NSYSM18640P	NSYSM18640T	NSYSPF6100	NSYSPS4100
1800	600	500	1	NSYSM18650	NSYSM18650P	-	NSYSPF6100	NSYSPS5100
1800	800	300	1	NSYSM18830	NSYSM18830P	NSYSM18830T	NSYSPF8100	NSYSPS3100
1800	800	400	1	NSYSM18840	NSYSM18840P	NSYSM18840T	NSYSPF8100	NSYSPS4100
1800	800	500	1	NSYSM18850	NSYSM18850P	NSYSM18850T	NSYSPF8100	NSYSPS5100
1800	800	600	1	NSYSM18860	NSYSM18860P	-	NSYSPF8100	NSYSPS6100
1800	1000	400	1	NSYSM181040	NSYSM181040P	-	NSYSPF10100	NSYSPS4100
1800	1000	400	2	NSYSM1810402D	NSYSM1810402DP	-	NSYSPF10100	NSYSPS4100
1800	1000	500	2	NSYSM1810502D	NSYSM1810502DP	-	NSYSPF10100	NSYSPS5100
1800	1200	400	2	NSYSM1812402D	NSYSM1812402DP	-	NSYSPF12100	NSYSPS4100
1800	1200	500	2	NSYSM1812502D	NSYSM1812502DP	-	NSYSPF12100	NSYSPS5100
1800	1600	400	2	NSYSM1816402D	NSYSM1816402DP	-	NSYSPF16100	NSYSPS4100
1800	1600	500	2	NSYSM1816502D	NSYSM1816502DP	-	NSYSPF16100	NSYSPS5100
2000	600	300	1	NSYSM20630	NSYSM20630P	-	NSYSPF6100	NSYSPS3100
2000	600	400	1	NSYSM20640	NSYSM20640P	NSYSM20640T	NSYSPF6100	NSYSPS4100
2000	600	500	1	NSYSM20650	NSYSM20650P	-	NSYSPF6100	NSYSPS5100
2000	800	300	1	NSYSM20830	NSYSM20830P	NSYSM20830T	NSYSPF8100	NSYSPS3100
2000	800	400	1	NSYSM20840	NSYSM20840P	NSYSM20840T	NSYSPF8100	NSYSPS4100
2000	800	500	1	NSYSM20850	NSYSM20850P	NSYSM20850T	NSYSPF8100	NSYSPS5100
2000	800	600	1	NSYSM20860	NSYSM20860P	NSYSM20860T	NSYSPF8100	NSYSPS6100
2000	1000	400	2	NSYSM2010402D	NSYSM2010402DP	-	NSYSPF10100	NSYSPS4100
2000	1000	500	2	NSYSM2010502D	NSYSM2010502DP	-	NSYSPF10100	NSYSPS5100
2000	1200	400	2	NSYSM2012402D	NSYSM2012402DP	-	NSYSPF12100	NSYSPS4100
2000	1200	500	2	NSYSM2012502D	NSYSM2012502DP	-	NSYSPF12100	NSYSPS5100
2000	1200	600	2	NSYSM2012602D	NSYSM2012602DP	-	NSYSPF12100	NSYSPS6100
2000	1600	400	2	NSYSM2016402D	NSYSM2016402DP	-	NSYSPF16100	NSYSPS4100
2000	1600	500	2	NSYSM2016502D	NSYSM2016502DP	-	NSYSPF16100	NSYSPS5100
2000	1600	600	2	NSYSM2016602D	NSYSM2016602DP	-	NSYSPF16100	NSYSPS6100

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Plinth (H 200 mm)		Inner door	Mounting plate	Vertical uprights		19" swing rack	
							
Front kit (corners + front panels)	Side panels, 4 u.	Plain door	Galvanized	Standard	Technical	Off-centre	Centred
NSYSPF8200	NSYSPS3200	-	NSYMP128	-	NSYTVR12	-	-
NSYSPF10200	NSYSPS3200	-	NSYMP1210	-	NSYTVR12	-	-
NSYSPF12200	NSYSPS4200	-	NSYMP1212	-	NSYTVR12	-	-
NSYSPF6200	NSYSPS3200	-	NSYMP146	-	NSYTVR14	-	-
NSYSPF6200	NSYSPS4200	-	NSYMP146	-	NSYTVR14	-	-
NSYSPF8200	NSYSPS3200	-	NSYMP148	-	NSYTVR14	NSYRSW27	NSYRSWC27
NSYSPF8200	NSYSPS4200	-	NSYMP148	-	NSYTVR14	NSYRSW27	NSYRSWC27
NSYSPF10200	NSYSPS4200	-	NSYMP1410	-	NSYTVR14	-	-
NSYSPF12200	NSYSPS4200	-	NSYMP1412	-	NSYTVR14	-	-
NSYSPF6200	NSYSPS3200	NSYID166	NSYMP166	-	NSYTVR16	-	-
NSYSPF6200	NSYSPS4200	NSYID166	NSYMP166	-	NSYTVR16	-	-
NSYSPF8200	NSYSPS3200	NSYID168	NSYMP168	-	NSYTVR16	NSYRSW31	NSYRSWC31
NSYSPF8200	NSYSPS4200	NSYID168	NSYMP168	-	NSYTVR16	NSYRSW31	NSYRSWC31
NSYSPF10200	NSYSPS3200	-	NSYMP1610	-	NSYTVR16	-	-
NSYSPF10200	NSYSPS4200	-	NSYMP1610	-	NSYTVR16	-	-
NSYSPF12200	NSYSPS3200	-	NSYMP1612	-	NSYTVR16	-	-
NSYSPF12200	NSYSPS4200	-	NSYMP1612	-	NSYTVR16	-	-
NSYSPF6200	NSYSPS3200	NSYID186	NSYMP186	NSYVR18	NSYTVR18	-	-
NSYSPF6200	NSYSPS4200	NSYID186	NSYMP186	NSYVR18	NSYTVR18	-	-
NSYSPF6200	NSYSPS5200	NSYID186	NSYMP186	NSYVR18	NSYTVR18	-	-
NSYSPF8200	NSYSPS3200	NSYID188	NSYMP188	NSYVR18	NSYTVR18	NSYRSW36	NSYRSWC36
NSYSPF8200	NSYSPS4200	NSYID188	NSYMP188	NSYVR18	NSYTVR18	NSYRSW36	NSYRSWC36
NSYSPF8200	NSYSPS5200	NSYID188	NSYMP188	NSYVR18	NSYTVR18	NSYRSW36	NSYRSWC36
NSYSPF8200	NSYSPS6200	NSYID188	NSYMP188	NSYVR18	NSYTVR18	NSYRSW36	NSYRSWC36
NSYSPF10200	NSYSPS4200	NSYID1810	NSYMP1810	NSYVR18	NSYTVR18	-	-
NSYSPF10200	NSYSPS4200	NSYID1810	NSYMP1810	NSYVR18	NSYTVR18	-	-
NSYSPF10200	NSYSPS5200	NSYID1810	NSYMP1810	NSYVR18	NSYTVR18	-	-
NSYSPF12200	NSYSPS4200	-	NSYMP1812	NSYVR18	NSYTVR18	-	-
NSYSPF12200	NSYSPS5200	-	NSYMP1812	NSYVR18	NSYTVR18	-	-
NSYSPF16200	NSYSPS4200	-	NSYMP1816	NSYVR18	NSYTVR18	-	-
NSYSPF16200	NSYSPS5200	-	NSYMP1816	NSYVR18	NSYTVR18	-	-
NSYSPF6200	NSYSPS3200	NSYID206	NSYMP206	NSYVR20	NSYTVR20	-	-
NSYSPF6200	NSYSPS4200	NSYID206	NSYMP206	NSYVR20	NSYTVR20	-	-
NSYSPF6200	NSYSPS5200	NSYID206	NSYMP206	NSYVR20	NSYTVR20	-	-
NSYSPF8200	NSYSPS3200	NSYID208	NSYMP208	NSYVR20	NSYTVR20	NSYRSW40	NSYRSWC40
NSYSPF8200	NSYSPS4200	NSYID208	NSYMP208	NSYVR20	NSYTVR20	NSYRSW40	NSYRSWC40
NSYSPF8200	NSYSPS5200	NSYID208	NSYMP208	NSYVR20	NSYTVR20	NSYRSW40	NSYRSWC40
NSYSPF8200	NSYSPS6200	NSYID208	NSYMP208	NSYVR20	NSYTVR20	NSYRSW40	NSYRSWC40
NSYSPF10200	NSYSPS4200	NSYID2010	NSYMP2010	NSYVR20	NSYTVR20	-	-
NSYSPF10200	NSYSPS5200	NSYID2010	NSYMP2010	NSYVR20	NSYTVR20	-	-
NSYSPF12200	NSYSPS4200	-	NSYMP2012	NSYVR20	NSYTVR20	-	-
NSYSPF12200	NSYSPS5200	-	NSYMP2012	NSYVR20	NSYTVR20	-	-
NSYSPF12200	NSYSPS6200	-	NSYMP2012	NSYVR20	NSYTVR20	-	-
NSYSPF16200	NSYSPS4200	-	NSYMP2016	NSYVR20	NSYTVR20	-	-
NSYSPF16200	NSYSPS5200	-	NSYMP2016	NSYVR20	NSYTVR20	-	-
NSYSPF16200	NSYSPS6200	-	NSYMP2016	NSYVR20	NSYTVR20	-	-

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

SF Steel floor-standing enclosures

Dimensions				Enclosures			Side panels	Cable entry plates		
(A)	(B)	(C)								
Height (mm)	Width (mm)	Depth (mm)	Doors	Plain door, without mounting plate	Plain door, with mounting plate	Transparent door, without mounting plate	Plain	Plain	1 entry	2 entries
1200	600	400	1	NSYSF12640	NSYSF12640P	-	NSY2SP124	NSYEC64	NSYEC641	-
1200	600	600	1	NSYSF12660	NSYSF12660P	-	NSY2SP126	NSYEC66	NSYEC661	NSYEC662
1200	800	400	1	NSYSF12840	NSYSF12840P	-	NSY2SP124	NSYEC84	NSYEC841	-
1200	800	600	1	NSYSF12860	NSYSF12860P	-	NSY2SP126	NSYEC86	NSYEC861	NSYEC862
1400	600	400	1	NSYSF14640	NSYSF14640P	-	NSY2SP144	NSYEC64	NSYEC641	-
1400	800	400	1	NSYSF14840	NSYSF14840P	-	NSY2SP144	NSYEC84	NSYEC841	-
1600	600	600	1	NSYSF16660	NSYSF16660P	-	NSY2SP166	NSYEC66	NSYEC661	NSYEC662
1600	600	800	1	NSYSF16680	NSYSF16680P	-	NSY2SP168	NSYEC68	NSYEC681	NSYEC682
1600	800	600	1	NSYSF16860	NSYSF16860P	-	NSY2SP166	NSYEC86	NSYEC861	NSYEC862
1600	800	800	1	NSYSF16880	NSYSF16880P	-	NSY2SP168	NSYEC88	NSYEC881	NSYEC882
1800	400	400	1	NSYSF18440	-	-	NSY2SP184	NSYEC44	NSYEC441	-
1800	400	500	1	NSYSF18450	-	-	NSY2SP185	NSYEC45	NSYEC451	-
1800	400	600	1	NSYSF18460	-	-	NSY2SP186	-	NSYEC461	-
1800	600	400	1	NSYSF18640	NSYSF18640P	NSYSF18640T	NSY2SP184	NSYEC64	NSYEC641	-
1800	600	500	1	NSYSF18650	NSYSF18650P	NSYSF18650T	NSY2SP185	NSYEC65	NSYEC651	-
1800	600	600	1	NSYSF18660	NSYSF18660P	-	NSY2SP186	NSYEC66	NSYEC661	NSYEC662
1800	600	800	1	-	-	NSYSF18680T	NSY2SP188	NSYEC68	NSYEC681	NSYEC682
1800	800	400	1	NSYSF18840	NSYSF18840P	NSYSF18840T	NSY2SP184	NSYEC84	NSYEC841	-
1800	800	500	1	NSYSF18850	NSYSF18850P	NSYSF18850T	NSY2SP185	NSYEC85	NSYEC851	-
1800	800	600	1	NSYSF18860	NSYSF18860P	NSYSF18860T	NSY2SP186	NSYEC86	NSYEC861	NSYEC862
1800	800	600	2	NSYSF188602D	NSYSF188602DP	-	NSY2SP186	NSYEC86	NSYEC861	NSYEC862
1800	1000	400	1	NSYSF181040	NSYSF181040P	-	NSY2SP184	NSYEC104	NSYEC1041	-
1800	1000	400	2	NSYSF1810402D	NSYSF1810402DP	-	NSY2SP184	NSYEC104	NSYEC1041	-
1800	1000	500	1	NSYSF181050	NSYSF181050P	-	NSY2SP185	NSYEC105	NSYEC1051	-
1800	1000	600	1	NSYSF181060	NSYSF181060P	-	NSY2SP186	NSYEC106	NSYEC1061	NSYEC1062
1800	1000	600	2	NSYSF1810602D	NSYSF1810602DP	-	NSY2SP186	NSYEC106	NSYEC1061	NSYEC1062
1800	1200	400	2	NSYSF1812402D	NSYSF1812402DP	-	NSY2SP184	NSYEC124	NSYEC1241	-
1800	1200	500	2	NSYSF1812502D	NSYSF1812502DP	-	NSY2SP185	NSYEC125	NSYEC1251	-
1800	1200	600	2	NSYSF1812602D	NSYSF1812602DP	-	NSY2SP186	NSYEC126	NSYEC1261	NSYEC1262
2000	300	500	1	NSYSF20350	-	-	NSY2SP205	NSYEC35	NSYEC351	-
2000	300	600	1	NSYSF20360	-	-	NSY2SP206	NSYEC36	NSYEC361	-
2000	300	800	1	NSYSF20380	-	-	NSY2SP208	-	NSYEC381	-
2000	400	400	1	NSYSF20440	-	-	NSY2SP204	NSYEC44	NSYEC441	-
2000	400	500	1	NSYSF20450	-	-	NSY2SP205	NSYEC45	NSYEC451	-
2000	400	600	1	NSYSF20460	-	-	NSY2SP206	NSYEC64	NSYEC461	-
2000	400	800	1	NSYSF20480	-	-	NSY2SP208	NSYEC84	NSYEC481	-
2000	600	400	1	NSYSF20640	NSYSF20640P	NSYSF20640T	NSY2SP204	NSYEC64	NSYEC641	-
2000	600	500	1	NSYSF20650	NSYSF20650P	NSYSF20650T	NSY2SP205	NSYEC65	NSYEC651	-
2000	600	600	1	NSYSF20660	NSYSF20660P	-	NSY2SP206	NSYEC66	NSYEC661	NSYEC662
2000	600	800	1	NSYSF20680	NSYSF20680P	-	NSY2SP208	NSYEC68	NSYEC681	NSYEC682
2000	800	400	1	NSYSF20840	NSYSF20840P	NSYSF20840T	NSY2SP204	NSYEC84	NSYEC841	-
2000	800	500	1	NSYSF20850	NSYSF20850P	NSYSF20850T	NSY2SP205	NSYEC85	NSYEC851	-
2000	800	600	1	NSYSF20860	NSYSF20860P	NSYSF20860T	NSY2SP206	NSYEC86	NSYEC861	NSYEC862
2000	800	600	2	NSYSF208602D	NSYSF208602DP	-	NSY2SP206	NSYEC86	NSYEC861	NSYEC862
2000	800	800	1	NSYSF20880	NSYSF20880P	NSYSF20880T	NSY2SP208	NSYEC88	NSYEC881	NSYEC882
2000	1000	400	1	NSYSF201040	NSYSF201040P	NSYSF201040T	NSY2SP204	NSYEC104	NSYEC1041	-
2000	1000	400	2	NSYSF2010402D	NSYSF2010402DP	-	NSY2SP204	NSYEC104	NSYEC1041	-
2000	1000	500	1	NSYSF201050	NSYSF201050P	NSYSF201050T	NSY2SP205	NSYEC105	NSYEC1051	-
2000	1000	500	2	NSYSF2010502D	NSYSF2010502DP	-	NSY2SP205	NSYEC105	NSYEC1051	-
2000	1000	600	1	NSYSF201060	NSYSF201060P	NSYSF201060T	NSY2SP206	NSYEC106	NSYEC1061	NSYEC1062
2000	1000	600	2	NSYSF2010602D	NSYSF2010602DP	-	NSY2SP206	NSYEC106	NSYEC1061	NSYEC1062
2000	1000	800	1	NSYSF201080	NSYSF201080P	-	NSY2SP208	NSYEC108	NSYEC1081	NSYEC1082
2000	1200	400	2	NSYSF2012402D	NSYSF2012402DP	-	NSY2SP204	NSYEC124	NSYEC1241	-
2000	1200	500	2	NSYSF2012502D	NSYSF2012502DP	-	NSY2SP205	NSYEC125	NSYEC1251	-
2000	1200	600	2	NSYSF2012602D	NSYSF2012602DP	-	NSY2SP206	NSYEC126	NSYEC1261	NSYEC1262
2000	1200	800	2	NSYSF2012802D	NSYSF2012802DP	-	NSY2SP208	NSYEC128	NSYEC1281	NSYEC1282
2000	1600	400	2	NSYSF2016402D	NSYSF2016402DP	-	NSY2SP204	NSYEC164	NSYEC1641	-
2000	1600	500	2	NSYSF2016502D	NSYSF2016502DP	-	NSY2SP205	NSYEC165	NSYEC1651	-
2000	1600	600	2	NSYSF2016602D	NSYSF2016602DP	-	NSY2SP206	NSYEC166	NSYEC1661	NSYEC1662
2200	400	600	1	NSYSF22460	-	-	NSY2SP226	-	NSYEC461	-
2200	600	600	1	NSYSF22660	NSYSF22660P	-	NSY2SP226	NSYEC66	NSYEC661	NSYEC662
2200	600	800	1	NSYSF22680	NSYSF22680P	-	NSY2SP228	NSYEC68	NSYEC681	NSYEC682
2200	800	600	1	NSYSF22860	NSYSF22860P	-	NSY2SP226	NSYEC86	NSYEC861	NSYEC862
2200	800	800	1	NSYSF22880	NSYSF22880P	NSYSF22880T	NSY2SP228	NSYEC88	NSYEC881	NSYEC882
2200	1000	600	1	NSYSF221060	NSYSF221060P	-	NSY2SP226	NSYEC106	NSYEC1061	NSYEC1062
2200	1200	600	2	NSYSF2212602D	NSYSF2212602DP	-	NSY2SP226	NSYEC126	NSYEC1261	NSYEC1262
2200	1200	800	2	NSYSF2212802D	NSYSF2212802DP	-	NSY2SP228	NSYEC128	NSYEC1281	NSYEC1282

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Plinths (H 100 mm)		Plinths (H 200 mm)		Mounting plates		Vertical uprights	
							
Front kit (corners + front panels)	Side panels, 2 u.	Front kit (corners + front panels)	Side panels, 4 u.	Mounting plate	Intermediate mounting plate	Standard	Technical
NSYSPF6100	NSYSPS4100	NSYSPF6200	NSYSPS4200	NSYMP126	NSYSIMP12	-	NSYTVR12
NSYSPF6100	NSYSPS6100	NSYSPF6200	NSYSPS6200	NSYMP126	NSYSIMP12	-	NSYTVR12
NSYSPF8100	NSYSPS4100	NSYSPF8200	NSYSPS4200	NSYMP128	NSYSIMP12	-	NSYTVR12
NSYSPF8100	NSYSPS6100	NSYSPF8200	NSYSPS6200	NSYMP128	NSYSIMP12	-	NSYTVR12
NSYSPF6100	NSYSPS4100	NSYSPF6200	NSYSPS4200	NSYMP146	NSYSIMP14	-	NSYTVR14
NSYSPF8100	NSYSPS4100	NSYSPF8200	NSYSPS4200	NSYMP148	NSYSIMP14	-	NSYTVR14
NSYSPF6100	NSYSPS6100	NSYSPF6200	NSYSPS6200	NSYMP166	NSYSIMP16	-	NSYTVR16
NSYSPF6100	NSYSPS8100	NSYSPF6200	NSYSPS8200	NSYMP166	NSYSIMP16	-	NSYTVR16
NSYSPF8100	NSYSPS6100	NSYSPF8200	NSYSPS6200	NSYMP168	NSYSIMP16	-	NSYTVR16
NSYSPF8100	NSYSPS8100	NSYSPF8200	NSYSPS8200	NSYMP168	NSYSIMP16	-	NSYTVR16
NSYSPF4100	NSYSPS4100	NSYSPF4200	NSYSPS4200	NSYMP184 New	-	NSYVR18	NSYTVR18
NSYSPF4100	NSYSPS5100	NSYSPF4200	NSYSPS5200	NSYMP184 New	-	NSYVR18	NSYTVR18
NSYSPF4100	NSYSPS6100	NSYSPF4200	NSYSPS6200	NSYMP184 New	-	NSYVR18	NSYTVR18
NSYSPF6100	NSYSPS4100	NSYSPF6200	NSYSPS4200	NSYMP186	NSYSIMP18	NSYVR18	NSYTVR18
NSYSPF6100	NSYSPS5100	NSYSPF6200	NSYSPS5200	NSYMP186	NSYSIMP18	NSYVR18	NSYTVR18
NSYSPF6100	NSYSPS6100	NSYSPF6200	NSYSPS6200	NSYMP186	NSYSIMP18	NSYVR18	NSYTVR18
NSYSPF6100	NSYSPS8100	NSYSPF6200	NSYSPS8200	NSYMP186	NSYSIMP18	NSYVR18	NSYTVR18
NSYSPF8100	NSYSPS4100	NSYSPF8200	NSYSPS4200	NSYMP188	NSYSIMP18	NSYVR18	NSYTVR18
NSYSPF8100	NSYSPS5100	NSYSPF8200	NSYSPS5200	NSYMP188	NSYSIMP18	NSYVR18	NSYTVR18
NSYSPF8100	NSYSPS6100	NSYSPF8200	NSYSPS6200	NSYMP188	NSYSIMP18	NSYVR18	NSYTVR18
NSYSPF8100	NSYSPS6100	NSYSPF8200	NSYSPS6200	NSYMP188	NSYSIMP18	NSYVR18	NSYTVR18
NSYSPF10100	NSYSPS4100	NSYSPF10200	NSYSPS4200	NSYMP1810	NSYSIMP18	NSYVR18	NSYTVR18
NSYSPF10100	NSYSPS4100	NSYSPF10200	NSYSPS4200	NSYMP1810	NSYSIMP18	NSYVR18	NSYTVR18
NSYSPF10100	NSYSPS5100	NSYSPF10200	NSYSPS5200	NSYMP1810	NSYSIMP18	NSYVR18	NSYTVR18
NSYSPF10100	NSYSPS6100	NSYSPF10200	NSYSPS6200	NSYMP1810	NSYSIMP18	NSYVR18	NSYTVR18
NSYSPF10100	NSYSPS6100	NSYSPF10200	NSYSPS6200	NSYMP1810	NSYSIMP18	NSYVR18	NSYTVR18
NSYSPF12100	NSYSPS4100	NSYSPF12200	NSYSPS4200	NSYMP1812	NSYSIMP18	NSYVR18	NSYTVR18
NSYSPF12100	NSYSPS5100	NSYSPF12200	NSYSPS5200	NSYMP1812	NSYSIMP18	NSYVR18	NSYTVR18
NSYSPF12100	NSYSPS6100	NSYSPF12200	NSYSPS6200	NSYMP1812	NSYSIMP18	NSYVR18	NSYTVR18
NSYSPF3100	NSYSPS5100	NSYSPF3200	NSYSPS5200	-	-	NSYVR20	NSYTVR20
NSYSPF3100	NSYSPS6100	NSYSPF3200	NSYSPS6200	-	-	NSYVR20	NSYTVR20
NSYSPF3100	NSYSPS8100	NSYSPF3200	NSYSPS8200	-	-	NSYVR20	NSYTVR20
NSYSPF4100	NSYSPS4100	NSYSPF4200	NSYSPS4200	NSYMP204 New	-	NSYVR20	NSYTVR20
NSYSPF4100	NSYSPS5100	NSYSPF4200	NSYSPS5200	NSYMP204 New	-	NSYVR20	NSYTVR20
NSYSPF4100	NSYSPS6100	NSYSPF4200	NSYSPS6200	NSYMP204 New	-	NSYVR20	NSYTVR20
NSYSPF4100	NSYSPS8100	NSYSPF4200	NSYSPS8200	NSYMP204 New	-	NSYVR20	NSYTVR20
NSYSPF6100	NSYSPS4100	NSYSPF6200	NSYSPS4200	NSYMP206	NSYSIMP20	NSYVR20	NSYTVR20
NSYSPF6100	NSYSPS5100	NSYSPF6200	NSYSPS5200	NSYMP206	NSYSIMP20	NSYVR20	NSYTVR20
NSYSPF6100	NSYSPS6100	NSYSPF6200	NSYSPS6200	NSYMP206	NSYSIMP20	NSYVR20	NSYTVR20
NSYSPF6100	NSYSPS8100	NSYSPF6200	NSYSPS8200	NSYMP206	NSYSIMP20	NSYVR20	NSYTVR20
NSYSPF8100	NSYSPS4100	NSYSPF8200	NSYSPS4200	NSYMP208	NSYSIMP20	NSYVR20	NSYTVR20
NSYSPF8100	NSYSPS5100	NSYSPF8200	NSYSPS5200	NSYMP208	NSYSIMP20	NSYVR20	NSYTVR20
NSYSPF8100	NSYSPS6100	NSYSPF8200	NSYSPS6200	NSYMP208	NSYSIMP20	NSYVR20	NSYTVR20
NSYSPF8100	NSYSPS6100	NSYSPF8200	NSYSPS6200	NSYMP208	NSYSIMP20	NSYVR20	NSYTVR20
NSYSPF8100	NSYSPS8100	NSYSPF8200	NSYSPS8200	NSYMP208	NSYSIMP20	NSYVR20	NSYTVR20
NSYSPF10100	NSYSPS4100	NSYSPF10200	NSYSPS4200	NSYMP2010	NSYSIMP20	NSYVR20	NSYTVR20
NSYSPF10100	NSYSPS4100	NSYSPF10200	NSYSPS4200	NSYMP2010	NSYSIMP20	NSYVR20	NSYTVR20
NSYSPF10100	NSYSPS5100	NSYSPF10200	NSYSPS5200	NSYMP2010	NSYSIMP20	NSYVR20	NSYTVR20
NSYSPF10100	NSYSPS5100	NSYSPF10200	NSYSPS5200	NSYMP2010	NSYSIMP20	NSYVR20	NSYTVR20
NSYSPF10100	NSYSPS6100	NSYSPF10200	NSYSPS6200	NSYMP2010	NSYSIMP20	NSYVR20	NSYTVR20
NSYSPF10100	NSYSPS6100	NSYSPF10200	NSYSPS6200	NSYMP2010	NSYSIMP20	NSYVR20	NSYTVR20
NSYSPF10100	NSYSPS8100	NSYSPF10200	NSYSPS8200	NSYMP2010	NSYSIMP20	NSYVR20	NSYTVR20
NSYSPF12100	NSYSPS4100	NSYSPF12200	NSYSPS4200	NSYMP2012	NSYSIMP20	NSYVR20	NSYTVR20
NSYSPF12100	NSYSPS5100	NSYSPF12200	NSYSPS5200	NSYMP2012	NSYSIMP20	NSYVR20	NSYTVR20
NSYSPF12100	NSYSPS6100	NSYSPF12200	NSYSPS6200	NSYMP2012	NSYSIMP20	NSYVR20	NSYTVR20
NSYSPF12100	NSYSPS8100	NSYSPF12200	NSYSPS8200	NSYMP2012	NSYSIMP20	NSYVR20	NSYTVR20
NSYSPF16100	NSYSPS4100	NSYSPF16200	NSYSPS4200	NSYMP2016	NSYSIMP20	NSYVR20	NSYTVR20
NSYSPF16100	NSYSPS5100	NSYSPF16200	NSYSPS5200	NSYMP2016	NSYSIMP20	NSYVR20	NSYTVR20
NSYSPF16100	NSYSPS6100	NSYSPF16200	NSYSPS6200	NSYMP2016	NSYSIMP20	NSYVR20	NSYTVR20
NSYSPF4100	NSYSPS6100	NSYSPF4200	NSYSPS6200	NSYMP224 New	-	NSYVR22	NSYTVR22
NSYSPF6100	NSYSPS6100	NSYSPF6200	NSYSPS6200	NSYMP226	NSYSIMP22	NSYVR22	NSYTVR22
NSYSPF6100	NSYSPS8100	NSYSPF6200	NSYSPS8200	NSYMP226	NSYSIMP22	NSYVR22	NSYTVR22
NSYSPF8100	NSYSPS6100	NSYSPF8200	NSYSPS6200	NSYMP228	NSYSIMP22	NSYVR22	NSYTVR22
NSYSPF8100	NSYSPS8100	NSYSPF8200	NSYSPS8200	NSYMP228	NSYSIMP22	NSYVR22	NSYTVR22
NSYSPF10100	NSYSPS6100	NSYSPF10200	NSYSPS6200	NSYMP2210	NSYSIMP22	NSYVR22	NSYTVR22
NSYSPF12100	NSYSPS6100	NSYSPF12200	NSYSPS6200	NSYMP2212	NSYSIMP22	NSYVR22	NSYTVR22
NSYSPF12100	NSYSPS8100	NSYSPF12200	NSYSPS8200	NSYMP2212	NSYSIMP22	NSYVR22	NSYTVR22

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Dimensions				Vertical uprights	Bottom frame and top frame with roof	Panels		Doors		Mounting plate	
(A) Height (mm)	(B) Width (mm)	(C) Depth (mm)	Doors			Rear panel	Side panel	Plain (Hinges, locking bar catches and handle with 5 mm double bar insert included.)	Transparent (Securit® glass, hinges, locking bar catches and handle with 5 mm double bar insert included.)		
1200	600	400	1	NSYSFV12	NSYSFC64	NSYBP126	NSY2SP124	NSYSFD126	NSYSFD126T	NSYMP126	
1200	600	500	1	NSYSFV12	NSYSFC65	NSYBP126	NSY2SP125	NSYSFD126	NSYSFD126T	NSYMP126	
1200	600	600	1	NSYSFV12	NSYSFC66	NSYBP126	NSY2SP126	NSYSFD126	NSYSFD126T	NSYMP126	
1200	600	800	1	NSYSFV12	NSYSFC68	NSYBP126	NSY2SP128	NSYSFD126	NSYSFD126T	NSYMP126	
1200	800	400	1	NSYSFV12	NSYSFC84	NSYBP128	NSY2SP124	NSYSFD128	NSYSFD128T	NSYMP128	
1200	800	500	1	NSYSFV12	NSYSFC85	NSYBP128	NSY2SP125	NSYSFD128	NSYSFD128T	NSYMP128	
1200	800	600	1	NSYSFV12	NSYSFC86	NSYBP128	NSY2SP126	NSYSFD128	NSYSFD128T	NSYMP128	
1200	800	800	1	NSYSFV12	NSYSFC88	NSYBP128	NSY2SP128	NSYSFD128	NSYSFD128T	NSYMP128	
1400	600	400	1	NSYSFV14	NSYSFC64	NSYBP146	NSY2SP144	NSYSFD146	NSYSFD146T	NSYMP146	
1400	600	500	1	NSYSFV14	NSYSFC65	NSYBP146	NSY2SP145	NSYSFD146	NSYSFD146T	NSYMP146	
1400	600	600	1	NSYSFV14	NSYSFC66	NSYBP146	NSY2SP146	NSYSFD146	NSYSFD146T	NSYMP146	
1400	600	800	1	NSYSFV14	NSYSFC68	NSYBP146	NSY2SP148	NSYSFD146	NSYSFD146T	NSYMP146	
1400	800	400	1	NSYSFV14	NSYSFC84	NSYBP148	NSY2SP144	NSYSFD148	NSYSFD148T	NSYMP148	
1400	800	500	1	NSYSFV14	NSYSFC85	NSYBP148	NSY2SP145	NSYSFD148	NSYSFD148T	NSYMP148	
1400	800	600	1	NSYSFV14	NSYSFC86	NSYBP148	NSY2SP146	NSYSFD148	NSYSFD148T	NSYMP148	
1400	800	800	1	NSYSFV14	NSYSFC88	NSYBP148	NSY2SP148	NSYSFD148	NSYSFD148T	NSYMP148	
1600	600	400	1	NSYSFV16	NSYSFC64	NSYBP166	NSY2SP164	NSYSFD166	NSYSFD166T	NSYMP166	
1600	600	500	1	NSYSFV16	NSYSFC65	NSYBP166	NSY2SP165	NSYSFD166	NSYSFD166T	NSYMP166	
1600	600	600	1	NSYSFV16	NSYSFC66	NSYBP166	NSY2SP166	NSYSFD166	NSYSFD166T	NSYMP166	
1600	600	800	1	NSYSFV16	NSYSFC68	NSYBP166	NSY2SP168	NSYSFD166	NSYSFD166T	NSYMP166	
1600	800	400	1	NSYSFV16	NSYSFC84	NSYBP168	NSY2SP164	NSYSFD168	NSYSFD168T	NSYMP168	
1600	800	500	1	NSYSFV16	NSYSFC85	NSYBP168	NSY2SP165	NSYSFD168	NSYSFD168T	NSYMP168	
1600	800	600	1	NSYSFV16	NSYSFC86	NSYBP168	NSY2SP166	NSYSFD168	NSYSFD168T	NSYMP168	
1600	800	800	1	NSYSFV16	NSYSFC88	NSYBP168	NSY2SP168	NSYSFD168	NSYSFD168T	NSYMP168	
1800	400	400	1	NSYSFV18	NSYSFC44	NSYBP184	NSY2SP184	NSYSFD184	-	NSYMP204 New	
1800	400	500	1	NSYSFV18	NSYSFC45	NSYBP184	NSY2SP185	NSYSFD184	-	NSYMP204 New	
1800	400	600	1	NSYSFV18	NSYSFC46	NSYBP184	NSY2SP186	NSYSFD184	-	NSYMP204 New	
1800	400	800	1	NSYSFV18	NSYSFC48	NSYBP184	NSY2SP188	NSYSFD184	-	NSYMP204 New	
1800	600	400	1	NSYSFV18	NSYSFC64	NSYBP186	NSY2SP184	NSYSFD186	NSYSFD186T	NSYMP186	
1800	600	500	1	NSYSFV18	NSYSFC65	NSYBP186	NSY2SP185	NSYSFD186	NSYSFD186T	NSYMP186	
1800	600	600	1	NSYSFV18	NSYSFC66	NSYBP186	NSY2SP186	NSYSFD186	NSYSFD186T	NSYMP186	
1800	600	800	1	NSYSFV18	NSYSFC68	NSYBP186	NSY2SP188	NSYSFD186	NSYSFD186T	NSYMP186	
1800	800	400	1	NSYSFV18	NSYSFC84	NSYBP188	NSY2SP184	NSYSFD188	NSYSFD188T	NSYMP188	
1800	800	500	1	NSYSFV18	NSYSFC85	NSYBP188	NSY2SP185	NSYSFD188	NSYSFD188T	NSYMP188	
1800	800	600	1	NSYSFV18	NSYSFC86	NSYBP188	NSY2SP186	NSYSFD188	NSYSFD188T	NSYMP188	
1800	800	600	2	NSYSFV18	NSYSFC86	NSYBP188	NSY2SP186	NSYSFD1882D	-	NSYMP188	
1800	800	800	1	NSYSFV18	NSYSFC88	NSYBP188	NSY2SP188	NSYSFD188	NSYSFD188T	NSYMP188	
1800	800	800	2	NSYSFV18	NSYSFC88	NSYBP188	NSY2SP188	NSYSFD1882D	-	NSYMP188	
1800	1000	400	1	NSYSFV18	NSYSFC104	NSYBP1810	NSY2SP184	NSYSFD1810	NSYSFD1810T	NSYMP1810	
1800	1000	400	2	NSYSFV18	NSYSFC104	NSYBP1810	NSY2SP184	NSYSFD18102D	-	NSYMP1810	
1800	1000	500	1	NSYSFV18	NSYSFC105	NSYBP1810	NSY2SP185	NSYSFD1810	NSYSFD1810T	NSYMP1810	
1800	1000	600	1	NSYSFV18	NSYSFC106	NSYBP1810	NSY2SP186	NSYSFD1810	NSYSFD1810T	NSYMP1810	
1800	1000	600	2	NSYSFV18	NSYSFC106	NSYBP1810	NSY2SP186	NSYSFD18102D	-	NSYMP1810	
1800	1000	800	1	NSYSFV18	NSYSFC108	NSYBP1810	NSY2SP188	NSYSFD1810	NSYSFD1810T	NSYMP1810	
1800	1000	800	2	NSYSFV18	NSYSFC108	NSYBP1810	NSY2SP188	NSYSFD18102D	-	NSYMP1810	
1800	1200	400	2	NSYSFV18	NSYSFC124	NSYBP1812	NSY2SP184	NSYSFD18122D	NSYSFD18122DT	NSYMP1812	
1800	1200	500	2	NSYSFV18	NSYSFC125	NSYBP1812	NSY2SP185	NSYSFD18122D	NSYSFD18122DT	NSYMP1812	
1800	1200	600	2	NSYSFV18	NSYSFC126	NSYBP1812	NSY2SP186	NSYSFD18122D	NSYSFD18122DT	NSYMP1812	
1800	1200	800	2	NSYSFV18	NSYSFC128	NSYBP1812	NSY2SP188	NSYSFD18122D	NSYSFD18122DT	NSYMP1812	

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Dimensions				Vertical uprights	Bottom frame and top frame with roof	Panels		Doors		Mounting plate
								(Hinges, locking bar catches and handle with 5 mm double bar insert included.)	(Securit® glass, hinges, locking bar catches and handle with 5 mm double bar insert included.)	
(A) Height (mm)	(B) Width (mm)	(C) Depth (mm)	Doors			Rear panel	Side panel	Plain	Transparent	
2000	300	500	1	NSYSFV20	NSYSFC35	NSYBP203	NSY2SP205	NSYSFD203	-	-
2000	300	600	1	NSYSFV20	NSYSFC36	NSYBP203	NSY2SP206	NSYSFD203	-	-
2000	300	800	1	NSYSFV20	NSYSFC38	NSYBP203	NSY2SP208	NSYSFD203	-	-
2000	400	400	1	NSYSFV20	NSYSFC44	NSYBP204	NSY2SP204	NSYSFD204	-	-
2000	400	500	1	NSYSFV20	NSYSFC45	NSYBP204	NSY2SP205	NSYSFD204	-	-
2000	400	600	1	NSYSFV20	NSYSFC46	NSYBP204	NSY2SP206	NSYSFD204	-	-
2000	400	800	1	NSYSFV20	NSYSFC48	NSYBP204	NSY2SP208	NSYSFD204	-	-
2000	600	400	1	NSYSFV20	NSYSFC64	NSYBP206	NSY2SP204	NSYSFD206	NSYSFD206T	NSYMP206
2000	600	500	1	NSYSFV20	NSYSFC65	NSYBP206	NSY2SP205	NSYSFD206	NSYSFD206T	NSYMP206
2000	600	600	1	NSYSFV20	NSYSFC66	NSYBP206	NSY2SP206	NSYSFD206	NSYSFD206T	NSYMP206
2000	600	800	1	NSYSFV20	NSYSFC68	NSYBP206	NSY2SP208	NSYSFD206	NSYSFD206T	NSYMP206
2000	800	400	1	NSYSFV20	NSYSFC84	NSYBP208	NSY2SP204	NSYSFD208	NSYSFD208T	NSYMP208
2000	800	500	1	NSYSFV20	NSYSFC85	NSYBP208	NSY2SP205	NSYSFD208	NSYSFD208T	NSYMP208
2000	800	600	1	NSYSFV20	NSYSFC86	NSYBP208	NSY2SP206	NSYSFD208	NSYSFD208T	NSYMP208
2000	800	600	2	NSYSFV20	NSYSFC86	NSYBP208	NSY2SP206	NSYSFD2082D	-	NSYMP208
2000	800	800	1	NSYSFV20	NSYSFC88	NSYBP208	NSY2SP208	NSYSFD208	NSYSFD208T	NSYMP208
2000	800	800	2	NSYSFV20	NSYSFC88	NSYBP208	NSY2SP208	NSYSFD2082D	-	NSYMP208
2000	1000	400	1	NSYSFV20	NSYSFC104	NSYBP2010	NSY2SP204	NSYSFD2010	NSYSFD2010T	NSYMP2010
2000	1000	400	2	NSYSFV20	NSYSFC104	NSYBP2010	NSY2SP204	NSYSFD20102D	-	NSYMP2010
2000	1000	500	1	NSYSFV20	NSYSFC105	NSYBP2010	NSY2SP205	NSYSFD2010	NSYSFD2010T	NSYMP2010
2000	1000	500	2	NSYSFV20	NSYSFC105	NSYBP2010	NSY2SP205	NSYSFD20102D	-	NSYMP2010
2000	1000	600	1	NSYSFV20	NSYSFC106	NSYBP2010	NSY2SP206	NSYSFD2010	NSYSFD2010T	NSYMP2010
2000	1000	600	2	NSYSFV20	NSYSFC106	NSYBP2010	NSY2SP206	NSYSFD20102D	-	NSYMP2010
2000	1000	800	1	NSYSFV20	NSYSFC108	NSYBP2010	NSY2SP208	NSYSFD2010	NSYSFD2010T	NSYMP2010
2000	1000	800	2	NSYSFV20	NSYSFC108	NSYBP2010	NSY2SP208	NSYSFD20102D	-	NSYMP2010
2000	1200	400	2	NSYSFV20	NSYSFC124	NSYBP2012	NSY2SP204	NSYSFD20122D	NSYSFD20122DT	NSYMP2012
2000	1200	500	2	NSYSFV20	NSYSFC125	NSYBP2012	NSY2SP205	NSYSFD20122D	NSYSFD20122DT	NSYMP2012
2000	1200	600	2	NSYSFV20	NSYSFC126	NSYBP2012	NSY2SP206	NSYSFD20122D	NSYSFD20122DT	NSYMP2012
2000	1200	800	2	NSYSFV20	NSYSFC128	NSYBP2012	NSY2SP208	NSYSFD20122D	NSYSFD20122DT	NSYMP2012
2000	1600	400	2	NSYSFV20	NSYSFC164	NSYBP2016	NSY2SP204	NSYSFD20162D	-	NSYMP2016
2000	1600	500	2	NSYSFV20	NSYSFC165	NSYBP2016	NSY2SP205	NSYSFD20162D	-	NSYMP2016
2000	1600	600	2	NSYSFV20	NSYSFC166	NSYBP2016	NSY2SP206	NSYSFD20162D	-	NSYMP2016
2200	400	400	1	NSYSFV22	NSYSFC44	NSYBP224	NSY2SP224	NSYSFD224	-	-
2200	400	500	1	NSYSFV22	NSYSFC45	NSYBP224	NSY2SP225	NSYSFD224	-	-
2200	400	600	1	NSYSFV22	NSYSFC46	NSYBP224	NSY2SP226	NSYSFD224	-	-
2200	400	800	1	NSYSFV22	NSYSFC48	NSYBP224	NSY2SP228	NSYSFD224	-	-
2200	600	400	1	NSYSFV22	NSYSFC64	NSYBP226	NSY2SP224	NSYSFD226	NSYSFD226T	NSYMP226
2200	600	500	1	NSYSFV22	NSYSFC65	NSYBP226	NSY2SP225	NSYSFD226	NSYSFD226T	NSYMP226
2200	600	600	1	NSYSFV22	NSYSFC66	NSYBP226	NSY2SP226	NSYSFD226	NSYSFD226T	NSYMP226
2200	600	800	1	NSYSFV22	NSYSFC68	NSYBP226	NSY2SP228	NSYSFD226	NSYSFD226T	NSYMP226
2200	800	400	1	NSYSFV22	NSYSFC84	NSYBP228	NSY2SP224	NSYSFD228	NSYSFD228T	NSYMP228
2200	800	500	1	NSYSFV22	NSYSFC85	NSYBP228	NSY2SP225	NSYSFD228	NSYSFD228T	NSYMP228
2200	800	600	1	NSYSFV22	NSYSFC86	NSYBP228	NSY2SP226	NSYSFD228	NSYSFD228T	NSYMP228
2200	800	800	1	NSYSFV22	NSYSFC88	NSYBP228	NSY2SP228	NSYSFD228	NSYSFD228T	NSYMP228
2200	1000	400	1	NSYSFV22	NSYSFC104	NSYBP2210	NSY2SP224	NSYSFD2210	NSYSFD2210T	NSYMP2210
2200	1000	500	1	NSYSFV22	NSYSFC105	NSYBP2210	NSY2SP225	NSYSFD2210	NSYSFD2210T	NSYMP2210
2200	1000	600	1	NSYSFV22	NSYSFC106	NSYBP2210	NSY2SP226	NSYSFD2210	NSYSFD2210T	NSYMP2210
2200	1000	800	1	NSYSFV22	NSYSFC108	NSYBP2210	NSY2SP228	NSYSFD2210	NSYSFD2210T	NSYMP2210
2200	1200	400	2	NSYSFV22	NSYSFC124	NSYBP2212	NSY2SP224	NSYSFD22122D	NSYSFD22122DT	NSYMP2212
2200	1200	500	2	NSYSFV22	NSYSFC125	NSYBP2212	NSY2SP225	NSYSFD22122D	NSYSFD22122DT	NSYMP2212
2200	1200	600	2	NSYSFV22	NSYSFC126	NSYBP2212	NSY2SP226	NSYSFD22122D	NSYSFD22122DT	NSYMP2212
2200	1200	800	2	NSYSFV22	NSYSFC128	NSYBP2212	NSY2SP228	NSYSFD22122D	NSYSFD22122DT	NSYMP2212

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

					304L stainless steel		316L stainless steel	304L stainless steel
External dimensions								
Height (mm)	Width (mm)	Depth (mm)	No. of locks	No. of doors	Plain door	Glazed door. The glazed door has no reinforcement.	Plain door	Canopy
300	200	150	1	1	**NSYS3X3215**	-	**NSYS3X3215H**	**NSYTX2015**
300	250	150	1	1	**NSYS3X302515**	-	**NSYS3X302515H**	**NSYTX2515**
300	300	150	1	1	**NSYS3X3315**	-	**NSYS3X3315H**	**NSYTX3015**
400	300	150	1	1	**NSYS3X4315**	-	**NSYS3X4315H**	**NSYTX3015**
400	300	200	1	1	**NSYS3X4320**	**NSYS3X4320T**	**NSYS3X4320H**	**NSYTX3020**
400	400	200	1	1	**NSYS3X4420**	-	**NSYS3X4420H**	**NSYTX4020**
400	600	200	1	1	**NSYS3X4620**	-	**NSYS3X4620H**	**NSYTX6020**
500	400	200	2	1	**NSYS3X5420**	**NSYS3X5420T**	**NSYS3X5420H**	**NSYTX4020**
600	400	200	2	1	**NSYS3X6420**	**NSYS3X6420T**	**NSYS3X6420H**	**NSYTX4020**
600	600	250	2	1	**NSYS3X6625**	-	**NSYS3X6625H**	**NSYTX6025**
600	1000	300		2	**NSYS3X601030**	-	-	-
600	1200	300	(1)	2	**NSYS3X601230**	-	-	**NSYTX12030**
700	500	250	2	1	**NSYS3X7525**	**NSYS3X7525T**	**NSYS3X7525H**	**NSYTX5025**
800	600	250	2	1	**NSYS3X8625**	**NSYS3X8625T**	**NSYS3X8625H**	**NSYTX6025**
800	800	300	2	1	**NSYS3X8830**	-	**NSYS3X8830H**	**NSYTX8030**
800	1000	300		2	**NSYS3X801030**	-	-	-
800	1200	300	(1)	2	**NSYS3X801230**	-	-	**NSYTX12030**
1000	800	300	2	1	**NSYS3X10830**	**NSYS3X10830T**	**NSYS3X10830H**	**NSYTX8030**
1000	1000	300	(1)	2	**NSYS3X101030**	-	**NSYS3X101030H**	**NSYTX10030**
1200	800	300	2	1	**NSYS3X12830**	-	**NSYS3X12830H**	**NSYTX8030**
1200	1000	300	(1)	2	**NSYS3X121030**	-	**NSYS3X121030H**	**NSYTX10030**

(1) Three-point closure system.

Accessories

External dimensions									
Height (mm)	Width (mm)	Depth (mm)	No. of modules	Mounting plate Plain	Mounting plate Silkscreened	Mounting plate Microperforated	Mounting plate Telequick	Mounting plate Modular	Step slides
300	200	150	-	**NSYMM32**	-	**NSYMF32**	**NSYMR32**	-	-
300	250	150	-	**NSYMM3025**	-	-	**NSYMR3025**	-	-
300	300	150	-	**NSYMM33**	-	**NSYMF33**	**NSYMR33**	-	-
400	300	150	24	**NSYMM43**	**NSYMS43**	**NSYMF43**	**NSYMR43**	**NSYDLM24**	-
400		200	24	**NSYMM43**	**NSYMS43**	**NSYMF43**	**NSYMR43**	**NSYDLM24**	**NSYSDCR200**
400	400	200	-	**NSYMM44**	**NSYMS44**	**NSYMF44**	**NSYMR44**	-	**NSYSDCR200**
400	600	200	-	**NSYMM64**	**NSYMS64**	**NSYMF64**	**NSYMR46**	-	**NSYSDCR200**
500	400	200	48	**NSYMM54**	**NSYMS54**	**NSYMF54**	**NSYMR54**	**NSYDLM48**	**NSYSDCR200**
600	400	200	48	**NSYMM64**	**NSYMS64**	**NSYMF64**	**NSYMR64**	**NSYDLM48P**	**NSYSDCR200**
600	600	250	84	**NSYMM66**	**NSYMS66**	**NSYMF66**	**NSYMR66**	**NSYDLM84P**	**NSYSDCR250**
600	1000	300*	-	**NSYMM106**	-	**NSYMF106**	**NSYMR106**	-	**NSYSDCR300**
600	1200	300*	-	**NSYMM126**	-	**NSYMF126**	-	-	**NSYSDCR300**
700	500	250	66	**NSYMM75**	**NSYMS75**	**NSYMF75**	**NSYMR75**	**NSYDLM66**	**NSYSDCR250**
700	500	250	88	-	-	-	-	**NSYDLM88**	-
800	600	250	84	**NSYMM86**	**NSYMS86**	**NSYMF86**	**NSYMR86**	**NSYDLM84**	**NSYSDCR250**
800	600	250	112	-	-	-	-	**NSYDLM112**	-
800	800	300	-	**NSYMM88**	-	**NSYMF88**	**NSYMR88**	-	**NSYSDCR300**
800	1000	300(1)	-	**NSYMM108**	-	**NSYMF108**	**NSYMR108**	-	**NSYSDCR300**
800	1200	300(1)	-	**NSYMM128**	-	**NSYMF128**	**NSYMR128**	-	**NSYSDCR300**
1000	800	300	234	**NSYMM108**	-	**NSYMF108**	**NSYMR108**	**NSYDLM240**	**NSYSDCR300**
1000	1000	300	-	**NSYMM1010**	-	**NSYMF1010**	**NSYMR1010**	-	**NSYSDCR300**
1200	800	300	-	**NSYMM128**	-	**NSYMF128**	**NSYMR128**	-	**NSYSDCR300**
1200	1000	300	-	**NSYMM1210**	-	**NSYMF1210**	**NSYMR1210**	-	**NSYSDCR300**

(1) Three-point closure system.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Stainless steel floor-standing monobloc

External dimensions Height (mm)	Width (mm)	Depth (mm)	No. of front doors	304L stainless steel Floor-standing enclosure	316L stainless steel Floor-standing enclosure	Brushed 304L / 316L stainless steel plinth height 100 mm* Kit (4 corners + front and back)	Set of 2 side panels	Brushed 304L / 316L stainless steel plinth height 200 mm* Kit (4 corners + front and back)	Set of 2 side panels (x2)	Mounting plate** Plain
						Plinth height 100 mm (4 corners + front and back)		Plinth height 100 mm (Set of 2 side panels)		
1400	1000	300	2	**NSYSMX141030**	–	**NSYSPFX10100**	**NSYSPSX3100**	**NSYSPFX10200**	**NSYSPSX3200**	**NSYMP1410**
1600	800	400	1	**NSYSMX16840**	–	**NSYSPFX8100**	**NSYSPSX4100**	**NSYSPFX8200**	**NSYSPSX4200**	**NSYMP168**
1800	600	400	1	**NSYSMX18640**	–	–	**NSYSPSX4100**	–	**NSYSPSX4200**	**NSYMP186**
1800	800	400	1	**NSYSMX18840**	**NSYSMX18840H**	**NSYSPFX8100**	**NSYSPSX4100**	**NSYSPFX8200**	**NSYSPSX4200**	**NSYMP188**
1800	1200	400	2	**NSYSMX181240**	**NSYSMX181240H**	**NSYSPFX12100**	**NSYSPSX4100**	**NSYSPFX12200**	**NSYSPSX4200**	**NSYMP1812**
1800	1600	400	2	**NSYSMX181640**	**NSYSMX181640H**	**NSYSPFX16100**	**NSYSPSX4100**	**NSYSPFX16200**	**NSYSPSX4200**	**NSYMP1816**
2000	800	500	1	**NSYSMX20850**	–	**NSYSPFX8100**	**NSYSPSX5100**	**NSYSPFX8200**	**NSYSPSX5200**	**NSYMP208**
2000	1000	400	2	**NSYSMX201040**	**NSYSMX201040H**	**NSYSPFX10100**	**NSYSPSX4100**	**NSYSPFX10200**	**NSYSPSX4200**	**NSYMP2010**
2000	1200	500	2	**NSYSMX201250**	**NSYSMX201250H**	**NSYSPFX12100**	**NSYSPSX5100**	**NSYSPFX12200**	**NSYSPSX5200**	**NSYMP2012**
2000	1600	600	2	**NSYSMX201660**	**NSYSMX201660H**	**NSYSPFX16100**	**NSYSPSX6100**	**NSYSPFX16200**	**NSYSPSX6200**	**NSYMP2016**

Stainless steel floor-standing monobloc

External dimensions Height (mm)	Width (mm)	Depth (mm)	No. of front doors	304L stainless steel (316L stainless steel enclosures on request) Suitable enclosure	Set of 2 side panels	Coupling kit	Brushed 304L stainless steel plinth height 100 mm* Kit (4 corners + front and back)	Set of 2 side panels	Brushed 304L stainless steel plinth height 200 mm* Kit (4 corners + front and back)	Side Set of 2 side panels (x2)	Mounting plate** Plain
							Plinth height 100 mm (4 corners + front and back)		Plinth height 100 mm (Set of 2 side panels)		
1800	600	400	1	**NSYSFX18640**	**NSY2SPX184**	**NSYSFBK19** + **NSYSFXJG**	**NSYSPFX6100**	**NSYSPSX4100SF**	**NSYSPFX6200**	**NSYSPSX4200SF**	**NSYMP186**
1800	800	400	1	**NSYSFX18840**	**NSY2SPX184**		**NSYSPFX8100**	**NSYSPSX4100SF**	**NSYSPFX8200**	**NSYSPSX4200SF**	**NSYMP188**
1800	1200	400	2	**NSYSFX181240**	**NSY2SPX184**		**NSYSPFX12100**	**NSYSPSX4100SF**	**NSYSPFX12200**	**NSYSPSX4200SF**	**NSYMP1812**
2000	600	500	1	**NSYSFX20650**	**NSY2SPX205**		**NSYSPFX6100**	**NSYSPSX5100SF**	**NSYSPFX6200**	**NSYSPSX5200SF**	**NSYMP206**
2000	800	400	1	**NSYSFX20840**	**NSY2SPX204**		**NSYSPFX8100**	**NSYSPSX4100SF**	**NSYSPFX8200**	**NSYSPSX4200SF**	**NSYMP208**
2000	800	600	1	**NSYSFX20860**	**NSY2SPX206**		**NSYSPFX8100**	**NSYSPSX6100SF**	**NSYSPFX8200**	**NSYSPSX6200SF**	**NSYMP208**
2000	1000	600	2	**NSYSFX201060**	**NSY2SPX206**		**NSYSPFX10100**	**NSYSPSX6100SF**	**NSYSPFX10200**	**NSYSPSX6200SF**	**NSYMP2010**
2000	1200	600	2	**NSYSFX201260**	**NSY2SPX206**		**NSYSPFX12100**	**NSYSPSX6100SF**	**NSYSPFX12200**	**NSYSPSX6200SF**	**NSYMP2012**

Stainless steel floor-standing suitable

External dimensions Height (mm)	Width (mm)	Depth (mm)	No. of front doors	Stainless steel Floor-standing suitable	304L stainless steel plinth, height 100 mm* Front and rear	side panels	304L stainless steel plinth, height 200 mm* Front and rear	side panels	Mounting plate** Plain
					Plinth height 100 mm (Front and rear)		Plinth height 100 mm (Side panels)		
1000	600	500	1	**NSYSDX6**	**NSYSPFX6100**	**NSYSPSX5100**	**NSYSPFX6200**	2x **NSYSPSX5100**	**NSYPMP8560**
1000	800	500	1	**NSYSDX8**	**NSYSPFX8100**	**NSYSPSX5100**	**NSYSPFX8200**	2x **NSYSPSX5100**	**NSYPMP8580**
1000	1000	500	2	**NSYSDX10**	**NSYSPFX10100**	**NSYSPSX5100**	**NSYSPFX10200**	2x **NSYSPSX5100**	**NSYPMP85100**
1000	1200	500	2	**NSYSDX12**	**NSYSPFX12100**	**NSYSPSX5100**	**NSYSPFX12200**	2x **NSYSPSX5100**	**NSYPMP85120**

* See section on stainless steel composition accessories.
** See other mounting plates in common accessories.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Polyester wall-mounting enclosures

Polyester wall-mounting enclosures IP66

According to Reach and RoHs & Halogen free

Class II

	ABS/PC wall-mounting enclosures		Polyester wall-mounting enclosures					
External dimensions			References of wall-mounting enclosures with door					
Height (mm)	Width (mm)	Depth (mm)	Plain	Transparent	Plain	Transparent	Plain	Transparent	Plain	Transparent
308	255	160	-	-	NSYPLM3025G	NSYPLM3025TG	-	-	-	-
310	215	160	NSYPLM32G	NSYPLM32TG	-	-	-	-	-	-
430	330	200	-	-	-	-	NSYPLM43G	NSYPLM43TG	NSYPLM43VG	NSYPLM43TVG
530	430	200	-	-	-	-	NSYPLM54G	NSYPLM54TG	NSYPLM54VG	NSYPLM54TVG
647	436	250	-	-	-	-	NSYPLM64G	NSYPLM64TG	NSYPLM64VG	NSYPLM64TVG
747	536	300	-	-	-	-	NSYPLM75G	NSYPLM75TG	NSYPLM75VG	NSYPLM75TVG
847	636	300	-	-	-	-	NSYPLM86G	NSYPLM86TG	NSYPLM86VG	NSYPLM86TVG
1056	852	350	-	-	-	-	NSYPLM108G	NSYPLM108TG	-	-
Details			see page 189							

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Polyester wall-mounting enclosures

Mounting accessories

	Metallic mounting plates				Insulating mounting plates		Modular distribution chassis	Step slides	Symmetrical DIN rail
									
Dimensions									
Height (mm)	Width (mm)	Depth (mm)	Plain	Silkscreened	Microperforated	Telequick	Bakelite	Polyester			
310	215	160	NSYMM32	-	-	NSYMR32	NSYMB32	NSYMPP32	-	-	NSYCS200PLM
308	255	160	NSYMM3025	-	-	NSYMR3025	NSYMB3025	NSYMPP3025	NSYDLPLM18G	-	-
430	330	200	NSYMM43	NSYMS43	NSYMF43	NSYMR43	NSYMB43	NSYMPP43	NSYDLA24G	NSYDPLM200	NSYCS300PLM
530	430	200	NSYMM54	NSYMS54	NSYMF54	NSYMR54	NSYMB54	NSYMPP54	NSYDLA48G	NSYDPLM200	NSYCS400PLM
647	436	250	NSYMM64	NSYMS64	NSYMF64	NSYMR64	NSYMB64	NSYMPP64	NSYDLA48PG	NSYDPLM250	NSYCS400PLM
747	536	300	NSYMM75	NSYMS75	NSYMF75	NSYMR75	NSYMB75	NSYMPP75	NSYDLA66G and NSYDLA88G	NSYDPLM300	NSYCS500PLM
847	636	300	NSYMM86	NSYMS86	NSYMF86	NSYMR86	NSYMB86	NSYMPP86	NSYDLA84G and NSYDLA112G	NSYDPLM300	NSYCS600PLM
1056	852	350	NSYMM108	-	NSYMF108	NSYMR108	NSYMB108	NSYMPP108	NSYDLA234G	NSYDPLM350	NSYCS800PLM
Details			see page 240				see page 241		see page 194	see page 198	

Main accessories

Dimensions								
Height (mm)	Width (mm)	Depth (mm)	Fixing lugs	Postfixing device	Floormounting pillar	Coupling frame	Cablegland plate	Internal door	Blanking plates	Plinth ZM RAL 7032
310	215	160	NSYPFPLM32G	-	-	-	-	-	NSYCEPLMAG	-
308	255	160	NSYPFPLMG	-	-	-	-	NSYPA3025PLMG	-	-
430	330	200	NSYPFPLMG	NSYSFP300	-	-	-	NSYPAP43G	NSYCEPLMBG	-
530	430	200	NSYPFPLMG	NSYSFP400	NSYSFSPLMG	-	-	NSYPAP54G	NSYCEPLMBG	-
647	436	250	NSYPFPLMG	NSYSFP400	NSYSFSPLMG	-	-	NSYPAP64G	NSYCEPLMCG	-
747	536	300	NSYPFPLMG	NSYSFP500	-	NSYBUPLMG	NSYTLA4420G	NSYPAP75G	NSYCEPLMCG	NSYZM253G
847	636	300	NSYPFPLMG	NSYSFP600	-	NSYBUPLMG	NSYTLA4420G	NSYPAP86G	NSYCEPLMCG	NSYZM263G
1056	852	350	NSYPFPLMG	-	-	NSYBU108PLMG	NSYTLA6420G	NSYPAP108G	-	NSYZM283G
Details			see page 192			see page 198		see page 193	see page 192	see page 191

Water drain plug: Page 199
Rail-fixing nuts: Page 198
Ventilation louvre: Page 199

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Polyester floor-standing enclosures

Indoor and Outdoor:
For outdoor use, must install a canopy.

Completely sealed enclosures, IP65						Enclosures with open bottom part, IP54
				PLA	PLA	PLAZ
Dimensions						
Height (mm)	Width (mm)	Depth (mm)	N° of doors	Plain	Glazed**	Plain
500	500	320	1	NSYPLA553G	NSYPLA553TG	NSYPLAZ553G
500	500	420	1	NSYPLA554G	NSYPLA554TG	NSYPLAZ554G
500	750	320	1	NSYPLA573G	NSYPLA573TG	NSYPLAZ573G
500	750	420	1	NSYPLA574G	NSYPLA574TG	NSYPLAZ574G
500	1000	320	2	NSYPLA5103G	NSYPLA5103TG	NSYPLAZ5103G
500	1000	420	2	NSYPLA5104G	NSYPLA5104TG	NSYPLAZ5104G
500	1250	320	2	NSYPLA5123G	NSYPLA5123TG	NSYPLAZ5123G
500	1250	420	2	NSYPLA5124G	NSYPLA5124TG	NSYPLAZ5124G
750	500	320	1	NSYPLA753G	NSYPLA753TG	NSYPLAZ753G
750	500	420	1	NSYPLA754G	NSYPLA754TG	NSYPLAZ754G
750	750	320	1	NSYPLA773G	NSYPLA773TG	NSYPLAZ773G
750	750	420	1	NSYPLA774G	NSYPLA774TG	NSYPLAZ774G
750	750	420	1	NSYPLA776G	NSYPLA776TG	NSYPLAZ776G
750	1000	320	2	NSYPLA7103G	NSYPLA7103TG	NSYPLAZ7103G
750	1000	420	2	NSYPLA7104G	NSYPLA7104TG	NSYPLAZ7104G
750	1250	320	2	NSYPLA7123G	NSYPLA7123TG	NSYPLAZ7123G
750	1250	420	2	NSYPLA7124G	NSYPLA7124TG	NSYPLAZ7124G
1000	500	320	1	NSYPLA1053G	NSYPLA1053TG	NSYPLAZ1053G
1000	500	420	1	NSYPLA1054G	NSYPLA1054TG	NSYPLAZ1054G
1000	750	320	1	NSYPLA1073G	NSYPLA1073TG	NSYPLAZ1073G
1000	750	420	1	NSYPLA1074G	NSYPLA1074TG	NSYPLAZ1074G
1000	1000	320	2	NSYPLA10103G	NSYPLA10103TG	NSYPLAZ10103G
1000	1000	420	2	NSYPLA10104G	NSYPLA10104TG	NSYPLAZ10104G
1000	1250	320	2	NSYPLA10123G	NSYPLA10123TG	NSYPLAZ10123G
1000	1250	420	2	NSYPLA10124G	NSYPLA10124TG	NSYPLAZ10124G
1250	500	320	1	NSYPLA1253G	NSYPLA1253TG	NSYPLAZ1253G
1250	500	420	1	NSYPLA1254G	NSYPLA1254TG	NSYPLAZ1254G
1250	750	320	1	NSYPLA1273G	NSYPLA1273TG	NSYPLAZ1273G
1250	750	420	1	NSYPLA1274G	NSYPLA1274TG	NSYPLAZ1274G
1250	750	620	1	NSYPLA1276G	NSYPLA1276TG	NSYPLAZ1276G
1250	1000	320	2	NSYPLA12103G	NSYPLA12103TG	NSYPLAZ12103G
1250	1000	420	2	NSYPLA12104G	NSYPLA12104TG	NSYPLAZ12104G
1250	1250	320	2	NSYPLA12123G	NSYPLA12123TG	NSYPLAZ12123G
1250	1250	420	2	NSYPLA12124G	NSYPLA12124TG	NSYPLAZ12124G
1250	1250	620	2	NSYPLA12126G	NSYPLA12126TG	NSYPLAZ12126G
1500	500	320	1	NSYPLA1553G	NSYPLA1553TG	NSYPLAZ1553G
1500	500	420	1	NSYPLA1554G	NSYPLA1554TG	NSYPLAZ1554G
1500	750	320	1	NSYPLA1573G	NSYPLA1573TG	NSYPLAZ1573G
1500	750	420	1	NSYPLA1574G	NSYPLA1574TG	NSYPLAZ1574G
1500	750	620	1	NSYPLA1576G	NSYPLA1576TG	NSYPLAZ1576G
1500	1000	320	2	NSYPLA15103G	NSYPLA15103TG	NSYPLAZ15103G
1500	1000	420	2	NSYPLA15104G	NSYPLA15104TG	NSYPLAZ15104G
1500	1250	320	2	NSYPLA15123G	NSYPLA15123TG	NSYPLAZ15123G
1500	1250	420	2	NSYPLA15124G	NSYPLA15124TG	NSYPLAZ15124G
1500	1250	620	2	NSYPLA15126G	NSYPLA15126TG	NSYPLAZ15126G
2000	750	420	2*	NSYPLA2074G	NSYPLA2074TG	NSYPLAZ2074G

*Two doors in vertical.

**Recommended to protect against the direct sun radiation.

PHD - Applicative and customised solutions:
See the Polyester Heavy Duty offer in the Applicative and customised solutions, page 416.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Polyester floor-standing enclosures

Indoor and Outdoor:
For outdoor use, must install a canopy.

Enclosures with ventilated canopy, IP44

PLAT

Enclosures with open bottom part and ventilated canopy, IP44

PLAZT

Dimensions					
Height (mm)	Width (mm)	Depth (mm)	N° of doors	Plain	Plain
500	500	320	1	NSYPLAT553G	NSYPLAZT553G
500	500	420	1	NSYPLAT554G	NSYPLAZT554G
500	750	320	1	NSYPLAT573G	NSYPLAZT573G
500	750	420	1	NSYPLAT574G	NSYPLAZT574G
500	1000	320	2	NSYPLAT5103G	NSYPLAZT5103G
500	1000	420	2	NSYPLAT5104G	NSYPLAZT5104G
500	1250	320	2	NSYPLAT5123G	NSYPLAZT5123G
500	1250	420	2	NSYPLAT5124G	NSYPLAZT5124G
750	500	320	1	NSYPLAT753G	NSYPLAZT753G
750	500	420	1	NSYPLAT754G	NSYPLAZT754G
750	750	320	1	NSYPLAT773G	NSYPLAZT773G
750	750	420	1	NSYPLAT774G	NSYPLAZT774G
750	750	620	1	NSYPLAT776G	NSYPLAZT776G
750	1000	320	2	NSYPLAT7103G	NSYPLAZT7103G
750	1000	420	2	NSYPLAT7104G	NSYPLAZT7104G
750	1250	320	2	NSYPLAT7123G	NSYPLAZT7123G
750	1250	420	2	NSYPLAT7124G	NSYPLAZT7124G
1000	500	320	1	NSYPLAT1053G	NSYPLAZT1053G
1000	500	420	1	NSYPLAT1054G	NSYPLAZT1054G
1000	750	320	1	NSYPLAT1073G	NSYPLAZT1073G
1000	750	420	1	NSYPLAT1074G	NSYPLAZT1074G
1000	1000	320	2	NSYPLAT10103G	NSYPLAZT10103G
1000	1000	420	2	NSYPLAT10104G	NSYPLAZT10104G
1000	1250	320	2	NSYPLAT10123G	NSYPLAZT10123G
1000	1250	420	2	NSYPLAT10124G	NSYPLAZT10124G
1250	500	320	1	NSYPLAT1253G	NSYPLAZT1253G
1250	500	420	1	NSYPLAT1254G	NSYPLAZT1254G
1250	750	320	1	NSYPLAT1273G	NSYPLAZT1273G
1250	750	420	1	NSYPLAT1274G	NSYPLAZT1274G
1250	750	620	1	NSYPLAT1276G	NSYPLAZT1276G
1250	1000	320	2	NSYPLAT12103G	NSYPLAZT12103G
1250	1000	420	2	NSYPLAT12104G	NSYPLAZT12104G
1250	1250	320	2	NSYPLAT12123G	NSYPLAZT12123G
1250	1250	420	2	NSYPLAT12124G	NSYPLAZT12124G
1250	1250	620	2	NSYPLAT12126G	NSYPLAZT12126G
1500	500	320	1	NSYPLAT1553G	NSYPLAZT1553G
1500	500	420	1	NSYPLAT1554G	NSYPLAZT1554G
1500	750	320	1	NSYPLAT1573G	NSYPLAZT1573G
1500	750	420	1	NSYPLAT1574G	NSYPLAZT1574G
1500	750	620	1	NSYPLAT1576G	NSYPLAZT1576G
1500	1000	320	2	NSYPLAT15103G	NSYPLAZT15103G
1500	1000	420	2	NSYPLAT15104G	NSYPLAZT15104G
1500	1250	320	2	NSYPLAT15123G	NSYPLAZT15123G
1500	1250	420	2	NSYPLAT15124G	NSYPLAZT15124G
1500	1250	620	2	NSYPLAT15126G	NSYPLAZT15126G
2000	750	420	2*	NSYPLAT2074G	NSYPLAZT2074G

*Two doors in vertical.

PHD - Applicative and customised solutions:
See the Polyester Heavy Duty offer in the Applicative and customised solutions, page 416.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Polyester floor-standing enclosures

Mounting accessories

			Metallic mounting plates		Insulating mounting plates		Modular distributionchassis		Internal door
									
Dimensions									
Height (mm)	Width (mm)	No. of doors	Plain	Telequick	Polyester	Bakelite			
500	500	1	**NSYPMM55**	**NSYPMR55**	**NSYPMA55**	**NSYPMB55**	-	-	**NSYPAPLA55G**
500	750	1	**NSYPMM75**	**NSYPMR57**	**NSYPMA75**	**NSYPMB75**	-	-	**NSYPAPLA57G**
500	1000	2	**NSYPMM510**	2 x **NSYPMR55**	**NSYPMA510**	**NSYPMB510**	-	-	2 x **NSYPAPLA55G**
500	1250	2	**NSYPMM55** + **NSYPMM75**	**NSYPMR55** + **NSYPMR57**	**NSYPMA55** + **NSYPMA75**	**NSYPMB55** + **NSYPMB75**	-	-	**NSYPAPLA55G** + **NSYPAPLA57G**
750	500	1	**NSYPMM75**	**NSYPMR75**	**NSYPMA75**	**NSYPMB75**	**NSYDLP76G**	**NSYDLP57G**	**NSYPAPLA75G**
750	750	1	**NSYPMM77**	**NSYPMR77**	**NSYPMA77**	**NSYPMB77**	**NSYDLP132G**	**NSYDLP99G**	**NSYPAPLA77G**
750	1000	2	**NSYPMM710**	2 x **NSYPMR75**	**NSYPMA710**	**NSYPMB710**	2 x **NSYDLP76G**	2 x **NSYDLP57G**	2 x **NSYPAPLA75G**
750	1250	2	**NSYPMM712**	**NSYPMR75** + **NSYPMR77**	**NSYPMA712**	**NSYPMB712**	**NSYDLP76G** + **NSYDLP132G**	**NSYDLP57G** + **NSYDLP99G**	**NSYPAPLA75G** + **NSYPAPLA77G**
1000	500	1	**NSYPMM105**	**NSYPMR105**	**NSYPMA105**	**NSYPMB105**	**NSYDLP114G**	**NSYDLP95G**	**NSYPAPLA105G**
1000	750	1	**NSYPMM107**	**NSYPMR107**	**NSYPMA107**	**NSYPMB107**	**NSYDLP198G**	**NSYDLP165G**	**NSYPAPLA107G**
1000	1000	2	**NSYPMM1010**	2 x **NSYPMR105**	**NSYPMA1010**	**NSYPMB1010**	2 x **NSYDLP114G**	2 x **NSYDLP95G**	2 x **NSYPAPLA105G**
1000	1250	2	**NSYPMM1012**	**NSYPMR105** + **NSYPMR107**	**NSYPMA1012**	**NSYPMB1012**	**NSYDLP114G** + **NSYDLP198G**	**NSYDLP95G** + **NSYDLP165G**	**NSYPAPLA105G** + **NSYPAPLA107G**
1250	500	1	**NSYPMM125**	**NSYPMR125**	**NSYPMA125**	**NSYPMB125**	**NSYDLP133G**	**NSYDLP114PG**	**NSYPAPLA125G**
1250	750	1	**NSYPMM127**	**NSYPMR127**	**NSYPMA127**	**NSYPMB127**	**NSYDLP231G**	**NSYDLP198PG**	**NSYPAPLA127G**
1250	1000	2	**NSYPMM1210**	2 x **NSYPMR125**	**NSYPMA1210**	**NSYPMB1210**	2 x **NSYDLP133G**	2 x **NSYDLP114PG**	2 x **NSYPAPLA125G**
1250	1250	2	**NSYPMM1212**	**NSYPMR125** + **NSYPMR127**	**NSYPMA1212**	**NSYPMB1212**	**NSYDLP133G** + **NSYDLP231G**	**NSYDLP114PG** + **NSYDLP198PG**	**NSYPAPLA125G** + **NSYPAPLA127G**
1500	500	1	**NSYPMM155**	**NSYPMR155**	-	**NSYPMB155**	**NSYDLP171G**	**NSYDLP152G**	**NSYPAPLA155G**
1500	750	1	**NSYPMM157**	**NSYPMR157**	-	**NSYPMB157**	**NSYDLP297G**	**NSYDLP264G**	**NSYPAPLA157G**
1500	1000	2	**NSYPMM1510**	2 x **NSYPMR155**	-	**NSYPMB1510**	2 x **NSYDLP171G**	2 x **NSYDLP152G**	2 x **NSYPAPLA155G**
1500	1250	2	**NSYPMM1512**	**NSYPMR155** + **NSYPMR157**	-	**NSYPMB1512**	**NSYDLP171G** + **NSYDLP297G**	**NSYDLP152G** + **NSYDLP264G**	**NSYPAPLA155G** + **NSYPAPLA157G**
2000	750	2	**NSYPMM207**	2 x **NSYPMR107**	2 x **NSYPMA107**	2 x **NSYPMB107**	-	-	-
Details			**see page 220**		**see page 220**		**see page 222**		**see page 216**

Step slides: **Page 224**
Uprights and mounting rails: **Page 250**
Door retainer: **Page 216**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Polyester floor-standing enclosures

Composition accessories

		N plinth	H plinth	ZA plinth	ZZ plinth		Floor-fixing frame	Canopy	Cable entry plate
Dimensions									
Width (mm)	Depth (mm)	Height 60 mm	Height 900 mm	Height 200 mm	Height 200 mm	Height 500 mm			
500	320	**NSYZNPLA53G**	**NSYZHPLA53G**	**NSYZA253G**	**NSYZZ253G**	**NSYZZ553G**	**NSYMFPLAZ53**	**NSYTJPLA53G**	**NSYECPLAZ53G**
500	420	**NSYZNPLA54G**	**NSYZHPLA54G**	**NSYZA254G**	**NSYZZ254G**	**NSYZZ554G**	**NSYMFPLAZ54**	**NSYTJPLA54G**	**NSYECPLAZ54G**
500	320	**NSYZNPLA73G**	**NSYZHPLA73G**	**NSYZA273G**	**NSYZZ273G**	**NSYZZ573G**	**NSYMFPLAZ73**	**NSYTJPLA73G**	**NSYECPLAZ73G**
500	420	**NSYZNPLA74G**	**NSYZHPLA74G**	**NSYZA274G**	**NSYZZ274G**	**NSYZZ574G**	**NSYMFPLAZ74**	**NSYTJPLA74G**	**NSYECPLAZ74G**
750	620	-	-	**NSYZA276G**	**NSYZZ276G**	-	**NSYMFPLAZ76**	**NSYTJPLA76G**	**NSYECPLAZ76G**
750	320	**NSYZNPLA103G**	**NSYZHPLA103G**	**NSYZA2103G**	**NSYZZ2103G**	**NSYZZ5103G**	**NSYMFPLAZ103**	**NSYTJPLA103G**	**NSYECPLAZ103G**
750	420	**NSYZNPLA104G**	**NSYZHPLA104G**	**NSYZA2104G**	**NSYZZ2104G**	**NSYZZ5104G**	**NSYMFPLAZ104**	**NSYTJPLA104G**	**NSYECPLAZ104G**
750	320	**NSYZNPLA123G**	**NSYZHPLA123G**	**NSYZA2123G**	**NSYZZ2123G**	**NSYZZ5123G**	**NSYMFPLAZ123**	**NSYTJPLA123G**	**NSYECPLAZ123G**
1000	420	**NSYZNPLA124G**	**NSYZHPLA124G**	**NSYZA2124G**	**NSYZZ2124G**	**NSYZZ5124G**	**NSYMFPLAZ124**	**NSYTJPLA124G**	**NSYECPLAZ124G**
1000	620	-	-	**NSYZA2126G**	**NSYZZ2126G**	-	**NSYMFPLAZ126**	**NSYTJPLA126G**	**NSYECPLAZ126G**
Details		**see page 213**	**see page 215**	**see page 212**	**see page 214**		**see page 215**	**see page 211**	**see page 211**

VDI accessories

		19" fixed chassis		19" swing chassis	
Dimensions					
Height (mm)	Width (mm)	Number of U	References	Number of U	References
500	750	8	**NSYBRF8PLAG**	7	**NSYBRP7PLAG**
750	750	12	**NSYBRF12PLAG** + **NSYSPLA75**	11	**NSYBRP11PLAG** + **NSYSPLA75**
1000	750	17	**NSYBRF17PLAG** + **NSYSPLA100**	16	**NSYBRP16PLAG** + **NSYSPLA100**
1250	750	21	**NSYBRF21PLAG** + **NSYSPLA125**	20	**NSYBRP20PLAG** + **NSYSPLA125**
1500	750	26	**NSYBRF26PLAG** + **NSYSPLA150***	25	**NSYBRP25PLAG** + **NSYSPLA150***
2000	750	2 x 17	2 x **NSYBRF17PLAG** + 2 x **NSYSPLA100** + **NSYPTZ4**	2 x 16	2 x **NSYBRP16PLAG** + 2 x **NSYSPLA100**
Details		**see page 219**		**see page 219**	

* not compatible with NSYCAAPVHD

Door switch: Page 216
Insert: Page 225
Document pocket: Page 300

VDI accessories and fixings: Page 269
Coupling Kit: Page 210
Anti graffiti paint: Page 211

Handles and inserts: Page 217
Wall fixing lug: Page 211

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Spacial SDB metallic junction boxes

Steel industrial boxes

Life Is On Schneider Electric

Steel industrial boxes

Spacial SDB

Metallic junction boxes 32

Spacial SBM

Introduction 34
Characteristics 35
Spacial SBM overview 36
Fixing accessories 38

Characteristics

Dimensions 41

Metallic junction boxes

Metallic junction boxes

- PVC sealing gasket on sizes up to 20/15 and a rubber gasket for > 25/20.
- Back ready for threaded drill holes for fixing equipment. From size 15/10 and up, there are four M4 threaded holes fitted with removable plugs for direct fixing of the mounting plate.
- With low cover.
- The SDB series consists of 2 basic models:
- without knock-outs: **NSYDB●●●**
- with knock-outs: **NSYDB●●●M**
- Material: Sheet steel
- Finish: Structured finish, epoxy polyester powder
- Colour: RAL 7035 grey
- Ingress protection rating: IP55 according to IEC 60529
- Mechanical protection rating: IK07 according to IEC 62262
- Installation: Indoor installation: Direct wall-mounting by means of drill holes fitted with plastic plugs to ensure sealing Outdoor installation: compliant with IEC 62208 regarding type tests specified in §9.12 (resistance to ultra-violet (UV) radiation) and §9.13 (resistance to corrosion).

Group n° 1



Group n° 2



NSYDBN●●●



NSYDB●●●M



Low cover models without knock-outs

NSYDBN1510

External dimensions (mm)			Dimensions (mm)				Weight	References
Height (A)	Width (B)	Depth (C)	D	E	F		(kg)	
85	85	49	58	58	-		0.18	**NSYDBN88**
105	105	49	76	76	-		0.25	**NSYDBN1010**
155	105	61	124	74	56		0.38	**NSYDBN1510**
206	156	83	172	122	78		1.00	**NSYDBN2015**
256	206	93	220	170	88		1.5	**NSYDBN2520**
307	257	116	268	218	110		3.3	**NSYDBN3025**

Low cover models with knock-outs

NSYDB2015M

External dimensions (mm)			Dimensions (mm)			Knock-outs		Weight	References
Height (A)	Width (B)	Depth (C)	D	E	F	Height (A)	Width (B)	(kg)	
85	85	49	58	58	-	1 n° 1	1 n° 1	0.18	**NSYDB88M**
105	105	49	76	76	-	2 n° 1	1 n° 1	0.25	**NSYDB1010M**
155	105	61	124	74	56	3 n° 1	1 n° 1	0.38	**NSYDB1510M**
206	156	83	172	122	78	3 n° 2	2 n° 2	1.00	**NSYDB2015M**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Metallic junction boxes

Plain mounting plates for SDB junction boxes

for models without knock-outs	for models with knock-outs	References
NSYDBN1510	NSYDB1510M	**NSYPMD1510**
NSYDBN2015	NSYDB2015M	**NSYPMD2015**
NSYDBN2520	NSYDB2520M	**NSYPMD2520**
NSYDBN3025	NSYDB3025M	**NSYPMD3025**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Steel industrial boxes

Simplicity, ergonomics and versatility, it's all in the box.

This range can be configured according to your needs

4 differents services available:

Assemble to order

Mounting of standard accessories

Painting

Machining

Modularity

- 28 sizes available.



Easy installation

- Direct mounting though the rear.
- Mounting with versatile external lugs.

Added value to your work

- Quality and aesthetics.

Sturdy and good ingress protection

- Mechanical protection rating up to IK10.
- Ingress protection rating up to IP66.

Ergonomics

- Cover opening and accessory mounting with just a screwdriver.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Characteristics	Spacial SBM - Flat box with plain cover
Box body	Single-piece body (cross-shaped structure). Front design incorporating folded gutters. Flat rear. 2 (or 3 profiles for width 800 mm) drilled profiles for installing mounting plates and DIN rails, with mounting centres of 12.5 mm.
Box cover	Equipped with 4 or 6 half-turn thread screws, according to the version (6 screws for width greater than 400 mm) to ensure maximum watertightness. Polyurethane sealing gasket.
Protection of personnel	Ground connection mandatory for all boxes: Spacial SBM steel boxes are equipped with a M6 x 16 ground stud welded in the cover, to be linked with the body for equipotential connection. Grounding strap to be ordered separately (Ø 6.4 mm terminal).
Material	Sheet steel
Finish	Structured finish, epoxy polyester powder
Colour	RAL 7035 grey
Ingress protection rating	• IP66 according to IEC 60529 • Type 4, 4X according to UL 50, 50E
Mechanical protection rating	IK10 according to IEC 62262
Standard	Compliance with enclosure standard IEC 62208 and the RoHS directive
Certifications (see page 624)	• UL, BV, DNV, LR, GL • Fire class: M0 (EN 13501-1)
Indoor installation	Direct wall-mounting (4 x Ø 10 mm holes) or with the help of mounting lugs installed from the outside (to be ordered separately, see the specific accessory pages).
Maximum load	Loading capacity on the body: 50 kg/m²
Vibration constraints	Specific construction of the Spacial SBM - Single-piece body (rectangular structure). The rear is flat without added parts - this ensures compliance with certain vibration constraints.
Seismic constraint	The seismic behavior of the the industrial boxes Spacial SBM have been qualified according to MRI spectra "big material" specified in the standard IEC 60068-2-6 and IEC 60068-2-57 (see page 430 for more details). Tested enclosure configuration: • Plain door, • Plain mounting plate with a load of 200 kg/m² uniformly distributed on the mounting plate, • Fixing to the wall with M8 screws (tightening torque: 12 Nm ± 1 Nm). Level of the seismic behavior obtained: • 1G for boxes with the following dimensions: - height = 400 mm and width ≥ 500 mm - height = 300 mm and width ≥ 600 mm - height = 200 mm and width = 800 mm • 3G for other dimension

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Steel industrial boxes

SBM

Standard Bus box phased out

Dimensions (mm)			Cover screws Bus Boxes phased out divide by 2	Flat box	Mounting plate without screws	DIN rail 10 rails, supplied without screws	Post mounting
Height	Width	Depth					
150	150	80	4	**NSYSBM15158**	**NSYMM11SB**	**NSYAMRD15357SB**	**NSYSFPSC15**
150	150	120	4	**NSYSBM151512**	**NSYMM11SB**	**NSYAMRD15357SB**	**NSYSFPSC15**
150	200	80	4	**NSYSBM15208**	**NSYMM12SB**	**NSYAMRD20357SB**	**NSYSFPSC20**
150	200	120	4	**NSYSBM152012**	**NSYMM12SB**	**NSYAMRD20357SB**	**NSYSFPSC20**
150	300	80	4	**NSYSBM15308**	**NSYMM13SB**	**NSYAMRD30357SB**	**NSYSFPSC30**
150	300	120	4	**NSYSBM153012**	**NSYMM13SB**	**NSYAMRD30357SB**	**NSYSFPSC30**
150	400	80	4	**NSYSBM15408**	**NSYMM14SB**	**NSYAMRD40357SB**	**NSYSFPSC40**
150	400	120	4	**NSYSBM154012**	**NSYMM14SB**	**NSYAMRD40357SB**	**NSYSFPSC40**
200	200	80	4	**NSYSBM20208**	**NSYMM22SB**	**NSYAMRD20357SB**	**NSYSFPSC20**
200	200	120	4	**NSYSBM202012**	**NSYMM22SB**	**NSYAMRD20357SB**	**NSYSFPSC20**
200	300	80	4	**NSYSBM20308**	**NSYMM23SB**	**NSYAMRD30357SB**	**NSYSFPSC30**
200	300	120	4	**NSYSBM203012**	**NSYMM23SB**	**NSYAMRD30357SB**	**NSYSFPSC30**
200	400	80	4	**NSYSBM20408**	**NSYMM24SB**	**NSYAMRD40357SB**	**NSYSFPSC40**
200	400	120	4	**NSYSBM204012**	**NSYMM24SB**	**NSYAMRD40357SB**	**NSYSFPSC40**
200	500	80	6	**NSYSBM20508**	**NSYMM25SB**	**NSYAMRD50357SB**	**NSYSFPSC50**
200	500	120	6	**NSYSBM205012**	**NSYMM25SB**	**NSYAMRD50357SB**	**NSYSFPSC50**
200	600	80	6	**NSYSBM20608**	**NSYMM26SB**	**NSYAMRD60357SB**	**NSYSFPSC60**
200	600	120	6	**NSYSBM206012**	**NSYMM26SB**	**NSYAMRD60357SB**	**NSYSFPSC60**
200	800	120	6	**NSYSBM208012**	**NSYMM28SB**	**NSYAMRD80357SB**	**NSYSFPSC80**
300	300	120	4	**NSYSBM303012**	**NSYMM33SB**	**NSYAMRD30357SB**	**NSYSFPSC30**
300	400	120	4	**NSYSBM304012**	**NSYMM34SB**	**NSYAMRD40357SB**	**NSYSFPSC40**
300	500	120	6	**NSYSBM305012**	**NSYMM35SB**	**NSYAMRD50357SB**	**NSYSFPSC50**
300	600	120	6	**NSYSBM306012**	**NSYMM36SB**	**NSYAMRD60357SB**	**NSYSFPSC60**
300	800	120	6	**NSYSBM308012**	**NSYMM38SB**	**NSYAMRD80357SB**	**NSYSFPSC80**
400	400	120	4	**NSYSBM404012**	**NSYMM44SB**	**NSYAMRD40357SB**	**NSYSFPSC40**
400	500	120	6	**NSYSBM405012**	**NSYMM45SB**	**NSYAMRD50357SB**	**NSYSFPSC50**
400	600	120	6	**NSYSBM406012**	**NSYMM46SB**	**NSYAMRD60357SB**	**NSYSFPSC60**
400	800	120	6	**NSYSBM408012**	**NSYMM48SB**	**NSYAMRD80357SB**	**NSYSFPSC80**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

				Head screws		
	1 gasket and necessary hardware					
	Mounting lugs	Self-tapping screws	Hinges	Double bar shaped head screw	Triangle shaped head screw	Sealing kit
	NSYAEFPFSB	NSYAMFSB	NSYAEDHSB	NSYAEDSBSB	NSYAEDSTSB	NSYPPSB
	NSYAEFPFSB	NSYAMFSB	NSYAEDHSB	NSYAEDSBSB	NSYAEDSTSB	NSYPPSB
	NSYAEFPFSB	NSYAMFSB	NSYAEDHSB	NSYAEDSBSB	NSYAEDSTSB	NSYPPSB
	NSYAEFPFSB	NSYAMFSB	NSYAEDHSB	NSYAEDSBSB	NSYAEDSTSB	NSYPPSB
	NSYAEFPFSB	NSYAMFSB	NSYAEDHSB	NSYAEDSBSB	NSYAEDSTSB	NSYPPSB
	NSYAEFPFSB	NSYAMFSB	NSYAEDHSB	NSYAEDSBSB	NSYAEDSTSB	NSYPPSB
	NSYAEFPFSB	NSYAMFSB	NSYAEDHSB	NSYAEDSBSB	NSYAEDSTSB	NSYPPSB
	NSYAEFPFSB	NSYAMFSB	NSYAEDHSB	NSYAEDSBSB	NSYAEDSTSB	NSYPPSB
	NSYAEFPFSB	NSYAMFSB	NSYAEDHSB	NSYAEDSBSB	NSYAEDSTSB	NSYPPSB
	NSYAEFPFSB	NSYAMFSB	NSYAEDHSB	NSYAEDSBSB	NSYAEDSTSB	NSYPPSB
	NSYAEFPFSB	NSYAMFSB	NSYAEDHSB	NSYAEDSBSB	NSYAEDSTSB	NSYPPSB
	NSYAEFPFSB	NSYAMFSB	NSYAEDHSB	NSYAEDSBSB	NSYAEDSTSB	NSYPPSB
	NSYAEFPFSB	NSYAMFSB	NSYAEDHSB	NSYAEDSBSB	NSYAEDSTSB	NSYPPSB
	NSYAEFPFSB	NSYAMFSB	NSYAEDHSB	NSYAEDSBSB	NSYAEDSTSB	NSYPPSB
	NSYAEFPFSB	NSYAMFSB	NSYAEDHSB	NSYAEDSBSB	NSYAEDSTSB	NSYPPSB
	NSYAEFPFSB	NSYAMFSB	NSYAEDHSB	NSYAEDSBSB	NSYAEDSTSB	NSYPPSB
	NSYAEFPFSB	NSYAMFSB	NSYAEDHSB	NSYAEDSBSB	NSYAEDSTSB	NSYPPSB
	NSYAEFPFSB	NSYAMFSB	NSYAEDHSB	NSYAEDSBSB	NSYAEDSTSB	NSYPPSB
	NSYAEFPFSB	NSYAMFSB	NSYAEDHSB	NSYAEDSBSB	NSYAEDSTSB	NSYPPSB
	NSYAEFPFSB	NSYAMFSB	NSYAEDHSB	NSYAEDSBSB	NSYAEDSTSB	NSYPPSB
	NSYAEFPFSB	NSYAMFSB	NSYAEDHSB	NSYAEDSBSB	NSYAEDSTSB	NSYPPSB
	NSYAEFPFSB	NSYAMFSB	NSYAEDHSB	NSYAEDSBSB	NSYAEDSTSB	NSYPPSB
	NSYAEFPFSB	NSYAMFSB	NSYAEDHSB	NSYAEDSBSB	NSYAEDSTSB	NSYPPSB
	NSYAEFPFSB	NSYAMFSB	NSYAEDHSB	NSYAEDSBSB	NSYAEDSTSB	NSYPPSB
	NSYAEFPFSB	NSYAMFSB	NSYAEDHSB	NSYAEDSBSB	NSYAEDSTSB	NSYPPSB
	NSYAEFPFSB	NSYAMFSB	NSYAEDHSB	NSYAEDSBSB	NSYAEDSTSB	NSYPPSB
	NSYAEFPFSB	NSYAMFSB	NSYAEDHSB	NSYAEDSBSB	NSYAEDSTSB	NSYPPSB

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Steel industrial boxes

Flat boxes (SBM)

NSYSBM15158

Characteristics	Height (mm)	Width (mm)	Depth (mm)	Power dissipation	Sheet thickness	References
Flat box IP66 IK10 RAL 7035, 4 screws f. cover	150	150	80	13.5	10/10e	**NSYSBM15158**
Flat box IP66 IK10 RAL 7035, 4 screws f. cover	150	150	120	17.2	10/10e	**NSYSBM151512**
Flat box IP66 IK10 RAL 7035, 4 screws f. cover	150	200	80	16.6	10/10e	**NSYSBM15208**
Flat box IP66 IK10 RAL 7035, 4 screws f. cover	150	200	120	20.8	10/10e	**NSYSBM152012**
Flat box IP66 IK10 RAL 7035, 4 screws f. cover	150	300	80	22.8	10/10e	**NSYSBM15308**
Flat box IP66 IK10 RAL 7035, 4 screws f. cover	150	300	120	28.1	10/10e	**NSYSBM153012**
Flat box IP66 IK10 RAL 7035, 4 screws f. cover	150	400	80	29.0	10/10e	**NSYSBM15408**
Flat box IP66 IK10 RAL 7035, 4 screws f. cover	150	400	120	35.3	10/10e	**NSYSBM154012**
Flat box IP66 IK10 RAL 7035, 4 screws f. cover	200	200	80	20.6	10/10e	**NSYSBM20208**
Flat box IP66 IK10 RAL 7035, 4 screws f. cover	200	200	120	25.6	10/10e	**NSYSBM202012**
Flat box IP66 IK10 RAL 7035, 4 screws f. cover	200	300	80	28.2	10/10e	**NSYSBM20308**
Flat box IP66 IK10 RAL 7035, 4 screws f. cover	200	300	120	34.2	10/10e	**NSYSBM203012**
Flat box IP66 IK10 RAL 7035, 4 screws f. cover	200	400	80	35.7	10/10e	**NSYSBM20408**
Flat box IP66 IK10 RAL 7035, 4 screws f. cover	200	400	120	42.8	10/10e	**NSYSBM204012**
Flat box IP66 IK10 RAL 7035, 6 screws f. cover	200	500	80	43.3	12/10e	**NSYSBM20508**
Flat box IP66 IK10 RAL 7035, 6 screws f. cover	200	500	120	51.4	12/10e	**NSYSBM205012**
Flat box IP66 IK10 RAL 7035, 6 screws f. cover	200	600	80	50.8	12/10e	**NSYSBM20608**
Flat box IP66 IK10 RAL 7035, 6 screws f. cover	200	600	120	60.1	12/10e	**NSYSBM206012**
Flat box IP66 IK10 RAL 7035, 6 screws f. cover	200	800	120	77.3	12/10e	**NSYSBM208012**
Flat box IP66 IK10 RAL 7035, 4 screws f. cover	300	300	120	46.4	10/10e	**NSYSBM303012**
Flat box IP66 IK10 RAL 7035, 4 screws f. cover	300	400	120	57.8	10/10e	**NSYSBM304012**
Flat box IP66 IK10 RAL 7035, 6 screws f. cover	300	500	120	69.1	12/10e	**NSYSBM305012**
Flat box IP66 IK10 RAL 7035, 6 screws f. cover	300	600	120	80.4	12/10e	**NSYSBM306012**
Flat box IP66 IK10 RAL 7035, 6 screws f. cover	300	800	120	103.0	12/10e	**NSYSBM308012**
Flat box IP66 IK10 RAL 7035, 4 screws f. cover	400	400	120	72.7	10/10e	**NSYSBM404012**
Flat box IP66 IK10 RAL 7035, 6 screws f. cover	400	500	120	86.7	12/10e	**NSYSBM405012**
Flat box IP66 IK10 RAL 7035, 6 screws f. cover	400	600	120	100.7	12/10e	**NSYSBM406012**
Flat box IP66 IK10 RAL 7035, 6 screws f. cover	400	800	120	128.7	12/10e	**NSYSBM408012**

Mounting plate

- Material: Galvanised steel
- Installation: Mounting by means of 2* or 4 x Ø 5 mm self-tapping screws, Pozidriv head, ref. **NSYAMFSB**.
  Attachment points compatible with many other brands of accessories

Supply:
1 unit, supplied without screws

NSYMM11SB

Characteristics	Height (mm)	Width (mm)	References
Mounting plate	125	135	**NSYMM11SB**
Mounting plate	125	185	**NSYMM12SB**
Mounting plate	125	285	**NSYMM13SB**
Mounting plate	125	385	**NSYMM14SB**
Mounting plate	175	185	**NSYMM22SB**
Mounting plate	175	265	**NSYMM23SB**
Mounting plate	175	385	**NSYMM24SB**
Mounting plate	175	485	**NSYMM25SB**
Mounting plate	175	585	**NSYMM26SB**
Mounting plate	175	785	**NSYMM28SB**
Mounting plate	275	285	**NSYMM33SB**
Mounting plate	275	385	**NSYMM34SB**
Mounting plate	275	485	**NSYMM35SB**
Mounting plate	275	585	**NSYMM36SB**
Mounting plate	275	785	**NSYMM38SB**
Mounting plate	375	385	**NSYMM44SB**
Mounting plate	375	485	**NSYMM45SB**
Mounting plate	375	585	**NSYMM46SB**
Mounting plate	375	785	**NSYMM48SB**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Steel industrial boxes

Symmetrical DIN rails 35 x 7.5 mm

- Material: Galvanised steel
- Installation: Mounting by means of 2 x Ø 5 mm self-tapping screws, Pozidriv head, ref. **NSYAMFSB**
- All boxes are delivered with 5 x Ø 5 mm self-tapping screws.

Supply:
10 rails, supplied without screws

NSYAMRD15357SB

Characteristics	Height (mm)	Width (mm)	References
Symmetrical DIN rail	35	150	**NSYAMRD15357SB**
Symmetrical DIN rail	35	200	**NSYAMRD20357SB**
Symmetrical DIN rail	35	300	**NSYAMRD30357SB**
Symmetrical DIN rail	35	400	**NSYAMRD40357SB**
Symmetrical DIN rail	35	200	**NSYAMRD20357SB**
Symmetrical DIN rail	35	300	**NSYAMRD30357SB**
Symmetrical DIN rail	35	400	**NSYAMRD40357SB**
Symmetrical DIN rail	35	500	**NSYAMRD50357SB**
Symmetrical DIN rail	35	600	**NSYAMRD60357SB**
Symmetrical DIN rail	35	800	**NSYAMRD80357SB**
Symmetrical DIN rail	35	300	**NSYAMRD30357SB**
Symmetrical DIN rail	35	400	**NSYAMRD40357SB**
Symmetrical DIN rail	35	500	**NSYAMRD50357SB**
Symmetrical DIN rail	35	600	**NSYAMRD60357SB**
Symmetrical DIN rail	35	800	**NSYAMRD80357SB**
Symmetrical DIN rail	35	400	**NSYAMRD40357SB**
Symmetrical DIN rail	35	500	**NSYAMRD50357SB**
Symmetrical DIN rail	35	600	**NSYAMRD60357SB**
Symmetrical DIN rail	35	800	**NSYAMRD80357SB**

Post mounting

- Material: Zinc plated steel
- Rail mounted externally to the rear of the box with 8 mm screws for installation on posts with diameters between 150 mm and 215 mm.
- For steel boxes with widths of 150, 200, 300, 400, 500, 600 and 800 mm.
- Maximum load: 100 kg

Supply:
1 unit

NSYSFPSC15

Characteristics	Height (mm)	Width (mm)	References
Post mounting	45	150	**NSYSFPSC15**
Post mounting	45	200	**NSYSFPSC20**
Post mounting	45	300	**NSYSFPSC30**
Post mounting	45	400	**NSYSFPSC40**
Post mounting	45	500	**NSYSFPSC50**
Post mounting	45	600	**NSYSFPSC60**
Post mounting	45	800	**NSYSFPSC80**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Steel industrial boxes

Mounting lugs

- Wall-mounting lugs to be mounted directly on the rear of the box, either in horizontal or vertical position. Their versatile design complies with the mounting dimensions of many other enclosures.
- Ingress protection rating: IP66 according to IEC 60529
- Installation: Horizontal or vertical position, distance between wall and enclosure: 10 mm, only requires a screw driver
- Maximum load: 70 kg

Supply:
4 wall-mounting lugs, screws and pre-mounted sealing gaskets

NSYAEFPFSB

Characteristics	References
wall-mounting lugs	**NSYAEFPFSB**

Self-tapping screws

- Same reference for all enclosure dimensions
- Self-tapping, Pozidriv head, screws, for Ø 5 mm holes.

Supply:
100 units

NSYAMFSB

Characteristics	References
Self-tapping screws	**NSYAMFSB**

Hinges

- The hinges allow the cover to be opened by more than 180°.
- They can be installed on all covers of the range.
- Ingress protection rating: IP66 according to IEC 60529

Installation:

- The box must be drilled before installing the 2 or 3 hinges on the body.
- 3 hinges are required for boxes of width more than 500 mm
- A specific mark on the body helps to locate where the hole should be drilled
- Maximum load: 30 kg/m² on the hinged cover
- Same reference for all enclosure dimensions

Supply:
Set of 6 hinges delivers with fixing hardware

NSYAEDHSB

Characteristics	References
Hinges SBM	**NSYAEDHSB**

Head screws

- The standard Pozidriv head screws can be replaced with the Double bar or Triangle shaped head screws, to discourage unauthorised opening of the cover with normal screwdrivers.
- Ingress protection rating: IP66 according to IEC 60529
- Installation: Simply replace the standard screw on the box
- Same reference for all enclosure dimensions

Supply:
20 units

NSYAEDSBSB NSYAEDSTSB

Characteristics	References
Double bar shaped head 3 mm screw	**NSYAEDSBSB**
Triangle shaped head 6.5 mm screw	**NSYAEDSTSB**

Sealing kit

- The sealing kit helps to set up a lead-sealed wire of cover opening.
- Colour: Green
- Ingress protection rating: IP66 according to IEC 60529
- Installation: Replaces the standard sealing washer on the box
- Same reference for all enclosure dimensions

Supply:
1 unit

NSYPPSB

Characteristics	References
Sealing kit SBM	**NSYPPSB**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Steel industrial boxes

Section A-A



Section B-B



External mounting of the box and mounting accessories

Box		Mounting								
Height	Width	Ah	Bh	Bw	C	D	E	F	G	H
150 mm	150 mm	20.5 mm	109 mm	109 mm	125 mm	-	12.5 mm	85 mm	85 mm	-
	200 mm	20.5 mm	109 mm	159 mm	175 mm	-	12.5 mm	85 mm	135 mm	-
	300 mm	20.5 mm	109 mm	259 mm	275 mm	-	12.5 mm	85 mm	235 mm	-
	400 mm	20.5 mm	109 mm	359 mm	375 mm	-	12.5 mm	85 mm	335 mm	-
200 mm	200 mm	20.5 mm	159 mm	159 mm	175 mm	-	12.5 mm	135 mm	135 mm	-
	300 mm	20.5 mm	159 mm	259 mm	275 mm	-	12.5 mm	135 mm	235 mm	-
	400 mm	20.5 mm	159 mm	359 mm	375 mm	-	12.5 mm	135 mm	335 mm	-
	500 mm	20.5 mm	159 mm	459 mm	475 mm	-	12.5 mm	135 mm	435 mm	200 mm
	600 mm	20.5 mm	159 mm	559 mm	575 mm	-	12.5 mm	135 mm	535 mm	250 mm
	800 mm	20.5 mm	159 mm	759 mm	775 mm	387.5 mm	12.5 mm	135 mm	735 mm	350 mm
300 mm	300 mm	20.5 mm	259 mm	259 mm	275 mm	-	12.5 mm	235 mm	235 mm	-
	400 mm	20.5 mm	259 mm	359 mm	375 mm	-	12.5 mm	235 mm	335 mm	-
	500 mm	20.5 mm	259 mm	459 mm	475 mm	-	12.5 mm	235 mm	435 mm	200 mm
	600 mm	20.5 mm	259 mm	559 mm	575 mm	-	12.5 mm	235 mm	535 mm	250 mm
	800 mm	20.5 mm	259 mm	759 mm	775 mm	387.5 mm	12.5 mm	235 mm	735 mm	350 mm
400 mm	400 mm	20.5 mm	359 mm	359 mm	375 mm	-	12.5 mm	335 mm	335 mm	-
	500 mm	20.5 mm	359 mm	459 mm	475 mm	-	12.5 mm	335 mm	435 mm	200 mm
	600 mm	20.5 mm	359 mm	559 mm	575 mm	-	12.5 mm	335 mm	535 mm	250 mm
	800 mm	20.5 mm	359 mm	759 mm	775 mm	387.5 mm	12.5 mm	335 mm	735 mm	350 mm

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

You need an enclosure for indoor non-clean industrial environment.

Life Is On Schneider Electric

Steel wall-mounting enclosures

Spacial S3D

Introduction	44
Characteristics	45
Selection guide	46
Fixing accessories	51
Plinth	54
Coupling accessories	55
Protection canopy	56
Handles	57
Locks	58
Accessories	60
Dimensions	72

The steel enclosure with the greatest range of available dimensions on the market!

This range can be configured according to your needs

4 differents services available:

Assemble to order

Mounting of standard accessories

Painting

Machining



Useful life
- Quality of the welding and the painting.

Personnel safety
- Earthing studs welded to the body and door.

Component protection
- Water and dust tightness and impact resistance.
- EMC and ATEX offer.

Added value to your work
- Quality and aesthetics.

Increased choice
- Large range of universal dimensions.
- Application offer with special dimensions.

Easy equipping
- 4 10 mm shouldered welded studs.
- Broad range of mounting plates.
- Broad range of cable gland plates.
- Wire guides welded to the door from the height of 400 mm.

Easy maintenance
- Removable hinges.
- 1 lock system from the height of 600 mm.
- 3-point lock from the height of 600 mm.



Easy handling
- Reusable, eco-friendly packaging.
- No sharp corners.

See page 532 for details or consult our web site www.se.com

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

S3D

Characteristics	Spacial S3D
	Three steel enclosure definitions are available: • Enclosure with plain door. • Enclosure with plain door delivered with a galvanised plain mounting plate, not installed. • Enclosure with glazed door, 4 mm-thick Securit® glass.
Personnel protection	• Earth connection: Spacial S3D steel enclosures are equipped with M6 x 16 earth studs welded in the body and the door for equipotential connection. Earth braid to be ordered separately (see page 305). • Closing the enclosure: The enclosures are equipped from the height of 600 mm with three locking points with linkage, with a single control point, helping prevent the enclosures from being left ajar. Locks and inserts, page 57.
Material	Steel
Finish	Structured finish, epoxy polyester powder
Colour	RAL 7035 grey
Ingress protection rating	IP66 for the single-door enclosures and IP55 for the double door enclosures, according to IEC 60529
Mechanical protection rating	IK10 for the plain-door enclosures and IK08 for the glazed-door enclosures according to IEC 62262
Standards	Compliance with enclosure standards IEC 62208 The Spacial S3D wall-mounting enclosures are compliant with the RoHS directive
Certifications (see page 624)	• UL, CUL, BV, DNV, GL, ATEX (modified enclosure) • NEMA type 4, 4X for the single-door enclosures and NEMA type 12, 13 for the double door enclosures according to NEMA 250 standard. Information on NEMA and UL classification on page 629 and 630 **Nuclear decontamination: RAL 7035 grey and AFNOR A550 tests available on demand.** **More information on coating properties on page 631 and 632** • Seismic behavior: 2.5G or 3G (details page 76)
Fixing	4 (or 6 studs for widths 1000 and 1200 (see page 74 and 75)) M8 x 25 shouldered backstuds for installing mounting plates and step slides, leaving a space of 10 mm behind them.
Supply	**Body** • Single-piece body (cross-shaped structure). Gutter-shaped front profile with double fold. **Flat rear** • M6 x 16 earthing screws for equipotential connection between the door and the body of the enclosure • Cable gland plate with marking for easy drilling and to enable the maximum access surface; Delivered with the enclosure. This plate is flush with the body of the enclosure (detail and other options on page 61) • Direct wall-mounting (4 Ø 10 holes for the sealing plugs for the the IP) or with the help of fixing lugs installed from the outside (to be ordered separately, see page 51) **Door** • Wall-mounting enclosure supplied with 3 mm double bar lock as standard • Polyurethane door gasket • M6 x 16 earthing screws for equipotential connection between the door and the body of the enclosure • Easily removable and reversible, with 20 mm return with double thickness granting excellent rigidity, opening to 120°, equipped with 2 or 3 invisible hinges (from the height of 800 mm) • Door opening to 180° with optional hinges (page 60) • For heights from 600 mm, three locking points with linkage, with a single control point. Simple reversal of linkage. Maximum load: 50 kg/m² • A handle is delivered which provides 2 functions: - Operating key - Tool for loosening the stud protection caps. This handle can be solidly attached to the locking system by means of a captive element • Perforated rails on the door, with drill holes with a diameter of 4.2 mm in steps of 25 mm: - 2 vertical rails from the height of 400 mm - 2 vertical rails and 2 horizontal rails from the width of 800 mm

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

S3D Steel wall-mounting enclosures

- Ingress protection rating: IP66 for the single-door enclosures and IP55 for the double door enclosures, according to IEC 60529
- For other dimensions, see our application offer.
- Enclosure without mounting plate..
- In inverted use of silkscreened mounting plates, the marking is inverted.

Dimensions [1]						Door			Mounting plates		
Height (mm)	Width (mm)	Depth (mm)	Doors	IP	Weight (kg) [2]	Plain without mounting plate	Plain with mounting plate	Glazed without mounting plate	Plain	Silkscreened [3]	Microperforated
300	200	150	1	66	3.02	**NSYS3D3215**	**NSYS3D3215P**	-	**NSYMM32**	-	**NSYMF32**
300	250	150	1	66	3.48	**NSYS3D32515**	**NSYS3D32515P**	**NSYS3D32515T**	**NSYMM3025**	-	-
300	300	150	1	66	3.90	**NSYS3D3315**	**NSYS3D3315P**	**NSYS3D3315T**	**NSYMM33**	-	**NSYMF33**
300	300	200	1	66	4.50	**NSYS3D3320**	**NSYS3D3320P**	**NSYS3D3320T**	**NSYMM33**	-	**NSYMF33**
300	400	150	1	66	4.82	**NSYS3D3415**	**NSYS3D3415P**	**NSYS3D3415T**	**NSYMM43**	**NSYMS43**	**NSYMF43**
300	400	200	1	66	5.60	**NSYS3D3420**	**NSYS3D3420P**	**NSYS3D3420T**	**NSYMM43**	**NSYMS43**	**NSYMF43**
400	300	150	1	66	4.90	**NSYS3D4315**	**NSYS3D4315P**	**NSYS3D4315T**	**NSYMM43**	**NSYMS43**	**NSYMF43**
400	300	200	1	66	5.00	**NSYS3D4320**	**NSYS3D4320P**	**NSYS3D4320T**	**NSYMM43**	**NSYMS43**	**NSYMF43**
400	400	200	1	66	6.50	**NSYS3D4420**	**NSYS3D4420P**	**NSYS3D4420T**	**NSYMM44**	**NSYMS44**	**NSYMF44**
400	600	200	1	66	10.50	**NSYS3D4620**	**NSYS3D4620P**	**NSYS3D4620T**	**NSYMM64**	**NSYMS64**	**NSYMF64**
400	600	250	1	66	12.00	**NSYS3D4625**	**NSYS3D4625P**	**NSYS3D4625T**	**NSYMM64**	**NSYMS64**	**NSYMF64**
500	300	200	1	66	7.50	**NSYS3D5320**	**NSYS3D5320P**	**NSYS3D5320T**	**NSYMM53**	**NSYMS53**	**NSYMF53**
500	400	200	1	66	9.30	**NSYS3D5420**	**NSYS3D5420P**	**NSYS3D5420T**	**NSYMM54**	**NSYMS54**	**NSYMF54**
500	400	250	1	66	10.20	**NSYS3D5425**	**NSYS3D5425P**	**NSYS3D5425T**	**NSYMM54**	**NSYMS54**	**NSYMF54**
500	500	200	1	66	11.18	**NSYS3D5520**	**NSYS3D5520P**	**NSYS3D5520T**	**NSYMM55**	**NSYMS55**	**NSYMF55**
500	500	250	1	66	12.06	**NSYS3D5525**	**NSYS3D5525P**	**NSYS3D5525T**	**NSYMM55**	**NSYMS55**	**NSYMF55**
600	400	200	1	66	11.00	**NSYS3D6420**	**NSYS3D6420P**	**NSYS3D6420T**	**NSYMM64**	**NSYMS64**	**NSYMF64**
600	400	250	1	66	12.00	**NSYS3D6425**	**NSYS3D6425P**	**NSYS3D6425T**	**NSYMM64**	**NSYMS64**	**NSYMF64**
600	500	250	1	66	16.20	**NSYS3D6525**	**NSYS3D6525P**	**NSYS3D6525T**	**NSYMM65**	-	**NSYMF65**
600	600	200	1	66	14.00	**NSYS3D6620**	**NSYS3D6620P**	**NSYS3D6620T**	**NSYMM66**	**NSYMS66**	**NSYMF66**
600	600	250	1	66	15.00	**NSYS3D6625**	**NSYS3D6625P**	**NSYS3D6625T**	**NSYMM66**	**NSYMS66**	**NSYMF66**
600	600	300	1	66	17.00	**NSYS3D6630**	**NSYS3D6630P**	**NSYS3D6630T**	**NSYMM66**	**NSYMS66**	**NSYMF66**
600	600	400	1	66	19.00	**NSYS3D6640**	**NSYS3D6640P**	**NSYS3D6640T**	**NSYMM66**	**NSYMS66**	**NSYMF66**
600	800	300	1	66	25.50	**NSYS3D6830**	**NSYS3D6830P**	**NSYS3D6830T**	**NSYMM86**	**NSYMS86**	**NSYMF86**
700	500	250	1	66	15.00	**NSYS3D7525**	**NSYS3D7525P**	**NSYS3D7525T**	**NSYMM75**	**NSYMS75**	**NSYMF75**
800	600	200	1	66	21.00	**NSYS3D8620**	**NSYS3D8620P**	**NSYS3D8620T**	**NSYMM86**	**NSYMS86**	**NSYMF86**
800	600	250	1	66	23.00	**NSYS3D8625**	**NSYS3D8625P**	**NSYS3D8625T**	**NSYMM86**	**NSYMS86**	**NSYMF86**
800	600	300	1	66	25.00	**NSYS3D8630**	**NSYS3D8630P**	**NSYS3D8630T**	**NSYMM86**	**NSYMS86**	**NSYMF86**
800	600	400	1	66	29.00	**NSYS3D8640**	**NSYS3D8640P**	**NSYS3D8640T**	**NSYMM86**	**NSYMS86**	**NSYMF86**
800	800	250	1	66	30.00	**NSYS3D8825**	**NSYS3D8825P**	**NSYS3D8825T**	**NSYMM88**	-	**NSYMF88**
800	800	300	1	66	32.00	**NSYS3D8830**	**NSYS3D8830P**	**NSYS3D8830T**	**NSYMM88**	-	**NSYMF88**
800	1000	300	1	66	38.00	**NSYS3D81030**	**NSYS3D81030P**	-	**NSYMM108**	-	**NSYMF108**
800	1000	300	2	55	43.50	**NSYS3D81030D**	**NSYS3D81030DP**	-	**NSYMM108**	-	**NSYMF108**
800	1200	300	2	55	46.00	**NSYS3D81230D**	**NSYS3D81230DP**	-	**NSYMM128**	-	**NSYMF128**
1000	600	250	1	66	28.00	**NSYS3D10625**	**NSYS3D10625P**	**NSYS3D10625T**	**NSYMM106**	-	**NSYMF106**
1000	600	300	1	66	30.60	**NSYS3D10630**	**NSYS3D10630P**	**NSYS3D10630T**	**NSYMM106**	-	**NSYMF106**
1000	600	400	1	66	33.00	**NSYS3D10640**	**NSYS3D10640P**	**NSYS3D10640T**	**NSYMM106**	-	**NSYMF106**
1000	800	250	1	66	35.00	**NSYS3D10825**	**NSYS3D10825P**	**NSYS3D10825T**	**NSYMM108**	-	**NSYMF108**
1000	800	300	1	66	38.00	**NSYS3D10830**	**NSYS3D10830P**	**NSYS3D10830T**	**NSYMM108**	-	**NSYMF108**
1000	800	400	1	66	42.00	**NSYS3D10840**	**NSYS3D10840P**	**NSYS3D10840T**	**NSYMM108**	-	**NSYMF108**
1000	1000	300	1	66	46.00	**NSYS3D101030**	**NSYS3D101030P**	**NSYS3D101030T**	**NSYMM1010**	-	**NSYMF1010**
1000	1000	300	2	55	46.00	**NSYS3D101030D**	**NSYS3D101030DP**	**NSYS3D101030DT**	**NSYMM1010**	-	**NSYMF1010**
1000	1200	300	2	55	53.00	**NSYS3D101230D**	**NSYS3D101230DP**	-	**NSYMM1210**	-	**NSYMF1210**
1000	1200	400	2	55	60.00	**NSYS3D101240D**	**NSYS3D101240DP**	-	**NSYMM1210**	-	**NSYMF1210**
1200	600	300	1	66	37.00	**NSYS3D12630**	**NSYS3D12630P**	**NSYS3D12630T**	**NSYMM126**	-	**NSYMF126**
1200	600	400	1	66	42.00	**NSYS3D12640**	**NSYS3D12640P**	**NSYS3D12640T**	**NSYMM126**	-	**NSYMF126**
1200	800	300	1	66	45.00	**NSYS3D12830**	**NSYS3D12830P**	**NSYS3D12830T**	**NSYMM128**	-	**NSYMF128**
1200	800	400	1	66	49.00	**NSYS3D12840**	**NSYS3D12840P**	**NSYS3D12840T**	**NSYMM128**	-	**NSYMF128**
1200	1000	300	1	66	53.00	**NSYS3D121030**	**NSYS3D121030P**	**NSYS3D121030T**	**NSYMM1210**	-	**NSYMF1210**
1200	1000	300	2	55	54.00	**NSYS3D121030D**	**NSYS3D121030DP**	**NSYS3D121030DT**	**NSYMM1210**	-	**NSYMF1210**
1200	1000	400	2	55	61.00	**NSYS3D121040D**	**NSYS3D121040DP**	-	**NSYMM1210**	-	**NSYMF1210**
1200	1200	300	2	55	64.00	**NSYS3D121230D**	**NSYS3D121230DP**	-	**NSYMM1212**	-	2x **NSYMF126** [4]
1200	1200	400	2	55	90.00	**NSYS3D121240D**	**NSYS3D121240DP**	-	**NSYMM1212**	-	2x **NSYMF126** [4]
1400	1000	300	2	55	80.00	**NSYS3D141030D**	**NSYS3D141030DP**	-	**NSYMM1410**	-	-

[1] For other dimensions, see our application offer, page 14.
[2] Enclosure without mounting plate.
[3] In inverted use, the marking is inverted.
[4] Order **NSYCRNGSDR** for double mounting of the mounting plates
[5] Order nuts ref. **NSYAMCSF**. Steel siderail ref. **NSYMDVR12**.
[6] When width ≥ 1000 ref. **NSYEMR** is mandatory (see on page 74).
[7] Possible assembling to ref. **NSYDLM84** or **NSYDLM112**.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

				Modular mounting plate			Cross rails	
								
Telequick	Bakelite	Modules	Modular chassis DLM Steel	Modular chassis DLA Insulated	DIN rail chassis	Typ	Aluminium vertical rails [5]	Door cross rails
NSYMR32	NSYMB32	-	-	-	-	-	NSYMDVR3	-
NSYMR3025	NSYMB3025	-	-	-	-	-	NSYMDVR3	-
NSYMR33	NSYMB33	-	-	-	NSYMD33	B	NSYMDVR3	-
NSYMR33	NSYMB33	-	-	-	NSYMD33	B	NSYMDVR3	-
NSYMR34	NSYMB43	-	-	-	-	-	NSYMDVR3	-
NSYMR34	NSYMB43	-	-	-	-	-	NSYMDVR3	-
NSYMR43	NSYMB43	24	NSYDLM24	-	NSYMD43	B	NSYMDVR4	-
NSYMR43	NSYMB43	24	NSYDLM24	NSYDLA24G	NSYMD43	B	NSYMDVR4	-
NSYMR44	-	-	-	-	-	-	NSYMDVR4	NSYTFPCRN4
NSYMR46	NSYMB64	-	-	-	-	-	NSYMDVR4	NSYTFPCRN6
NSYMR46	NSYMB64	-	-	-	-	-	NSYMDVR4	NSYTFPCRN6
NSYMR53	-	-	-	-	-	-	NSYMDVR5	-
NSYMR54	NSYMB54	48	NSYDLM48	NSYDLA48G	NSYMD54	B	NSYMDVR5	NSYTFPCRN4
NSYMR54	NSYMB54	48	NSYDLM48	-	NSYMD54	B	NSYMDVR5	NSYTFPCRN4
NSYMR55	-	-	-	-	-	-	NSYMDVR5	NSYTFPCRN5
NSYMR55	-	-	-	-	-	-	NSYMDVR5	NSYTFPCRN5
NSYMR64	NSYMB64	48	NSYDLM48P	NSYDLA48PG	NSYMD64	B	NSYMDVR6	NSYTFPCRN4
NSYMR64	NSYMB64	48	NSYDLM48P	NSYDLA48PG	NSYMD64	B	NSYMDVR6	NSYTFPCRN4
NSYMR65	NSYMB65	-	-	-	-	-	NSYMDVR6	-
NSYMR66	-	84	NSYDLM84P	-	NSYMD66	A	NSYMDVR6	NSYTFPCRN6
NSYMR66	-	84	NSYDLM84P	-	NSYMD66	A	NSYMDVR6	NSYTFPCRN6
NSYMR66	-	84	NSYDLM84P	-	NSYMD66	A	NSYMDVR6	NSYTFPCRN6
NSYMR66	-	84	NSYDLM84P	-	NSYMD66	A	NSYMDVR6	NSYTFPCRN6
NSYMR68	NSYMB86	-	-	-	NSYMD86	A	NSYMDVR6	NSYTFPCRN8
NSYMR75	NSYMB75	66	NSYDLM66	NSYDLA66G	NSYMD75	B	NSYMDVR7	NSYTFPCRN5
NSYMR86	NSYMB86	84 [7]	NSYDLM84	NSYDLA84G / NSYDLA112G	NSYMD86	A	NSYMDVR8	NSYTFPCRN6
NSYMR86	NSYMB86	112 [7]	NSYDLM112	NSYDLA84G / NSYDLA112G	NSYMD86	A	NSYMDVR8	NSYTFPCRN6
NSYMR86	NSYMB86	112 [7]	NSYDLM112	NSYDLA84G / NSYDLA112G	NSYMD86	A	NSYMDVR8	NSYTFPCRN6
NSYMR86	NSYMB86	112 [7]	NSYDLM112	NSYDLA84G / NSYDLA112G	NSYMD86	A	NSYMDVR8	NSYTFPCRN6
NSYMR88	-	-	-	-	-	-	NSYMDVR8	NSYTFPCRN8
NSYMR88	-	-	-	-	-	-	NSYMDVR8	NSYTFPCRN8
NSYMR810	NSYMB108	-	-	-	-	-	NSYMDVR8	NSYTFPCRN10
NSYMR810	NSYMB108	-	-	-	-	-	NSYMDVR8	-
2x NSYMR86 (4)	2x NSYMB86 [4]	-	-	-	2x NSYMD86 [4]	A	NSYMDVR8	-
NSYMR106	NSYMB106	168	NSYDLM168	-	-	-	NSYMDVR10	NSYTFPCRN6
NSYMR106	NSYMB106	168	NSYDLM168	-	-	-	NSYMDVR10	NSYTFPCRN6
NSYMR106	NSYMB106	168	NSYDLM168	-	-	-	NSYMDVR10	NSYTFPCRN6
NSYMR108	NSYMB108	234	NSYDLM240	NSYDLA234G	NSYMD108	A	NSYMDVR10	NSYTFPCRN8
NSYMR108	NSYMB108	234	NSYDLM240	NSYDLA234G	NSYMD108	A	NSYMDVR10	NSYTFPCRN8
NSYMR108	NSYMB108	234	NSYDLM240	NSYDLA234G	NSYMD108	A	NSYMDVR10	NSYTFPCRN8
NSYMR1012 [6]	-	-	-	-	-	-	NSYMDVR10	NSYTFPCRN10
NSYMR1012 [6]	-	-	-	-	-	-	NSYMDVR10	-
NSYMR1012 [6]	NSYMB1210	-	-	-	-	-	NSYMDVR10	-
NSYMR1012 [6]	NSYMB1210	-	-	-	-	-	NSYMDVR10	-
-	-	-	-	-	-	-	NSYMDVR12	-
-	-	-	-	-	-	-	NSYMDVR12	-
NSYMR128	-	-	-	-	NSYMD128	A	NSYMDVR12	NSYTFPCRN8
NSYMR128	-	-	-	-	NSYMD128	A	NSYMDVR12	NSYTFPCRN8
NSYMR1210 [6]	NSYMB1210	-	-	-	-	-	NSYMDVR12	NSYTFPCRN10
NSYMR1210 [6]	NSYMB1210	-	-	-	-	-	NSYMDVR12	-
NSYMR1210 [6]	NSYMB1210	-	-	-	-	-	NSYMDVR12	-
2x NSYMR126 [4]	-	-	-	-	-	-	NSYMDVR12	-
2x NSYMR126 [4]	-	-	-	-	-	-	NSYMDVR12	-
NSYMR1410 [6]	-	-	-	-	-	-	-	-

Wall fixing lugs: page 51
Steel: **NSYAEFPFSC**
Stainless steel: **NSYAEFPFXSC**

Reinforcement for heavy loads: page 51
NSYAEFAHLBSC
Locking accessories: page 58

Door accessories: page 300
Clip-on nuts: page 270
Self-tapping screw: **NSYS13M5HS** / page 271

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

S3D Steel wall-mounting enclosures

- Ingress protection rating: IP66 for the single-door enclosures and IP55 for the double door enclosures, according to IEC 60529
- For other dimensions, see our application offer.
- Enclosure without mounting plate..
- In inverted use of silkscreened mounting plates, the marking is inverted.

Electronics and networks, 19'' racks						Cable entry accessories, Cable gland plates				
Dimensions [1]			Fixed	No. of U	Swing	No. of U	Entry type	Standard steel	Aluminium	Steel with cut-out for FL membrane [2]	FlexiCable [6]
Height (mm)	Width (mm)	Depth (mm)									
300	200	150	-	-	-	-	A	NSYTLA	NSYTLAU	-	-
300	250	150	-	-	-	-	A	NSYTLA	NSYTLAU	-	-
300	300	150	-	-	-	-	B	NSYTLB	NSYTLBU	NSYTLBFL	-
300	300	200	-	-	-	-	C	NSYTLC	NSYTLCU	NSYTLCFL	NSYTLCME
300	400	150	-	-	-	-	B	NSYTLB	NSYTLBU	NSYTLBFL	-
300	400	200	-	-	-	-	D	NSYTLD	NSYTLDU	NSYTLDFL	NSYTLDME
400	300	150	-	-	-	-	B	NSYTLB	NSYTLBU	NSYTLBFL	-
400	300	200	-	-	-	-	C	NSYTLC	NSYTLCU	NSYTLCFL	NSYTLCME
400	400	200	-	-	-	-	D	NSYTLD	NSYTLDU	NSYTLDFL	NSYTLDME
400	600	200	NSYVDM8UF	8	NSYVDM7UP	7	F	NSYTLF	NSYTLFU	NSYTLFFL	NSYTLFME
400	600	250	NSYVDM8UF	8	NSYVDM7UP	7	F	NSYTLF	NSYTLFU	NSYTLFFL	NSYTLFME
500	300	200	-	-	-	-	C	NSYTLC	NSYTLCU	NSYTLCFL	NSYTLCME
500	400	200	-	-	-	-	D	NSYTLD	NSYTLDU	NSYTLDFL	NSYTLDME
500	400	250	-	-	-	-	D	NSYTLD	NSYTLDU	NSYTLDFL	NSYTLDME
500	500	200	-	-	-	-	E	NSYTLE	NSYTLEU	NSYTLEFL	NSYTLEME
500	500	250	-	-	-	-	E	NSYTLE	NSYTLEU	NSYTLEFL	NSYTLEME
600	400	200	-	-	-	-	D	NSYTLD	NSYTLDU	NSYTLDFL	NSYTLDME
600	400	250	-	-	-	-	D	NSYTLD	NSYTLDU	NSYTLDFL	NSYTLDME
600	500	250	-	-	-	-	E	NSYTLE	NSYTLEU	NSYTLEFL	NSYTLEME
600	600	200	NSYVDM12UF	12	NSYVDM11UP	11	F	NSYTLF	NSYTLFU	NSYTLFFL	NSYTLFME
600	600	250	NSYVDM12UF	12	NSYVDM11UP	11	F	NSYTLF	NSYTLFU	NSYTLFFL	NSYTLFME
600	600	300	NSYVDM12UF	12	NSYVDM11UP	11	G	NSYTLG	NSYTLGU	NSYTLG2FL (5)	NSYTLGME
600	600	400	NSYVDM12UF	12	NSYVDM11UP	11	G	NSYTLG	NSYTLGU	NSYTLG2FL (5)	NSYTLGME
600	800	300	-	-	-	-	D [4]	NSYTLD	NSYTLDU	NSYTLDFL	2x NSYTLDME
700	500	250	-	-	-	-	E	NSYTLE	NSYTLEU	NSYTLEFL	NSYTLEME
800	600	200	NSYVDM17UF	17	NSYVDM16UP	16	F	NSYTLF	NSYTLFU	NSYTLFFL	NSYTLFME
800	600	250	NSYVDM17UF	17	NSYVDM16UP	16	F	NSYTLF	NSYTLFU	NSYTLFFL	NSYTLFME
800	600	300	NSYVDM17UF	17	NSYVDM16UP	16	G	NSYTLG	NSYTLGU	NSYTLG2FL (5)	NSYTLGME
800	600	400	NSYVDM17UF	17	NSYVDM16UP	16	G	NSYTLG	NSYTLGU	NSYTLG2FL (5)	NSYTLGME
800	800	250	-	-	-	-	D [4]	NSYTLD	NSYTLDU	NSYTLDFL	2x NSYTLDME
800	800	300	-	-	-	-	D [4]	NSYTLD	NSYTLDU	NSYTLDFL	2x NSYTLDME
800	1000	300	-	-	-	-	E [4]	NSYTLE	NSYTLEU	NSYTLEFL	2x NSYTLEME
800	1000	300	-	-	-	-	E [4]	NSYTLE	NSYTLEU	NSYTLEFL	2x NSYTLEME
800	1200	300	-	-	-	-	E [4]	NSYTLE	NSYTLEU	NSYTLEFL	2x NSYTLEME
1000	600	250	NSYVDM21UF	21	NSYVDM20UP	20	F	NSYTLF	NSYTLFU	NSYTLFFL	NSYTLFME
1000	600	300	NSYVDM21UF	21	NSYVDM20UP	20	G	NSYTLG	NSYTLGU	NSYTLG2FL (5)	NSYTLGME
1000	600	400	NSYVDM21UF	21	NSYVDM20UP	20	G	NSYTLG	NSYTLGU	NSYTLG2FL (5)	NSYTLGME
1000	800	250	-	-	NSYVDM20U8P	20	D [4]	NSYTLD	NSYTLDU	NSYTLDFL	2x NSYTLDME
1000	800	300	-	-	NSYVDM20U8P	20	D [4]	NSYTLD	NSYTLDU	NSYTLDFL	2x NSYTLDME
1000	800	400	-	-	NSYVDM20U8P	20	D [4]	NSYTLD	NSYTLDU	NSYTLDFL	2x NSYTLDME
1000	1000	300	-	-	-	-	E [4]	NSYTLE	NSYTLEU	NSYTLEFL	2x NSYTLEME
1000	1000	300	-	-	-	-	E [4]	NSYTLE	NSYTLEU	NSYTLEFL	2x NSYTLEME
1000	1200	300	-	-	-	-	E [4]	NSYTLE	NSYTLEU	NSYTLEFL	2x NSYTLEME
1000	1200	400	-	-	-	-	E [4]	NSYTLE	NSYTLEU	NSYTLEFL	2x NSYTLEME
1200	600	300	-	-	-	-	G	NSYTLG	NSYTLGU	NSYTLG2FL (5)	NSYTLGME
1200	600	400	-	-	-	-	G	NSYTLG	NSYTLGU	NSYTLG2FL (5)	NSYTLGME
1200	800	300	-	-	NSYVDM25U8P	25	D [4]	NSYTLD	NSYTLDU	NSYTLDFL	2x NSYTLDME
1200	800	400	-	-	NSYVDM25U8P	25	D [4]	NSYTLD	NSYTLDU	NSYTLDFL	2x NSYTLDME
1200	1000	300	-	-	-	-	E [4]	NSYTLE	NSYTLEU	NSYTLEFL	2x NSYTLEME
1200	1000	300	-	-	-	-	E [4]	NSYTLE	NSYTLEU	NSYTLEFL	2x NSYTLEME
1200	1000	400	-	-	-	-	E [4]	NSYTLE	NSYTLEU	NSYTLEFL	2x NSYTLEME
1200	1200	300	-	-	-	-	E [4]	NSYTLE	NSYTLEU	NSYTLEFL	2x NSYTLEME
1200	1200	400	-	-	-	-	E [4]	NSYTLE	NSYTLEU	NSYTLEFL	2x NSYTLEME
1400	1000	300	-	-	-	-	E [4]	NSYTLE	NSYTLEU	NSYTLEFL	2x NSYTLEME

[1] For other dimensions, see our application offer, page 14.
[2] FL13 for entry type A and B FL21 for all other entries.
[3] To adjust the depth of the internal door, please order the step slides.
[4] 2 plates.
[5] Exists with 1 cut-out **NSYTLGFL**.
[6] Cable entry FlexiCable IP55

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

	Composition accessories					Plinths			
						100 mm		200 mm	
	Internal door [3]	Step slides	Canopy	Fixing on post	Full width wall fixing lugs	Single plinths side plate [9]	Single plinths front plate [9]	Single plinths side plate [7] [9]	Single plinths front plate [7] [9]
	-	-	NSYTJ2015	-	NSYAEFPFS3DW20	-	-	-	-
	-	-	NSYTJ2515	-	-	-	-	-	-
	-	-	NSYTJ3015	NSYSFPSC30	NSYAEFPFS3DW30	-	-	-	-
	-	NSYSDCR200	NSYTJ3020	NSYSFPSC30	NSYAEFPFS3DW30	-	-	-	-
	-	-	NSYTJ4015	NSYSFPSC40	NSYAEFPFS3DW40	-	-	-	-
	-	NSYSDCR200	NSYTJ4020	NSYSFPSC40	NSYAEFPFS3DW40	-	-	-	-
	NSYPIN43	-	NSYTJ3015	NSYSFPSC30	NSYAEFPFS3DW30	-	-	-	-
	NSYPIN43	NSYSDCR200	NSYTJ3020	NSYSFPSC30	NSYAEFPFS3DW30	-	-	-	-
	-	NSYSDCR200	NSYTJ4020	NSYSFPSC40	NSYAEFPFS3DW40	-	-	-	-
	-	NSYSDCR200	NSYTJ6020	NSYSFPSC60	NSYAEFPFS3DW60	-	-	-	-
	-	NSYSDCR250	NSYTJ6025	NSYSFPSC60	NSYAEFPFS3DW60	-	-	-	-
	-	NSYSDCR200	NSYTJ3020	NSYSFPSC30	NSYAEFPFS3DW30	-	-	-	-
	NSYPIN54	NSYSDCR200	NSYTJ4020	NSYSFPSC40	NSYAEFPFS3DW40	-	-	-	-
	NSYPIN54	NSYSDCR250	NSYTJ4025	NSYSFPSC40	NSYAEFPFS3DW40	-	-	-	-
	-	NSYSDCR200	NSYTJ5020	NSYSFPSC50	NSYAEFPFS3DW50	-	-	-	-
	-	NSYSDCR250	NSYTJ5025	NSYSFPSC50	NSYAEFPFS3DW50	-	-	-	-
	NSYPIN64	NSYSDCR200	NSYTJ4020	NSYSFPSC40	NSYAEFPFS3DW40	-	-	-	-
	NSYPIN64	NSYSDCR250	NSYTJ4025	NSYSFPSC40	NSYAEFPFS3DW40	-	-	-	-
	-	NSYSDCR250	NSYTJ5025	NSYSFPSC50	NSYAEFPFS3DW50	-	-	-	-
	-	NSYSDCR200	NSYTJ6020	NSYSFPSC60	NSYAEFPFS3DW60	-	-	-	-
	-	NSYSDCR250	NSYTJ6025	NSYSFPSC60	NSYAEFPFS3DW60	-	-	-	-
	-	NSYSDCR300	NSYTJ6030	NSYSFPSC60	NSYAEFPFS3DW60	NSYSPF6100	NSYSPS3100SD	NSYSPF6200	NSYSPS3200SD
	-	NSYSDCR400	NSYTJ6040	NSYSFPSC60	NSYAEFPFS3DW60	NSYSPF6100	NSYSPS4100SD	NSYSPF6200	NSYSPS4200SD
	-	NSYSDCR300	NSYTJ8030	NSYSFPSC80	NSYAEFPFS3DW80	NSYSPF8100	NSYSPS3100SD	NSYSPF8200	NSYSPS3200SD
	NSYPIN75	NSYSDCR250	NSYTJ5025	NSYSFPSC50	NSYAEFPFS3DW50	-	-	-	-
	NSYPIN86	NSYSDCR200	NSYTJ6020	NSYSFPSC60	NSYAEFPFS3DW60	-	-	-	-
	NSYPIN86	NSYSDCR250	NSYTJ6025	NSYSFPSC60	NSYAEFPFS3DW60	-	-	-	-
	NSYPIN86	NSYSDCR300	NSYTJ6030	NSYSFPSC60	NSYAEFPFS3DW60	NSYSPF6100	NSYSPS3100SD	NSYSPF6200	NSYSPS3200SD
	NSYPIN86	NSYSDCR400	NSYTJ6040	NSYSFPSC60	NSYAEFPFS3DW60	NSYSPF6100	NSYSPS4100SD	NSYSPF6200	NSYSPS4200SD
	-	NSYSDCR250	NSYTJ8025	NSYSFPSC80	NSYAEFPFS3DW80	-	-	-	-
	-	NSYSDCR300	NSYTJ8030	NSYSFPSC80	NSYAEFPFS3DW80	NSYSPF8100	NSYSPS3100SD	NSYSPF8200	NSYSPS3200SD
	-	NSYSDCR300	NSYTJ10030	-	NSYAEFPFS3DW100	NSYSPF10100	NSYSPS3100SD	NSYSPF10200	NSYSPS3200SD
	-	NSYSDCR300	NSYTJ10030	-	NSYAEFPFS3DW100	NSYSPF10100	NSYSPS3100SD	NSYSPF10200	NSYSPS3200SD
	-	NSYSDCR300 [8]	NSYTJ12030	-	NSYAEFPFS3DW120	-	-	-	-
	NSYPIN106	NSYSDCR250	NSYTJ6025	-	NSYAEFPFS3DW60	-	-	-	-
	NSYPIN106	NSYSDCR300	NSYTJ6030	-	NSYAEFPFS3DW60	NSYSPF6100	NSYSPS3100SD	NSYSPF6200	NSYSPS3200SD
	NSYPIN106	NSYSDCR400	NSYTJ6040	-	NSYAEFPFS3DW60	NSYSPF6100	NSYSPS4100SD	NSYSPF6200	NSYSPS4200SD
	NSYPIN108	NSYSDCR250	NSYTJ8025	-	NSYAEFPFS3DW80	-	-	-	-
	NSYPIN108	NSYSDCR300	NSYTJ8030	-	NSYAEFPFS3DW80	NSYSPF8100	NSYSPS3100SD	NSYSPF8200	NSYSPS3200SD
	NSYPIN108	NSYSDCR400	NSYTJ8040	-	NSYAEFPFS3DW80	NSYSPF8100	NSYSPS4100SD	NSYSPF8200	NSYSPS4200SD
	-	NSYSDCR300	NSYTJ10030	-	NSYAEFPFS3DW100	NSYSPF10100	NSYSPS3100SD	NSYSPF10200	NSYSPS3200SD
	-	NSYSDCR300	NSYTJ10030	-	NSYAEFPFS3DW100	NSYSPF10100	NSYSPS3100SD	NSYSPF10200	NSYSPS3200SD
	-	NSYSDCR300 [8]	NSYTJ12030	-	NSYAEFPFS3DW120	NSYSPF12100	NSYSPS3100SD	NSYSPF12200	NSYSPS3200SD
	-	NSYSDCR400 [8]	NSYTJ12040	-	NSYAEFPFS3DW120	NSYSPF12100	NSYSPS4100SD	NSYSPF12200	NSYSPS4200SD
	NSYPIN126	NSYSDCR300	NSYTJ6030	-	NSYAEFPFS3DW60	NSYSPF6100	NSYSPS3100SD	NSYSPF6200	NSYSPS3200SD
	NSYPIN126	NSYSDCR400	NSYTJ6040	-	NSYAEFPFS3DW60	NSYSPF6100	NSYSPS4100SD	NSYSPF6200	NSYSPS4200SD
	NSYPIN128	NSYSDCR300	NSYTJ8030	-	NSYAEFPFS3DW80	NSYSPF8100	NSYSPS3100SD	NSYSPF8200	NSYSPS3200SD
	NSYPIN128	NSYSDCR400	NSYTJ8040	-	NSYAEFPFS3DW80	NSYSPF8100	NSYSPS4100SD	NSYSPF8200	NSYSPS4200SD
	-	NSYSDCR300	NSYTJ10030	-	NSYAEFPFS3DW100	NSYSPF10100	NSYSPS3100SD	NSYSPF10200	NSYSPS3200SD
	-	NSYSDCR300	NSYTJ10030	-	NSYAEFPFS3DW100	NSYSPF10100	NSYSPS3100SD	NSYSPF10200	NSYSPS3200SD
	-	NSYSDCR400	NSYTJ10040	-	NSYAEFPFS3DW100	NSYSPF10100	NSYSPS4100SD	NSYSPF10200	NSYSPS4200SD
	-	NSYSDCR300 [8]	NSYTJ12030	-	NSYAEFPFS3DW120	NSYSPF12100	NSYSPS3100SD	NSYSPF12200	NSYSPS3200SD
	-	NSYSDCR400 [8]	NSYTJ12040	-	NSYAEFPFS3DW120	NSYSPF12100	NSYSPS4100SD	NSYSPF12200	NSYSPS4200SD
	-	NSYSDCR300	NSYTJ10030	-	NSYAEFPFS3DW100	NSYSPF10100	NSYSPS3100SD	NSYSPF10200	NSYSPS3200SD

[7] Also available in ventilated version with cable gland for widths of 600 and 800, see page 97.

[8] For the double mounting plates, order also ref. **NSYSDRSDCR300** (D300) or **NSYSDRSDCR400** (D400).

[9] To install the plinth to a wall-mounting enclosure, order ref. **NSYAPFWM**.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Dimensions			Composition accessories				
Height (mm)	Width (mm)	Depth (mm)	Support pillar adaption plate	Support pillar	Floor stand kit for wall-mounting 300 mm	400 mm	Support bracket for enclosure with anti-tilt kit and reinforcement1400 mm (1)
300	200	150	-	-	-	-	NSYCOCNS1400
300	250	150	-	-	-	-	NSYCOCNS1400
300	300	150	NSYAEFP315S3D	NSYCOCN80	-	-	NSYCOCNS1400
300	300	200	NSYAEFP32S3D	NSYCOCN80	-	-	NSYCOCNS1400
300	400	150	NSYAEFP315S3D	NSYCOCN80	-	-	NSYCOCNS1400
300	400	200	NSYAEFP42S3D	NSYCOCN80	-	-	NSYCOCNS1400
400	300	150	NSYAEFP315S3D	NSYCOCN80	-	-	NSYCOCNS1400
400	300	200	NSYAEFP32S3D	NSYCOCN80	-	-	NSYCOCNS1400
400	400	200	NSYAEFP42S3D	NSYCOCN80	-	-	NSYCOCNS1400
400	600	200	-	-	-	-	NSYCOCNS1400
400	600	250	-	-	-	-	NSYCOCNS1400
500	300	200	NSYAEFP32S3D	NSYCOCN80	-	-	NSYCOCNS1400
500	400	200	NSYAEFP42S3D	NSYCOCN80	-	-	NSYCOCNS1400
500	400	250	NSYAEFP42S3D	NSYCOCN80	-	-	NSYCOCNS1400
500	500	200	-	-	-	-	NSYCOCNS1400
500	500	250	-	-	-	-	NSYCOCNS1400
600	400	200	NSYAEFP42S3D	NSYCOCN80	-	-	NSYCOCNS1400
600	400	250	NSYAEFP42S3D	NSYCOCN80	-	-	NSYCOCNS1400
600	500	250	-	-	-	-	NSYCOCNS1400
600	600	200	-	-	-	-	NSYCOCNS1400
600	600	250	-	-	-	-	NSYCOCNS1400
600	600	300	-	-	-	-	NSYCOCNS1400
600	600	400	-	-	-	-	NSYCOCNS1400
600	800	300	-	-	-	-	NSYCOCNS1400
700	500	250	-	-	-	-	NSYCOCNS1400
800	600	200	-	-	-	-	NSYCOCNS1400
800	600	250	-	-	-	-	NSYCOCNS1400
800	600	300	-	-	-	-	NSYCOCNS1400
800	600	400	-	-	-	-	NSYCOCNS1400
800	800	250	-	-	-	-	NSYCOCNS1400
800	800	300	-	-	NSYWMK33	NSYWMK34	NSYCOCNS1400
800	1000	300	-	-	NSYWMK33	NSYWMK34	NSYCOCNS1400
800	1000	300	-	-	-	-	NSYCOCNS1400
800	1200	300	-	-	NSYWMK33	NSYWMK34	NSYCOCNS1400
1000	600	250	-	-	-	-	NSYCOCNS1400
1000	600	300	-	-	-	-	NSYCOCNS1400
1000	600	400	-	-	-	-	NSYCOCNS1400
1000	800	250	-	-	-	-	NSYCOCNS1400
1000	800	300	-	-	NSYWMK33	NSYWMK34	NSYCOCNS1400
1000	800	400	-	-	NSYWMK43	NSYWMK44	-
1000	1000	300	-	-	NSYWMK33	NSYWMK34	-
1000	1000	300	-	-	NSYWMK33	NSYWMK34	-
1000	1200	300	-	-	NSYWMK33	NSYWMK34	-
1000	1200	400	-	-	NSYWMK43	NSYWMK44	-
1200	600	300	-	-	-	-	-
1200	600	400	-	-	-	-	-
1200	800	300	-	-	NSYWMK33	NSYWMK34	-
1200	800	400	-	-	NSYWMK43	NSYWMK44	-
1200	1000	300	-	-	NSYWMK33	NSYWMK34	-
1200	1000	300	-	-	NSYWMK33	NSYWMK34	-
1200	1000	400	-	-	NSYWMK43	NSYWMK44	-
1200	1200	300	-	-	NSYWMK33	NSYWMK34	-
1200	1200	400	-	-	NSYWMK43	NSYWMK44	-
1400	1000	300	-	-	NSYWMK33	NSYWMK34	-

(1) Available in version 1800 mm: ref. **NSYCOCNS1800**.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Steel wall-mounting enclosures

Comment:
You will find the weights of the Spacial S3D enclosures without mounting plate in the selection guide on page 46.



Wall fixing lugs

NSYAEFPFSC

- Set of 4 wall fixing lugs.
- Mounted directly on the rear of the enclosure, either in horizontal or vertical position.
- Wall-enclosure separation of 12 mm.
- Do not use for dynamic loads.
- Maximum load: 250 kg

Supply:
Supplied with fixing screws and pre-mounted sealing gaskets

Characteristics	References
Wall fixing lugs, passivated zinc-coated steel, for indoor enclosure	**NSYAEFPFSC**
Wall fixing lugs, 304L stainlesssteel, for outdoor enclosure	**NSYAEFPFXSC**

NSYAEFPFSC2

Supply:
4 fixing brackets + covers

Characteristics	References
Wall fixing lugs + cover, passivated zinc-coated steel + PA	**NSYAEFPFSC2**

NSYCAEFPF

Supply:
Kit of 4 covers

Characteristics	References
Cover for wall fixing brackets, PA	**NSYCAEFPF**

Kit for heavy loads

NSYAEFAHLBSC

- Kit made up of 2 reinforcement pieces.
- To be mounted before installing the mounting plate in top position with the standard lugs (to be ordered separately).
- This kit is mandatory for wall-mounting enclosures bigger than 800 x 800 mm.
- Material: Passivated zinc-coated steel
- Maximum load: 400 kg

Characteristics	References
Kit for heavy loads	**NSYAEFAHLBSC**

Wall fixing lugs with wall-enclosure separation

NSYAEFPF40SC

- Batch of 4 wall fixing lugs.
- Separation of 40 mm from the wall at the rear of the enclosure.
- Need to drill a hole to help prevent rotation.
- Material: Passivated zinc-coated steel
- Maximum load: 100 kg



Characteristics	References
Wall fixing lugs with wall-enclosure separation	**NSYAEFPF40SC**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Steel wall-mounting enclosures

Full-width wall fixing lugs



- Kit made of 2 parts (top and bottom).
- Screwed from the inside.
- Material: Passivated zinc-coated steel
- Maximum load: 350 kg

Comment:
For more information, see page 77

NSYAEFPFS3DW20

Characteristics	Width (mm)	A (mm)	References
Heavy load reinforcement	200	-	**NSYAEFPFS3DW20**
Heavy load reinforcement	300	295	**NSYAEFPFS3DW30**
Heavy load reinforcement	400	395	**NSYAEFPFS3DW40**
Heavy load reinforcement	500	495	**NSYAEFPFS3DW50**
Heavy load reinforcement	600	595	**NSYAEFPFS3DW60**
Heavy load reinforcement	800	795	**NSYAEFPFS3DW80**
Heavy load reinforcement	1000	-	**NSYAEFPFS3DW100**
Heavy load reinforcement	1200	-	**NSYAEFPFS3DW120**

Post fixing device for Spacial steel enclosure



- For indoor installations on posts with a maximum circumference of 675 mm (minimum diameter 150 mm and maximum diameter 215 mm).
- Rail fixed to the inserts in the rear of the enclosure with 8 mm screws.
- They allow the mounting of protection canopies.
- Material: Passivated zinc-coated steel
- Maximum load: 100 kg

Comment:
For more information, see page 77

NSYSFPSC30

Characteristics	Width (mm)	A (mm)	References
Post fixing	300	295	**NSYSFPSC30**
Post fixing	400	395	**NSYSFPSC40**
Post fixing	500	495	**NSYSFPSC50**
Post fixing	600	595	**NSYSFPSC60**
Post fixing	800	795	**NSYSFPSC80**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Steel wall-mounting enclosures

Support pillar

NSYCOCN80

- The support pillar is fixed directly to the bottom face of the Spacial steel enclosure by means of an adapter plate.
- The latter, to be ordered in addition to the pillar, replaces the cable gland plate.
- Overall height of the support foot: 800 mm.
- Mounting possible on all enclosures with dimensions up to 600 x 400 x 250 mm (except 200 x 200 x 150 mm and 250 x 200 x 150 mm enclosures).
- Material: Extruded aluminium
- Finish: Epoxy polyester paint
- Colour: RAL 7035 grey



Characteristics	Height (mm)	References
Support pillar	800	**NSYCOCN80**

Support pillar adaptation plate

- Description: Plate for fixing the support pillar on the enclosure.
- This plate replaces the cable gland plate delivered with the enclosure.
- Material: Steel
- Finish: Polyester powder
- Colour: RAL 7035 grey

NSYAEFP315S3D

Characteristics	For enclosure width (mm)	For enclosure depth (mm)	References
Support pillar adaptation plate	300-400	150	**NSYAEFP315S3D**
Support pillar adaptation plate	300	200	**NSYAEFP32S3D**
Support pillar adaptation plate	400	200-250	**NSYAEFP42S3D**

Support bracket for enclosure with anti-tilt kit and reinforcement

NSYCOCNS1400

- The support bracket is used when the enclosure cannot be hung from a wall or a post.
- Suitable for outdoor use.
- Maximum enclosure dimensions: 1000 x 800 x 300 mm.
- Floor attachment by standard M12 fastenings.
- Material: Steel
- Finish: Epoxy polyester paint
- Colour: RAL 7035 grey
- Maximum load: 120 kg

Characteristics	Height (mm)	References
Support bracket for enclosure with anti-tilt kit and reinforcement	1400	**NSYCOCNS1400**
Support bracket for enclosure with anti-tilt kit and reinforcement	1800	**NSYCOCNS1800**

Floor Stand Kit for wall-mounting enclosure

- Set of 2 feet, elevating wall-mounting enclosures.
- Cut-outs needed on enclosure – drilling template provided with the kit.
- Material: Steel
- Finish: Epoxy polyester paint
- Colour: RAL 7035 grey
- Thickness: Sides: 25/10^{e} mm, Base: 30/10^{e} mm
- Maximum load: **250** kg
- Compatible with Spacial S3D, S3DC enclosures.
- Enclosure depth 300 mm: When enclosures are equipped with a cable gland plate, it only fits with enclosures of width 800, 1000 and 1200 mm, except model H 600 x W 800 x D 300 mm.
- Enclosure depth 400 mm: When enclosures are equipped with a cable gland plate, it does not fit with enclosures of width 600 mm.

Supply:
2 platform feet (right and left) and fixing elements

NSYWMK33

Characteristics	Enclosure depth (mm)	(Inches)	Foot height (mm)	(Inches)	References
Floor stand for Spacial S3D	300	12	300	12	**NSYWMK33**
Floor stand for Spacial S3D	400	16	300	12	**NSYWMK43**
Floor stand for Spacial S3D	300	12	450	18	**NSYWMK34**
Floor stand for Spacial S3D	400	16	450	18	**NSYWMK44**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Steel wall-mounting enclosures

Front and rear plinths

Installation:
It is necessary to order separately the plinth fixing kit (ref. **NSYAPFWM**) composed by fixing hardware and drilling jig

Comment:
For more information, see page 96

- The front and rear of the plinth consists of 4 corners with 2 or 4 panels.
- Material: Folded sheet steel, corner with a thickness of 25/10e mm
- Finish: Structured finish, epoxy polyester powder
- Colour: RAL 7022 grey
- Ingress protection rating: IP30 according to IEC 60529
- Mechanical protection rating: IK10 according to IEC 62262

Supply:
Height 100 mm: 4 corners, 2 panels (front and rear), 4 corner covers and fixing elements. Height 200 mm: 4 corners, 4 panels (2 front and 2 rear), 4 corner covers and fixing elements

NSYSPF6100

NSYSPF6200

Characteristics	Width (mm)	Height (mm)	References
Front plinths for Spacial	600	100	**NSYSPF6100**
Front plinths for Spacial	800	100	**NSYSPF8100**
Front plinths for Spacial	1000	100	**NSYSPF10100**
Front plinths for Spacial	1200	100	**NSYSPF12100**
Front plinths for Spacial	600	200	**NSYSPF6200**
Front plinths for Spacial	800	200	**NSYSPF8200**
Front plinths for Spacial	1000	200	**NSYSPF10200**
Front plinths for Spacial	1200	200	**NSYSPF12200**

Plinth side panels

- They are fixed to the corner of the plinth by 2 fixing screws.
- Folded sheet steel
- Finish: Structured finish, epoxy polyester powder
- Colour: RAL 7022 grey
- Ingress protection rating: IP30 according to IEC 60529
- Mechanical protection rating: Mechanical protection rating

Supply:
Height 100 mm: 2 side panels, 4 corner covers and fixing elements. Height 200 mm:
4 side panels (height of 100 mm, 2 for each side), 4 corner covers and fixing elements

NSYSPS3100SD

NSYSPS3200SD

Characteristics	Depth (mm)	Height (mm)	References
Side plinths for Spacial	300	100	**NSYSPS3100SD**
Side plinths for Spacial	400	100	**NSYSPS4100SD**
Side plinths for Spacial	300	200	**NSYSPS3200SD**
Side	400	200	**NSYSPS4200SD**

Stainless steel plinths (standard plinths page 141, ventilated plinths page 423) are compatible with steel wall-mounting S3D enclosures using an earthing cable reference **NSYEL226D13** (description page 305) to be ordered separatly.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Steel wall-mounting enclosures

Coupling of S3D steel enclosures

- Available in 2 versions:
  Coupling version without cable entry.
  Version with coupling frame allowing the entry of cables.
- Separation of 17 mm between 2 coupled enclosures, allowing full opening of the doors.
- Allows lateral coupling of 2 enclosures.
- These frames allow the door to open to 120°.
- Material: Polyester charged with fibreglass, self-extinguishing
- Ingress protection rating: IP66 according to IEC 60529



Supply:
Kit made up of 4 spacers and their fixings. Mounting by screws, included

Coupling spacers

NSYAEUBUSC

Characteristics	References
Batch of 4 coupling spacers	**NSYAEUBUSC**

Coupling frame

NSYAEUBU41SC

Characteristics	References
Coupling frame, 435 x 185 mm	**NSYAEUBU41SC**
Coupling frame, 635 x 185 mm	**NSYAEUBU61SC**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Steel wall-mounting enclosures

Eyebolts

NSYAELYTCRG8

- Set of two M8 eyebolts. They are fixed directly to the body of the floor-standing enclosure. Cannot be installed with the canopy in place or if it is planned to put one.
- Material: Zinc-coated moulded steel
- Maximum load: 200 kg per enclosure when slinging at 60°



Supply:
Reinforcing brackets attached to the rings (these brackets also act as a drilling template)

Characteristics	References
Batch of 2 M8 eyebolts	**NSYAELYTCRG8**

Protection canopy

NSYTJ2015

- Direct fixing to the body of the enclosure by four M6 screws.
- To be used for all outdoor installations.
- Material: Sheet steel
- Finish: Epoxy polyester paint
- Colour: RAL 7035 grey



Supply:
Delivered with the fixings required for installation

Characteristics	Width (mm)	Depth (mm)	F (mm)	G (mm)	H (mm)	References
Protection canopy	200	150	36	75	23	**NSYTJ2015**
Protection canopy	250	150	36	75	23	**NSYTJ2515**
Protection canopy	300	150	36	75	23	**NSYTJ3015**
Protection canopy	400	150	36	75	23	**NSYTJ4015**
Protection canopy	500	150	36	75	23	**NSYTJ5015**
Protection canopy	500	200	36	130	23	**NSYTJ5020**
Protection canopy	600	200	36	130	23	**NSYTJ6020**
Protection canopy	250	200	36	130	23	**NSYTJ2520**
Protection canopy	300	200	36	130	23	**NSYTJ3020**
Protection canopy	400	200	36	130	23	**NSYTJ4020**
Protection canopy	800	200	36	130	23	**NSYTJ8020**
Protection canopy	400	250	42	150	48	**NSYTJ4025**
Protection canopy	500	250	42	150	48	**NSYTJ5025**
Protection canopy	600	250	42	150	48	**NSYTJ6025**
Protection canopy	800	250	42	150	48	**NSYTJ8025**
Protection canopy	600	300	42	200	48	**NSYTJ6030**
Protection canopy	800	300	42	200	48	**NSYTJ8030**
Protection canopy	1000	300	42	200	48	**NSYTJ10030**
Protection canopy	1200	300	42	200	48	**NSYTJ12030**
Protection canopy	600	400	42	300	48	**NSYTJ6040**
Protection canopy	800	400	42	300	48	**NSYTJ8040**
Protection canopy	1000	400	42	300	48	**NSYTJ10040**
Protection canopy	1200	400	42	300	48	**NSYTJ12040**

Mounting rail



- Accessory designed to optimize the available space inside the enclosure.
- It is intended for the installation of switchgear to extend the chassis.
- Mounting possible after installing the mounting plate.
- It is mounted horizontally, with a single screw, on the side panels.
- Door switch mounting possibility.
- It is possible to vertically fasten **NSYSLCR●●** light cross rails (description on page 256) and **NSYSQCR●●** quick fixing cross rails (description on page 254).
- Material: Galvanised steel
- Maximum load: Static load: 6 kg (sides) and 1.5 kg (top); Dynamic load (transport horizontally): 2 kg according to ASTM D-4169-16
- Installation: In order to help ensure the electrical continuity in all cases it is recommended to use an earthing cable **NSYEL●●●D6** or **NSYEL●●●D8**, se page 305







Supply:
Set of 2 cross rails

NSYSUCR200WM

Characteristics	Cubicle depth (mm)	References
Mounting rail for wall mounting enclosure S3D/CRN	200	**NSYSUCR200WM**
Mounting rail for wall mounting enclosure S3D/CRN	250	**NSYSUCR250WM**
Mounting rail for wall mounting enclosure S3D/CRN	300	**NSYSUCR300WM**
Mounting rail for wall mounting enclosure S3D/CRN	400	**NSYSUCR400WM**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Steel wall-mounting enclosures

Standard handle

- Operating handle delivered with the enclosure.
- It can be attached to the locking system by means of a fixing element.
- It can also be used to loosen the caps helping protect the studs when painting.

NSYAEDLS3DKDB3

Characteristics	References
Standard handle	**NSYAEDLS3DKDB3**

Handle lock operated using screwdriver insert

NSYTSMLS3D

Characteristics	References
Handle lock operated using screwdriver insert	**NSYTSMLS3D**

Standard handles with keys

- Attractive and ergonomic bi-material handle.
- Large range of barrels covering all the most common needs.
- The installation of the standard handle does not require the escutcheon to be removed.
- Locks may only be operated using the supplied keys.
- Composition: Delivered with 2 keys



NSYAEDL1242S3D

Characteristics	References
405	**NSYAEDL405S3D**
421	**NSYAEDL421S3D**
455	**NSYAEDL455S3D**
520	**NSYAEDL520S3D**
601	**NSYAEDL601S3D**
610E	**NSYAEDL610S3D**
705E	**NSYAEDL705S3D**
1242	**NSYAEDL1242S3D**
1332E	**NSYAEDL1332S3D**
1344E	**NSYAEDL1344S3D**
2124E	**NSYAEDL2124S3D**
2131A	**NSYAEDL2131S3D**
2132A	**NSYAEDL2132S3D**
2133A	**NSYAEDL2133S3D**
2241A	**NSYAEDL2241S3D**
2244E	**NSYAEDL2244S3D**
2314E	**NSYAEDL2314S3D**
2322A	**NSYAEDL2322S3D**
2331A	**NSYAEDL2331S3D**
2432E	**NSYAEDL2432S3D**
2433A	**NSYAEDL2433S3D**
3113A	**NSYAEDL3113S3D**
3123E	**NSYAEDL3123S3D**
3131A	**NSYAEDL3131AS3D**
3132A	**NSYAEDL3132S3D**
3432E	**NSYAEDL3432S3D**
3524E	**NSYAEDL3524S3D**
4322A	**NSYAEDL4322S3D**
4324E	**NSYAEDL4324S3D**
5124A	**NSYAEDL5124S3D**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Steel wall-mounting enclosures

Standard locks

- Spacial S3D wall-mounting enclosures are supplied with a 3 mm double bar lock as **standard**.
- Spare lock: Order ref. NSYAEDLS3DRL (escutcheon + cam + washer).
- Large range of standardised inserts covering all the most common needs.
- Installation and removal with a single screw.
- Material: Zamack + polyamide
- Ingress protection rating: IP66 according to IEC 60529

Supply:
Delivered with 1 plastic key

NSYAEDLS6S3D

Characteristics	References
6 mm square	**NSYAEDLS6S3D**
7 mm square	**NSYAEDLS7S3D**
8 mm square	**NSYAEDLS8S3D**
3 mm double bar	**NSYAEDLB3S3D**
5 mm double bar	**NSYAEDLB5S3D**
CNOMO 6.5 mm triangular	**NSYAEDLT6S3D**
8 mm triangular	**NSYAEDLT8S3D**

Barrel DIN kit

- Mounting of half-cylinder according to DIN 18252 (EN1303). Cam can be turned every 45°.
- Easy mounting instead of standard lock.
- Compatible with PLM barrels offer. See page 174. (Example: **NSYTL1242EME**).
- Material: Polyamide GF
- Ingress protection rating: IP66 according to IEC 60529

Supply:
Delivered with metal cam 1 point and metal cam 3 points

NSYAEDDINS3D

Characteristics	References
Barrel DIN kit	**NSYAEDDINS3D**

Double bar 3 mm metal lock

- Easy mounting instead of standard lock.
- Material: Zamak
- Ingress protection rating: IP66 according to IEC 60529

Supply:
Delivered with metal cam 1 point and metal cam 3 points

NSYAEDLB3MS3D

Characteristics	References
Double bar 3 mm metal lock	**NSYAEDLB3MS3D**

Metal cam kit 1 point and 3 points

- To adapt other locks.
- Material: Zinc-coated metal

NSYAEDLMETS3D

Characteristics	References
Metal cam kit 1 point and 3 points	**NSYAEDLMETS3D**

Lock with screwdriver insert and metal latch

- Material: Zamak
- Ingress protection rating: IP55 (IEC 60529)

Supply:
Delivered with housing, insert, fixing nut and metal cam 3 points

NSYAEDLSDS3D

Characteristics	References
Lock with screwdriver insert and metal latch	**NSYAEDLSDS3D**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Steel wall-mounting enclosures

Padlock



NSYAEDLPADS3D

- Easy mounting instead of the standard lock.
- Padlockable, Diameter 8 mm
- Material: Zamak
- Ingress protection rating: IP66 (IEC 60529)

Supply:
Delivered with metal key

Characteristics	References
Padlock	**NSYAEDLPADS3D**

Other locks with keys

- Material: Zamak
- Ingress protection rating: IP66 (IEC 60529)

Supply:
Delivered with metal cam 1 point
and metal cam 3 points

NSYAEDLEDF9S3D

Characteristics	References
EDF 900	**NSYAEDLEDF9S3D**
EDF 1300	**NSYAEDLEDF13S3D**
EDF 1400	**NSYAEDLEDF14S3D**

"Push-close" locking system

- The Spacial S3D enclosures can be transformed into push-close enclosures.
- The push-close enclosure is used in various applications and fully meets the security demands of the market.
- Locking system with a 6.5 mm push-close system in accordance with CNOMO standards.
- This system allows the door to be closed and locked by simply pushing it.
- System made up of a lock and a closure plate.
- It is only installed on enclosures with 1 locking point (H < 600 mm).
- Other dimensions: Contact us.
- Ingress protection rating: IP55 according to IEC 60529

Supply:
Delivered with metal cam 1 point

NSYAEDLPSS3D

Characteristics	References
"Push-close" locking system	**NSYAEDLPSS3D**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Steel wall-mounting enclosures

Door hinges



NSYAEDH180S3D

NSYAEDH120S3D

- Captive pin, indexed by a spring.
- Material: Zamak body for ref.**NSYAEDH180S3D**, treated sheet steel body for ref. **NSYAEDH120S3D**, aluminium pin
- Maximum load: For the 180° hinge, the maximum admissible load on the door is 20 kg/m²
- For the 120° hinge, the maximum admissible load on the door is 50 kg/m²

Supply:
Batch of 1 hinge, delivered with fixings

Characteristics	References
180° hinge for S3D enclosure	**NSYAEDH180S3D**
Standard 120° hinge for S3D	**NSYAEDH120S3D**

Door switch for wall-mounting enclosures

NSYINLCRN

- Switch/commutator unit equipped with support and fixings for direct fixing to the enclosure.
- Can be used to control lighting, air-conditioning units, etc.
- It is not compatible with installing the 19" swing rack and the internal door.
- NC + NO contact, 10 A/500 V.

Supply:
1 door switch and fixing elements

Characteristics	References
Door switch	**NSYINLCRN**

Wall-mounting door retainer Steel

NSYAEDRSCST

To block the door in the open position.

- It is installed on enclosures with heights from 400 mm and widths from 300 mm.
- Door opening angle: 120°.
- Earthing connection of the enclosure by means of the reinforcement rail.
- Earthing accessories supplied with the enclosure (earth-connection wire to be ordered separately), see For more information, see page 305.
- Material: Steel

Comment:
It is not compatible with installing the 19" swing rack and the internal door.

Characteristics	References
Wall-mounting door retainer Steel	**NSYAEDRSCST**

Wall-mounting door retainer Polyamide

NSYAEDRS3DPA6

To block the door in the open position.

- It is installed on the perforated rails of the enclosure doors at the required height.
- Material: Polyamide 6 (PA6)

Comment:
It is only installed on enclosures with a height of less than 400 mm (no perforated rails).

Characteristics	References
Wall-mounting door retainer Polyamide	**NSYAEDRS3DPA6**

Internal door

NSYPIN43

- Locking with 3 mm double bar lock.
- The internal door can be installed directly on the front face of the enclosure or on the step slides (not supplied as standard).
- To mount an inner door and a mounting plate at the same time on the step slides is possible as standard.
- Incompatible with the installation of the door stop and door switch. For further details, please consult us.
- Material: Steel
- Colour: RAL 7035 grey
- Maximum load: 30 kg/m²

Comment:
For more information, see page 79
(1) Equipped with welded vertical profiles in order to facilitate cable management.

Characteristics	High (mm)	Width (mm)	References
Internal door	400	300	**NSYPIN43**
Internal door	500	400	**NSYPIN54**
Internal door	600	400	**NSYPIN64**
Internal door	700	500	**NSYPIN75**
Internal door	800	600	**NSYPIN86**
Internal door	1000	600	**NSYPIN106** (1)
Internal door	1000	800	**NSYPIN108** (1)
Internal door	1200	600	**NSYPIN126** (1)
Internal door	1200	800	**NSYPIN128** (1)

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Steel wall-mounting enclosures

Standard cable gland plate

- Plate delivered as standard with the Spacial S3D universal enclosure.
- Surface with markings in steps of 25 mm, to facilitate drilling.
- Material: Steel, structured finish RAL 7035 grey
- Thickness: 15/10e mm
- Ingress protection rating: IP66 according to IEC 60529
- Fixing: Fixing by 4, 6, 8, 10 or 12 screws, according to the model

Comment:
For more information, see page 79

Supply:
Delivered with sealing gasket and fixing hardware

NSYTLA

Characteristics	Enclosures width (mm)	Enclosures depth (mm)	Type	Width (A)	Depth (B)	No. of markings	No. of Ø 6 holes	References
Standard	200-250	150	A	140	80	4	4	**NSYTLA**
Standard	300-400	150	B	245	80	7	4	**NSYTLB**
Standard	300	200	C	245	130	21	6	**NSYTLC**
Standard	400	200-250	D	345	130	33	8	**NSYTLD**
Standard	500	200-250	E	445	130	45	8	**NSYTLE**
Standard	600	200-250	F	545	130	57	10	**NSYTLF**
Standard	600	300-400	G	495	220	102	12	**NSYTLG**
Standard	800	250-300-400	D	345	130	-	-	2x **NSYTLD**
Standard	1000-1200	300-400	E	445	130	-	-	2x **NSYTLE**

Aluminium cable gland plate

- Suitable for non-magnetic applications.
- Material: Brushed-finish aluminium
- Thickness: 30/10e mm
- Ingress protection rating: IP66 according to IEC 60529
- Fixing: Fixing by 4, 6, 8, 10 or 12 screws, according to the model´

Supply:
Delivered with sealing gasket and fixing hardware

NSYTLAU

Characteristics	Enclosures width (mm)	Enclosures depth (mm)	Type	Width (A)	Depth (B)	No. of Ø 6 holes	References
Aluminium	200-250	150	A	140	80	4	**NSYTLAU**
Aluminium	300-400	150	B	245	80	4	**NSYTLBU**
Aluminium	300	200	C	245	130	6	**NSYTLCU**
Aluminium	400	200-250	D	345	130	8	**NSYTLDU**
Aluminium	500	200-250	E	445	130	9	**NSYTLEU**
Aluminium	600	200-250	F	545	130	10	**NSYTLFU**
Aluminium	600	300-400	G	495	220	12	**NSYTLGU**
Aluminium	800	250-300-400	D	345	130	-	2x **NSYTLDU**
Aluminium	1000-1200	300-400	E	445	130	-	2x **NSYTLEU**

Cable gland plates with FL type cut-out for cable gland membranes

- Mounting instead of the Spacial S3D plate.
- Cut-outs for installation of membranes type FL 21 (Cut-out FL13 for depth 150 mm; And cut-out FL21 for other depths.), page 285.
- Material: Steel, structured finish RAL 7035 grey
- Thickness: 15/10e mm
- Fixing: Fixing by 4, 6, 8, 10 or 12 screws, according to the model
- **NSYTLG2FL** with 2 FL21 cut-outs
- **NSYTLG4FL** with 4 FL21 cut-outs
- **NSYTLAFL** cannot be mounted on enclosure width 200 and depth 150
- **NSYTLBFL** with FL13 cut-out

Comment:
For more information, see page 79

Supply:
Delivered with sealing gasket and fixing hardware

NSYTLAFL

Characteristics	Enclosures width (mm)	Enclosures depth (mm)	Type	Width (A)	Depth (B)	No. of markings	No. of Ø 6 holes	References
Cut-out	200-250	150	A	140	80	4	4	**NSYTLAFL**
Cut-out	300-400	150	B	245	80	7	4	**NSYTLBFL**
Cut-out	300	200	C	245	130	21	6	**NSYTLCFL**
Cut-out	400	200-250	D	345	130	33	8	**NSYTLDFL**
Cut-out	500	200-250	E	445	130	45	9	**NSYTLEFL**
Cut-out	600	200-250	F	545	130	57	10	**NSYTLFFL**
Cut-out	600	200-250	F	545	130	57	10	**NSYTLF2FL**
Cut-out	600	300-400	G	495	220	102	12	**NSYTLGFL**
Cut-out	600	300-400	G	495	220	102	12	**NSYTLG2FL**
Cut-out	600	300-400	G	495	220	102	12	**NSYTLG4FL**
Cut-out	800	250-300-400	D	345	130	-	-	2x **NSYTLDFL**
Cut-out	1000-1200	300-400	E	445	130	-	-	2x **NSYTLEFL**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Steel wall-mounting enclosures

FlexiCable cable entries

FlexiCable is an innovative cable gland plate for simple and fast cable entrance.
There is no need to drill holes: The creation of the cable entrances takes a few seconds.

- Installation possibilities: Replaces cable gland plate (S3D) or directly on enclosure.
- Cable diameter: Up to 26 mm.
- Ingress protection rating: IP55 according to IEC 60529
- Fixing: By 4, 6, 8, 10 or 12 screws, according to the model

Other characteristics:

- Exists in 5 sizes matching 46 sizes (132 models) of Spacial S3D steel wall-mounting enclosures
- Fire resistant 650°C following IEC 60695-2-11
- Tested on short-circuit effect 250 A, 25 kA following IEC 61439-1

Mount FlexiCable on your S3D enclosure.

Create a hole with a screw driver.

Push the cable through FlexiCable and finish-off your installation.

Supply:
1 metallic frame with pre-mounted membrane, 1 gasket, Fixing hardware

FlexiCable cable entries

NSYTLCME

Characteristics	Enclosures width (mm)	Enclosures depth (mm)	Type	Width (A)	Depth (B)	Effective cable entrance dimensions (mm)	References
Standard	300	200	C	245	130	178 x 63	**NSYTLCME**
Standard	400	200-250	D	345	130	278 x 63	**NSYTLDME**
Standard	500	200-250	E	445	130	378 x 63	**NSYTLEME**
Standard	600	200-250	F	545	130	478 x 63	**NSYTLFME**
Standard	600	300-400	G	495	220	428 x 153	**NSYTLGME**
Standard	800	250-300-400	D	345	130	-	**NSYTLDME**
Standard	1000-1200	300-400	E	445	130	-	**NSYTLEME**

Cable management solutions for FlexiCable plate





NSYEDCME

- Cable-guide to be mounted directly on FlexiCable plate

Supply: 1

Characteristics	References
Cable-guide for FlexiCable plate	**NSYEDCME**

Cable-guide to be mounted on adjustable step slides

NSYTFPCRN



Supply: 2

NSYTFPCRN4

- Direct mounting of cable guides NSYTFPCRN●● on bracket.

Characteristics	References
Cable-guide for wall-mounting enclosure, door width 400 mm	**NSYTFPCRN4**
Cable-guide for wall-mounting enclosure, door width 500 mm	**NSYTFPCRN5**
Cable-guide for wall-mounting enclosure, door width 600 mm	**NSYTFPCRN6**
Cable-guide for wall-mounting enclosure, door width 800 mm	**NSYTFPCRN8**
Cable-guide for wall-mounting enclosure, door width 1000 mm	**NSYTFPCRN10**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Steel wall-mounting enclosures

• For details, type the reference in the search engine of www.se.com.

Multi-A	Multi-C	Multi-R	Multi-CS	Multi-T
			New	
FL13 and FL21 type membranes	Circular connector-free entries	Rectangular connector-free entries	Modular entry allowing the passing of up to 48 pre-assembled cables.	FL21-type membranes
NSYAECPFLA7	**NSYTSAM504SE**	**NSYTSA2414SE**	**NSYDCD2412**	**NSYAECPFLBP** (1)
NSYAECPFLA10	**NSYTSAM508SE**	**NSYTSA2417SE**	**NSYDCD244**	**NSYAECPFLT7**
NSYAECPFLA25	**NSYTSAM638SE**	**NSYTSA2422SE**	**NSYDCD248**	**NSYAECPFLT25**
NSYAECPFLA33	**NSYTSAM6313SE**	**NSYTSA2423SE**	**NSYDCD249**	**NSYAECPFLT35**
		NSYTSA2429SE		

(1) Metallic plate

Prisma	Multi-F	Multi-CF	Multi-CR	Multi-H
		New		
FL21 or rectangular.	FL13 and FL21 preconfigured flanges.	Cable entry for protected cables.	Cable entries with dies for cables equipped with connectors.	FL21 insulated flange with ISO knockouts.
08881	**NSYAECPKFL11**	**NSYTLK2414**	**NSYDCE168**	**NSYTSAKFL**
08892	**NSYAECPKFL7A**	**NSYTLK2422**	**NSYDCE244**	
08895	**NSYAECPKFL10**	**NSYTLK2428**	**NSYDCE2410**	
08897		**NSYTLK2446**		
08898		**NSYTLK24M**		
08899				

Simple-1	Simple-2	Simple-3	Simple-4	Simple-5	Synthetic snap in cable gland	Stainless steel cable gland with lamellar insert	
					New		New
Mixed membrane entries for enclosure thickness 20/10e - 32/10e mm.	PVC adjustable coneshaped entries for enclosure thickness 30/10e - 32/10e mm.	Quick cable entries for enclosure thickness 10/10e - 40/10e mm (5/10e - 20/10e mm for ref. **IMT36179**).	PVC adjustable coneshaped entries for PG tubes or for enclosure thickness 12/10e - 15/10e mm.	Presse-étoupe ISO.	Without thread. Easy assembly and disassembly. Suitable for walls from 0.5 to 4 mm thick.	Lamellar technology provides excellent resistance to traction as well as excellent torsional protection. For outdoor use, or for aggressive environments. AISI 304L	AISI 316L
ISM71071	**NSYECPC3**	**IMT36179**	**NSYEC7**	**ISM71501**	**NSYCGSP16**	**NSYCGX12**	**NSYCGX12H**
ISM71072	**NSYECPC5**	**IMT36180**		**ISM71502**	**NSYCGSP20**	**NSYCGX16**	**NSYCGX16H**
ISM71073	**NSYECPC6**	**IMT36181**		**ISM71503**	**NSYCGSP25**	**NSYCGX20**	**NSYCGX20H**
ISM71074	**NSYECPC9**	**IMT36182**		**ISM71504**	**NSYCGSP32**	**NSYCGX25**	**NSYCGX25H**
IMT36172	**NSYECPC15**	**IMT36183**		**ISM71505**	**NSYCGSP40**	**NSYCGX32**	**NSYCGX32H**
IMT36173		**IMT36184**		**ISM71506**		**NSYCGX40**	**NSYCGX40H**
		IMT36185		**IMT36150**			

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Steel wall-mounting enclosures

Multi-A

- Material: TPE, SBS, SEBS and PP co-polymer - halogen free
- Colour: RAL 7035 grey
- Cable entry material: Combined
- Cable glands to be fitted: Optional: Specific cable clamp ref. **NSYAECPFLACA●●** to be used
- Installation possibilities: On cable gland plate adapter or directly on enclosure
- Flexibility of the installation: Medium
- Reversibility: Medium
- Ingress protection rating: IP55 according to IEC 60529
- Cable retention: High with cable clamp, (up to 18 daN)
- Cable diameter (mm): From 13 to 30
- Cable Installation time: Moyenne
- Quantity of cables to be fitted for a given surface: ++
- Cable entries for cables with connectors: No
- Cut-out dimensions (mm): 134 x 52 (FL13); 214 x 90 (FL21)
- External dimensions (mm): 216 x 84
- Certificates: Cable anchorage pull test: EN 50262. Long term UV resistance: ASTM G 154-06
- Flame resistance: 750°C
- Temperature range: -40°C to +85°C

NSYAECPFLA10

NSYAECPFLA33

Characteristics	Height	Width	Depth	Diameter of the cable entry (Ø mm)								References
	(mm)	(mm)	(mm)	No.	13	14	15	16	18	21	30	
FL13 and FL21 type membranes	20	135	47	7	-	-	4	-	-	3	-	**NSYAECPFLA7**
FL13 and FL21 type membranes	20	135	47	10	6	-	-	4	-	-	-	**NSYAECPFLA10**
FL13 and FL21 type membranes	25	215	86	25	-	16	-	-	6	-	3	**NSYAECPFLA25**
FL13 and FL21 type membranes	25	215	86	33	-	24	-	-	9	-	-	**NSYAECPFLA33**

Multi-C

- Order by multiples of 10 (10, 20, 30...)
- Material: Polyamide
- Cable entry material: Soft membrane
- Cable glands to be fitted: No
- Installation possibilities: On modified cable gland plate or directly on enclosure
- Flexibility of the installation: Medium
- Reversibility: Full
- Ingress protection rating: IP55 according to IEC 60529
- Cable retention: Medium
- Cable diameter (mm): From 3 to 15.9
- Cable Installation time: Fast
- Quantity of cables to be fitted for a given surface: ++
- Cable entries for cables with connectors: No
- Cut-out dimensions (mm): Ø 50.5; Ø 63.5
- External dimensions (mm): Ø 58; Ø 71
- Certificates: UL 94 V-0
- Flame resistance: 650°C

NSYTSAM508SE

Characteristics	Cut-out Ø	Diameter of the cable entry (Ø mm)							References
	(mm)	No.	3-5.5	3-6.5	3.6-6.5	5-9.2	6-10	9.6-15.9	
Circular connector-free entries	50.5	4	-	-	-	-	3	1	**NSYTSAM504SE**
Circular connector-free entries	50.5	8	-	-	7	-	1	-	**NSYTSAM508SE**
Circular connector-free entries	63.5	8	-	2	-	4	-	2	**NSYTSAM638SE**
Circular connector-free entries	63.5	13	6	-	6	-	1	-	**NSYTSAM6313SE**

Multi-R

- Material: Polyamide
- Cable entry material: Soft membrane
- Cable glands to be fitted: No
- Installation possibilities: On cable gland plate with special cut-out or directly on enclosure
- Flexibility of the installation: Medium
- Reversibility: Full
- Ingress protection rating: IP55 according to IEC 60529
- Cable retention: Medium
- Cable diameter (mm): From 4.3 to 15.9
- Cable Installation time: Fast
- Quantity of cables to be fitted for a given surface: ++
- Cable entries for cables with connectors: No
- Cut-out dimensions (mm): 112 x 36
- External dimensions (mm): 146 x 14 x 58
- Certificates: UL 94 V-0
- Flame resistance: 650°C



Supply:
1 unit

NSYTSA2414SE

Characteristics	Cut-out Ø	Diameter of the cable entry (Ø mm)						References
	(mm)	No.	4.3-8.1	3-6.5	5-9.2	8-12.5	9.6-15.9	
Rectangular connector-free entries	112 x 36	14	-	6	4	-	-	**NSYTSA2414SE**
Rectangular connector-free entries	112 x 36	17	-	-	17	-	-	**NSYTSA2417SE**
Rectangular connector-free entries	112 x 36	22	-	16	4	2	-	**NSYTSA2422SE**
Rectangular connector-free entries	112 x 36	23	23	-	-	-	-	**NSYTSA2423SE**
Rectangular connector-free entries	112 x 36	29	-	29	-	-	-	**NSYTSA2429SE**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Steel wall-mounting enclosures

Multi-CS

- Material: Reinforced polypropylene and TPE. Halogen free
- Colour: Black
- Cable entry material: Soft membrane
- Cable glands to be fitted: No
- Installation possibilities:
  On cable gland plate adapter or directly on enclosure
- Flexibility of the installation: Full
- Reversibility: Full
- Ingress protection rating: IP55 according to IEC 60529
- Cable retention: Medium
- Cable diameter (mm): Up to 22
- Cable Installation time: Fast
- Quantity of cables to be fitted for a given surface: +++
- Cable entries for cables with connectors: Yes
- Cut-out dimensions (mm): 112 x 36
- External dimensions (mm): 148 x 58 x 15; 148 x 58 x 18
- Certificates: UL 94 V-0, Fire resistance: V0
- Temperature range: -30°C to +100°C

NSYDCD2412

Characteristics	References	
Modular entry allowing the passing of up to 48 pre-assembled cables	**NSYDCD2412**	New
Modular entry allowing the passing of up to 48 pre-assembled cables	**NSYDCD244**	New
Modular entry allowing the passing of up to 48 pre-assembled cables	**NSYDCD248**	New
Modular entry allowing the passing of up to 48 pre-assembled cables	**NSYDCD249**	New

Multi-T

- Material: TPE
- Colour: RAL 7035 grey
- Cable entry material: Soft membrane
- Cable glands to be fitted: No
- Installation possibilities:
  On cable gland plate adapter or directly on enclosure
- Flexibility of the installation: Medium
- Reversibility: Medium
- Ingress protection rating: IP66 according to IEC 60529
  (IP65 for **NSYAECPFLBP**)
- Cable retention: Low
- Cable diameter (mm): From 5 to 60
- Cable Installation time: Fast
- Quantity of cables to be fitted for a given surface: ++
- Cable entries for cables with connectors: No
- Cut-out dimensions (mm): 214 x 90 (FL21)
- External dimensions (mm): 214 x 88
- Certificates: UL 94 V-0, Fire resistance: UL 94 V-0
- Flame resistance: 650°C
- Temperature range: -40°C to +100°C

NSYAECPFLT25

Characteristics	Diameter of the cable entry (Ø mm)												References
	No.	5-7	6-10	8-12	8-16	10-14	12-18	14-20	17-32	20-26	24-54	30-60	
metallic plate	0	-	-	-	-	-	-	-	-	-	-	-	**NSYAECPFLBP**
FL21 membranes	7	-	-	-	4	-	-	-	-	-	2	1	**NSYAECPFLT7**
FL21 membranes	27	4	-	4	-	13	-	4	-	2	-	-	**NSYAECPFLT25**
FL21 membranes	37	-	4	14	-	16	2	-	1	-	-	-	**NSYAECPFLT35**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Steel wall-mounting enclosures

Prisma

- Material: Insulating material
- Colour: RAL 9001
- Cable entry material: Soft membrane
- Cable glands to be fitted: No
- Installation possibilities:
  On cable gland plate adapter or directly on enclosure
- Flexibility of the installation: Medium
- Reversibility: Medium
- Ingress protection rating: IP55 according to IEC 60529
- Cable retention: Low
- Cable diameter (mm): From 28 to 60 (FL21), From 7 to 72 (rectangular)
- Cable Installation time: Fast
- Quantity of cables to be fitted for a given surface: ++
- Cable entries for cables with connectors: No
- Cut-out dimensions (mm): 214 x 90 (FL21)
- External dimensions (mm): 216 x 84

Prisma, plain

08881

- Solid cable gland plates

Characteristics	Type	References
Prisma	FL21	**08881**

Prisma, pre-drilled

08892

08895


08898


08899

- Suitable for receiving cable glands with metric pitch

Characteristics	Type	References
Pre-drilled, 2 x M20 or M32 + 2 x M25 or M40	FL21	**08892**
Pre-drilled, 5 x M16 or M25 + 8 x M20	FL21	**08895**
Pre-drilled, 39 x Ø 7 - 26 mm	opening 225 x 137 mm	**08898**
Pre-drilled, 2 x Ø 33 - 72 mm	opening 225 x 137 mm	**08899**

Prisma, membrane


08897

- Membrane to be drilled according to the required diameter

Characteristics	Type	References
Membrane, 2 x Ø 28 - 60 mm	FL21	**08897**

Multi-F

- Type FL13 or FL21
- "Pop-out" membranes only
- "Pop-out" membranes or cable gland installation
- Knock out system
- Material: Fibreglass-reinforced polypropylene and TPE - Halogen Free
- Colour: RAL 7035 grey
- Cable entry material: Soft membrane
- Cable glands to be fitted: No
- Installation possibilities:
  On cable gland plate adapter or directly on enclosure
- Flexibility of the installation: Medium
- Reversibility: Medium
- Ingress protection rating: IP65 according to IEC 60529
- Cable retention: Low
- Cable diameter (mm): From 16 to 50
- Cable Installation time: Fast
- Quantity of cables to be fitted for a given surface: ++
- Cable entries for cables with connectors: No
- Cut-out dimensions (mm): 134 x 52 (FL13); 214 x 90 (FL21)
- External dimensions (mm): From 134 x 52 to 214 x 90
- Certificates: UL 94-HB; Test standard EN 60529:1991 + A1; EN 60670-1:2005, EN 50262:1998 EMKO-TUI (03-SEC) FI001/84; Semko report 816003; UL-approved materials
- Temperature range: -20°C to +125°C ("Pop-out" membranes only)



NSYAECPKFL11

Characteristics	Dimesions (mm)				Diameter of the cable entry (Ø mm)						References
	L1	L2	H	H2	No.	4-10	M16 (5-10)	M20 (6-13)	M25 (8-17)	M32, M40 oder M50	
MMulti-F FL13	134	52	6.5	35	11	10	-	1	-	-	**NSYAECPKFL11**
Multi-F	214	90	9	35	7	-	2	2	2	1	**NSYAECPKFL7A**
Multi-F	214	90	9	35	10	-	4	2	4	-	**NSYAECPKFL10**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Steel wall-mounting enclosures

Multi-CF

- Material: Reinforced polypropylene and TPE. Halogen free
- Colour: Black
- Cable entry material: Soft membrane
- Cable glands to be fitted: No
- Installation possibilities:
  On cable gland plate adapter or directly on enclosure
- Flexibility of the installation: Full
- Reversibility: Full
- Ingress protection rating: IP65 according to IEC 60529
- Cable retention: Medium
- Cable diameter (mm): From 9 to 30
- Cable Installation time: Fast
- Quantity of cables to be fitted for a given surface: +++
- Cable entries for cables with connectors: Yes
- Cut-out dimensions (mm): 112 x 36
- External dimensions (mm): 148 x 60 x 10
- Certificates: UL 94-HB; Fire resistance: V0
- Temperature range: -30°C to +70°C

NSYTLK2414

Characteristics	References	
Cable entry for protected cables	**NSYTLK2414**	New
Cable entry for protected cables	**NSYTLK2422**	New
Cable entry for protected cables	**NSYTLK2428**	New
Cable entry for protected cables	**NSYTLK2446**	New
Cable entry for protected cables	**NSYTLK24M**	New

Multi-CR

- Material: Polyamide
- Cable entry material: Hard plastic
- Cable glands to be fitted: Yes
- Installation possibilities:
  On cable gland plate adapter or directly on enclosure
- Flexibility of the installation: Low
- Reversibility: Medium
- Ingress protection rating: IP54 according to IEC 60529
- Cable retention: High (with fastener)
- Cable diameter (mm): From 3 to 31
- Cable Installation time: Slow
- Quantity of cables to be fitted for a given surface: ++
- Cable entries for cables with connectors: Yes
- Cut-out dimensions (mm):
  36 x 91 (**NSYDCE168**); 36 x 112 (**NSYDCE24•**)
- External dimensions (mm): 146 x 58
- Flame resistance: 650 °C
- Temperature range: -40°C to +80°C

Supply:
1 die and fixing elements

NSYDCE168

NSYDCE244

NSYDCE2410

Characteristics	Height (mm)	Width (mm)	Depth (mm)	Connector cut-out type	Number of cable entries	References
Cable entries with dies for cables equipped with connectors.	14	146	58	16	8	**NSYDCE168**
Cable entries with dies for cables equipped with connectors.	14	146	58	24	4	**NSYDCE244**
Cable entries with dies for cables equipped with connectors.	14	146	58	24	10	**NSYDCE2410**

Multi-H

- Material: Polycarbonate glass-fiber reinforced
- Colour: RAL 7035 grey
- Cable entry material: Hard plastic
- Cable glands to be fitted: Yes
- Installation possibilities:
  On cable gland plate adapter or directly on enclosure
- Flexibility of the installation: Low
- Reversibility: Medium
- Ingress protection rating: IP65 according to IEC 60529
- Cable retention: High (with cable clamp)
- Cable diameter (mm): From 12 to 25
- Cable Installation time: Slow
- Quantity of cables to be fitted for a given surface: ++
- Cable entries for cables with connectors: No
- Cut-out dimensions (mm): 214 x 90 (FL21)
- External dimensions (mm): 215 x 85
- Certificates: UL 94 V-1
- Flame resistance: 750 °C
- Temperature range: For normal operation: -40°C to +80°C;
  For a short time: -40°C to +120°C

NSYTSAKFL

Characteristics	Height	Width	Depth	Diameter of the cable entry (Ø mm)				References
	(mm)	(mm)	(mm)	No.	M12	M12 or M20	M16 oder M25	
FL21 insulated flange with ISO knockouts	10	215	85	12	4	4	4	**NSYTSAKFL**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Steel wall-mounting enclosures

Simple-1

- Mixed membrane entries for enclosure thickness 20/10e - 32/10e mm.
- Material: SBS
- Colour: RAL 7035 grey or RAL 9010 white
- Cable entry material: Soft membrane
- Cable glands to be fitted: Not applicable
- Installation possibilities: On cable gland plate or directly on enclosure
- Flexibility of the installation: Low
- Reversibility: Medium
- Ingress protection rating: IP55 according to IEC 60529
- Cable retention: Low
- Cable diameter (mm): From 20 to 40
- Cable Installation time: Fast
- Quantity of cables to be fitted for a given surface: +
- Cable entries for cables with connectors: No
- Cut-out dimensions (mm): Various circular hole diameters according to cable diameter
- External dimensions (mm): From Ø 23 to 44
- Flame resistance: 750°C

Supply:
Minor packaging of 10 pieces

ISM71074

Characteristics	Drill hole Ø (mm)	Cable / conduit Ø (mm)	References
Mixed membrane entries for IP55 direct cable entries, RAL 9010	23	4 - 20	**IMT36172**
Mixed membrane entries for IP55 direct cable entries, RAL 9010	29	4 - 25	**IMT36173**
Mixed membrane entries for IP55 direct cable entries, RAL 7035	23	4 - 20	**ISM71071**
Mixed membrane entries for IP55 direct cable entries, RAL 7035	29	4 - 25	**ISM71072**
Mixed membrane entries for IP55 direct cable entries, RAL 7035	36	4 - 32	**ISM71073**
Mixed membrane entries for IP55 direct cable entries, RAL 7035	44	4 - 40	**ISM71074**

Simple-2

- PVC adjustable coneshaped entries for enclosure thickness 30/10e - 32/10e mm.
- Material: PVC
- Cable entry material: Soft membrane
- Cable glands to be fitted: Not applicable
- Installation possibilities: On cable gland plate or directly on enclosure
- Flexibility of the installation: Low
- Reversibility: Medium
- Ingress protection rating: IP55 according to IEC 60529
- Cable retention: Low
- Cable diameter (mm): From 5 to 87
- Cable Installation time Fast
- Quantity of cables to be fitted for a given surface: +
- Cable entries for cables with connectors: No
- Cut-out dimensions (mm): Various circular hole diameters according to cable diameter
- External dimensions (mm): From Ø 25 to 98



Supply:
NSYECPC3 50 cable entries, **NSYECPC5** and **NSYECPC6** each 25 cable entries, **NSYECPC9** and **NSYECPC15** each 10 cable entries

NSYECPC15

Characteristics	Dimensions (mm)						Capacity		References
	Ø A	Ø B	Ø C	Ø D	E	F	Cable (Ø mm)	Tube	
PVC adjustable cone-shaped entries	25	21.5	18	5	3.2	13	5-18	PG 9-11	**NSYECPC3**
PVC adjustable cone-shaped entries	33	29.5	26	5	3.2	20	5-26	PG 9-16	**NSYECPC5**
PVC adjustable cone-shaped entries	43	38.5	36	5	3.2	22	5-36	PG 9-21	**NSYECPC6**
PVC adjustable cone-shaped entries	70	63	60	28	3	20	28-60	PG 21-48	**NSYECPC9**
PVC adjustable cone-shaped entries	98	90	87	28	3	23	28-87	PG 21-48	**NSYECPC15**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Steel wall-mounting enclosures

Simple-3

- Quick cable entries for enclosure thickness 10/10e - 40/10e mm (5/10e - 20/10e mm for ref. **IMT36179**).
- Material: EPDM plastic
- Colour: Grey cable entries: NCS 5500; Black cable entries: NCS 9000
- Cable entry material: Combined
- Cable glands to be fitted: Not applicable
- Installation possibilities: On cable gland plate or directly on enclosure
- Flexibility of the installation: Low
- Reversibility: Medium
- Ingress protection rating: IP67 according to IEC 60529
- Cable retention: Medium
- Cable diameter (mm): From 12 to 50
- Cable Installation time: Fast
- Quantity of cables to be fitted for a given surface: +
- Cable entries for cables with connectors: No
- Cut-out dimensions (mm):
  Various circular hole diameters according to cable diameter
- External dimensions (mm): From Ø 12.5 to 50.7
- Flame resistance: 750°C



Supply:
50 (M12 to M32)
25 (M40 and M50)

IMT36179

Characteristics	Dimensions			References
	ISO	Drill hole (Ø mm)	Cable (Ø mm)	
Quick cable entries	M12	12.5	3 - 5	**IMT36179**
Quick cable entries	M16	16	5 - 7	**IMT36180**
Quick cable entries	M20	20.3	7 - 10	**IMT36181**
Quick cable entries	M25	25.3	10 - 14	**IMT36182**
Quick cable entries	M32	32.4	14 - 20	**IMT36183**
Quick cable entries	M40	40.7	20 - 26	**IMT36184**
Quick cable entries	M50	50.7	26 - 35	**IMT36185**

PVC adjustable cone-shaped entries

- PVC adjustable coneshaped entries for PG tubes
  or for enclosure thickness 12/10e - 15/10e mm.
- Material: PVC
- Colour: Black
- Cable entry material: Combined
- Cable glands to be fitted: Not applicable
- Installation possibilities:
  On cable gland plate or directly on enclosure
- Flexibility of the installation: Low
- Reversibility: Medium
- Ingress protection rating: IP55 according to IEC 60529
- Cable retention: Low
- Cable diameter (mm): From 16 to 44
- Cable Installation time: Fast
- Quantity of cables to be fitted for a given surface: +
- Cable entries for cables with connectors: No
- Cut-out dimensions (mm):
  Various circular hole diameters according to cable diameter
- External dimensions (mm): From Ø 25 to 52



Supply:
25 cable entries

NSYEC7

Characteristics	Dimensions (mm)						Capacity		References
	Ø A	Ø B	Ø C	Ø D	E	F	Cable (Ø mm)	Tube	
PVC adjustable cone-shaped entries	52	48.5	44	13	1.5	30	13 to 44	PG 36	**NSYEC7**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Steel wall-mounting enclosures

Simple-5

- ISO cable gland.
- Material: PA6 Polyamide, neoprene gasket
- Colour: RAL 7035 grey
- Cable entry material: Combined
- Installation possibilities: On cable gland plate or directly on enclosure
- Flexibility of the installation: Low
- Reversibility: Medium
- Ingress protection rating: IP68
- Cable retention: High
- Cable diameter (mm): From 12 to 40
- Cable Installation time: Slow
- Quantity of cables to be fitted for a given surface: +
- Cable entries for cables with connectors: No
- Cut-out dimensions (mm): Various circular hole diameters according to cable diameter
- External dimensions (mm): From Ø 15 to 46
- Certificates: Glow wire resistance: 960°C
- Standard: Compliance with VDE, UL and CSA
- Flame resistance: 750 °C



Supply:
The cable glands are supplied with nuts
Pack of 20 (M12 to M20), of 10 (M25 and M32), of 5 (M40)

ISM71503

Characteristics	Dimensions					References
	Cable (Ø mm)	Drill hole (Ø mm)	TD	TL	SW	
Cable gland	3 / 6.5	12.2 (0 + 0.2)	12	6	15	**ISM71501**
Cable gland	4 / 8	16.2 (0 + 0.2)	16	8	19	**ISM71502**
Cable gland	6 / 12	20.2 (0 + 0.2)	20	10	24	**ISM71503**
Cable gland with high resistance to fire	6 / 12	20.2 (0 + 0.2)	20	10	24	**IMT36150**
Cable gland	11 / 17	25.2 (0 + 0.2)	25	8	29	**ISM71504**
Cable gland	15 / 21	32.2 (0 + 0.3)	32	10	36	**ISM71505**
Cable gland	19 / 28	40.5 (0 + 0.3)	40	10	46	**ISM71506**

Synthetic snap in cable gland

- Without thread.
- Easy assembly and disassembly.
- Suitable for walls from 0.5 to 4 mm thick.
- Material: PA6 Polyamide, neoprene gasket
- Colour: RAL 7035 grey, RAL 7001, RAL 9005. Other colours on demand
- Cable entry material: Non armoured
- Installation possibilities: On cable gland plate or directly on enclosure
- Flexibility of the installation: Low
- Reversibility: Medium
- Ingress protection rating: IP66
- Cable retention: High
- Cable diameter (mm): From 16 to 40
- Cable Installation time: Slow
- Quantity of cables to be fitted for a given surface: +
- Cable entries for cables with connectors: No
- Thread type: Metric EN 60423 Other types are available on demand
- Cut-out dimensions (mm): Various circular hole diameters according to cable diameter
- External dimensions (mm): From Ø 22 to 46
- Certificates: UL 94 V-2 (except for the size M40)
- Standard: DIN EN 62444, UL 514B, UL 514B§8.26.7
- Temperature range: -20°C to + 100°C



Supply:
The cable glands are supplied with nuts
Pack of 20 (M16 and M20), of 10 (M25 and M32), of 5 (M40)

NSYCGSP16

Characteristics	Dimensions							References	
	Ø	Ø min / max	Drill Ø	SL	SD	H			
Synthetic snap in cable gland	M16	5/10	16.2 to 16.4	9	15.9	42.5	22	**NSYCGSP16**	New
Synthetic snap in cable gland	M20	6/12	20.2 to 20.4	9	19.9	41.5	24	**NSYCGSP20**	New
Synthetic snap in cable gland	M25	11/17	25.2 to 25.4	9	24.9	43.5	29	**NSYCGSP25**	New
Synthetic snap in cable gland	M32	15/21	32.2 to 32.4	9	31.9	49.5	36	**NSYCGSP32**	New
Synthetic snap in cable gland	M40	19/28	40.2 to 40.4	11.5	39.9	56	46	**NSYCGSP40**	New

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Snap in cable gland disassembling tool

- Material: Plastic

NSYDT16

NSYDT20

Characteristics	Ø	References	
Tool to quickly disassemble cable gland	M16	**NSYDT16**	New
Tool to quickly disassemble cable gland	M20	**NSYDT20**	New
Tool to quickly disassemble cable gland	M25	**NSYDT25**	New
Tool to quickly disassemble cable gland	M32	**NSYDT32**	New
Tool to quickly disassemble cable gland	M40	**NSYDT40**	New

Stainless steel cable gland with lamellar insert

- Lamellar technology provides excellent resistance to traction as well as excellent torsional protection. For outdoor use, or for aggressive environments.
- Material: Stainless steel AISI 304L or AISI 316L, neoprene gasket
- Cable entry material: Non armoured
- Installation possibilities: On cable gland plate or directly on enclosure
- Flexibility of the installation: Low
- Reversibility: Medium
- Ingress protection rating: IP68
- Cable retention: High
- Cable diameter (mm): From 12 to 40
- Cable Installation time: Slow
- Quantity of cables to be fitted for a given surface: +
- Cable entries for cables with connectors: No
- Thread type: Metric EN 60423
- Cut-out dimensions (mm): Various circular hole diameters according to cable diameter
- External dimensions (mm): From Ø 14 to 43
- Certificates: UL 94 V-2
- Standard: DIN EN 62444, UL 514
- Temperature range: -20°C to + 100°C



Supply:
The cable glands are supplied with nuts
Pack of 5 (M12 and M16), of 4 (M20 and M25), of 2 (M32 and M40)

NSYCGX12

Characteristics	Dimensions							References	
	Ø	Ø min / max	Drill Ø	TD	TL	H			
AISI 304L	M12	3/6.5	12 to 12.2	12	12	22	14	**NSYCGX12**	New
AISI 304L	M16	5/10	16 to 16.2	16	12	28.5	20	**NSYCGX16**	New
AISI 304L	M20	6/12	20 to 20.2	20	12	24	22	**NSYCGX20**	New
AISI 304L	M25	11/17	25 to 25.2	25	12	32.5	27	**NSYCGX25**	New
AISI 304L	M32	15/21	32 to 32.3	32	15	36	34	**NSYCGX32**	New
AISI 304L	M40	19/28	40 to 40.3	40	15	43.5	43	**NSYCGX40**	New
AISI 316L	M12	3/6.5	12 to 12.2	12	12	22	14	**NSYCGX12H**	New
AISI 316L	M16	5/10	16 to 16.2	16	12	28.5	20	**NSYCGX16H**	New
AISI 316L	M20	6/12	20 to 20.2	20	12	24	22	**NSYCGX20H**	New
AISI 316L	M25	11/17	25 to 25.2	25	12	32.5	27	**NSYCGX25H**	New
AISI 316L	M32	15/21	32 to 32.3	32	15	36	34	**NSYCGX32H**	New
AISI 316L	M40	19/28	40 to 40.3	40	15	43.5	43	**NSYCGX40H**	New

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Steel wall-mounting enclosures

1-door enclosure



2-door enclosure





Detail (2) Detail (3)

A: Enclosure height
B: Enclosure width
C: Enclosure depth

1. A-200 from the height of 800 mm.
2. 4 or 6 (widths 1000 - 1200 mm) M8 x 25 mm backstuds.
3. 2 M6 x 17.5 mm earthing studs
4. Stud centre-to-centre distance.
5. Centre-to-centre distance of the holes for direct fixing.

Comment:
The DXF diagrams can be downloaded from our websites.

Enclosure		Cable gland plate						
Width (mm)	Depth (mm)	Dim. (mm)	Type	No.	J	K	L	References
200 - 250	150 - 250	140 x 80	A	1	57	115	55	**NSYTLA**
300 - 400	150	245 x 80	B	1	57	220	55	**NSYTLB**
300	200	245 x 130	C	1	80	220	105	**NSYTLC**
400	200 - 250	345 x 130	D	1	80	320	105	**NSYTLD**
500	200 - 250	445 x 130	E	1	80	420	105	**NSYTLE**
600	200 - 250	545 x 130	F	1	80	520	105	**NSYTLF**
600	300 - 400	495 x 220	G	1	126*	470	195	**NSYTLG**
800	250 - 300 - 400	345 x 130	D	2	95**	320	105	2 x **NSYTLD**
1000 - 1200	300 - 400	445 x 130	E	2	95	420	105	2 x **NSYTLE**

* Except enclosure 1000 x 600 x 400 mm, J = 140 mm.
** Except enclosure 600 x 800 x 300 mm, J = 80 mm.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Steel wall-mounting enclosures

Perforated rails on plain door*



1 Perforations in steps of 25 mm.
2 1 M6 x 17.5 mm earthing stud.

* The glazed doors are equipped with a vertical cable guide, on the hinge side.

Enclosure**		Perforated rails on the door				Perforated rails on the double door				Perforated rails on the internal door			
Height (mm)	Width (mm)	Vertical (mm)		Horizontal (mm)		Vertical (mm)		Horizontal (mm)		Vertical (mm)		Horizontal (mm)	
		F	D	E	C	F	D	E	C	F	D	E	C
400	300	320	237	-	-	-	-	-	-	-	-	-	-
400	400	320	337	-	-	-	-	-	-	-	-	-	-
400	600	320	537	-	-	-	-	-	-	-	-	-	-
500	300	370	237	-	-	-	-	-	-	-	-	-	-
500	400	370	337	-	-	-	-	-	-	-	-	-	-
500	500	370	437	-	-	-	-	-	-	-	-	-	-
600	400	370	337	-	-	-	-	-	-	-	-	-	-
600	500	370	437	-	-	-	-	-	-	-	-	-	-
600	600	370	537	-	-	-	-	-	-	-	-	-	-
600	800	370	737	-	-	-	-	-	-	-	-	-	-
700	500	470	437	-	-	-	-	-	-	-	-	-	-
800	600	570	537	-	-	-	-	-	-	-	-	-	-
800	800	570	737	620	749	-	-	-	-	-	-	-	-
800	1000	570	937	820	749	570	437	320	749	620	437	320	749
800	1200	-	-	-	-	570	537	420	749	620	537	420	749
1000	600	770	537	420	949	-	-	-	-	-	-	-	-
1000	800	770	737	620	949	-	-	-	-	-	-	-	-
1000	1000	770	937	820	949	770	437	320	949	820	437	320	949
1000	1200	-	-	-	-	770	537	420	949	820	537	420	949
1200	600	970	537	420	1149	-	-	-	-	-	-	-	-
1200	800	970	737	620	1149	-	-	-	-	-	-	-	-
1200	1000	970	937	820	1149	970	437	320	1149	1020	437	320	1149
1200	1200	-	-	-	-	970	537	420	1149	1020	537	420	1149
1400	1000	-	-	-	-	970	437	320	1349	1020	437	320	1349

** The doors of enclosures with dimensions of less than 800 x 600 mm do not have horizontal cable guides.

Download the configuration sheets and DXF diagrams from www.se.com
Send them back to your local Schneider Electric office.
Take advantage of a shorter delivery time!

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Installation of 2 mounting plates in the enclosures with width of 1000 or 1200 mm and depth of 300 or 400 mm

Step slides, page 243.

1 On the 6 backstuds



2 Two offset mounting plates with depthwise adjustment







Detail A

1 Left mounting plate
2 Right mounting plate
3 Central backstud
4 Bracket ref. **NSYCRNGSDR** with 2 M8 x 20 mm screws
5 Step slide ref. **NSYSDRSDCR300** (depth 300 mm), **NSYSDRSDCR400** (depth 400 mm)
6 M8 x 20 mm screw

Installation of Telequick mounting plates

Spacers for raising the mounting plate in the enclosures equipped with 6 studs.





Reference **NSYEMR**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Steel wall-mounting enclosures

Acceptable loads on the mounting plates, bases and doors

Spacial 3D wall-mounting enclosures

Acceptable loads (kg)					
On plain mounting plates	On base	On door *	On vertical lug	On horizontal lug	References
60	135	50	350	190	**NSYS3D3215** to **NSYS3D5320**
90	135	50	350	190	**NSYS3D5420** to **NSYS3D6425**
135	135	50	350	190	**NSYS3D6620** to **NSYS3D8630**
150	135	50	350	190	**NSYS3D10625** to **NSYS3D10830**
180	135	50	350	190	**NSYS3D101030D** to **NSYS3D141030D**

* On a sheet door with a thickness of 20/10e mm: 60 kg of maximum acceptable load (please consult us).

Areas without cut-outs



- For 800, 1000 and 1200 mm widths, 2 cable gland plates: See previous page.
- Vertical cable guides from 400 mm height.
- Horizontal cable guides from 800 mm width.
- Download our DXF diagrams from our websites.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

EMC protection



Standard Spacial S3D enclosures are tested against electromagnetic disruptions. Since the enclosure is tested empty, it is advisable to rerun the tests with the enclosure completely equipped in its final configuration.

Earth braids to be ordered separately, see page 305.

Another solution and information on electromagnetic compatibility: Spacial S3HF enclosure, page 476.

Attenuation curve of the Spacial S3D compared with the Spacial S3HF



Frequency: 3 - 13.2 Hz
Amplitude: 1 mm/sec below 22 Hz
Frequency: 3 - 100 Hz
Acceleration: 0.7 g above 30 Hz

Vibration constraints
Specific construction of the Spacial S3D - Single-piece body (cross-shaped structure). The rear is flat without added parts - this allows it to comply with certain vibration constraints. The tests were conducted according to the "rules for ships" by "Det Norske Veritas". Enclosures labelled "DNV" have undergone these tests and obtained classification "A". Since the enclosure is tested empty, it is advisable to rerun the tests with the enclosure completely equipped in its final configuration.

Seismic constraint
The seismic behavior of the the wall-mounting enclosure Spacial S3D have been qualified according to MRI spectra "big material" specified in the standard IEC 60068-2-6 and IEC 60068-2-57 (see page 430 for more details).
Tested enclosure configuration:
- Plain door,
- Plain mounting plate with a load of 250 kg/m² uniformly distributed on the mounting plate,
- Fixing to the wall with M8 screws (tightening torque: 12 Nm ± 1 Nm).

Level of the seismic behavior obtained:
- 2.5G for enclosure with the following dimensions: height ≥ 700 mm, height = 600 mm and width ≥ 600 mm
- 3G for other dimensions.

ATEX compliance
The Spacial S3D enclosure (with adaptation) is certified ATEX by the LCIE.

Environnemental consideration
Compliance with RoHS standard.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Steel wall-mounting enclosures

Post fixing device for Spacial steel enclosure





Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Mounting rail



With quick fixing cross rail



Ease of installation

Door switch mounting possibility



With DIN rail



With light cross rails and cage nut



Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Steel wall-mounting enclosures

Standard cable gland plate



Width (A)	Depth (B)	Standard References	Aluminium References
140	80	**NSYTLA**	**NSYTLAU**
245	80	**NSYTLB**	**NSYTLBU**
245	130	**NSYTLC**	**NSYTLCU**
345	130	**NSYTLD**	**NSYTLDU**
445	130	**NSYTLE**	**NSYTLEU**
545	130	**NSYTLF**	**NSYTLFU**
495	220	**NSYTLG**	**NSYTLGU**
345	130	2x **NSYTLD**	2x **NSYTLDU**
445	130	2x **NSYTLE**	2x **NSYTLEU**

Cable gland plates with FL type cut-out for cable gland membranes



NSYTLBFL, NSYTLCFL, NSYTLDFL, NSYTLEFL, NSYTLFFL, NSYTGBFL,



NSYTLBFL, NSYTLG2FL



NSYTLBFL



NSYTLBFL

Width (A)	Depth (B)	References
140	80	**NSYTLAFL**
245	80	**NSYTLBFL**
245	130	**NSYTLCFL**
345	130	**NSYTLDFL**
445	130	**NSYTLEFL**
545	130	**NSYTLFFL**
545	130	**NSYTLF2FL**
495	220	**NSYTLGFL**
495	220	**NSYTLG2FL**
495	220	**NSYTLG4FL**
345	130	2x **NSYTLDFL**
445	130	2x **NSYTLEFL**

Internal door



1 Installation on the front of the enclosure or
2 installation on step slides
3 Dimension resulting from installation on step slides: B-83 mm.
Dimension resulting from direct installation (without step slides): B-91 mm

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Compact enclosures Spacial SM

Suitable enclosures Spacial SF - Assembled supply

Life Is On Schneider Electric

Steel floor-standing enclosures

Spacial SM-SF

Introduction	82
Characteristics	84
Selection guide	86
Accessories	92
Dimensions	120

Multi-purpose IP55 compact steel enclosure for fast and simple solutions.

This range can be configured according to your needs

4 differents services available:

Assemble to order

Mounting of standard accessories

Painting

Machining

SM

Robust

- Body made as a single piece with welded rear panel.
- Front part forming a rigid frame with welded corners.

Protection

- IP guaranteed by the rigidity of the enclosure, the expanded-polyurethane sealing gasket of the enclosure and the subsequent welding.
- Double door enclosures with inner lock on the left door.

Practical

- Door rails, which can be height-adjustable and used for fixing cables.
- Can be installed adaptation profile in the front and rear of the enclosure and the universal 40 mm cross rail (1 row) in the rear provide the same fixing points as the modular enclosure.



Comfort

- Handle with sturdy design for easily activating the locking system, allowing the installation of any shape insert and any cylindrical combination key.
- Easily interchangeable insert with one click.

See page 532 for details or consult our web site www.se.com

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Adapts to all your needs. Assembled delivery for a ready-to-use solution.

SF

Adapts to customer needs. Delivered as kit, with up to 600 different possible configurations.

SF kit



Volume of packaging in kit supply

Assembled supply



Robust

- Structure formed from a single 15/10e mm
- galvanised steel section, with a high rigidity.
- Vertical uprights screwed together with connections of full steel. Placement and screwing of the 4 vertical uprights at the corners of the top and bottom frames. Fixing by 8 screws, one at each corner of the enclosure.
- Capable of withstanding 1000 kg distributed in its volume.



Fast

- The double system of cut-outs on the structure allows most accessories to be installed using self-tapping TORX T30 M6 screws or nuts.
- Clip-on quick fixing cross rails, fixed with self-tapping screws.
- Door installation inserting the captive pins of the hinge in their housing in the door.



Reliable

- The design of the profile creates a double protective barrier against the entry of water and dust when coupling two enclosures.
- The first barrier is the metal connection of the sections, and the second barrier is the EPDM gasket that helps guarantee the sealing.

Practical

- Suspension of the rear panel using a self-centring piece to facilitate screwing.



Aesthetics

- The built-in panels and handle with new design give the enclosure a new appearance.



Simple

The new design allows enclosures to be coupled in any direction, adapting to all installation surfaces.

Comfort

- Handle with robust design for easily activating the locking system, allowing the installation of any shape insert and any cylindrical combination key.
- Panels with captive screws for easier assembly and dismantling.

Accessible

The symmetric design of the profile allows doors to be installed on any side of the enclosure, opening to right or left, providing full accessibility to the enclosure.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Steel floor-standing enclosures

SM

Characteristics	Compact enclosures Spacial SM
	• Compact body with a front rigid frame with welded corners and rear panel supports installed in depth to adjust and fix the equipment with a pitch of 25 mm
Basic composition	• The double doors are overlapping, with system for fixing the left door • Door reversible, 120° opening • Welded rear panel • 4 locking points system with handle 5 mm double bar insert • Cable gland plate 1 entry • Mounting plate support brackets
Versions / Configurations	• Compact enclosure with plain door and mounting plate • Compact enclosure with plain door and without mounting plate • Compact enclosure with transparent Securit® glass door and without mounting plate
Protection of personnel	Earthing accessories needed to help ensure the grounding continuity, page 305
Material	Steel
Finish	Structured finish, epoxy polyester powder
Colour	RAL 7035 grey
Ingress protection rating	IP55 according to IEC 60529
Mechanical protection rating	IK10 for plain door and IK08 for transparent door according to IEC 62262
Standards	Compliance with enclosure standard IEC 62208 and the RoHS and REACH directive
Certifications	BV, DNV, UL * and cUL, *1 door: 1, 2, 3R, 4, 5 and 13, * 2 doors: 1, 12
Installation	Indoor / Outdoor* installation * Compliant with IEC 62208 regarding type tests specified in §9.12 (resistance to UV radiation) and §9.13 (resistance to corrosion) Outdoor installation: Canopy needed to avoid water stagnation on the upper part of the enclosure, page 107
Maximum load	500 kg
Options	• Plinths, heights 100 mm and 200 mm, page 98 • Lifting eyebolts, page 106 • Internal door, page 111 • Door accessories, page 113 • Other locking options, page 116 • Mounting plates and Telequick system, page 245

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

SF

SF kit

Suitable enclosures Spacial SF - Assembled supply	Suitable enclosures Spacial SF - Supplied as a kit
• Structure made up of vertical uprights joined with top and bottom frames • Panels and doors built into the structure • Formed from a single section and perforated structure with a pitch of 25 mm	
• Front door with a reinforcement frame (horizontal rails height-adjustable) • The double doors are overlapping, with system for fixing the left door • Door reversible, 120° opening • Rear panel screwed on with captive screws • Removable roof • 4 locking points system with handle 5 mm double bar insert • Mounting plate support brackets • Mounting plate sliding rails • 2 quick fixing cross rails	• Front door with a reinforcement frame (horizontal rails height-adjustable) • The double doors are overlapping, with system for fixing the left door • Door reversible, 120° opening • Rear panel to be screwed on with captive screws • Removable roof delivered with top frame • 4 locking points system with handle 5 mm double bar insert • Mounting plate support brackets delivered with top and bottom frames kit • Mounting plate sliding rails delivered with top and bottom frames kit • 2 quick fixing cross rails delivered with top and bottom frames kit
• Modular enclosure with plain door and mounting plate • Modular enclosure with plain door and without mounting plate • Modular enclosure with transparent Securit® glass door and without mounting plate	• Uprights kit • Top and bottom frames kit • Rear panel kit • Door kit (plain or transparent)
Earthing accessories needed to help ensure the grounding continuity	
Steel	
Structured finish, epoxy polyester powder	
RAL 7035 grey	
IP55 according to IEC 60529	
IK10 for plain door and IK08 for transparent door according to IEC 62262	
Compliance with enclosure standard IEC 62208 and the RoHS and REACH directive	
BV, DNV-GL, UL and cUL*, *1 door: 1, 3R, 12, 12K, *2 doors: 1, 3R, 12	
1000 kg	
• Side panels options, page 94 • Enclosure suites options, page 95 • Plinths, heights 100 mm and 200 mm, page 96 • Cable gland plates, page 102 • Lifting systems, page 106 • Roof options, page 108 • Door accessories, page 113 • Other locking options, page 116 • Mounting plates and Telequick system, page 245	• Side panels options, page 94 • Enclosure suites options, page 95 • Plinths, heights 100 mm and 200 mm, page 96 • Cable gland plates, page 102 • Lifting systems, page 106 • Roof options, page 108 • Other locking options, page 116 • Mounting plates and Telequick system, page 245

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

SM Steel floor-standing enclosures

Dimensions				Enclosures			Plinth (H 100 mm)	
								
Height (mm)	Width (mm)	Depth (mm)	Doors	Plain door, without mounting plate	Plain door, with mounting plate	Transparent door, without mounting plate	Front kit (corners + front panels)	Side panels, 2 pieces
1200	800	300	1	NSYSM12830	NSYSM12830P	-	NSYSPF8100	NSYSPS3100
1200	1000	300	2	NSYSM1210302D	NSYSM1210302DP	-	NSYSPF10100	NSYSPS3100
1200	1200	400	2	NSYSM1212402D	NSYSM1212402DP	-	NSYSPF12100	NSYSPS4100
1400	600	300	1	NSYSM14630	NSYSM14630P	-	NSYSPF6100	NSYSPS3100
1400	600	400	1	NSYSM14640	NSYSM14640P	-	NSYSPF6100	NSYSPS4100
1400	800	300	1	NSYSM14830	NSYSM14830P	-	NSYSPF8100	NSYSPS3100
1400	800	400	1	NSYSM14840	NSYSM14840P	NSYSM14840T	NSYSPF8100	NSYSPS4100
1400	1000	400	2	NSYSM1410402D	NSYSM1410402DP	-	NSYSPF10100	NSYSPS4100
1400	1200	400	2	NSYSM1412402D	NSYSM1412402DP	-	NSYSPF12100	NSYSPS4100
1600	600	300	1	NSYSM16630	NSYSM16630P	-	NSYSPF6100	NSYSPS3100
1600	600	400	1	NSYSM16640	NSYSM16640P	NSYSM16640T	NSYSPF6100	NSYSPS4100
1600	800	300	1	NSYSM16830	NSYSM16830P	NSYSM16830T	NSYSPF8100	NSYSPS3100
1600	800	400	1	NSYSM16840	NSYSM16840P	NSYSM16840T	NSYSPF8100	NSYSPS4100
1600	1000	300	2	NSYSM1610302D	NSYSM1610302DP	-	NSYSPF10100	NSYSPS3100
1600	1000	400	2	NSYSM1610402D	NSYSM1610402DP	-	NSYSPF10100	NSYSPS4100
1600	1200	300	2	NSYSM1612302D	NSYSM1612302DP	-	NSYSPF12100	NSYSPS3100
1600	1200	400	2	NSYSM1612402D	NSYSM1612402DP	-	NSYSPF12100	NSYSPS4100
1800	600	300	1	NSYSM18630	NSYSM18630P	-	NSYSPF6100	NSYSPS3100
1800	600	400	1	NSYSM18640	NSYSM18640P	NSYSM18640T	NSYSPF6100	NSYSPS4100
1800	600	500	1	NSYSM18650	NSYSM18650P	-	NSYSPF6100	NSYSPS5100
1800	800	300	1	NSYSM18830	NSYSM18830P	NSYSM18830T	NSYSPF8100	NSYSPS3100
1800	800	400	1	NSYSM18840	NSYSM18840P	NSYSM18840T	NSYSPF8100	NSYSPS4100
1800	800	500	1	NSYSM18850	NSYSM18850P	NSYSM18850T	NSYSPF8100	NSYSPS5100
1800	800	600	1	NSYSM18860	NSYSM18860P	-	NSYSPF8100	NSYSPS6100
1800	1000	400	1	NSYSM181040	NSYSM181040P	-	NSYSPF10100	NSYSPS4100
1800	1000	400	2	NSYSM1810402D	NSYSM1810402DP	-	NSYSPF10100	NSYSPS4100
1800	1000	500	2	NSYSM1810502D	NSYSM1810502DP	-	NSYSPF10100	NSYSPS5100
1800	1200	400	2	NSYSM1812402D	NSYSM1812402DP	-	NSYSPF12100	NSYSPS4100
1800	1200	500	2	NSYSM1812502D	NSYSM1812502DP	-	NSYSPF12100	NSYSPS5100
1800	1600	400	2	NSYSM1816402D	NSYSM1816402DP	-	NSYSPF16100	NSYSPS4100
1800	1600	500	2	NSYSM1816502D	NSYSM1816502DP	-	NSYSPF16100	NSYSPS5100
2000	600	300	1	NSYSM20630	NSYSM20630P	-	NSYSPF6100	NSYSPS3100
2000	600	400	1	NSYSM20640	NSYSM20640P	NSYSM20640T	NSYSPF6100	NSYSPS4100
2000	600	500	1	NSYSM20650	NSYSM20650P	-	NSYSPF6100	NSYSPS5100
2000	800	300	1	NSYSM20830	NSYSM20830P	NSYSM20830T	NSYSPF8100	NSYSPS3100
2000	800	400	1	NSYSM20840	NSYSM20840P	NSYSM20840T	NSYSPF8100	NSYSPS4100
2000	800	500	1	NSYSM20850	NSYSM20850P	NSYSM20850T	NSYSPF8100	NSYSPS5100
2000	800	600	1	NSYSM20860	NSYSM20860P	NSYSM20860T	NSYSPF8100	NSYSPS6100
2000	1000	400	2	NSYSM2010402D	NSYSM2010402DP	-	NSYSPF10100	NSYSPS4100
2000	1000	500	2	NSYSM2010502D	NSYSM2010502DP	-	NSYSPF10100	NSYSPS5100
2000	1200	400	2	NSYSM2012402D	NSYSM2012402DP	-	NSYSPF12100	NSYSPS4100
2000	1200	500	2	NSYSM2012502D	NSYSM2012502DP	-	NSYSPF12100	NSYSPS5100
2000	1200	600	2	NSYSM2012602D	NSYSM2012602DP	-	NSYSPF12100	NSYSPS6100
2000	1600	400	2	NSYSM2016402D	NSYSM2016402DP	-	NSYSPF16100	NSYSPS4100
2000	1600	500	2	NSYSM2016502D	NSYSM2016502DP	-	NSYSPF16100	NSYSPS5100
2000	1600	600	2	NSYSM2016602D	NSYSM2016602DP	-	NSYSPF16100	NSYSPS6100

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Plinth (H 200 mm)		Inner door	Mounting plate	Vertical uprights		19" swing rack	
							
Front kit (corners + front panels)	Side panels, 4 pieces	Plain door	Galvanized	Standard	Technical	Off-centre	Centred
NSYSPF8200	NSYSPS3200	-	NSYMP128	-	NSYTVR12	-	-
NSYSPF10200	NSYSPS3200	-	NSYMP1210	-	NSYTVR12	-	-
NSYSPF12200	NSYSPS4200	-	NSYMP1212	-	NSYTVR12	-	-
NSYSPF6200	NSYSPS3200	-	NSYMP146	-	NSYTVR14	-	-
NSYSPF6200	NSYSPS4200	-	NSYMP146	-	NSYTVR14	-	-
NSYSPF8200	NSYSPS3200	-	NSYMP148	-	NSYTVR14	NSYRSW27	NSYRSWC27
NSYSPF8200	NSYSPS4200	-	NSYMP148	-	NSYTVR14	NSYRSW27	NSYRSWC27
NSYSPF10200	NSYSPS4200	-	NSYMP1410	-	NSYTVR14	-	-
NSYSPF12200	NSYSPS4200	-	NSYMP1412	-	NSYTVR14	-	-
NSYSPF6200	NSYSPS3200	NSYID166	NSYMP166	-	NSYTVR16	-	-
NSYSPF6200	NSYSPS4200	NSYID166	NSYMP166	-	NSYTVR16	-	-
NSYSPF8200	NSYSPS3200	NSYID168	NSYMP168	-	NSYTVR16	NSYRSW31	NSYRSWC31
NSYSPF8200	NSYSPS4200	NSYID168	NSYMP168	-	NSYTVR16	NSYRSW31	NSYRSWC31
NSYSPF10200	NSYSPS3200	-	NSYMP1610	-	NSYTVR16	-	-
NSYSPF10200	NSYSPS4200	-	NSYMP1610	-	NSYTVR16	-	-
NSYSPF12200	NSYSPS3200	-	NSYMP1612	-	NSYTVR16	-	-
NSYSPF12200	NSYSPS4200	-	NSYMP1612	-	NSYTVR16	-	-
NSYSPF6200	NSYSPS3200	NSYID186	NSYMP186	NSYVR18	NSYTVR18	-	-
NSYSPF6200	NSYSPS4200	NSYID186	NSYMP186	NSYVR18	NSYTVR18	-	-
NSYSPF6200	NSYSPS5200	NSYID186	NSYMP186	NSYVR18	NSYTVR18	-	-
NSYSPF8200	NSYSPS3200	NSYID188	NSYMP188	NSYVR18	NSYTVR18	NSYRSW36	NSYRSWC36
NSYSPF8200	NSYSPS4200	NSYID188	NSYMP188	NSYVR18	NSYTVR18	NSYRSW36	NSYRSWC36
NSYSPF8200	NSYSPS5200	NSYID188	NSYMP188	NSYVR18	NSYTVR18	NSYRSW36	NSYRSWC36
NSYSPF8200	NSYSPS6200	NSYID188	NSYMP188	NSYVR18	NSYTVR18	NSYRSW36	NSYRSWC36
NSYSPF10200	NSYSPS4200	NSYID1810	NSYMP1810	NSYVR18	NSYTVR18	-	-
NSYSPF10200	NSYSPS4200	NSYID1810	NSYMP1810	NSYVR18	NSYTVR18	-	-
NSYSPF10200	NSYSPS5200	NSYID1810	NSYMP1810	NSYVR18	NSYTVR18	-	-
NSYSPF12200	NSYSPS4200	-	NSYMP1812	NSYVR18	NSYTVR18	-	-
NSYSPF12200	NSYSPS5200	-	NSYMP1812	NSYVR18	NSYTVR18	-	-
NSYSPF16200	NSYSPS4200	-	NSYMP1816	NSYVR18	NSYTVR18	-	-
NSYSPF16200	NSYSPS5200	-	NSYMP1816	NSYVR18	NSYTVR18	-	-
NSYSPF6200	NSYSPS3200	NSYID206	NSYMP206	NSYVR20	NSYTVR20	-	-
NSYSPF6200	NSYSPS4200	NSYID206	NSYMP206	NSYVR20	NSYTVR20	-	-
NSYSPF6200	NSYSPS5200	NSYID206	NSYMP206	NSYVR20	NSYTVR20	-	-
NSYSPF8200	NSYSPS3200	NSYID208	NSYMP208	NSYVR20	NSYTVR20	NSYRSW40	NSYRSWC40
NSYSPF8200	NSYSPS4200	NSYID208	NSYMP208	NSYVR20	NSYTVR20	NSYRSW40	NSYRSWC40
NSYSPF8200	NSYSPS5200	NSYID208	NSYMP208	NSYVR20	NSYTVR20	NSYRSW40	NSYRSWC40
NSYSPF8200	NSYSPS6200	NSYID208	NSYMP208	NSYVR20	NSYTVR20	NSYRSW40	NSYRSWC40
NSYSPF10200	NSYSPS4200	NSYID2010	NSYMP2010	NSYVR20	NSYTVR20	-	-
NSYSPF10200	NSYSPS5200	NSYID2010	NSYMP2010	NSYVR20	NSYTVR20	-	-
NSYSPF12200	NSYSPS4200	-	NSYMP2012	NSYVR20	NSYTVR20	-	-
NSYSPF12200	NSYSPS5200	-	NSYMP2012	NSYVR20	NSYTVR20	-	-
NSYSPF12200	NSYSPS6200	-	NSYMP2012	NSYVR20	NSYTVR20	-	-
NSYSPF16200	NSYSPS4200	-	NSYMP2016	NSYVR20	NSYTVR20	-	-
NSYSPF16200	NSYSPS5200	-	NSYMP2016	NSYVR20	NSYTVR20	-	-
NSYSPF16200	NSYSPS6200	-	NSYMP2016	NSYVR20	NSYTVR20	-	-

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

SF Steel floor-standing enclosures

Dimensions				Enclosures			Side panels	Cable entry plates		
(A)	(B)	(C)								
Height (mm)	Width (mm)	Depth (mm)	Doors	Plain door, without mounting plate	Plain door, with mounting plate	Transparent door, without mounting plate	Standard	Plain	1 entry	2 entries
1200	600	400	1	NSYSF12640	NSYSF12640P	-	NSY2SP124	NSYEC64	NSYEC641	-
1200	600	600	1	NSYSF12660	NSYSF12660P	-	NSY2SP126	NSYEC66	NSYEC661	NSYEC662
1200	800	400	1	NSYSF12840	NSYSF12840P	-	NSY2SP124	NSYEC84	NSYEC841	-
1200	800	600	1	NSYSF12860	NSYSF12860P	-	NSY2SP126	NSYEC86	NSYEC861	NSYEC862
1400	600	400	1	NSYSF14640	NSYSF14640P	-	NSY2SP144	NSYEC64	NSYEC641	-
1400	800	400	1	NSYSF14840	NSYSF14840P	-	NSY2SP144	NSYEC84	NSYEC841	-
1600	600	600	1	NSYSF16660	NSYSF16660P	-	NSY2SP166	NSYEC66	NSYEC661	NSYEC662
1600	600	800	1	NSYSF16680	NSYSF16680P	-	NSY2SP168	NSYEC68	NSYEC681	NSYEC682
1600	800	600	1	NSYSF16860	NSYSF16860P	-	NSY2SP166	NSYEC86	NSYEC861	NSYEC862
1600	800	800	1	NSYSF16880	NSYSF16880P	-	NSY2SP168	NSYEC88	NSYEC881	NSYEC882
1800	400	400	1	NSYSF18440	-	-	NSY2SP184	NSYEC44	NSYEC441	-
1800	400	500	1	NSYSF18450	-	-	NSY2SP185	NSYEC45	NSYEC451	-
1800	400	600	1	NSYSF18460	-	-	NSY2SP186	-	NSYEC461	-
1800	600	400	1	NSYSF18640	NSYSF18640P	NSYSF18640T	NSY2SP184	NSYEC64	NSYEC641	-
1800	600	500	1	NSYSF18650	NSYSF18650P	NSYSF18650T	NSY2SP185	NSYEC65	NSYEC651	-
1800	600	600	1	NSYSF18660	NSYSF18660P	-	NSY2SP186	NSYEC66	NSYEC661	NSYEC662
1800	600	800	1	-	-	NSYSF18680T	NSY2SP188	NSYEC68	NSYEC681	NSYEC682
1800	800	400	1	NSYSF18840	NSYSF18840P	NSYSF18840T	NSY2SP184	NSYEC84	NSYEC841	-
1800	800	500	1	NSYSF18850	NSYSF18850P	NSYSF18850T	NSY2SP185	NSYEC85	NSYEC851	-
1800	800	600	1	NSYSF18860	NSYSF18860P	NSYSF18860T	NSY2SP186	NSYEC86	NSYEC861	NSYEC862
1800	800	600	2	NSYSF188602D	NSYSF188602DP	-	NSY2SP186	NSYEC86	NSYEC861	NSYEC862
1800	1000	400	1	NSYSF181040	NSYSF181040P	-	NSY2SP184	NSYEC104	NSYEC1041	-
1800	1000	400	2	NSYSF1810402D	NSYSF1810402DP	-	NSY2SP184	NSYEC104	NSYEC1041	-
1800	1000	500	1	NSYSF181050	NSYSF181050P	-	NSY2SP185	NSYEC105	NSYEC1051	-
1800	1000	600	1	NSYSF181060	NSYSF181060P	-	NSY2SP186	NSYEC106	NSYEC1061	NSYEC1062
1800	1000	600	2	NSYSF1810602D	NSYSF1810602DP	-	NSY2SP186	NSYEC106	NSYEC1061	NSYEC1062
1800	1200	400	2	NSYSF1812402D	NSYSF1812402DP	-	NSY2SP184	NSYEC124	NSYEC1241	-
1800	1200	500	2	NSYSF1812502D	NSYSF1812502DP	-	NSY2SP185	NSYEC125	NSYEC1251	-
1800	1200	600	2	NSYSF1812602D	NSYSF1812602DP	-	NSY2SP186	NSYEC126	NSYEC1261	NSYEC1262
2000	300	500	1	NSYSF20350	-	-	NSY2SP205	NSYEC35	NSYEC351	-
2000	300	600	1	NSYSF20360	-	-	NSY2SP206	NSYEC36	NSYEC361	-
2000	300	800	1	NSYSF20380	-	-	NSY2SP208	-	NSYEC381	-
2000	400	400	1	NSYSF20440	-	-	NSY2SP204	NSYEC44	NSYEC441	-
2000	400	500	1	NSYSF20450	-	-	NSY2SP205	NSYEC45	NSYEC451	-
2000	400	600	1	NSYSF20460	-	-	NSY2SP206	NSYEC64	NSYEC461	-
2000	400	800	1	NSYSF20480	-	-	NSY2SP208	NSYEC84	NSYEC481	-
2000	600	400	1	NSYSF20640	NSYSF20640P	NSYSF20640T	NSY2SP204	NSYEC64	NSYEC641	-
2000	600	500	1	NSYSF20650	NSYSF20650P	NSYSF20650T	NSY2SP205	NSYEC65	NSYEC651	-
2000	600	600	1	NSYSF20660	NSYSF20660P	-	NSY2SP206	NSYEC66	NSYEC661	NSYEC662
2000	600	800	1	NSYSF20680	NSYSF20680P	-	NSY2SP208	NSYEC68	NSYEC681	NSYEC682
2000	800	400	1	NSYSF20840	NSYSF20840P	NSYSF20840T	NSY2SP204	NSYEC84	NSYEC841	-
2000	800	500	1	NSYSF20850	NSYSF20850P	NSYSF20850T	NSY2SP205	NSYEC85	NSYEC851	-
2000	800	600	1	NSYSF20860	NSYSF20860P	NSYSF20860T	NSY2SP206	NSYEC86	NSYEC861	NSYEC862
2000	800	600	2	NSYSF208602D	NSYSF208602DP	-	NSY2SP206	NSYEC86	NSYEC861	NSYEC862
2000	800	800	1	NSYSF20880	NSYSF20880P	NSYSF20880T	NSY2SP208	NSYEC88	NSYEC881	NSYEC882
2000	1000	400	1	NSYSF201040	NSYSF201040P	NSYSF201040T	NSY2SP204	NSYEC104	NSYEC1041	-
2000	1000	400	2	NSYSF2010402D	NSYSF2010402DP	-	NSY2SP204	NSYEC104	NSYEC1041	-
2000	1000	500	1	NSYSF201050	NSYSF201050P	NSYSF201050T	NSY2SP205	NSYEC105	NSYEC1051	-
2000	1000	500	2	NSYSF2010502D	NSYSF2010502DP	-	NSY2SP205	NSYEC105	NSYEC1051	-
2000	1000	600	1	NSYSF201060	NSYSF201060P	NSYSF201060T	NSY2SP206	NSYEC106	NSYEC1061	NSYEC1062
2000	1000	600	2	NSYSF2010602D	NSYSF2010602DP	-	NSY2SP206	NSYEC106	NSYEC1061	NSYEC1062
2000	1000	800	1	NSYSF201080	NSYSF201080P	-	NSY2SP208	NSYEC108	NSYEC1081	NSYEC1082
2000	1200	400	2	NSYSF2012402D	NSYSF2012402DP	-	NSY2SP204	NSYEC124	NSYEC1241	-
2000	1200	500	2	NSYSF2012502D	NSYSF2012502DP	-	NSY2SP205	NSYEC125	NSYEC1251	-
2000	1200	600	2	NSYSF2012602D	NSYSF2012602DP	-	NSY2SP206	NSYEC126	NSYEC1261	NSYEC1262
2000	1200	800	2	NSYSF2012802D	NSYSF2012802DP	-	NSY2SP208	NSYEC128	NSYEC1281	NSYEC1282
2000	1600	400	2	NSYSF2016402D	NSYSF2016402DP	-	NSY2SP204	NSYEC164	NSYEC1641	-
2000	1600	500	2	NSYSF2016502D	NSYSF2016502DP	-	NSY2SP205	NSYEC165	NSYEC1651	-
2000	1600	600	2	NSYSF2016602D	NSYSF2016602DP	-	NSY2SP206	NSYEC166	NSYEC1661	NSYEC1662
2200	400	600	1	NSYSF22460	-	-	NSY2SP226	-	NSYEC461	-
2200	600	600	1	NSYSF22660	NSYSF22660P	-	NSY2SP226	NSYEC66	NSYEC661	NSYEC662
2200	600	800	1	NSYSF22680	NSYSF22680P	-	NSY2SP228	NSYEC68	NSYEC681	NSYEC682
2200	800	600	1	NSYSF22860	NSYSF22860P	-	NSY2SP226	NSYEC86	NSYEC861	NSYEC862
2200	800	800	1	NSYSF22880	NSYSF22880P	NSYSF22880T	NSY2SP228	NSYEC88	NSYEC881	NSYEC882
2200	1000	600	1	NSYSF221060	NSYSF221060P	-	NSY2SP226	NSYEC106	NSYEC1061	NSYEC1062
2200	1200	600	2	NSYSF2212602D	NSYSF2212602DP	-	NSY2SP226	NSYEC126	NSYEC1261	NSYEC1262
2200	1200	800	2	NSYSF2212802D	NSYSF2212802DP	-	NSY2SP228	NSYEC128	NSYEC1281	NSYEC1282

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Plinths (H 100 mm)		Plinths (H 200 mm)		Mounting plates		Vertical uprights	
							
Front kit (corners + front panels)	Side panels, 2 u.	Front kit (corners + front panels)	Side panels, 4 u.	Mounting plate	Intermediate mounting plate	Standard	Technical
NSYSPF6100	NSYSPS4100	NSYSPF6200	NSYSPS4200	NSYMP126	NSYSIMP12	-	NSYTVR12
NSYSPF6100	NSYSPS6100	NSYSPF6200	NSYSPS6200	NSYMP126	NSYSIMP12	-	NSYTVR12
NSYSPF8100	NSYSPS4100	NSYSPF8200	NSYSPS4200	NSYMP128	NSYSIMP12	-	NSYTVR12
NSYSPF8100	NSYSPS6100	NSYSPF8200	NSYSPS6200	NSYMP128	NSYSIMP12	-	NSYTVR12
NSYSPF6100	NSYSPS4100	NSYSPF6200	NSYSPS4200	NSYMP146	NSYSIMP14	-	NSYTVR14
NSYSPF8100	NSYSPS4100	NSYSPF8200	NSYSPS4200	NSYMP148	NSYSIMP14	-	NSYTVR14
NSYSPF6100	NSYSPS6100	NSYSPF6200	NSYSPS6200	NSYMP166	NSYSIMP16	-	NSYTVR16
NSYSPF6100	NSYSPS8100	NSYSPF6200	NSYSPS8200	NSYMP166	NSYSIMP16	-	NSYTVR16
NSYSPF8100	NSYSPS6100	NSYSPF8200	NSYSPS6200	NSYMP168	NSYSIMP16	-	NSYTVR16
NSYSPF8100	NSYSPS8100	NSYSPF8200	NSYSPS8200	NSYMP168	NSYSIMP16	-	NSYTVR16
NSYSPF4100	NSYSPS4100	NSYSPF4200	NSYSPS4200	NSYMP184 New	-	NSYVR18	NSYTVR18
NSYSPF4100	NSYSPS5100	NSYSPF4200	NSYSPS5200	NSYMP184 New	-	NSYVR18	NSYTVR18
NSYSPF4100	NSYSPS6100	NSYSPF4200	NSYSPS6200	NSYMP184 New	-	NSYVR18	NSYTVR18
NSYSPF6100	NSYSPS4100	NSYSPF6200	NSYSPS4200	NSYMP186	NSYSIMP18	NSYVR18	NSYTVR18
NSYSPF6100	NSYSPS5100	NSYSPF6200	NSYSPS5200	NSYMP186	NSYSIMP18	NSYVR18	NSYTVR18
NSYSPF6100	NSYSPS6100	NSYSPF6200	NSYSPS6200	NSYMP186	NSYSIMP18	NSYVR18	NSYTVR18
NSYSPF6100	NSYSPS8100	NSYSPF6200	NSYSPS8200	NSYMP186	NSYSIMP18	NSYVR18	NSYTVR18
NSYSPF8100	NSYSPS4100	NSYSPF8200	NSYSPS4200	NSYMP188	NSYSIMP18	NSYVR18	NSYTVR18
NSYSPF8100	NSYSPS5100	NSYSPF8200	NSYSPS5200	NSYMP188	NSYSIMP18	NSYVR18	NSYTVR18
NSYSPF8100	NSYSPS6100	NSYSPF8200	NSYSPS6200	NSYMP188	NSYSIMP18	NSYVR18	NSYTVR18
NSYSPF8100	NSYSPS6100	NSYSPF8200	NSYSPS6200	NSYMP188	NSYSIMP18	NSYVR18	NSYTVR18
NSYSPF10100	NSYSPS4100	NSYSPF10200	NSYSPS4200	NSYMP1810	NSYSIMP18	NSYVR18	NSYTVR18
NSYSPF10100	NSYSPS4100	NSYSPF10200	NSYSPS4200	NSYMP1810	NSYSIMP18	NSYVR18	NSYTVR18
NSYSPF10100	NSYSPS5100	NSYSPF10200	NSYSPS5200	NSYMP1810	NSYSIMP18	NSYVR18	NSYTVR18
NSYSPF10100	NSYSPS6100	NSYSPF10200	NSYSPS6200	NSYMP1810	NSYSIMP18	NSYVR18	NSYTVR18
NSYSPF10100	NSYSPS6100	NSYSPF10200	NSYSPS6200	NSYMP1810	NSYSIMP18	NSYVR18	NSYTVR18
NSYSPF12100	NSYSPS4100	NSYSPF12200	NSYSPS4200	NSYMP1812	NSYSIMP18	NSYVR18	NSYTVR18
NSYSPF12100	NSYSPS5100	NSYSPF12200	NSYSPS5200	NSYMP1812	NSYSIMP18	NSYVR18	NSYTVR18
NSYSPF12100	NSYSPS6100	NSYSPF12200	NSYSPS6200	NSYMP1812	NSYSIMP18	NSYVR18	NSYTVR18
NSYSPF3100	NSYSPS5100	NSYSPF3200	NSYSPS5200	-	-	NSYVR20	NSYTVR20
NSYSPF3100	NSYSPS6100	NSYSPF3200	NSYSPS6200	-	-	NSYVR20	NSYTVR20
NSYSPF3100	NSYSPS8100	NSYSPF3200	NSYSPS8200	-	-	NSYVR20	NSYTVR20
NSYSPF4100	NSYSPS4100	NSYSPF4200	NSYSPS4200	NSYMP204 New	-	NSYVR20	NSYTVR20
NSYSPF4100	NSYSPS5100	NSYSPF4200	NSYSPS5200	NSYMP204 New	-	NSYVR20	NSYTVR20
NSYSPF4100	NSYSPS6100	NSYSPF4200	NSYSPS6200	NSYMP204 New	-	NSYVR20	NSYTVR20
NSYSPF4100	NSYSPS8100	NSYSPF4200	NSYSPS8200	NSYMP204 New	-	NSYVR20	NSYTVR20
NSYSPF6100	NSYSPS4100	NSYSPF6200	NSYSPS4200	NSYMP206	NSYSIMP20	NSYVR20	NSYTVR20
NSYSPF6100	NSYSPS5100	NSYSPF6200	NSYSPS5200	NSYMP206	NSYSIMP20	NSYVR20	NSYTVR20
NSYSPF6100	NSYSPS6100	NSYSPF6200	NSYSPS6200	NSYMP206	NSYSIMP20	NSYVR20	NSYTVR20
NSYSPF6100	NSYSPS8100	NSYSPF6200	NSYSPS8200	NSYMP206	NSYSIMP20	NSYVR20	NSYTVR20
NSYSPF8100	NSYSPS4100	NSYSPF8200	NSYSPS4200	NSYMP208	NSYSIMP20	NSYVR20	NSYTVR20
NSYSPF8100	NSYSPS5100	NSYSPF8200	NSYSPS5200	NSYMP208	NSYSIMP20	NSYVR20	NSYTVR20
NSYSPF8100	NSYSPS6100	NSYSPF8200	NSYSPS6200	NSYMP208	NSYSIMP20	NSYVR20	NSYTVR20
NSYSPF8100	NSYSPS6100	NSYSPF8200	NSYSPS6200	NSYMP208	NSYSIMP20	NSYVR20	NSYTVR20
NSYSPF8100	NSYSPS8100	NSYSPF8200	NSYSPS8200	NSYMP208	NSYSIMP20	NSYVR20	NSYTVR20
NSYSPF10100	NSYSPS4100	NSYSPF10200	NSYSPS4200	NSYMP2010	NSYSIMP20	NSYVR20	NSYTVR20
NSYSPF10100	NSYSPS4100	NSYSPF10200	NSYSPS4200	NSYMP2010	NSYSIMP20	NSYVR20	NSYTVR20
NSYSPF10100	NSYSPS5100	NSYSPF10200	NSYSPS5200	NSYMP2010	NSYSIMP20	NSYVR20	NSYTVR20
NSYSPF10100	NSYSPS5100	NSYSPF10200	NSYSPS5200	NSYMP2010	NSYSIMP20	NSYVR20	NSYTVR20
NSYSPF10100	NSYSPS6100	NSYSPF10200	NSYSPS6200	NSYMP2010	NSYSIMP20	NSYVR20	NSYTVR20
NSYSPF10100	NSYSPS6100	NSYSPF10200	NSYSPS6200	NSYMP2010	NSYSIMP20	NSYVR20	NSYTVR20
NSYSPF10100	NSYSPS8100	NSYSPF10200	NSYSPS8200	NSYMP2010	NSYSIMP20	NSYVR20	NSYTVR20
NSYSPF12100	NSYSPS4100	NSYSPF12200	NSYSPS4200	NSYMP2012	NSYSIMP20	NSYVR20	NSYTVR20
NSYSPF12100	NSYSPS5100	NSYSPF12200	NSYSPS5200	NSYMP2012	NSYSIMP20	NSYVR20	NSYTVR20
NSYSPF12100	NSYSPS6100	NSYSPF12200	NSYSPS6200	NSYMP2012	NSYSIMP20	NSYVR20	NSYTVR20
NSYSPF12100	NSYSPS8100	NSYSPF12200	NSYSPS8200	NSYMP2012	NSYSIMP20	NSYVR20	NSYTVR20
NSYSPF16100	NSYSPS4100	NSYSPF16200	NSYSPS4200	NSYMP2016	NSYSIMP20	NSYVR20	NSYTVR20
NSYSPF16100	NSYSPS5100	NSYSPF16200	NSYSPS5200	NSYMP2016	NSYSIMP20	NSYVR20	NSYTVR20
NSYSPF16100	NSYSPS6100	NSYSPF16200	NSYSPS6200	NSYMP2016	NSYSIMP20	NSYVR20	NSYTVR20
NSYSPF4100	NSYSPS6100	NSYSPF4200	NSYSPS6200	NSYMP224 New	-	NSYVR22	NSYTVR22
NSYSPF6100	NSYSPS6100	NSYSPF6200	NSYSPS6200	NSYMP226	NSYSIMP22	NSYVR22	NSYTVR22
NSYSPF6100	NSYSPS8100	NSYSPF6200	NSYSPS8200	NSYMP226	NSYSIMP22	NSYVR22	NSYTVR22
NSYSPF8100	NSYSPS6100	NSYSPF8200	NSYSPS6200	NSYMP228	NSYSIMP22	NSYVR22	NSYTVR22
NSYSPF8100	NSYSPS8100	NSYSPF8200	NSYSPS8200	NSYMP228	NSYSIMP22	NSYVR22	NSYTVR22
NSYSPF10100	NSYSPS6100	NSYSPF10200	NSYSPS6200	NSYMP2210	NSYSIMP22	NSYVR22	NSYTVR22
NSYSPF12100	NSYSPS6100	NSYSPF12200	NSYSPS6200	NSYMP2212	NSYSIMP22	NSYVR22	NSYTVR22
NSYSPF12100	NSYSPS8100	NSYSPF12200	NSYSPS8200	NSYMP2212	NSYSIMP22	NSYVR22	NSYTVR22

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

SF kit Steel floor-standing enclosures

Dimensions				Vertical uprights	Bottom frame and top frame with roof	Panels		Doors		Mounting plate
								(Hinges, locking bar catches and handle with 5 mm double bar insert included.)	(Securit® glass, hinges, locking bar catches and handle with 5 mm double bar insert included.)	
(A) Height (mm)	(B) Width (mm)	(C) Depth (mm)	Doors	Standard	Frames	Rear panel	Side panel	Plain	Transparent	Standard
1200	600	400	1	NSYSFV12	NSYSFC64	NSYBP126	NSY2SP124	NSYSFD126	NSYSFD126T	NSYMP126
1200	600	500	1	NSYSFV12	NSYSFC65	NSYBP126	NSY2SP125	NSYSFD126	NSYSFD126T	NSYMP126
1200	600	600	1	NSYSFV12	NSYSFC66	NSYBP126	NSY2SP126	NSYSFD126	NSYSFD126T	NSYMP126
1200	600	800	1	NSYSFV12	NSYSFC68	NSYBP126	NSY2SP128	NSYSFD126	NSYSFD126T	NSYMP126
1200	800	400	1	NSYSFV12	NSYSFC84	NSYBP128	NSY2SP124	NSYSFD128	NSYSFD128T	NSYMP128
1200	800	500	1	NSYSFV12	NSYSFC85	NSYBP128	NSY2SP125	NSYSFD128	NSYSFD128T	NSYMP128
1200	800	600	1	NSYSFV12	NSYSFC86	NSYBP128	NSY2SP126	NSYSFD128	NSYSFD128T	NSYMP128
1200	800	800	1	NSYSFV12	NSYSFC88	NSYBP128	NSY2SP128	NSYSFD128	NSYSFD128T	NSYMP128
1400	600	400	1	NSYSFV14	NSYSFC64	NSYBP146	NSY2SP144	NSYSFD146	NSYSFD146T	NSYMP146
1400	600	500	1	NSYSFV14	NSYSFC65	NSYBP146	NSY2SP145	NSYSFD146	NSYSFD146T	NSYMP146
1400	600	600	1	NSYSFV14	NSYSFC66	NSYBP146	NSY2SP146	NSYSFD146	NSYSFD146T	NSYMP146
1400	600	800	1	NSYSFV14	NSYSFC68	NSYBP146	NSY2SP148	NSYSFD146	NSYSFD146T	NSYMP146
1400	800	400	1	NSYSFV14	NSYSFC84	NSYBP148	NSY2SP144	NSYSFD148	NSYSFD148T	NSYMP148
1400	800	500	1	NSYSFV14	NSYSFC85	NSYBP148	NSY2SP145	NSYSFD148	NSYSFD148T	NSYMP148
1400	800	600	1	NSYSFV14	NSYSFC86	NSYBP148	NSY2SP146	NSYSFD148	NSYSFD148T	NSYMP148
1400	800	800	1	NSYSFV14	NSYSFC88	NSYBP148	NSY2SP148	NSYSFD148	NSYSFD148T	NSYMP148
1600	600	400	1	NSYSFV16	NSYSFC64	NSYBP166	NSY2SP164	NSYSFD166	NSYSFD166T	NSYMP166
1600	600	500	1	NSYSFV16	NSYSFC65	NSYBP166	NSY2SP165	NSYSFD166	NSYSFD166T	NSYMP166
1600	600	600	1	NSYSFV16	NSYSFC66	NSYBP166	NSY2SP166	NSYSFD166	NSYSFD166T	NSYMP166
1600	600	800	1	NSYSFV16	NSYSFC68	NSYBP166	NSY2SP168	NSYSFD166	NSYSFD166T	NSYMP166
1600	800	400	1	NSYSFV16	NSYSFC84	NSYBP168	NSY2SP164	NSYSFD168	NSYSFD168T	NSYMP168
1600	800	500	1	NSYSFV16	NSYSFC85	NSYBP168	NSY2SP165	NSYSFD168	NSYSFD168T	NSYMP168
1600	800	600	1	NSYSFV16	NSYSFC86	NSYBP168	NSY2SP166	NSYSFD168	NSYSFD168T	NSYMP168
1600	800	800	1	NSYSFV16	NSYSFC88	NSYBP168	NSY2SP168	NSYSFD168	NSYSFD168T	NSYMP168
1800	400	400	1	NSYSFV18	NSYSFC44	NSYBP184	NSY2SP184	NSYSFD184	-	NSYMP184 New
1800	400	500	1	NSYSFV18	NSYSFC45	NSYBP184	NSY2SP185	NSYSFD184	-	NSYMP184 New
1800	400	600	1	NSYSFV18	NSYSFC46	NSYBP184	NSY2SP186	NSYSFD184	-	NSYMP184 New
1800	400	800	1	NSYSFV18	NSYSFC48	NSYBP184	NSY2SP188	NSYSFD184	-	NSYMP184 New
1800	600	400	1	NSYSFV18	NSYSFC64	NSYBP186	NSY2SP184	NSYSFD186	NSYSFD186T	NSYMP186
1800	600	500	1	NSYSFV18	NSYSFC65	NSYBP186	NSY2SP185	NSYSFD186	NSYSFD186T	NSYMP186
1800	600	600	1	NSYSFV18	NSYSFC66	NSYBP186	NSY2SP186	NSYSFD186	NSYSFD186T	NSYMP186
1800	600	800	1	NSYSFV18	NSYSFC68	NSYBP186	NSY2SP188	NSYSFD186	NSYSFD186T	NSYMP186
1800	800	400	1	NSYSFV18	NSYSFC84	NSYBP188	NSY2SP184	NSYSFD188	NSYSFD188T	NSYMP188
1800	800	500	1	NSYSFV18	NSYSFC85	NSYBP188	NSY2SP185	NSYSFD188	NSYSFD188T	NSYMP188
1800	800	600	1	NSYSFV18	NSYSFC86	NSYBP188	NSY2SP186	NSYSFD188	NSYSFD188T	NSYMP188
1800	800	600	2	NSYSFV18	NSYSFC86	NSYBP188	NSY2SP186	NSYSFD1882D	-	NSYMP188
1800	800	800	1	NSYSFV18	NSYSFC88	NSYBP188	NSY2SP188	NSYSFD188	NSYSFD188T	NSYMP188
1800	800	800	2	NSYSFV18	NSYSFC88	NSYBP188	NSY2SP188	NSYSFD1882D	-	NSYMP188
1800	1000	400	1	NSYSFV18	NSYSFC104	NSYBP1810	NSY2SP184	NSYSFD1810	NSYSFD1810T	NSYMP1810
1800	1000	400	2	NSYSFV18	NSYSFC104	NSYBP1810	NSY2SP184	NSYSFD18102D	-	NSYMP1810
1800	1000	500	1	NSYSFV18	NSYSFC105	NSYBP1810	NSY2SP185	NSYSFD1810	NSYSFD1810T	NSYMP1810
1800	1000	600	1	NSYSFV18	NSYSFC106	NSYBP1810	NSY2SP186	NSYSFD1810	NSYSFD1810T	NSYMP1810
1800	1000	600	2	NSYSFV18	NSYSFC106	NSYBP1810	NSY2SP186	NSYSFD18102D	-	NSYMP1810
1800	1000	800	1	NSYSFV18	NSYSFC108	NSYBP1810	NSY2SP188	NSYSFD1810	NSYSFD1810T	NSYMP1810
1800	1000	800	2	NSYSFV18	NSYSFC108	NSYBP1810	NSY2SP188	NSYSFD18102D	-	NSYMP1810
1800	1200	400	2	NSYSFV18	NSYSFC124	NSYBP1812	NSY2SP184	NSYSFD18122D	NSYSFD18122DT	NSYMP1812
1800	1200	500	2	NSYSFV18	NSYSFC125	NSYBP1812	NSY2SP185	NSYSFD18122D	NSYSFD18122DT	NSYMP1812
1800	1200	600	2	NSYSFV18	NSYSFC126	NSYBP1812	NSY2SP186	NSYSFD18122D	NSYSFD18122DT	NSYMP1812
1800	1200	800	2	NSYSFV18	NSYSFC128	NSYBP1812	NSY2SP188	NSYSFD18122D	NSYSFD18122DT	NSYMP1812

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Dimensions				Vertical uprights	Bottom frame and top frame with roof	Panels		Doors		Mounting plate
								(Hinges, locking bar catches and handle with 5 mm double bar insert included.)	(Securit® glass, hinges, locking bar catches and handle with 5 mm double bar insert included.)	
(A) Height (mm)	(B) Width (mm)	(C) Depth (mm)	Doors	Standard	Frames	Rear panel	Side panel	Plain	Transparent	Standard
2000	300	500	1	NSYSFV20	NSYSFC35	NSYBP203	NSY2SP205	NSYSFD203	-	-
2000	300	600	1	NSYSFV20	NSYSFC36	NSYBP203	NSY2SP206	NSYSFD203	-	-
2000	300	800	1	NSYSFV20	NSYSFC38	NSYBP203	NSY2SP208	NSYSFD203	-	-
2000	400	400	1	NSYSFV20	NSYSFC44	NSYBP204	NSY2SP204	NSYSFD204	-	NSYMP204
2000	400	500	1	NSYSFV20	NSYSFC45	NSYBP204	NSY2SP205	NSYSFD204	-	NSYMP204
2000	400	600	1	NSYSFV20	NSYSFC46	NSYBP204	NSY2SP206	NSYSFD204	-	NSYMP204
2000	400	800	1	NSYSFV20	NSYSFC48	NSYBP204	NSY2SP208	NSYSFD204	-	NSYMP204
2000	600	400	1	NSYSFV20	NSYSFC64	NSYBP206	NSY2SP204	NSYSFD206	NSYSFD206T	NSYMP206
2000	600	500	1	NSYSFV20	NSYSFC65	NSYBP206	NSY2SP205	NSYSFD206	NSYSFD206T	NSYMP206
2000	600	600	1	NSYSFV20	NSYSFC66	NSYBP206	NSY2SP206	NSYSFD206	NSYSFD206T	NSYMP206
2000	600	800	1	NSYSFV20	NSYSFC68	NSYBP206	NSY2SP208	NSYSFD206	NSYSFD206T	NSYMP206
2000	800	400	1	NSYSFV20	NSYSFC84	NSYBP208	NSY2SP204	NSYSFD208	NSYSFD208T	NSYMP208
2000	800	500	1	NSYSFV20	NSYSFC85	NSYBP208	NSY2SP205	NSYSFD208	NSYSFD208T	NSYMP208
2000	800	600	1	NSYSFV20	NSYSFC86	NSYBP208	NSY2SP206	NSYSFD208	NSYSFD208T	NSYMP208
2000	800	600	2	NSYSFV20	NSYSFC86	NSYBP208	NSY2SP206	NSYSFD2082D	-	NSYMP208
2000	800	800	1	NSYSFV20	NSYSFC88	NSYBP208	NSY2SP208	NSYSFD208	NSYSFD208T	NSYMP208
2000	800	800	2	NSYSFV20	NSYSFC88	NSYBP208	NSY2SP208	NSYSFD2082D	-	NSYMP208
2000	1000	400	1	NSYSFV20	NSYSFC104	NSYBP2010	NSY2SP204	NSYSFD2010	NSYSFD2010T	NSYMP2010
2000	1000	400	2	NSYSFV20	NSYSFC104	NSYBP2010	NSY2SP204	NSYSFD20102D	-	NSYMP2010
2000	1000	500	1	NSYSFV20	NSYSFC105	NSYBP2010	NSY2SP205	NSYSFD2010	NSYSFD2010T	NSYMP2010
2000	1000	500	2	NSYSFV20	NSYSFC105	NSYBP2010	NSY2SP205	NSYSFD20102D	-	NSYMP2010
2000	1000	600	1	NSYSFV20	NSYSFC106	NSYBP2010	NSY2SP206	NSYSFD2010	NSYSFD2010T	NSYMP2010
2000	1000	600	2	NSYSFV20	NSYSFC106	NSYBP2010	NSY2SP206	NSYSFD20102D	-	NSYMP2010
2000	1000	800	1	NSYSFV20	NSYSFC108	NSYBP2010	NSY2SP208	NSYSFD2010	NSYSFD2010T	NSYMP2010
2000	1000	800	2	NSYSFV20	NSYSFC108	NSYBP2010	NSY2SP208	NSYSFD20102D	-	NSYMP2010
2000	1200	400	2	NSYSFV20	NSYSFC124	NSYBP2012	NSY2SP204	NSYSFD20122D	NSYSFD20122DT	NSYMP2012
2000	1200	500	2	NSYSFV20	NSYSFC125	NSYBP2012	NSY2SP205	NSYSFD20122D	NSYSFD20122DT	NSYMP2012
2000	1200	600	2	NSYSFV20	NSYSFC126	NSYBP2012	NSY2SP206	NSYSFD20122D	NSYSFD20122DT	NSYMP2012
2000	1200	800	2	NSYSFV20	NSYSFC128	NSYBP2012	NSY2SP208	NSYSFD20122D	NSYSFD20122DT	NSYMP2012
2000	1600	400	2	NSYSFV20	NSYSFC164	NSYBP2016	NSY2SP204	NSYSFD20162D	-	NSYMP2016
2000	1600	500	2	NSYSFV20	NSYSFC165	NSYBP2016	NSY2SP205	NSYSFD20162D	-	NSYMP2016
2000	1600	600	2	NSYSFV20	NSYSFC166	NSYBP2016	NSY2SP206	NSYSFD20162D	-	NSYMP2016
2200	400	400	1	NSYSFV22	NSYSFC44	NSYBP224	NSY2SP224	NSYSFD224	-	NSYMP224
2200	400	500	1	NSYSFV22	NSYSFC45	NSYBP224	NSY2SP225	NSYSFD224	-	NSYMP224
2200	400	600	1	NSYSFV22	NSYSFC46	NSYBP224	NSY2SP226	NSYSFD224	-	NSYMP224
2200	400	800	1	NSYSFV22	NSYSFC48	NSYBP224	NSY2SP228	NSYSFD224	-	NSYMP224
2200	600	400	1	NSYSFV22	NSYSFC64	NSYBP226	NSY2SP224	NSYSFD226	NSYSFD226T	NSYMP226
2200	600	500	1	NSYSFV22	NSYSFC65	NSYBP226	NSY2SP225	NSYSFD226	NSYSFD226T	NSYMP226
2200	600	600	1	NSYSFV22	NSYSFC66	NSYBP226	NSY2SP226	NSYSFD226	NSYSFD226T	NSYMP226
2200	600	800	1	NSYSFV22	NSYSFC68	NSYBP226	NSY2SP228	NSYSFD226	NSYSFD226T	NSYMP226
2200	800	400	1	NSYSFV22	NSYSFC84	NSYBP228	NSY2SP224	NSYSFD228	NSYSFD228T	NSYMP228
2200	800	500	1	NSYSFV22	NSYSFC85	NSYBP228	NSY2SP225	NSYSFD228	NSYSFD228T	NSYMP228
2200	800	600	1	NSYSFV22	NSYSFC86	NSYBP228	NSY2SP226	NSYSFD228	NSYSFD228T	NSYMP228
2200	800	800	1	NSYSFV22	NSYSFC88	NSYBP228	NSY2SP228	NSYSFD228	NSYSFD228T	NSYMP228
2200	1000	400	1	NSYSFV22	NSYSFC104	NSYBP2210	NSY2SP224	NSYSFD2210	NSYSFD2210T	NSYMP2210
2200	1000	500	1	NSYSFV22	NSYSFC105	NSYBP2210	NSY2SP225	NSYSFD2210	NSYSFD2210T	NSYMP2210
2200	1000	600	1	NSYSFV22	NSYSFC106	NSYBP2210	NSY2SP226	NSYSFD2210	NSYSFD2210T	NSYMP2210
2200	1000	800	1	NSYSFV22	NSYSFC108	NSYBP2210	NSY2SP228	NSYSFD2210	NSYSFD2210T	NSYMP2210
2200	1200	400	2	NSYSFV22	NSYSFC124	NSYBP2212	NSY2SP224	NSYSFD22122D	NSYSFD22122DT	NSYMP2212
2200	1200	500	2	NSYSFV22	NSYSFC125	NSYBP2212	NSY2SP225	NSYSFD22122D	NSYSFD22122DT	NSYMP2212
2200	1200	600	2	NSYSFV22	NSYSFC126	NSYBP2212	NSY2SP226	NSYSFD22122D	NSYSFD22122DT	NSYMP2212
2200	1200	800	2	NSYSFV22	NSYSFC128	NSYBP2212	NSY2SP228	NSYSFD22122D	NSYSFD22122DT	NSYMP2212

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Steel floor-standing enclosures

Side door

- Door for the side of the enclosure, replaces the side panel.
- Installation directly on the structure of the enclosure, opening 120°.
- Lock with handle and 5 mm double bar insert. 4 locking points.
- Reinforcement frame, cut-out with a pitch of 25 mm.
- Opening to right or left.
- Material: Steel
- Finish: Structured finish, epoxy polyester powder
- Colour: RAL 7035 grey
- Ingress protection rating: IP55 according to IEC 60529

Supply:
One side door, four hinges, four catches and handle lock

NSYSFD126

Characteristics	Height (mm)	Depth (mm)	References
Spacial SF Side door	1200	600	**NSYSFD126**
Spacial SF Side door	1200	800	**NSYSFD128**
Spacial SF Side door	1400	600	**NSYSFD146**
Spacial SF Side door	1400	800	**NSYSFD148**
Spacial SF Side door	1600	600	**NSYSFD166**
Spacial SF Side door	1600	800	**NSYSFD168**
Spacial SF Side door	1800	400	**NSYSFD184**
Spacial SF Side door	1800	500	**NSYSFD185**
Spacial SF Side door	1800	600	**NSYSFD186**
Spacial SF Side door	1800	800	**NSYSFD188**
Spacial SF Side door	2000	400	**NSYSFD204**
Spacial SF Side door	2000	500	**NSYSFD205**
Spacial SF Side door	2000	600	**NSYSFD206**
Spacial SF Side door	2000	800	**NSYSFD208**
Spacial SF Side door	2200	400	**NSYSFD224**
Spacial SF Side door	2200	500	**NSYSFD225**
Spacial SF Side door	2200	600	**NSYSFD226**
Spacial SF Side door	2200	800	**NSYSFD228**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Steel floor-standing enclosures

External fixing

NSY2SP124

- Set of 2 side panels fixed from the outside of the enclosure.
- Material: Steel
- Finish: Structured finish, epoxy polyester powder
- Colour: RAL 7035 grey
- Ingress protection rating: IP55 according to IEC 60529

Supply:
2 side panels, with sealing gasket and bag of accessories

Characteristics	Height (mm)	Depth (mm)	References
Set of 2 side panels fixed from the outside of the enclosure	1200	400	**NSY2SP124**
Set of 2 side panels fixed from the outside of the enclosure	1200	500	**NSY2SP125**
Set of 2 side panels fixed from the outside of the enclosure	1200	600	**NSY2SP126**
Set of 2 side panels fixed from the outside of the enclosure	1200	800	**NSY2SP128**
Set of 2 side panels fixed from the outside of the enclosure	1400	400	**NSY2SP144**
Set of 2 side panels fixed from the outside of the enclosure	1400	500	**NSY2SP145**
Set of 2 side panels fixed from the outside of the enclosure	1400	600	**NSY2SP146**
Set of 2 side panels fixed from the outside of the enclosure	1400	800	**NSY2SP148**
Set of 2 side panels fixed from the outside of the enclosure	1600	400	**NSY2SP164**
Set of 2 side panels fixed from the outside of the enclosure	1600	500	**NSY2SP165**
Set of 2 side panels fixed from the outside of the enclosure	1600	600	**NSY2SP166**
Set of 2 side panels fixed from the outside of the enclosure	1600	800	**NSY2SP168**
Set of 2 side panels fixed from the outside of the enclosure	1800	400	**NSY2SP184**
Set of 2 side panels fixed from the outside of the enclosure	1800	500	**NSY2SP185**
Set of 2 side panels fixed from the outside of the enclosure	1800	600	**NSY2SP186**
Set of 2 side panels fixed from the outside of the enclosure	1800	800	**NSY2SP188**
Set of 2 side panels fixed from the outside of the enclosure	2000	400	**NSY2SP204**
Set of 2 side panels fixed from the outside of the enclosure	2000	500	**NSY2SP205**
Set of 2 side panels fixed from the outside of the enclosure	2000	600	**NSY2SP206**
Set of 2 side panels fixed from the outside of the enclosure	2000	800	**NSY2SP208**
Set of 2 side panels fixed from the outside of the enclosure	2200	400	**NSY2SP224**
Set of 2 side panels fixed from the outside of the enclosure	2200	500	**NSY2SP225**
Set of 2 side panels fixed from the outside of the enclosure	2200	600	**NSY2SP226**
Set of 2 side panels fixed from the outside of the enclosure	2200	800	**NSY2SP228**

Internal fixing

NSY2SPI126

- Set of 2 side panels fixed from the enclosure, helping prevent access by unauthorized persons.
- Very useful in public spaces.
- Material: Steel
- Finish: Painted with epoxy polyester resin
- Colour: RAL 7035 grey
- Ingress protection rating: IP55 according to IEC 60529

Supply:
2 side panels, with sealing gasket and bag of accessories

Characteristics	Height (mm)	Depth (mm)	References
Set of 2 side panels fixed from the enclosure	1200	600	**NSY2SPI126**
Set of 2 side panels fixed from the enclosure	1800	500	**NSY2SPI185**
Set of 2 side panels fixed from the enclosure	1800	600	**NSY2SPI186**
Set of 2 side panels fixed from the enclosure	1800	800	**NSY2SPI188**
Set of 2 side panels fixed from the enclosure	2000	400	**NSY2SPI204**
Set of 2 side panels fixed from the enclosure	2000	500	**NSY2SPI205**
Set of 2 side panels fixed from the enclosure	2000	600	**NSY2SPI206**
Set of 2 side panels fixed from the enclosure	2000	800	**NSY2SPI208**
Set of 2 side panels fixed from the enclosure	2200	600	**NSY2SPI226**
Set of 2 side panels fixed from the enclosure	2200	800	**NSY2SPI228**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Steel floor-standing enclosures

Internal fixing rear panel

- Rear panel fixed from the inside of the enclosure, helping prevent unauthorized personnel from accessing and removing it. Normally used in public spaces.
- Material: Steel
- Finish: Painted wih epoxy polyester resin
- Colour: RAL 7035 grey
- Ingress protection rating: IP55 according to IEC 60529

Supply:
1 rear panel and fixing elements

NSYBPI1810

Characteristics	Height (mm)	Depth (mm)	References
Rear panel fixed from the inside of the enclosure	1800	1000	**NSYBPI1810**
Rear panel fixed from the inside of the enclosure	2000	600	**NSYBPI206**
Rear panel fixed from the inside of the enclosure	2000	800	**NSYBPI208**
Rear panel fixed from the inside of the enclosure	2000	1000	**NSYBPI2010**
Rear panel fixed from the inside of the enclosure	2200	800	**NSYBPI228**
Rear panel fixed from the inside of the enclosure	2200	1000	**NSYBPI2210**

Partition panel

- Partition panel for direct fixing to the structure, helps guarantee a water/dustproof protection of IP10 between enclosure suites.
- Material: Galvanised steel
- Colour: RAL 7035 grey
- Ingress protection rating: IP55 according to IEC 60529

Supply:
1 partition panel, sealing gasket and fixing elements

NSYPPS166

Characteristics	Height (mm)	Depth (mm)	References
Spacial SF partition panel	1600	600	**NSYPPS166**
Spacial SF partition panel	1600	800	**NSYPPS168**
Spacial SF partition panel	1800	400	**NSYPPS184**
Spacial SF partition panel	1800	500	**NSYPPS185**
Spacial SF partition panel	1800	600	**NSYPPS186**
Spacial SF partition panel	2000	400	**NSYPPS204**
Spacial SF partition panel	2000	500	**NSYPPS205**
Spacial SF partition panel	2000	600	**NSYPPS206**
Spacial SF partition panel	2000	800	**NSYPPS208**
Spacial SF partition panel	2200	600	**NSYPPS226**
Spacial SF partition panel	2200	800	**NSYPPS228**

Accessories

- Trim cap for external fixing panels, both sides and rear
- Material: Polyamide 6
- Colour: RAL 7035 grey

Supply:
50 units

NSYCSP

Characteristics	References
Trim cap for external fixing panels	**NSYCSP**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Steel floor-standing enclosures

SF Standard coupling kit

NSYSFBK

- Used for joining enclosures side-to-side or depthwide.
- Fixing from the inside of the enclosure.
- Material: Flat connectors and brackets: Zinc-coated steel
  Sealing gasket: EPDM

Supply:
4 brackets, 2 flat connectors, sealing gasket and fixing elements and 16 caps

Characteristics	References
Spacial SF Standard coupling kit	**NSYSFBK**

SF Swing 19" rack coupling kit


NSYSFBK19

- Used for joining enclosures equipped with swing 19" rack, side-to-side or depthwise.
- Fixing from the inside of the enclosures.
- Material: Flat connectors: Zinc-coated steel
  Sealing gasket: EPDM

Supply:
8 flat connectors, sealing gasket and fixing elements and 16 caps

Characteristics	References
Spacial SF-19" Swing 19" rack coupling kit	**NSYSFBK19**

SF Reinforced coupling

NSYSFBKR

- It is used together with the coupling kit to reinforce the connection between 2 enclosures when they carry heavy loads.
- Fixing from the inside of the enclosures.
- Material: Zinc-coated steel

Supply:
4 reinforced connectors and fixing elements

Characteristics	References
Spacial SF Reinforced coupling	**NSYSFBKR**

SF Quick coupling


NSYSFBKF

- Used for quickly joining 2 enclosures.
- Fixing from the inside of the enclosures.
- Material: Zinc-coated steel

Supply:
4 flat links and fixing elements

Characteristics	References
Spacial SF Quick coupling, IP 40	**NSYSFBKF**

SF Kit for coupling the previous version with Spacial SF

NSYSFBKSH

- It is used for coupling an enclosure of a previous version (OLN or Spacial 6000) side-to-side or depthwise with a Spacial SF enclosure.
- Fixing from the inside of the enclosures.
- Material: Flat connectors and spacers: Zinc-coated steel
  Sealing gasket: EPDM

Supply:
6 flat connectors, sealing gasket and fixing elements

Characteristics	References
Spacial SF Kit for coupling the previous version with Spacial SF	**NSYSFBKSH**

SF External coupling

NSYSFBKE

- Allows two enclosures to be joined by their structure.
- To be used with the standard coupling kit in those cases where front and back uprights are not accesibles.
- The mounting plate or vertical uprights fixed to the back of the enclosure help prevent the assembly and dismantling of the kit.
- It can be combined with the reinforced or the quick coupling kit.
- Material: External connectors: Zinc-coated steel

Supply:
4 external connectors and fixing elements

Characteristics	References
Spacial SF External coupling	**NSYSFBKE**

SM Enclosure coupling kit for Spacial SM



NSYSMBK

- Used for joining enclosuresside-to-side.
- Enclosures fixed from the inside.
- Material: 3 x 10 mm sealing gasket: EPDM

Supply:
1 sealing gasket and fixing elements

Characteristics	References
Spacial SM Enclosure coupling kit for Spacial SM	**NSYSMBK**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Plinth as a kit

The complete plinth consists of two elements, one is the front and rear kit, determined by the length of the enclosure, and the other consists of the side panels, which determine the depth of the enclosure. The number of side panels required is decided according to the desired plinth combination.

3

Robust design.
The modular plinth system makes it possible to reduce the number of references in stock.

Characteristics	Front and rear kit	Side panels	Complete plinth
Plinth height 100 mm			
Plinth height 200 mm			

Floor

Examples of solutions

Plinth cross rail fixed in position B, it requires 2 cross rails in position A to be fixed

- They are fixed to the plinth cross rails, both the universal and the quick fixing types.
- Their depth is adjustable with a pitch of 25 mm.



Comment: Universal and quick fixing cross rail references, page 254

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Steel floor-standing enclosures

Possibility of joining plinths



The surfaces between corners are always in contact.
They are joined by a M8 screw and nut, not included in the standard supply.
⊕ Longitudinally free space for passing cables
⊕ Greater rigidity of the resultant assembly unit





By side panels
the M6 screws and caged nuts, not included in the standard supply, reference **NSYSPM6** and reference **NSYCN9M625**, which can be mounted above and/or below.
⊕ Improves rigidity in the depthwise direction during transport



Vertical plinth assembly
by means of M12 screws and nuts, not included in the standard supply.
⊕ The two heights of corners can be combined

Possibility of fixing the enclosure to the plinth



Fixing from the inside of the enclosure
by means of an M12 screw, screwing directly into the corner of the plinth.
⊕ Fixing convenience and speed



Fixing from the outside of the enclosure
with a M12 screw, screwing directly onto the vertical upright.
⊕ Maximum rigidity of the enclosure-plinth assembly

Possibility of fixing the plinth to the floor



Fixing from the inside of the enclosure.
The machining angle varies according to the plinth model:
- Plinth height 100 mm φ = 18°.
- Plinth height 200 mm φ = 9°.

Fixing from the outside of the enclosure, optimum point for the rigidity of the assembly.
The machining angle varies according to the plinth model:
- Plinth height 100 mm φ = 22°.
- Plinth height 200 mm φ = 11°.



It is also possible to use floor-fixing supports
- reference **NSYSGF**, to fix the corner or the panel and the corner to the floor.

The corners of the ends can be rotated in the event of needing to remove the side panels of the plinth and/or to obtain access to the fixing outside the floor, when the set is installed against the wall.

Fixing the enclosure to the ground

Fixing from the outside of the enclosure
optimum point for the rigidity of the assembly.

The machining angle varies according to the plinth model:
- Plinth height 100 mm φ = 22°.
- Plinth height 200 mm φ = 11°.

Fixing the enclosure to the ground

Enclosure against a wall
Thanks to the design of the corners, when the enclosure is installed against the wall, the following is possible:
- to remove the side panels (turning back corners),
- to access the external fixing to the floor.

It is also possible to use floor-fixing supports, reference **NSYSGF**, to fix the corner or the panel and the corner to the floor.

Fixing the enclosure to the plinth



Fixing from the inside of the enclosure
by means of a M12 screw, screwing directly into the corner of the plinth
⊕ Fixing convenience and speed.

Assembly of the plinth panels

The panels are fixed with an M6 screw to the corner
included in the standard supply of the side panels.
- The front and rear panels are delivered mounted on the corners

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Steel floor-standing enclosures

Front and rear plinths



B: Width
C: Height



- The front and rear of the plinth consists of 4 corners with 2 or 4 panels.
- Material: Folded sheet steel, corner with a thickness of 25/10e mm
- Finish: Structured finish, epoxy polyester powder
- Colour: RAL 7022 grey
- Ingress protection rating: IP30 according to IEC 60529
- Mechanical protection rating: IK10 according to IEC 62262

Supply:
Height 100 mm: 4 corners, 2 panels (front and rear), 4 corner covers and fixing elements
Height 200 mm: 4 corners, 4 panels (2 front and 2 rear), 4 corner covers and fixing elements

NSYSPF3100

NSYSPF3200

Characteristics	Height (mm)	Width (mm)	References
Front plinths for Spacial	100	300	**NSYSPF3100**
Front plinths for Spacial	100	400	**NSYSPF4100**
Front plinths for Spacial	100	600	**NSYSPF6100**
Front plinths for Spacial	100	800	**NSYSPF8100**
Front plinths for Spacial	100	1000	**NSYSPF10100**
Front plinths for Spacial	100	1200	**NSYSPF12100**
Front plinths for Spacial	100	1600	**NSYSPF16100**
Front plinths for Spacial	200	300	**NSYSPF3200**
Front plinths for Spacial	200	400	**NSYSPF4200**
Front plinths for Spacial	200	600	**NSYSPF6200**
Front plinths for Spacial	200	800	**NSYSPF8200**
Front plinths for Spacial	200	1000	**NSYSPF10200**
Front plinths for Spacial	200	1200	**NSYSPF12200**
Front plinths for Spacial	200	1600	**NSYSPF16200**

Plinth side panels

NSYSPS3100

NSYSPS3200

- They are fixed to the corner of the plinth by 2 fixing screws.
- Material: Folded sheet steel
- Finish: Structured finish, epoxy polyester powder
- Colour: RAL 7022 grey
- Ingress protection rating: IP30 according to IEC 60529
- Mechanical protection rating: IK10 according to IEC 62262

Supply:
Height 100 mm: 2 side panels, 4 corner covers and fixing elements
Height 200 mm: 4 side panels (height of 100 mm, 2 for each side), 4 corner covers and fixing elements

Characteristics	Height (mm)	Depth (mm)	References
Side plinths for Spacial	100	300	**NSYSPS3100**
Side plinths for Spacial	100	400	**NSYSPS4100**
Side plinths for Spacial	100	500	**NSYSPS5100**
Side plinths for Spacial	100	600	**NSYSPS6100**
Side plinths for Spacial	100	800	**NSYSPS8100**
Side plinths for Spacial	200	300	**NSYSPS3200**
Side plinths for Spacial	200	400	**NSYSPS4200**
Side plinths for Spacial	200	500	**NSYSPS5200**
Side plinths for Spacial	200	600	**NSYSPS6200**
Side plinths for Spacial	200	800	**NSYSPS8200**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Steel floor-standing enclosures

Ventilated front plinth

NSYSPFV6100

- The front and rear of the ventilated plinth is made up of 4 corners with 2 front panels.
- Material: Folded sheet steel, corner with a thickness of 25/10e mm
- Finish: Structured finish, epoxy polyester powder
- Colour: RAL 7022 grey
- Ingress protection rating: IP20 according to IEC 60529
- Mechanical protection rating: IK10 according to IEC 62262

Supply:
Height 100 mm: 4 corners, 2 ventilated panels (front and rear), 4 corner covers and fixing elements

Characteristics	Height (mm)	Width (mm)	References
Ventilated front plinth for Spacial SF-SM	100	600	**NSYSPFV6100**
Ventilated front plinth for Spacial SF-SM	100	800	**NSYSPFV8100**

Ventilated side panels

NSYSPV6100

- They are fixed to the corner of the plinth by fixing screws.
- Material: Folded sheet steel
- Finish: Structured finish, epoxy polyester powder
- Colour: RAL 7022 grey
- Ingress protection rating: IP20 according to IEC 60529
- Mechanical protection rating: IK10 according to IEC 6226

Supply:
Height 100 mm: 2 ventilated side panels, 4 corner covers and fixing elements

Characteristics	Height (mm)	Depth (mm)	References
Ventilated side panels for Spacial SF-SM	100	600	**NSYSPV6100**
Ventilated side panels for Spacial SF-SM	100	800	**NSYSPV8100**

Panels with brush

NSYSPB6100



- They allow the entry and fixing of cables inside the enclosure, through the plinth.
- Material: Folded sheet steel
- Finish: Structured finish, epoxy polyester powder
- Colour: RAL 7022 grey
- Ingress protection rating: IP20 according to IEC 60529
- Mechanical protection rating: IK10 according to IEC 6226

Supply:
Height 100 mm: 2 panels with brushes, 4 corner covers and fixing elements

Characteristics	Height (mm)	Depth (mm)	References
Panels with brush for Spacial SF-SM	100	600	**NSYSPB6100**
Panels with brush for Spacial SF-SM	100	800	**NSYSPB8100**

Stainless steel plinths (standard plinths page 150, ventilated plinths page 423) are compatible with steel floor-standing enclosure SM and SF using an earthing cable reference **NSYEL226D13** (description page 305) to be ordered separatly.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Steel floor-standing enclosures

Fixing to the floor

NSYSGF

- Part for fixing the plinth to the floor in the event of not being able to use the drillholes made in the plinth.
- Material: Steel
- Finish: Zinc-coated

Supply:
4 pieces, fixing element not supplied

Characteristics	References
Spacial SF-Fixing to the floor	**NSYSGF**

Fixing to the floor by fixing points of previous version (OLN/CMO or Spacial 6000 and 18500)

NSYOL6GF

- Parts that reproduce the floor-fixing points of the previous plinth.
- Material: Steel
- Finish: Zinc-coated



Supply:
4 pieces, fixing elements not supplied

Characteristics	References
Fixing to the floor by fixing points of previous version	**NSYOL6GF**

Plinth cross rail support

Comment:
Reference by unit Order by multiples of 12 (12, 24, 36…)

NSYSPCR

- Support for fixing a cross rail inside the plinth.
- Material: Steel
- Finish: Zinc-coated

Supply:
12 pieces and fixing elements

Characteristics	References
Spacial SF-Plinth cross rail support, 100 mm	**NSYSPCR**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Life Is On Schneider Electric

Steel floor-standing enclosures

Plinth cross rails

- They are fixed across the width and/or depth between the corners of the plinth.
- The plinth cross rail supports are required for its assembly.
- Material: Steel
- Finish: Zinc-coated

Supply:
2 cross rails and fixing elements

NSYSUCR4030

Characteristics	Cross rails	Width (mm)	Depth (mm)	References
Plinth cross rails for Spacial SF-SM	1 row (40)	400	-	**NSYSUCR4030**
Plinth cross rails for Spacial SF-SM	1 row (40)	600	-	**NSYSUCR4050**
Plinth cross rails for Spacial SF-SM	1 row (40)	800	-	**NSYSUCR4070**
Plinth cross rails for Spacial SF-SM	1 row (40)	1000	-	**NSYSUCR4090**
Plinth cross rails for Spacial SF-SM	1 row (40)	1200	-	**NSYSUCR40110**
Plinth cross rails for Spacial SF-SM	3 row (90)	400	-	**NSYSUCR9030**
Plinth cross rails for Spacial SF-SM	3 row (90)	600	-	**NSYSUCR9050**
Plinth cross rails for Spacial SF-SM	3 row (90)	800	-	**NSYSUCR9070**
Plinth cross rails for Spacial SF-SM	3 row (90)	1000	-	**NSYSUCR9090**
Plinth cross rails for Spacial SF-SM	3 row (90)	1200	-	**NSYSUCR90110**
Plinth cross rails for Spacial SF-SM	1 row (40)	-	500	**NSYSUCR4040**
Plinth cross rails for Spacial SF-SM	3 row (90)	-	500	**NSYSUCR9040**

Fixing options, Screw M6

NSYSPM6

- M6 x 10 mm

Supply:
50 screws

Characteristics	References
Screw M6	**NSYSPM6**

Fixing options, Caged nuts

NSYCN9M625

- M6 caged nuts.

Supply:
100 caged nuts.

Characteristics	References
Caged nuts	**NSYCN9M625**

Fixing options, Levelling the plinth

NSYSPLK

- The plinth allows levelling by means of a M12 screw.

Characteristics	References
Levelling the plinth	**NSYSPLK**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Steel floor-standing enclosures

Cable entries

Possibilities of cable gland plate adjustment



Plain cable gland plate

- The design of the compact cable gland plate, coupled with the use of the sealing gasket **NSYCEK** enable the maximum dust/water tightness.
- Material: Steel painted with epoxy polyester resin
- Colour: RAL 7035 grey
- Thicknesses: 10/10[e] mm

Supply:
Plain plate and fixing elements

NSYSMEC63

Characteristics	Width (mm)	Depth (mm)	References
Spacial SM Plain cable gland plate	600	300	**NSYSMEC63**
Spacial SM Plain cable gland plate	600	400	**NSYSMEC64**
Spacial SM Plain cable gland plate	600	500	**NSYSMEC65**
Spacial SM Plain cable gland plate	600	600	**NSYSMEC66**
Spacial SM Plain cable gland plate	800	300	**NSYSMEC83**
Spacial SM Plain cable gland plate	800	400	**NSYSMEC84**
Spacial SM Plain cable gland plate	800	500	**NSYSMEC85**
Spacial SM Plain cable gland plate	800	600	**NSYSMEC86**
Spacial SM Plain cable gland plate	1000	300	**NSYSMEC103**
Spacial SM Plain cable gland plate	1000	400	**NSYSMEC104**
Spacial SM Plain cable gland plate	1000	500	**NSYSMEC105**
Spacial SM Plain cable gland plate	1200	300	2x **NSYSMEC63**
Spacial SM Plain cable gland plate	1200	400	2x **NSYSMEC64**
Spacial SM Plain cable gland plate	1200	500	2x **NSYSMEC65**
Spacial SM Plain cable gland plate	1200	600	2x **NSYSMEC66**
Spacial SM Plain cable gland plate	1600	400	2x **NSYSMEC84**
Spacial SM Plain cable gland plate	1600	500	2x **NSYSMEC85**
Spacial SM Plain cable gland plate	1600	600	2x **NSYSMEC86**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Life Is On Schneider Electric

Steel floor-standing enclosures

Plain cable gland plate



- The design of the compact cable gland plate, coupled with the use of the sealing gasket **NSYCEK** enable the maximum dust/water tightness.
- Material: Galvanised steel
- Thicknesses: 15/10e mm

Supply:
Plain plate and fixing elements

NSYEC35

Characteristics	(B) Width (mm)	(C) Depth (mm)	References
Spacial SF Plain cable gland plate	300	500	**NSYEC35**
Spacial SF Plain cable gland plate	300	600	**NSYEC36**
Spacial SF Plain cable gland plate	400	400	**NSYEC44**
Spacial SF Plain cable gland plate	400	500	**NSYEC45**
Spacial SF Plain cable gland plate	400	600	**NSYEC64**
Spacial SF Plain cable gland plate	400	800	**NSYEC84**
Spacial SF Plain cable gland plate	600	400	**NSYEC64**
Spacial SF Plain cable gland plate	600	500	**NSYEC65**
Spacial SF Plain cable gland plate	600	600	**NSYEC66**
Spacial SF Plain cable gland plate	600	800	**NSYEC68**
Spacial SF Plain cable gland plate	800	400	**NSYEC84**
Spacial SF Plain cable gland plate	800	500	**NSYEC85**
Spacial SF Plain cable gland plate	800	600	**NSYEC86**
Spacial SF Plain cable gland plate	800	800	**NSYEC88**
Spacial SF Plain cable gland plate	1000	400	**NSYEC104**
Spacial SF Plain cable gland plate	1000	500	**NSYEC105**
Spacial SF Plain cable gland plate	1000	600	**NSYEC106**
Spacial SF Plain cable gland plate	1000	800	**NSYEC108**
Spacial SF Plain cable gland plate	1200	400	**NSYEC124**
Spacial SF Plain cable gland plate	1200	500	**NSYEC125**
Spacial SF Plain cable gland plate	1200	600	**NSYEC126**
Spacial SF Plain cable gland plate	1200	800	**NSYEC128**
Spacial SF Plain cable gland plate	1600	400	**NSYEC164**
Spacial SF Plain cable gland plate	1600	500	**NSYEC165**
Spacial SF Plain cable gland plate	1600	600	**NSYEC166**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Steel floor-standing enclosures

Plate with 1 entry



Enclosures of 300 and 400 mm width.



Enclosures of 600, 800, 1000 and 1200 mm width.

- Facilitates the entry of cables thanks to a longitudinal opening.
- Material: Galvanised steel
- Thicknesses: 15/10e mm

Supply:
Plate with 1 entry; Self-extinguishing polyurethane adhesive gasket with cross-section of 15 x 25 mm (helps guarantee good sealing) and fixing elements

NSYEC351

Characteristics	(B) Width (mm)	(C) Depth (mm)	References
Spacial SF Plate with 1 entry	300	500	**NSYEC351**
Spacial SF Plate with 1 entry	300	600	**NSYEC361**
Spacial SF Plate with 1 entry	400	400	**NSYEC441**
Spacial SF Plate with 1 entry	400	500	**NSYEC451**
Spacial SF Plate with 1 entry	400	600	**NSYEC461**
Spacial SF Plate with 1 entry	400	800	**NSYEC481**
Spacial SF Plate with 1 entry	600	400	**NSYEC641**
Spacial SF Plate with 1 entry	600	500	**NSYEC651**
Spacial SF Plate with 1 entry	600	600	**NSYEC661**
Spacial SF Plate with 1 entry	600	800	**NSYEC681**
Spacial SF Plate with 1 entry	800	400	**NSYEC841**
Spacial SF Plate with 1 entry	800	500	**NSYEC851**
Spacial SF Plate with 1 entry	800	600	**NSYEC861**
Spacial SF Plate with 1 entry	800	800	**NSYEC881**
Spacial SF Plate with 1 entry	1000	400	**NSYEC1041**
Spacial SF Plate with 1 entry	1000	500	**NSYEC1051**
Spacial SF Plate with 1 entry	1000	600	**NSYEC1061**
Spacial SF Plate with 1 entry	1000	800	**NSYEC1081**
Spacial SF Plate with 1 entry	1200	400	**NSYEC1241**
Spacial SF Plate with 1 entry	1200	500	**NSYEC1251**
Spacial SF Plate with 1 entry	1200	600	**NSYEC1261**
Spacial SF Plate with 1 entry	1200	800	**NSYEC1281**
Spacial SF Plate with 1 entry	1600	400	**NSYEC1641**
Spacial SF Plate with 1 entry	1600	500	**NSYEC1651**
Spacial SF Plate with 1 entry	1600	600	**NSYEC1661**

Plate with 2 entries



- Cable entry for very deep enclosures (600 and 800 mm).
- Two longitudinal openings allowing a large number of cables through.
- Material: Galvanised steel
- Thicknesses: 15/10e mm

Supply:
1 plate with 2 entries; Polyurethane adhesive gasket with cross-section of 15 x 25 mm (helps guarantee good sealing) and fixing elements

NSYEC662

Characteristics	(B) Width (mm)	(C) Depth (mm)	References
Spacial SF Plate with 2 entries	600	600	**NSYEC662**
Spacial SF Plate with 2 entries	600	800	**NSYEC682**
Spacial SF Plate with 2 entries	800	600	**NSYEC862**
Spacial SF Plate with 2 entries	800	800	**NSYEC882**
Spacial SF Plate with 2 entries	1000	600	**NSYEC1062**
Spacial SF Plate with 2 entries	1000	800	**NSYEC1082**
Spacial SF Plate with 2 entries	1200	600	**NSYEC1262**
Spacial SF Plate with 2 entries	1200	800	**NSYEC1282**
Spacial SF Plate with 2 entries	1600	600	**NSYEC1662**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Steel floor-standing enclosures

SF Cable gland plate for connectors

- Adapter plate to install cable entry plates for connectors, see page 285.
- To be used together with cable gland plates, 1 or 2 entries, adding or replacing one of the parts.
- Material: Galvanised steel
- Thicknesses: 15/10e mm

Supply:
Plate and fixing elements

NSYDCE6

Characteristics	No. of cuts	Width (mm)	References
Spacial SF Cable gland plate for connectors	2	600	**NSYDCE6**
Spacial SF Cable gland plate for connectors	3	800	**NSYDCE8**
Spacial SF Cable gland plate for connectors	4	1000	**NSYDCE10**
Spacial SF Cable gland plate for connectors	4	1200	**NSYDCE12**

SF Brush-type cable entry gasket

- For plates with 1 or 2 cable entries.
- The cables can have different diameters.

NSYBCE4

Characteristics	Width (mm)	References
Spacial SF Brush-type cable entry gasket	400	**NSYBCE4**
Spacial SF Brush-type cable entry gasket	600	**NSYBCE6**
Spacial SF Brush-type cable entry gasket	800	**NSYBCE8**
Spacial SF Brush-type cable entry gasket	1000	**NSYBCE10**
Spacial SF Brush-type cable entry gasket	1200	**NSYBCE12**
Spacial SF Brush-type cable entry gasket	1600	**NSYBCE16**

SM Brush-type cable entry gasket

- Brush-type gasket for installation on the cable gland plates.
- The cables can have different diameters.

NSYSMBCE6

Characteristics	Width (mm)	References
Spacial SM-Brush-type cable entry gasket	600	**NSYSMBCE6**
Spacial SM-Brush-type cable entry gasket	800	**NSYSMBCE8**
Spacial SM-Brush-type cable entry gasket	1000	**NSYSMBCE10**
Spacial SM-Brush-type cable entry gasket	1200	2x **NSYSMBCE6**
Spacial SM-Brush-type cable entry gasket	1600	2x **NSYSMBCE8**

SF Foam cable entry gasket

- Spare gasket, made from self-extinguishing expanded polyurethane with a cross-section of 15 x 25 mm, for fixing on cable gland plates.

NSYCEJ

Characteristics	References
Spacial SF Foam cable entry gasket	**NSYCEJ**

SF Sealing gasket

- Sealing gasket, made from ethylene-propylene with a cross-section of 3 x 10 mm, for mounting on the perimeter of the cable gland plates. Adhesive to help guarantee good sealing.

NSYCEK

Characteristics	References
Spacial SF Sealing gasket	**NSYCEK**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

3

Lifting systems

SF Eyebolts

NSYSFEB



- Set of M12 lifting eyebolts, which screw directly into the structure of the enclosure, in the axis of the uprights.
- Material: Galvanised cast steel
- Maximum load: 340 kg
- Maximum amount of assembled enclosures to be lifted: 1

Supply:
4 eyebolts

Characteristics	Enclosures to be lifted	Max. load (kg)	References
Spacial SF Eyebolts	**1**	**340**	**NSYSFEB**

SM Eyebolts

NSYSMEB





- Set of M12 lifting eyebolts, fixed to the enclosure by fixing nuts.
- Material: Galvanised cast steel
- Maximum load: 340 kg
- Maximum amount of assembled enclosures to be lifted: 1

Supply:
4 eyebolts and
4 fixing nuts

Characteristics	Enclosures to be lifted	Max. load (kg)	References
Spacial SM Eyebolts	**1**	**340**	**NSYSMEB**

SF Lifting brackets

NSYSFELB





- Set of lifting and transport brackets, fixed to the structure between two coupled enclosures, in the axis of the uprights.
- Material: Zinc-coated steel
- Maximum load: 500 kg
- Maximum amount of assembled enclosures to be lifted: 2

Supply:
4 brackets and fixing elements (M12 screws)

Characteristics	Enclosures to be lifted	Max. load (kg)	References
Spacial SF Lifting brackets	**2**	**500**	**NSYSFELB**

SF Lifting bar

NSYSFTB16



- Set of bars for lifting and transporting enclosures suites.
- They are fixed to the structure of the enclosure, in the axis of the uprights.
- Material: Steel

Supply:
2 lifting bars and fixing elements (M12 screws)

Characteristics	Length (mm)	Enclosures to be lifted	Max. load (kg)	References
Spacial SF Lifting bar	**1600**	**2**	**2000**	**NSYSFTB16**
Spacial SF Lifting bar	**1800**	**3**	**3000**	**NSYSFTB18**
Spacial SF Lifting bar	**2400**	**4**	**3000**	**NSYSFTB24**
Spacial SF Lifting bar	**3200**	**5**	**4000**	**NSYSFTB32**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Steel floor-standing enclosures

Roof Canopy

- Provides excellent protection against splashes from rainwater.
- Canopy mandatory for outdoor use, not compatible with the simultaneous use of lifting elements.
- Spacial SF: It is possible to use a single canopy with combinations of modular enclosures (example of a 1600 mm canopy with two coupled 800 mm enclosures).
- Material: Galvanised steel
- Finish: Structured finish, epoxy polyester powder
- Colour: RAL 7035 grey



Fixing:
Spacial SF: Fixing by drill holes to be made in the roof of the enclosure
Spacial SM: Fixing by drill holes already made in the roof

Supply:
One canopy, drilling template and fixing elements

NSYSC630

Characteristics	(B) Width (mm)	(C) Depth (mm)	References
Spacial SF/SM Canopy	600	300	**NSYSC630**
Spacial SF/SM Canopy	600	400	**NSYSC640**
Spacial SF/SM Canopy	600	500	**NSYSC650**
Spacial SF/SM Canopy	600	600	**NSYSC660**
Spacial SF/SM Canopy	800	300	**NSYSC830**
Spacial SF/SM Canopy	800	400	**NSYSC840**
Spacial SF/SM Canopy	800	500	**NSYSC850**
Spacial SF/SM Canopy	800	600	**NSYSC860**
Spacial SF/SM Canopy	1000	300	**NSYSC1030**
Spacial SF/SM Canopy	1000	400	**NSYSC1040**
Spacial SF/SM Canopy	1000	500	**NSYSC1050**
Spacial SF/SM Canopy	1000	600	**NSYSC1060**
Spacial SF/SM Canopy	1200	300	**NSYSC1230**
Spacial SF/SM Canopy	1200	400	**NSYSC1240**
Spacial SF/SM Canopy	1200	500	**NSYSC1250**
Spacial SF/SM Canopy	1200	600	**NSYSC1260**
Spacial SF/SM Canopy	1600	400	**NSYSC1640**
Spacial SF/SM Canopy	1600	500	**NSYSC1650**
Spacial SF/SM Canopy	1600	600	**NSYSC1660**
Spacial SF/SM Canopy	1800	500	**NSYSC1850**
Spacial SF/SM Canopy	1800	600	**NSYSC1860**
Spacial SF/SM Canopy	2000	500	**NSYSC2050**
Spacial SF/SM Canopy	2000	600	**NSYSC2060**
Spacial SF/SM Canopy	2400	500	**NSYSC2450**
Spacial SF/SM Canopy	2400	600	**NSYSC2460**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Steel floor-standing enclosures

Ventilated roof



- Roof providing natural ventilation for the enclosure, with IP30 protection.
- Height: An extra 63 mm in relation to the structure.
- Material: Steel
- Finish: Structured finish, epoxy polyester powder
- Colour: RAL 7035 grey
- Fixing: They are screwed onto the structure, at the roof fixing point

Supply:
One ventilated roof and four elevators

NSYSVR606

Characteristics	(B) Width (mm)	(C) Depth (mm)	References
Spacial SF Ventilated roof	600	600	**NSYSVR606**
Spacial SF Ventilated roof	600	800	**NSYSVR608**
Spacial SF Ventilated roof	800	600	**NSYSVR806**
Spacial SF Ventilated roof	800	800	**NSYSVR808**

Ventilation elevators for roof





- Allows the roof to be raised, providing natural ventilation.
- They are screwed onto the structure, at the roof fixing point.
- Material: Zinc-coated steel

Supply:
4 elevators

NSYRE26

Characteristics	(H) Height (mm)	IP	References
Spacial SF Ventilation elevators for roof	23	10	**NSYRE26**
Spacial SF Ventilation elevators for roof	60	00	**NSYRE60**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Life Is On Schneider Electric

Steel floor-standing enclosures

FL21 cable entry membranes

- Membrane plate for watertight cable entries made from insulating material (fireresistance level UL 94 V-0).
- Direct installation in the FL21 cable entry plate adapter.
- 4 models: Plain plate and membrane plates from 7 to 37 cable entries.
- Material: Grey plastic
- Ingress protection rating: IP66 according to IEC 60529

Comment:
For more information, see page 285

Supply:
Membrane plate and fixing elements.

NSYAECPFLT25

Characteristics	No. of entries	References
FL21 plain metallic plate	0	**NSYAECPFLBP**
FL21 cable entry membranes	7	**NSYAECPFLT7**
FL21 cable entry membranes	27	**NSYAECPFLT25**
FL21 cable entry membranes	37	**NSYAECPFLT35**

Standard cable entry plate

Comment:
For more information, see page 285

NSYTLC

- Thickness: 15/10e mm

Characteristics	References
Standard cable entry plate	**NSYTLC**

Aluminium cable entry plate

NSYTLCU

- Thickness: 30/10e mm

Characteristics	References
Aluminium cable entry plate	**NSYTLCU**

FlexiCable

Characteristics	References
FlexiCable	**NSYTLCME**

Adapter for FL21 cable entry plate



- Thickness: 15/10e mm

Characteristics	References
Adapter for FL21 cable entry plate	**NSYTLCFL**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Steel floor-standing enclosures

Wall fixing

SF Wall fixing support



NSYSFWFIX

- Supports for fixing the enclosure on the wall and helping prevent it from turning over.
- They cannot be used for hanging the enclosure.
- They are installed using the roof mounting screws.
- Material: Zinc-coated steel sheet



Supply:
2 supports

Characteristics	References
Spacial SF Wall fixing support	**NSYSFWFIX**

SM Wall fixing support

NSYSMWFIX

- Supports for fixing the enclosure on the wall and helping prevent it from turning over.
- They are installed using the drill holes in the back of the enclosure.
- Enclosure fixed from the outside.
- Material: Zinc-coated steel sheet



Supply:
2 supports

Characteristics	References
Spacial SM Wall fixing support	**NSYSMWFIX**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Steel floor-standing enclosures

Doors SF SM

Inner door

SF

NSYID166

- Door for additional protection. Helps prevent the switchgear from being manipulated by unauthorised personnel.
- Allows the installation of switchgear mounted directly on the door.
- Mounting on the top and bottom frame of the enclosure.
- Depth adjustable with a pitch of 25 mm, from the first fixing point.
- Opening to right or left, with two locks, 3 mm double bar, with central handle.
- Reinforcement frames on the rear, cut-outs with a 25 mm pitch, for equipping the door.
- Maximum acceptable load: 15 kg.
- Inner doors can be mounted in our stainless steel floor-standing enclosures (SFX and SMX).
- Material: Steel
- Finish: Structured finish, epoxy polyester powder
- Colour: RAL 7035 grey

SF



SM



Comment:
Dimensions, see page 17

Supply:
One inner door and fixing elements

SM

NSYID166

Characteristics	Height (mm)	Width (mm)	References
Spacial SF/SM Inner door	1600	600	**NSYID166**
Spacial SF/SM Inner door	1600	800	**NSYID168**
Spacial SF/SM Inner door	1800	600	**NSYID186**
Spacial SF/SM Inner door	1800	800	**NSYID188**
Spacial SF/SM Inner door	1800	1000	**NSYID1810**
Spacial SF/SM Inner door	2000	600	**NSYID206**
Spacial SF/SM Inner door	2000	800	**NSYID208**
Spacial SF/SM Inner door	2000	1000	**NSYID2010**
Spacial SF/SM Inner door	2200	600	**NSYID226**
Spacial SF/SM Inner door	2200	800	**NSYID228**

SF Side Door



NSYSFD126

- Door for all sides of the enclosure, replaces the side panel.
- Installation directly on the structure of the enclosure, opening 120°.
- Lock with handle and 5 mm double bar insert.
- 4 locking points.
- Reinforcement frame, cut-out with a pitch of 25 mm.
- Opening to right or left.
- Material: Steel
- Finish: Structured finish, epoxy polyester powder
- Colour: RAL 7035 grey

Comment:
Dimensions, see page 20

Supply:
One side door, four hinges, four catches and handle lock

Characteristics	Height (mm)	Width (mm)	References
Spacial SF Side door	1200	600	**NSYSFD126**
Spacial SF Side door	1200	800	**NSYSFD128**
Spacial SF Side door	1400	600	**NSYSFD146**
Spacial SF Side door	1400	800	**NSYSFD148**
Spacial SF Side door	1600	600	**NSYSFD166**
Spacial SF Side door	1600	800	**NSYSFD168**
Spacial SF Side door	1800	400	**NSYSFD184**
Spacial SF Side door	1800	500	**NSYSFD185**
Spacial SF Side door	1800	600	**NSYSFD186**
Spacial SF Side door	1800	800	**NSYSFD188**
Spacial SF Side door	2000	300	**NSYSFD203**
Spacial SF Side door	2000	400	**NSYSFD204**
Spacial SF Side door	2000	500	**NSYSFD205**
Spacial SF Side door	2000	600	**NSYSFD206**
Spacial SF Side door	2000	700	**NSYSFD207**
Spacial SF Side door	2000	800	**NSYSFD208**
Spacial SF Side door	2200	400	**NSYSFD224**
Spacial SF Side door	2200	500	**NSYSFD225**
Spacial SF Side door	2200	600	**NSYSFD226**
Spacial SF Side door	2200	800	**NSYSFD228**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Partial doors

Front fix panel for modularity

- Top and bottom fix panel to obtain modularity required to install partial doors.
- It is needed to purchase **NSYMIC6** and **NSYMIC8**.
- Height 100 mm fixed panels are delivered as standard for the compartmentalised enclosure, Spacial SFM.
- Possibility to order it separately for Spacial SF framework in kit supply.
- Available in 2 heights (mm).
- Ingress protection rating: IP54 according to IEC 60529

NSYMFP2M6

Characteristics	Height (mm)	Width (mm)	References
Spacial SFM - Front Fix panel for modularity	100	600	**NSYMFP2M6**
Spacial SFM - Front Fix panel for modularity	250	600	**NSYMFP5M6**
Spacial SFM - Front Fix panel for modularity	100	800	**NSYMFP2M8**
Spacial SFM - Front Fix panel for modularity	250	800	**NSYMFP5M8**

Frontal partial doors

- Plain partial door with lock 5 mm double bar insert.
- They are fixed to the uprights of the framework by means of hinges.
- Drilling template for uprights ref. NSYMDT (Only one drilling template required per order).
- Opening to right or left.
- 1, 2 or 4 locking points according different heights.
- Possibility to replace locking insert.
- Available in following heights (mm).
- Ingress protection rating: IP54 according to IEC 60529

NSYMPD3M6

Characteristics	Height (mm)	Width (mm)	References
Spacial SFM Frontal partial door	150	600	**NSYMPD3M6**
Spacial SFM Frontal partial door	200	600	**NSYMPD4M6**
Spacial SFM Frontal partial door	250	600	**NSYMPD5M6**
Spacial SFM Frontal partial door	300	600	**NSYMPD6M6**
Spacial SFM Frontal partial door	400	600	**NSYMPD8M6**
Spacial SFM Frontal partial door	450	600	**NSYMPD9M6**
Spacial SFM Frontal partial door	600	600	**NSYMPD12M6**
Spacial SFM Frontal partial door	800	600	**NSYMPD16M6**
Spacial SFM Frontal partial door	900	600	**NSYMPD18M6**
Spacial SFM Frontal partial door	1000	600	**NSYMPD20M6**
Spacial SFM Frontal partial door	1200	600	**NSYMPD24M6**
Spacial SFM Frontal partial door	150	800	**NSYMPD3M8**
Spacial SFM Frontal partial door	200	800	**NSYMPD4M8**
Spacial SFM Frontal partial door	250	800	**NSYMPD5M8**
Spacial SFM Frontal partial door	300	800	**NSYMPD6M8**
Spacial SFM Frontal partial door	400	800	**NSYMPD8M8**
Spacial SFM Frontal partial door	450	800	**NSYMPD9M8**
Spacial SFM Frontal partial door	600	800	**NSYMPD12M8**
Spacial SFM Frontal partial door	800	800	**NSYMPD16M8**
Spacial SFM Frontal partial door	900	800	**NSYMPD18M8**
Spacial SFM Frontal partial door	1000	800	**NSYMPD20M8**
Spacial SFM Frontal partial door	1200	800	**NSYMPD24M8**

Frontal transparent partial doors

- Glazed (Securit glass) partial door with lock 5 mm double bar insert.
- They are fixed to the uprights of the framework by means of hinges.
- Opening to right or left.
- 1 or 2 locking points according different heights.
- Available in following heights (mm).
- Ingress protection rating: IP54 according to IEC 60529


NSYMPD26T

Characteristics	Height (mm)	Width (mm)	References
Spacial SFM Frontal Transparent partial doors	200	600	**NSYMPD26T**
Spacial SFM Frontal Transparent partial doors	400	600	**NSYMPD46T**
Spacial SFM Frontal Transparent partial doors	600	600	**NSYMPD66T**
Spacial SFM Frontal Transparent partial doors	800	600	**NSYMPD86T**
Spacial SFM Frontal Transparent partial doors	1000	600	**NSYMPD106T**
Spacial SFM Frontal Transparent partial doors	200	800	**NSYMPD28T**
Spacial SFM Frontal Transparent partial doors	400	800	**NSYMPD48T**
Spacial SFM Frontal Transparent partial doors	600	800	**NSYMPD68T**
Spacial SFM Frontal Transparent partial doors	800	800	**NSYMPD88T**
Spacial SFM Frontal Transparent partial doors	1000	800	**NSYMPD108T**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Steel floor-standing enclosures

Intermediate crossbar

NSYMIC6

- Mounted between partial doors or between doors and control desk, guaranteeing IP54 according to IEC 60529.
- Crossbar with direct fixing to the structure.
- Available in 2 widths (mm).

Supply:
2 crossbars with fixing elements.

Characteristics	Width (mm)	References
Spacial SF-Intermediate Crossbar	600	**NSYMIC6**
Spacial SF-Intermediate Crossbar	800	**NSYMIC8**

Folding panel

NSYCDP36

- Height 300 mm horizontal panel, hinged at the top.
- Helps guarantee" protection of the sets of bars.
- Opening angle: 110°.
- It is installed together with partial doors to create the modularity of the enclosure.
- 2 locking points, 5 mm double bar insert.
- Available in 2 widths (mm).

Characteristics	Width (mm)	References
Spacial SF Folding panel	600	**NSYCDP36**
Spacial SF Folding panel	800	**NSYCDP38**

Control desk

NSYMCOD264

- Support for human-machine dialogue.
- Height 400 mm Control desk is installed together with partial doors to create the modularity of the enclosure.
- 2 locking points, 5 mm double bar insert.
- Available in 2 widths (mm).

Characteristics	Width (mm)	References
Spacial SF Control desk	600	**NSYMCOD264**
Spacial SF Control desk	800	**NSYMCOD284**

Metal document pocket

NSYSDP6M

- Direct mounting on the reinforcement frame of the door.
- Adjustable depth with a pitch of 25 mm.
- Material: Steel
- Finish: Structured finish, epoxy polyester powder
- Colour: RAL 7035 grey



Supply:
1 metal document pocket and fixing elements

Characteristics	(D) Width (mm)	References
Spacial SF/SM Metal document pocket	600	**NSYSDP6M**
Spacial SF/SM Metal document pocket	800	**NSYSDP8M**

Plastic document pocket

NSYDPA5

- Attachment by adhesive tape.
- Material: Polystyrene (PS)
- Colour: RAL 7035 grey (NSYDPA4: RAL 9001)



Comment:
NSYDPA44 not compatible with 19" chassis or modular distribution.

Supply:
1 plastic document pocket

Characteristics	Doc. format	A (mm)	B (mm)	C (mm)	References
Spacial SF/SM Plastic document pocket	A5	174	188	22	**NSYDPA5**
Spacial SF/SM Plastic document pocket	A4	230	247	23	**NSYDPA4**
Spacial SF/SM Plastic document pocket	A4	234	278	40	**NSYDPA44**
Spacial SF/SM Plastic document pocket	A3	285	476	35	**NSYDPA3**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Steel floor-standing enclosures

Folding support tray

NSYSDT5

NSYSDT8

- Adjustable horizontal support for laptop computers, documents or any other element.
- Installation on the reinforcement frame of the door.
- Can also be installed on the door cross rails, see page 301.
- 4 positions: 45°, 60°, 75° and 90°.
- Maximum load: 30 kg
- Material: Steel
- Finish: Structured finish, epoxy polyester powder
- Colour: RAL 7035 grey



Supply:
1 folding support tray and fixing elements

Characteristics	Width (mm)	References
Spacial SF/SM-Folding support tray	500	**NSYSDT5**
Spacial SF/SM-Folding support tray	600	**NSYSDT6**
Spacial SF/SM-Folding support tray	800	**NSYSDT8**

180° hinge

- Hinge with opening of 180°.
- Intended to replace the 120° hinges installed as standard.
- They are compatible with the transparent door and can be installed even with enclosure suites.
- Maximum load: 60 kg on the door
- Material: Aluminium and zamak
- Finish: Painted RAL 9005 black
- NEMA Types:
  - SF: NEMA Type 1, 3R and 12
  - SM single door: NEMA Type 1, 2, 3, 3R, 5, 12 and 13

Supply:
4 hinges

NSYSH180NC

Characteristics	References
Spacial SF/SM 180° hinge	**NSYSH180NC**

Door-centring caster

NSYSDRC

- Allows the door to be raised when closing.
- Direct mounting on the reinforcement frame.
- Maximum load: 90 kg

Supply:
One centring roller and fixing elements

Characteristics	References
Spacial SF/SM Door-centring caster	**NSYSDRC**

Door switch

- The switch is fixed to the structure of the enclosure.
- Drilled M20 cable entry for cable gland.
- NC + NO contact, 240 V AC / 3 A (IEC 60947-5-1)
  250 V DC / 0,1 A (IEC 60947-5-1)

Supply:
1 door switch and fixing elements

NSYDCM20

Characteristics	References
Spacial SF/SFX Door switch	**NSYDCM20**
Spacial SM Door switch	**NSYMDCM20**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Life Is On Schneider Electric

Steel floor-standing enclosures

Locking system

Padlock locking

NSYBLKH123

- Padlock locking system, for installation in all the handles of the Spacial SF and Spacial SM enclosures.
- Bolt with 7.5 mm drill hole.

Supply:
One cut-out handle, bolt for padlock and bolt fixing screw

Characteristics	References
Spacial SF/SM Padlock locking	**NSYBLKH123**

CNOMO kit

NSYCNOH123

- Locking system to be installed on the central locking bar of the door.
- It works as a locking bar immobiliser, helping prevent the handle from closing while the door is still open.
- It is compatible with all handle lock versions, except the flat lock and the small flat lock.

Supply:
One mechanism and fixing elements

Characteristics	References
Spacial SF/SM CNOMO kit	**NSYCNOH123**

Push button handle with 3524E key

NSYSFHPB



- Push button handle with 3524E key for Spacial SF and Spacial SM enclosures.
- Locking and unlocking by key and opening by pushing the insert.
- Handle material: Polyamide 6 with 30% fibreglass
- Color: RAL 9005
- Fire resistant: 650°C

Supply:
Push button handle, two 3524E keys and fixing elements (insert included)

Characteristics	References
Spacial SF/SM Push button handle with 3524E key	**NSYSFHPB** New

Handle for shape inserts and cylindrical barrels

NSYSFHS1



- Easy to change the opening direction of the door, right/left.
- Space reserved for enclosure identification, 21 x 27 mm, protected by a label frame.
- Handle material: Polyamide 6 with 30 % fibreglass
- Colour: RAL 9005
- Mechanical protection rating: IK10 according to IEC 62262
- Fire resistance: 650°C

Supply:
Standard handle and fixing elements (insert not included)

Characteristics	References
Spacial SF/SM Handle for shape inserts and cylindrical barrels	**NSYSFHS1**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Steel floor-standing enclosures

Shape inserts



NSYINS61

Characteristics	References
6 mm square insert	**NSYINS61**
Female 6 mm square insert	**NSYINS6G1**
7 mm square insert	**NSYINS71**
8 mm square insert	**NSYINS81**
Female 8 mm square insert	**NSYINS8G1**
6.5 mm triangular insert	**NSYINT61**
7 mm triangular insert	**NSYINT71**
8 mm triangular insert	**NSYINT81**
9 mm triangular insert	**NSYINT91**
10 mm triangular insert	**NSYINT101**
10 mm keyless hexagonal insert	**NSYINH31**
3 mm double bar insert	**NSYINDB31**
5 mm double bar insert	**NSYINDB51**
Daimler Benz insert	**NSYINBENZ1**
Fiat insert	**NSYINFIAT1**
Keyless USA slot insert	**NSYINUSA1**
Crown insert	**NSYINCW1**

Push button

NSYINPULS1

Characteristics	References
Push button	**NSYINPULS1**

Cylindrical barrels



NSYIN405E1

Characteristics	References
405E key lock	**NSYIN405E1**
421E key lock	**NSYIN421E1**
455 key lock	**NSYIN4551**
1242E key lock	**NSYIN1242E1**
1332E key lock	**NSYIN1332E1**
2124E key lock	**NSYIN2124E1**
2131A key lock	**NSYIN2131A1**
2132A key lock	**NSYIN2132A1**
2331A key lock	**NSYIN2331A1**
2433A key lock	**NSYIN2433A1**
2452E key lock	**NSYIN2452E1**
3113A key lock	**NSYIN3113A1**
3122E key lock	**NSYIN3122E1**
3123A key lock	**NSYIN3123A1**
3131A1 key lock	**NSYIN3131A1**
3133A key lock	**NSYIN3133A1**
3422E key lock	**NSYIN3422E1**
3432E key lock	**NSYIN3432E1**
6101 key lock	**NSYIN6101**
EDF1300 key lock	**NSYINF1301**
EDF1400 key lock	**NSYINF1401**
Michelin 8079 keyless lock	**NSYINICHEL8791**
Michelin 8133 keyless lock	**NSYINICHEL8131**
Michelin 8376 keyless lock	**NSYINICHEL8371**
E1 keyless lock	**NSYINE11**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Steel floor-standing enclosures

Handles for insert types DIN, KABA, ASSA, Insert handle

NSYSFHD2

- The inserts are easily and quickly mounted without any screws and allow the installation of profiled DIN, KABA and ASSA locks.
- To install shape inserts or cylindrical barrels, it is necessary to add adapter ref. NSYLADP.
- Easy to change the opening direction of the door, right/left.
- Space reserved for enclosure identification, 21 x 27 mm, protected by a label frame.
- Handle material: Polyamide 6 with 30 % fibreglass
- Colour: RAL 9005
- Mechanical protection rating: IK10 according to IEC 62262
- Fire resistance: 650°C



Supply:
One handle for DIN, KABA and ASSA inserts and fixing elements (insert not included)

Characteristics	References
Spacial SF/SM Insert handle	**NSYSFHD2**

Handles for insert types DIN, KABA, ASSA, Double-insert handle

NSYSFHD3

- The double insert handle can perform the "AND" and "OR" functions (are supplied with the handle).
  - "AND" function: One insert blocks the activation of the other insert.
  - "OR" function: Either insert can release the handle.
- Easy to change the opening direction of the door, right/left.
- Space reserved for enclosure identification, 21 x 27 mm, protected by a label frame.
- To install shape inserts or cylindrical barrels, it is necessary to add adapter ref. **NSYLADP**.
- Handle material: Polyamide 6 with 30 % fibreglass
- Colour: RAL 9005
- Mechanical protection rating: IK10 according to IEC 62262
- Fire resistance: 650°C



Supply:
One handle for DIN, KABA and ASSA inserts and fixing elements (insert not included)

Characteristics	References
Spacial SF/SM Double-insert handle	**NSYSFHD3**

Lock system: DIN, KABA and ASSA


NSYINDIN2


NSYIN1242E2



Comment:
NSYINKBA2: Adapter for receiving the KABA8, KABA20 and KABA start cylinders.

Characteristics	References
Spacial SF/SM Adapter for DIN cylinder	**NSYINDIN2**
Spacial SF/SM Adapter for KABA cylinder	**NSYINKBA2**
Spacial SF/SM Adapter for ASSA cylinder	**NSYINASSA2**
Spacial SF/SM 1242E key lock	**NSYIN1242E2**
Spacial SF/SM Reinforced key lock	**NSYINKR2**
Spacial SF/SM JIS key lock	**NSYINKJIS2**
Spacial SF/SM FAC key lock	**NSYINKFAC2**

Adapter for shape inserts and cylindrical barrels

NSYLADP



- Plastic adapter for installing shape inserts and cylindrical barrels in handle lock types DIN, KABA, ASSA.
- See shape inserts and cylindrical barrels.
- See insert types DIN, KABA, ASSA.

Supply:
1 unit

Characteristics	References
Spacial SF/SM Adapter for shape inserts and cylindrical barrels	**NSYLADP**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Steel floor-standing enclosures

Flat escutcheon lock

- Optional flat escutcheon lock. Replaces the handle lock.
- Easy to change the opening direction of the door, right/ left.
- Possibility of changing the turning direction of the insert.
- Handle material: Polyamide 6 with 30 % fibreglass
- Colour: RAL 9005
- Mechanical protection rating: IK10 according to IEC 62262
- Fire resistance: 650°C



Supply:
Flat lock, shape insert, key and fixing elements

NSYSFLOCK24

NSYSFLOCKT8

NSYSFLOCKT7

NSYSFLOCKT6

NSYSFLOCKSG8

NSYSFLOCKS8

NSYSFLOCKS7

NSYSFLOCKS6

NSYSFLOCKDB5

Characteristics	References
Flat lock + screwdriver slot, 2 mm groove	**NSYSFLOCK24**
Flat lock + 8 mm triangular insert	**NSYSFLOCKT8**
Flat lock + 7 mm triangular insert	**NSYSFLOCKT7**
Flat lock + 6.5 mm triangular insert	**NSYSFLOCKT6**
Flat lock + 8 mm female square insert	**NSYSFLOCKSG8**
Flat lock + 8 mm square insert	**NSYSFLOCKS8**
Flat lock + 7 mm square insert	**NSYSFLOCKS7**
Flat lock + 6 mm square insert	**NSYSFLOCKS6**
Flat lock + 5 mm double bar insert	**NSYSFLOCKDB5**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.













Models with a width of 1200 mm
without top/bottom adjustment rails

Inner door



Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.















Inner door



Side door



Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Spacial SBX

Stainless-Steel Industrial Boxes

Spacial SBX

Introduction	124
Characteristics	127
Common Accessories	128
Dimensions	132

4

What is stainless steel?

How is the stainless steel grade determined?

These enclosures have been specially designed for the chemical, oil and food and beverage industries, among others, which are particularly demanding in terms of hygiene and resistance to corrosion.

Thanks to an elaborate composition

The following table shows the percentages of the main alloy elements that make up stainless steels. The resistance of the material to aggressive agents in the environment depends mainly on these alloys.

Stainless steel type		Chemical composition (%)			
AISI grade	N. Europe	Carbon	Chromium	Nickel	Molybdenum
304L	1.4307	< 0.03	17 - 19	8 - 10	0
316L	1.4404	< 0.03	17 - 19	10 - 13	2 - 2.25

Choosing a stainless steel grade AISI 304L stainless steel

The most commonly used type in the food and beverage industry for its resistance to corrosion and easy cleaning.

- Prevention against corrosion, especially in the presence of organic acids.
- Resistance to the action of nitrous gas in the presence of condensation water and in most aggressive environments.

AISI 316L stainless steel

Recommended in salty or chlorinated environments due to its very high resistance to corrosion thanks to the presence of molybdenum.

- Improved resistance to corrosion.
- Particularly well adapted to environments charged with acidity, bromine and saline halides or which use very corrosive additives and solvents.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

The finish

The finish: 3 solutions against aggressive environmental agents

Surface condition plays an important role in the fight against bacteria. The lower the roughness, the fewer bacteria become incrusted. Reduced roughness means fewer bacteria, less adherence of materials and an impeccable finish. To choose a finish is also to choose an appearance of the enclosures that matches the environment of other machines and equipment.

Solution 1: Scotch-Brite® brushing

The method used consists of brushing as defined by the ASTM (American Society for Testing and Material).

- Finish very commonly used for the chemical and food and beverage industries.
- Surface roughness is improved thanks to an additional polishing process which offers more efficient characteristics against polluting elements.
- Surface roughness: Ra ≤ 0.8 µm.

Solution 2: Micro-beading (on request)

Exclusiveness, an impeccable finish with smooth silky appearance.

The method:
- Bombardment with miniscule ceramic balls of the entire surface to be treated at very high speed.
- Closes micro-cracks caused during lamination by flattening.

The result:
- Increased hardness.
- Reduced surface roughness: Ra ≈ 0.8 µm.
- A perfectly even surface, with a silky appearance (no scratches and no burrs).
- Reduces the adherence of materials.
- Allows disinfection.
- Typical application: Pharmaceutical and food and beverage industries.

Solution 3: Protective painting (on request)

The highest protection against aggressions, external pollution and projections of metal particles.

- Provides the ultimate protection against corrosion.
- Typical applications: Marine, seaside, off-shore.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

New Stainless-Steel Industrial Boxes

Simplicity, ergonomics and quality.

Save Time

Get the Best Esthetic

Get a High Quality Cut-Out

Selection

- 6 sizes
- 80 mm and 120 mm in depth.

Personalized cut-outs.

- Enclosure delivered with cut-outs, so you can focus on your added-value work
- Cut-outs made with an industrial laser machine for a perfect result, burr-free, with high accuracy machining tolerances
- Scotch-Brite® brushed.
- External surfaces with no scratches

Sturdy with Good Ingress Protection

- Thickness of 1.2 mm
- Mechanical protection rating up to IK10.
- Ingress protection rating up to IP66.



Added Value to your Work

- Quality and esthetics.
- Same dimensions as steel boxes (SBM range).
- Mounting with versatile external brackets.
- Certification (on request): UL, Veritas and BVM.

Ergonomics

- Cover opening and accessory mounting with just a screwdriver.

See page 532 for details or consult our web site www.se.com

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Characteristics	Spacial SBX Flat box
	Box with plain faces Single-piece body (rectangular structure). Front design incorporating folded gutters. Flat rear. 2 drilled profiles for installing mounting plates and DIN rails, with mounting centers of 12.5 mm. Equipped with 4 half-turn thread screws to help help ensure maximum watertightness. Polyurethane sealing gasket. **Protection of personnel** Earthing connection mandatory for all boxes: Spacial SBX Stainless-Steel boxes are equipped with an M6 x 10 mm earthing stud welded in the cover, to be linked with the body for equipotential connection. Earthing braid to be ordered separately (Ø 6.4 mm terminal).
Material	AISI 304L stainless steel, thickness of 1.2 mm.
Finish	Scotch-Brite® brushed.
Ingress protection rating	IP66
Mechanical protection rating	IK10
Standard compliance with enclosure standard	IEC 62208 and the RoHS directive.
Certifications	• UL, BV, BVM • NEMA Type 4, 4X, 13 according to UL 508A standard • Fire class: M0
Installation	**Indoor installation** Direct wall-mounting (4 x Ø 10 mm holes with sealing plugs to maintain the IP rating) or with the help of fixing lugs installed from the outside (to be ordered separately, see the specific accessory pages). Distance between mounting holes enables the installation of the box in the same locations as many existing enclosures. **Outdoor installation** Compliant with IEC 62208 regarding type tests specified in §9.12 resistance to ultra-violet (UV) radiation and §9.13 resistance to corrosion. It is always advisable to place the box under shelter to avoid water stagnation on the upper part of the enclosure.
Maximum load capacity	On the body: 50 kg/m²
Other characteristics	**Vibration constraints** Specific construction of the Spacial SBX - Single-piece body (rectangular structure). The rear is flat without added parts - this helps ensure compliance with certain vibration constraints. The tests were conducted according to the marine application by Bureau Veritas Marine.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Stainless-Steel Industrial Boxes

Dimensions			Box	Mounting plate	DIN rail	Fixing lugs	Sealing kit
Height (mm)	Width (mm)	Depth (mm)	Supply: 1 piece	Supply: 1 piece	Supply: 10 pieces	Supply: 4 pieces	Supply: 1 piece
			References	References	References	References	References
150	150	80	**NSYSBX15158** New	**NSYMM11SB**	**NSYAMRD15357SB**		
150	300	80	**NSYSBX15308** New	**NSYMM13SB**	**NSYAMRD30357SB**		
200	200	80	**NSYSBX20208** New	**NSYMM22SB**	**NSYAMRD20357SB**	**NSYAEFPFSBX**	**NSYPPSB**
200	300	80	**NSYSBX20308** New	**NSYMM23SB**	**NSYAMRD30357SB**		
200	400	120	**NSYSBX204012** New	**NSYMM24SB**	**NSYAMRD40357SB**		
300	300	120	**NSYSBX303012** New	**NSYMM33SB**	**NSYAMRD30357SB**		

Mounting plate

- Material: Galvanised steel
- Installation: Mounting by means of 2* or 4 x Ø 5 mm self-tapping screws, Pozidriv head, ref. **NSYAMFSB**. Mounting plate installation points compatible with many other brands of accessories.



Comment:
* Only 2 screws for mounting plates with height of 150 mm

Supply:
1 unit, supplied without screws

NSYMM11SB

Characteristics	Dimensions Height (mm)	Width (mm)	Mounting plate, Dimensions A (mm)	B (mm)	C (mm)	Thickness (mm)	References
Mounting plate	150	150	135	135	-	1.5	**NSYMM11SB**
Mounting plate	150	300	135	285	-	1.5	**NSYMM13SB**
Mounting plate	200	200	185	185	100	1.5	**NSYMM22SB**
Mounting plate	200	300	185	285	100	1.5	**NSYMM23SB**
Mounting plate	200	400	185	385	100	2.0	**NSYMM24SB**
Mounting plate	300	300	185	185	200	1.5	**NSYMM33SB**

Symmetrical DIN rails 35 x 7.5 mm

- Material: Galvanised steel
- Installation: Mounting by means of 2 x Ø 5 mm self-tapping screws, Pozidriv head, ref. **NSYAMFSB** (All boxes are delivered with 5 x Ø 5 mm self-tapping screws).



Supply:
10 rails, supplied without screws

NSYAMRD15357SB

Characteristics	Box Width (mm)	DIN rail Length A (mm)	References
Symmetrical DIN rail	150	135	**NSYAMRD15357SB**
Symmetrical DIN rail	200	185	**NSYAMRD20357SB**
Symmetrical DIN rail	300	285	**NSYAMRD30357SB**
Symmetrical DIN rail	400	385	**NSYAMRD40357SB**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Stainless-Steel Industrial Boxes

Self-tapping screws

- Same reference for all dimensions
- Self-tapping, Pozidriv head, screws, for Ø 5 mm holes.

Supply:
100 units

NSYAMFSB

Characteristics	References
Self-tapping screws	**NSYAMFSB**

Sealing kit

- The sealing kit helps to set up a lead-sealed wire of cover opening.
- Colour: Green
- Ingress protection rating: IP66 according to IEC 60529
- Installation: Replaces the standard sealing washer on the box
- Same reference for all dimensions

Supply:
1 unit

NSYPPSB

Characteristics	References
Sealing kit SBM	**NSYPPSB**

Mounting lugs

A: Enclosure height
B: Enclosure width



- Wall-mounting lugs to be mounted directly on the rear of the box, either in horizontal or vertical position. Their versatile design complies with the mounting dimensions of many other enclosures.
- Installation: Horizontal or vertical position, distance between wall and enclosure: 10 mm
- Maximum load: 70 kg

Supply:
4 wall-mounting lugs, screws and pre-mounted sealing gaskets

NSYAEFPFSB

Characteristics	References
Wall-mounting lugs	**NSYAEFPFSB**

4

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Simple-5

- ISO cable gland.
- Material: PA6 Polyamide, neoprene gasket
- Colour: RAL 7035 grey
- Cable entry material: Combined
- Installation possibilities: On cable gland plate or directly on enclosure
- Flexibility of the installation: Low
- Reversibility: Medium
- Ingress protection rating: IP68
- Cable retention: High
- Cable diameter (mm): From 12 to 40
- Cable Installation time: Slow
- Quantity of cables to be fitted for a given surface: +
- Cable entries for cables with connectors: No
- Cut-out dimensions (mm): Various circular hole diameters according to cable diameter
- External dimensions (mm): From Ø 15 to 46
- Certificates: Glow wire resistance: 960°C
- Standard: Compliance with VDE, UL and CSA
- Flame resistance: 750 °C



Supply:
The cable glands are supplied with nuts
Pack of 20 (M12 to M20), of 10 (M25 and M32), of 5 (M40)

ISM71503

Characteristics	Dimensions					References
	Cable (Ø mm)	Drill hole (Ø mm)	TD	TL	SW	
Kabelverschraubung M12, RAL 7035	3 / 6.5	12.2 (0 + 0.2)	12	6	15	**ISM71501**
Kabelverschraubung M16, RAL 7035	4 / 8	16.2 (0 + 0.2)	16	8	19	**ISM71502**
Kabelverschraubung M20, RAL 7035	6 / 12	20.2 (0 + 0.2)	20	10	24	**ISM71503**
Sicherheits-Kabelverschraubung M20, RAL 3000	6 / 12	20.2 (0 + 0.2)	20	10	24	**IMT36150**
Kabelverschraubung M25, RAL 7035	11 / 17	25.2 (0 + 0.2)	25	8	29	**ISM71504**
Kabelverschraubung M32, RAL 7035	15 / 21	32.2 (0 + 0.3)	32	10	36	**ISM71505**
Kabelverschraubung M40, RAL 7035	19 / 28	40.5 (0 + 0.3)	40	10	46	**ISM71506**

Synthetic snap in cable gland

- Without thread.
- Easy assembly and disassembly.
- Suitable for walls from 0.5 to 4 mm thick.
- Material: PA6 Polyamide, neoprene gasket
- Colour: RAL 7035 grey, RAL 7001, RAL 9005. Other colours on demand
- Cable entry material: Non armoured
- Installation possibilities: On cable gland plate or directly on enclosure
- Flexibility of the installation: Low
- Reversibility: Medium
- Ingress protection rating: IP66
- Cable retention: High
- Cable diameter (mm): From 16 to 40
- Cable Installation time: Slow
- Quantity of cables to be fitted for a given surface: +
- Cable entries for cables with connectors: No
- Thread type: Metric EN 60423 Other types are available on demand
- Cut-out dimensions (mm): Various circular hole diameters according to cable diameter
- External dimensions (mm): From Ø 22 to 46
- Certificates: UL 94 V-2 (except for the size M40)
- Standard: DIN EN 62444, UL 514B, UL 514B§8.26.7
- Temperature range: -20°C to + 100°C



Supply:
The cable glands are supplied with nuts
Pack of 20 (M16 and M20), of 10 (M25 and M32), of 5 (M40)

NSYCGSP16

Characteristics	Dimensions							References	
	Ø	Ø min / max	Drill Ø	SL	SD	H			
Synthetic snap in cable gland	M16	5/10	16.2 to 16.4	9	15.9	42.5	22	**NSYCGSP16**	New
Synthetic snap in cable gland	M20	6/12	20.2 to 20.4	9	19.9	41.5	24	**NSYCGSP20**	New
Synthetic snap in cable gland	M25	11/17	25.2 to 25.4	9	24.9	43.5	29	**NSYCGSP25**	New
Synthetic snap in cable gland	M32	15/21	32.2 to 32.4	9	31.9	49.5	36	**NSYCGSP32**	New
Synthetic snap in cable gland	M40	19/28	40.2 to 40.4	11.5	39.9	56	46	**NSYCGSP40**	New

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Stainless-Steel Industrial Boxes

Stainless steel cable gland with lamellar insert

- Lamellar technology provides excellent resistance to traction as well as excellent torsional protection. For outdoor use, or for aggressive environments.
- Material: Stainless steel AISI 304L or AISI 316L, neoprene gasket
- Cable entry material: Non armoured
- Installation possibilities: On cable gland plate or directly on enclosure
- Flexibility of the installation: Low
- Reversibility: Medium
- Ingress protection rating: IP68
- Cable retention: High
- Cable diameter (mm): From 12 to 40
- Cable Installation time: Slow
- Quantity of cables to be fitted for a given surface: +
- Cable entries for cables with connectors: No
- Thread type: Metric EN 60423
- Cut-out dimensions (mm): Various circular hole diameters according to cable diameter
- External dimensions (mm): From Ø 14 to 43
- Certificates: UL 94 V-2
- Standard: DIN EN 62444, UL 514
- Temperature range: -20°C to + 100°C



Supply:
The cable glands are supplied with nuts
Pack of 5 (M12 and M16), of 4 (M20 and M25), of 2 (M32 and M40)

NSYCGX12

Characteristics	Dimensions							References	
	Ø	Ø min / max	Drill Ø	TD	TL	H			
AISI 304L	M12	3/6.5	12 to 12.2	12	12	22	14	**NSYCGX12**	New
AISI 304L	M16	5/10	16 to 16.2	16	12	28.5	20	**NSYCGX16**	New
AISI 304L	M20	6/12	20 to 20.2	20	12	24	22	**NSYCGX20**	New
AISI 304L	M25	11/17	25 to 25.2	25	12	32.5	27	**NSYCGX25**	New
AISI 304L	M32	15/21	32 to 32.3	32	15	36	34	**NSYCGX32**	New
AISI 304L	M40	19/28	40 to 40.3	40	15	43.5	43	**NSYCGX40**	New
AISI 316L	M12	3/6.5	12 to 12.2	12	12	22	14	**NSYCGX12H**	New
AISI 316L	M16	5/10	16 to 16.2	16	12	28.5	20	**NSYCGX16H**	New
AISI 316L	M20	6/12	20 to 20.2	20	12	24	22	**NSYCGX20H**	New
AISI 316L	M25	11/17	25 to 25.2	25	12	32.5	27	**NSYCGX25H**	New
AISI 316L	M32	15/21	32 to 32.3	32	15	36	34	**NSYCGX32H**	New
AISI 316L	M40	19/28	40 to 40.3	40	15	43.5	43	**NSYCGX40H**	New

Earth braids

Supply:
10 earth braids
(nuts and washers not included)
Reference by unit. Order by multiples of 10 (10, 20, 30...)

- They help guarantee the earth connection for high frequencies, avoiding the disturbing electric currents that are produced.
- Material: Tinned copper.

NSYEB156D6

Characteristics	Section (mm²)	Terminal Ø (mm)	Length (mm)	Width (mm)	References
Earth braids	6	6.5	150	12	**NSYEB156D6**
Earth braids	10	6.5	150	17	**NSYEB1510D6**

Earth cables

Supply:
10 earth cables (nuts and washers not included).
Reference by unit. Order by multiples of 10 (10, 20, 30...)

- Make it easier to install a safe earth connection, with a perfect contact, with optimised length.
- Material: Brass and copper alloy terminal, green and yellow PVC insulating sheath

NSYEL136D6

Characteristics	Section (mm²)	Terminal Ø (mm)	Length (mm)	References
Earth cables	6	6.4	130	**NSYEL136D6**
Earth cables	6	6.4	160	**NSYEL166D6**
Earth cables	6	8.3	160	**NSYEL166D8**
Earth cables	10	8.3	170	**NSYEL1710D6**
Earth cables	6	6.4	220	**NSYEL226D6**
Earth cables	6	13	220	**NSYEL226D13**
Earth cables	25	8.3	220	**NSYEL2225D8**
Earth cables	10	6.4	250	**NSYEL2510D6**
Earth cables	25	8.3	350	**NSYEL3525D8**

Earthing strip

Supply:
- 1 earthing strip and fixing elements

- Perforated brass bar, 15 x 3 mm.
- 1 m long.
- 87 connection points, M5 drill holes

NSYECB1M153

Characteristics	References
Earthing strip	**NSYECB1M153**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Stainless-Steel Industrial Boxes

Section A-A



Section B-B



4

Dimensions Height (mm)	Width (mm)	Depth (mm)	Sheet thickness (mm)	Box installation Ah (mm)	Bh (mm)	Bw (mm)	Mounting C (mm)	D (mm)
150	150	80	1.2	20.5	109	109	125	12.5
150	300	80	1.2	20.5	109	259	275	12.5
200	200	80	1.2	20.5	159	159	175	12.5
200	300	80	1.2	20.5	159	259	275	12.5
200	400	120	1.2	20.5	159	359	375	12.5
300	300	120	1.2	20.5	259	259	275	12.5

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Limit of Cut-Out Zone



Dimensions			References	Dimensions for allowed zone for cut-out																
Height (mm)	Width (mm)	Depth (mm)		Bh (mm)	Bw (mm)	Ghr (mm)	Ghl (mm)	Gw (mm)	Jh (mm)	Jw (mm)	Kh (mm)	Kw (mm)	Lhl (mm)	Lhr (mm)	Lw (mm)	Mh (mm)	Mw (mm)	N (mm)	P (mm)	Q (mm)	R (mm)
150	150	80	NSYSBX15158	109	109	70	49	70	110	110	150	150	40	34.5	130	80	60	34.5	130	60	40
150	300	80	NSYSBX15308	109	259	70	49	220	110	260	150	300	40	34.5	280	80	210	34.5	130	60	40
200	200	80	NSYSBX20208	159	159	120	99	120	160	160	200	200	40	34.5	180	80	110	34.5	180	110	40
200	300	80	NSYSBX20308	159	259	120	99	220	160	260	200	300	40	34.5	280	80	210	34.5	180	110	40
200	400	120	NSYSBX204012	159	359	120	99	320	160	360	200	400	80	74.5	380	120	310	74.5	180	110	80
300	300	120	NSYSBX303012	259	259	220	199	220	260	260	300	300	80	74.5	280	120	210	74.5	280	210	80

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Stainless steel wall-mounting enclosures

5

Life Is On Schneider Electric

Stainless steel wall-mounting enclosures

Spacial S3X, Stainless steel wall-mounting enclosures

Introduction	136
Characteristics	138
Selection guide	140
Accessories	141
Dimensions	145

5

What is stainless steel?

How is the stainless steel grade determined?

These enclosures have been specially designed for the chemical, oil and food and beverage industries, among others, which are particularly demanding in terms of hygiene and resistance to corrosion.

Thanks to an elaborate composition

The following table shows the percentages of the main alloy elements that make up stainless steels. The resistance of the material to aggressive agents in the environment depends mainly on these alloys.

Stainless steel type		Chemical composition (%)			
AISI grade	N. Europe	Carbon	Chromium	Nickel	Molybdenum
304L	1.4307	< 0.03	17 - 19	8 - 10	0
316L	1.4404	< 0.03	17 - 19	10 - 13	2 - 2.25

Choosing a stainless steel grade AISI 304L stainless steel

The most commonly used type in the food and beverage industry for its resistance to corrosion and easy cleaning.

- Prevention against corrosion, especially in the presence of organic acids.
- Resistance to the action of nitrous gas in the presence of condensation water and in most aggressive environments.

AISI 316L stainless steel

Recommended in salty or chlorinated environments due to its very high resistance to corrosion thanks to the presence of molybdenum.

- Improved resistance to corrosion.
- Particularly well adapted to environments charged with acidity, bromine and saline halides or which use very corrosive additives and solvents.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

The finish

The finish: 3 solutions against aggressive environmental agents

Surface condition plays an important role in the fight against bacteria. The lower the roughness, the fewer bacteria become incrusted. Reduced roughness means fewer bacteria, less adherence of materials and an impeccable finish. To choose a finish is also to choose an appearance of the enclosures that matches the environment of other machines and equipment.

Solution 1: Scotch-Brite® brushing

The method used consists of brushing as defined by the ASTM (American Society for Testing and Material).

- Finish very commonly used for the chemical and food and beverage industries.
- Surface roughness is improved thanks to an additional polishing process which offers more efficient characteristics against polluting elements.
- Surface roughness: Ra ≤ 0.8 µm.

Solution 2: Micro-beading (on request)

Exclusiveness, an impeccable finish with smooth silky appearance.

The method:
- Bombardment with miniscule ceramic balls of the entire surface to be treated at very high speed.
- Closes micro-cracks caused during lamination by flattening.

The result:
- Increased hardness.
- Reduced surface roughness: Ra ≈ 0.8 µm.
- A perfectly even surface, with a silky appearance (no scratches and no burrs).
- Reduces the adherence of materials.
- Allows disinfection.
- Typical application: Pharmaceutical and food and beverage industries.

Solution 3: Protective painting (on request)

The highest protection against aggressions, external pollution and projections of metal particles.

- Provides the ultimate protection against corrosion.
- Typical applications: Marine, seaside, off-shore.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Stainless steel wall-mounting enclosures

These enclosures have been specially designed for the chemical, oil and food and beverage industries, among others, which are particularly demanding in terms of hygiene and resistance to corrosion.

This range can be configured according to your needs

4 differents services available:

- Assemble to order
- Mounting of standard accessories
- Painting
- Machining

Finishes

- Two types of steel offered as standard: 304L and 316L, with Scotch-Brite® brushed finish.
- Painted or micro-beaded finish (on request).

Robustness and durability

Resistance to external mechanical impacts:

- IK10: Plain door, IK08: Glazed door.
- Door reinforcement frame or profile.
- Stainless steel hinges.

Large range of accessories

- Stainless steel accessories: canopy, wall fixing lugs.
- Accessories of the standard offer: mounting plate, inner door, modular chassis and step slides.
- Large selection of locks with 100 % stainless steel transformation.

Convenience and time saving

- 304L or 316L stainless steel wall fixing lugs.
- Vertical reinforcement perforated profiles, which make it easier to equip the door.
- Reversible door opening to 120°.
- Easy installation directly on the machine thanks to the 4 rear drill holes.

Sealing

- Protection rating of IP66 (1 door) or IP55 (2 doors) according to IEC 60529: Complete protection against dust and water sprays.
- Polyurethane gasket.
- Gutter-shaped front profile.
- Three closure points for the double door.

See page 532 for details or consult our web site www.se.com

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Comment:
For more information, see page 145

Characteristics	NSYS3X●●●●	NSYS3X●●●●T	NSYS3X●●●●H
	304L stainless steel Enclosure with plain door.	304L stainless steel Enclosure with glazed door, Securit® glass, 4 mm thick.	316L stainless steel Enclosure with plain door.
Material	AISI 304L		AISI 316L
Finish	Scotch-Brite® brushed		
Thickness	10/10e - 15/10e mm		
Ingress protection rating	IP66 (1 door) or IP55 (2 doors) according to IEC 60529		
Mechanical protection rating	IK10 according to IEC 62262	IK08 according to IEC 62262	IK10 according to IEC 62262
Standards and certifications	See technical guides page 624		
Installation	Outdoor installation: Compliant with IEC 62208 regarding type tests specified in §9.12 (resistance to ultra-violet (UV) radiation) and §9.13 (resistance to corrosion). It is always advisable to install a canopy to avoid water stagnation on the upper part of the enclosure		
Other characteristics	• Single-piece body (cross-shaped structure). Gutter-shaped front profile • 4 rear studs for fixing the material • 2 cut-out vertical profiles on the door (from a height of 600 mm), with drill holes with a diameter of 4.25 mm and a pitch of 25 mm for installing accessories • Door strengthening frame (from a height of 1000 mm), cross-section of 20 mm x 15 mm, with drill holes with a diameter of 5 mm and a pitch of 25 mm • Standard lock with 3 mm double bar lock (chrome-plated zamak) • 2 locking points for heights of more than 500 mm or three points for two-door enclosures • Stainless steel hinges screwed to the body of the enclosure. They make it easier to remove and invert the door. Opening angle: 120° • Maximum load on the door: 50 kg/m² • Polyurethane gasket • M6 x 16 mm screws on the door and on the body, allowing equipotential connection between the earth connections (on request) • 4 holes for fixing to the wall directly or with the help of mounting lugs (on request), blocked by sealing plugs		

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

					304L stainless steel		316L stainless steel
External dimensions							
Height (mm)	Width (mm)	Depth (mm)	No. of locks	No. of doors	Plain door	Glazed door. The glazed door has no reinforcement.	Plain door
300	200	150	1	1	**NSYS3X3215**	-	**NSYS3X3215H**
300	250	150	1	1	**NSYS3X302515**	-	**NSYS3X302515H**
300	300	150	1	1	**NSYS3X3315**	-	**NSYS3X3315H**
400	300	150	1	1	**NSYS3X4315**	-	**NSYS3X4315H**
400	300	200	1	1	**NSYS3X4320**	**NSYS3X4320T**	**NSYS3X4320H**
400	400	200	1	1	**NSYS3X4420**	-	**NSYS3X4420H**
400	600	200	1	1	**NSYS3X4620**	-	**NSYS3X4620H**
500	400	200	2	1	**NSYS3X5420**	**NSYS3X5420T**	**NSYS3X5420H**
600	400	200	2	1	**NSYS3X6420**	**NSYS3X6420T**	**NSYS3X6420H**
600	600	250	2	1	**NSYS3X6625**	-	**NSYS3X6625H**
600	1000	300		2	**NSYS3X601030**	-	-
600	1200	300	[1]	2	**NSYS3X601230**	-	-
700	500	250	2	1	**NSYS3X7525**	**NSYS3X7525T**	**NSYS3X7525H**
800	600	250	2	1	**NSYS3X8625**	**NSYS3X8625T**	**NSYS3X8625H**
800	800	300	2	1	**NSYS3X8830**	-	**NSYS3X8830H**
800	1000	300		2	**NSYS3X801030**	-	-
800	1200	300	[1]	2	**NSYS3X801230**	-	-
1000	800	300	2	1	**NSYS3X10830**	**NSYS3X10830T**	**NSYS3X10830H**
1000	1000	300	[1]	2	**NSYS3X101030**	-	**NSYS3X101030H**
1200	800	300	2	1	**NSYS3X12830**	-	**NSYS3X12830H**
1200	1000	300	[1]	2	**NSYS3X121030**	-	**NSYS3X121030H**

[1] Three-point closure system.

Accessories

External dimensions									
Height (mm)	Width (mm)	Depth (mm)	No. of modules	Mounting plate Plain	Mounting plate Silkscreened	Mounting plate Microperforated	Mounting plate Telequick	Modular Chassis	Step slides
300	200	150	-	**NSYMM32**	-	**NSYMF32**	**NSYMR32**	-	-
300	250	150	-	**NSYMM3025**	-	-	**NSYMR3025**	-	-
300	300	150	-	**NSYMM33**	-	**NSYMF33**	**NSYMR33**	-	-
400	300	150	24	**NSYMM43**	**NSYMS43**	**NSYMF43**	**NSYMR43**	**NSYDLM24**	-
400		200	24	**NSYMM43**	**NSYMS43**	**NSYMF43**	**NSYMR43**	**NSYDLM24**	**NSYSDCR200**
400	400	200	-	**NSYMM44**	**NSYMS44**	**NSYMF44**	**NSYMR44**	-	**NSYSDCR200**
400	600	200	-	**NSYMM64**	**NSYMS64**	**NSYMF64**	**NSYMR46**	-	**NSYSDCR200**
500	400	200	48	**NSYMM54**	**NSYMS54**	**NSYMF54**	**NSYMR54**	**NSYDLM48**	**NSYSDCR200**
600	400	200	48	**NSYMM64**	**NSYMS64**	**NSYMF64**	**NSYMR64**	**NSYDLM48P**	**NSYSDCR200**
600	600	250	84	**NSYMM66**	**NSYMS66**	**NSYMF66**	**NSYMR66**	**NSYDLM84P**	**NSYSDCR250**
600	1000	300*	-	**NSYMM106**	-	**NSYMF106**	**NSYMR106**	-	**NSYSDCR300**
600	1200	300*	-	**NSYMM126**	-	**NSYMF126**	-	-	**NSYSDCR300**
700	500	250	66	**NSYMM75**	**NSYMS75**	**NSYMF75**	**NSYMR75**	**NSYDLM66**	**NSYSDCR250**
700	500	250	88	-	-	-	-	**NSYDLM88**	-
800	600	250	84	**NSYMM86**	**NSYMS86**	**NSYMF86**	**NSYMR86**	**NSYDLM84**	**NSYSDCR250**
800	600	250	112	-	-	-	-	**NSYDLM112**	-
800	800	300	-	**NSYMM88**	-	**NSYMF88**	**NSYMR88**	-	**NSYSDCR300**
800	1000	300[1]	-	**NSYMM108**	-	**NSYMF108**	**NSYMR108**	-	**NSYSDCR300**
800	1200	300[1]	-	**NSYMM128**	-	**NSYMF128**	**NSYMR128**	-	**NSYSDCR300**
1000	800	300	234	**NSYMM108**	-	**NSYMF108**	**NSYMR108**	**NSYDLM240**	**NSYSDCR300**
1000	1000	300	-	**NSYMM1010**	-	**NSYMF1010**	**NSYMR1010**	-	**NSYSDCR300**
1200	800	300	-	**NSYMM128**	-	**NSYMF128**	**NSYMR128**	-	**NSYSDCR300**
1200	1000	300	-	**NSYMM1210**	-	**NSYMF1210**	**NSYMR1210**	-	**NSYSDCR300**

[1] Three-point closure system.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Life Is On Schneider Electric

Stainless steel wall-mounting enclosures

Plinth

- Material: Stainless steel, AISI 304L or AISI 316L
- Finish: Scotch-Brite® brushing, to help guarantee the durability in application where the contact with the floor increase the risk of corrosion
- Installation: It is necessary to order separately the plinth fixing kit (ref. **NSYAPFXWM**) composed by fixing elements and drilling jig

NSYSPFX8100

Characteristics	Width	References
Plinth height 100 mm, Kit (4 corners + front and back), AISI 304L	800	**NSYSPFX8100**
Plinth height 100 mm, Kit (4 corners + front and back), AISI 304L	1000	**NSYSPFX10100**
Plinth height 100 mm, Kit (4 corners + front and back), AISI 316L	800	**NSYSPFX8100H**
Plinth height 100 mm, Kit (4 corners + front and back), AISI 316L	1000	**NSYSPFX10100H**

NSYSPSX3100

Characteristics	Depth	References
Plinth height 100 mm, Set of 2 side panels, AISI 304L	300	**NSYSPSX3100**
Plinth height 100 mm, Set of 2 side panels, AISI 316L	300	**NSYSPSX3100H**

NSYSPFX8200

Characteristics	Width	References
Plinth height 200 mm, Kit (4 corners + front and back), AISI 304L	800	**NSYSPFX8200**
Plinth height 200 mm, Kit (4 corners + front and back), AISI 304L	1000	**NSYSPFX10200**
Plinth height 200 mm, Kit (4 corners + front and back), AISI 316L	800	**NSYSPFX8200H**
Plinth height 200 mm, Kit (4 corners + front and back), AISI 316L	1000	**NSYSPFX10200H**

NSYSPSX3200

Characteristics	Depth	References
Plinth height 200 mm, Set of 2 side panels (x2), AISI 304L	300	**NSYSPSX3200**
Plinth height 200 mm, Set of 2 side panels (x2), AISI 316L	300	**NSYSPSX3200H**

Plain mounting plate screw

NSYS13M5HS

Characteristics	Supply	References
Plain mounting plate screw, Self-tapping screw M5 x 13	100	**NSYS13M5HS**
Plain mounting plate screw, Self-tapping screw M5 x 16	100	**NSYS16M5HS**
Plain mounting plate screw, Self-tapping screw M6 x 16	100	**NSYS16M6HS**

Accessories

Clip-on nuts: page 270
Reference: **AF1EA6**
Cable entries: page 272
Reference: **NSYSAM504SE**

Stainless steel cable gland with lamellar insert: page 274
Reference: **NSYCGX12**
Lighting: page 296
Reference: **NSYLAMLDS**

Adhesive plastic document pocket: page 300
Reference: **NSYDPA44**
Door switch: page 300
Reference: **NSYINLCRN**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Stainless steel wall-mounting enclosures

Canopy



NSYTX2015

- Material: 304L stainless steel sheet
- Finish: Scotch-Brite® brushed
- Thickness: 15/10e mm
- Installation: Direct fixing to the body of the enclosure

Supply:
Delivered with the fixings required for installation

Characteristics	Width (mm)	Depth (mm)	Dimensions A (mm)	B (mm)	C (mm)	D (mm)	E (mm)	References
Canopy	200	150	205	183	51	120	-	**NSYTX2015**
Canopy	250	150	205	183	51	120	-	**NSYTX2515**
Canopy	300	150	305	183	51	220	-	**NSYTX3015**
Canopy	300	200	305	233	51	220	70	**NSYTX3020**
Canopy	400	200	405	233	70	320	70	**NSYTX4020**
Canopy	600	200	605	233	70	520	70	**NSYTX6020**
Canopy	600	250	605	283	70	520	120	**NSYTX6025**
Canopy	1000	300	1005	333	70	920	170	**NSYTX10030**
Canopy	1200	300	1205	333	70	1120	120	**NSYTX12030**
Canopy	500	250	505	283	70	420	120	**NSYTX5025**
Canopy	800	300	805	333	70	720	170	**NSYTX8030**

Wall fixing lugs

- **A:** Enclosure height
- **B:** Enclosure width



Vertical position Horizontal position

NSYPFCX

Installation:
Mounting of the wall fixing lugs in horizontal or vertical position. Fixing from the outside.
- Wall-enclosure separation of 12 mm
- Maximum load: 250 kg

Supply:
Set of four wall fixing lugs

Characteristics	References
Wall fixing-lug, 304L stainless steel	**NSYPFCX**
Wall fixing-lug, 316L stainless steel	**NSYPFC2X**

Support bracket for enclosure with anti-tilt kit and reinforcement

NSYCOCNS1400

- Material: Steel
- The support bracket is used when the enclosure cannot be hung from a wall or a post.
- Suitable for outdoor use.
- Maximum enclosure dimensions: 1000 x 800 x 300 mm.
- Floor attachment by standard M12 fastenings.
- Finish: Epoxy polyester paint
- Colour: RAL 7035 grey
- Maximum load: 120 kg

Characteristics	Height (mm)	References
Support bracket for enclosure with anti-tilt kit and reinforcement	1400	**NSYCOCNS1400**
Support bracket for enclosure with anti-tilt kit and reinforcement	1800	**NSYCOCNS1800**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Stainless steel wall-mounting enclosures

1 point lock options



NSYSTDNCSX

NSYSTDCX2H

NSYCBXHCRN

NSYCL610CSX

NSYCBXHCRN

- Protection rating: IP66
- For the closures of double door enclosures, contact us.

Characteristics	Type	Material	References
Double bar lock	Escutcheon with insert, 3 mm	Chrome-plated zamak	**NSYSTDNCSX**
Insert	triangular, 8 mm	304L stainless steel	**NSYTT8CSX**
Insert	square, 7 mm	304L stainless steel	**NSYTC7CSX**
Insert	square, 6 mm	304L stainless steel	**NSYTC6CSX**
Round lock	round, 3 mm (spare)	Chromeplated zamak	**NSYSTDCSX**
Round lock	round, 3 mm	304L stainless steel	**NSYSTDCXH**
Round lock	round	316 stainless steel, Consult us for availability.	**NSYSTDCX2H** New
Handle lock	Padlock	316 stainless steel, Consult us for availability.	**NSYCBXHCRN** New
Handle lock	1242E	Chrome-plated zamak	**NSYCL1242ECSX**
Handle lock	405	Polyamide	**NSYCL405CSX**
Handle lock	610	Polyamide	**NSYCL610CSX**

3 points lock options

NSYTSML

NSYTSMLS3D



- Protection rating: IP66

Type	Material	References
Handle lock	100% stainless steel	**NSYTSML**
Screw driver insert	Zamak	**NSYTSMLS3D**

Wall-mounting door retainer Steel

To block the door in the open position.
- It is installed on enclosures with heights from 400 mm and widths from 300 mm.
- Door opening angle: 120°.
- Earthing connection of the enclosure by means of the reinforcement rail.
- Earthing accessories supplied with the enclosure (earth-connection wire to be ordered separately), see page 305.
- Material: Steel

Comment:
It is not compatible with installing the 19" swing rack and the internal door.

NSYAEDRSCST

Characteristics	References
Wall-mounting door retainer Steel	**NSYAEDRSCST**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Stainless steel wall-mounting enclosures

Eyebolts, Consult us for availability

- Material: Stainless steel 304L
- Maximum load: 210 kg per enclosure when slinging at 60°
- Supply reinforcing brackets attached to therings (these brackets also act as a drilling template)

NSYAELYTCRXG8

Characteristics	References
Batch of 2 M8 eyebolts	**NSYAELYTCRXG8** New

Inner door

- 3 mm double bar lock.
- Not compatible with door retainer and door switch. Consult us.
- Maximum load: 30 kg/m²

Installation: As standard it can be mounted an inner door and a mounting plate, on the step slides, at the same time

- Can be mounted either on the front side of the enclosure or on step slides (not suplied with standard)

Supply:
1 inner door

NSYPIN43

Characteristics	Height (mm)	Width (mm)	D (mm)	E (mm)	G (mm)	H (mm)	I min. (mm)	References
Inner door for wall-mounting enclosures	400	300	349	241	208	32	51	**NSYPIN43**
Inner door for wall-mounting enclosures	500	400	449	341	308	32	51	**NSYPIN54**
Inner door for wall-mounting enclosures	600	400	549	341	308	32	51	**NSYPIN64**
Inner door for wall-mounting enclosures	700	500	649	441	408	32	51	**NSYPIN75**
Inner door for wall-mounting enclosures	800	600	749	541	508	32	51	**NSYPIN86**
Inner door for wall-mounting enclosures	1000	800	949	741	708	32	51	**NSYPIN108**
Inner door for wall-mounting enclosures	1200	800	1149	741	708	32	52	**NSYPIN128**



● **NSYPIN** inner door fixed directly to the enclosure.

● **NSYPIN** inner door fixed to the adjustable **NSYSDCR●●** support.
In this case, both the inner door and the mounting plate may be depth adjustable.

Height (mm)	Width (mm)	D (mm)	E (mm)	G (mm)	H (mm)	I min. (mm)	References
400	300	349	241	208	32	51	**NSYPIN43**
500	400	449	341	308	32	51	**NSYPIN54**
600	400	549	341	308	32	51	**NSYPIN64**
700	500	649	441	408	32	51	**NSYPIN75**
800	600	749	541	508	32	51	**NSYPIN86**
1000	800	949	741	708	32	51	**NSYPIN108**
1200	800	1149	741	708	32	52	**NSYPIN128**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Stainless steel wall-mounting enclosures

Fig. 1



Fig. 2



External dimensions (mm)			Fig.
A	B	C	
300	200	150	1
300	250	150	1
300	300	150	1
400	300	150	1
400	300	200	1
400	400	200	1
400	600	200	1
500	400	200	2 Without door reinforcement
600	400	200	2
600	600	250	2
700	500	250	2
800	600	250	2
800	800	300	2

Fig. 3



Fig. 4



External dimensions (mm)			Fig.
A	B	C	
1000	800	300	3
1000	1000	300	4
1200	800	300	3
1200	1000	300	4

** For glazed door.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Spacial SMX

Spacial SFX

Stainless steel floor-standing enclosures

Spacial SMX SFX

Introduction	**148**
Characteristics	**149**
Accessories	**150**
Dimensions	**154**

Stainless steel floor-standing enclosures

These enclosures have been specially designed for the chemical, oil and food and beverage industries, among others, which are particularly demanding in terms of hygiene and resistance to corrosion.

This range can be configured according to your needs

4 differents services available:

- Assemble to order
- Mounting of standard accessories
- Painting
- Machining

Material and finishes

- AISI 304L as standard in Spacial SMX and SFX.
- AISI 316L as standard in Spacial SMX and on request in Spacial SFX.
- Finishes:
- Scotch-Brite® brushed (standard).
- Micro-beaded (on request).
- Painted (on request).



Convenience and time saving

- Complete range of accessories for installation, cable management, etc.
- 316L stainless steel plinth: easy cable entry.
- 304L or 316L stainless steel plinth: easy cable entry (Spacial SFX and SMX).
- Reversible door opening to 120°.
- Padlock lock with key or form insert.
- Adjustment rails perforated with a pitch of 25 mm.
- Perforated reinforcement frame allowing accessories to be mounted on the door.

Sealing

- Protection rating against dust and water IP66 or IP55 depending model according to IEC 60529.
- 3-point closures.
- Canopy (optional):
- helps protect the sealing plane of the door,
- helps guarantee correct water drainage,
- no stagnation on the top.
- Single-piece cable gland plate with polyurethane gasket.

Compatible with the other ranges

- The mounting plates and other accessories of the Spacial SM and SF standards metal offers.

Hygiene

- The high quality of the standard finish enables very easy maintenance while avoiding contamination.
- The hygienic feet made from 316L stainless steel, adjustable between 140 mm and 200 mm height, make it easier to clean under the enclosures.

Robustness and durability

- Resistance to external mechanical impacts: IK10 according to IEC 62262.
- 3 hinges made entirely from stainless steel.
- Door reinforcement frame.

Resistance to corrosion

- High resistance to corrosion. 304L and 316L stainless steels provide the best solutions for applications in extremely demanding environments.

See page 532 for details or consult our web site www.se.com

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Characteristics	Spacial SMX	Spacial SFX
	• Stainless steel sheet floor-standing enclosure, folded and welded. • Single and double front door, with reinforcement frame.	• Enclosure made up of a structure, consisting of top and bottom, rear panel and vertical profiles. • Single and double front door, with reinforcement frame.
Material	304L stainless steel, 316L stainless steel	304L stainless steel, 316L version (on request)
Finish	Scotch-Brite® brushed finish Micro-beaded and painted finishes (on request)	
Thickness	15/10e mm	Consult us
Ingress protection rating	IP66 according to IEC 60529 (only for 1 door enclosure)	IP66 (1 door) and IP55 (2 doors) according to IEC 60529
Mechanical protection rating	IK10 according to IEC 62262	
Standards and certifications	See technical guides page 624	
Installation	Outdoor installation: Compliant with IEC 62208 regarding type tests specified in §9.12 (resistance to ultra-violet (UV) radiation) and §9.13 (resistance to corrosion). **Comment:** For SMX and SFX is not mandatory the installation of a canopy for outdoor use	
Other characteristics	• Plain front door. Opening to left or right to 120° with reinforcement frame installed: • 3 stainless steel hinges • 3-point closure with handle made from painted zamak, 5 mm double bar • acceptable load of 50 kg	
Supply	• Welded compact body • Single-piece cable gland plate with sealing gasket • Welded mounting plate support brackets	• Welded rear panel • 4 mounting plate-supporting brackets • Single-piece cable gland plate with sealing gasket

Comment:
Dimensions, see page 154

External dimensions				304L	316L	304L
Height (mm)	Width (mm)	Depth (mm)	Number of front doors	Stainless steel enclosure	Stainless steel enclosure	Stainless steel suitable enclosure
1400	1000	300	2	**NSYSMX141030**	–	–
1600	800	400	1	**NSYSMX16840**	–	–
1800	600	400	1	**NSYSMX18640**	–	**NSYSFX18640**
1800	800	400	1	**NSYSMX18840**	**NSYSMX18840H**	**NSYSFX18840**
1800	1200	400	2	**NSYSMX181240**	**NSYSMX181240H**	**NSYSFX181240**
1800	1600	400	2	**NSYSMX181640**	**NSYSMX181640H**	–
2000	600	500	1	–	–	**NSYSFX20650**
2000	800	400	1	–	–	**NSYSFX20840**
2000	800	500	1	**NSYSMX20850**	–	–
2000	800	600	1	–	–	**NSYSFX20860**
2000	1000	400	2	**NSYSMX201040**	**NSYSMX201040H**	–
2000	1000	600	2	–	–	**NSYSFX201060**
2000	1200	500	2	**NSYSMX201250**	**NSYSMX201250H**	–
2000	1200	600	2	–	–	**NSYSFX201260**
2000	1600	600	2	**NSYSMX201660**	**NSYSMX201660H**	–

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Stainless steel floor-standing enclosures

Plinth

- Material: Stainless steel, AISI 304L or AISI 316L
- Finish: Scotch-Brite® brushing, to help guarantee the durability in application where the contact with the floor increase the risk of corrosion
- Installation: It is necessary to order separately the plinth fixing kit (ref. **NSYAPFXWM**) composed by fixing elements and drilling jig

Comment:
Ventilated plinths made up of stainless steel from heavy duty outdoor enclosures (page 423) are compatible to Spacial SMX stainless steel compact enclosures.

Front and rear plinths

Supply:
4 corners, 2 panels (front and rear), 4 corner covers and fixing elements

NSYSPFX10100

Characteristics	AISI	Height (mm)	Width (mm)	References
Front and rear plinths	304L	100	600	**NSYSPFX6100**
Front and rear plinths	304L	100	800	**NSYSPFX8100**
Front and rear plinths	304L	100	1000	**NSYSPFX10100**
Front and rear plinths	304L	100	1200	**NSYSPFX12100**
Front and rear plinths	304L	100	1600	**NSYSPFX16100**
Front and rear plinths	316L	100	800	**NSYSPFX8100H**
Front and rear plinths	316L	100	1000	**NSYSPFX10100H**
Front and rear plinths	316L	100	1200	**NSYSPFX12100H**
Front and rear plinths	316L	100	1600	**NSYSPFX16100H**

Side plinths

Supply:
2 side panels, 4 corner covers and fixing elements

NSYSPSX3100

Characteristics	AISI	Height (mm)	Depth (mm)	References
Side plinths	304L	100	300	**NSYSPSX3100**
Side plinths	304L	100	400	**NSYSPSX4100**
Side plinths	304L	100	500	**NSYSPSX5100**
Side plinths	304L	100	600	**NSYSPSX6100**
Side plinths	316L	100	300	**NSYSPSX3100H**
Side plinths	316L	100	400	**NSYSPSX4100H**
Side plinths	316L	100	500	**NSYSPSX5100H**
Side plinths	316L	100	600	**NSYSPSX6100H**

Front and rear plinths

Supply:
4 corners, 2 panels (front and rear), 4 corner covers and fixing elements

NSYSPFX10200

Characteristics	AISI	Height (mm)	Width (mm)	References
Front and rear plinths	304L	200	600	**NSYSPFX6200**
Front and rear plinths	304L	200	800	**NSYSPFX8200**
Front and rear plinths	304L	200	1000	**NSYSPFX10200**
Front and rear plinths	304L	200	1200	**NSYSPFX12200**
Front and rear plinths	304L	200	1600	**NSYSPFX16200**
Front and rear plinths	316L	200	800	**NSYSPFX8200H**
Front and rear plinths	316L	200	1000	**NSYSPFX10200H**
Front and rear plinths	316L	200	1200	**NSYSPFX12200H**
Front and rear plinths	316L	200	1600	**NSYSPFX16200H**

Side plinths

Supply:
2 side panels, 4 corner covers and fixing elements

NSYSPSX3200

Characteristics	AISI	Height (mm)	Depth (mm)	References
Side plinths	304L	200	300	**NSYSPSX3200**
Side plinths	304L	200	400	**NSYSPSX4200**
Side plinths	304L	200	500	**NSYSPSX5200**
Side plinths	304L	200	600	**NSYSPSX6200**
Side plinths	316L	200	300	**NSYSPSX3200H**
Side plinths	316L	200	400	**NSYSPSX4200H**
Side plinths	316L	200	500	**NSYSPSX5200H**
Side plinths	316L	200	600	**NSYSPSX6200H**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Life Is On Schneider Electric

Stainless steel floor-standing enclosures

SMX Canopy

NSYSCMX10030

- Helps guarantee very high protection of the enclosure when used outdoors.
- Material: 304L stainless steel sheet
  Other types of stainless steel, contact us
- Finish: Scotch-Brite® brushed
- Other finishes, contact us
- Thickness 15/10e
- Installation: It is fixed in the same holes as the eyebolt.

Supply:
Delivered with fixings. Other dimensions and canopy for sets, contact us

Characteristics	Width (mm)	Depth (mm)	References
Top-mounting	600	400	**NSYSCMX6040** New
Top-mounting	800	400	**NSYSCMX8040** New
Top-mounting	800	500	**NSYSCMX8050** New
Top-mounting	1000	300	**NSYSCMX10030** New
Top-mounting	1000	400	**NSYSCMX10040** New
Top-mounting	1200	400	**NSYSCMX12040** New
Top-mounting	1200	500	**NSYSCMX12050** New
Top-mounting	1600	400	**NSYSCMX16040** New
Top-mounting	1600	600	**NSYSCMX16060** New

SFX Canopy

NSYSCX6040

Supply:
Delivered with fixings. Other dimensions and canopy for sets, contact us

Characteristics	Width (mm)	Depth (mm)	References
Top-mounting	600	400	**NSYSCX6040**
Top-mounting	600	500	**NSYSCX6050**
Top-mounting	800	400	**NSYSCX8040**
Top-mounting	800	600	**NSYSCX8060**
Top-mounting	1000	600	**NSYSCX10060**
Top-mounting	1200	400	**NSYSCX12040**
Top-mounting	1200	600	**NSYSCX12060**
Top-mounting (used when coupling 2 SFX together)	1200	500	**NSYSCX12050**
Top-mounting (used when coupling 2 SFX together)	1600	400	**NSYSCX16040**
Top-mounting (used when coupling 2 SFX together)	1600	600	**NSYSCX16060**

Locking options

NSYTDB5ME

NSYTDB5ME

NSYBCME

- The enclosures Spacial SMX and SFX are delivered as standard with retractable handle made from
- painted zamak with 5 mm double bar insert, spare ref. **NSYMCSX**
- Transformation of the standard insert by other shape inserts or barrels according the following table:

Door switch for Spacial SF and SFX: page 300
Reference: **NSYDCM20**
Door switch for Spacial SM: page 300
Reference: **NSYMDCM20**

Characteristics	Type	Supply	References
Shape insert	5 mm doublebar insert.	Insert with key	**NSYTDB5ME**
Shape insert	Square insert, 6 mm	Insert with key	**NSYTC6ME**
Shape insert	Square insert, 8 mm	Insert with key	**NSYTC8ME**
Shape insert	Triangular insert, 6.5 mm	1 pack	**NSYTT6ME**
Shape insert	Triangular insert, 8 mm	1 pack	**NSYTT8ME**
Padlocking system	Padlocking device	1 pack	**NSYBCME**
Barrels	Reinforced key and barrel	1 pack	**NSYTLRME**
Barrels	JIS key and barrel	1 pack	**NSYTLJISME**
Barrels	Manual	1 pack	**NSYTMME**
Barrels	Barrel and key 405E	Barrels with 1 key	**NSYTCL405ME**
Barrels	Barrel and key 610E	Barrels with 1 key	**NSYTCL610ME**
Barrels	Barrel and key 1242E	Barrels with 1 key	**NSYTL1242EME**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Stainless steel floor-standing enclosures

SFX Side panels

NSY2SPX184

- Side panels including a polyurethane sealing gasket.
- Their special design helps guarantee the protection of the door gasket
- 304L stainless steel sheet

Characteristics	Height (mm)	Depth (mm)	References
Set of 2 side panels	1800	400	**NSY2SPX184**
Set of 2 side panels	2000	400	**NSY2SPX204**
Set of 2 side panels	2000	500	**NSY2SPX205**
Set of 2 side panels	2000	600	**NSY2SPX206**

SMX Plain mounting plate

NSYMP1410

Characteristics	Height (mm)	Width (mm)	References
Plain mounting plate	1400	1000	**NSYMP1410**
Plain mounting plate	1600	800	**NSYMP168**
Plain mounting plate	1800	600	**NSYMP186**
Plain mounting plate	1800	800	**NSYMP188**
Plain mounting plate	1800	1200	**NSYMP1812**
Plain mounting plate	1800	1600	**NSYMP1816**
Plain mounting plate	2000	800	**NSYMP208**
Plain mounting plate	2000	1000	**NSYMP2010**
Plain mounting plate	2000	1200	**NSYMP2012**
Plain mounting plate	2000	1600	**NSYMP2016**

SFX Plain mounting plate

NSYMP186

Characteristics	Height (mm)	Width (mm)	References
Plain mounting plate	1800	600	**NSYMP186**
Plain mounting plate	1800	800	**NSYMP188**
Plain mounting plate	1800	1200	**NSYMP1812**
Plain mounting plate	2000	600	**NSYMP206**
Plain mounting plate	2000	800	**NSYMP208**
Plain mounting plate	2000	1000	**NSYMP2010**
Plain mounting plate	2000	1200	**NSYMP2012**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Stainless steel floor-standing enclosures

SMX SFX Uprights vertical

NSYVR18

NSYTVR14

Characteristics	Height (mm)	References
Uprights vertical, Standard	1800	**NSYVR18**
Uprights vertical, Standard	2000	**NSYVR20**
Uprights vertical, Technical	1400	**NSYTVR14**
Uprights vertical, Technical	1600	**NSYTVR16**
Uprights vertical, Technical	1800	**NSYTVR18**
Uprights vertical, Technical	2000	**NSYTVR20**

Eyebolts

NSYSMXEB

- Material: Stainless steel 304L
- Installation: It is fixed using fixing nuts supplied
- Maximum load: 340 kg when slinging at 60°

Supply:
Set of four M12 eyebolts

Characteristics	References
Eyebolt	**NSYSMXEB** New

SFX Lifting bracket

NSYPUNX

- Material: Treated steel
- Installation: They are fixed instead of the eyebolts on two suitable enclosures side-by-side, helping guarantee the rigidity of the enclosure when lifted
- Maximum load: 1300 kg when slinging at 60°

Supply:
Set of four lifting brackets

Characteristics	References
Lifting bracket for SFX	**NSYPUNX**

SMX Wall fixing lugs

NSYFCMX

- Material: Stainless steel 304L
- Installation: Mounting of the wall fixing lugs in horizontal or vertical position; Fixing from the outside
- Maximum load: Horizontal: 180 kg, Vertical: 350 kg

Supply:
Set of four wall fixing lugs

Characteristics	References
Wall fixing lugs for SMX	**NSYFCMX**

Hygienic feet

NSYPHX200

- Recommended for applications that require special hygiene conditions.
- Material: 316L stainless steel
- Installation: Adjustable between 140 mm and 200 mm height
- Maximum load: Per foot: 100 kg

Supply:
Set of 4 adjustable feet

Characteristics	References
Hygienic feet	**NSYPHX200**

SFX Coupling kit


NSYSFBK19

- Used for joining enclosures side by side.
- Material: Flat connectors and brackets: Zinc-coated steel (**NSYSFBK19**); Sealing gasket: EPDM (**NSYSFXJG**)
- Ingress protection rating: IP55
- Installation: Fixing from the inside of the enclosures

Characteristics	References
Coupling kit for SFX	**NSYSFBK19**
Coupling kit for SFX	**NSYSFXJG**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.





Enclosure width of 1000 and 1200 mm



Enclosure width of 1600 mm

Floor-standing enclosure			No. of front doors	No. of cable gland plates	Dimensions	
Height (A) (mm)	Width (B) (mm)	Depth (C) (mm)			E (mm)	F (mm)
1400	1000	300	1	1	720	270
1600	800	400	1	1	520	270
1800	600	400	1	1	520	270
1800	800	400	1	1	520	270
1800	1200	400	2	1	920	270
1800	1600	400	2	2	1320	270
2000	800	500	1	1	520	370
2000	1000	400	2	1	720	270
2000	1200	500	2	1	920	370
2000	1600	600	2	2	1320	470

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Life Is On Schneider Electric











Enclosure width 1000

External dimensions			Number of front doors	No. of cable gland plates
Height (A) (mm)	Width (B) (mm)	Depth (C) (mm)		
1800	600	400	1	1
1800	800	400	1	1
1800	1200	400	2	2
2000	600	500	1	1
2000	800	400	1	1
2000	800	600	1	1
2000	1000	600	2	1
2000	1200	600	2	2



Enclosure width 1200 mm

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Thalassa TBS

Thalassa TBP

7

Thalassa PLS

Life Is On Schneider Electric

Insulating boxes

Thalassa TBS - TBP Insulating industrial boxes

Introduction	158
Characteristics	159
Selection guide	160
Specific accessories	162
Common accessories	167

Thalassa PLS Insulating modular boxes

Introduction	171
Characteristics	172
Selection guide	174
Accessories	176

Technical Guide

Insulating industrial boxes Dimensions	180

Insulating industrial boxes

Insulating industrial boxes:
- ABS for conventional applications (IK07) with the usual constraints,
- polycarbonate for enhanced impact resistance (IK08) and for outdoor applications or applications directly exposed to UV,
- polycarbonate certified UL, IP66 rating for all ranges, Protection against electrical impacts Class II.

This range can be configured according to your needs

4 differents services available:

Assemble to order

Mounting of standard accessories

Painting

Machining

Easy to install
- 3 methods of fixing the box to its support

Smart
- Fixing studs on the cover.

Easy to use
- Only one tool is required: A flat screwdriver.

See page 532 for details or consult our web site www.se.com

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Class II

Characteristics	Universal boxes with IP66	Equipped button boxes, in ABS with IP54	ABS boxes for buttons, to be equipped
	Boxes that can be coupled (exactly the same dimensions) with kit ref. **13934**. Locks from box size of 116 x 116 x 62 mm: • cover locking by 4 plastic captive screws with coarse thread outside the sealed area, • plumbable lock. Locks from box size of 138 x 93 x 72 mm: • the standard screws (flat screwdriver) can be replaced with other standardised screws. The 4 reinforced edges of the cover help ensure its robustness and perfect support during customisation operations. Adaptable hinges on all the 20 and 40 mm covers.		
Material	ABS boxes: • transparent cover made of polycarbonate • glow wire resistance: 650°C according to IEC 60695-2-11 • usage temperature: -25°C...+60°C • installation temperature: -15 C...+40°C Polycarbonate boxes: • glow wire resistance: 960°C • usage temperature: -25°C...+80°C • installation temperature: -15°C...+60°C	ABS boxes: • glow wire resistance: 650°C according to IEC 60695-2-11 • usage temperature: -25°C...+60°C • installation temperature: -15 C...+40°C	
Colour	• Body: RAL 7035 grey • Cover: RAL 7035 grey or transparent		
Ingress protection rating	IP66 according to IEC 60529	IP54 according to IEC 60529	–
Mechanical protection rating	ABS: IK07 according to IEC 62262 Polycarbonate: IK08 according to IEC 62262	ABS: IK07 according to IEC 62262	
Standards	IEC 62208		
Certifications	• IEC 62208 certified by TÜV • UL 508A: Polycarbonate range • Product Environmental Profile • Class II according to IEC 61140 Polycarbonate range: • NEMA 4.4X according to NEMA 250 • self-extinguishing: UL 94 V-0	• IEC 62208 certified by TÜV • Product Environmental Profile • Class II according to IEC 61140	
Installation	Fixing the box: • Outside the sealed sensitive volume by the 4 chimneys in the corners from box size of 138 x 93 x 72 mm • Through the rear of the box by 2 or 4 elongated holes to be perforated • With fixing lugs from box size of 116 x 116 x 62 mm (ref. **NSYAEFTB**) Outdoor installation, only for polycarbonate range: Compliant with IEC 62208 regarding type tests specified in §9.12 (resistance to ultra-violet (UV) radiation) and §9.13 (resistance to corrosion). Equipment installation: • Studs for fixing the equipment in the body and the cover of the box by means of a Ø 4 mm self-tapping screw (ref. **NSYAMFSTB**, screw Ø 4 x 10 mm with Pozidriv and slotted head) • Option of installing rails, plates or other types of supports (card, etc.) • Spacers and stand-offs to be installed on the studs, for adjusting the height of the equipment		

Comment:
For external use and based on the configuration of the installation, a canopy must be installed on the upper side of the boxes or the boxes should be installed under a shelter to protect them against the different weather conditions and to avoid water stagnation between body and lid. Anti-condensation valves must be installed to help prevent condensation and deformations of the boxes.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Insulating industrial boxes

Comment:
Dimensions, see page 180

Overall external dimensions			Overall internal dimensions							Universal boxes with IP66			
										ABS IP66 IK07		PC-UL IP66 IK08	
										Opaque cover	Transparent cover	Opaque cover	Transparent cover
Height (mm)	Width (mm)	Depth (mm)	Height (mm)	Width (mm)	Depth (mm)	Body (mm)	Cover (mm)	Minor pack.	Cover screw	References	References	References	References
74	74	54	65	65	47	37	10	5	Metal	**NSYTBS775**	-	**NSYTBP775**	-
89	89	54	80	80	47	37	10	5	Metal	**NSYTBS885**	-	**NSYTBP885**	-
116	74	62	105	65	55	45	10	5	Metal	**NSYTBS1176**	-	**NSYTBP1176**	-
116	74	94	105	65	85	45	40	3	Metal	**NSYTBS1179H**	-	-	-
116	116	62	105	105	55	45	10	5	Plastic	**NSYTBS11116**	-	**NSYTBP11116**	-
138	116	133	105	105	125	45	80	2	Plastic	**NSYTBS111113H**	-	-	-
164	93	72	125	80	65	45	20	2	Plastic	**NSYTBS1397**	**NSYTBS1397T**	**NSYTBP1397**	**NSYTBP1397T**
192	121	87	150	105	80	60	20	2	Plastic	**NSYTBS16128**	**NSYTBS16128T**	**NSYTBP16128**	**NSYTBP16128T**
192	121	87	175	105	80	60	20	2	Plastic	**NSYTBS19128**	**NSYTBS19128T**	**NSYTBP19128**	**NSYTBP19128T**
192	121	105	175	105	100	60	40	2	Plastic	**NSYTBS191210H**	**NSYTBS191210HT**	**NSYTBP191210H**	**NSYTBP191210HT**
192	164	87	175	150	80	60	20	1	Plastic	**NSYTBS19168**	**NSYTBS19168T**	**NSYTBP19168**	**NSYTBP19168T**
192	164	105	175	150	100	60	40	1	Plastic	**NSYTBS191610H**	**NSYTBS191610HT**	**NSYTBP191610H**	**NSYTBP191610HT**
241	194	87	225	175	80	60	20	1	Plastic	**NSYTBS24198**	**NSYTBS24198T**	**NSYTBP24198**	**NSYTBP24198T**
241	194	107	225	175	100	80	20	1	Plastic	**NSYTBS241910**	**NSYTBS241910T**	**NSYTBP241910**	**NSYTBP241910T**
241	194	107	225	175	100	60	40	1	Plastic	**NSYTBS241910H**	**NSYTBS241910HT**	**NSYTBP241910H**	**NSYTBP241910HT**
241	194	127	225	175	120	80	40	1	Plastic	**NSYTBS241912H**	**NSYTBS241912HT**	**NSYTBP241912H**	**NSYTBP241912HT**
291	241	88	275	225	80	60	20	1	Plastic	**NSYTBS29248**	**NSYTBS29248T**	**NSYTBP29248**	**NSYTBP29248T**
291	241	128	275	225	120	100	20	1	Plastic	**NSYTBS292412**	**NSYTBS292412T**	**NSYTBP292412**	**NSYTBP292412T**
291	241	128	275	225	120	60	60	1	Plastic	**NSYTBS292412H**	**NSYTBS292412HT**	**NSYTBP292412H**	**NSYTBP292412HT**
291	241	168	275	225	160	100	60	1	Plastic	**NSYTBS292416H**	**NSYTBS292416HT**	**NSYTBP292416H**	**NSYTBP292416HT**
341	291	128	325	275	120	100	20	1	Plastic	**NSYTBS342912**	**NSYTBS342912T**	**NSYTBP342912**	**NSYTBP342912T**
341	291	168	325	275	160	100	60	1	Plastic	**NSYTBS342916H**	**NSYTBS342916HT**	**NSYTBP342916H**	**NSYTBP342916HT**

Mounting plates made to adapt to all usage scenarios

Installation:

- Fixing by means of Ø 4 mm self-tapping screws, Pozidrive and slotted head, ref. **NSYAMFSTB**
- To raise the plate, use the stand-offs ref. **NSYAMFET154TB**, **NSYAMFET204TB**, **NSYAMFET304TB** and the screw **NSYAMFESTB**

Supply:
Plates supplied without screws

Box		Mounting plate dimensions			Mounting plates	
					Material: Galvanised steel	**Material:** Insulating polyester plate reinforced with fibreglass, halogen-free: Glow wire resistance 750°C according to IEC 60695-2-11.
					Thickness: 15/10e mm	Thickness: 25/10e mm
Height (mm)	Width (mm)	A (mm)	B (mm)	Minor pack.	References	References
192	164	168.5	140	1	**NSYAMPM1916TB**	**NSYAMPA1916TB**
241	194	215	168.5	1	**NSYAMPM2419TB**	**NSYAMPA2419TB**
291	241	265	215	1	**NSYAMPM2924TB**	**NSYAMPA2924TB**
341	291	315	265	1	**NSYAMPM3429TB**	**NSYAMPA3429TB**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Insulating industrial boxes

Button description

- Emergency switching off function with a red, Ø 40 mm, "turn to unlock" palm button.
- Start / Stop function with 2 push buttons.
- Up / Down / Stop function with 3 push buttons.

Technical features of the switches:

- "NC" switch with positive opening manoeuvre according to IEC 60947-5-1 appendix K,
- mechanical durability of the emergency switch: 0.1 million cycles,
- mechanical durability of the "NC" and "NO" switches: 5 million cycles,
- protection against short circuits: 10 A.

- Ref. **XALEK1702** houses an emergency switching off palm button with mechanical locking according to standards IEC 60364-5-53 and 60947-5-5.

Comment:
Dimensions, see page 180

Overall external dimensions			Overall internal dimensions								Boxes equipped with IP54 ABS buttons	ABS button boxes, to be equipped
Height (mm)	Width (mm)	Depth (mm)	Height (mm)	Width (mm)	Depth (mm)	Body (mm)	Cover (mm)	Minor pack.	No. of holes	Function	References	References
74	74	83	-	-	-	-	-	1	-	Emergency switching off	**XALEK170**	-
116	74	62	105	65	55	45	10, Grey	5	2	-	-	**XALE2**
116	74	62	105	65	55	45	10, Grey	5	3	-	-	**XALE3**
116	74	75	-	-	-	-	-	1	-	Start / stop	**XALE2141**	-
116	74	75	-	-	-	-	-	1	-	Up / down / stop	**XALE3255**	-

Function	Type of push	Type NO
Emergency switching off	Latching, red	1
Start/stop		
Start	Flush, green	1
Stop	Projecting, red	-
Up / down / stop		
Up	Flush, black	-
Down	Flush, white	-
Stop	Projecting, red	-

Function	Type of push	Type NC
Emergency switching off	Latching, red	1
Start/stop		
Start	Flush, green	-
Stop	Projecting, red	1
Up / down / stop		
Up	Flush, black	-
Down	Flush, white	-
Stop	Projecting, red	1

Function	Type of push	Type C / O
Emergency switching off	Latching, red	-
Start/stop		
Start	Flush, green	-
Stop	Projecting, red	-
Up / down / stop		
Up	Flush, black	1
Down	Flush, white	1
Stop	Projecting, red	-



Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Insulating industrial boxes

Coupling kit



13934

The coupling kit allows you to join several boxes with dimensions from 138 x 93 mm.
- Material: Polystyrene, glow wire resistance: 650°C according to IEC 60695-2-11
- Ingress protection rating: IP66 according to IEC 60529
- Installation: The kit is installed by drilling a hole with Ø 32 mm in the boxes to be coupled

Supply:
The kit consists of 2 linking parts, nuts and seals

Characteristics	Drilling Ø	Minor pack.	Reference
Coupling kit	32 mm	1	**13934**

Sealed anti-condensation valve

Controls the pressure to avoid condensation and/or deformations of the boxes due to the internal temperature increase. Applications Protection of equipment for luminaires, industrial control, transportation, pumps, etc.
- Material: PA6-V2, acrylic co-polymer membrane, water and oil repellent
- Ingress protection rating: IP68
- Installation: The valve is installed by drilling a hole with Ø 12 mm in the box
- Usage temperature: -40...+105°C
- Permeability: Air flow under ΔP = 0.7 bar
- Pressure difference: Condition for IP68

NSYCAG12LPH1

Supply:
10 valves, nuts and seals

Characteristics	Permeability	Pressure difference	Drilling Ø	Minor pack.	Reference
Sealed anti-condensation valve IP68	16 litres/h	ΔP < 1 bar	12 mm	1	**NSYCAG12LPH1**
Sealed anti-condensation valve IP68	120 litres/h	ΔP < 0.1 bar	12 mm	1	**NSYCAG12LPH2**

Cover accessories Set

NSYAEDST620TB

NSYAEDSB320TB

NSYAEDS20TB

- The Thalassa boxes are delivered as standard with slotted-head screws for flat screwdrivers from 4 to 5.5 mm.
- With box sizes from 138 x 93 x 72 mm, these screws canbe replaced for screws with different standardised heads, to comply with most cases.
- After removing the standard screw, simply positionthe new screw by pressing on it.
- The adapter clips (intermediate parts for tightening thecover on the body of the box) are the same as those for thestandard screws. They are not delivered with the shape screws.
- A single key for opening the boxes as well as the other enclosures of your installation.



Supply:
Set of 4 shape screws

Characteristics	Minor pack.	Reference
Triangle screw Ø8 mm, for Thalassa boxes, Height of the lid 20 mm	1	**NSYAEDST820TB**
Double bar screw Ø5 mm, for Thalassa boxes, Height of the lid 20 mm	1	**NSYAEDSB520TB**
Spare standard plastic screw for Thalassa boxes, Height of the lid 20 mm	1	**NSYAEDS20TB**
Spare standard plastic screw for Thalassa boxes, Height of the lid 40 mm	1	**NSYAEDS40TB**
Spare standard plastic screw for Thalassa boxes, Height of the lid 60 mm	1	**NSYAEDS60TB**

Cover accessories Pack



NSYAEDKTB

- The handle (or thumbwheel) allows the screws to be handled without any tools. It is ideally associated with a box equipped with hinges.
- It snaps onto the head of the standard plastic screw.

Supply:
Pack of 4 handles

Characteristics	Minor pack.	Reference
Handles	1	**NSYAEDKTB**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Insulating industrial boxes

Terminal blocks

- The new Linergy TR terminal blocks have 3 types of connections: screw, spring or "push-in" and they can be mounted on a DIN rail.
- Available in grey, blue, orange, red, green, black or white color.

Supply:
Minor pack. 50

Terminal blocks Screw connection

NSYTRV22

Characteristics	H (mm)	W (mm)	D (mm)	Reference
Screw connection Passthrough, 2.5 mm², grey	47.7	5.2	47.5	**NSYTRV22**
Screw connection Passthrough, 2.5 mm², blue	47.7	5.2	47.5	**NSYTRV22BL**
Screw connection Protective earth, 2.5 mm²	47.7	5.2	47.5	**NSYTRV22PE**
Screw connection Passthrough, 4 mm², grey	47.7	6.2	47.5	**NSYTRV44**
Screw connection Passthrough, 4 mm², blue	47.7	6.2	47.5	**NSYTRV44BL**
Screw connection Protective earth, 4 mm²	47.7	6.2	47.5	**NSYTRV44PE**

Terminal blocks Spring connection

NSYTRR22

Characteristics	H (mm)	W (mm)	D (mm)	Reference
Spring connection Passthrough, 2.5 mm², grey	36.5	5.2	48.5	**NSYTRR22**
Spring connection Passthrough, 2.5 mm², blue	36.5	5.2	48.5	**NSYTRR22BL**
Spring connection Protective earth, 2.5 mm²	36.5	5.2	48.5	**NSYTRR22PE**
Spring connection Passthrough, 4 mm², grey	36.5	6.2	56	**NSYTRR42**
Spring connection Passthrough, 4 mm², blue	36.5	6.2	56	**NSYTRR42BL**
Spring connection Protective earth, 4 mm²	36.5	6.2	56	**NSYTRR42PE**

Terminal blocks "Push-in" connection

NSYTRP22

Characteristics	H (mm)	W (mm)	D (mm)	Reference
"Push-in" connection Passthrough, 2.5 mm², grey	36.5	5.2	48.5	**NSYTRP22**
"Push-in" connection Passthrough, 2.5 mm², blue	36.5	5.2	48.5	**NSYTRP22BL**
"Push-in" connection Protective earth, 2.5 mm²	36.5	5.2	48.5	**NSYTRP22PE**
"Push-in" connection Passthrough, 4 mm², grey	36.5	6.2	56	**NSYTRP42**
"Push-in" connection Passthrough, 4 mm², blue	36.5	6.2	56	**NSYTRP42BL**
"Push-in" connection Protective earth, 4 mm²	36.5	6.2	56	**NSYTRP42PE**

4-hole terminal blocks

IMT34003

IMT34005

IMT34007



- The terminal-block support bar is particularly well suited to the thermoplastic boxes.
- Boxes with sizes from 192 x 116 mm can accommodate a terminal-block support bar of 12 x 2 mm.
- The screwing terminal blocks are easily clipped onto this bar.
- Terminal-block connection capacity: See the selection table below.
- 4-hole terminal block length (Lb): 30 mm.
- The earth terminal snap fits into boxes with dimensions of less than 116 x 116 mm.

Supply:
Red (live) Minor pack. 10
Blue (neutral) Minor pack. 5
Green (earth) Minor pack. 5

Characteristics	Reference
4-hole terminal blocks 2 x 10^2 + 2 x 16^2 – Red (live)	**IMT34003**
Earth terminal block 2 x 252 – Red (live)	**IMT34009**
4-hole terminal blocks 2 x 10^2 + 2 x 16^2 – Blue (neutral)	**IMT34005**
4-hole terminal blocks 2 x 10^2 + 2 x 16^2 – Green (earth)	**IMT34007**

Terminal-block support bar


IMT34000

Supply:
Minor pack. 1

- Discover our complete terminal blocks range in **LVYED213001EN**.

Characteristics	No. of Terminal blocks 2 x 102 + 2 x 162 4 holes	Support length Ls (mm)	Height or width (mm)	Min.depth (mm)	Reference
Terminal-block support bar	4	140	192	87	**IMT34000**
Terminal-block support bar	6	185	241	87	**IMT34001**
Terminal-block support bar	8	235	291	128	**IMT34002**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Insulating industrial boxes

Hinges, Set of 2 hinges

NSYAEDH20TB

- The hinges can be adapted to all covers with a height of 20 and 40 mm with dimensions from 138 x 93 mm.
- The hinge allows the lid to open fully to 200°.
- Ingress protection rating: IP66 according to IEC 60529
- Installation: The hinge does not require any machining and is installed
- easily even with the box already equipped
- Maximum load: Hinged cover: 10 kg/m²



Supply:
The hinges (2 per set) are delivered with the fixings, minor pack 1

Characteristics	Height of the lid (mm)	References
Set of 2 hinges	20	**NSYAEDH20TB**
Set of 2 hinges	40	**NSYAEDH40TB**

Hinges, Set of 4 fixing lugs

NSYAEFTB

- Plastic fixing lugs for installation on boxes with dimensions from 116 x 116 mm.
- Option of vertical or horizontal installation.
- Installation: Installation by a single screw at the last moment, with the box closed and equipped
- Maximum load: Body: 30 kg/m², Cover: 10 kg/m²



Supply:
4 lugs + screws, minor pack 1

Characteristics	Reference
Set of 4 fixing lugs	**NSYAEFTB**

Mounting plates



- Mounting plates made to adapt to all usage scenarios.
- Material: Galvanised steel
- Thickness: 15/10e mm
- Installation: Fixing by means of Ø 4 mm self-tapping screws, Pozidrive and slotted head, ref. NSYAMFSTB
- To raise the plate, use the stand-offs ref. NSYAMFET154TB, NSYAMFET204TB,
- NSYAMFET304TB and the screw NSYAMFESTB

Supply:
Plates supplied without screws

Characteristics	Box		Dimensions		Minor pack.	References
	Height (mm)	Width (mm)	A (mm)	B (mm)		
Mounting plate	192	164	168.5	140	1	**NSYAMPM1916TB**
Mounting plate	241	194	215	168.5	1	**NSYAMPM2419TB**
Mounting plate	291	241	265	215	1	**NSYAMPM2924TB**
Mounting plate	341	291	315	265	1	**NSYAMPM3429TB**

NSYAMPM1916TB



- Mounting plates made to adapt to all usage scenarios.
- Material: Insulating polyester plate reinforced with fibreglass, halogen-free: Glow wire resistance 750°C.
- Thickness: 25/10e mm
- Installation: Fixing by means of Ø 4 mm self-tapping screws, Pozidrive and slotted head, ref. NSYAMFSTB
- To raise the plate, use the stand-offs ref. NSYAMFET154TB, NSYAMFET204TB,
- NSYAMFET304TB and the screw NSYAMFESTB

Supply:
Plates supplied without screws

Characteristics	Box		Dimensions		Minor pack.	References
	Height (mm)	Width (mm)	A (mm)	B (mm)		
Insulating mounting plate	192	164	168.5	140	1	**NSYAMPA1916TB**
Insulating mounting plate	241	194	215	168.5	1	**NSYAMPA2419TB**
Insulating mounting plate	291	241	265	215	1	**NSYAMPA2924TB**
Insulating mounting plate	341	291	315	265	1	**NSYAMPA3429TB**

NSYAMPA1916TB

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Insulating industrial boxes

Symmetric DIN rails



- A 15 x 5 mm rail is provided for the compact terminal blocks.
- To raise the rail, use stand-offs ref. **NSYAMFET154TB**, **NSYAMFET204TB**, **NSYAMFET304TB** and the screw **NSYAMFESTB**.
- Installation: Fixing of the rails with Ø 4 mm self-tapping screws, (not included), Pozidrive and slotted head, ref. **NSYAMFSTB**

Supply:
Supplied without screws
(except for the 15 x 5 mm rails)

NSYAMRD11155TB

NSYAMRD11357TB

NSYAMRD243515TB

Characteristics	Height (mm)	Depth (mm)	Length (mm)	Box (mm)	References
Symmetric DIN rail	15	5	97	105	**NSYAMRD11155TB**
Symmetric DIN rail	15	5	140	150	**NSYAMRD16155TB**
Symmetric DIN rail	15	5	168	175	**NSYAMRD19155TB**
Symmetric DIN rail	15	5	214	225	**NSYAMRD24155TB**
Symmetric DIN rail	15	5	264	275	**NSYAMRD29155TB**
Symmetric DIN rail	15	5	316	325	**NSYAMRD34155TB**
Symmetric DIN rail	35	7.5	97	105	**NSYAMRD11357TB**
Symmetric DIN rail	35	7.5	140	150	**NSYAMRD16357TB**
Symmetric DIN rail	35	7.5	168	175	**NSYAMRD19357TB**
Symmetric DIN rail	35	7.5	214	225	**NSYAMRD24357TB**
Symmetric DIN rail	35	7.5	264	275	**NSYAMRD29357TB**
Symmetric DIN rail	35	7.5	316	325	**NSYAMRD34357TB**
Symmetric DIN rail	35	15	214	225	**NSYAMRD243515TB**
Symmetric DIN rail	35	15	264	275	**NSYAMRD293515TB**
Symmetric DIN rail	35	15	316	325	**NSYAMRD343515TB**

Screws for rails

NSYAMFSTB

- Ø 4 x 10 mm

Supply:
Pack of 100 screws

Characteristics	References
Screws Ø4 mm, height 10 mm	**NSYAMFSTB**

7

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Insulating industrial boxes

Stand-offs



- Stand-offs consisting of a Ø 4 mm self-tapping thread at one end (for direct screwing into the rivets of the box) and an M4 tapping on the other end, for direct installation of a card with an M4 screw, ref. **NSYAMFESTB**, or of a spacer.
- Material: Steel

Supply:
Set of four M4 self-tapping stand-offs

NSYAMFET154TB

Characteristics	Minor pack.	References
Stand-offs M4, steel, height: 15 mm	1	**NSYAMFET154TB**
Stand-offs M4, steel, height: 20 mm	1	**NSYAMFET204TB**
Stand-offs M4, steel, height: 30 mm	1	**NSYAMFET304TB**

Screw for stand-offs and spacers

NSYAMFESTB

- M4 x 10 mm screw for fixing cards on the spacers and stand-offs.
- The plate always at the right level.
- A single Ø 4 mm screw for fixing any element.

Supply:
Batch of 50 screws

Characteristics	Minor pack.	References
Screw Ø4x100 for fixing cards on the spacers and stand-offs	1	**NSYAMFESTB**

7

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Insulating industrial boxes

Simple-1	Simple-2	Simple-3	Simple-4	Simple-5	Synthetic snap in cable gland
				New	
Mixed membrane entries for enclosure thickness 20/10e - 32/10e mm.	PVC adjustable conesha-ped entries for enclosure thickness 30/10e - 32/10e mm.	Quick cable entries for enclosure thickness 10/10e - 40/10e mm (5/10e - 20/10e mm for ref. **IMT36179**).	PVC adjustable conesha-ped entries for PG tubes or for enclosure thickness 12/10e - 15/10e mm.	Presse-étoupe ISO.	Without thread. Easy assembly and dis-assembly. Suitable for walls from 0.5 to 4 mm thick.
ISM71071	**NSYECPC3**	**IMT36179**	**NSYEC7**	**ISM71501**	**NSYCGSP16**
ISM71072	**NSYECPC5**	**IMT36180**		**ISM71502**	**NSYCGSP20**
ISM71073	**NSYECPC6**	**IMT36181**		**ISM71503**	**NSYCGSP25**
ISM71074	**NSYECPC9**	**IMT36182**		**ISM71504**	**NSYCGSP32**
IMT36172	**NSYECPC15**	**IMT36183**		**ISM71505**	**NSYCGSP40**
IMT36173		**IMT36184**		**ISM71506**	
		IMT36185		**IMT36150**	

Accesories bag for enclosure TBS/TBP

NSYTBPASBS

Characteristics	References
Spare Parts	**NSYTBPASBS**

Simple-1

- Mixed membrane entries for enclosure thickness 20/10e - 32/10e mm.
- Material: SBS
- Colour: RAL 7035 grey or RAL 9010 white
- Cable entry material: Soft membrane
- Cable glands to be fitted: Not applicable
- Installation possibilities: On cable gland plate or directly on enclosure
- Flexibility of the installation: Low
- Reversibility: Medium
- Ingress protection rating: IP55 according to IEC 60529
- Cable retention: Low
- Cable diameter (mm): From 20 to 40
- Cable Installation time: Fast
- Quantity of cables to be fitted for a given surface: +
- Cable entries for cables with connectors: No
- Cut-out dimensions (mm): Various circular hole diameters according to cable diameter
- External dimensions (mm): From Ø 23 to 44
- Flame resistance: 750°C

Supply:
Minor packaging of 10 pieces

ISM71074

Characteristics	Drill hole Ø (mm)	Cable / conduit Ø (mm)	References
Mixed membrane entries for IP55 direct cable entries, RAL 9010	23	4 - 20	**IMT36172**
Mixed membrane entries for IP55 direct cable entries, RAL 9010	29	4 - 25	**IMT36173**
Mixed membrane entries for IP55 direct cable entries, RAL 7035	23	4 - 20	**ISM71071**
Mixed membrane entries for IP55 direct cable entries, RAL 7035	29	4 - 25	**ISM71072**
Mixed membrane entries for IP55 direct cable entries, RAL 7035	36	4 - 32	**ISM71073**
Mixed membrane entries for IP55 direct cable entries, RAL 7035	44	4 - 40	**ISM71074**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Insulating industrial boxes

Simple-2

- PVC adjustable coneshaped entries for enclosure thickness 30/10e - 32/10e mm.
- Material: PVC
- Cable entry material: Soft membrane
- Cable glands to be fitted: Not applicable
- Installation possibilities: On cable gland plate or directly on enclosure
- Flexibility of the installation: Low
- Reversibility: Medium
- Ingress protection rating: IP55 according to IEC 60529
- Cable retention: Low
- Cable diameter (mm): From 5 to 87
- Cable Installation time Fast
- Quantity of cables to be fitted for a given surface: +
- Cable entries for cables with connectors: No
- Cut-out dimensions (mm): Various circular hole diameters according to cable diameter
- External dimensions (mm): From Ø 25 to 98



Supply:
NSYECPC3 50 cable entries, **NSYECPC5** and **NSYECPC6** each 25 cable entries, **NSYECPC9** and **NSYECPC15** each 10 cable entries

NSYECPC15

Characteristics	Dimensions (mm)						Capacity		References
	Ø A	Ø B	Ø C	Ø D	E	F	Cable (Ø mm)	Tube	
PVC adjustable coneshaped entrie 25x3 mm	25	21.5	18	5	3.2	13	5-18	PG 9-11	**NSYECPC3**
PVC adjustable coneshaped entrie 32x3 mm	33	29.5	26	5	3.2	20	5-26	PG 9-16	**NSYECPC5**
PVC adjustable coneshaped entrie 43x3 mm	43	38.5	36	5	3.2	22	5-36	PG 9-21	**NSYECPC6**
PVC adjustable coneshaped entrie 70x3 mm	70	63	60	28	3	20	28-60	PG 21-48	**NSYECPC9**
PVC adjustable coneshaped entrie 98x3 mm	98	90	87	28	3	23	28-87	PG 21-48	**NSYECPC15**

Simple-3

- Quick cable entries for enclosure thickness 10/10e - 40/10e mm (5/10e - 20/10e mm for ref. **IMT36179**).
- Material: EPDM plastic
- Colour: Grey cable entries: NCS 5500; Black cable entries: NCS 9000
- Cable entry material: Combined
- Cable glands to be fitted: Not applicable
- Installation possibilities: On cable gland plate or directly on enclosure
- Flexibility of the installation: Low
- Reversibility: Medium
- Ingress protection rating: IP67 according to IEC 60529
- Cable retention: Medium
- Cable diameter (mm): From 12 to 50
- Cable Installation time: Fast
- Quantity of cables to be fitted for a given surface: +
- Cable entries for cables with connectors: No3
- Cut-out dimensions (mm): Various circular hole diameters according to cable diameter
- External dimensions (mm): From Ø 12.5 to 50.7
- Flame resistance: 750°C



Supply:
50 (M12 to M32)
25 (M40 and M50)

IMT36179

Characteristics	Dimensions			References
	ISO	Drill hole (Ø mm)	Cable (Ø mm)	
Quick cable entries	M12	12.5	3 - 5	**IMT36179**
Quick cable entries	M16	16	5 - 7	**IMT36180**
Quick cable entries	M20	20.3	7 - 10	**IMT36181**
Quick cable entries	M25	25.3	10 - 14	**IMT36182**
Quick cable entries	M32	32.4	14 - 20	**IMT36183**
Quick cable entries	M40	40.7	20 - 26	**IMT36184**
Quick cable entries	M50	50.7	26 - 35	**IMT36185**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Insulating industrial boxes

PVC adjustable cone-shaped entries

- PVC adjustable coneshaped entries for PG tubes or for enclosure thickness 12/10e - 15/10e mm.
- Material: PVC
- Colour: Black
- Cable entry material: Combined
- Cable glands to be fitted: Not applicable
- Installation possibilities: On cable gland plate or directly on enclosure
- Flexibility of the installation: Low
- Reversibility: Medium
- Ingress protection rating: IP55 according to IEC 60529
- Cable retention: Low
- Cable diameter (mm): From 16 to 44
- Cable Installation time: Fast
- Quantity of cables to be fitted for a given surface: +
- Cable entries for cables with connectors: No
- Cut-out dimensions (mm): Various circular hole diameters according to cable diameter
- External dimensions (mm): From Ø 25 to 52



Supply:
25 cable entries

NSYEC7

Characteristics	Dimensions (mm)						Capacity		References
	Ø A	Ø B	Ø C	Ø D	E	F	Cable (Ø mm)	Tube	
PVC adjustable cone-shaped entries	52	48.5	44	13	1.5	30	13 to 44	PG 36	**NSYEC7**

Simple-5

- Presse-étoupe ISO
- Material: PA6 Polyamide, neoprene gasket
- Colour: RAL 7035 grey
- Cable entry material: Combined
- Installation possibilities: On cable gland plate or directly on enclosure
- Flexibility of the installation: Low
- Reversibility: Medium
- Ingress protection rating: IP68
- Cable retention: High
- Cable diameter (mm): From 12 to 40
- Cable Installation time: Slow
- Quantity of cables to be fitted for a given surface: +
- Cable entries for cables with connectors: No
- Cut-out dimensions (mm): Various circular hole diameters according to cable diameter
- External dimensions (mm): From Ø 15 to 46
- Certificates: Glow wire resistance: 960°C
- Standard: Compliance with VDE, UL and CSA
- Flame resistance: 750 °C



Supply:
The cable glands are supplied with nuts Pack of 20 (M12 to M20), of 10 (M25 and M32), of 5 (M40)

ISM71503

Characteristics	Dimensions					References
	Cable (Ø mm)	Drill hole (Ø mm)	TD	TL	SW	
Cable gland M12, RAL 7035	3 / 6.5	12.2 (0 + 0.2)	12	6	15	**ISM71501**
Cable gland M16, RAL 7035	4 / 8	16.2 (0 + 0.2)	16	8	19	**ISM71502**
Cable gland M20, RAL 7035	6 / 12	20.2 (0 + 0.2)	20	10	24	**ISM71503**
Safety Cable gland M20, RAL 3000	6 / 12	20.2 (0 + 0.2)	20	10	24	**IMT36150**
Cable gland M25, RAL 7035	11 / 17	25.2 (0 + 0.2)	25	8	29	**ISM71504**
Cable gland M32, RAL 7035	15 / 21	32.2 (0 + 0.3)	32	10	36	**ISM71505**
Cable gland M40, RAL 7035	19 / 28	40.5 (0 + 0.3)	40	10	46	**ISM71506**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Insulating industrial boxes

Synthetic snap in cable gland

- Without thread.
- Easy assembly and disassembly.
- Suitable for walls from 0.5 to 4 mm thick.
- Material: PA6 Polyamide, neoprene gasket
- Colour: RAL 7035 grey, RAL 7001, RAL 9005. Other colours on demand
- Cable entry material: Non armoured
- Installation possibilities: On cable gland plate or directly on enclosure
- Flexibility of the installation: Low
- Reversibility: Medium
- Ingress protection rating: IP66
- Cable retention: High
- Cable diameter (mm): From 16 to 40
- Cable Installation time: Slow
- Quantity of cables to be fitted for a given surface: +
- Cable entries for cables with connectors: No
- Thread type: Metric EN 60423 Other types are available on demand
- Cut-out dimensions (mm): Various circular hole diameters according to cable diameter
- External dimensions (mm): From Ø 22 to 46
- Certificates: UL 94 V-2 (except for the size M40)
- Standard: DIN EN 62444, UL 514B, UL 514B§8.26.7
- Temperature range: -20°C to + 100°C



Supply:
The cable glands are supplied with nuts Pack of 20 (M16 and M20), of 10 (M25 and M32), of 5 (M40)

NSYCGSP16

Characteristics	Dimensions (mm)							References	
	Ø	Ø min / max	Drill Ø	SL	SD	H			
Synthetic snap in cable gland	M16	5/10	16.2 to 16.4	9	15.9	42.5	22	**NSYCGSP16**	New
Synthetic snap in cable gland	M20	6/12	20.2 to 20.4	9	19.9	41.5	24	**NSYCGSP20**	New
Synthetic snap in cable gland	M25	11/17	25.2 to 25.4	9	24.9	43.5	29	**NSYCGSP25**	New
Synthetic snap in cable gland	M32	15/21	32.2 to 32.4	9	31.9	49.5	36	**NSYCGSP32**	New
Synthetic snap in cable gland	M40	19/28	40.2 to 40.4	11.5	39.9	56	46	**NSYCGSP40**	New

Snap in cable gland disassembling tool

- Material: Plastic

NSYDT16

NSYDT20

Characteristics	Ø	References	
Tool to quickly disassemble cable gland	M16	**NSYDT16**	New
Tool to quickly disassemble cable gland	M20	**NSYDT20**	New
Tool to quickly disassemble cable gland	M25	**NSYDT25**	New
Tool to quickly disassemble cable gland	M32	**NSYDT32**	New
Tool to quickly disassemble cable gland	M40	**NSYDT40**	New

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Life Is On Schneider Electric

PLS boxes: Polyester rear and PC transparent cover with wing screws for manual opening.

This range can be configured according to your needs

4 differents services available:

Assemble to order

Mounting of standard accessories

Painting

Machining

Green Premium™



Protection

IP66.
Gasket between body and cover.
IK09.
Insulation Class II.

Modular

The dimensions of the sides, multiples of 9 cm, allow the creation of assemblies.

Easy

Bosses with inserts, at the rear of the body, for fixing plates or various supports.

See page 532 for details or consult our web site www.se.com

Prolonged exposure to UV radiation, wind and rain can cause aesthetics changes in the external surface of the enclosure.
Without affecting the technical properties according to IEC 62208. For long exposure applications, it is recommended to use painted enclosures available through the P&S offer.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Insulating modular boxes

According to Reach and RoHs & Halogen free

Class II

Characteristics	Complete box NSYPLS5454AG	NSYPLS1827G	NSYPLSC5472AG	NSYPLSC1827G	NSYPLSP1827G
	• Insulating boxes that can be coupled by all their side surfaces, allowing the creation of the greatest variety of modular assemblies. • The product references show the two lateral dimensions in cm. • 14 sizes of insulating boxes; The sides are multiples of 9 cm. • Body made from polyester reinforced with fibreglass, moulded by hot compression, 9 sizes. • 3 types of cover available according to the sizes: • standard cover, made from transparent polycarbonate with neoprene gasket, 45 mm high, or 95 mm high (final index A) according to the sizes, • opaque polycarbonate cover (index C), with neoprene gasket, 45 mm high, or 95 mm high (final index A) according to the sizes, • polyester reinforced with fiberglass cover (index P) with PUR gasket, 45 mm high. • Complete box includes body, cover, locking screws and sealing device. • The bodies (prefix F) and the covers (prefix T) are supplied separately as standard references. The separate covers are supplied without locking screws or sealing accessories. • The PLS enclosures with transparent cover are also offered in batches; The reference refers to the complete batch. • Excellent resistance to corrosion; Can withstand most chemical agents. • Full insulation to create class II assemblies. • Standard lock with slot screws outside the volume of the boxes. Delivered with sealing system. • External wall-mounting by 4 lugs, to be ordered separately. • Service temperature: -40 to +80°C. • Bosses with M6 inserts for fixing the mounting plate. • Halogen-free and compliant with the RoHS directive.				
Colour	RAL 7035 grey (opaque bodies and cover)				
Ingress protection rating	IP66				
Mechanical protection rating	IK09				
Certifications	• Certification according to standard IEC 62208, helping guarantee IP, IK, resistance to heat and fire (self-extinguishing), insulation to 5000 V, and load of the mounting plate, 100 kg/m² • UL508A* CAN/CSA-C22.2 - Types 1, 2, 3, 3R, 3S, 4, 4X, 12 and 13				
Installation	Outdoor installation: Compliant with IEC 62208 regarding type tests specified in §9.12 (resistance to ultra-violet (UV) radiation) and §9.13 (resistance to corrosion). It is always advisable to install a canopy to avoid water stagnation on the upper part of the enclosure and help protect against the sun radiation.				
Options	-				
Supply	-				

* **NSYPLS**, **NSYPLSP** and **NSYPLSC** followed by suffixes.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

	Insulating modular boxes with modular distribution chassis	Modular distribution chassis
	NSYDLS12	**NSYPLS1827DLS12**
	PLS boxes, polyester body and PC transparent cover with hinges and wing screws for manual opening. Built-in DLS modular chassis, made up of an insulating protection panel, RAL 7011 colour, 35 mm DIN rails and a 2 x 16 + 5 x 6 mm² neutral/earth connection strip. • Opening for cable entry, delivered with lock plate, ref. **NSYTL27270G**. • Double-insulating installation. • Plastic external hinges, allowing opening to 180°. • Removable 36 mm blanking covers (2 modules): 1 per row in the standard offer.	Built-in DLS modular chassis, made up of an insulating protection panel, RAL 7011 colour, 35 mm DIN rails and a 2 x 16 + 5 x 6 mm² neutral/earth connection strip.
	-	-
	IP43	IP43
	IK09	IK09
	-	-
	Indoor	Indoor
	The boxes can be equipped with a double bar lock and handle ref. **NSYCL27M**, or a lock with key ref. **NSYCL27L405**, by specific demand	-
	The modular chassis can be ordered separately	-

7

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Insulating modular boxes

			Complete box		
Dimensions			Transparent cover	Opaque cover	Polyester cover
Height (mm)	Width (mm)	Depth (mm)	References	References	References
180	270	180	**NSYPLS1827G**	**NSYPLSC1827G**	**NSYPLSP1827G**
270	270	180	**NSYPLS2727G**	**NSYPLSC2727G**	**NSYPLSP2727G**
270	270	230	**NSYPLS2727AG**	**NSYPLSC2727AG**	-
270	360	180	**NSYPLS2736G**	**NSYPLSC2736G**	**NSYPLSP2736G**
270	360	230	**NSYPLS2736AG**	**NSYPLSC2736AG**	-
270	540	180	**NSYPLS2754G**	**NSYPLSC2754G**	**NSYPLSP2754G**
270	540	230	**NSYPLS2754AG**	**NSYPLSC2754AG**	-
360	270	180	-	-	-
360	360	180	**NSYPLS3636G**	**NSYPLSC3636G**	**NSYPLSP3636G**
360	540	180	**NSYPLS3654G**	**NSYPLSC3654G**	**NSYPLSP3654G**
360	540	230	**NSYPLS3654AG**	**NSYPLSC3654AG**	-
360	720	230	**NSYPLS3672AG**	**NSYPLSC3672AG**	-
540	270	180	-	-	-
540	540	180	**NSYPLS5454G**	**NSYPLSC5454G**	**NSYPLSP5454G**
540	540	230	**NSYPLS5454AG**	**NSYPLSC5454AG**	-
540	720	230	**NSYPLS5472AG**	**NSYPLSC5472AG**	-

7

			Rear	Low covers: 45 mm		
Dimensions			Rear 135 mm	Transparent	Opaque	Polyester
Height (mm)	Width (mm)	Depth (mm)	References	References	References	References
180	270	180	**NSYFPLS1827G**	**NSYTPLS1827**	**NSYTPLSC1827G**	**NSYTPLSP1827G**
270	270	180	**NSYFPLS2727G**	**NSYTPLS2727**	**NSYTPLSC2727G**	**NSYTPLSP2727G**
270	270	230	**NSYFPLS2727G**	-	-	-
270	360	180	**NSYFPLS2736G**	**NSYTPLS2736**	**NSYTPLSC2736G**	**NSYTPLSP2736G**
270	360	230	**NSYFPLS2736G**	-	-	-
270	540	180	**NSYFPLS2754G**	**NSYTPLS2754**	**NSYTPLSC2754G**	**NSYTPLSP2754G**
270	540	230	**NSYFPLS2754G**	-	-	-
360	360	180	**NSYFPLS3636G**	**NSYTPLS3636**	**NSYTPLSC3636G**	**NSYTPLSP3636G**
360	540	180	**NSYFPLS3654G**	**NSYTPLS3654**	**NSYTPLSC3654G**	**NSYTPLSP3654G**
360	540	230	**NSYFPLS3654G**	-	-	-
360	720	230	**NSYFPLS3672G**	-	-	-
540	540	180	**NSYFPLS5454G**	**NSYTPLS5454**	**NSYTPLSC5454G**	**NSYTPLSP5454G**
540	540	230	**NSYFPLS5454G**	-	-	-
540	720	230	**NSYFPLS5472G**	-	-	-

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

	Insulating modular boxes with modular distribution chassis				Modular distribution chassis
	No. of 18 mm modules	No. of rows	Approximate weight (kg)	References	References
	12	1	1.7	**NSYPLS1827DLS12**	**NSYDLS12**
	24	2	2.5	**NSYPLS2727DLS24**	**NSYDLS24**
	-	-	-	-	-
	-	-	-	-	-
	-	-	-	-	-
	-	-	-	-	-
	-	-	-	-	-
	24	2	2.7	**NSYPLS3627DLS24**	**NSYDLS242**
	36	3	2.8	**NSYPLS3627DLS36**	**NSYDLS36**
	-	-	-	-	-
	-	-	-	-	-
	-	-	-	-	-
	-	4	3.8	**NSYPLS5427DLS48**	-
	48	-	-	-	**NSYDLS48**
	-	-	-	-	-
	-	-	-	-	-

	High covers: 95 mm		Metallic mounting plates		Insulating mounting plates	
						
	Transparent	Opaque	Plain	Telequick	Polyester	Bakelite
	References	References	References	References	References	References
	-	-	**NSYPMM1827**	**NSYPMR1827**	**NSYPMA1827G**	**NSYPMB1827**
	-	-	**NSYPMM2727**	**NSYPMR2727**	**NSYPMA2727G**	**NSYPMB2727**
	NSYTPLS2727A	**NSYTPLSC2727AG**	**NSYPMM2727**	**NSYPMR2727**	**NSYPMA2727G**	**NSYPMB2727**
	-	-	**NSYPMM2736**	**NSYPMR2736**	**NSYPMA2736G**	**NSYPMB2736**
	NSYTPLS2736A	**NSYTPLSC2736AG**	**NSYPMM2736**	**NSYPMR2736**	**NSYPMA2736G**	**NSYPMB2736**
	-	-	**NSYPMM2754**	**NSYPMR2754**	**NSYPMA2754G**	**NSYPMB2754**
	NSYTPLS2754A	**NSYTPLSC2754AG**	**NSYPMM2754**	**NSYPMR2754**	**NSYPMA2754G**	**NSYPMB2754**
	-	-	**NSYPMM3636**	-	**NSYPMA3636G**	**NSYPMB3636**
	-	-	**NSYPMM3654**	**NSYPMR3654**	**NSYPMA3654G**	**NSYPMB3654**
	NSYTPLS3654A	**NSYTPLSC3654AG**	**NSYPMM3654**	**NSYPMR3654**	**NSYPMA3654G**	**NSYPMB3654**
	NSYTPLS3672A	**NSYTPLSC3672AG**	**NSYPMM3672**	**NSYPMR3672**	**NSYPMA3672G**	**NSYPMB3636**
	-	-	**NSYPMM5454**	**NSYPMR5454**	**NSYPMA5454G**	**NSYPMB3654**
	NSYTPLS5454A	**NSYTPLSC5454AG**	**NSYPMM5454**	**NSYPMR5454**	**NSYPMA5454G**	**NSYPMB3654**
	NSYTPLS5472A	**NSYTPLSC5472AG**	**NSYPMM5472**	**NSYPMR5472**	**NSYPMA5472G**	**NSYPMB5472**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Insulating modular boxes

Wall fixing lugs

NSYPF27N




NSYPF27X

- Passivated zinc-coated steel
- Stainless steel

Supply:
Set of 4 lugs and fixings

Characteristics	References
Wall fixing lug, passivated zinc-coated steel	**NSYPF27N**
Wall fixing lug, stainless steel	**NSYPF27X**

Post fixing device

Supply:
Contains all the elements required for mounting on a post

NSYFSP27270

Characteristics	Max. length of enclosure rear side (mm)	References
Post fixing device	270	**NSYFSP27270**
Post fixing device	360	**NSYFSP27360**
Post fixing devicec	540	**NSYFSP27540**

Plastic carrying handle

NSYATM27

- Material: Plastic
- Ingress protection rating: IP43



Characteristics	References
Plastic carrying handle	**NSYATM27**

7

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Life Is On Schneider Electric

Insulating modular boxes

Coupling frames

NSYUM27180

- Ingress protection rating: Frame with full opening: IP65 between enclosures

Comment:
Use the boxes dimensional drawings to identify what coupling frame you need. Consider the sides and surfaces you will join. Not UL certified.

Characteristics	For surfaces (mm)	Opening (mm)	References
Full-opening frame	180	110	**NSYUM27180**
Full-opening frame	270	200	**NSYUM27270**
Full-opening frame	360	290	**NSYUM27360**

NSYUCC270

- Ingress protection rating: Frame with full opening: IP44 between enclosures

Comment:
Use the boxes dimensional drawings to identify what coupling frame you need. Consider the sides and surfaces you will join. Not UL certified.

Supply:
References by unit. Order by multiples of 10 units (10, 20, 30, etc.).

Characteristics	For surfaces (mm)	Opening (mm)	References
Partial-opening frame	270	200	**NSYUCC270**
Partial-opening frame	360	290	**NSYUCC360**

Side plates

NSYTL27270G

- Ingress protection rating: IP65

Characteristics	For surfaces (mm)	Width (mm)	References
Side plate	270	200	**NSYTL27270G**
Side plate	360	290	**NSYTL27360G**

Box coupling unit piece

NSYPS2C27



- For coupling 2, 3 or 4 boxes, with optional wallmounting.
- M6 x 8 mm screw with cylindrical head.

Supply:
To be ordered in multiples of 25

Characteristics	References
Box coupling unit piece for coupling 2 boxes	**NSYPS2C27**
Box coupling unit piece for coupling 3 or 4 boxes	**NSYPS4C27**

7

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Insulating modular boxes

Closing for PLS boxes

- Slotted screw: Included in the standard references of boxes **NSYPLS●●●**.
- Wing screw: Included in the standard references of modular distribution boxes **NSYPLS●●●DLS●●●**.
- Triangular screw: **NSYLT27**

Supply:
Set of 4, 6 or 8 screws.
The references also include 4 M6 screws for fixing mounting plates and 2 steel sealing accessories

NSYTCD274

NSYTCM274

NSYTCT274

Characteristics	Tool	References
Set of 4 slotted screws	Flat-blade screwdriver	**NSYTCD274**
Set of 6 slotted screws	Flat-blade screwdriver	**NSYTCD276**
Set of 8 slotted screws	Flat-blade screwdriver	**NSYTCD278**
Set of 4 wing screws	Manual	**NSYTCM274**
Set of 4 triangular screws	Triangular key	**NSYTCT274**

Closing locks

- Option of installing a side lock, on the opposite side to where the hinges are installed
- Ingress protection rating: IP43

NSYCL27M

NSYCL27L405

Characteristics	Tool	References
Double bar side lock and handle	NSYDBP	**NSYCL27M**
Side lock with key 405	Key 405	**NSYCL27L405**

Sealing and opening

NSYLT27

Characteristics	References
Triangular key for PLS	**NSYLT27**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Insulating modular boxes

External hinges

NSYBE27G

Comment:
IP level cannot be guaranteed due to type of application and installation

- To open the door to 180°.
- Material: Plastic

Supply:
Set of 2 hinges

Characteristics	References
External hinges, plastic	**NSYBE27G**

Internal hinges

Comment:
IP level cannot be guaranteed due to type of application and installation

NSYBL27

- To open the door to 180°.
- Material: Brass

Supply:
Set of 2 hinges

Characteristics	References
Internal hinges, brass	**NSYBL27**

7

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Insulating industrial boxes

Box of 74 x 74 x 54 mm (external dimensions) **NSYTB●●●775**

Interior



Side



Rear



Box of 89 x 89 x 54 mm (external dimensions) **NSYTB●●●885**

Interior



Side



Rear



Box of 116 x 74 x 62 or 94 mm (external dimensions) **NSYTB●●●1176** or **NSYTB●●●1179**

Interior



Side





Rear



Box of 116 x 116 x 62 or 133 mm (external dimensions) **NSYTB●●●11116** or **NSYTB●●●111113**

Interior



Side





Rear



Cover



Box of 138 x 93 x 72 mm (external dimensions) **NSYTB●●●1397**

Interior



Side



Rear



Cover



Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Life Is On Schneider Electric

Insulating industrial boxes

Box of 164 x 121 x 87 mm (external dimensions) **NSYTB●●●16128**

Interior



Side



Rear



Cover



Box of 192 x 121 x 87 or 105 mm (external dimensions) **NSYTB●●●19128** or **NSYTB●●●191210**

Interior



Side
Height 80 mm
(60 + 20 mm)



Side
Height 100 mm
(60 + 40 mm)



Rear



Cover



Box of 192 x 164 x 87 or 105 mm (external dimensions) **NSYTB●●●19168** or **NSYTB●●●191610**





Height 80 mm
(60 + 20 mm)





Height 100 mm
(60 + 40 mm)



7

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Insulating industrial boxes

Box of 241 x 194 x 87, 107 or 127 mm (external dimensions)
NSYTB●●●24198, **NSYTB●●●241910** or **NSYTB●●●241912**



Box of 291 x 241 x 88, 128 or 168 mm (external dimensions)
NSYTB●●●29248, **NSYTB●●●292412** or **NSYTB●●●292416**



Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Life Is On Schneider Electric

Insulating industrial boxes

Box of 341 x 291 x 128 or 168 mm (external dimensions)
NSYTB●●●342912 or **NSYTB●●●342916**











7

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Insulating industrial boxes

The surfaces are numbered to enable identification of the surfaces to be drilled in the customised offer.

NSYPLS●●●1827G



NSYPLS●●●2727●G



NSYPLS●●●2736●G



NSYPLS●●●3636G



NSYPLS●●●2754●G



NSYPLS●●●3654●G



NSYPLS●●●5454●G



NSYPLS●●●3672●G



NSYPLS●●●5472●G



A



B



A - B: Internal view of the corners of the polyester covers with bosses for inserts
ref. **NSYTEX5** for M5 screws.

* Thickness of 30/10[e] mm for the polyester cover.

Insulating modular boxes with modular distribution chassis

NSYPLS1827DLS12



NSYPLS2727DLS24



NSYPLS3627DLS24



NSYPLS3627DLS36



NSYPLS5427DLS48



Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Life Is On Schneider Electric

Insulating industrial boxes

Examples of assembly

All the boxes can be joined by their lateral surfaces, using the coupling frames **NSYUM●●●** or **NSYUCC●●●**, and the joining and fixing pieces **NSYPS2C27** and **NSYPS4C27**.





7

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Polyester wall-mounting enclosures

8

Life Is On Schneider Electric

Insulating wall-mounting enclosures

Thalassa PLM

Introduction	188
Characteristics	189
Selection guide	190
Specific accessories	191
Dimensions	202

8

Insulating wall-mounting enclosures

Monobloc wall-mounting enclosure, made of polyester reinforced with fibreglass, moulded by hot compression. Degree of protection IP66, Impact resistance IK10 for the plain doors and surfaces and IK08 for the glazed doors of the polyester versions, UL certification and NEMA classification 4x and 13 for the polyester wall-mounting enclosures, Total insulation to produce class II units, Complies with RoHS and REACH Directives

This range can be configured according to your needs

4 differents services available:

Assemble to order

Mounting of standard accessories

Painting

Machining

Green Premium™

Easy

- Door easily reversible by turning it over.
- Opening to 120° or 180°.
- Easy machining with no corrosion.
- Lightness.
- Polyamide hinge pin, easily removable and captive.

Service life

- High resistance to corrosion in harsh environments, maintaining its mechanical properties and insulation.

Smart

- Notches for easy fixing of DIN rails.
- Grid pattern on the rear of the door for marking the machining operations.

See page 532 for details or consult our web site www.se.com

Prolonged exposure to UV radiation, wind and rain can cause aesthetics changes in the external surface of the enclosure. Without affecting the technical properties according to IEC 62208. For long exposure applications, it is recommended to use painted enclosures available through the P&S offer.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

According to Reach and RoHs & Halogen free

Class II

Characteristics	ABS/PC wall-mounting enclosures	Polyester wall-mounting enclosures		
	• Monobloc wall-mounting enclosure. • Version with transparent polycarbonate door. • Closes with a 3 mm double bar lock. • Door opening: 180°.	• Monobloc wall-mounting enclosure. • Version with transparent tempered-glass door. • Closes with one 3 mm double bar lock. • Door opening angle: 120°. • Grid pattern with a pitch of 50 mm on the back of the door.	• Monobloc wall-mounting enclosure. • Version with transparent tempered-glass door. • Locking device outside the sealed area, helping guarantee the tightness of IP66 over time. • Locking system: enclosure height ≤ 847 mm: 2 locks with double bar insert or 1 handle with key lock and 3-point closure, • enclosure height 1056 mm: 1 lock with double bar insert and 4-point closure. • Door opening angle: 180°. • Bosses for accessory-fixing inserts: M6 inside the enclosure, M5 in the door for enclosure heights of 430 and 530 mm, M6 in the door for enclosure heights ≥ 647 mm. • Grid pattern with a pitch of 25 mm on the back of the door.	
Material	ABS/PC	Polyester reinforced with fibreglass, moulded by hot compression		
Temperature range - Gasket	-40°C to +80°C			
Colour	RAL 7035 grey			
Ingress protection rating	IP66 according to IEC 60529			
Mechanical protection rating	• IK10 plain door • IK08 glazed door			
Certifications (see page 624)	• IEC 62208 • Bureau Veritas Marine	• IEC 62208 • Marine • UL 508A - NEMA type: 1, 2, 3, 3R, 3S, 4, 4X, 5, 12 and 13		• IEC 62208 • Marine
Installation	• Direct fixing of symmetrical rails ref. **NSYCS200PLM** with plastic nuts ref. **NSYTCSPLM**, to be installed in the notches on the rear of the body, with a pitch of 25 mm • Fixing of installation plates on the studs at the rear of the enclosure	• Fixing of rear accessories on 4 M8 x 18 studs	• Fixing of rear accessories on 4 M8 studs, included in the standard supply • Direct fixing of symmetrical rails ref. **NSYCS●●●PLM**, with plastic nuts, ref. **NSYTCSPLM**, to be installed in the notches on the rear of the body, with a pitch of 25 mm	

External dimensions			References of wall-mounting enclosures with door							
Height (mm)	Width (mm)	Depth (mm)	Plain (3)	Transparent (4)	Plain (3)	Transparent (4)	Plain (3)	Transparent (4)	Plain (1)	Transparent (1) (4)
308	255	160	-	-	**NSYPLM3025G**	**NSYPLM3025TG**	-	-	-	-
310	215	160	**NSYPLM32G**	**NSYPLM32TG**	-	-	-	-	-	-
430	330	200	-	-	-	-	**NSYPLM43G**	**NSYPLM43TG**	**NSYPLM43VG**	**NSYPLM43TVG**
530	430	200	-	-	-	-	**NSYPLM54G**	**NSYPLM54TG**	**NSYPLM54VG**	**NSYPLM54TVG**
647	436	250	-	-	-	-	**NSYPLM64G**	**NSYPLM64TG**	**NSYPLM64VG**	**NSYPLM64TVG**
747	536	300	-	-	-	-	**NSYPLM75G**	**NSYPLM75TG**	**NSYPLM75VG**	**NSYPLM75TVG**
847	636	300	-	-	-	-	**NSYPLM86G**	**NSYPLM86TG**	**NSYPLM86VG**	**NSYPLM86TVG**
1056	852	350	-	-	-	-	**NSYPLM108G** (2)	**NSYPLM108TG** (2)	-	-

(1) Wall-mounting enclosure with handle and lock with 3-point closure and key 1242 E delivered as standard.
(2) Wall-mounting enclosure with standard 5 mm double bar lock and lock with 4-point closure.
(3) These enclosures are also available equipped with metallic or insulating mounting plates.
(4) Must be protected against sun radiation.

Comment:
For air shipments of **NSYPLM108G**, the reference **NSYPLMRS108GA** must be ordered

8

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Insulating wall-mounting enclosures

Comment:
Dimensions, see page 202

ABS/PC wall-mounting enclosures with door			Polyester wall-mounting enclosures with door	
Plain (3)	Transparent (4)		Plain (3)	Transparent (4)
References	References		References	References
NSYPLM32G	**NSYPLM32TG**		**-**	**-**
-	**-**		**NSYPLM3025G**	**NSYPLM3025TG**

External dimensions		
Height (mm)	Width (mm)	Depth (mm)
310	215	160
308	255	160

Comment:
Dimensions, see page 202

Polyester wall-mounting enclosures with door					
Plain (3)	NSYPLM108G	Transparent (4)	NSYPLM108TG	Plain (1)	Transparent (1) (4)
References		References		References	References
NSYPLM43G		**NSYPLM43TG**		**NSYPLM43VG**	**NSYPLM43TVG**
NSYPLM54G		**NSYPLM54TG**		**NSYPLM54VG**	**NSYPLM54TVG**
NSYPLM64G		**NSYPLM64TG**		**NSYPLM64VG**	**NSYPLM64TVG**
NSYPLM75G		**NSYPLM75TG**		**NSYPLM75VG**	**NSYPLM75TVG**
NSYPLM86G		**NSYPLM86TG**		**NSYPLM86VG**	**NSYPLM86TVG**
NSYPLM108G (2)		**NSYPLM108TG (2)**		**-**	**-**

External dimensions		
Height (mm)	Width (mm)	Depth (mm)
430	330	200
530	430	200
647	436	250
747	536	300
847	636	300
1056	852	350

(1) Wall-mounting enclosure with handle and lock with 3-point closure and key 1242 E delivered as standard.
(2) Wall-mounting enclosure with standard 5 mm double bar lock and lock with 4-point closure.
(3) These enclosures are also available equipped with metallic or insulating mounting plates.
(4) Must be protected against sun radiation.

8

Comment:
Dimensions, see page 202

Wall-mounting enclosures with plain door and mounting plate (Not mounted)			
Plain	Bakelite	Plain	Bakelite
References	References	References	References
NSYPLM32PG	**NSYPLM32BG**	**-**	**-**
-	**-**	**NSYPLM3025PG**	**NSYPLM3025BG**

External dimensions		
Height (mm)	Width (mm)	Depth (mm)
310	215	160
308	255	160

Comment:
Dimensions, see page 202

Wall-mounting enclosures with plain door and mounting plate (Not mounted)			
Plain		Bakelite	NSYPLM108BG
References		References	
NSYPLM43PG		**NSYPLM43BG**	
NSYPLM54PG		**NSYPLM54BG**	
NSYPLM64PG		**NSYPLM64BG**	
NSYPLM75PG		**NSYPLM75BG**	
NSYPLM86PG		**NSYPLM86BG**	
-		**NSYPLM108BG**	

External dimensions		
Height (mm)	Width (mm)	Depth (mm)
430	330	200
530	430	200
647	436	250
747	536	300
847	636	300
1056	852	350

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Insulating wall-mounting enclosures

Characteristics	ZM plinth for PLM enclosure
	• Designed to support and raise enclosures **NSYPLM75G**, **NSYPLM86G** and **NSYPLM108G**. • Plinth height of 200 mm; Stackable to obtain a 400 mm plinth. • Four floor attachment points; The symmetry of the parts helps prevent incorrect assembly. The frontal parts of the plinth (front and rear) have two stainless steel screws protected by a plastic cap; These screws make it possible (using an Allen key) to open and remove the frontal parts for easier cable installation. In stacked position, the bottom plinth can be partially buried. It is provided with one transverse reinforcement rail, adjustable to adapt to the position of the cables. The reference of the plinth contains all the accessories required for attaching the enclosure to the plinth and for stacking two plinths.
Material	Polyester reinforced with fibreglass, moulded by hot compression
Ingress protection rating	IP44
Mechanical protection rating	IK10
Standards	Helps guarantee total insulation according to IEC 61439-1

Plinth

NSYZM253G

Characteristics	PLM enclosure	Height (mm)	Width (mm)	Depth (mm)	Reference
Plinth	NSYPLM75G	200	456	302	**NSYZM253G**
Plinth	NSYPLM86G	200	556	302	**NSYZM263G**
Plinth	NSYPLM108G	200	772	352	**NSYZM283G**

Cable supporting cross rail

The lateral sides of the plinths are provided with bosses for attaching cross rails with cut-out profiles, for supporting cables. The reference of the cross rail includes all the elements required for assembly.

NSYAC280

Characteristics	For plinth	Reference
Cable supporting cross rail	NSYZM253G	**NSYAC280**
Cable supporting cross rail	NSYZM263G	**NSYAC360**
Cable supporting cross rail	NSYZM283G	**NSYAC600**

Kit for IP54

NSYAEPZM

Required to obtain IP54 for the plinth and the plinth enclosure coupling.

Characteristics	Reference
Kit for IP54	**NSYAEPZM**

Feet for partially buried installation

NSYAEBFZ

Allows the partially buried installation of plinths before completion of the floor.
The plinths are attached by four feet with a standard length of 750 mm.
Possibility of horizontal adjustment of the plinth. The reference includes a kit made up of four feet and fixings.

Characteristics	Reference
Feet for partially buried installation	**NSYAEBFZ**

8

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Insulating wall-mounting enclosures

Floor-mounting pillar

To protect cables entering the enclosure in outdoor installations.
Cable entry section: 165 x 100 mm.
For enclosures ref. **NSYPLM54G**, **NSYPLM54TG**, **NSYPLM64G** and **NSYPLM64TG**.



NSYSFSPLMG

- Material: Polyester reinforced with fibreglass
- Colour: RAL 7035 grey

Supply:
Delivered with steel frame for secure fixing to the floor

Characteristics	Reference
Floor-mounting pillar	**NSYSFSPLMG**

Wall fixing lugs

Set of 4 wall fixing lugs. Mounted directly on the enclosure, either in horizontal position or in vertical position.

- Material: Polyamide loaded with fibreglass
- Colour: RAL 7035 grey
- **Maximum load:**
  On PLM32: Vertical or horizontal: 10 kg
  Other PLM models: Vertical position: 200 kg, horizontal position: 100 kg

NSYPFPLMG

NSYPFPLM32G

Supply:
Delivered with fixings

Characteristics	Reference
Wall fixing lugs	**NSYPFPLMG**
Wall fixing lugs, Exclusive for enclosures ref. NSYPLM32G and NSYPLM32TG.	**NSYPFPLM32G**

Wall fixing lugs

Set of 4 wall fixing lugs. Mounted directly on the enclosure, either in horizontal position or in vertical position.

- Material: Stainless steel
- Colour: RAL 7035 grey
- **Maximum load:**
  On PLM32: Vertical or horizontal: 10 kg
  Other PLM models: Vertical position: 200 kg, horizontal position: 100 kg

NSYPFXPLM

Supply:
Delivered with fixings

Characteristics	Reference
Wall fixing lugs	**NSYPFXPLM**

Post fixing device

NSYSFP300



- For outdoor installations on a post with a maximum circumference of 675 mm, Ø 215 mm.
- Material: Galvanised steel
- Maximum load: 100 kg

Supply:
Supply of the rail, the strips and the fixings

Characteristics	For wall-mounting enclosure	Reference
Post fixing device	NSYPLM43G	**NSYSFP300**
Post fixing device	NSYPLM54G and NSYPLM64G	**NSYSFP400**
Post fixing device	NSYPLM75G	**NSYSFP500**
Post fixing device	NSYPLM86G	**NSYSFP600**

Blanking plates

Aesthetic Accessory. They are positioned on the rear surface of the enclosures to block the openings in the corners in order to improve their appearance or help prevent the entry of unwanted elements in the ventilation shaft. Supplied as standard for enclosure, ref. **NSYPLM108G**.

- Material: Thermoplastic
- Colour: RAL 7035 grey
- Ingress protection rating: IP40

NSYCEPLMAG

Accessorie out of the protected area IP66

Characteristics	For wall-mounting enclosure	Reference
Blanking plates	NSYPLM32G	**NSYCEPLMAG**
Blanking plates	NSYPLM43G and NSYPLM54G	**NSYCEPLMBG**
Blanking plates	NSYPLM64G, 75G and 86G	**NSYCEPLMCG**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Insulating wall-mounting enclosures

Support bracket for enclosure with anti-tilt kit and reinforcement

NSYCOCNS1400

- The support bracket is used when the enclosure cannot be hung from a wall or a post.
- Suitable for outdoor use.
- Maximum enclosure dimensions: 1000 x 800 x 300 mm.
- Floor attachment by standard M12 fastenings.
- Material: Steel
- Finish: Epoxy polyester paint
- Colour: RAL 7035 grey
- Maximum load: 120 kg

Characteristics	Height (mm)	References
Support bracket for enclosure with anti-tilt kit and reinforcement	1400	**NSYCOCNS1400**
Support bracket for enclosure with anti-tilt kit and reinforcement	1800	**NSYCOCNS1800**

Internal door



- Reversible door.
- Grid pattern with a pitch of 25 mm for easier marking out before drilling.
- Closes with 2 double bar locks.
- Door handle.
- Steel internal door, without grid pattern and locking by a screw, for enclosures ref. **NSYPLM3025G**.
- Incompatible with the modular distribution chassis.
- Material: Polyester reinforced with fibreglass, self-extinguishing
- Colour: RAL 7035 grey

Supply:
Delivered with fixings and brass inserts

NSYPA3025PLMG

Characteristics	Height (mm)	Width (mm)	A (mm)	B (mm)	C (mm)	D Plain door (mm)	D Transp. door (mm)	Reference
Internal door	308	255	248	165	62	76	71	**NSYPA3025PLMG**
Internal door	430	330	315	205	152	26	21	**NSYPAP43G**
Internal door	530	430	415	305	152	26	21	**NSYPAP54G**
Internal door	645	435	515	305	194	32	27	**NSYPAP64G**
Internal door	745	535	615	405	244	32	27	**NSYPAP75G**
Internal door	845	635	715	505	244	32	27	**NSYPAP86G**
Internal door	1055	850	850	650	269	37	32	**NSYPAP108G**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Insulating wall-mounting enclosures

					Metallic mounting Plate			
								
Characteristics					**Plain**	**Skilscreened**	**Microperforated**	
Model	Enclosure Dimensions			MP Dimension				
	Height (mm)	Width (mm)	Depth (mm)	Height (mm)	Width (mm)	Reference	Reference	Reference
NSYPLM32	310	215	160	250	150	**NSYMM32**	-	-
NSYPLM3025	308	255	160	250	200	**NSYMM3025**	-	-
NSYPLM43	430	330	200	230	350	**NSYMM43**	**NSYMS43**	**NSYMF43**
NSYPLM54	530	430	200	450	350	**NSYMM54**	**NSYMS54**	**NSYMF54**
NSYPLM64	647	436	250	550	350	**NSYMM64**	**NSYMS64**	**NSYMF64**
NSYPLM75	747	536	300	650	450	**NSYMM75**	**NSYMS75**	**NSYMF75**
NSYPLM86	847	636	300	750	550	**NSYMM86**	**NSYMS86**	**NSYMF86**
NSYPLM108	1056	852	350	950	750	**NSYMM108**	-	**NSYMF108**

8

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

	Insulating mounting plates	
		
Telequick	**Bakelite**	**Polyester**

Height (mm)	Width (mm)	# of perfo-ration H	# of perfo-ration W	Reference	Height (mm)	Width (mm)	Thick. (mm)	Reference	Height (mm)	Width (mm)	Thick. (mm)	Reference
255	153.7	16	5	**NSYMR32**	265	150	4	**NSYMB32**	265	150	4	**NSYMPP32**
253	228	16	8	**NSYMR3025**	265	200	4	**NSYMB3025**	265	200	4	**NSYMPP3025**
348.7	251	22	9	**NSYMR43**	325	250	4	**NSYMB43**	325	250	4	**NSYMPP43**
450	351	31	11	**NSYMR54**	465	350	4	**NSYMB54**	465	350	4	**NSYMPP54**
555	351	38	11	**NSYMR64**	565	350	4	**NSYMB64**	565	350	4	**NSYMPP64**
645	451	44	14	**NSYMR75**	665	450	4	**NSYMB75**	665	450	4	**NSYMPP75**
750	551	51	17	**NSYMR86**	765	550	4	**NSYMB86**	765	550	5	**NSYMPP86**
945	751	64	24	**NSYMR108**	965	750	4	**NSYMB108**	965	750	5	**NSYMPP108**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Insulating wall-mounting enclosures

- The ABS/PC 310 x 215 mm enclosure is supplied with a lock with a double bar insert as standard.
- The 308 x 255 mm enclosure is supplied with one lock with a double bar insert as standard.
- The polyester enclosures from 430 to 847 mm high are delivered as standard with: 2 locks with double bar insert, ref. **NSYCDBPLM**, or a 3-point closure with handle and lock with key 1242 E (enclosures **NSYPLM●●VG**).
- Double bar insert ref. **NSYTDBCRN**, is placed in a rectangular escutcheon.
- A plastic key, ref. **NSYDBP**, enabling the opening of the double bar insert, is included in the standard supply. This key can be fixed to the double bar system to remain on the enclosure and be used as a handle.

Options to transform the locks with double bar inserts **NSYPLM32G** to **NSYPLM86G**

NSYTC8CRN

NSYTT8CRN

NSYTL405PLM

- Changing the shape inserts for locks with keys according to the following table.

Characteristics	Operated with a key	References
Square insert 6 mm □	LC-7	**NSYTC6CRN**
Square insert 7 mm □	LC-7	**NSYTC7CRN**
Square insert 8 mm □	LC-8	**NSYTC8CRN**
Triangular insert 6 mm ▲	LT-8	**NSYTT6CRN**
Triangular insert 8 mm ▲	LT-8	**NSYTT8CRN**
Lock and key 405		**NSYTL405PLM**
Lock and key 220		**NSYTL220PLM**
Lock TJIS		**NSYTJIS**

Options to transform the locks with double bar inserts **NSYPLM32G** to **NSYPLM86G**

NSYTHL1242EPLM

- Replacement for locking handle with cylindrical barrel, delivered with all the parts required to change the lock.

Characteristics	References
Key 1242 E	**NSYTHL1242EPLM**
Key 405	**NSYTHL405PLM**
Key 421	**NSYTHL421PLM**
Key 455	**NSYTHL455PLM**
Key 2331 A	**NSYTHL2331APLM**
Key 2433 A	**NSYTHL2433APLM**
Key 3113 A	**NSYTHL3113APLM**
Key 3131A	**NSYTHL3131APLM**
Manual	**NSYTHPLM**

Options to transform versions **NSYPLM●●V**, with retractable handle and 3-point closure


NSYTDB5ME

- Transformation of the standard insert (barrel for key 1242E, ref. **NSYTL1242EME**) for other shape inserts or barrels according to the following table.

Characteristics	References
5 mm double bar	**NSYTDB5ME**
6 mm male square	**NSYTC6ME**
8 mm male square	**NSYTC8ME**
6.5 mm male triangle	**NSYTT6ME**
8 mm male triangle	**NSYTT8ME**
Barrel and key 405	**NSYTCL405ME**
Reinforced key and barrel	**NSYTLRME**
JIS key and barrel	**NSYTLJISME**
Manual	**NSYTMME**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Insulating wall-mounting enclosures

- Enclosures delivered as standard with 5 mm double bar insert.
- Double bar insert ref. **NSYTDB5PL**, placed in a long rectangular escutcheon, activates a 4-point closure system.

Locks and inserts for enclosures **NSYPLM108/T**

- Options to transform the insert
- The standard insert can be replaced with other shape inserts, according to the following table.



NSYTDB5PL

Characteristics	References
Double bar insert	**NSYTDB5PL**
6.5 mm male triangle	**NSYTT6PL**
7 mm male triangle	**NSYTT7PL**
8 mm male triangle	**NSYTT8PL**

Locks and inserts for enclosures **NSYPLM108/T**

- Options to transform for a retractable handle
- The escutcheon and rosette assembly can be replaced with a lock with retractable handle equipped with inserts or barrels, according to the following table.



NSYTEDB5PL

Characteristics	References
5 mm double bar	**NSYTEDB5PL**
6 mm male square	**NSYTEC6PL**
7 mm male square	**NSYTEC7PL**
8 mm male square	**NSYTEC8PL**
6.5 mm male triangle	**NSYTET6PL**
8 mm male triangle	**NSYTET8PL**
Lock key 1242 E	**NSYTEL1242EPL**
Barrel and key 405	**NSYTEL405PL**
Reinforced key and barrel	**NSYTERPL**
JIS key and barrel	**NSYTELJISPL**
FAC key and barrel	**NSYTELFACPL**
Manual	**NSYTEMPL**

Padlocking accessories

Padlocking system positioned around the rectangular escutcheon of the enclosures with a height of ≤ 847 mm to block access to the lock; For a Ø 9 mm padlock.

NSYKPLM

Characteristics	References
Padlocking accessories	**NSYKPLM**

Padlocking accessories

Padlocking system positioned around the long rectangular escutcheon of the enclosures ref. **NSYPLM108G/TG**, to block access to the lock; For Ø 9 mm padlock.

NSYBCPL

Characteristics	References
Padlocking accessories	**NSYBCPL**

Padlocking accessories

Padlocking system to block access to the retractable handle, for the versions **NSYPLM●●V** or optionally for enclosures ref. **NSYPLM108G/TG**, for a Ø 9 mm padlock.

NSYBCME

Characteristics	References
Padlocking accessories	**NSYBCME**

8

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Insulating wall-mounting enclosures

Step slides



Kit allowing depth adjustment with a pitch of 12.5 mm, and the fixings required for the installation. Incompatible with the modular distribution chassis.

Supply:
4 step slides with brackets

NSYDPLM200

Characteristics (Material: Galvanised steel)	For wall-mounting enclosure depth (mm)	Depth adjustment A (mm)	Depth adjustment B (mm)	References
Step slides	200	156	94	**NSYDPLM200**
Step slides	250	200	100	**NSYDPLM250**
Step slides	300	250	100	**NSYDPLM300**
Step slides	350	306	106	**NSYDPLM350**

Plastic nuts for rail fixing

They slide directly into the notches, with a pitch of 25 mm, which are located on the rear of the enclosures, except enclosure ref. **NSYPLM3025G/TG**. They allow direct fixing of symmetrical DIN rails by self-tapping screws. Option of raising the rails with an M6 spacer using a plastic nut containing an M6 nut.

Supply:
References by unit. Order by multiples of 20 units (20, 40, 60, etc.)

NSYTCSPLM

Characteristics	References
Plastic nut with self- tapping screw	**NSYTCSPLM**
Plastic nut containing an M6 metal nut	**NSYTCSM6PLM**

35 mm symmetrical DIN rails

They are fixed to the rear of the enclosure without uprights, with a pitch of 25 mm for the notches on the rear of the enclosure, with the help of direct-fixing nuts ref. **NSYTCSPLM** or **NSYTCSM6PLM**.
- Material: Galvanised steel

Supply:
References by unit. Order by multiples of 2 units (2, 4, 6, etc.)

NSYCS200PLM

Characteristics	For wall-mounting enclosure width (mm)	Rail length (mm)	References
35 mm symmetrical DIN rails	215	180	**NSYCS200PLM**
35 mm symmetrical DIN rails	330	280	**NSYCS300PLM**
35 mm symmetrical DIN rails	430 / 436	380	**NSYCS400PLM**
35 mm symmetrical DIN rails	536	480	**NSYCS500PLM**
35 mm symmetrical DIN rails	636	580	**NSYCS600PLM**
35 mm symmetrical DIN rails	852	795	**NSYCS800PLM**

Coupling frame

Allows the lateral coupling of two enclosures.
- Material: Polyester frame
- Colour: RAL 7035 grey
- Ingress protection rating:
  A built-in sealing gasket guarantees a protection rating of IP66

Supply:
Delivered with fixings

NSYBUPLMG

Characteristics	External dimensions (mm)	Entry	For wall-mounting enclosure	References
Coupling frame	435 x 185 x 15	398 x 148	NSYPLM75G and NSYPLM86G	**NSYBUPLMG**
Coupling frame	635 x 185 x 15	598 x 148	NSYPLM108G	**NSYBU108PLMG**

Cable gland plates

- Material: Polyester
- Colour: RAL 7035 grey

Supply:
Delivered with fixings

NSYTLA4420G

Characteristics	External dimensions (mm)	Entry	For wall-mounting enclosure	References
Cable gland plates	435 x 185 x 15	398 x 148	NSYPLM75G and NSYPLM86G	**NSYTLA4420G**
Cable gland plates	635 x 185 x 15	598 x 148	NSYPLM108G	**NSYTLA6420G**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Insulating wall-mounting enclosures

Fixing inserts

NSYTEX5

NSYTEX6

NSYTEX8PLM

Expanding inserts for addition to the M6 bosses of the enclosure, the M5 or M6 bosses of the door and the M8 bosses of the external rear part of the enclosure.

Supply:
References by unit. Order by multiples of 8 units (8, 16, 24, etc.). M5 and M6 inserts to be ordered in multiples of 20

Characteristics	Insert size	For wall-mounting enclosure	References
Fixing inserts	M5	NSYPLM43G and NSYPLM54G	**NSYTEX5**
Fixing inserts	M6	NSYPLM64G to NSYPLM108G	**NSYTEX6**
Fixing inserts	M8	For the rear of the enclosure	**NSYTEX8PLM**

Ventilation louvres

NSYCAG35LP

- They can be positioned inside the wall-mounting enclosures with heights from 430 to 846 mm, allowing ventilation through the channels of the enclosure.

Supply:
References by unit. Order by multiples of 2 units (2, 4, 6, etc.)

Characteristics	References
Ventilation louvres	**NSYCAG35LP**

Water drain plug

NSYVEA9

- For drainage of condensation water.(Condensation should be eliminated using ClimaSys solution.) It is placed in the Ø 8.5 mm (8.2 mm for wall-mounting enclosures **NSYPLM32G**, **NSYPLM32TG**, **NSYPLM32PG** and **NSYPLM32BG**. diverse accesories) housing at the bottom of the enclosure.
- Ingress protection rating: IP53

Supply:
References by unit. Order by multiples of 10 units (10, 20, 30, etc.)

Characteristics	References
Water drain plug	**NSYVEA9**

Renovation and anti graffiti paint

NSYAUPG1G

Supply: NSYAUPG1G
The 1 kg reference includes 1 pot with 800 g of base paint and 200 g of hardener
(It is enough to paint a surface of around 5 m²)

Supply: NSYAUPG5G
The 5 kg reference includes 1 pot with 4 kg of base paint and 1 kg of hardener
(It is enough to paint a surface of around 25 m²)

- Paint kit with two components (base 80 % + hardener 20 %)
- Specially designed for polyester enclosures, for their renovation and/or as prevention to allow easy removal of graffiti.
- Colour: RAL 7035 grey

Characteristics	References
Renovation and anti graffiti paint	**NSYAUPG1G**
Renovation and anti graffiti paint	**NSYAUPG5G**

Supply:
1 kg

- Solvent bottles to be used as a paint thinner or to clean brushes.

Characteristics	References
Renovation and anti graffiti paint solvent	**NSYAUPGS**

8

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

S3D* S3X PLM

Characteristics	DLA modular chassis
	• Front panels and covers installed in the front part, are not depth adjustable. • Rigid structure for the installation of modular devices. • Open front panels with 35 mm DIN rail and plain front panels with mounting plate, according to the model. • Front plates quick installation with no fixings. • Rail depth adjustable from 40 to 85 mm. • System for standard circuit marking. • Incompatible with the internal doors and the step slides. • Neutral / earth strip: 2 x 16 mm² + 5 x 6 mm².
Material	Front panels and finish covers: Polystyrene Rigid structure: Galvanised steel
Colour	Front panels and finish covers: RAL 7035 grey

DLA modular chassis

NSYDLA24G

Characteristics	No. of rows	No. of 18 mm modules per row	No. of 18 mm modules	No. of plates	PLM enclosure References		S3D enclosure (depth ≥ 200 mm) Height (mm)	Width (mm)	Reference
DLA modular chassis	2	12	24	-	NSYPLM43G	NSYPLM43TG	400	300	**NSYDLA24G**
DLA modular chassis	3	16	48	-	NSYPLM54G	NSYPLM54TG	500	400	**NSYDLA48G**
DLA modular chassis	3	16	48	-	NSYPLM64G	NSYPLM64TG	600	400	**NSYDLA48PG**
DLA modular chassis	3	22	66	1	NSYPLM75G	NSYPLM75TG	700	500	**NSYDLA66G**
DLA modular chassis	4	22	88	-	NSYPLM75G	NSYPLM75TG	700	500	**NSYDLA88G**
DLA modular chassis	3	28	84	1	NSYPLM86G	NSYPLM86TG	800	600	**NSYDLA84G**
DLA modular chassis	4	28	112	-	NSYPLM86G	NSYPLM86TG	800	600	**NSYDLA112G**
DLA modular chassis	6	39	234	-	NSYPLM108G	NSYPLM108TG	1000	800	**NSYDLA234G**



NSYDLA24 **NSYDLA48** **NSYDLA48P** **NSYDLA66** **NSYDLA88** **NSYDLA84** **NSYDLA112** **NSYDLA234**





★ Models **NSYDLA48PG**, **66**, **88**, **84** and **112**.
★★ Models **NSYDLA234**.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Insulating wall-mounting enclosures

Plain front panels for Dinimel DLA chassis

- Front panel for non modular device protection, on one row.
- To be ordered in multiples of two.
- Material: Polystyrene
- Colour: RAL 7035 grey

NSYCTL300DLAG

Characteristics	Width (mm)	For installing on the chassis	Reference
Plain front panels for Dinimel DLA chassis	256	NSYDLA24G	**NSYCTL300DLAG**
Plain front panels for Dinimel DLA chassis	356	NSYDLA48G and NSYDLA48PG	**NSYCTL400DLAG**
Plain front panels for Dinimel DLA chassis	456	NSYDLA66G and NSYDLA88G	**NSYCTL500DLAG**
Plain front panels for Dinimel DLA chassis	555	NSYDLA84G and NSYDLA112G	**NSYCTL600DLAG**
Plain front panels for Dinimel DLA chassis	755	NSYDLA234G	**NSYCTL800DLAG**

Mounting plate for Dinimel DLA chassis

- Mounting plate for mounting nonmodular devices, on one row.
- To be ordered in multiples of two.
- Material: Galvanised steel


NSYPMP400DLA

Characteristics	Width (mm)	For installing on the chassis	Reference
Mounting plate for Dinimel DLA chassis	315	NSYDLA48G and NSYDLA48PG	**NSYPMP400DLA**
Mounting plate for Dinimel DLA chassis	415	NSYDLA66G and NSYDLA88G	**NSYPMP500DLA**
Mounting plate for Dinimel DLA chassis	514	NSYDLA84G and NSYDLA112G	**NSYPMP600DLA**
Mounting plate for Dinimel DLA chassis	714	NSYDLA234G	**NSYPMP800DLA**

Modular distribution chassis

- For mounting modular devices on two rows of nine 18 mm modules.
- Material:
  Chassis: Metal Protective
  Plate: Insulating material

NSYDLPLM18G

Characteristics	For enclosure	Reference
Modular distribution chassis	NSYPLM3025G/TG	**NSYDLPLM18G**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Insulating wall-mounting enclosures

ABS/PC wall-mounting enclosures



Polyester wall-mounting enclosures 308 x 255 mm



Warning! now there's only one lock for this model

8

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Insulating wall-mounting enclosures

Other polyester wall-mounting enclosures



External fixing with lugs (mm)				
	Vertical		Horizontal	
References	X	Y	X'	Y'
NSYPLM43G	490	225	355	360
NSYPLM54G	590	325	455	460
NSYPLM64G	690	330	555	465
NSYPLM75G	790	430	655	565
NSYPLM86G	890	530	755	665
NSYPLM108G	1090	750	955	885

Glazed door opening (mm)		
References	U	V
NSYPLM43TG	273	194
NSYPLM43TVG	273	151
NSYPLM54TG	373	294
NSYPLM54TVG	373	251
NSYPLM64TG	463	294
NSYPLM64TVG	463	252
NSYPLM75TG	563	394
NSYPLM75TVG	563	352
NSYPLM86TG	663	494
NSYPLM86TVG	663	452
NSYPLM108TG	854	661

	Dimensions (mm)										Bottom screw and door bosses (mm)		Internal fixing (mm)		
References	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O
NSYPLM43G	430	330	200	380	260	181	247	247	179	168	325	225	225	150	13
NSYPLM54G	530	430	200	480	360	181	347	347	279	168	425	325	325	250	13
NSYPLM64G	647	436	250	580	360	228	388	388	279	212	525	325	325	250	13
NSYPLM75G	747	536	300	680	460	278	487	487	379	261	625	425	425	350	15
NSYPLM86G	847	636	300	780	560	278	587	587	479	261	725	525	525	450	15
NSYPLM108G	1056	852	350	980	760	327	775	775	680	300	925	725	725	650	15

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

PLA Version

PLAT Version

PLAZ Version

PLAZT Version

PLD Version

Life Is On Schneider Electric

Insulating floor-standing enclosures

Thalassa PLA Polyester floor-standing enclosures

Introduction	206
Characteristics	207
Selection guide	208
Specific accessories overview	210
Dimensions	223

Thalassa PLD Polyester DIN floor-standing enclosure

Introduction	226
Characteristics	227
Specific accessories overview	228
Dimensions	230

Polyester floor-standing enclosures

The **floor-standing enclosures** are made of **polyester reinforced with fibreglass**, moulded by hot compression. High resistance to corrosion in harsh environments, it maintains its mechanical and insulation properties.

This range can be configured according to your needs

4 differents services available:

Assemble to order

Mounting of standard accessories

Painting

Machining

Green Premium™

New Bigger dimensions
2000 mm height and 620 mm depth dimensions have been included to fit industry and infrastructure demands for motor control, power distribution, electronics or telecom applications.

PLAT version

Ventilation
- Open top with canopy allows passive ventilation.

Easy
- Various bosses for M8 inserts.

PLAZ version

Open bottom
- Big open bottom to be mounted directly on the floor or on a plinth.

Smart
- Plain mounting plate installed on step slides and compulsory adapter plates in all the enclosures with open bottom part.

PLAZT version

Easy
- Door opening to 180°.

Resistant
- Anti lever security system..

See page 532 for details or consult our web site www.se.com

Prolonged exposure to UV radiation, wind and rain can cause aesthetics changes in the external surface of the enclosure.
Without affecting the technical properties according to IEC 62208.
For long exposure applications, it is recommended to use painted enclosures available through the P&S offer.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Class II

Characteristics	PLA	PLAT	PLAZ	PLAZT
	Completely sealed enclosure Enclosure obtained by assembling: • 1 sealed top part, • 1 sealed bottom part, • 2 side parts, • 1 or 2 rear panels (according to width), • 1 or 2 doors (according to width). • Locking system with handle with a 5 mm double bar insert block, included in the standard supply. Other blocks with inserts or barrels and keys optionally available. • Door opening to 120°.	**Enclosure with ventilated canopy** Enclosure obtained by assembling: • 1 open top part with canopy, • 1 sealed bottom part, • 2 side parts, • 1 or 2 rear panels (according to width), • 1 or 2 doors (according to width). • Locking system with handle with a 5 mm double bar insert block, included in the standard supply. Other blocks with inserts or barrels and keys optionally available. • Door opening to 120°.	**Enclosure with open bottom** Enclosure obtained by assembling: • 1 sealed top part, • 1 plinth-type open bottom part, • 2 side parts, • 1 or 2 rear panels (according to width), • 1 or 2 doors (according to width). • Locking system with handle with a 5 mm double bar insert block, included in the standard supply. Other blocks with inserts or barrels and keys optionally available. • Door opening to 120°.	**Enclosure with open bottom and ventilated canopy** • Enclosure obtained by assembling: • 1 open top part with canopy, • 1 plinth-type open bottom part, • 2 side parts, • 1 or 2 rear panels (according to width), • 1 or 2 doors (according to width). • Locking system with handle with a 5 mm double bar insert block. Other blocks with inserts or barrels and keys optionally available. • Door opening to 180°. • Anti-lever system to help prevent forcing of the door.
Material	• Polyester reinforced with fibreglass			
Finish	• Moulded by hot compression: The pieces have an excellent finish on both sides and can include numerous bosses for accommodating inserts and mounting or cable management accessories			
Colour	• RAL 7035 grey			
Ingress protection rating	IP65 according to IEC 60529	• IP44 according to IEC 60529 • IP54 with 1 or 2 internal grilles, ref. **NSYCAG125LPF**, to be ordered separately.	IP54 according to IEC 60529	• IP44 according to IEC 60529 • IP54 with 1 or 2 internal grilles, ref. **NSYCAG125LPF**, to be ordered separately
Mechanical protection rating	IK10 (20 joules) plain door - IEC62262 and IK08 glazed door			
Insulation	• Class II according to IEC 60950-1 if the mounting process follow the included mounting instructions sheet			
Certifications	• UL 508A/CAN-CSA 22 • single door: NEMA types 1, 2, 3, 3R, 3S, 5, 12 and 13 • double door: NEMA types 1, 2, 12 and 13 • Bureau Veritas Marine • IEC 62208	• IEC 62208		
Installation	• Indoor use only. For outdoor use, must install a canopy	• Outdoor or indoor installation		
	• Direct fixing to the floor or by means of a plinth with a height of 60 mm, as an option, see page 212 • Possibility of fixing on a semi-embedded plinth, see page 212 • Optional wall fixing lugs		• The open bottom part forms a 60 mm plinth which is fixed to the floor directly or by means of an optional fixing frame, see page 214, or else it is installed on a semi-embedded plinth, see page 214	
	• The versions with glassed door must be protected against the direct sun shine to avoid greenhouse effect			
Options	• Anti-posting door upon request			

PHD - Applicative and customised solutions:
See the Polyester Heavy Duty offer in the Applicative and customised solutions, page 416.

9

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Polyester floor-standing enclosures

Indoor and Outdoor:
For outdoor use, must install a canopy.

Dimensions (mm)				Completely sealed enclosures, IP65		Enclosures with open bottom part, IP54
				PLA	PLA	PLAZ
Height	Width	Depth	N° of doors	Plain	Glazed**	Plain
500	500	320	1	NSYPLA553G	NSYPLA553TG	NSYPLAZ553G
500	500	420	1	NSYPLA554G	NSYPLA554TG	NSYPLAZ554G
500	750	320	1	NSYPLA573G	NSYPLA573TG	NSYPLAZ573G
500	750	420	1	NSYPLA574G	NSYPLA574TG	NSYPLAZ574G
500	1000	320	2	NSYPLA5103G	NSYPLA5103TG	NSYPLAZ5103G
500	1000	420	2	NSYPLA5104G	NSYPLA5104TG	NSYPLAZ5104G
500	1250	320	2	NSYPLA5123G	NSYPLA5123TG	NSYPLAZ5123G
500	1250	420	2	NSYPLA5124G	NSYPLA5124TG	NSYPLAZ5124G
750	500	320	1	NSYPLA753G	NSYPLA753TG	NSYPLAZ753G
750	500	420	1	NSYPLA754G	NSYPLA754TG	NSYPLAZ754G
750	750	320	1	NSYPLA773G	NSYPLA773TG	NSYPLAZ773G
750	750	420	1	NSYPLA774G	NSYPLA774TG	NSYPLAZ774G
750	750	420	1	NSYPLA776G	NSYPLA776TG	NSYPLAZ776G
750	1000	320	2	NSYPLA7103G	NSYPLA7103TG	NSYPLAZ7103G
750	1000	420	2	NSYPLA7104G	NSYPLA7104TG	NSYPLAZ7104G
750	1250	320	2	NSYPLA7123G	NSYPLA7123TG	NSYPLAZ7123G
750	1250	420	2	NSYPLA7124G	NSYPLA7124TG	NSYPLAZ7124G
1000	500	320	1	NSYPLA1053G	NSYPLA1053TG	NSYPLAZ1053G
1000	500	420	1	NSYPLA1054G	NSYPLA1054TG	NSYPLAZ1054G
1000	750	320	1	NSYPLA1073G	NSYPLA1073TG	NSYPLAZ1073G
1000	750	420	1	NSYPLA1074G	NSYPLA1074TG	NSYPLAZ1074G
1000	1000	320	2	NSYPLA10103G	NSYPLA10103TG	NSYPLAZ10103G
1000	1000	420	2	NSYPLA10104G	NSYPLA10104TG	NSYPLAZ10104G
1000	1250	320	2	NSYPLA10123G	NSYPLA10123TG	NSYPLAZ10123G
1000	1250	420	2	NSYPLA10124G	NSYPLA10124TG	NSYPLAZ10124G
1250	500	320	1	NSYPLA1253G	NSYPLA1253TG	NSYPLAZ1253G
1250	500	420	1	NSYPLA1254G	NSYPLA1254TG	NSYPLAZ1254G
1250	750	320	1	NSYPLA1273G	NSYPLA1273TG	NSYPLAZ1273G
1250	750	420	1	NSYPLA1274G	NSYPLA1274TG	NSYPLAZ1274G
1250	750	620	1	NSYPLA1276G	NSYPLA1276TG	NSYPLAZ1276G
1250	1000	320	2	NSYPLA12103G	NSYPLA12103TG	NSYPLAZ12103G
1250	1000	420	2	NSYPLA12104G	NSYPLA12104TG	NSYPLAZ12104G
1250	1250	320	2	NSYPLA12123G	NSYPLA12123TG	NSYPLAZ12123G
1250	1250	420	2	NSYPLA12124G	NSYPLA12124TG	NSYPLAZ12124G
1250	1250	620	2	NSYPLA12126G	NSYPLA12126TG	NSYPLAZ12126G
1500	500	320	1	NSYPLA1553G	NSYPLA1553TG	NSYPLAZ1553G
1500	500	420	1	NSYPLA1554G	NSYPLA1554TG	NSYPLAZ1554G
1500	750	320	1	NSYPLA1573G	NSYPLA1573TG	NSYPLAZ1573G
1500	750	420	1	NSYPLA1574G	NSYPLA1574TG	NSYPLAZ1574G
1500	750	620	1	NSYPLA1576G	NSYPLA1576TG	NSYPLAZ1576G
1500	1000	320	2	NSYPLA15103G	NSYPLA15103TG	NSYPLAZ15103G
1500	1000	420	2	NSYPLA15104G	NSYPLA15104TG	NSYPLAZ15104G
1500	1250	320	2	NSYPLA15123G	NSYPLA15123TG	NSYPLAZ15123G
1500	1250	420	2	NSYPLA15124G	NSYPLA15124TG	NSYPLAZ15124G
1500	1250	620	2	NSYPLA15126G	NSYPLA15126TG	NSYPLAZ15126G
2000	750	420	2*	NSYPLA2074G	NSYPLA2074TG	NSYPLAZ2074G

*Two doors in vertical.

**Recommended to protect against the direct sun radiation.

PHD - Applicative and customised solutions:
See the Polyester Heavy Duty offer in the applicative and customised solutions, page 416.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Polyester floor-standing enclosures

Indoor and Outdoor:
For outdoor use, must install a canopy.

Enclosures with ventilated canopy, IP44		Enclosures with open bottom part and ventilated canopy, IP44	
	PLAT		PLAZT

Dimensions (mm)					
Height	Width	Depth	N° of doors	Plain	Plain
500	500	320	1	**NSYPLAT553G**	**NSYPLAZT553G**
500	500	420	1	**NSYPLAT554G**	**NSYPLAZT554G**
500	750	320	1	**NSYPLAT573G**	**NSYPLAZT573G**
500	750	420	1	**NSYPLAT574G**	**NSYPLAZT574G**
500	1000	320	2	**NSYPLAT5103G**	**NSYPLAZT5103G**
500	1000	420	2	**NSYPLAT5104G**	**NSYPLAZT5104G**
500	1250	320	2	**NSYPLAT5123G**	**NSYPLAZT5123G**
500	1250	420	2	**NSYPLAT5124G**	**NSYPLAZT5124G**
750	500	320	1	**NSYPLAT753G**	**NSYPLAZT753G**
750	500	420	1	**NSYPLAT754G**	**NSYPLAZT754G**
750	750	320	1	**NSYPLAT773G**	**NSYPLAZT773G**
750	750	420	1	**NSYPLAT774G**	**NSYPLAZT774G**
750	750	620	1	**NSYPLAT776G**	**NSYPLAZT776G**
750	1000	320	2	**NSYPLAT7103G**	**NSYPLAZT7103G**
750	1000	420	2	**NSYPLAT7104G**	**NSYPLAZT7104G**
750	1250	320	2	**NSYPLAT7123G**	**NSYPLAZT7123G**
750	1250	420	2	**NSYPLAT7124G**	**NSYPLAZT7124G**
1000	500	320	1	**NSYPLAT1053G**	**NSYPLAZT1053G**
1000	500	420	1	**NSYPLAT1054G**	**NSYPLAZT1054G**
1000	750	320	1	**NSYPLAT1073G**	**NSYPLAZT1073G**
1000	750	420	1	**NSYPLAT1074G**	**NSYPLAZT1074G**
1000	1000	320	2	**NSYPLAT10103G**	**NSYPLAZT10103G**
1000	1000	420	2	**NSYPLAT10104G**	**NSYPLAZT10104G**
1000	1250	320	2	**NSYPLAT10123G**	**NSYPLAZT10123G**
1000	1250	420	2	**NSYPLAT10124G**	**NSYPLAZT10124G**
1250	500	320	1	**NSYPLAT1253G**	**NSYPLAZT1253G**
1250	500	420	1	**NSYPLAT1254G**	**NSYPLAZT1254G**
1250	750	320	1	**NSYPLAT1273G**	**NSYPLAZT1273G**
1250	750	420	1	**NSYPLAT1274G**	**NSYPLAZT1274G**
1250	750	620	1	**NSYPLAT1276G**	**NSYPLAZT1276G**
1250	1000	320	2	**NSYPLAT12103G**	**NSYPLAZT12103G**
1250	1000	420	2	**NSYPLAT12104G**	**NSYPLAZT12104G**
1250	1250	320	2	**NSYPLAT12123G**	**NSYPLAZT12123G**
1250	1250	420	2	**NSYPLAT12124G**	**NSYPLAZT12124G**
1250	1250	620	2	**NSYPLAT12126G**	**NSYPLAZT12126G**
1500	500	320	1	**NSYPLAT1553G**	**NSYPLAZT1553G**
1500	500	420	1	**NSYPLAT1554G**	**NSYPLAZT1554G**
1500	750	320	1	**NSYPLAT1573G**	**NSYPLAZT1573G**
1500	750	420	1	**NSYPLAT1574G**	**NSYPLAZT1574G**
1500	750	620	1	**NSYPLAT1576G**	**NSYPLAZT1576G**
1500	1000	320	2	**NSYPLAT15103G**	**NSYPLAZT15103G**
1500	1000	420	2	**NSYPLAT15104G**	**NSYPLAZT15104G**
1500	1250	320	2	**NSYPLAT15123G**	**NSYPLAZT15123G**
1500	1250	420	2	**NSYPLAT15124G**	**NSYPLAZT15124G**
1500	1250	620	2	**NSYPLAT15126G**	**NSYPLAZT15126G**
2000	750	420	Two doors in vertical	**NSYPLAT2074G**	**NSYPLAZT2074G**

PHD - Applicative and customised solutions:
See the Polyester Heavy Duty offer in the applicative and customised solutions, page 416.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Polyester floor-standing enclosures

Horizontal coupling kits, 15 mm, join two enclosures mounted on ZA plinths

- For coupling two enclosures side by side.
- Coupling frame kit: Made up of a coupling kit and the fixings required for installation.
- Trim kit: Made up of two frames for aesthetic fitting of the two coupled enclosures
- Coupling kit widths: 15 mm - Join two enclosures mounted on ZA plinths
- Ingress protection rating: IP55 at the coupling point

Note:
Not valid for coupling two enclosures using ZZ or ZH type plinth.



NSYMUPLA53G

Characteristics	Depth (mm)	Height (mm)	References
Coupling frame kit 15 mm	320	500	**NSYMUPLA53G**
Coupling frame kit 15 mm	320	750	**NSYMUPLA73G**
Coupling frame kit 15 mm	320	1000	**NSYMUPLA103G**
Coupling frame kit 15 mm	320	1250	**NSYMUPLA123G**
Coupling frame kit 15 mm	320	1500	**NSYMUPLA153G**
Coupling frame kit 15 mm	420	500	**NSYMUPLA54G**
Coupling frame kit 15 mm	420	750	**NSYMUPLA74G**
Coupling frame kit 15 mm	420	1000	**NSYMUPLA104G**
Coupling frame kit 15 mm	420	1250	**NSYMUPLA124G**
Coupling frame kit 15 mm	420	1500	**NSYMUPLA154G**
Coupling frame kit 15 mm	420	2000	**NSYMUPLA204G**
Coupling frame kit 15 mm	620	750	**NSYMUPLA76G**
Coupling frame kit 15 mm	620	1250	**NSYMUPLA126G**
Coupling frame kit 15 mm	620	1500	**NSYMUPLA156G**
Trim kit for enclosure without canopy	320	-	**NSYSUPLA3G**
Trim kit for enclosure witht canopy	320	-	**NSYSUPLA3TG**
Trim kit for enclosure without canopy	420	-	**NSYSUPLA4G**
Trim kit for enclosure with canopy	420	-	**NSYSUPLA4TG**

Horizontal coupling kits 35 mm, join two enclosures mounted on ZZ or ZH plinths

- For coupling two enclosures side by side.
- Coupling frame kit: Made up of a coupling kit and the fixings required for installation.
- Trim kit: Made up of two frames for aesthetic fitting of the two coupled enclosures
- Coupling kit widths: 35 mm - Join two enclosures mounted on ZZ or ZH plinths
- Ingress protection rating: IP55 at the coupling point

Note:
Not valid for coupling two enclosures using ZA plinths



NSYMUPLA53W

Characteristics	Depth (mm)	Height (mm)	References
Coupling frame kit 35 mm	320	500	**NSYMUPLA53W**
Coupling frame kit 35 mm	320	750	**NSYMUPLA73W**
Coupling frame kit 35 mm	320	1000	**NSYMUPLA103W**
Coupling frame kit 35 mm	320	1250	**NSYMUPLA123W**
Coupling frame kit 35 mm	320	1500	**NSYMUPLA153W**
Coupling frame kit 35 mm	420	500	**NSYMUPLA54W**
Coupling frame kit 35 mm	420	750	**NSYMUPLA74W**
Coupling frame kit 35 mm	420	1000	**NSYMUPLA104W**
Coupling frame kit 35 mm	420	1250	**NSYMUPLA124W**
Coupling frame kit 35 mm	420	1500	**NSYMUPLA154W**
Coupling frame kit 35 mm	420	2000	**NSYMUPLA204W**
Coupling frame kit 35 mm	620	750	**NSYMUPLA76W**
Coupling frame kit 35 mm	620	1250	**NSYMUPLA126W**
Coupling frame kit 35 mm	620	1500	**NSYMUPLA156W**

Vertical coupling kit

- For coupling two enclosures on top of one another.
- Kit made up of 3.5 m of adhesive seal and the fixings required for mounting.
- Ingress protection rating: IP55 at the coupling point



NSYUVPLA

Characteristics	References
Vertical coupling kit	**NSYUVPLA**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Polyester floor-standing enclosures

Canopy

- It can be installed in all enclosure models.
- High resistance to impacts, temperature and bad weather.
- Increases the height (A) of the enclosure by 38 mm, without modifying its width or depth.
- Material: Polyester reinforced with fibreglass
- Colour: RAL 7035 grey
- Installation: Essential for outdoor use



Supply:
Delivered with the fixings required for installation

NSYTJPLA53G

Characteristics	Width (mm)	Depth (mm)	References
Canopy	500	320	**NSYTJPLA53G**
Canopy	500	420	**NSYTJPLA54G**
Canopy	750	320	**NSYTJPLA73G**
Canopy	750	420	**NSYTJPLA74G**
Canopy	750	620	**NSYTJPLA76G**
Canopy	1000	320	**NSYTJPLA103G**
Canopy	1000	420	**NSYTJPLA104G**
Canopy	1250	320	**NSYTJPLA123G**
Canopy	1250	420	**NSYTJPLA124G**
Canopy	1250	620	**NSYTJPLA126G**

Wall fixing lugs

NSYFMPLA

Drilling positions and marks inside the side panels.
- Material: Carbon steel with passivated zinc-coated
- Maximum load: 180 kg including weight of enclosure

Fixing: Fixing on the sides by four or six lugs in horizontal position
(six lugs for enclosures with height ≥ 1000 mm)
10 mm fixing distance on the rear of the enclosure plane



Supply:
Set of six lugs and fixings

Characteristics	References
Wall fixing lugs	**NSYFMPLA**

PLAZ PLAZT Cable entry plate



- Easy drilling in specific customised version.
- Incompatibility with: Adapter plates, step slides, internal door and chassis for modular distribution.
- Material: Polyester reinforced with fibreglass
- Thickness: 4 mm

Supply:
Delivered with the fixings required for installation

NSYECPLAZ53G

Characteristics	Width (mm)	Depth (mm)	References
Cable entry plate	500	320	**NSYECPLAZ53G**
Cable entry plate	500	420	**NSYECPLAZ54G**
Cable entry plate	750	320	**NSYECPLAZ73G**
Cable entry plate	750	420	**NSYECPLAZ74G**
Cable entry plate	750	620	**NSYECPLAZ76G**
Cable entry plate	1000	320	**NSYECPLAZ103G**
Cable entry plate	1000	420	**NSYECPLAZ104G**
Cable entry plate	1250	320	**NSYECPLAZ123G**
Cable entry plate	1250	420	**NSYECPLAZ124G**
Cable entry plate	1250	620	**NSYECPLAZ126G**

Renovation and anti graffiti paint

Supply: NSYAUPG1G
The 1 kg reference includes one pot with 800 g of base paint and 200 g of hardener
(It is enough to paint a surface of around 5 m²)

Supply: NSYAUPG5G
The 5 kg reference includes one pot with 4 kg of base paint and 1 kg of hardener
(It is enough to paint a surface of around 25 m²)

- Paint kit with two components (base 80 % + hardener 20 %)
- Specially designed for polyester enclosures, for their renovation and/or as prevention to allow easy removal of graffiti.
- Colour: RAL 7035 grey

NSYAUPG1G

Characteristics	References
Renovation and anti graffiti paint	**NSYAUPG1G**
Renovation and anti graffiti paint	**NSYAUPG5G**

Supply:
1 kg

- Solvent bottles to be used as a paint thinner or to clean brushes.

Characteristics	References
Renovation and anti graffiti paint solvent	**NSYAUPGS**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Polyester floor-standing enclosures

Characteristics	ZA plinths
	• The frontal parts of the plinth (front and rear) have two stainless steel screws protected by a plastic cap; these screws, which can be accessed from the outside, make it possible (using an Allen key) to open and remove the frontal parts for easier cable installation. • In stacked position, the bottom plinth can be partially buried. • It is provided with one or two reinforcement cross rails, adjustable to adapt to the position of the cables.
Material	Polyester reinforced with fibreglass
Colour	RAL 7035 grey
Ingress protection rating	IP44
Mechanical protection rating	IK10
Fixing	Four floor attachment points; The symmetry of the parts helps prevent incorrect assembly
Supply	The reference of the plinth contains all the accessories required for attaching the enclosure to the plinth and for stacking two plinths

For floor-standing enclosure			Plinth		Cable gland area		Height 200 mm
Width (mm)	Depth (mm)	References	Width (mm)	Depth (mm)	Width (mm)	Depth (mm)	References
500	320	**NSYPLA(T)●53G**	494	250	360	205	**NSYZA253G**
750	320	**NSYPLA(T)●73G**	744	250	610	205	**NSYZA273G**
1000	320	**NSYPLA(T)●103G**	994	250	860	205	**NSYZA2103G**
1250	320	**NSYPLA(T)●123G**	1244	250	1100	205	**NSYZA2123G**
500	420	**NSYPLA(T)●54G**	494	350	360	305	**NSYZA254G**
750	420	**NSYPLA(T)●74G**	744	350	610	305	**NSYZA274G**
1000	420	**NSYPLA(T)●104G**	994	350	860	305	**NSYZA2104G**
1250	420	**NSYPLA(T)●124G**	1244	350	1110	305	**NSYZA2124G**
750	620	**NSYPLA(T)●76G**	744	550	610	505	**NSYZA276G**
1250	620	**NSYPLA(T)●126G**	1244	550	1110	505	**NSYZA2126G**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Polyester floor-standing enclosures

Cable supporting cross rail

NSYAC320

- Description: The lateral sides of the plinth are provided with bosses for attaching cross rails with cut-out profiles, for supporting cables.

Supply:
the reference of the cross rail includes all the elements required for assembly.

Characteristics	For plinth	For plinth	References
Cable supporting cross rail	NSYZA253G	NSYZA254G	**NSYAC320**
Cable supporting cross rail	NSYZA273G	NSYZA274G	**NSYAC560**
Cable supporting cross rail	NSYZA2103G	NSYZA2104G	**NSYAC840**
Cable supporting cross rail	NSYZA2123G	NSYZA2124G	**NSYAC1080**

Kit for IP54

NSYAEPZA

- Description: Makes it possible to obtain IP 54 for the plinth and the plinth enclosure connection..
- Standard: IEC 61439-1

Characteristics	References
Kit for IP54	**NSYAEPZA**

Feet for partially buried installation

NSYAEBFZ

Description: Allows the partially buried installation of plinths before completion of the floor. The plinths are attached by four feet with a standard length of 750 mm. Possibility of horizontal adjustment of the plinth.

Supply:
the kit is made up of four feet and fixings.

Characteristics	References
Feet for partially buried installation	**NSYAEBFZ**

N plinths

NSYZNPLA53G

Designed to be installed under the closed bottom enclosures (version PLA or PLAT).

- Material: Polyester reinforced with fibreglass
- Colour: RAL 7035 grey
- Height 60 mm

Supply:
Delivered with fixings required for installation

Characteristics	References
N plinths	**NSYZNPLA53G**
N plinths	**NSYZNPLA73G**
N plinths	**NSYZNPLA103G**
N plinths	**NSYZNPLA123G**
N plinths	**NSYZNPLA54G**
N plinths	**NSYZNPLA74G**
N plinths	**NSYZNPLA104G**
N plinths	**NSYZNPLA124G**

Connectors between plinths

Description: Designed to allow the adaptation of a closed bottom enclosure
+ N plinth on a H-type partially buried plinth.





Supply:
two parts for adapting the centre-to-centre distances.

NSYAZ3PLA

Characteristics	For floor-standing enclosure Depth (mm)	References
Linking parts for N plinth on 320 mm H plinth	320	**NSYAZ3PLA**
Linking parts for N plinth on 420 mm H plinth	420	**NSYAZ4PLA**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Polyester floor-standing enclosures

(1) For enclosures using ZZ or ZH type plinths the coupling kit to use is the **NSYMUPLA●●●W**.

Characteristics	ZZ plinths (1)
	• The frontal parts (front and rear) are removed from the inside. Removing them makes it easier to install the cables. • The 500 mm plinth can be partially buried. • It is provided with one or two reinforcement cross rails, adjustable to adapt to the position of the cables.
Material	Polyester reinforced with fibreglass
Colour	RAL 7035 grey
Ingress protection rating	IP44
Mechanical protection rating	IK10
Fixing	Four floor attachment points; The symmetry of the parts helps prevent incorrect assembly
Supply	The reference of the plinth contains all the accessories required for attaching the enclosure to the plinth

For floor-standing enclosure			Plinth		Cable gland area		Height 200 mm	Height 500 mm
Width (mm) (B)	Depth (mm) (C)	References	Width (mm)	Depth (mm)	Width (mm)	Depth (mm)	References	References
500	320	**NSYPLAZ(T)●53G**	535	310	419	252	**NSYZZ253G**	**NSYZZ553G**
750	320	**NSYPLAZ(T)●73G**	785	310	669	252	**NSYZZ273G**	**NSYZZ573G**
1000	320	**NSYPLAZ(T)●103G**	1035	310	919	252	**NSYZZ2103G**	**NSYZZ5103G**
1250	320	**NSYPLAZ(T)●123G**	1285	310	1169	252	**NSYZZ2123G**	**NSYZZ5123G**
500	420	**NSYPLAZ(T)●54G**	535	410	419	352	**NSYZZ254G**	**NSYZZ554G**
750	420	**NSYPLAZ(T)●74G**	785	410	669	352	**NSYZZ274G**	**NSYZZ574G**
1000	420	**NSYPLAZ(T)●104G**	1035	410	919	352	**NSYZZ2104G**	**NSYZZ5104G**
1250	420	**NSYPLAZ(T)●124G**	1285	410	1169	352	**NSYZZ2124G**	**NSYZZ5124G**
750	620	**NSYPLAZ(T)●76G**	785	610	669	552	**NSYZZ276G**	-
1250	620	**NSYPLAZ(T)●126G**	1285	610	1169	552	**NSYZZ2126G**	-

9

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Polyester floor-standing enclosures

Cable supporting cross rail


NSYAC360

- Description: The lateral sides of the plinths are provided with bosses for attaching cross rails with cut-out profiles, for supporting cables.

Supply:
the reference of the cross rail includes all the elements required for assembly

Characteristics	For plinth	For plinth	For plinth	For plinth	References
Cable supporting cross rail	NSYZZ253G	NSYZZ254G	NSYZZ553G	NSYZZ554G	**NSYAC360**
Cable supporting cross rail	NSYZZ273G	NSYZZ274G	NSYZZ573G	NSYZZ574G	**NSYAC600**
Cable supporting cross rail	NSYZZ2103G	NSYZZ2104G	NSYZZ5103G	NSYZZ5104G	**NSYAC840**
Cable supporting cross rail	NSYZZ2123G	NSYZZ2124G	NSYZZ5123G	NSYZZ5124G	**NSYAC1120**

Outside opening kit

NSYAELZ

- Description: The 200 mm front part of the 200 and 500 mm plinths can be opened from the outside, after installing a kit made up of two locks with double bar insert.

Characteristics	References
Outside opening kit	**NSYAELZ**

Buriable H plinths

NSYZHPLA53G

- Front panel with a height of 170 mm, retractable, providing easy access to the inside.
- Fixed front panel with a height of 305 mm, corresponding to the finished floor height area.
- The height above the floor after built-in varies between 200 and 500 mm.
- A metal rail helps to fix the entry cables.
- Lateral uprights with pre-knock-out auxiliary output with Ø Pg 36 (48 mm).
- A pre-knock-out area is provided at the bottom of the lateral uprights for cable entry, if necessary.
- Material: Polyester reinforced with fibreglass
- Colour: RAL 7035 grey

Supply:
Delivered with the fixings required for installation

Note:
Dimensions, see page 232

NSYZHPLA53G

Characteristics	References
Buriable H plinths	**NSYZHPLA53G**
Buriable H plinths	**NSYZHPLA73G**
Buriable H plinths	**NSYZHPLA103G**
Buriable H plinths	**NSYZHPLA123G**
Buriable H plinths	**NSYZHPLA54G**
Buriable H plinths	**NSYZHPLA74G**
Buriable H plinths	**NSYZHPLA104G**
Buriable H plinths	**NSYZHPLA124G**

Floor-standing frame

- Frame for direct fixing on the floor for installing open bottom enclosures (version PLAZ or PLAZT).
- Material: Passivated zinc-coated steel

Supply:
Delivered with fixings required for installation

Note:
Dimensions, see page 232

NSYMFPLAZ53

Characteristics	References
Floor-standing frame	**NSYMFPLAZ53**
Floor-standing frame	**NSYMFPLAZ73**
Floor-standing frame	**NSYMFPLAZ103**
Floor-standing frame	**NSYMFPLAZ123**
Floor-standing frame	**NSYMFPLAZ54**
Floor-standing frame	**NSYMFPLAZ74**
Floor-standing frame	**NSYMFPLAZ104**
Floor-standing frame	**NSYMFPLAZ124**
Floor-standing frame	**NSYMFPLAZ76**
Floor-standing frame	**NSYMFPLAZ126**

Floor-fixing studs

NSYFSPLAZ

- Description: Set of four threaded parts and fixings, for fixing the enclosures on concrete plinths.

Characteristics	References
Floor-fixing studs	**NSYFSPLAZ**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Polyester floor-standing enclosures

Internal door



- Designed for direct installation in enclosures with sealed bottom part. In the enclosures with the bottom part open, installation can be
- performed by ordering the necessary adapter plates, ref. **NSYPTZ●●●**.
- Two depthwise mounting positions (two positions for depthwise installation) according to the chosen M8 impressions, on the top and bottom parts of the enclosure, for fixing.
- Lock with 5 mm double bar inserts.
- Incompatibility with: Modular distribution chassis, 19" chassis, cable entry plate and door retainer, ref. **NSYRETPLAU**.
- Material: Aluminium
- Colour: RAL 7035 grey

Supply:
Delivered with M8 brass inserts and fixings

Note:
Dimensions, see page 232

Dimensions		Internal door dimensions		
Height (mm)	Width (mm)	D (mm)	E (mm)	References
500	500	398	398	**NSYPAPLA55G**
500	750	398	648	**NSYPAPLA57G**
500	1000	398	796 (2 x 398)	2 x **NSYPAPLA55G**
500	1250	398	1046 (398 + 648)	**NSYPAPLA55G** + **NSYPAPLA57G**
750	500	648	398	**NSYPAPLA75G**
750	750	648	648	**NSYPAPLA77G**
750	1000	648	796 (2 x 398)	2 x **NSYPAPLA75G**
750	1250	648	1046 (398 + 648)	**NSYPAPLA75G** + **NSYPAPLA77G**
1000	500	898	398	**NSYPAPLA105G**
1000	750	898	648	**NSYPAPLA107G**
1000	1000	898	796 (2 x 398)	2 x **NSYPAPLA105G**
1000	1250	898	1046 (398 + 648)	**NSYPAPLA105G** + **NSYPAPLA107G**
1250	500	1148	398	**NSYPAPLA125G**
1250	750	1148	648	**NSYPAPLA127G**
1250	1000	1148	796 (2 x 398)	2 x **NSYPAPLA125G**
1250	1250	1148	1046 (398 + 648)	**NSYPAPLA125G** + **NSYPAPLA127G**
1500	500	1398	398	**NSYPAPLA155G**
1500	750	1398	648	**NSYPAPLA157G**
1500	1000	1398	796 (2 x 398)	2 x **NSYPAPLA155G**
1500	1250	1398	1046 (398 + 648)	**NSYPAPLA155G** + **NSYPAPLA157G**

Door retainer

Supply:
Delivered with the fixings required for installation

Note:
ref. **NSYRETPLAU** is incompatible with internal doors, modular distribution chassis, step slides, adapter plates and cable entry plates. In the event of incompatibility, use ref. **NSYRETPLA**.

- Designed to adapt directly to the enclosure
- Can be installed on a door opening to the left or right indistinctly
- Material: Galvanised steel

Characteristics	References
Door retainer, PLA, PLAZ, PLAT versions, opening to 110°	**NSYRETPLA**
Door retainer, PLA, PLAZ, PLAT, PLAZT versions*, with 2 positions, 90° and 120°	**NSYRETPLAU**

NSYRETPLA

NSYRETPLAU

Door switch

NSYSNLPLA

- NC + NO switch.
- Incompatible with the rear door and modular distribution chassis

Supply:
Switch, fixing bracket and fixings

Characteristics	References
Door switch	**NSYSNLPLA**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Polyester floor-standing enclosures

Lock with handle

- Ergonomic locking system with pivoting handle installed as standard on enclosures with ventilated canopy and/or open bottom part, with a 5 mm double bar insert block.
- Material: PA6
- Colour: RAL 7035 grey



1 Block mit Formeinsatz.
2 Block mit voll Zylinder.
3 Block mit halb Zylinder.

Options for changing the form-insert blocks


NSYINS61

Characteristics	References
6 mm square insert	**NSYINS61**
7 mm square insert	**NSYINS71**
8 mm square insert	**NSYINS81**
6.5 mm triangular insert	**NSYINT61**
8 mm triangular insert	**NSYINT81**
Push-button	**NSYTSPLA**
Double bar	**NSYINDB51**

Options for changing the blocks with cylindrical barrels


NSYIN405E1

Characteristics	References
405E key lock	**NSYIN405E1**
421E key lock	**NSYIN421E1**
455 key lock	**NSYIN4551**
1242E key lock	**NSYIN1242E1**
1332E key lock	**NSYIN1332E1**
2124E key lock	**NSYIN2124E1**
2131A key lock	**NSYIN2131A1**
2132A key lock	**NSYIN2132A1**
2331A key lock	**NSYIN2331A1**
2433A key lock	**NSYIN2433A1**
2452E key lock	**NSYIN2452E1**
3113A key lock	**NSYIN3113A1**
3122E key lock	**NSYIN3122E1**
3123A key lock	**NSYIN3123A1**
3131A1 key lock	**NSYIN3131A1**
3133A key lock	**NSYIN3133A1**
3422E key lock	**NSYIN3422E1**
3432E key lock	**NSYIN3432E1**
6101 key lock	**NSYIN6101**

Options for changing the blocks with semi-cylindrical barrels


NSYIN1242E2

Characteristics	References
Spacial SF/SM 1242E key lock	**NSYIN1242E2**
Spacial SF/SM Adapter for DIN cylinder	**NSYINDIN2**
Spacial SF/SM JIS key lock	**NSYINKJIS2**
Spacial SF/SM Reinforced key lock	**NSYINKR2**
Spacial SF/SM FAC key lock	**NSYINKFAC2**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Options for changing the handle lock

- Changing the handle for a handle including a padlocking device (Ø 10 mm) allowing the handle to be locked. The handle is delivered without barrel or insert block.

NSYCBCMPLAG

Characteristics	References
Options for changing the handle lock	**NSYCBCMPLAG**

Options for changing the handle lock

- Spare handle lock without barrel or insert blocks.
  The insert or barrel are to be chosen from the option table.

NSYCBCMPLAG

Characteristics	References
Options for changing the handle lock	**NSYEBMPLAG**

Type of lock	Insert references	Key references
5 mm double bar ⊜	NSYTDB5PLA	**NSYLDB5**
6 mm □	NSYTC6CRN	**NSYLC7**
7 mm □	NSYTC7CRN	**NSYLC7**
8 mm □	NSYTC8CRN	**NSYLC8**
6.5 mm ▲	NSYTT6CRN	**NSYLT8**
7 mm ▲	NSYTT7CRN	**NSYLT8**
8 mm ▲	NSYTT8CRN	**NSYLT8**

9

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Polyester floor-standing enclosures

19'' fixed chassis



Installation: For heights from 750 to 1500 mm, the installation requires ordering one batch of two matching uprights. If a chassis is installed in an enclosure with a greater height, it is necessary to use the suitable uprights for the size of the enclosure

- Very sturdy 19" metal chassis, designed for installation in enclosures with a width of 750 and 1250 mm.
  In the 1250 mm enclosure, the chassis is installed in the 750 mm part with an intermediate support, ref. **NSYSBPLA**.
- These chassis can be used as partial mounting plates in enclosures with higherthan nominal height.
- Incompatible with the internal doors and the step slides.
- Fixed chassis made up of two uprights with fixings
- Material: Galvanised steel
- Finish: Epoxy polyester paint
- Colour: RAL 7035 grey
- Maximum load: 3 kg per unit

Note:
Dimensions, see page 235

NSYBRF8PLAG

Characteristics	Height (mm)	Width (mm)	# of units	References
19'' fixed chassis	500	750	8	**NSYBRF8PLAG**
19'' fixed chassis	750	750	12	**NSYBRF12PLAG**
19'' fixed chassis	1000	750	17	**NSYBRF17PLAG**
19'' fixed chassis	1250	750	21	**NSYBRF21PLAG**
19'' fixed chassis	1500	750	26	**NSYBRF26PLAG**
19'' fixed chassis	2000	750	2 x 17	2 x **NSYBRF17PLAG** + **NSYPTZ4**
Batch of two uprights	750	750	12	**NSYSPLA75**
Batch of two uprights	1000	750	17	**NSYSPLA100**
Batch of two uprights	1250	750	21	**NSYSPLA125**
Batch of two uprights	1500	750	26	**NSYSPLA150***
Batch of two uprights	2000	750	2 x 17	2 x **NSYSPLA100**

* Not compatible with **NSYCAAPVHD**.

19'' swing chassis



Installation: For heights from 750 to 1500 mm, the installation requires ordering one batch of two matching uprights. If a chassis is installed in an enclosure with a greater height, it is necessary to use the suitable uprights for the size of the enclosure

- Very sturdy 19" metal chassis, designed for installation in enclosures with a width of 750 and 1250 mm.
  In the 1250 mm enclosure, the chassis is installed in the 750 mm part with an intermediate support, ref. **NSYSBPLA**.
- These chassis can be used as partial mounting plates in enclosures with higherthan nominal height.
- Incompatible with the internal doors and the step slides.
- Swing chassis opening to 120° with 5 mm double bar key lock.
- Material: Galvanised steel
- Finish: Swing part: Epoxy polyester paint
- Colour: RAL 7035 grey (swing part only)
- Maximum load: 3 kg per unit

Note:
Dimensions, see page 235

NSYBRP7PLAG

Characteristics	Height (mm)	Width (mm)	# of units	References
19'' swing chassis	500	750	7	**NSYBRP7PLAG**
19'' swing chassis	750	750	11	**NSYBRP11PLAG**
19'' swing chassis	1000	750	16	**NSYBRP16PLAG**
19'' swing chassis	1250	750	20	**NSYBRP20PLAG**
19'' swing chassis	1500	750	25	**NSYBRP25PLAG**
19'' swing chassis	2000	750	2 x 16	2 x **NSYBRP16PLAG**
Batch of two uprights	750	750	11	**NSYSPLA75**
Batch of two uprights	1000	750	16	**NSYSPLA100**
Batch of two uprights	1250	750	20	**NSYSPLA125**
Batch of two uprights	1500	750	25	**NSYSPLA150**
Batch of two uprights	2000	750	2 x 16	2 x **NSYSPLA100**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Polyester floor-standing enclosures

Note:
Dimensions, see page 233

	Metallic mounting plate		Insulating mounting plate	
				
Characteristics	**Plain mounting plate**	**Telequick mounting plate**		
	• Direct installation on M8 inserts at the rear of the enclosure or on step slides for depth adjustment (see page 224). The enclosures with height of ≥ 1000 mm have intermediate impressions for installing mounting plates of a lesser height (M8 inserts, ref. **NSYTEX8**, to be ordered separately). • In the two door enclosures, it is possible to install one complete mounting plate or two individual mounting plates.	• Grille with 11 x 26 mm drill holes, with a step of 15 x 30 mm, for direct installation, with clip nuts, of all the devices with fixing at 2, 3 or 4 points, by screws with diameters of 3, 4, 5 or 6 mm. • Direct installation on M8 inserts at the rear of the enclosure or on step slides for depth adjustment (see page 224). The enclosures with height of ≥ 1000 mm have intermediate impressions for installing mounting plates of a lesser height (M8 inserts, ref. **NSYTEX8**, to be ordered separately).	• Direct installation on M8 inserts at the rear of the enclosure or on step slides for depth adjustment (see page 224). The enclosures with height of ≥ 1000 mm have intermediate impressions for installing mounting plates of a lesser height (M8 inserts, ref. **NSYTEX8**, to be ordered separately). • In the two door enclosures, it is possible to install one complete mounting plate or two individual mounting plates.	
Material	Galvanised sheet steel	Galvanised steel	Bakelite	Polyester
Finish	–	–	–	–
Colour	–	–	–	–
Thickness	2.5 mm	–	4 mm	• 4 mm up to 700 mm height • 5 mm from 800 mm height
Maximum load	150 kg/m²	150 kg/m²	100 kg/m²	100 kg/m²
Supply	One mounting plate	One mounting plate	One mounting plate	One mounting plate

Dimensions					Dimensions					
Height (A) (mm)	Width (B) (mm)	H (mm)	Surface (dm²)	References	E (mm)	D (mm)	Surface (dm²)	References	References	References
500	500	-	14	**NSYPMM55**	350	350	13	**NSYPMR55**	**NSYPMB55**	**NSYPMA55**
500	750	-	24	**NSYPMM75**	350	600	23	**NSYPMR57**	**NSYPMB75**	**NSYPMA75**
500	1000	437.5	32	**NSYPMM510**	350	2 x 350	26	2 x **NSYPMR55**	**NSYPMB510**	**NSYPMA510**
500	1250	-	38	**NSYPMM55** + **NSYPMM75**	350	350 + 600	36	**NSYPMR55** + **NSYPMR57**	**NSYPMB55** + **NSYPMB75**	**NSYPMA55** + **NSYPMA75**
750	500	-	24	**NSYPMM75**	600	350	23	**NSYPMR75**	**NSYPMB75**	**NSYPMA75**
750	750	-	40	**NSYPMM77**	600	600	38	**NSYPMR77**	**NSYPMB77**	**NSYPMA77**
750	1000	437.5	54	**NSYPMM710**	600	2 x 350	46	2 x **NSYPMR75**	**NSYPMB710**	**NSYPMA710**
750	1250	687.5	70	**NSYPMM712**	600	350 + 600	61	**NSYPMR75** + **NSYPMR77**	**NSYPMB712**	**NSYPMA712**
1000	500	-	33	**NSYPMM105**	850	350	32	**NSYPMR105**	**NSYPMB105**	**NSYPMA105**
1000	750	-	55	**NSYPMM107**	850	600	54	**NSYPMR107**	**NSYPMB107**	**NSYPMA107**
1000	1000	437.5	74	**NSYPMM1010**	850	2 x 350	64	2 x **NSYPMR105**	**NSYPMB1010**	**NSYPMA1010**
1000	1250	687.5	96	**NSYPMM1012**	850	350 + 600	86	**NSYPMR105** + **NSYPMR107**	**NSYPMB1012**	**NSYPMA1012**
1250	500	-	42	**NSYPMM125**	1100	350	42	**NSYPMR125**	**NSYPMB125**	**NSYPMA125**
1250	750	-	70	**NSYPMM127**	1100	600	70	**NSYPMR127**	**NSYPMB127**	**NSYPMA127**
1250	1000	437.5	96	**NSYPMM1210**	1100	2 x 350	84	2 x **NSYPMR125**	**NSYPMB1210**	**NSYPMA1210**
1250	1250	687.5	124	**NSYPMM1212**	1100	350 + 600	112	**NSYPMR125** + **NSYPMR127**	**NSYPMB1212**	**NSYPMA1212**
1500	500	-	51	**NSYPMM155**	1350	350	51	**NSYPMR155**	**NSYPMB155**	-
1500	750	-	85	**NSYPMM157**	1350	600	85	**NSYPMR157**	**NSYPMB157**	-
1500	1000	437.5	118	**NSYPMM1510**	1350	2 x 350	102	2 x **NSYPMR155**	**NSYPMB1510**	-
1500	1250	687.5	152	**NSYPMM1512**	1350	350 + 600	136	**NSYPMR155** + **NSYPMR157**	**NSYPMB1512**	-
2000	750	-	115	**NSYPMM207**	2 x 850	2 x 600	108	2 x **NSYPMR107**	2 x **NSYPMB107**	2 x **NSYPMA107**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

	Side mounting plates			Partial plain mounting plate		Technical uprights		Anti burglary accessory	
									
	• Polyester mounting plates fixed to the sides of the enclosure for additional installations. Installation on the M8 bosses by adding inserts, ref. **NSYTEX8**.			• Direct fixing on the uprights, with the notched sliding nuts or pivoting nuts, see common accessories section.		• Supports for fixing rails, perforated grilles and plain partial mounting plates. • Details in the common accessory section. • Fixing at the rear on the M8 inserts or on the step slides.		• Anti burglary accessory for polyester outdoor Heavy Duty in accordance with ENV 1627-1630:2011 Class II. It keeps the Insulation Class II according to IEC 61439-1:2011.	
	Polyester			Galvanised sheet steel		Zinc-coated steel		Steel with anti-corrosive coating	
	–			–		–		Structured finish, 100 % polyester powder	
	–			–		–		RAL 7035 grey	
	• 4 mm up to 750 mm height • 5 mm from 800 mm height			2.5 mm		2 mm		–	
	100 kg/m²			150 kg/m²					
	Reference by unit. Order by multiples of 2			One mounting plate		Two technical uprights		One anti burglary frame	
	Enclosure depth 320 mm	Enclosure depth 420 mm	Enclosure depth 620 mm	Height 247 mm (H)	Height 397 mm (H)			Depth 420 mm	Depth 620 mm
	References	References	References	References	References	Dimensions (mm)	References	References	References
	NSYPMLA53	**NSYPMLA54**	-	-	-	-	-	-	-
	NSYPMLA53	**NSYPMLA54**	-	**NSYSPMP2575**	-	-	-	-	-
	NSYPMLA53	**NSYPMLA54**	-	**NSYSPMP25100**	**NSYSPMP40100**	-	-	-	-
	NSYPMLA53	**NSYPMLA54**	-	-	-	-	-	-	-
	NSYPMLA73	**NSYPMLA74**	-	-	-	625	**NSYTVR7**	-	-
	NSYPMLA73	**NSYPMLA74**	-	**NSYSPMP2575**	-	625	**NSYTVR7**	**NSYBGN774HD**	**NSYBGN776HD**
	NSYPMLA73	**NSYPMLA74**	-	**NSYSPMP25100**	**NSYSPMP40100**	625	**NSYTVR7**	-	-
	NSYPMLA73	**NSYPMLA74**	-	-	-	625	**NSYTVR7**	-	-
	NSYPMLA103	**NSYPMLA104**	-	-	-	875	**NSYTVR10**	**NSYBGN1054HD**	-
	NSYPMLA103	**NSYPMLA104**	-	**NSYSPMP2575**	-	875	**NSYTVR10**	**NSYBGN1074HD**	-
	NSYPMLA103	**NSYPMLA104**	-	**NSYSPMP25100**	**NSYSPMP40100**	875	**NSYTVR10**	-	-
	NSYPMLA103	**NSYPMLA104**	-	-	-	875	**NSYTVR10**	-	-
	NSYPMLA123	**NSYPMLA124**	**NSYPMLA126**	-	-	1125	**NSYTVR125**	**NSYBGN1254HD**	-
	NSYPMLA123	**NSYPMLA124**	-	**NSYSPMP2575**	-	1125	**NSYTVR125**	**NSYBGN1274HD**	**NSYBGN1276HD**
	NSYPMLA123	**NSYPMLA124**	-	**NSYSPMP25100**	**NSYSPMP40100**	1125	**NSYTVR125**	-	-
	NSYPMLA123	**NSYPMLA124**	-	-	-	1125	**NSYTVR125**	**NSYBGN12124HD**	**NSYBGN12126HD**
	-	-	-	-	-	1375	**NSYTVR15**	-	-
	-	-	-	**NSYSPMP2575**	-	1375	**NSYTVR15**	**NSYBGN1574HD**	**NSYBGN1576HD**
	-	-	-	**NSYSPMP25100**	**NSYSPMP40100**	1375	**NSYTVR15**	-	-
	-	-	-	-	-	1375	**NSYTVR15**	**NSYBGN15124HD**	**NSYBGN15126HD**
	-	2 x **NSYPMLA104**	-	**NSYSPMP2575**	-	1875	2 x **NSYTVR10**	**NSYBGN2074HD**	-
						Note: Enclosures with widths of 1000 and 1250 allow the installation of four uprights to integrate two mounting plates of 500 mm or of 500 and 750 mm.			

9

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Polyester floor-standing enclosures

Modular distribution chassis

- Chassis for modular switchgear, installed directly in the sealed enclosures (PLA version). For installation in enclosures with open bottom part (PLAZ version) it is necessary to use a set of adapter plates (ref. **NSYPTZ●●●**).
- Chassis made up of cover plates on a rigid structure.
- Quick installation without fixings.
- Distance between rail and front panel with adjustable depth from 40 to 85 mm.
- System for identifying electrical circuits supplied.
- Neutral/earth strip: 2 x 16 mm² + 5 x 6 mm² included in the standard offer.
- Incompatibility with: Cable entry plate, internal door, door switch and door retainer (ref. **NSYRETPLAU**).
- Material: Rigid structure: Galvanised steel, Cover plates: Self-extinguishing insulating
- Colour: Cover plates: RAL 7035 grey

Note:
Dimensions, see page 223
Other modular distribution accessories on page 224

Dimensions (mm)		No. of doors	No. of rows	Rows for module	No. of modules 18 mm	No. of plates	References
Height (A)	Width (B)						
750	500	1	4	4	76	-	**NSYDLP76G**
750	500	1	4	3	57	1	**NSYDLP57G**
750	750	1	4	4	132	-	**NSYDLP132G**
750	750	1	4	3	99	1	**NSYDLP99G**
750	1000	2	4 + 4	4 + 4	152	-	2 x **NSYDLP76G**
750	1000	2	4 + 4	3 + 3	114	1 + 1	2 x **NSYDLP57G**
750	1250	2	4 + 4	4 + 4	208	-	**NSYDLP76G** + **NSYDLP132G**
750	1250	2	4 + 4	3 + 3	156	1 + 1	**NSYDLP57G** + **NSYDLP99G**
1000	500	1	6	6	114	-	**NSYDLP114G**
1000	500	1	6	5	95	1	**NSYDLP95G**
1000	750	1	6	6	198	-	**NSYDLP198G**
1000	750	1	6	5	165	1	**NSYDLP165G**
1000	1000	2	6 + 6	6 + 6	228	-	2 x **NSYDLP114G**
1000	1000	2	6 + 6	5 + 5	190	1 + 1	2 x **NSYDLP95G**
1000	1250	2	6 + 6	6 + 6	312	-	**NSYDLP114G** + **NSYDLP198G**
1000	1250	2	6 + 6	5 + 5	260	1 + 1	**NSYDLP95G** + **NSYDLP165G**
1250	500	1	7	7	133	-	**NSYDLP133G**
1250	500	1	7	6	114	1	**NSYDLP114PG**
1250	750	1	7	7	231	-	**NSYDLP231G**
1250	750	1	7	6	198	1	**NSYDLP198PG**
1250	1000	2	7 + 7	7 + 7	266	-	2 x **NSYDLP133G**
1250	1000	2	7 + 7	6 + 6	228	1 + 1	2 x **NSYDLP114PG**
1250	1250	2	7 + 7	7 + 7	364	-	**NSYDLP133G** + **NSYDLP231G**
1250	1250	2	7 + 7	6 + 6	312	1 + 1	**NSYDLP114PG** + **NSYDLP198PG**
1500	500	1	9	9	171	-	**NSYDLP171G**
1500	500	1	9	8	152	1	**NSYDLP152G**
1500	750	1	9	9	297	-	**NSYDLP297G**
1500	750	1	9	8	264	1	**NSYDLP264G**
1500	1000	2	9 + 9	9 + 9	342	-	2 x **NSYDLP171G**
1500	1000	2	9 + 9	8 + 8	304	-	2 x **NSYDLP152G**
1500	1250	2	9 + 9	9 + 9	468	1 + 1	**NSYDLP171G** + **NSYDLP297G**
1500	1250	2	9 + 9	8 + 8	416	1 + 1	**NSYDLP152G** + **NSYDLP264G**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Polyester floor-standing enclosures

Modular distribution chassis

Details of the depth adjustment

Detail from front panel mounting.

Detail from the circuitmarking system.











1 Dimensions of 42 or 67 mm or a pitch of 25 mm, according to the M8 boss chosen for the installation. See details in the enlarged image on the right. In the enclosures with glazed doors, the two dimensions are reduced by 5 mm.

2 C = Depth of the enclosure.

9

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Polyester floor-standing enclosures

Step slides

- Set of four step slides with brackets allowing continuous depth adjustment of the mounting plate, with a pitch of 25 mm.
- Designed for direct installation in the enclosures with sealed bottom part (versions PLA or PLAT).
- In the enclosures with open bottom part (versions PLAZ or PLAZT), installation is made possible by adding the relevant adapter plates.
- Incompatibility with: Internal door, modular distribution chassis, 19" chassis, cableentry plate and door retainer, ref. **NSYRETPLAU**.
- Material: Bracket with steel M8 stud on aluminium rail
- Fixing: Fixing on the top and bottom parts of the enclosure by means of M8 inserts and screws (supplied)

Note:
Dimensions, see page 233

NSYDPLA3

Characteristics	Depth (mm)	No. of doors	References
Step slides	320	1	**NSYDPLA3**
Step slides	320	2	2 x **NSYDPLA3**
Step slides	420	1	**NSYDPLA4**
Step slides	420	2	2 x **NSYDPLA4**
Step slides	620	1	**NSYDPLA6**
Step slides	620	2	2 x **NSYDPLA6**

Adapter plates

- The enclosures with open bottom part (versions PLAZ and PLAZT) require a set of adapter plates for mounting: An internal door, step slides, modular chassis and 19" chassis.
- **NSYPTZ●●●** for one door enclosures
- **NSYPTX●●●** 2P for two door enclosures
- Material: Galvanised steel
- Fixing: Fixing on the bottom part of the enclosure by means of M8 inserts and screws (supplied)

NSYPTZ3

Characteristics	Depth (mm)	No. of doors	References
Adapter plates	320	1	**NSYPTZ3**
Adapter plates	320	2	**NSYPTZ32P**
Adapter plates	420	1	**NSYPTZ4**
Adapter plates	420	2	**NSYPTZ42P**
Adapter plates	620	1	**NSYPTZ6**
Adapter plates	620	2	**NSYPTZ62P**

Additional support

- Set of four additional brackets, to be slid into the step slides, for the installation of an additional mounting plate.

NSYEDPLA

Characteristics	Reference
Additional support	**NSYEDPLA**

Plain cover plate

- Plain cover plate for non modular switchgear protection.
- Can be cutted out according to needs.
- Material: Polystyrene (PS) (for 146 mm high)
- Fiberglass reinforced polyester (for 298 mm high)
- Colour: RAL 7035 grey

Supply:
Order by multiples of 2 (2, 4, 6...)

Note:
Dimensions, page 234

NSYCTL500DLPG

Characteristics	References
Plain cover plate	**NSYCTL500DLPG**
Plain cover plate	**NSYCTL500DLP2**
Plain cover plate	**NSYCTL750DLPG**
Plain cover plate	**NSYCTL750DLP2**

Plain mounting plate

Supply:
Order by multiples of 2 (2, 4, 6...)

- Plate for fixing non modular devices.
- Depth-adjustable fixing on the supports from 40 to 85 mm..
- Material: Galvanised steel 2 mm thick

Note:
Dimensions, page 234

Characteristics	References
Plain mounting plate	**NSYPMP500DLP**
Plain mounting plate	**NSYPMP5002DLP**
Plain mounting plate	**NSYPMP750DLP**
Plain mounting plate	**NSYPMP7502DLP**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Polyester floor-standing enclosures

Support plate

NSYSPLA75

Installation:
It is installed directly on the bottom part of the enclosure.
For the installation of one or several support plates, use two sets of two uprights suitable for the height (to be ordered separately). These uprights offer the option of adjusting the height with a step of 50 mm





- Designed to support assorted equipment or simply to install a separation.
- In the two door enclosures, the installation of the plate or the uprights requires the prior installation of an intermediate support, ref. **NSYSBPLA**, presented beside.
- Material: Galvanised steel

Supply:
Delivered with the fixings required for installation

Height	Depth	Upright No. of adjustments	References
750	320 / 420	2	2 x **NSYSPLA75**
1000	320 / 420	3	2 x **NSYSPLA100**
1250	320 / 420	4	2 x **NSYSPLA125**
1500	–	5	2 x **NSYSPLA150**

Depth (C)	Width (B)	Plate Max. load	References
320	500	60 kg	**NSYBANPLA53**
320	750	60 kg	**NSYBANPLA73**
420	500	50 kg	**NSYBANPLA54**
420	750	50 kg	**NSYBANPLA74**
620	500	50 kg	**NSYBANPLA56***
620	750	50 kg	**NSYBANPLA76**

*Designed for PLA enclosures of 1250 mm width and 620 mm depth.

M8 inserts

NSYTEX8

- To be placed in the bosses moulded on the doors, uprights, rear panels and bottom and top parts, for fixing accessories and assorted devices.
- Material: Brass

Supply:
References by unit. Order by multiples of 8 units (8, 16, 24, etc.)

Characteristics	References
Fixing inserts	**NSYTEX8**

Intermediate support in the two door enclosures

NSYSBPLA

- Required accessory for installing support plates, ref. **NSYBANPLA●●●** or uprights, ref. **NSYSPLA●●●** in the two door enclosures
- Material: Galvanised steel

Supply:
Two support kits

Characteristics	References
Intermediate support in the two door enclosures	**NSYSBPLA**

Recommendation



Intermediate support
Accessory required for installing uprights, ref. **NSYSPLA●●●**.
Only for two door enclosures.
Supply: one (including two supports)
ref. **NSYSBPLA**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Polyester DIN floor-standing enclosure

Floor-standing enclosures designed mainly to accommodate busbars and DIN type three pole LV fuse, for LV public distribution network. The properties of the material and the manufacturing process are identical to those of the Thalassa PLA range.

This range can be configured according to your needs

4 differents services available:

Assemble to order

Mounting of standard accessories

Painting

Machining

Green Premium™

Smart

- Enclosure ref. **NSYPLD8122G** with the central upright fixed to the left door.
- Enclosure ref. **NSYPLD8122CG** with central upright, two doors and two locks.

9

LV public distribution application with DIN three pole fuse blocks: Floor-standing enclosure and plinth

1

2

3

4

Prolonged exposure to UV radiation, wind and rain can cause aesthetics changes in the external surface of the enclosure. Without affecting the technical properties according to IEC 62208. For long exposure applications, it is recommended to use painted enclosures available through the P&S offer.

See page 532 for details or consult our web site www.se.com
The customized solutions Configured or Specific types use existing ranges from Universal Enclosures standard offer as a base for its development. Depending on the modifications made on the enclosures or accessories, they could affect the certification or declarations of conformity existing in the standard ranges. The certifications and declarations of conformity needed for the solution must be defined early in the process as part of the offer specifications.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

According to Reach and RoHs & Halogen free

PLD

Note:
Dimensions, see page 236

Characteristics	Thalassa PLD
	• Floor-standing enclosure with built-in canopy, not overhanging, allowing the coupling of enclosures side-to-side or back-to-back. • Easily removable inner hinges, allowing the door to be reversed and to open to more than 180°. • Doors equipped with impressions allowing the integration of inserts for M6 screws. • Closing by handle with lever and 1242 E cylindrical safety lock. Other locks optionally available (see page 228). • Door floor standing enclosure with central upright fixed to the left door: a single lock on the right door. • M8 boss for installation on the lateral surfaces, inserts ref. **NSYTEX8** not supplied. • M6 bosses in the roof for fixing the lighting or auxiliary equipment, inserts ref. **NSYTEX6** not supplied.
Material	Polyester reinforced with fibreglass
Colour	RAL 7035 grey
Ingress protection rating	IP43 according to IEC 60529
Mechanical protection rating	IK10
Installation	• Outdoor installation: Compliant with IEC 62208 • Direct fixing to the floor or on a plinth, with a height of 900 mm, partially embedded • Fixing points at the rear of the enclosure with: M10 inserts: For installing, direct or on insulators, distribution bars for DIN type three pole fuse holder strips and for a neutral bar M6 inserts: For installing a mounting plate

Height (mm)	Width (mm)	Depth (mm)	Size DIN	No. of doors	No. of locks	References
850	465	320	00	1	1	**NSYPLD8500G**
850	590	320	0	1	1	**NSYPLD860G**
850	785	320	1	1	1	**NSYPLD881G**
850	1115	320	2	2	1	**NSYPLD8122G**

Plinth height 900 mm

NSYZD5300G

- Easy machining.
- Embeddable plinth ready for direct fixing of DIN floor-standing enclosures.
- Retractable top front panel, providing easy access to the inside of the enclosure.
- On the rear panel, housings with M6 inserts, allowing the fixing of the plate, DIN rail or assorted hardware.
- Lateral uprights with knock-out auxiliary outlet with a diameter of Pg 36 (48 mm).
- Internal U- and L-shaped metal uprights, adjustable, for fixing cables.
- A knock-out zone is provided at the bottom of the lateral uprights for cable entry.
- Material: Polyester reinforced with fibreglass
- Colour: RAL 7035 grey

Note:
Dimensions, see page 237

Characteristics	Width (mm)	References	References
Plinth height 900 mm	465	NSYPLD8500G	**NSYZD5300G**
Plinth height 900 mm	590	NSYPLD860G	**NSYZD630G**
Plinth height 900 mm	785	NSYPLD881G	**NSYZD831G**
Plinth height 900 mm	1115	NSYPLD8122G	**NSYZD1232G**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Polyester DIN floor-standing enclosure

Floor-standing supports

NSYSPLD

- Set of two metal supports for fixing the enclosure directly to the floor.
- Material: Galvanised steel
- Colour: RAL 7035 grey

Note:
Dimensions, see page 237

Characteristics	Table of fixing and opening dimensions			
	K	L	M	References
Floor-standing supports	360	320	224	**NSYSPLD**
Floor-standing supports	495	455	224	**NSYSPLD**
Floor-standing supports	690	650	224	**NSYSPLD**
Floor-standing supports	1020	980	224	**NSYSPLD**

Locking options

NSYTDB5ME

NSYTDB5ME

- Standard lock with retractable plastic handle and 1242 E semi-cylindrical safety lock.
- Options: Other optional shape inserts or barrels and keys

Characteristics	Type	Supply	References
Shape insert	5 mm doublebar insert.	Insert with key	**NSYTDB5ME**
Shape insert	Square insert, 6 mm	Insert with key	**NSYTC6ME**
Shape insert	Square insert, 8 mm	Insert with key	**NSYTC8ME**
Shape insert	Triangular insert, 6.5 mm	1 pack	**NSYTT6ME**
Shape insert	Triangular insert, 8 mm	1 pack	**NSYTT8ME**
Barrels	Barrel and key 405E	Barrels with 1 key	**NSYTCL405ME**
Barrels	Barrel and key 1242E	Barrels with 1 key	**NSYTL1242EME**
Barrels	Reinforced key and barrel	1 pack	**NSYTLRME**
Barrels	JIS key and barrel	1 pack	**NSYTLJISME**

Padlocking accessory

NSYBCME

- padlocking system, for Ø 9 mm padlock, preventing access to the handle.
- Material: Stainless steel.

Characteristics	Type	Supply	References
Padlocking system	Padlocking device	1 pack	**NSYBCME**

Sealing kit

NSYJED8500

- Placed directly on the door and on the rear of the enclosure.
- Seal made from black synthetic rubber.

Characteristics	For floor-standing enclosure width (mm)	References
Sealing kit	465	**NSYJED8500**
Sealing kit	590	**NSYJED860**
Sealing kit	785	**NSYJED881**
Sealing kit	1115	**NSYJED8122**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Polyester DIN floor-standing enclosure

Insulating mounting plate

NSYAPLD85

- It is placed directly on the rear of the enclosure.
- Material: Insulating material, bakelite
- Colour: Black
- Thickness: 4 mm



Characteristics	Width (mm)	D (mm)	E (mm)	Maximum load (kg)	References
Insulating mounting plate	465	356	304	19	**NSYAPLD85**
Insulating mounting plate	590	481	429	27	**NSYAPLD86**
Insulating mounting plate	785	676	624	39	**NSYAPLD88**
Insulating mounting plate	1115	448.5	396.5	2 x 24	**NSYAPLD812** *

*The reference includes 2 mounting plates with the dimensions of the table.

Insulating mounting plate

NSYBPLDNG

- They are fixed to the plinth, ref. **NSYZD●●●**.
- They are designed to accommodate busbars, fixed to the built-in inserts.
- This installation is used with a polyester DIN floor-standing enclosure previously machined to obtain a completely open bottom part. This machining is available in the customised offer.
- The enclosure is positioned from the top on the set made of both lateral uprights plus the plinth.
- The fixings supplied allow the attachement of the two uprights to the enclosure.
- Material: Polyester reinforced with fibreglass
- Colour: RAL 7035 grey



Characteristics	Width (mm)	D (mm)	E (mm)	Maximum load (kg)	References
Insulating mounting plate	465	356	304	19	**NSYBPLDNG**

Renovation and anti graffiti paint

NSYAUPG1G

- Paint kit with two components (base 80 % + hardener 20 %)
- Specially designed for polyester enclosures, for their renovation and/or as prevention to allow easy removal of graffiti.
- Colour: RAL 7035 grey

Supply: NSYAUPG1G
The 1 kg reference includes one pot with 800 g of base paint and 200 g of hardener
(It is enough to paint a surface of around 5 m²)

Supply: NSYAUPG5G
The 5 kg reference includes one pot with 4 kg of base paint and 1 kg of hardener
(It is enough to paint a surface of around 25 m²)

Characteristics	References
Renovation and anti graffiti paint	**NSYAUPG1G**
Renovation and anti graffiti paint	**NSYAUPG5G**

- Solvent bottles to be used as a paint thinner or to clean brushes.

Supply:
1 kg

Characteristics	References
Renovation and anti graffiti paint solvent	**NSYAUPGS**

9

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Polyester floor-standing enclosures

Sealed enclosure or enclosure with ventilated canopy

For enclosures without canopy, please just disregard the related 38 mm.















1. 4 bosses with M8 inserts and studs for direct fixing of mounting plates.
2. Bosses designed to accommodate M8 inserts, ref. **NSYTEX8**. They are placed:
   - On the back of the enclosure, from the height of 1000 mm. They allow the fixing of partial mounting plates and assorted equipment.
   - On the top and bottom parts of the enclosure. They are used for fixing the step slides, an internal door, 19" chassis, etc.
3. Dimensions for fixing on the floor or on a plinth.
4. Entry dimensions, door open.
5. Dimension of 28 mm for enclosures with heights of more than 1000 mm (height after the installation of the plain mounting plates with reinforcement foldings).
6. With a width of 1250 mm in standard supply, 500 mm door on the left and 750 mm door on the right.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Polyester floor-standing enclosures

Enclosures with open bottom - plinth type With or without ventilated canopy

For enclosures without canopy, please just disregard the related 38 mm















1. 4 bosses with M8 inserts and studs for direct fixing of mounting plates.
2. Bosses designed to accommodate M8 inserts, ref. **NSYTEX8**. They are placed:
   – On the back of the enclosure, from the height of 1000 mm. They allow the fixing of partial mounting plates and assorted equipment.
   – On the top and bottom parts of the enclosure. They are used for fixing the step slides, an internal door, 19" chassis, etc.
3. Dimensions for fixing on the floor or on a plinth.
4. Entry dimensions, door open.
5. Dimension of 28 mm for enclosures with heights of more than 1000 mm (height after the installation of the plain mounting plates with reinforcement foldings).
6. With a width of 1250 mm in standard supply, 500 mm door on the left and 750 mm door on the right.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Polyester floor-standing enclosures

Connectors between plinths







Buriable H plinths



Floor-standing frame



Internal door



1 Two positions for depthwise installation
2 The 2nd position moves the position of the internal door back by 25 mm

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Polyester floor-standing enclosures

Plain mounting plate



Telequick mounting plate



Insulating mounting plate



1 Reinforcing fold for steel mounting plate **NSYPMM1010** to **NSYPMM1512**
2 A-125 for references **NSYPMM1010** to **NSYPMM1512**, A-120 for the polyester mounting plate, ref. **NSYPMA●●●**.

Step slides



Installation of step slide ref. **NSYDPLA●●●**,
1 57 mm with one transparent door.

Step slides



Installation of step slide ref. **NSYDPLA●●●**, with adapter plate ref. **NSYPTZ●●●**, 1 57 mm with one transparent door.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Polyester floor-standing enclosures

Upright



Plate



Plain cover plate





For enclosure Width (mm)	Height A (mm)	Thickness (mm)	References
500	146	2	**NSYCTL500DLPG**
500	298	4	**NSYCTL500DLP2**
750	146	2	**NSYCTL750DLPG**
750	298	4	**NSYCTL750DLP2**

Plain mounting plate



For enclosure Width (mm)	Height A (mm)	Thickness (mm)	References
500	149	2	**NSYPMP500DLP**
500	298	2	**NSYPMP5002DLP**
750	149	2	**NSYPMP750DLP**
750	298	2	**NSYPMP7502DLP**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Polyester floor-standing enclosures

19'' fixed chassis



19'' swing chassis



Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Polyester DIN floor-standing enclosure

Floor-standing enclosures



* Housing for M8 inserts, ref. NSYTEPLDM8 (to be ordered in multiples of 25).

Floor-standing enclosure plus plinth



Floor-standing enclosures References	Plinths References	B (mm)	D (mm) (1)
NSYPLD8500G	**NSYZD5300G**	465	360
NSYPLD860G	**NSYZD630G**	590	495
NSYPLD881G	**NSYZD831G**	785	690
NSYPLD8122G	**NSYZD1232G**	1115	1020

(1) Distance between the points for fixing the enclosure to the plinth.

The H dimension relates to the finished floor height area.

Plinths



Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Polyester DIN floor-standing enclosure

Knock-out Pg 36 auxiliary outlet

Lateral knock-out is removed

Removable top front panel (not hinged)

Table of fixing and opening dimensions



9

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Mounting

Cable management



Terminal blocks



Lighting and power socket

Floor accessories

Door accessories



Other accessories

10

Life Is On Schneider Electric

Accessories

Content

Mounting	240
Cable management	272
Terminal blocks	294
Lighting and power socket	296
Floor accessories	299
Door accessories	300
Other accessories	305
Dimensions	307

Mounting plates for wall-mounting enclosures

S3D
S3X
PLM



Characteristics				Mounting plates Plain	Mounting plates Silkscreened	Mounting plates Microperforated**	Telequick Mounting plate**		
				–	Silkscreened for easier distribution of the products to be installed. Centimetric grid pattern.	They considerably reduce the products installation time thanks to the holes prepared to receive the self-tapping screws. Holes with Ø 3.6 mm in steps of 12.5 mm.	They allow cable guides and ducting and other installation accessories to be clipped on, making it easier to install switchgear. 11 x 26 mm slots. Switchgear fixing by clip-on nuts.		
Material				Galvanised steel	Galvanised steel	Galvanised steel	Zinc-coated steel		
Maximum load				PLM: 150 kg/m² S3D, S3X, CRN, CRNG: 250 kg/m²			PLM: 150 kg/m² S3D, S3X, CRN: 250 kg/m²		
Supply				one mounting plate without fixing elements			one mounting plate without fixing elements		
For enclosures (mm)		Dimensions (mm)					No. of perforations in		
Height	Width	H	W	References	References	References	H	W	References
200	200	150	150	**NSYMM22**	-	-	-	-	-
200	300	150	250	**NSYMM23**	-	-	-	-	-
250	200	200	150	**NSYMM2520**	-	-	-	-	-
250	300	250	200	**NSYMM3025**					
250	400	200	350	**NSYMM2540**	-	-	-	-	-
250	500	200	450	**NSYMM2550**	-	-	-	-	-
300	200	250	150	**NSYMM32**	-	**NSYMF32**	16	5	**NSYMR32**
300	250	250	200	**NSYMM3025***	-	-	16	8	**NSYMR3025**
300	300	250	250	**NSYMM33**	-	**NSYMF33**	16	9	**NSYMR33**
300	400	250	350	**NSYMM43***	**NSYMS43***	**NSYMF43***	18	11	**NSYMR34**
300	450	250	400	**NSYMM3045**	-	-	-	-	-
300	500	450	250	**NSYMM53***	-	-	-	-	-
300	600	250	550	**NSYMM36**	-	-	-	-	-
400	300	230	350	**NSYMM43***	**NSYMS43**	**NSYMF43**	22	9	**NSYMR43**
400	400	350	350	**NSYMM44**	**NSYMS44**	**NSYMF44**	24	11	**NSYMR44**
400	600	350	550	**NSYMM64***	**NSYMS64***	-	24	19	**NSYMR46**
400	800	350	750	**NSYMM48**	-	-	-	-	-
500	300	450	250	**NSYMM53***	**NSYMS53***	**NSYMF53**	29	9	**NSYMR53**
500	400	450	350	**NSYMM54**	**NSYMS54**	**NSYMF54**	31	11	**NSYMR54**
500	500	450	450	**NSYMM55***	**NSYMS55***	**NSYMF55**	31	14	**NSYMR55**
500	600	550	450	**NSYMM65**	-	-	-	-	-
600	400	550	350	**NSYMM64**	**NSYMS64**	**NSYMF64***	38	11	**NSYMR64**
600	500	550	450	**NSYMM65**	-	**NSYMF65**	38	14	**NSYMR65**
600	600	550	550	**NSYMM66**	**NSYMS66**	**NSYMF66**	38	17	**NSYMR66**
600	800	-	-	-	-	-	36	24	**NSYMR68**
700	500	650	450	**NSYMM75**	**NSYMS75**	**NSYMF75**	44	14	**NSYMR75**
700	600	650	550	**NSYMM76**	-	-	44	17	**NSYMR76**
800	600	750	550	**NSYMM86***	**NSYMS86***	**NSYMF86***	51	17	**NSYMR86**
800	800	750	750	**NSYMM88**	-	**NSYMF88**	51	24	**NSYMR88**
800	1000	-	-	**NSYMM108**	-	**NSYMF108**	49	31	**NSYMR810**
800	1200	-	-	**NSYMM128**	-	**NSYMF128**			2 x **NSYMR86**
1000	600	950	550	**NSYMM106**	-	**NSYMF106**	64	17	**NSYMR106**
1000	800	950	750	**NSYMM108***	-	**NSYMF108***	64	24	**NSYMR108**
1000	1000	950	950	**NSYMM1010**	-	**NSYMF1010**	62	31	**NSYMR1010**
1000	1200	-	-	-	-	-	62	37	**NSYMR1012**
1200	600	1150	550	**NSYMM126**	-	**NSYMF126**	75	17	**NSYMR126**
1200	800	1150	750	**NSYMM128***	-	**NSYMF128**	75	24	**NSYMR128**
1200	1000	1150	950	**NSYMM1210***	-	**NSYMF1210***	75	31	**NSYMR1210**
1200	1200	1150	1150	**NSYMM1212**	-	2 x **NSYMF126**	-	-	2 x **NSYMR126**
1400	1000	1350	950	**NSYMM1410**	-	-	88	31	**NSYMR1410**

* Plate with reversible dimensions; It can be installed in enclosures with inverted dimensions. Example: Plate ref. **NSYMM64** can be used for the following enclosures: H 600 x W 400 mm or H 400 x W 600 mm. For plain and silkscreened mounting plates: In wall-mounting enclosures with widths of 1000 and 1200 mm, it is possible to install two mounting plates at different depths using an additional central step slide **NSYSDRSDCR•••** (more information on page 243).

** To install two mounting plates in a single enclosure, also order reference **NSYCRNGSDR**. See details on page 243.
To install the plate in an enclosure with six studs, also order reference **NSYEMR**.

10

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Mounting plates for wall-mounting enclosures

S3D
S3X
PLM







Characteristics	Bakelite mounting plate**	Polyester mounting plate**	DIN rail chassis	Joinable Telequick mounting plate
	• They are coupled directly to the rear of the actual enclosure or to the sliding plate supports. • Double door enclosures offer the option of installing two plates.		Components supplied with a DIN rail chassis: • Aluminium uprights. • DIN rails (symmetric section A or B, according to the reference). • Screws, washers and nuts need to mount the DIN rails to the uprights. • Batch of four adapters, ref. NSYAMCSF, needed to fix the uprights to the enclosure.	• 20/10e mm Telequick mounting plates. • These mounting plates are suitable for mounting vertically multiple plates. • 11 x 26 mm slots. • Switchgear fixing by clip-on nuts.
Material	Bakelite	Polyester reinforced with fibreglass	Aluminum or zinc-coated steel	Zinc-coated steel
Colour	RAL 9005 black	RAL 7035 grey	–	–
Maximum load	100 kg/m²	150 kg/m²	–	–
Supply	One mounting plate without fixing elements		One DIN rail chassis	One mounting plate and fixing elements

For enclosures (mm)		Dimensions (mm)				Dimensions (mm)				Type of rails	No. of rails		Dimensions (mm)		
Height	Width	H (P)	W (S)	Thick.	References	H (P)	W (S)	Thick.	References			References	H	W	References
60	700	-	-	-	-	-	-	-	-	-	-	-	120	734	**AM1PA0670**
120	700	-	-	-	-	-	-	-	-	-	-	-	180	734	**AM1PA1270**
300	150	-	-	-	-	-	-	-	-	-	-	-	349	228	**AM1PA3015**
300	195	-	-	-	-	-	-	-	-	-	-	-	349	258	**AM1PA3020**
300	200	265	150	4	**NSYMB32**	265	150	4	**NSYMPP32**	-	-	-	-	-	-
300	250	265	200	4	**NSYMB3025**	265	200	4	**NSYMPP3025**	-	-	-	-	-	-
300	300	265	250	4	**NSYMB33**	-	-	-	-	B	4	**NSYMD33**	-	-	-
300	500	-	-	-	-	-	-	-	-	-	-	-	360	534	**AM1PA3050**
300	700	-	-	-	-	-	-	-	-	-	-	-	360	734	**AM1PA3070**
400	300	325	250	4	**NSYMB43**	325	250	4	**NSYMPP43**	B	4	**NSYMD43**	-	-	-
405	300	-	-	-	-	-	-	-	-	-	-	-	465	334	**AM1PA4030**
500	400	465	350	4	**NSYMB54**	465	350	4	**NSYMPP54**	B	4	**NSYMD54**	-	-	-
600	400	565	350	4	**NSYMB64**	565	350	4	**NSYMPP64**	B	6	**NSYMD64**	660	434	**AM1PA6040**
600	500	565	450	4	**NSYMB65**	-	-	-	-	-	-	-	660	534	**AM1PA6050**
600	600	-	-	-	-	-	-	-	-	A	6	**NSYMD66**	660	634	**AM1PA6060**
600	700	-	-	-	-	-	-	-	-	-	-	-	660	734	**AM1PA6070**
700	500	665	450	4	**NSYMB75**	665	450	4	**NSYMPP75**	B	6	**NSYMD75**	-	-	-
705	500	-	-	-	-	-	-	-	-	-	-	-	765	534	**AM1PA7050**
795	600	-	-	-	-	-	-	-	-	-	-	-	855	634	**AM1PA8060**
800	600	765	550	4	**NSYMB86**	765	550	5	**NSYMPP86**	A	6	**NSYMD86**	-	-	-
800	1000	-	-	-	**NSYMB108**	-	-	-	-	-	-	-			
800	1200	-	-	-	**2 x NSYMB86**	-	-	-	-	-	-	**2 x NSYMD86**			
900	500	-	-	-	-	-	-	-	-	-	-	-	960	534	**AM1PA9050**
900	600	-	-	-	-	-	-	-	-	-	-	-	960	634	**AM1PA9060**
900	700	-	-	-	-	-	-	-	-	-	-	-	960	734	**AM1PA9070**
1000	600	965	550	4	**NSYMB106**	-	-	-	-	-	-	-	-	-	-
1000	800	965	750	4	**NSYMB108**	965	750	5	**NSYMPP108**	A	6	**NSYMD108**	-	-	-
1200	800	-	-	-	-	-	-	-	-	A	7	**NSYMD128**	-	-	-
1200	1000	1150	950	4	**NSYMB1210**	-	-	-	-	-	-	-	-	-	-

* Plate with reversible dimensions; It can be installed in enclosures with inverted dimensions. Example: Plate ref. **NSYMM64** can be used for the following enclosures: H 600 x W 400 mm or H 400 x W 600 mm. For plain and silkscreened mounting plates: In wall-mounting enclosures with widths of 1000 and 1200 mm, it is possible to install two mounting plates at different depths using an additional central step slide **NSYSDRSDCR•••** (more information on page 243).

** To install two mounting plates in a single enclosure, also order reference **NSYCRNGSDR**. See details on page 243.
To install the plate in an enclosure with six studs, also order reference **NSYEMR**.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Mounting plates for wall-mounting enclosures

S3D S3X PLM Elevator for microperforated mounting plate

AZ1CA04

- Mounting plate elevator to mount the Microperforated mounting plate at the same level as the other Telequick system components.

Supply:
Four units

Characteristics	Reference
Elevator for microperforated mounting plate	**AZ1CA04**

Clip-on nuts for Telequick mounting plate

AF1EA3

- Used to easily fix devises in the Telequick mounting plate with the possibility of changing the layout as much as needed.

Supply:
100 units. Reference by unit. Order by multiples of 100 (100, 200, 300...)

Characteristics	Reference
Clip-on nuts for Telequick mounting plate, Model M3	**AF1EA3**
Clip-on nuts for Telequick mounting plate, Model M4	**AF1EA4**
Clip-on nuts for Telequick mounting plate, Model M5	**AF1EA5**
Clip-on nuts for Telequick mounting plate, Model M6	**AF1EA6**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Step slides for wall-mounting enclosures

S3D S3X Step slides for mounting plate



- Set of four supports intended for installation in enclosures with depths of 200, 250, 300 and 400 mm.
- The rail allows the depth of the plate and other accessories to be adjusted in steps of 12.5 mm.

Supply:
Four step slides

NSYSDCR200

Characteristics	Enclosure depth (mm)	Reference
Step slides for mounting plate	200	**NSYSDCR200**
Step slides for mounting plate	250	**NSYSDCR250**
Step slides for mounting plate	300	**NSYSDCR300**
Step slides for mounting plate	400	**NSYSDCR400**

S3D S3X Step slides for two mounting plates in one enclosure

Comment:
Details, see page 74

- In 1000 and 1200 mm wall-mounting enclosures, it is possible to install two mounting plates side by side, using the additional central step slides.
- Not applicable for stainless steel enclosures.

Supply:
Two step slides

NSYSDRSDCR300

Characteristics	Enclosure depth (mm)	Reference
Step slides for 2 mounting plates in one enclosure	300	**NSYSDRSDCR300**
Step slides for 2 mounting plates in one enclosure	400	**NSYSDRSDCR400**

S3D S3X Slide bracket for two mounting plates at different depths



- Additional slide bracket to be installed on the central step slides in order to mount two mounting plates, side by side, in different depths.

Supply:
Two slide brackets

NSYCRNGSDR

Characteristics	Reference
Slide bracket for two mounting plates at different depths	**NSYCRNGSDR**

10

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Vertical rails for wall-mounting enclosures

S3D S3X PLM PLA Aluminium vertical rails

Telequick



- Fixing in the enclosure with M8 nuts, ref. **NSYAMCSF** (batch of 4 adapters to be ordered separately).

NSYMDVR3

Characteristics	Height (mm)	Supply (units)	References
Aluminium vertical rail, aluminium	300	10	**NSYMDVR3**
Aluminium vertical rail, aluminium	400	10	**NSYMDVR4**
Aluminium vertical rail, aluminium	500	10	**NSYMDVR5**
Aluminium vertical rail, aluminium	600	10	**NSYMDVR6**
Aluminium vertical rail, aluminium	700	10	**NSYMDVR7**
Aluminium vertical rail, aluminium	800	10	**NSYMDVR8**
Aluminium vertical rail, aluminium	1000	10	**NSYMDVR10**
Aluminium vertical rail, steel	1200	2	**NSYMDVR12**
Aluminium vertical rail, aluminium	3000	10	**NSYMDVR3M**

S3D S3X PLM 20/10e mm zinc-coated pre-drilled uprights

Telequick

DZ6MZ121

- Ø 11 mm holes enable to adjust the rows of equipment by 20 mm steps.

Comment:
Details, see page 308

Characteristics	Height (mm)	Weight (g)	References
20/10e mm zinc-coated pre-drilled uprights	1020	2330	**DZ6MZ121**
20/10e mm zinc-coated pre-drilled uprights	1320	2920	**DZ6MZ151**
20/10e mm zinc-coated pre-drilled uprights	1620	3375	**DZ6MZ181**
20/10e mm zinc-coated pre-drilled uprights	1920	4000	**DZ6MZ211**

Sliding Nuts

Supply:
100 Sliding nuts

- Sliding nuts to be used on aluminium vertical rails.

NSYNM5

Characteristics	Type	References
Sliding Nut	M4	**NSYNM4**
Sliding Nut	M5	**NSYNM5**
Sliding Nut	M6	**NSYNM6**

Brass nuts to fix the upright to the enclosures



Supply:
Four Brass nuts

NSYAMCSF

Characteristics	References
Brass nuts to fix the upright to the enclosures	**NSYAMCSF**

Slides and brackets

Supply:
10 units. References per unit. To be ordered in multiples of 10 (10, 20, 30, etc.).

NSYSB90

NSYFB

- They allow the depth of the plates and rails to be adjusted.

Characteristics	Width (mm)	Enclosure depth (mm)	References
Slide with bracket	90	150 and 200	**NSYSB90**
Slide with bracket	130	250 and 300	**NSYSB130**
Bracket for slides (customised mounting plate)			**NSYFB**

Notched clamp nuts



DZ5MF6

Supply:
100 units. References per unit. To be ordered in multiples of 100 (100, 200, 300, etc).

- Specially designed for pre-drilled uprights.

Characteristics	Type	Weight (g)	References
Notched clamp nuts	M6	7.0	**DZ5MF6**
Notched clamp nuts	M8	8.0	**DZ5MF8**

10

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Mounting plates for floor-standing enclosures

SM SMX SF SFX Plain mounting plate

- Depth adjustable with a pitch of 25 mm, provided with plastic shoe for easier sliding.
- Once the plate is fixed, in advanced position, the sliding shoe can be easily removed, to increase the available plate surface.
- In sets made up of two or more enclosures with mounting plates, it is possible to obtain a continuous plate surface using intermediate mounting plates (see page 247).
- Load: 300 kg/ m²
- Maximum load: 600 kg in the back of the enclosure and 500 kg in the intermediate position
- Material: Galvanised steel

Fixing options:
- At the sides of the enclosure with the orthogonal brackets (see page 247)
- Back-to-back, with the brackets for fixing the mounting plates in back-to-back position (see page 247)

Supply:
One mounting plate and sliding shoes

NSYMP124

Characteristics	Width (mm)	Height (mm)	References	
Plain mounting plate	400	1200	**NSYMP124**	New
Plain mounting plate	400	1400	**NSYMP144**	New
Plain mounting plate	400	1600	**NSYMP164**	New
Plain mounting plate	400	1800	**NSYMP184**	New
Plain mounting plate	400	2000	**NSYMP204**	New
Plain mounting plate	400	2200	**NSYMP224**	New
Plain mounting plate	600	1200	**NSYMP126**	
Plain mounting plate	600	1400	**NSYMP146**	
Plain mounting plate	600	1600	**NSYMP166**	
Plain mounting plate	600	1800	**NSYMP186**	
Plain mounting plate	600	2000	**NSYMP206**	
Plain mounting plate	600	2200	**NSYMP226**	
Plain mounting plate	800	1200	**NSYMP128**	
Plain mounting plate	800	1400	**NSYMP148**	
Plain mounting plate	800	1600	**NSYMP168**	
Plain mounting plate	800	1800	**NSYMP188**	
Plain mounting plate	800	2000	**NSYMP208**	
Plain mounting plate	800	2200	**NSYMP228**	
Plain mounting plate	1000	1200	**NSYMP1210**	
Plain mounting plate	1000	1400	**NSYMP1410**	
Plain mounting plate	1000	1600	**NSYMP1610**	
Plain mounting plate	1000	1800	**NSYMP1810**	
Plain mounting plate	1000	2000	**NSYMP2010**	
Plain mounting plate	1000	2200	**NSYMP2210**	
Plain mounting plate	1200	1200	**NSYMP1212**	
Plain mounting plate	1200	1400	**NSYMP1412**	
Plain mounting plate	1200	1600	**NSYMP1612**	
Plain mounting plate	1200	1800	**NSYMP1812**	
Plain mounting plate	1200	2000	**NSYMP2012**	
Plain mounting plate	1200	2200	**NSYMP2212**	
Plain mounting plate	1600	1800	**NSYMP1816**	
Plain mounting plate	1600	2000	**NSYMP2016**	

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Mounting plates for floor-standing enclosures

SM SMX SF SFX SD SDX Perforated mounting plate Telequick

- Allows the installation of switchgear without drilling or screwing.
- Plate designed for quick fixing of switchgear by means of clip-on nuts ref. **AF1EA3** to **AF1EA6**.
- Vertical continuity is reinforced by the vertical installation of plates.
- The top plate must be fixed in the third hole, 80 mm from the top frame.
- Load: 150 kg/m²
- Material: Zinc-coated steel

Fixing options:
- Directly to the vertical uprights of the structure, by means of self-tapping screws (only Spacial SF)
- To the technical vertical uprights, by means of sliding nuts, see page 251;
- to standard uprights by means of flat nuts, see page 251 or self-tapping screws, and to cross rails

Comment:
Examples of combination see page 309

Supply:
One perforated mounting plate and fixing elements for technical uprights and screws for fixing to the structure or cross rails


NSYSTMP4560

Characteristics	Width (mm)	Plate height (mm) D	E	F	G	Useful surface (dm²)	References
Perforated mounting plate Telequick	600	450	200	-	100	11.4	**NSYSTMP2260**
Perforated mounting plate Telequick	600	450	425	-	325	22.8	**NSYSTMP4560**
Perforated mounting plate Telequick	600	450	575	125	475	30.4	**NSYSTMP6060**
Perforated mounting plate Telequick	600	450	800	250	700	11.9	**NSYSTMP8260**
Perforated mounting plate Telequick	800	650	200	-	100	15.9	**NSYSTMP2280**
Perforated mounting plate Telequick	800	650	425	-	325	31.8	**NSYSTMP4580**
Perforated mounting plate Telequick	800	650	575	125	475	42.4	**NSYSTMP6080**
Perforated mounting plate Telequick	800	650	800	250	700	58.4	**NSYSTMP8280**
Perforated mounting plate Telequick	1000	850	200	-	100	20.4	**NSYSTMP22100**
Perforated mounting plate Telequick	1000	850	425	-	325	40.8	**NSYSTMP45100**
Perforated mounting plate Telequick	1000	850	575	125	475	54.4	**NSYSTMP60100**
Perforated mounting plate Telequick	1000	850	800	250	700	74.9	**NSYSTMP82100**
Perforated mounting plate Telequick	1200	1050	200	-	100	24.9	**NSYSTMP22120**
Perforated mounting plate Telequick	1200	1050	425	-	325	49.9	**NSYSTMP45120**
Perforated mounting plate Telequick	1200	1050	575	125	475	66.5	**NSYSTMP60120**
Perforated mounting plate Telequick	1200	1050	800	250	700	91.5	**NSYSTMP82120**

SM SF SFX Partial mounting plate

- Partial mounting plate, provided with reinforcement flange on its four sides.
- Load: 250 kg/m²
- Material: Galvanised steel

Fixing options:
Spacial SF, SFX:
- Fixing to the vertical uprights of the structure
- Fixing to the technical or standard vertical uprights, see page 251
- For installations in advanced position, fixing to cross rails, see page 254

Spacial SM:
- Fixing by means of adaptation profiles and 40 mm universal cross rails (one row) in vertical position, or also on horizontal universal cross rails
- It can be mounted horizontally, as a tray, by means of depthwise cross rails, see page 254

Supply:
Partial mounting plate and fixingelements

NSYSPMP2560

Characteristics	Width (mm) B	Plate height (mm) H	Plate length (mm) B-100	References
Partial mounting plate	400	247	300	**NSYSPMP2540**
Partial mounting plate	400	397	300	**NSYSPMP4040**
Partial mounting plate	400	597	300	**NSYSPMP6040**
Partial mounting plate	600	247	500	**NSYSPMP2560**
Partial mounting plate	600	247	750	**NSYSPMP2575**
Partial mounting plate	600	397	500	**NSYSPMP4060**
Partial mounting plate	600	597	500	**NSYSPMP6060**
Partial mounting plate	800	247	700	**NSYSPMP2580**
Partial mounting plate	800	397	700	**NSYSPMP4080**
Partial mounting plate	800	597	700	**NSYSPMP6080**
Partial mounting plate	1000	247	900	**NSYSPMP25100**
Partial mounting plate	1000	397	900	**NSYSPMP40100**
Partial mounting plate	1000	597	900	**NSYSPMP60100**
Partial mounting plate	1200	247	1100	**NSYSPMP25120**
Partial mounting plate	1200	397	1100	**NSYSPMP40120**
Partial mounting plate	1200	597	1100	**NSYSPMP60120**
Partial mounting plate	1600	397	1100	**NSYSPMP40160**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Mounting plates for floor-standing enclosures

SF SFX Intermediate mounting plate

- Obtains a continuous surface of the mounting plate at enclosure suites.
- Adjustable depth with a pitch of 25 mm. When the mounting plates are located in the back of the enclosure, the vertical profiles of the structure are flush with the plates, acting as an intermediate mounting plate. In this case the intermediate plate cannot be installed.
- Material: Galvanised steel

Supply:
One intermediate plate and fixing elements


NSYSIMP12

Characteristics	Height (mm)	References
Intermediate mounting plate	1200	**NSYSIMP12**
Intermediate mounting plate	1400	**NSYSIMP14**
Intermediate mounting plate	1600	**NSYSIMP16**
Intermediate mounting plate	1800	**NSYSIMP18**
Intermediate mounting plate	2000	**NSYSIMP20**
Intermediate mounting plate	2200	**NSYSIMP22**

SF SFX Intermediate fixing of the mounting plate, located in the back of the enclosure

- Support for additional fixing of the mounting plate, at any height of the plate, when the plate is mounted in the back of the enclosure.
- The supports minimise the vibration of the plate during the transport and operation of the panel.
- Material: Zinc-coated steel
- **Fixing:** The supports are fixed to the structure when the plate is already located in the back of the enclosure
  Spacial SM: Fixing to 40 mm universal cross rails (one row), installed vertically in the back of the enclosure, see page 254

Supply:
Ten units and fixing elements. Reference by unit. Order by multiples of 10 (10, 20, 30…)


NSYSMPFB

Characteristics	References
Intermediate fixing of the mounting plate, located in the back of the enclosure	**NSYSMPFB**

SF SFX Intermediate fixing of the mounting plate, in advanced position

- Support for additional fixing of the mounting plate, at any height of the plate, when the plate is mounted in advanced position.
- The supports minimise the vibration of the plate during the transport and operation of the panel.
- Material: Zinc-coated steel
- **Fixing:** The supports are mounted on light cross rails or on 40 mm (one row) universal or quick fixing cross rails (not supplied), see page 254

Supply:
Ten units and fixing elements. Reference by unit. Order by multiples of 10 (10, 20, 30…)


NSYSMPFA

Characteristics	References
Intermediate fixing of the mounting plate, in advanced position	**NSYSMPFA**

SF SFX Reinforcement for mounting plate

- Reinforcement kit for transversal mounting plate.
- Provides extra rigidity to the mounting plates and absorbs vibrations.
- Can be used as a support for fixing very heavy elements.
- Material: Zinc-coated steel
- Thickness: 15/10e mm

Supply:
Two profiles, four supports for fixing to the mounting plate and fixing elements

NSYMPRK8

Characteristics	Width (mm)	References
Reinforcement for mounting plate	800	**NSYMPRK8**
Reinforcement for mounting plate	1000	**NSYMPRK10**
Reinforcement for mounting plate	1200	**NSYMPRK12**
Reinforcement for mounting plate	1600	**NSYMPRK16**

Mounting plate accessories

Self-tapping screw

- Hexagonal head, 4.8 x 16 mm thread.
- Drilling capacity: Thicknesses between 17.5/10e and 40/10e mm.

Supply:
100 units. To be ordered in multiples of 100 (100, 200, 300, etc.).

NSYS16M5HS

Characteristics	References
Self-tapping screw	**NSYS16M5HS**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Mounting plate brackets for floor-standing enclosures

SM SMX SF SFX Mounting plate fixing brackets

- For direct mounting on the structure of the enclosure.
- Adjustable depth with a pitch of 25 mm.
- Material: Zinc-coated steel
- Maximum load: Four brackets: 600 kg

NSYSFPB

Supply:
Four brackets and fixing elements

Characteristics	References
Spacial SF Mounting plate fixing brackets	**NSYSFPB**
Spacial SM/SMX/SFX Mounting plate fixing brackets	**NSYSMPB**

SF SFX Orthogonal brackets

NSYSMPSB

- Designed for the installation of mounting plates on the sides of the enclosure.
- In the event of installing one plate in the back of the enclosure and one plate at the side, they must both be installed using orthogonal brackets.
- Spacial SFX: In order to mount the lateral mounting plate is necessary to remove the one on the back and its fixing brackets.
- Material: Zinc-coated steel
- Maximum load: Four brackets: 600 kg



Supply:
Four brackets and fixing elements

Characteristics	References
Spacial SF/SFX Orthogonal brackets	**NSYSMPSB**

SF Mounting plate sliding rails

- Rails which the mounting plate slides along when inserted in the enclosure.
- Once the mounting plate is installed and fixed to the brackets, the sliding rails can be removed to maximise the cable passage surface, and can be installed depthwise in other positions.
- Material: Zinc-coated steel

Supply:
Four brackets and fixing elements

NSYSMPS4

Characteristics	Depth (mm)	References
Spacial SF Mounting plate sliding rails	400	**NSYSMPS4**
Spacial SF Mounting plate sliding rails	500	**NSYSMPS5**
Spacial SF Mounting plate sliding rails	600	**NSYSMPS6**
Spacial SF Mounting plate sliding rails	800	**NSYSMPS8**

Brackets for fixing mounting plates in back-to-back position





- Doubling the mounting surface.
- Adjustable with a pitch of 25 mm.
- Material: Zinc-coated steel

Supply:
Four brackets for fixing back-to-back and fixing elements

NSYSBTB

Characteristics	References
Brackets for fixing mounting plates in back-to-back position	**NSYSBTB**

SM SMX SF SFX Brackets for fixing intermediate mounting plates in back-to-back position



- Doubling the mounting surface.
- Adjustable with a pitch of 25 mm.
- Material: Zinc-coated steel

Supply:
2 brackets for fixing intermediate plates back-to-back and fixing elements


NSYSIBTB

Characteristics	References
Spacial SM/SMX/SF/SDX Brackets for fixing intermediate mounting plates in back-to-back position	**NSYSIBTB**

10

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Mounting rails for floor-standing enclosures

SF SFX Side entry rails for the mounting plate



- Side entry device for the mounting plates when coupling Spacial SF enclosures or Spacial SFX.
- The mounting plates can be coupled with one another, and are fixed to the side entry guide by pressure.
- Material: Zinc-coated steel

Supply:
Two rails (top and bottom) and fixing elements

NSYSMPSE6

Characteristics	Width (mm)	References
Spacial SF/SFX Side entry rails for the mounting plate	600	**NSYSMPSE6**
Spacial SF/SFX Side entry rails for the mounting plate	800	**NSYSMPSE8**
Spacial SF/SFX Side entry rails for the mounting plate	1000	**NSYSMPSE10**
Spacial SF/SFX Side entry rails for the mounting plate	1200	**NSYSMPSE12**

Mounting plates

- Mounting plates for the side entry device when coupling Spacial SF enclosures or Spacial SFX.
- Solution for enclosures of width and depth of 400.
- Material: Galvanised steel

Supply:
One mounting plate and fixing elements

NSYMP224

Characteristics	Height (mm)	References	
Partial mounting plate 400	250	**NSYSPMP2540**	New
Partial mounting plate 400	400	**NSYSPMP4040**	New
Partial mounting plate 400	600	**NSYSPMP6040**	New
Mounting plate 400	1200	**NSYMP124**	New
Mounting plate 400	1400	**NSYMP144**	New
Mounting plate 400	1600	**NSYMP164**	New
Mounting plate 400	1800	**NSYMP184**	New
Mounting plate 400	2000	**NSYMP204**	New
Mounting plate 400	2200	**NSYMP224**	New

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Mounting rails for floor-standing enclosures

SM Top/bottom adjustment rails





- Allows the installation of two mounting plates or vertical uprights in enclosures with a width of 1200 mm, as if in two independent enclosures.
- A set of mounting plate fixing brackets ref. **NSYSMPB** is required for this.
- Optional installation of an intermediate mounting plate.
- Material: Galvanised steel

Comment:
Examples of combination
see page 310

Supply:
Two rails, top and bottom

NSYSTBR3

Characteristics	Depth (mm)	References
Spacial SM Top/bottom adjustment rails	300	**NSYSTBR3**
Spacial SM Top/bottom adjustment rails	400	**NSYSTBR4**
Spacial SM Top/bottom adjustment rails	500	**NSYSTBR5**
Spacial SM Top/bottom adjustment rails	600	**NSYSTBR6**

SF Kit for adapting two-door enclosures



- Allows the installation of two mounting plates as if in two independent enclosures.
- A set of brackets for fixing mounting plates ref. **NSYSMPB** is required for this.
- Option of installing an intermediate mounting plate.
- Valid for enclosures with widths of 1200 and 1600 mm.
- In the event of installing a cable gland plate for a width of 1200 mm, it is necessary to install two with a width of 600 mm, and for widths of 1600 mm, two with a width of 800 mm.

Comment:
Examples of combination
see page 310



NSYSMP2D4

Characteristics	Depth (mm)	References
Spacial SF Kit for adapting two-door enclosures	400	**NSYSMP2D4**
Spacial SF Kit for adapting two-door enclosures	500	**NSYSMP2D5**
Spacial SF Kit for adapting two-door enclosures	600	**NSYSMP2D6**
Spacial SF Kit for adapting two-door enclosures	800	**NSYSMP2D8**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Uprights for floor-standing enclosures

SM SMX SF SFX SD SDX PLA PHD Technical uprights

Telequick

- Vertical uprights for fixing plates and rails.
- They can be fixed to the fixing brackets of the mounting plate or to the uprightfixing bracket (ref. **NSYMFB**).
- Adjustable height in steps of 2.5 mm (with quarter-turn nuts, ref. **NSYSNM6** or **NSYSNM8**) or 25 mm (with cage nuts, ref. **NSYCNM6** or **NSYCNM8**).
- Material: Galvanised steel
- Thickness: 20/10e mm



Comment:
NSYTVR20 is not compatible with PLA or PHD 2000 mm high enclosures. Use 2 x **NSYTVR10**.

Supply:
Set of two uprights

NSYTVR7

Characteristics	Height (mm)	A (mm)	References
SM/SMX/SF/SFX/SD/SDX/PLA/PHD Technical uprights	750	625	**NSYTVR7**
SM/SMX/SF/SFX/SD/SDX/PLA/PHD Technical uprights * Control desk.	1000*	675	**NSYTVR8**
SM/SMX/SF/SFX/SD/SDX/PLA/PHD Technical uprights	1000	875	**NSYTVR10**
SM/SMX/SF/SFX/SD/SDX/PLA/PHD Technical uprights	1200	1075	**NSYTVR12**
SM/SMX/SF/SFX/SD/SDX/PLA/PHD Technical uprights	1250	1125	**NSYTVR125**
SM/SMX/SF/SFX/SD/SDX/PLA/PHD Technical uprights	1400	1275	**NSYTVR14**
SM/SMX/SF/SFX/SD/SDX/PLA/PHD Technical uprights	1500	1375	**NSYTVR15**
SM/SMX/SF/SFX/SD/SDX/PLA/PHD Technical uprights	1600	1475	**NSYTVR16**
SM/SMX/SF/SFX/SD/SDX/PLA/PHD Technical uprights	1800	1675	**NSYTVR18**
SM/SMX/SF/SFX/SD/SDX Technical uprights	2000	1875	**NSYTVR20**
SM/SMX/SF/SFX/SD/SDX/PLA/PHD Technical uprights	2200	2075	**NSYTVR22**

SM SMX SF SFX Standard uprights

Telequick

- Vertical uprights for fixing plates and rails.
- They can be fixed on the mounting plate fixing brackets or on the upright fixing bracket, ref. **NSYMFB**.
- Adjustable height with a pitch of 25 or 50 mm.
- Material: Galvanised steel
- Thickness: 20/10e mm



Supply:
Set of two uprights

NSYVR18

Characteristics	Height (mm)	A (mm)	References
SM/SMX/SF/SFX Standard uprights	1800	1696	**NSYVR18**
SM/SMX/SF/SFX Standard uprights	2000	1896	**NSYVR20**
SM/SMX/SF/SFX Standard uprights	2200	2096	**NSYVR22**

Nuts and screws for technical uprights

NSYSNSM6

NSYSNM6

NSYCNM6

AF1VA612

Characteristics	Supply (units)	References
M6 quarter-turn sliding nut	10	**NSYSNM6**
M8 quarter-turn sliding nut	10	**NSYSNM8**
M6 quarter-turn serrated sliding nut	10	**NSYSNSM6**
M8 quarter-turn serrated sliding nut	10	**NSYSNSM8**
M6 renovable nut	50	**NSYCNM6**
M8 renovable nut	50	**NSYCNM8**
M6 x 12 screw	100	**AF1VA612**
M6 x 18 screw	100	**AF1VA618**
M8 x 20 screw	100	**AF1VC820**

Nuts and screws for standard uprights

NSYFNM6

AF1VA612

Characteristics	Supply (units)	References
M6 flat nut	50	**NSYFNM6**
M8 flat nut	50	**NSYFNM8**
M6 x 12 screw	100	**AF1VA612**
M6 x 18 screw	100	**AF1VA618**
M8 x 20 screw	100	**AF1VC820**

Bracket for fixing uprights

- Brackets for fixing the uprights, standard or technical, at the same level as the structure, obtaining a greater working surface inside the enclosure.
- They allow two pairs of uprights to be fixed back to back, doubling the working surface.
- The brackets are fixed to the structure by means of M6 self-tapping screws.
- Adjustable depth with a pitch of 25 mm.
- Material: Zinc-coated steel.

Supply:
Four brackets for fixing uprights and fixing elements.

NSYMFB

Characteristics	References
Bracket for fixing uprights	**NSYMFB**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Other support brackets

SM SMX SF SFX SD SDX Rail support bracket

NSYFB45

- Bracket for fixing rails at an angle of 45°.
- Material: Zinc-coated steel
- Insallation: Spacial SF: Mounted on the structure and/or mounting plates
  Spacial SM: Mounted on the bottom mounting rail and/or mounting plates

Telequick

Supply:
Ten units and fixing elements.
Reference by unit. Order by multiples of 10 (10, 20, 30...)

Characteristics	References
Rail support bracket	**NSYFB45**

Combined support bracket

NSYETF

- Allow the installation of a DIN rail and an earthing strip on different planes, to minimise the cable radiuses.
- Material: Zinc-coated steel
- Insallation: Spacial SF: Directly on the structure and/or using mounting plates
  Spacial SM: On the bottom adjustment rails and/or on mounting plates



Supply:
Ten combined support brackets and fixing elements.
Referenceby unit. Order by multiples of 10 (10, 20, 30...)

Characteristics	References
Combined support bracket	**NSYETF**

Terminal-block support bracket

NSYEDCO

- They allow the mounting of a DIN rail.
- Tilted to 45°.
- Material: Treated steel



Telequick

Supply:
Two lugs and fixings

Characteristics	References
Terminal-block support bracket	**NSYEDCO**

Combined fixing lugs for the earthing strip

NSYEDCOC

- They allow the mounting of an earth collector rail and a DIN rail.
- Tilted to 30°.
- Earthing strip, ref. **NSYECB1M153**. See page 305.



Telequick

Supply:
Two fixing lugs and fixing elements

Characteristics	References
Combined fixing lugs for the earthing strip	**NSYEDCOC**

Combined support bracket (vertical)

DZ5MS10

- Allow the installation of a DIN rail and an earthing strip on different planes, to minimise the cable radiuses.
- Material: Zinc-coated steel
- Installation: Spacial SF/SM: Directly on the vertical structure and/or using mounting plates

Supply:
10 brackets

Characteristics	References
Combined support bracket (vertical)	**DZ5MS10**

Clicked support plate

AX2DL01

- For screw mounted equipment.
- For mounting on 35 mm symmetric and double profile DIN rails or Telequick mounting plate.
- Material: Zinc-plate coated



Telequick

Supply:
Ten units and fixing elements.
Reference by unit. Order by multiples of 10 (10, 20, 30...)

Characteristics	References
Clicked support plate, 44 x 65 - 9 screws	**AX2DL01**
Clicked support plate, 49 x 65 - 4 screws	**AX2DL02**

Bracket for fixing control units (Ø 22)

DX1AP52

- To mount any 22 mm diameter device directly on mounting plates.



Telequick

Supply:
Ten units and fixing elements.
Reference by unit. Order by multiples of 10 (10, 20, 30...)

Characteristics	References
Bracket for fixing control units (Ø 22)	**DX1AP52**

10

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Cross rails and profiles for floorstanding enclosures

SM | SMX | SF | SFX | SD | SDX

Telequick

In the Spacial SF, SM, SFX and SMX enclosures, it is possible to create a fixing at any point of the inner volume, providing mounting planes with different widths, heights and depths. In the case of the Spacial SM, it may be necessary to install vertical/horizontal adaptation profiles and 40 mm universal cross rails (one row).

New

Four types of cross rails are available to create fixing points:
- Universal cross rails (see page 254)
- Quick fixing cross rails (see page 255)
- Integrated cross rails (see page 256) New
- light cross rails (see page 256)

Universal, quick fixing and integrated cross rails are available in 3 sizes:
- 40 mm (1 row)
- 65 mm (2 rows)
- 90 mm (3 rows)



Cross rails for specific applications are also available:
- Cross rails for heavy loads (see page 257) to be fixed on the bottom part of of the enclosure or to be associated with a "heavy load kit" (see page 260) to be used at any height in the enclosure
- Cross rails fo Lütze chassis (see page 257)



Combination examples



Spacial SF and SFX:
The cross rails can be fixed to the structure and among each other, offering multiple possibilities.



The quick fixing cross rails can be fixed directly to the structure, quickly and easily.
Spacial SF and SFX*:
- They clip onto the structure and are fixed by M6 self-tapping screws, or optionally with M6 caged nuts.

Spacial SM:
- Possibility of clipping onto the adaptation profile or another cross rail.
- Fixing by means of M6 self-tapping screws.
- Fixing by means of M6 caged nuts.

* In enclosures Spacial SFX is not possible to mount it in depth.



Universal cross rails and integrated cross rails can be simultaneously mounted at the same height, on all the sides of the enclosure.
To perform this type of installation in a Spacial SM enclosure, the vertical adaptation profile and the vertical 40 mm universal cross rail (one row) are required, mounted in the back of the enclosure.



Quick fixing cross rails can be used to support equipments at the back of the enclosure or be fixed every 25 mm on two cross rails (universal or integrated) in vertical position.



40 mm wide universal and integrated cross rails can be used as uprights, adjustable every 25 mm in depth. They enable the fixing of diverse equipment supports and are adjustable every 25 mm in height.

Spacial SF:
Universal cross rails and integrated cross rails can be mounted in vertical position.



The main fixing point to the quick fixing cross rails is the 5.2 mm drill hole for M6 self-tapping screw, although they can also receive M6 and M8 caged nuts.

10

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Cross rails for floor-standing enclosures

SM SMX SF SFX SD SDX Universal cross rails

Telequick

- Used for the creation of structures inside the enclosure.
- Cross rails available in three sizes:
  40 mm (one row), 65 mm (two rows) and 90 mm (three rows).
- Each row is perforated every 25 mm with a 5.2 mm diameter hole and a 11x13 mm cutout which enables fixing by means of M6 self-tapping screws, ref **NSYST30M6S**.
- Equipment are fixed by means of caged nuts or self-tapping screws.
- Material: Zinc-coated steel
- Thickness: 15/10^{e} mm

Fixing to the structure:
Fixing accordingly to uprights axis.
Possibility to mount cross rails simultaneously on all sides, at the same height of the enclosure.

Comment:
(1) For vertical assembly only.
(2) Cross rails only for fixing cables.
(3) These cross rails have not been sized to be used in the width, depth or height of the enclosure, but to be mounted in other positions or in between cross rails.
Dimensions see page 311

Supply:
Two cross rails, four supports for cross rails and fixing elements


NSYSUCR4030

Characteristics	Width of the cross rails (mm)	H / L / P (Dn) of cubicle (mm)	Maximum load by rail (kg)	References
Universal cross rails	40 (1 row)	300	70	**NSYSUCR4030**
Universal cross rails	40 (1 row)	400	60	**NSYSUCR4040**
Universal cross rails	40 (1 row)	500	60	**NSYSUCR4050**
Universal cross rails	40 (1 row)	600	50	**NSYSUCR4060**
Universal cross rails	40 (1 row)	700 (3)	50	**NSYSUCR4070**
Universal cross rails	40 (1 row)	800	40	**NSYSUCR4080**
Universal cross rails	40 (1 row)	900 (3)	40	**NSYSUCR4090**
Universal cross rails	40 (1 row)	1000	30	**NSYSUCR40100**
Universal cross rails	40 (1 row)	1100 (3)	30	**NSYSUCR40110**
Universal cross rails	40 (1 row)	1200	20	**NSYSUCR40120**
Universal cross rails	40 (1 row)	1400	(1)	**NSYSUCR40140**
Universal cross rails	40 (1 row)	1600	(1)	**NSYSUCR40160**
Universal cross rails	40 (1 row)	1800	(1)	**NSYSUCR40180**
Universal cross rails	40 (1 row)	2000	(1)	**NSYSUCR40200**
Universal cross rails	40 (1 row)	2200	(1)	**NSYSUCR40220**
Universal cross rails	65 (2 rows)	300	110	**NSYSUCR6530**
Universal cross rails	65 (2 rows)	400	100	**NSYSUCR6540**
Universal cross rails	65 (2 rows)	500	90	**NSYSUCR6550**
Universal cross rails	65 (2 rows)	600	80	**NSYSUCR6560**
Universal cross rails	65 (2 rows)	800	70	**NSYSUCR6580**
Universal cross rails	65 (2 rows)	1000	50	**NSYSUCR65100**
Universal cross rails	65 (2 rows)	1200	50	**NSYSUCR65120**
Universal cross rails	65 (2 rows)	1400	(1)	**NSYSUCR65140**
Universal cross rails	65 (2 rows)	1600	(1)	**NSYSUCR65160**
Universal cross rails	65 (2 rows)	1800	(1)	**NSYSUCR65180**
Universal cross rails	65 (2 rows)	2000	(1)	**NSYSUCR65200**
Universal cross rails	65 (2 rows)	2200	(1)	**NSYSUCR65220**
Universal cross rails	90 (3 rows)	300	130	**NSYSUCR9030**
Universal cross rails	90 (3 rows)	400	120	**NSYSUCR9040**
Universal cross rails	90 (3 rows)	500	120	**NSYSUCR9050**
Universal cross rails	90 (3 rows)	600	110	**NSYSUCR9060**
Universal cross rails	90 (3 rows)	700 (3)	110	**NSYSUCR9070**
Universal cross rails	90 (3 rows)	800	100	**NSYSUCR9080**
Universal cross rails	90 (3 rows)	900 (3)	100	**NSYSUCR9090**
Universal cross rails	90 (3 rows)	1000	70	**NSYSUCR90100**
Universal cross rails	90 (3 rows)	1100 (3)	70	**NSYSUCR90110**
Universal cross rails	90 (3 rows)	1200	70	**NSYSUCR90120**
Universal cross rails	90 (3 rows)	1400	(1)	**NSYSUCR90140**
Universal cross rails	90 (3 rows)	1600	(1)	**NSYSUCR90160**
Universal cross rails	90 (3 rows)	1800	(1)	**NSYSUCR90180**
Universal cross rails	90 (3 rows)	2000	(1)	**NSYSUCR90200**
Universal cross rails	90 (3 rows)	2200	(1)	**NSYSUCR90220**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Cross rails for floor-standing enclosures

SM SMX SF SFX SD SDX Quick fixing cross rails

Telequick

NSYSQCR4040

- Used for the creation of structures inside the enclosure.
- Cross rails available in three sizes:
  40 mm (one row), 65 mm (two rows) and 90 mm (three rows).
- Each row is perforated every 25 mm with a 5.2 mm diameter hole and a 11x13 mm cutout which enables fixing by means of M6 self-tapping screws, ref **NSYST30M6S**.
- Equipment are fixed by means of caged nuts or self-tapping screws.
- Material: Zinc-coated steel
- Thickness: 15/10e mm

Fixing to the structure:
Fixing accordingly to uprights axis.
No possibility to mount two cross rails at the same level of an upright.

Comment:
(1) For vertical assembly only.
(2) Cross rails only for fixing cables.
(3) These cross rails have not been sized to be used in the width, depth or height of the enclosure, but to be mounted in other positions or in between cross rails.
Dimensions see page 311

Supply:
Two cross rails and fixing elements

Characteristics	Width of the cross rails (mm)	H / L / P (Dn) of cubicle (mm)	Maximum load by rail (kg)	References
Quick fixing cross rails	40 (1 row)	400	60	**NSYSQCR4040**
Quick fixing cross rails	40 (1 row)	500	60	**NSYSQCR4050**
Quick fixing cross rails	40 (1 row)	600	50	**NSYSQCR4060**
Quick fixing cross rails	40 (1 row)	800	40	**NSYSQCR4080**
Quick fixing cross rails	40 (1 row)	1000	30	**NSYSQCR40100**
Quick fixing cross rails	40 (1 row)	1200	20	**NSYSQCR40120**
Quick fixing cross rails	65 (2 rows)	400	100	**NSYSQCR6540**
Quick fixing cross rails	65 (2 rows)	500	90	**NSYSQCR6550**
Quick fixing cross rails	65 (2 rows)	600	80	**NSYSQCR6560**
Quick fixing cross rails	65 (2 rows)	800	70	**NSYSQCR6580**
Quick fixing cross rails	65 (2 rows)	1000	50	**NSYSQCR65100**
Quick fixing cross rails	65 (2 rows)	1200	50	**NSYSQCR65120**
Quick fixing cross rails	90 (3 rows)	400	120	**NSYSQCR9040**
Quick fixing cross rails	90 (3 rows)	500	120	**NSYSQCR9050**
Quick fixing cross rails	90 (3 rows)	600	110	**NSYSQCR9060**
Quick fixing cross rails	90 (3 rows)	800	100	**NSYSQCR9080**
Quick fixing cross rails	90 (3 rows)	1000	70	**NSYSQCR90100**
Quick fixing cross rails	90 (3 rows)	1200	70	**NSYSQCR90120**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Cross rails for floor-standing enclosures

Integrated cross rails



30 mm space saving thanks to new fixation mode


Quick mounting, at same level, on all enclosure perimeter

- Used for the creation of structures inside the enclosure.
- Cross rails available in three sizes:
  40 mm (one row), 65 mm (two rows) and 90 mm (three rows).
- Each row is perforated every 25 mm with a 5.2 mm diameter hole and a 11x13 mm cutout which enables fixing by means of M6 self-tapping screws, ref **NSYST30M6S**.
- Equipment are fixed by means of caged nuts or self-tapping screws
- Material: Zinc-coated steel
- Thickness: 15/10e mm

Fixing to the structure:
Fixing is shifted by 30 mm relatively to uprights axis.
Possibility to mount cross rails simultaneously on all sides, at the same height of the enclosure.

Comment:
Dimensions see page 311

Supply:
Two cross rails and fixing elements

NSYSICR4030

Characteristics	Width of the cross rails (mm)	H / L / P (Dn) of cubicle (mm)	Maximum load by rail (kg)	References
Integrated cross rails	40 (1 row)	300	70	**NSYSICR4030** New
Integrated cross rails	40 (1 row)	400	60	**NSYSICR4040** New
Integrated cross rails	40 (1 row)	500	60	**NSYSICR4050** New
Integrated cross rails	40 (1 row)	600	50	**NSYSICR4060** New
Integrated cross rails	40 (1 row)	800	40	**NSYSICR4080** New
Integrated cross rails	40 (1 row)	1000	30	**NSYSICR40100** New
Integrated cross rails	40 (1 rows)	1200	20	**NSYSICR40120** New
Integrated cross rails	65 (2 rows)	300	110	**NSYSICR6530** New
Integrated cross rails	65 (2 rows)	400	100	**NSYSICR6540** New
Integrated cross rails	65 (2 rows)	500	90	**NSYSICR6550** New
Integrated cross rails	65 (2 rows)	600	80	**NSYSICR6560** New
Integrated cross rails	65 (2 rows)	800	70	**NSYSICR6580** New
Integrated cross rails	65 (2 rows)	1000	50	**NSYSICR65100** New
Integrated cross rails	65 (2 rows)	1200	50	**NSYSICR65120** New
Integrated cross rails	90 (3 rows)	300	130	**NSYSICR9030** New
Integrated cross rails	90 (3 rows)	400	120	**NSYSICR9040** New
Integrated cross rails	90 (3 rows)	500	120	**NSYSICR9050** New
Integrated cross rails	90 (3 rows)	600	110	**NSYSICR9060** New
Integrated cross rails	90 (3 rows)	800	100	**NSYSICR9080** New
Integrated cross rails	90 (3 rows)	1000	70	**NSYSICR90100** New
Integrated cross rails	90 (3 rows)	1200	70	**NSYSICR90120** New

SM SF SFX Light cross rails



- **Spacial SF and SFX:** Direct fixing to the structure or between cross rails.
- **Spacial SM:** Fixing by means of adaptation profiles and 40 mm universal cross rails (one row), or between cross rails in any other position.
- Adjustable with a pitch of 25 mm.
- The light cross rails are equipped with a row of drill holes with a diameter of 5.2 mm and a pitch of 25 mm, which allows fixing with an M6 self-tapping screw, ref. **NSYST30M6S**.
- Material: Zinc-coated steel

Comment:
Dimensions see page 311

Supply:
Two light cross rails and fixing elements

NSYSLCR40

Characteristics	Width/Depth (mm)	References
Spacial SF/SFX/SM Light cross rails	400	**NSYSLCR40**
Spacial SF/SFX/SM Light cross rails	500	**NSYSLCR50**
Spacial SF/SFX/SM Light cross rails	600	**NSYSLCR60**
Spacial SF/SFX/SM Light cross rails	800	**NSYSLCR80**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Cross rails for floor-standing enclosures

SF Rails for heavy loads

- They can be mounted with a cable gland plate or with a previously mounted mounting plate.
- Laterally adjustable with a pitch of 25 mm.
- Elongated holes, for adjusting the centre-to-centre distance of the switchgear.
- Fixing to the structure: Directly fixed on the bottom frame of the enclosure
- Thickness: 30/10e mm
- Material: Galvanised steel

Supply:
Two rails for heavy loads and fixing elements

NSYHLCR40

Characteristics	Maximum load (kg)	Depth (mm)	References
Rail for heavy loads	575	400	**NSYHLCR40** New
Rail for heavy loads	525	500	**NSYHLCR50** New
Rail for heavy loads	500	600	**NSYHLCR60** New
Rail for heavy loads	500	700	**NSYHLCR70** New
Rail for heavy loads	475	800	**NSYHLCR80** New

SF Cross rail for Lütze chassis




NSYLCR40

- Cross rail for fixing and adjusting the depth of the Lütze chassis.
- Thickness: 25/10e mm
- Material: Galvanised steel

Supply:
Six cross rails for Lütze chassis and fixingelements

Characteristics	Depth (mm)	References
Cross rail for Lütze chassis	400	**NSYLCR40**
Cross rail for Lütze chassis	500	**NSYLCR50**
Cross rail for Lütze chassis	600	**NSYLCR60**

Support for Lütze chassis




NSYLSUP

Comment:
Dimensions see page 311

- Support for installing Lütze chassis in the back of the enclosure.
- Thickness: 25/10e mm
- Material: Galvanised steel

Supply:
Six supports and fixing elements

Characteristics	References
Spacial SF Support for Lütze chassis	**NSYLSUP**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Profiles for floor-standing enclosures

SM Vertical adaptation profiles

NSYSMVR12

- The vertical adaptation profiles provide fixing points at the entrance to the enclosure.
- Fixing on the screws of the hinge and catches of the lock.
- Allows the depthwise fixing of cross rails, etc.
- Thickness: 15/10e mm
- Material: Zinc-coated steel



Comment:
Dimensions see page 312

Supply:
2 vertical adaptation profiles and fixing screws

Characteristics	Height (mm)	References
Vertical adaptation profiles	1200	**NSYSMVR12**
Vertical adaptation profiles	1400	**NSYSMVR14**
Vertical adaptation profiles	1600	**NSYSMVR16**
Vertical adaptation profiles	1800	**NSYSMVR18**
Vertical adaptation profiles	2000	**NSYSMVR20**

SM Horizontal adaptation profiles

NSYSMHR6

- The horizontal adaptation profiles provide fixing points at the entrance to the enclosure.
- Thickness: 15/10e mm
- Material: Zinc-coated steel



Comment:
Dimensions see page 312

Supply:
2 horizontal adaptation profiles and fixing screws

Characteristics	Width (mm)	References
Horizontal adaptation profiles	600	**NSYSMHR6**
Horizontal adaptation profiles	800	**NSYSMHR8**
Horizontal adaptation profiles	1000	**NSYSMHR10**
Horizontal adaptation profiles	1200	**NSYSMHR12**
Horizontal adaptation profiles	1600	**NSYSMHR16**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Standard supports

SM SF Fixed tray

Options for fixing the tray to the enclosure:
If the tray has the same dimensions as the enclosure:
- Spacial SF: Direct fixing to the structure.
- Spacial SFX: Instalation possible only with universal cross rails, see page 254.
- Spacial SM: Fixing by means of adaptation profiles and 40 mm universal cross rails (1 row) in vertical position.

If the tray is smaller than the dimensions of the enclosure:
- fixing on depth cross rails.
- Depth-adjustable tray with a pitch of 25 mm.

- Provided with cut-outs for improving air circulation inside.
- Material: Steel
- Finish: Painted with epoxy polyester resin
- Colour: RAL 7035 grey
- Maximum load: 150 kg direct fixed to the structure, 40 kg when universal cross rails are used

Supply:
1 fixed tray and fixing elements


NSYFXT6040

Characteristics	Depth (mm)	Width (mm)	References
Fixed tray	400	600	**NSYFXT6040**
Fixed tray	400	800	**NSYFXT8040**
Fixed tray	500	600	**NSYFXT6050**
Fixed tray	500	800	**NSYFXT8050**
Fixed tray	600	600	**NSYFXT6060**
Fixed tray	600	800	**NSYFXT8060**
Fixed tray	800	800	**NSYFXT8080**

SM SF Telescopic rails

Options for fixing the tray to the enclosure:
- Spacial SF: Installation directly on the structure of the enclosure or on universal cross rails.
- Spacial SFX: Instalation possible only with universal cross rails, see page 254.
- Spacial SM: Installation by means of adaptation profiles and 40 mm universal cross rails (1 row) in vertical position, or on horizontal universal cross rails.

The installation of a telescopic tray consists of the following:
- 1 fixed tray.
- 2 telescopic rails.

NSYTTG40

- End-of-travel stop of the rails in open and closed position.
- Material: Zinc-coated steel
- Finish: Painted with epoxy polyester resin
- Maximum load: 25 kg evenly distributed

Supply:
2 telescopic rails and fixing elements

Characteristics	Depth (mm)	Width (mm)	References
Telescopic rails	400	600/800	**NSYTTG40**
Telescopic rails	500	600/800	**NSYTTG50**
Telescopic rails	600/800	600/800	**NSYTTG60**

Handle for telescopic trays

- Designed for easy extraction of the sliding trays.
- Material: Polyamide 6 (black).

Supply:
2 units and fixing elements

NSY1TH

Characteristics	References
Handle for telescopic trays	**NSY1TH**

SM SMX SF SFX Tray cross rails


NSYSUCR4040


NSYSQCR4040

- Allow the installation of fixed trays and telescopic rails. Quick and universal cross rails, see page 254 - 255

Characteristics	Depth (mm)	References
Tray cross rails, Universal cross rail, 40 mm (1 row)	400	**NSYSUCR4040**
Tray cross rails, Universal cross rail, 40 mm (1 row)	500	**NSYSUCR4050**
Tray cross rails, Universal cross rail, 40 mm (1 row)	600	**NSYSUCR4060**
Tray cross rails, Universal cross rail, 40 mm (1 row)	800	**NSYSUCR4080**
Tray cross rails, Quick fixing cross rail, 40 mm (1 row)	400	**NSYSQCR4040**
Tray cross rails, Quick fixing cross rail, 40 mm (1 row)	500	**NSYSQCR4050**
Tray cross rails, Quick fixing cross rail, 40 mm (1 row)	600	**NSYSQCR4060**
Tray cross rails, Quick fixing cross rail, 40 mm (1 row)	800	**NSYSQCR4080**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Heavy load supports

SF Heavy load kit

- 4 parts designed to strengthen installation supports (shelves or cross rails) in case of heavy loads.
- Several kits can be set up in the same enclosure as long as the maximum load of 1000 kg is not exceeded.
- Strengthen the stiffness of the enclosure.
- Supports set up in the depth direction embed cut outs to help secure equipment fixing.
- Material: Steel
- Colour: RAL 7035 grey
- Maximum load: Up to 500 kg

The kit can be used with following rails:
- standard crossrails delivered with Spacial SF,
- quick fixing cross rails **NSYSQCR●●●●**,
- DIN rails **NSYSDR●●** and **NSYDPR●●**,
- **NSYCN●●** rails,
- heavy load cross rails **NSYHLCR●●**.

Comment:
Combination examples
see page 312

Supply:
2 cross rails (front/rear)
+ 2 supports to be mounted according to depth direction

NSYSHLT6040

Characteristics	Depth (mm)	Width (mm)	References
Heavy load kit	400	600	**NSYSHLT6040** New
Heavy load kit	400	800	**NSYSHLT8040** New
Heavy load kit	600	600	**NSYSHLT6060** New
Heavy load kit	600	800	**NSYSHLT8060** New
Heavy load kit	800	600	**NSYSHLT6080** New
Heavy load kit	800	800	**NSYSHLT8080** New

SF Ventilated shelf


NSYDHLT6040

+


NSYSHLT6040

- Ventilation is ensured by two cut-out sizes:
  11 x 13 mm rectangles for fixation on both sides with self- tapping screws,
  40 x 8.5 mm rectangles.
- The ventilated shelf must be fixed in the enclosure with a heavy load kit.
- Material: Steel
- Colour: RAL 7035 grey
- Maximum load: 350 kg

Supply:
1 tray and fixing elements

Characteristics	Tray dimensions W x D x H (mm)	Depth (mm)	Width (mm)	References
Ventilated shelf	500 x 359 x 50	400	600	**NSYDHLT6040** New
Ventilated shelf	700 x 359 x 50	400	800	**NSYDHLT8040** New
Ventilated shelf	500 x 559 x 50	600	600	**NSYDHLT6060** New
Ventilated shelf	700 x 559 x 50	600	800	**NSYDHLT8060** New
Ventilated shelf	500 x 759 x 50	800	600	**NSYDHLT6080** New
Ventilated shelf	700 x 759 x 50	800	800	**NSYDHLT8080** New

SF Partially ventilated shelf


NSYPPHLT6040

+


NSYSHLT6040

- in order to support the maximum load, the shelf must be mounted either in the rear or in the front of the enclosure.
- An intermediary cross rail must be set up in the middle to bear a heavy loads.
- Ventilation is ensured by two cut-out sizes:
  11 x 13 mm rectangles for fixation on both sides with selftapping screws,
  40 x 8.5 mm rectangles.
- The partially ventilated shelf must be fixed in the enclosure with a heavy load kit.
- Material: Steel
- Colour: RAL 7035 grey
- Maximum load: 250 kg



Supply:
1 tray and fixing elements

Characteristics	Tray dimensions W x D x H (mm)	Depth (mm)	Width (mm)	References
Partially ventilated shelf	500 x 325 x 2	400	600	**NSYPPHLT6040** New
Partially ventilated shelf	700 x 325 x 2	400	800	**NSYPPHLT8040** New

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Heavy load supports

SF Plain shelf for battery

NSYPHLT6040

+



NSYSHLT6040

- Painted shelf with rims to avoid potential liquid leakage.
- Electrical continuity is ensured by specific staples.
- Acces and replacement (thus maintenance) are eased by mounting brackets.
- The plain shelf must be fixed in the enclosure with a heavy load kit.
- Material: Steel
- Colour: RAL 7035 grey
- Maximum load: 350 kg



Supply:
1 tray and fixing elements

Characteristics	Tray dimensions W x D x H (mm)	Depth (mm)	Width (mm)	References	
Plain shelf for battery	500 x 300 x 16	400	600	**NSYPHLT6040**	New
Plain shelf for battery	700 x 300 x 16	400	800	**NSYPHLT8040**	New
Plain shelf for battery	500 x 500 x 16	600	600	**NSYPHLT6060**	New
Plain shelf for battery	700 x 500 x 16	600	800	**NSYPHLT6080**	New
Plain shelf for battery	500 x 700 x 16	800	600	**NSYPHLT6080**	New
Plain shelf for battery	700 x 700 x 16	800	800	**NSYPHLT8080**	New

SF Heavy load cross rails

NSYHLCR40

+



NSYSHLT6040

- Can be fixed anywhere in the enclosure with a heavy load kit.
- Free space useful for thermal management.
- Nominal width of cross rails must be 100 mm shorter than the associated heavy load kit width.
- Material: Steel

Supply:
2 cross rails and fixing elements

Characteristics	Associated heavy load kit references	Maximum load (kg)	Nominal width (mm)	References	
Heavy load cross rails	Not usable with heavy load kit	575	400	**NSYHLCR40**	New
Heavy load cross rails	NSYSHLT6040 NSYSHLT6060 NSYSHLT6080	525	500	**NSYHLCR50**	New
Heavy load cross rails	Not usable with heavy load kit	500	600	**NSYHLCR60**	New
Heavy load cross rails	NSYSHLT8040 NSYHLT8060 NSYHLT8080	500	700	**NSYHLCR70**	New
Heavy load cross rails	Not usable with heavy load kit	475	800	**NSYHLCR80**	New

Heavy load supports

Combination examples

- Heavy load kit + Ventilated shelf

- Heavy load kit + Partially ventilated shelf

- Heavy load kit + Plain shelf for battery

- Heavy load kit + Heavy load cross rails

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

S3D S3X PLM Symmetric mounting rail for the wall-mounting enclosures

Telequick

- 2 types: Type A: 35 x 15 mm, Type B: 35 x 7.5 mm
- Material: Zinc-coated steel
- Standards: IEC 715
- Thickness: Type A: 15/10e mm, Type B: 10/10e mm
- Fixing: Fixed to mounting plates or another fixing elements, uprights not included in the supply



Supply:
10 rails and fixings for direct assembling to the structure. References by unit. Order by multiples of 10 units(10, 20, etc.)

NSYSDR30B

Characteristics	Type	Enclosure width (mm)	Rail length (mm)	References
Symmetric mounting rail for the wall-mounting enclosures	B	300	250	**NSYSDR30B**
Symmetric mounting rail for the wall-mounting enclosures	B	400	350	**NSYSDR40B**
Symmetric mounting rail for the wall-mounting enclosures	A	500	450	**NSYSDR50A**
Symmetric mounting rail for the wall-mounting enclosures	A	600	550	**NSYSDR60A**
Symmetric mounting rail for the wall-mounting enclosures	A	800	750	**NSYSDR80A**
Symmetric mounting rail for the wall-mounting enclosures	A	1000	950	**NSYSDR100A**

SM SMX SF SFX SD SDX Symmetric DIN rails forthe floor-standing enclosures

Telequick

- Help ensure horizontal continuity in case of enclosure assembly.
- Rail type: Type A: 35 x 15 mm.
- Material: Zinc-coated steel
- Standards: IEC 715
- Thickness: 15/10e mm
- Fixing: Fixed to the standard or technical upights (see page 251) or directly to the structure



Supply:
10 rails and fixings for direct assembling to the structure. References by unit. Order by multiples of 10 units(10, 20, etc.)

NSYSDR60

Characteristics	Enclosure width (mm)	Rail length (mm)	References
Symmetric DIN rail for the floor-standing enclosures	600	588	**NSYSDR60**
Symmetric DIN rail for the floor-standing enclosures	800	788	**NSYSDR80**
Symmetric DIN rail for the floor-standing enclosures	1000	988	**NSYSDR100**
Symmetric DIN rail for the floor-standing enclosures	1200	1188	**NSYSDR120**

Asymmetric DIN rails for the floor-standing enclosures

Telequick

- Help ensure horizontal continuity in the case of enclosure assembly.
- Material: Zinc-coated steel
- Standards: IEC 715
- Thickness: 15/10e mm
- Fixing: Fixed to the standard or technical upights (see page 251) or directly to the structure



Supply:
10 rails and fixings for direct assembling to the structure. References by unit. Order by multiples of 10 units(10, 20, etc.)

NSYADR60

Characteristics	Enclosure width (mm)	Rail length (mm)	References
Asymmetric DIN rail for the floor-standing enclosures	600	588	**NSYADR60**
Asymmetric DIN rail for the floor-standing enclosures	800	788	**NSYADR80**
Asymmetric DIN rail for the floor-standing enclosures	1000	988	**NSYADR100**
Asymmetric DIN rail for the floor-standing enclosures	1200	1188	**NSYADR120**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Double-profile DIN rails

- They combine the advantages of symmetric and asymmetric rails.
- Quick installation of terminals according to standard DIN 46277/1.
- Material: Zinc-coated steel
- Thickness: 15/10e mm
- Fixing: Fixed to the standard or technical upights (see page 313) or directly to the structure



Telequick

Supply:
10 rails and fixings for direct assembling to the structure. References by unit. Order by multiples of 10 units(10, 20, etc.)

NSYDPR25

Characteristics	Type	Enclosure width (mm)	Rail length (mm)	References
Double-profile DIN rail, for wall-mounting enclosure	W	300	250	**NSYDPR25**
Double-profile DIN rail, for wall-mounting enclosure	W	400	350	**NSYDPR35**
Double-profile DIN rail, for wall-mounting enclosure	W	500	450	**NSYDPR45**
Double-profile DIN rail, for wall-mounting enclosure	W	600	550	**NSYDPR55**
Double-profile DIN rail, for floor-standing enclosure	F	600	588	**NSYDPR60**
Double-profile DIN rail, for wall-mounting enclosure	W	700	650	**NSYDPR65**
Double-profile DIN rail, for wall-mounting enclosure	W	600	750	**NSYDPR75**
Double-profile DIN rail, for floor-standing enclosure	F	600	788	**NSYDPR80**
Double-profile DIN rail, for floor-standing enclosure	F	1000	988	**NSYDPR100**
Double-profile DIN rail, for floor-standing enclosure	F	1200	1188	**NSYDPR120**

Serrated C-shaped rail for heavy loads

- Marked in steps of 25 mm to facilitate switchgear positioning.
- Material: Zinc-coated steel
- Thickness: 20/10e mm



Supply:
2 rails with a length of 2 m

AM1EC200

Characteristics	Rail length (mm)	References
Serrated C-shaped rail for heavy loads	2000	**AM1EC200**

Symmetric C-shaped rails

- Rails for supporting and fixing switchgear on panels and enclosures, formation of chassis, racks and panel reinforcements.
- Material: Galvanised steel
- Fixing: They are fixed to the structure and to one another by means of fixing elements

Comment:
Dimensions see page 313



Supply:
References by unit. Order by multiples of 10 units(10, 20, etc.)

NSYCN20

Characteristics	Rail length (mm)	References
Symmetric C-shaped rails 21x11x10, not perforated	2000	**NSYCN20**
Symmetric C-shaped rails 21x11x10	2000	**NSYCNT20**
Symmetric C-shaped rails 40x20x24, not perforated	2000	**NSYCN40**
Symmetric C-shaped rails 40X20X24	2000	**NSYCNT40**

Combiplas nut for symmetric C-shaped rails

NSYBN206

Characteristics	Rail type	Nuts type	Supply	References
Combiplas nut for symmetric C-shaped rails	C20	M4	100	**NSYBN204**
Combiplas nut for symmetric C-shaped rails	C20	M6	100	**NSYBN206**
Combiplas nut for symmetric C-shaped rails	C40	M4	50	**NSYBN404**
Combiplas nut for symmetric C-shaped rails	C40	M6	50	**NSYBN406**
Combiplas nut for symmetric C-shaped rails	C40	M8	50	**NSYBN408**
Combiplas nut for symmetric C-shaped rails	C60	M6	20	**NSYBN606**
Combiplas nut for symmetric C-shaped rails	C60	M8	20	**NSYBN608**
Combiplas nut for symmetric C-shaped rails	C60	M10	20	**NSYBN610**

Metal sliding nut for symmetric C-shaped rails

NSYB204

Characteristics	Rail type	Nuts type	Supply	References
Metal sliding nut for symmetric C-shaped rails	C20	M4	100	**NSYB204**
Metal sliding nut for symmetric C-shaped rails	C40	M4	100	**NSYB404**
Metal sliding nut for symmetric C-shaped rails	C40	M6	-	**NSYB406**

10

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

2000 mm rails

Symmetric rails

Telequick



- Material: Galvanized steel, zinc-coated steel or aluminium
- Length: 2000 mm

NSYSDR200D

Characteristics	Type	Supply	Perforations	References
Symmetric rail, Galvanized steel	A	20	Perforated	**NSYSDR200D**
Symmetric rail, Galvanized steel	B	20	Perforated	**NSYSDR200BD**
Symmetric rail, Galvanized steel	A	20	Not perforated	**NSYSDR200**
Symmetric rail, Galvanized steel	B	20	Not perforated	**NSYSDR200B**
Symmetric rail, Zinc-coated steel	C	6	Not perforated	**AM1DL201**
Symmetric rail, Aluminium	D	10	Not perforated	**AM1EA200**

Asymmetric DIN rails

Telequick



Supply:
20 rails with a length of 2 m.
References by unit. Order by multiples of 20 units (20, 40, etc.)

- Material: Galvanised steel
- Length: 2000 mm


NSYADR200D

Characteristics	Perforations	References
Asymmetric DIN rail	Perforated	**NSYADR200D**
Asymmetric DIN rail	Not perforated	**NSYADR200**

Double-profile DIN rails

Telequick



Supply:
20 rails with a length of 2 m.
References by unit. Order by multiples of 20 units (20, 40, etc.)

- Material: Galvanised steel
- Length: 2000 mm

NSYDPR200D

Characteristics	Thickness (mm)	Perforations	References
Double-profile DIN rail	15/10[e]	Perforated	**NSYDPR200D**
Double-profile DIN rail	10/10[e]	Perforated	**NSYDPR200T**
Double-profile DIN rail	15/10[e]	Not perforated	**NSYDPR200**

10

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Life Is On Schneider Electric

Rail accessories

Nuts for symmetric rails

AF1GC4

- Clip-on nut.

Supply:
100 nuts

Characteristics	Type	References
Nuts for symmetric rails	M4	**AF1GC4**
Nuts for symmetric rails	M5	**AF1GC5**
Nuts for symmetric rails	M6	**AF1GC6**

Nuts for asymmetric DIN rails, 2000 mm version

DZ5ME5

- Quarter-turn sliding nut.

Supply:
100 nuts

Characteristics	Type	References
Nuts for asymmetric DIN rails, 2000 mm version	M4	**DZ5ME5**
Nuts for asymmetric DIN rails, 2000 mm version	M5	**DZ5ME8**
Nuts for asymmetric DIN rails, 2000 mm version	M6	**DZ5ME9**

Nuts for double-profile DIN rails

AF1CF34

- Quarter-turn sliding nut.

Supply:
100 nuts

Characteristics	Type	References
Nuts for double-profile DIN rails	M3 + M4	**AF1CF34**
Nuts for double-profile DIN rails	M5 + M6	**AF1CF56**

Nuts for serrated C-shaped rails

NSYSNM6

NSYSNSM6

- Quarter-turn sliding nuts.

Supply:
10 nuts

Characteristics	Type	References
M6 quarter-turn sliding nut	M6	**NSYSNM6**
M8 quarter-turn sliding nut	M8	**NSYSNM8**
M6 quarter-turn serrated sliding nut	M6	**NSYSNSM6**
M8 quarter-turn serrated sliding nut	M8	**NSYSNSM8**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Connectors for symmetric C-shaped rails

- The connectors enable the formation of chassis or frames and structures for fixing switchgear, in any position inside the enclosures, allowing the fixing of DIN rails or other elements.
- See symmetric C-shaped rails.

EMA connectors

NSYEMA20

- To joint two symmetric C-shaped rails, C20 and C40 types, at right angles; They can also be used to obtain a T-shaped assembly.
- Material: Zinc-coated steel
- Thickness: 20/10[e] mm



Comment:
Dimensions
see page 314

Supply:
20 units. References by unit. Order by multiples of 20 units (20, 40, 60, etc.)

Characteristics	References
EMA connectors	**NSYEMA20**
EMA connectors	**NSYEMA40**

EVA connectors

NSYEVA20

- To join two symmetric C-shaped rails, C20 and C40 types, forming an overlapping assembly with plane change, or also at right angles for the formation of spacers or supports at a different level.
- Material: Zinc-coated steel



Comment:
Dimensions
see page 314

Supply:
20 units. References by unit. Order by multiples of 20 units (20, 40, 60, etc.)

Characteristics	References
EVA connectors	**NSYEVA20**
EVA connectors	**NSYEVA40**

UCA connectors

NSYUCA22

- To join symmetric C-shaped rails, types C20 and C40, forming a cross-shaped assembly of three rails located on the same plane, for example inside a frame.
- Material: Zinc-coated steel



Comment:
Dimensions
see page 315

Supply:
20 units. References by unit. Order by multiples of 20 units (20, 40, 60, etc.)

Characteristics	References
UCA connectors	**NSYUCA22**
UCA connectors	**NSYUCA44**

UTA connectors

NSYUTA22

- To create a T-shaped assembly between two symmetric C-shaped rails, C20 and C40 types, especially recommended for forming crossbars on chassis and frames.
- The **UTA42** connectors type allows C20 rails to be joined with C40 rails.
- Material: Zinc-coated steel



Comment:
Dimensions
see page 315

Supply:
20 units. References by unit. Order by multiples of 20 units (20, 40, 60, etc.)

Characteristics	References
UTA connectors	**NSYUTA22**
UTA connectors	**NSYUTA42**
UTA connectors	**NSYUTA44**

10

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Connectors for symmetric C-shaped rails

ECA connectors

NSYECA22

- To form a cross-shaped assembly with two symmetric C-shaped rails, C20 and C40 types, located perpendicularly on different planes.
- The **ECA42** connector type makes it possible to join C20 rails with C40 rails.
- Material: Zinc-coated steel



Comment:
Dimensions
see page 315

Supply:
20 units. References by unit. Order by multiples of 20 units (20, 40, 60, etc.)

Characteristics	References
ECA connectors	**NSYECA22**
ECA connectors	**NSYECA42**
ECA connectors	**NSYECA44**

UR connectors

NSYUR20

- For rectilinear joining of symmetric C-shaped rails.
- Recommended when the standard length is not sufficient or for maximising fractions.
- Material: Zinc-coated steel



Comment:
Dimensions
see page 315

Supply:
20 units. References by unit. Order by multiples of 20 units (20, 40, 60, etc.)

Characteristics	References
UR connectors	**NSYUR20**
UR connectors	**NSYUR40**
UR connectors	**NSYUR60**

UT connectors

NSYUT20

- To form T-shaped assemblies between symmetric C-shaped rails.
- They are used to form crossbars on frames and structures.
- Material: Zinc-coated steel



Comment:
Dimensions
see page 315

Supply:
20 units. References by unit. Order by multiples of 20 units (20, 40, 60, etc.)

Characteristics	References
UT connectors	**NSYUT20**
UT connectors	**NSYUT40**
UT connectors	**NSYUT60**

EN connectors

NSYEN20

- To create L-shaped assemblies with plane change in the symmetric C-shaped rails, between them or with any other section.
- Material: Zinc-coated steel



Comment:
Dimensions
see page 315

Supply:
20 units. References by unit. Order by multiples of 20 units (20, 40, 60, etc.)

Characteristics	References
EN connectors	**NSYEN20**
EN connectors	**NSYEN40**
EN connectors	**NSYEN60**

10

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Spacers

Hexagonal spacers



- Hexagonal spacers for raising switchgear, mounting plates, etc. They can be linked together to achieve variable heights with gradual elevation.
- Their assembly requires M6 or M8 caged nuts.
- Material: Zinc-coated steel
- Installation: If used to raise a mounting plate, the maximum load of the mounting plate is decreased

Supply:
100 hexagonal connectors.
References by unit.
Order by multiples of 100 units (100, 200, 300, etc.)

NSYE1025

Characteristics	Thread type	Spacer height (mm)	References
Hexagonal spacers	M5	10	**NSYE1025**
Hexagonal spacers	M5	15	**NSYE1525**
Hexagonal spacers	M5	20	**NSYE2025**
Hexagonal spacers	M6	10	**NSYEX106**
Hexagonal spacers	M6	12	**NSYEX126**
Hexagonal spacers	M6	14	**NSYEX146**
Hexagonal spacers	M6	16	**NSYEX166**
Hexagonal spacers	M6	18	**NSYEX186**
Hexagonal spacers	M6	20	**NSYEX206**
Hexagonal spacers	M6	30	**NSYEX306**
Hexagonal spacers	M6	40	**NSYEX406**
Hexagonal spacers	M6	50	**NSYEX506**
Hexagonal spacers	M6	100	**NSYEX1006**
Hexagonal spacers	M8	15	**NSYEX158**
Hexagonal spacers	M8	20	**NSYEX208**
Hexagonal spacers	M8	30	**NSYEX308**
Hexagonal spacers	M8	40	**NSYEX408**
Hexagonal spacers	M8	50	**NSYEX508**
Hexagonal spacers	M8	60	**NSYEX608**
Hexagonal spacers	M8	100	**NSYEX1008**

ETU modular spacers



Note:
Combination of spacers
see page 316

- Modular spacers for installing devices or rails at a different level from that achieved with the basic chassis or mounting plate.
- Material: Zinc-coated steel

Supply:
20 units. References by unit.
Order by multiples of 20 units (20, 40, 60, etc.)

NSYETU48

Characteristics	A (mm)	B (mm)	References
ETU modular spacers	48	25	**NSYETU48**
ETU modular spacers	58	25	**NSYETU58**
ETU modular spacers	79	55	**NSYETU79**
ETU modular spacers	118	55	**NSYETU118**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Life Is On Schneider Electric

19" Chassis

S3D S3X 19" fixed chassis for wall-mounting enclosure

- 19" fixed chassis comprising 2 19" uprights with fixing.
- Adjustable in depth by fixing on the step slides in accessories.
- Material: Galvanized steel
- Thickness: 20/10e mm
- Maximum load: 3 kg per unit

NSYVDM8UF

Characteristics	Enclosure dimensions (mm)		Unit number	References
	Height	Width		
19" fixed chassis for wall-mounting enclosure	400	600	8	**NSYVDM8UF**
19" fixed chassis for wall-mounting enclosure	600	600	12	**NSYVDM12UF**
19" fixed chassis for wall-mounting enclosure	800	600	17	**NSYVDM17UF**
19" fixed chassis for wall-mounting enclosure	1000	600	21	**NSYVDM21UF**

S3D S3X 19" swing chassis for wall-mounting enclosure

- 19" swing chassis opening to 120° with closure by 3 mm double bar insert.
- Material: Steel
- Finish: Structured finish, epoxy polyester powder
- Colour: RAL 7035 grey
- Maximum load: 3 kg per unit

NSYVDM7UP

Characteristics	Enclosure dimensions (mm)		Unit number	References
	Height	Width		
19" swing chassis for wall-mounting enclosure	400	600	7	**NSYVDM7UP**
19" swing chassis for wall-mounting enclosure	600	600	11	**NSYVDM11UP**
19" swing chassis for wall-mounting enclosure	800	600	16	**NSYVDM16UP**
19" swing chassis for wall-mounting enclosure	1000	600	20	**NSYVDM20UP**
19" swing chassis for wall-mounting enclosure	1000	800	20	**NSYVDM20U8P**
19" swing chassis for wall-mounting enclosure	1200	800	25	**NSYVDM25U8P**

Fixings for 19" rack

- They allow 19" accessories to be mounted.
- Caged nut compatible with 8.5 x 8.5 mm and 9.5 x 9.5 mm holes.

NSYGFR95M63

Characteristics	Batch of	References
M6 screws + washers + nuts	30	**NSYGFR95M63**
M6 x 16 screws and washers	50	**NSYGFR166P**
M6 caged nuts	100	**NSYCN9M625**
M6 screws + washers + nuts	50	**NSYGFR95M65**
M5 screws + washers + nuts	50	**NSYGFR95M55**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Nuts and screws overview

Characteristics	Clip-on nuts		Combiplas slide nuts					Screws with captive washer		
			Combiplas nut			Metal sliding nut		Hexagonal head		
Usage	For Telequick mounting plates		C - shaped rail - 20/40/60 mm					All nuts		
Type	Supply	References	Rail type	Supply	References	Supply	References	Models	Supply	References
M3	**100**	**AF1EA3**	-	-	**-**	-	**-**	-	-	**-**
M4	**100**	**AF1EA4**	C20	**100**	**NSYBN204**	**100**	**NSYB204**	M4 x 10 mm	**100**	**AF1VA410**
M4	-	**-**	C40	**100**	**NSYBN404**	**100**	**NSYB404**	M4 x 16 mm	**100**	**AF1VA416**
M5	**100**	**AF1EA5**	-	-	**-**	-	**-**	M5 x 12 mm	**100**	**AF1VA512**
M5	-	**-**	-	-	**-**	-	**-**	M5 x 18 mm	**100**	**AF1VA518**
M6	**100**	**AF1EA6**	C20	**100**	**NSYBN206**	-	**-**	M6 x 12 mm	**100**	**AF1VA612**
M6	-	**-**	C40	**100**	**NSYBN406**	-	**-**	M6 x 18 mm	**100**	**AF1VA618**
M6	-	**-**	C60	**100**	**NSYBN606**	**100**	**NSYB406**	-	-	**-**
M8	-	**-**	C40	**100**	**NSYBN408**	-	**-**	M8 x 20 mm	**100**	**AF1VC820**
M8	-	**-**	C60	**100**	**NSYBN608**	-	**-**	-	-	**-**
M10	-	**-**	C60	**100**	**NSYBN610**	-	**-**	-	-	**-**

Supply:
References by unit. Order by multiples of the units specified in the supply.

Characteristics	Fixings and nuts for serrated uprights					Nuts for uprights and cross rails			
	Fixing brackets		1/4 turn		Serrated 1/4 turn	 Removable nut		Cage nut	
Usage	2 x serrated mounting uprights for floor-standing enclosures								
Type	Supply	References	Supply	References	References	Supply	References	Supply	References
M4	**4**	**NSYMFB**	-	**-**	**-**	-	**-**	-	**-**
M5	-	**-**	-	**-**	**-**	-	**-**	-	**-**
M6	-	**-**	**10**	**NSYSNM6**	**NSYSNSM6**	**50**	**NSYCNM6**	**50**	**NSYCNFM6**
M8	-	**-**	**10**	**NSYSNM8**	**NSYSNSM8**	**50**	**NSYCNM8**	**50**	**NSYCNFM8**
-	-	**-**	-	**-**	**-**	-	**-**	-	**-**
-	-	**-**	-	**-**	**-**	-	**-**	-	**-**

Supply:
References by unit. Order by multiples of the units specified in the supply.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

	Torx screws			Self-tapping screw			Fixings and nuts for aluminium uprights			
							Sliding nuts	Brass nuts		
	Nuts and 6 mm Spacial enclosures holes						Mounting uprights for wall-mounting enclosures			
										
	Models	Supply	References	Models	Supply	References	Supply	References	Supply	References
	-	-	-	-	-	-	-	-	4	NSYAMCSF
	-	-	-	-	-	-	100	NSYNM4		
	-	-	-	-	-	-	-	-		
	-	-	-	M5 x 13 mm	100	NSYS13M5HS	100	NSYNM5		
	-	-	-	M5 x 16 mm	100	NSYS16M5HS	-	-		
	T30 M6 x 16 mm	100	NSYST30M6	M6 x 16 mm	100	NSYS16M6HS	100	NSYNM6		
	T30 M6 x 12 mm self-tapping	100	NSYST30M6S	-	-	-	-	-		
		-	-	-	-	-	-	-		
	T40 M8 x 16 mm	100	NSYST40M8	-	-	-	-	-		
	-	-	-	-	-	-	-	-		
	-	-	-	-	-	-	-	-		

	Flat nuts for standard uprights		Clip nut for symmetric DIN rail		Quarter turn nut for double profile DIN rail			Quarter turn nut for asymmetric DIN rail	
									
	2 x standard mounting uprights for floor-standing enclosures		35 x 15 mm symmetric DIN rail		35 mm double profile DIN rail			35 mm asymmetric DIN rail	
	Supply	References	Supply	References	Models	Supply	References	Supply	References
	-	-	100	AF1CG4	-	-	-	100	DZ5ME5
	-	-	100	AF1CG5	-	-	-	100	DZ5ME8
	50	NSYFNM6	100	AF1CG6	-	-	-	100	DZ5ME9
	50	NSYFNM8	-	-	-	-	-	-	-
	-	-	-	-	M3 + M4	100	AF1CF34	-	-
	-	-	-	-	M5 + M6	100	AF1CF56	-	-

10

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Multiple cable entries overview

• For details, type the reference in the search engine of www.se.com.

Characteristics	FlexiCable	Multi-A	Multi-C	Multi-R	Multi-CS	Multi-T
	Full membrane cable gland plate.	FL13 and FL21 type membranes.	Circular connector-free entries.	Rectangular connector-free entries.	Modular entry allowing the passing of up to 48 pre-assembled cables.	FL21-type membranes.
Material	HCE for membrane. Steel for frame	TPE, SBS, SEBS and PP co-polymer - Halogen free	Polyamide	Polyamide	Reinforced polypropylene and TPE. Halogen free	TPE
Colour	Frame: RAL 7035 grey	RAL 7035 grey	-	-	Black	RAL 7035 grey
Cable entry material	Soft membrane	Combined	Soft membrane			
Cable glands to be fitted	No	Optional: Specific cable clamp ref. **NSYAECPFLACA●●** to be used	No	No	No	No
Installation possibilities	Replaces cable gland plate (S3D) or directly on enclosure	On cable gland plate adapter or directly on enclosure	On modified cable gland plate or directly on enclosure	On cable gland plate with special cut-out or directly on enclosure	On cable gland plate adapter or directly on enclosure	
Flexibility of the installation	Full	Medium	Medium	Medium	Full	Medium
Reversibility	Medium	Medium	Full	Full	Full	Medium
Ingress protection rating	IP55 according to IEC 60529	IP65 according to IEC 60529	IP65 according to IEC 60529	IP65 according to IEC 60529	IP65 according to IEC 60529	IP66 according to IEC 60529*
Cable retention	Low	High with cable clamp, (up to 18 daN)	Medium	Medium	Medium	Low
Cable diameter (mm)	Up to 26	From 13 to 30	From 3 to 15.9	From 4.3 to 15.9	Up to 22	From 5 to 60
Cable Installation time	Fast	Medium	Fast	Fast	Fast	Fast
Quantity of cables to be fitted for a given surface	+++	++	++	++	+++	++
Cable entries for cables with connectors	No	No	No	No	Yes	No
Cut-out dimensions (mm)	178 x 63 to 478 x 63	134 x 52 (FL13) 214 x 90 (FL21)	Ø 50.5 Ø 63.5	112 x 36	112 x 36	214 x 90 (FL21)
External dimensions (mm)	245 x 130 to 545 x 130 or 495 x 220	216 x 84	Ø 58 Ø 71	146 x 14 x 58	148 x 58 x 15 148 x 58 x 18	214 x 88
Certificates	Tested on short-circuit effect 250 A, 25 kA following IEC 61439-1	Cable anchorage pull test: EN 50262. Long term UV- resistance: ASTM G 154-06	UL 94 V-0	UL 94 V-0	• UL 94 V-0 • Fire resistance: V0	UL 94 V-0
Fire resistance	650°C	750°C	650°C	650°C	-	650°C
Temperature range	-	-40°C to +85°C	-	-	-30°C to +100°C	-40°C to +100°C
References	See **page 280** **NSYTL●●●**	See **page 280** **NSYAECPFLA●●**	See **page 280** **NSYTSAM●●●●●**	See **page 281** **NSYTSA24●●●●**	See **page 282** **NSYDCD24●●**	See **page 281** **NSYAECPFL●●●**

* IP65 for **NSYAECPFLBP**.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Multiple cable entries overview

• For further information please have a look on the next page

Characteristics	Prisma	Multi-F	Multi-CF	Multi-CR	Multi-H
			New		
	FL21 or rectangular.	FL13 and FL21 pre-configured flanges.	Cable entry for protected cables.	Cable entries with dies for cables equipped with connectors.	FL21 insulated flange with ISO knockouts.
Material	Insulating material	Fibreglass-reinforced polypropylene and TPE - Calogen Free	Reinforced polypropylene and TPE. Halogen free	Polyamide	Polycarbonate glass-fiber reinforced
Colour	RAL 9001	RAL 7035 grey	Black	-	RAL 7035 grey
Cable entry material	Soft membrane			Hard plastic	
Cable glands to be fitted	No	No	No	Yes	Yes
Installation possibilities	On cable gland plate adapter or directly on enclosure				
Flexibility of the installation	Medium	Medium	Full	Low	Low
Reversibility	Medium	Medium	Full	Medium	Medium
Ingress protection rating	IP55 according to IEC 60529	IP65 according to IEC 60529	IP65 according to IEC 60529	IP54 according to IEC 60529	IP65 according to IEC 60529
Cable retention	Low	Low	Medium	High (with fastener)	High (with cable clamp)
Cable diameter (m	From 28 to 60 (FL21) From 7 to 72 (rectangular)	From 16 to 50	From 9 to 30	From 3 to 31	From 12 to 25
Cable Installation time	Fast	Fast	Fast	Slow	Slow
Quantity of cables to be fitted for a given surface	++	++	+++	++	++
Cable entries for cables with connectors	No	No	Yes	Yes	No
Cut-out dimensions (mm)	214 x 90 (FL21)	134 x 52 (FL13) 214 x 90 (FL21)	112 x 36	36 x 91 (NSYDCE168) 36 x 112 (NSYDCE24•)	214 x 90 (FL21)
External dimensions (mm)	216 x 84	From 134 x 52 to 214 x 90	148 x 60 x 10	146 x 58	215 x 85
Certificates	-	• UL 94-HB • Test standard EN 60529:1991 + A1 EN 60670-1:2005, EN 50262:1998 EMKO-TUI (03-SEC) FI001/84. Semko report 816003 • UL-approved materials	• UL 94-HB • Fire resistance: V0	-	UL 94 V-1
Flame resistance	-	-	-	650 °C	750 °C
Temperature range	-	-20°C to +125°C "Pop-out" membranes only.	-30°C to +70°C	-40°C to +80°C	• For normal operation: -40°C to +80°C • For a short time: -40°C to +120°C
References	See **page 284** **088●●**	See **page 281** **NSYAECPKFL●●**	See **page 283** **NSYTLK24●●**	See **page 282** **NSYDCE●●●●**	See **page 281** **NSYTSAKFL**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Simple cable entries overview

• For details, type the reference in the search engine of www.se.com.

Characteristics	Simple-1	Simple-2	Simple-3	Simple-4	Simple-5
	Mixed membrane entries for enclosure thickness 20/10^{e} - 32/10^{e} mm.	PVC adjustable coneshaped entries for enclosure thickness 30/10^{e} - 32/10^{e} mm.	Quick cable entries for enclosure thickness 10/10^{e} - 40/10^{e} mm (5/10^{e} - 20/10^{e} mm for ref. IMT36179).	PVC adjustable coneshaped entries for PG tubes or for enclosure thickness 12/10^{e} - 15/10^{e} mm.	ISO cable gland.
Material	SBS	PVC	EPDM plastic	PVC	PA6 Polyamide, neoprene gasket
Colour	RAL 7035 grey or RAL 9010 white	-	Grey cable entries: NCS 5500 Black cable entries: NCS 9000	Black	RAL 7035 grey
Cable entry material	Soft membrane		Combined		
Cable glands to be fitted	Not applicable				
Installation possibilities	On cable gland plate or directly on enclosure				
Flexibility of the installation	Low				
Reversibility	Medium				
Ingress protection rating	IP55 according to IEC 60529	IP55 according to IEC 60529	IP67 according to IEC 60529	IP55 according to IEC 60529	IP68 according to IEC 60529
Cable retention	Low	Low	Medium	Low	High
Cable diameter (mm)	From 20 to 40	From 5 to 87	From 12 to 50	From Ø 13 to Ø 44	From 12 to 40
Cable Installation time	Fast	Fast	Fast	Fast	Slow
Quantity of cables to be fitted for a given surface	+	+	+	+	+
Cable entries for cables with connectors	No	No	No	No	No
Cut-out dimensions (mm)	Various circular hole diameters according to cable diameter				
External dimensions (mm)	From Ø 23 to 44	From Ø 25 to 98	From Ø 12.5 to 50.7	52	From Ø 15 to 46
Certificates	-	-	-	-	Glow wire resistance: 960°C
Standard	-	-	-	-	Compliance with VDE, UL and CSA
Flame resistance	750°C	-	750°C	-	750 °C
References	See **page 285 IMT36●●●/I SM71●●●**	See **page 285 NSYECPC●●**	See **page 286 IMT361●●**	See **page 286 NSYEC●**	See **page 286 ISM71●●●**

Characteristics	Synthetic snap in cable gland	Stainless steel cable gland with lamellar insert
	New	New
	Without thread. Easy assembly and disassembly. Suitable for walls from 0.5 to 4 mm thick.	Lamellar technology provides excellent resistance to traction as well as excellent torsional protection. For outdoor use, or for aggressive environments.
Material	PA6 Polyamide, neoprene gasket	Stainless steel AISI 304L or AISI 316L, neoprene gasket
Colour	RAL 7035 grey, RAL 7001, RAL 9005. Other colours on demand	-
Cable entry material	Non armoured	Non armoured
Installation possibilities	On cable gland plate or directly on enclosure	
Flexibility of the installation	Low	
Reversibility	Medium	
Ingress protection rating	IP68	IP68
Cable retention	High	High
Cable diameter (mm)	From 16 to 40	From 12 to 40
Cable Installation time	Slow	Slow
Quantity of cables to be fitted for a given surface	+	+
Cable entries for cables with connectors	No	No
Thread type	Metric EN 60423, other types are available on demand	Metric EN 60423
Cut-out dimensions (mm)	Various circular hole diameters according to cable diameter	
External dimensions (mm)	From Ø 22 to 46	From Ø 14 to 43
Certificates	UL 94 V-2	UL 94 V-2
Standard	DIN EN 62444, UL 514B, UL 514B§8.26.7	DIN EN 62444, UL 514
Temperature range	-20°C to + 100°C	-20°C to + 100°C
References	See **page 287, NSYCGSP●●**	See **page 287 NSYCGX●●●**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Simple cable entries overview

Characteristics	Multi-cable disc		Cable gland gasket	Blanking plug	Transport plug
	It is possible to pass several cables through a single cable gland using the multi-cable bushing.			It is screwed into the cable gland's plate.	It is installed to block the cable gland during transport or during maintenance operations.
Material	EDPM rubber		EDPM rubber	PA6	PA6
Colour	Black		Black	RAL 7035 grey	Black
Ingress protection rating	-		IP68	-	-
Standards	-		-	-	-
Other characteristics	-		-	-	-
Supply	Batch of 40 (M16 and M20), 20 (M25 and M32)		Batch of 100 (M12 to M20), 50 (M25 and M32), 25 (M40)	Pack of 40 plugs (M12 to M20), 20 plugs (M25 and M32), 10 plugs (M40)	Pack of 40 plugs (M16 to M20), pack of 20 (M25 and M32), pack of 10 (M40)
Ø	Number / Ø (mm)	References	References	References	References
M12	-	**-**	**IMT36151**	**IMT36161**	**-**
M16	2 x Ø 4	**IMT36157**	**IMT36152**	**IMT36162**	**IMT36167**
M20	3 x Ø 4	**IMT36158**	**IMT36153**	**IMT36163**	**IMT36168**
M25	4 x Ø 5	**IMT36159**	**IMT36154**	**IMT36164**	**IMT36169**
M32	6 x Ø 5	**IMT36160**	**IMT36155**	**IMT36165**	**IMT36170**
M40	-	**-**	**IMT36156**	**IMT36166**	**IMT36171**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Key features when selecting a cable entry (1/4)

1

Multiple

Single

Multiple cable entries or single cable entries?

- This choice depends on the number of cables going through the cable entry: Generally for 3 or more cables, choose a multiple cable entry. This will make your installation faster and more economical.
- In other words, your final bill will not necessarily be lower if you use single cable entries!
- Flexibility of installation: For high flexibility, multiple cable entry is the right choice.

2

Cable entry material

- **Soft membranes** allow cables to be easily pushed through, but still offer a good IP rating and protection from moisture and physical intrusions. Cable retention force, however, is lower than with other alternatives.

Push the membrane into a standard hole.

Make a small hole in the membrane.

Push the cable or tube through the guide hole.

Pull the cable or tube back some 20 mm to lock it.

- **Hard plastic cable entry plates** require tools to create the opening (drill or knife) but, thanks to the cable gland, they offer a very high retention force. Another use of this solution is for public places, since the hard surface helps prevent objects being pushed in.

- **Combined: The material of the cable entry plate is hard plastic,** but the cable is pushed through a soft membrane. In this case you have the advantages of both soft membranes (easy and fast installation, flexibility) and hard plastic membranes (high retention force, when using specific cable clamps).

3



Cable glands to be fitted

- Some multiple cable entries require a cable gland to be able to retain the cables and ensure the degree of protection

10

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Key features when selecting a cable entry (2/4)

4

Installation possibilities

There are 4 ways to install your cable entries on the enclosure:

- **Using a cable entry:**
  the standard cable gland plate of your S3D wall-mounting enclosure is unscrewed and replaced by the cable entry. A gasket between enclosure and cable entry will help ensure good water and dust tightness.

- **Modifying the standard cable gland plate:**
  the standard cable gland plate is unscrewed and machined. A cut-out is created in it.



- **On cable gland plate adapter:**
  this plate, which has the outer dimensions of a standard cable gland plate, has one or more pre-cut cut-outs of standard dimensions (FL13 and FL21).
  On steel wall-mounting enclosures, the plate can replace the standard cable gland plate once the cable entry is fitted into it. On polyester enclosures, a cut-out must be created. Schneider Electric provides this service: a precise laser cut-out can be factory-created upon request.
  On steel floor-standing enclosures, you may either use the specific cable gland roof or create a cut-out **(see expert's tip 1 - page 279)**.



Cable gland plate adapters				
Enclosure range	1 membrane	2 membranes	3 membranes	4 membranes
Spacial S3D	**NSYTL●FL**	**NSYTL●2FL**	-	**NSYTLG4FL**
Spacial SF	**NSYSFLR●●** **NSYSFLR●●●**	**NSYSFLR●●** **NSYSFLR●●●**	**NSYSFLR●●●**	-

- Drilling directly the enclosure: A cut-out is created on the enclosure's side according to the cable entry's dimensions **(see expert's tip 1 - page 279)**.

Spotlight On…
FL13 and FL21 are standard cut-out dimensions frequently used in northern European countries and also used by our enclosures for several years now.

10

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Key features when selecting a cable entry (3/4)

Full flexibility

Medium flexibility

5 Flexibility of the installation

- **Full flexibility:**
  this means that cables can be added/removed easily, changing:
  - quantity
  - diameter
  - position
  (see expert's tip 2, page 279)
- **Medium flexibility:**
  - the amount, diameter or position of cables can be changed to a limited extent.
- **Low flexibility:**
  - it is not possible to change the above parameters.

6 Reversibility

- **Full reversibility:** This means that cables can be added/ removed easily without losing their initial characteristics, such as water tightness.
- **Medium reversibility:** For soft membranes, once the cable has been removed, there may be a loss of IP depending on the size of the cable and the cut. For hard plastic entries or combined material entries, initial characteristics are regained by adding plugs.
- **Low reversibility:** The cable entry must be completely replaced in order to regain the initial characteristics.

7 Degree of protection (IP)

- If an enclosure is to be used in a clean, dry and well insulated environment, lower levels of IP may be acceptable (IP54 or IP55).
- In a dusty environment you may require higher IP levels, such as IP65 or IP68 **(see expert's tip 4, page 279)**.

8 Cable retention

- Choose the right level of cable retention according to your needs.
  For locations accessible to the public, preferably choose a high level of cable retention.

9 Cable diameter

- Choose the cable entry seal according to the cable diameter.
  Take into account cable diameter tolerances.





10 Cable installation time

- Each cable entry has different installation characteristics. Some can be installed easily and quickly thanks to the soft membrane. Take this into account depending on labour costs in your region.



Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Key features when selecting a cable entry (4/4)

11 Quantity of cables to be fitted for a given surface

- For some installations, a large quantity of cables must go through the cable entry. Some cable entries can receive a high density of cables, which can result in more economical installation (fewer cable entries to be bought). For small enclosures, it may simply be impossible to install too many cable entries due to the available space on the enclosure's wall **(see expert's tip 3, page 279)**.

12 Cable entries for cables with connectors

- Some cables have large connectors which cannot be pushed through tight cable clamps or cable seals. These cable entries have the unique advantage of not requiring the cable to be cut, thanks to the snap-fitting system.



A high cable retention force is provided thanks to the integrated cable fastener

Expert's tip

Specific Configured

1 Some cable entries require cut-outs to be machined on the enclosure or cable gland plate. Our customized offer provides this service. The quality of your enclosure will therefore be improved since the painting operation is performed after creating the cut-outs.



2 Installing a cable entry with full flexibility is the solution when a large series of enclosures is being prepared for different types of installations. By using one combination of enclosure-cable entry, you can cover a large variety of installations!



3 When the cable entry has been defined, the next step is cable management inside the enclosure. For correct thermal management, all wires must be fitted and attached so as not to create an obstacle for correct air flow. Consult our Universal Enclosures catalogue for cable management accessories (such as cable ducts) and consumables (such as cable ties).

4 When your environment requires a high level of IP for your installation, make sure you have an appropriate thermal management system to avoid condensation or overheating problems. Consult our Thermal Management offer in our Universal Enclosures catalogue and our Control Panel Technical Guide related to this issue.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Cable entries

FlexiCable cable entries

Mount FlexiCable on your S3D enclosure.

Create a hole with a screw driver.

Push the cable through FlexiCable and finish-off your installation.

Note:
Details see page 272

Supply:
1 metallic frame with pre-mounted membrane, 1 gasket, fixing hardware

NSYTLGME

Characteristics	Type	Plate width (mm)	Plate depth (mm)	Effective cable entrance dimensions (mm)	References
FlexiCable cable entries	C	245	130	178 x 63	**NSYTLCME**
FlexiCable cable entries	D	345	130	278 x 63	**NSYTLDME**
FlexiCable cable entries	E	445	130	378 x 63	**NSYTLEME**
FlexiCable cable entries	F	545	130	478 x 63	**NSYTLFME**
FlexiCable cable entries	G	495	220	428 x 153	**NSYTLGME**
FlexiCable cable entries for enclosure with 2 cable gland plates	D	345	130	-	2x **NSYTLDME**
FlexiCable cable entries for enclosure with 2 cable gland plates	E	445	130	-	2x **NSYTLEME**

Multi-A

NSYAECPFLA7

NSYAECPFLA10

NSYAECPFLA25

NSYAECPFLA33

FL13

FL21

Note:
Details see page 272

Characteristics	Height (mm)	Width (mm)	Depth (mm)	Diameter of the cable entry (Ø mm) No.	13	14	15	16	18	21	30	References
Multi-A Type FL13	20	135	47	7	-	-	4	-	-	3	-	**NSYAECPFLA7**
Multi-A Type FL13	20	135	47	10	6	-	-	4	-	-	-	**NSYAECPFLA10**
Multi-A Type FL21	25	215	86	25	-	16	-	-	6	-	3	**NSYAECPFLA25**
Multi-A Type FL21	25	215	86	33	-	24	-	-	9	-	-	**NSYAECPFLA33**

Multi-C

NSYTSAM508SE

Position of the holes on the circular cable entries with diameters 50 and 63 mm:



NSYTSAM504SE NSYTSAM508SE NSYTSAM638SE NSYTSAM6313SE





Note:
Details see page 272

Supply:
10 units.
Reference by unit.
Order by multiples of 10 (10, 20, 30...)

Characteristics	Cut-out Ø (mm)	Diameter of the cable entry (Ø mm) No.	3-5.5	3-6.5	3.6-6.5	5-9.2	6-10	9.6-15.9	References
Multi-C	50.5	4	-	-	-	-	3	1	**NSYTSAM504SE**
Multi-C	50.5	8	-	-	7	-	1	-	**NSYTSAM508SE**
Multi-C	63.5	8	-	2	-	4	-	2	**NSYTSAM638SE**
Multi-C	63.5	13	6	-	6	-	1	-	**NSYTSAM6313SE**

10

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Life Is On Schneider Electric

Cable entries

Multi-R

- Material: Polyamide
- Cable entry material: Soft membrane
- Cable glands to be fitted: No
- Installation possibilities: On cable gland plate with special cut-out or directly on enclosure
- Flexibility of the installation: Medium
- Reversibility: Full
- Ingress protection rating: IP55 according to IEC 60529
- Cable retention: Medium
- Cable diameter (mm): From 4.3 to 15.9
- Cable Installation time: Fast
- Quantity of cables to be fitted for a given surface: ++
- Cable entries for cables with connectors: No
- Cut-out dimensions (mm): 112 x 36
- External dimensions (mm): 146 x 14 x 58
- Certificates: UL 94 V-0
- Flame resistance: 650°C



Note:
Dimensions and positions of the holes on a rectangular cable entry see page 317
Details see page 272

Supply:
1 unit

NSYTSA2414SE

Characteristics	Cut-out Ø (mm)	Diameter of the cable entry (Ø mm) No.	4.3-8.1	3-6.5	5-9.2	8-12.5	9.6-15.9	References
Multi-R	112 x 36	14	-	6	4	-	-	**NSYTSA2414SE**
Multi-R	112 x 36	17	-	-	17	-	-	**NSYTSA2417SE**
Multi-R	112 x 36	22	-	16	4	2	-	**NSYTSA2422SE**
Multi-R	112 x 36	23	23	-	-	-	-	**NSYTSA2423SE**
Multi-R	112 x 36	29	-	29	-	-	-	**NSYTSA2429SE**

Multi-T



- Type FL21

Note:
Details see page 272

NSYAECPFLT25

Characteristics	Diameter of the cable entry (Ø mm) No.	5-7	6-10	8-12	8-16	10-14	12-18	14-20	17-32	20-26	24-54	30-60	References
Multi-T, metallic plate	0	-	-	-	-	-	-	-	-	-	-	-	**NSYAECPFLBP**
Multi-T	7	-	-	-	4	-	-	-	-	-	2	1	**NSYAECPFLT7**
Multi-T	27	4	-	4	-	13	-	4	-	2	-	-	**NSYAECPFLT25**
Multi-T	37	-	4	14	-	16	2	-	1	-	-	-	**NSYAECPFLT35**

Multi-H



- Type FL21

Note:
Details see page 273

NSYTSAKFL

Characteristics	L1 (mm)	L2 (mm)	H (mm)	Diameter of the cable entry (Ø mm) M12	M12 or M20	M16 or M25	References
Multi-H	10	215	85	4	4	4	**NSYTSAKFL**

Multi-F

- Type FL13 or FL21
- Diameter of the cable entry 4-10 mm: "Pop-out" membranes only
- Diameter of the cable entry M16, M20 or M25: "Pop-out" membranes or cable gland installation
- Diameter of the cable entry M32, M40 or M50: Knock out system



Note:
Details see page 273

NSYAECPKFL11

Characteristics	Dimesions (mm) L1	L2	H	H2	Diameter of the cable entry (Ø mm) 4-10	M16 (5-10)	M20 (6-13)	M25 (8-17)	M32, M40 or M50	References
MMulti-F FL13	134	52	6.5	~ 35	10	-	1	-	-	**NSYAECPKFL11**
Multi-F	214	90	9	~ 35	-	2	2	2	1	**NSYAECPKFL7A**
Multi-F	214	90	9	~ 35	-	4	2	4	-	**NSYAECPKFL10**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Cable entries

Multi-CR

NSYDCE168


NSYDCE244


NSYDCE2410

NSYDCE16●●●



NSYDCE24●●●



Note:
Details see page 273

Supply:
1 die and fixing elements

Characteristics	Connector cut-out type	Number of cable entries	References
Multi-CR	16	8	**NSYDCE168**
Multi-CR	24	4	**NSYDCE244**
Multi-CR	24	10	**NSYDCE2410**

Split seals for cable entries equipped with connectors

Supply:
10 units. Reference per unit. To be ordered in multiples of 10 (10, 20, 30, etc.).

- Split seals suited to the diameter of the cable to be mounted on the cable entry dies for the connectors. Ref. **NSYDCE●●●**

NSYCEJD

Characteristics	For cables Ø (mm)	References
Split seals for cable entries equipped with connectors	0	**NSYCEJD**
Split seals for cable entries equipped with connectors	3-4	**NSYCEJD3**
Split seals for cable entries equipped with connectors	5-6	**NSYCEJD5**
Split seals for cable entries equipped with connectors	7-8	**NSYCEJD7**
Split seals for cable entries equipped with connectors	9-10	**NSYCEJD9**
Split seals for cable entries equipped with connectors	11-12	**NSYCEJD11**
Split seals for cable entries equipped with connectors	13-14	**NSYCEJD13**
Split seals for cable entries equipped with connectors, large seal, 24/4 die only	16-17	**NSYCEJD16**
Split seals for cable entries equipped with connectors, large seal, 24/4 die only	18-19	**NSYCEJD18**
Split seals for cable entries equipped with connectors, large seal, 24/4 die only	20-21	**NSYCEJD20**
Split seals for cable entries equipped with connectors, large seal, 24/4 die only	22-23	**NSYCEJD22**
Split seals for cable entries equipped with connectors, large seal, 24/4 die only	24-25	**NSYCEJD24**
Split seals for cable entries equipped with connectors, large seal, 24/4 die only	26-27	**NSYCEJD26**
Split seals for cable entries equipped with connectors, large seal, 24/4 die only	28-29	**NSYCEJD28**
Split seals for cable entries equipped with connectors, large seal, 24/4 die only	30-31	**NSYCEJD30**

Multi-CS





Note:
Details see page 272

Supply:
1 unit

NSYDCD2412

Characteristics	Cut-out (mm)	Diameter of the cable entry (Ø mm) No.	2-12	12-24	References
Multi-CS	112 x 36	12	12	-	**NSYDCD2412** New
Multi-CS	112 x 36	4	-	4	**NSYDCD244** New
Multi-CS	112 x 36	8	6	2	**NSYDCD248** New
Multi-CS	112 x 36	9	8	1	**NSYDCD249** New

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Life Is On Schneider Electric

Cable entries

Cable gland

Supply:
Small cable gland: Pack of 12
Large cable gland: Pack of 4

NSYCEJDS2

Characteristics	Cable Ø (mm)	References
Cable gland, small	2-3	**NSYCEJDS2**
Cable gland, small	3-4	**NSYCEJDS3**
Cable gland, small	4-5	**NSYCEJDS4**
Cable gland, small	5-6	**NSYCEJDS5**
Cable gland, small	6-7	**NSYCEJDS6**
Cable gland, small	7-8	**NSYCEJDS7**
Cable gland, small	8-9	**NSYCEJDS8**
Cable gland, small	9-10	**NSYCEJDS9**
Cable gland, small	10-11	**NSYCEJDS10**
Cable gland, small	11-12	**NSYCEJDS11**
Cable gland, large	12-13	**NSYCEJDL12**
Cable gland, large	13-14	**NSYCEJDL13**
Cable gland, large	14-15	**NSYCEJDL14**
Cable gland, large	15-16	**NSYCEJDL15**
Cable gland, large	16-17	**NSYCEJDL16**
Cable gland, large	17-18	**NSYCEJDL17**
Cable gland, large	18-19	**NSYCEJDL18**
Cable gland, large	19-20	**NSYCEJDL19**
Cable gland, large	20-21	**NSYCEJDL20**
Cable gland, large	21-22	**NSYCEJDL21**

Blanking plugs

Supply:
Small blanking plugs: Pack of 12
Large blanking plugs: Pack of 4

NSYCEJDS0

Characteristics	References
Blanking plugs, small	**NSYCEJDS0**
Blanking plugs, large	**NSYCEJDL0**

Multi-CF



Note:
Details see page 273

Supply:
1 unit

NSYTLK2414

NSYTLK2422

Characteristics	Diameter of the cable entry (Ø mm)							References	
	No.	No. x Ø max.	a	b	c	d	e		
Multi-CF	14	6 x 9 4 x 11 4 x 18	112	36	65	16	5.5	**NSYTLK2414**	New
Multi-CF	22	16 x 9 4 x 11 2 x 15	112	36	65	16	5.5	**NSYTLK2422**	New
Multi-CF	28	28 x 9	112	36	65	16	5.5	**NSYTLK2428**	New
Multi-CF	46	46 x 9	112	36	65	16	5.5	**NSYTLK2446**	New
Multi-CF	multi	3 / 27 x 300	112	36	65	16	5.5	**NSYTLK24M**	New

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Cable entries

Prisma, plain

08881

- Solid cable gland plates

Note:
Details see page 273

Characteristics	Type	References
Prisma, plain	FL21	**08881**

Prisma, pre-drilled

08892

08895


08898


08899

- Suitable for receiving cable glands with metric pitch

Note:
Reference 08898 is made up of:
3 cables with diameters from 14 to 26.
4 cables with diameters from 10 to 20.
32 cables with diameters from 7 to 16.
Details see page 273

Characteristics	Type	References
Prisma, pre-drilled, with 4 entries 2 x M20 or M32 + 2 x M25 or M40	FL21	**08892**
Prisma, pre-drilledn, with 13 entries 5 x M16 or M25 + 8 x M20	FL21	**08895**
Prisma, pre-drilled, with 39 entries Ø 7 - 26 mm	opening 225 x 137 mm	**08898**
Prisma, pre-drilled, with 2 entries Ø 33 - 72 mm	opening 225 x 137 mm	**08899**

Prisma, membrane


08897

- Membrane to be drilled according to the required diameter

Note:
Details see page 273

Characteristics	Type	References
Prisma, membrane, 2 entries, 2 x Ø 28 - 60 mm	FL21	**08897**

Cable clamp for improved cable retention for Multi-A

- Installation on FL 21 membrane type "A" for cable entrance to block cables when installed. It can be easily removed.
- Material: PA6
- Temperature range: -40 to +85 °C

Installation:
1. Push the cable through the membrane entrance to the desired position
2. Put the cable clamp around the cable and slide it into the cable entry
3. Push the cable clamp fully into the membrane entrance and the cable will be fixed

Note:
Secure your installation with an easy solution for cable anchorage.

NSYAECPFLACA30

Characteristics	Cable clamp outer Ø (mm)	Membrane entrance Ø (mm)	Cable Ø range (mm)	References
Set of 8 cable clamps for improved cable retention for Multi-A	15	14	7-9	**NSYAECPFLACA14**
Set of 6 cable clamps for improved cable retention for Multi-A	18	18	9-11	**NSYAECPFLACA18**
Set of 6 cable clamps for improved cable retention for Multi-A	20	18	10-12	**NSYAECPFLACA20**
Set of 3 cable clamps for improved cable retention for Multi-A	30	30	20-23	**NSYAECPFLACA30**

Blanking plugs for Multi-A

- Installation on FL 21 membrane type "A" for cable entrance to fill the opening used.
- Material: LDPE
- Temperature range: -30 to +50°C

Supply:
Set of 2 x 30 mm, 3 x 18 mm and 5 x14 mm

NSYAECPFLAP

Characteristics	References
Blanking plugs for Multi-A	**NSYAECPFLAP**

10

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Cable entries

Steel adapter plate for FL13 and FL21 membranes



- Allows the mounting of FL13 and FL21 membranes on every type of enclosure.
- Our membrane can be easily adapted to fit onto all our metallic enclosures using the adapter plate.
- Ingress protection rating IP55 according to IEC 60529

Supply:
Delivered with fixing screws and gasket

NSYTLBFL

Characteristics	Type	Plate dimensions (mm)		Cut-out dimensions (mm)		References
		A	B	H	I	
Steel adapter plate for FL13 membranes (1)	B	245	80	212	47	**NSYTLBFL**
Steel adapter plate for FL21 membranes (1)	C	245	130	212	97	**NSYTLCFL**
Steel adapter plate for FL21 membranes (1)	D	345	130	312	97	**NSYTLDFL**
Steel adapter plate for FL21 membranes (1)	E	445	130	412	97	**NSYTLEFL**
Steel adapter plate for FL21 membranes (1)	F	545	130	512	97	**NSYTLFFL**
Steel adapter plate for FL21 membranes (2)	F	545	130	512	97	**NSYTLF2FL**
Steel adapter plate for FL21 membranes (1)	G	495	220	462	187	**NSYTLGFL**
Steel adapter plate for FL21 membranes (2)	G	495	220	462	187	**NSYTLG2FL**
Steel adapter plate for FL21 membranes (3)	G	495	220	462	187	**NSYTLG4FL**

Mixed membrane entries for IP55 direct cable entries



Note:
Details see page 274

Supply:
Minor packaging of 10 pieces

ISM71074

Characteristics	Drill hole Ø (mm)	Cable / conduit Ø (mm)	References
Mixed membrane entries for IP55 direct cable entries, RAL 9010	23	4 - 20	**IMT36172**
Mixed membrane entries for IP55 direct cable entries, RAL 9010	29	4 - 25	**IMT36173**
Mixed membrane entries for IP55 direct cable entries, RAL 7035	23	4 - 20	**ISM71071**
Mixed membrane entries for IP55 direct cable entries, RAL 7035	29	4 - 25	**ISM71072**
Mixed membrane entries for IP55 direct cable entries, RAL 7035	36	4 - 32	**ISM71073**
Mixed membrane entries for IP55 direct cable entries, RAL 7035	44	4 - 40	**ISM71074**

PVC adjustable cone-shaped entries



Note:
* Drill-hole for mounting.
Details see page 274

Supply:
NSYECPC3 50 cable entries,
NSYECPC5 and **NSYECPC6** each 25 cable entries,
NSYECPC9 and **NSYECPC15** each 10 cable entries

NSYECPC15

Characteristics	Dimensions (mm)						Capacity		References
	Ø A	Ø B*	Ø C	Ø D	E	F	Cable (Ø mm)	Tube	
PVC adjustable cone-shaped entries	25	21.5	18	5	3.2	13	5-18	PG 9-11	**NSYECPC3**
PVC adjustable cone-shaped entries	33	29.5	26	5	3.2	20	5-26	PG 9-16	**NSYECPC5**
PVC adjustable cone-shaped entries	43	38.5	36	5	3.2	22	5-36	PG 9-21	**NSYECPC6**
PVC adjustable cone-shaped entries	70	63	60	28	3	20	28-60	PG 21-48	**NSYECPC9**
PVC adjustable cone-shaped entries	98	90	87	28	3	23	28-87	PG 21-48	**NSYECPC15**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Cable entries

ISO cable gland



Note:
* In brackets: Tolerance.
Details see page 274

Supply:
The cable glands are supplied with nuts. Pack of 20 (M12 to M20), 10 (M25 and M32), 5 (M40)

- The cable gland (ref. **IMT36150**) is especially recommended for security circuits.

ISM71503

Characteristics	Dimensions						References
	ISO	Cable Ø (mm)	Drill hole* Ø (mm)	TD	TL		
Cable gland	M12	3 / 6.5	12.2 (0 + 0.2)	12	6	15	**ISM71501**
Cable gland	M16	4 / 8	16.2 (0 + 0.2)	16	8	19	**ISM71502**
Cable gland	M20	6 / 12	20.2 (0 + 0.2)	20	10	24	**ISM71503**
Cable gland with high resistance to fire	M20	6 / 12	20.2 (0 + 0.2)	20	10	24	**IMT36150**
Cable gland	M25	11 / 17	25.2 (0 + 0.2)	25	8	29	**ISM71504**
Cable gland	M32	15 / 21	32.2 (0 + 0.3)	32	10	36	**ISM71505**
Cable gland	M40	19 / 28	40.5 (0 + 0.3)	40	10	46	**ISM71506**

Quick cable entries



Note:
Details see page 274

Supply:
50 (M12 to M32), 25 (M40 and M50)

IMT36179

Characteristics	Dimensions			References
	Ø	Drill hole Ø (mm)	Cable Ø (mm)	
Quick cable entries	M12	12.5	3 - 5	**IMT36179**
Quick cable entries	M16	16	5 - 7	**IMT36180**
Quick cable entries	M20	20.3	7 - 10	**IMT36181**
Quick cable entries	M25	25.3	10 - 14	**IMT36182**
Quick cable entries	M32	32.4	14 - 20	**IMT36183**
Quick cable entries	M40	40.7	20 - 26	**IMT36184**
Quick cable entries	M50	50.7	26 - 35	**IMT36185**

PVC adjustable cone-shaped entries



Note:
Details see page 274

Supply:
25 cable entries

NSYEC7

Characteristics	Dimensions (mm)						Capacity		References
	Ø A	Ø B	Ø C	Ø D	E	F	Cable Ø (mm)	Tube	
PVC adjustable cone-shaped entries	52	48.5	44	13	1.5	30	13 to 44	PG 36	**NSYEC7**

10

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Life Is On Schneider Electric

Cable entries

Synthetic snap in cable gland



Note:
Details see page 274

Supply:
The cable glands are supplied with nuts. Pack of 20 (M16 and M20), of 10 (M25 and M32), of 5 (M40)

- Wall thickness : E = 0.5 à 4 mm.

NSYCGSP16

Characteristics	Dimensions							References	
	Ø	Ø min / max	Drill Ø	SL	SD	H			
Synthetic snap in cable gland	M16	5/10	16.2 to 16.4	9	15.9	42.5	22	**NSYCGSP16**	New
Synthetic snap in cable gland	M20	6/12	20.2 to 20.4	9	19.9	41.5	24	**NSYCGSP20**	New
Synthetic snap in cable gland	M25	11/17	25.2 to 25.4	9	24.9	43.5	29	**NSYCGSP25**	New
Synthetic snap in cable gland	M32	15/21	32.2 to 32.4	9	31.9	49.5	36	**NSYCGSP32**	New
Synthetic snap in cable gland	M40	19/28	40.2 to 40.4	11.5	39.9	56	46	**NSYCGSP40**	New

Snap in cable gland disassembling tool

- Tool to quickly disassemble cable gland.
- Material: Plastic

Note:
Details see page 274

NSYDT16

NSYDT20

Characteristics	Ø	References	
Snap in cable gland disassembling tool	M16	**NSYDT16**	New
Snap in cable gland disassembling tool	M20	**NSYDT20**	New
Snap in cable gland disassembling tool	M25	**NSYDT25**	New
Snap in cable gland disassembling tool	M32	**NSYDT32**	New
Snap in cable gland disassembling tool	M40	**NSYDT40**	New

Stainless steel cable gland with lamellar insert



Note:
Details see page 274

Supply:
The cable glands are supplied with nuts. Pack of 5 (M12 and M16), of 4 (M20 and M25), of 2 (M32 and M40)

- Applications: Outdoor, food and beuverage industries, pharmazeutical industry and other sensitive applications.

NSYCGX12

Characteristics	Dimensions							References	
	Ø	Ø min / max	Drill Ø	TD	TL	H			
AISI 304L	M12	3/6.5	12 to 12.2	12	12	22	14	**NSYCGX12**	New
AISI 304L	M16	5/10	16 to 16.2	16	12	28.5	20	**NSYCGX16**	New
AISI 304L	M20	6/12	20 to 20.2	20	12	24	22	**NSYCGX20**	New
AISI 304L	M25	11/17	25 to 25.2	25	12	32.5	27	**NSYCGX25**	New
AISI 304L	M32	15/21	32 to 32.3	32	15	36	34	**NSYCGX32**	New
AISI 304L	M40	19/28	40 to 40.3	40	15	43.5	43	**NSYCGX40**	New
AISI 316L	M12	3/6.5	12 to 12.2	12	12	22	14	**NSYCGX12H**	New
AISI 316L	M16	5/10	16 to 16.2	16	12	28.5	20	**NSYCGX16H**	New
AISI 316L	M20	6/12	20 to 20.2	20	12	24	22	**NSYCGX20H**	New
AISI 316L	M25	11/17	25 to 25.2	25	12	32.5	27	**NSYCGX25H**	New
AISI 316L	M32	15/21	32 to 32.3	32	15	36	34	**NSYCGX32H**	New
AISI 316L	M40	19/28	40 to 40.3	40	15	43.5	43	**NSYCGX40H**	New

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Cable holding

SM SMX SF SFX Lower cable-guide cross rail

- It allows quick fixing of cables entering and exiting the enclosure.
- Depth adjustable every 25 mm.
- Material: Galvanised steel

Fixing:

- Spacial SF: for suitable enclosures with widths of 1200 and 1600 mm, use the adaptationkit for 2-door suitable enclosures, see page 250
- Spacial SM: for floor-standing enclosures with a width of 1200 mm, a top/bottom mounting rail installed in central position is required
- Spacial SFX: no adaptation piece is required for the 1200 mm suitable enclosures
- Spacial SMX: no adaptation piece is required for the 1600 mm floor-standing enclosures





Supply:
1 cable-guide cross rail and fixingelements

NSYCFP60

Characteristics	Width (mm)	References
Lower cable-guide cross rail	600	**NSYCFP60**
Lower cable-guide cross rail	800	**NSYCFP80**
Lower cable-guide cross rail	1000	**NSYCFP100**
Lower cable-guide cross rail	1200	2x **NSYCFP60**
Lower cable-guide cross rail	1600	2x **NSYCFP80**

SM SMX SF SFX Cable-guide cross rails for framework

Support types:

- Angle support at 90°: For vertical cable fixing.
- Angle support at 120°: For fixing cables near the cable entry.
- Material: Zinc-coated steel

Fixing:

- Spacial SF/SFX: support for direct mounting on the framework, cross rails or rails
- Spacial SM: fixing on the bottom mounting rail, or on the floor-standing enclosure by means of adaptation rails and 40 mm universal cross rails (1 row) in vertical position
- Spacial SMX: fixing on the bottom mounting rail and 40 mm universal cross rails (1 row) in vertical position



Supply:
2 supports and fixing elements

NSYCFS96

Characteristics	Support angle	Width (mm)	References
Cable-guide cross rails for framework	90°	600	**NSYCFS96**
Cable-guide cross rails for framework	120°	600	**NSYCFS126**
Cable-guide cross rails for framework	90°	800	**NSYCFS98**
Cable-guide cross rails for framework	120°	800	**NSYCFS128**

SM SMX SF SFX L-rail for fixing cables

- Rail for fixing cables entering from the bottom.
- Adjustable depth with a pitch of 25 mm.
- It is not possible to mount it on a plinth cross rail.
- Material: Zinc-coated steel

Fixing:

- Spacial SF/SFX: fixing to the bottom frame, above the cable entry, or else to the plinth, using the plinth cross rails, see page 96
- Spacial SM/SMX: fixingto the bottom adjustment rails, above the cable entry, or else to the plinth, using the plinth cross rails, see page 96
- The cables are fixed to the rail by means of metal clamps



Supply:
One rail, two mounting supports and fixing elements

NSYFCG60

Characteristics	Width (mm)	References
L-rail for fixing cables	600	**NSYFCG60**
L-rail for fixing cables	800	**NSYFCG80**
L-rail for fixing cables	1000	**NSYFCG100**
L-rail for fixing cables	1200	**NSYFCG120**
L-rail for fixing cables	1600	**NSYFCG160**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Cable holding

SM SMX SF SFX Door cable-guide cross rail



- Recommended for fixing cables in the internal equipment of the door.
- Height adjustable every 25 mm.
- Material: Zinc-coated steel
- Fixing: Direct fixing on the reinforcement frame

Supply:
2 cable-guide cross rails and fixing elements

NSYSDGCR5

Characteristics	Width (mm)	References
Door cable-guide cross rail	600	**NSYSDGCR5**
Door cable-guide cross rail	600	**NSYSDGCR6**
Door cable-guide cross rail	800	**NSYSDGCR8**
Door cable-guide cross rail	1000	**NSYSDGCR10**

Plastic cable support



Supply:
10 units. Reference by unit. Order by multiples of 10 (10, 20, 30...)

NSYSCCDINLG75

- It clips or screws onto 35 mm symmetric rails or a C-shaped rail.
- Fixing: Quick and easy fixing of cables using cable ties

Characteristics	Max. no. of cables	Width (mm)	References
Plastic cable support	5	75	**NSYSCCDINLG75**
Plastic cable support	9	140	**NSYSCCDINLG140**

S3D S3X Door cable-guide cross rails for wall-mounting enclosures



- They are installed on wall-mounting enclosures with heights from 400 mm for Spacial S3D and 500 mm for Spacial S3X.
- They make it easy to equip the inside of the door.
- Installation cable ties, see **page 316**.
- Fixing: They are fixed to the door reinforcement frame by 2 self-tapping screws. The angle can be directed towards the body of the enclosure or towards the door

Supply:
2 cable-guide cross rails and fixing elements

NSYTFPCRN4

Characteristics	Width (mm)	References
Door cable-guide cross rails for wall-mounting enclosures	400	**NSYTFPCRN4**
Door cable-guide cross rails for wall-mounting enclosures	500	**NSYTFPCRN5**
Door cable-guide cross rails for wall-mounting enclosures	600	**NSYTFPCRN6**
Door cable-guide cross rails for wall-mounting enclosures	800	**NSYTFPCRN8**
Door cable-guide cross rails for wall-mounting enclosures	1000	**NSYTFPCRN10**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Cable ties

Thorsman cable ties

Description
- Cable ties are used for a wide range of applications including bundle up and fix cables, conduits and tubing
- Material: PA6.6
- Available in black and clear colour
- Max operating temperature -40°C to +85°C
- Minimum installation temperature -20°C.

Application
- There are two types of Thorsman cable ties available:
  made of clear polyamide, for indoor use
  made of UV-stabilized black polyamide for both indoor and outdoor use

Benefits
- The cable ties are self-locking. They cannot be opened and re-sealed.
- The cable ties have smooth rounded edges for easier handling and safer installation.
- The bent rounded tip allows easier insertion through the head of the cable tie.
- User friendly re-sealable packaging and documented quality.
- Manufactured and tested to EN62275, RoHS compliant.



IMT46026

Characteristics	Type	Length (mm)	Colour	Qty per package	References
Thorsman cable ties	2.5 mm	100	Clear	100	**IMT46026**
Thorsman cable ties	2.5 mm	100	Black	100	**IMT46033**
Thorsman cable ties	2.5 mm	120	Clear	100	**IMT46035**
Thorsman cable ties	2.5 mm	120	Black	100	**IMT46036**
Thorsman cable ties	2.5 mm	160	Clear	100	**IMT46074**
Thorsman cable ties	2.5 mm	160	Black	100	**IMT46073**
Thorsman cable ties	2.5 mm	200	Clear	100	**IMT46158**
Thorsman cable ties	2.5 mm	200	Black	100	**IMT46157**
Thorsman cable ties	3.6 mm	150	Clear	100	**IMT46064**
Thorsman cable ties	3.6 mm	150	Black	100	**IMT46071**
Thorsman cable ties	3.6 mm	200	Clear	100	**IMT46149**
Thorsman cable ties	3.6 mm	200	Black	100	**IMT46156**
Thorsman cable ties	3.6 mm	300	Clear	100	**IMT46921**
Thorsman cable ties	3.6 mm	300	Black	100	**IMT46922**
Thorsman cable ties	4.8 mm	200	Clear	100	**IMT46101**
Thorsman cable ties	4.8 mm	200	Black	100	**IMT46118**
Thorsman cable ties	4.8 mm	250	Clear	100	**IMT46918**
Thorsman cable ties	4.8 mm	250	Black	100	**IMT46968**
Thorsman cable ties	4.8 mm	300	Clear	100	**IMT46919**
Thorsman cable ties	4.8 mm	300	Black	100	**IMT46969**
Thorsman cable ties	4.8 mm	370	Clear	100	**IMT46248**
Thorsman cable ties	4.8 mm	370	Black	100	**IMT46970**
Thorsman cable ties	7.6 mm	300	Black	100	**IMT46923**
Thorsman cable ties	7.6 mm	380	Clear	100	**IMT46286**
Thorsman cable ties	7.6 mm	380	Black	100	**IMT46293**
Thorsman cable ties	8.8 mm	550	Clear	100	**IMT46926**
Thorsman cable ties	8.8 mm	550	Black	100	**IMT46924**
Thorsman cable ties	8.8 mm	780	Black	100	**IMT46927**
Thorsman cable ties	2.5 mm	100	Black	20	**IMT46231**
Thorsman cable ties	2.5 mm	100	Clear	20	**IMT46221**
Thorsman cable ties	4.6 mm	200	Black	20	**IMT46232**
Thorsman cable ties	4.6 mm	200	Clear	20	**IMT46222**
Thorsman cable ties	4.8 mm	280	Black	20	**IMT46233**
Thorsman cable ties	4.8 mm	280	Clear	20	**IMT46223**
Thorsman cable ties	4.8 mm	380	Clear	20	**IMT46224**
Thorsman cable ties	4.8 mm	380	Black	20	**IMT46234**

Thorsman accessories

IMT47000

IMT47002

IMT47004

- Self -adhesive base for fixing of cable ties. There are two sizes base, one for max. tie width 3.6 mm and the other for max. tie width 4.8 mm. Both self-adhesives are using high-end 3M form. There are additional screw-fix option cradle for fixing cable tie and cable tie with identification and marking tab.
- Material: PA6.6

Characteristics	Type	Dimensions H x W x D (mm)	Colour	Qty per package	References
Self-adhesive bases	For max. tie width 3.6 mm	19/19/5.8	Clear	100	**IMT47000**
Self-adhesive bases	For max. tie width 4.8 mm	28/28/6.4	Clear	100	**IMT47001**
Cradle	For max. tie width 7.8 mm	22/16/9.6	Clear	100	**IMT47002**
Cable tie with ID tab	Cable tie with ID tab 100 x 2.5 mm	100/2.5	Clear	100	**IMT47004**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Ducts

Corrugated cable tube

- Corrugated tube allowing cable entry between the structure and the door.
- Free from halogens and heavy metals.
- UV protection.
- Material: Low-density polyethylene (LDPE)
- Colour: Black

Supply:
One 25 m reel

NSYCPT17

Characteristics	Ø Nominal (mm)	Ø Inner (mm)	Ø Outer (mm)	References
Corrugated cable tube	17	16.6	21.2	**NSYCPT17**
Corrugated cable tube	29	29	34.5	**NSYCPT29**
Corrugated cable tube	37	36	42.4	**NSYCPT37**
Corrugated cable tube	50	47.7	54.5	**NSYCPT50**

Fixing support for corrugated tube

- Mounting options: Directly on the enclosure, on a 19" swing rack and/or on cross rails, by means of a fixing point.
- The supports can be assembled with one another to form sets of tubes that allow a better arrangement of the cables.
- It allows the rotation of the tube once it is fixed on the support and prevents the corrugated tube from coming loose if subject to pulling movements.
- Material: Polyamide (PA), black.

Supply:
10 units and fixing elements.
The support is supplied with its cover.

NSYCPTS17

Characteristics	Model (nominal Ø)	References
Fixing support for corrugated tube	17	**NSYCPTS17**
Fixing support for corrugated tube	29	**NSYCPTS29**
Fixing support for corrugated tube	37	**NSYCPTS37**
Fixing support for corrugated tube	50	**NSYCPTS50**

Spiral cable duct

- Spiral strip for bundling cables.
- Allows cables to enter between the body and the door.
- Colour: Colourless

Supply:
One 50 m reel

NSYTC12100

Characteristics	Tightening range (mm)	Ø Inner (mm)	Ø Outer (mm)	References
Corrugated cable tube	12 to 100	9	12	**NSYTC12100**

Lyre-shaped clamps

- Clip-on clamps designed for direct installation on the 19" racks, Telequick mounting plates and symmetric DIN rails.
- Colour: Black

Supply:
10 units. Reference by unit.
Order by multiples of 10 (10, 20, 30...)

AK2LA39

Characteristics	Use	References
Lyre-shaped clamps	For Telequick mounting plates and 19" racks	**AK2LA39**
Lyre-shaped clamps	For symmetric DIN rail 90 x 2.5 mm cables	**AK2LD01**
Lyre-shaped clamps	For symmetric DIN rail 75 x 2.5 mm cables	**AK2LD02**

Steel wired cable tray

- Mounting on the cable supports.
- Dimensions (2 types):
  1845 x 200 x 35 mm.
  1845 x 200 x 54 mm.
- Material: Zinc-coated steel wire

Supply:
1 vertical steel wired cable tray and fixing elements

NSYBPC3

Characteristics	Necessary depth (mm)	References
Steel wired cable tray	35	**NSYBPC3**
Steel wired cable tray	54	**NSYBPC5**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Cable-duct

- Temperature resistance: -5 ... +60°C
- Behaviour in fire: Material V0 according to UL 94
- Fire resistance: 960°C according to IEC 60695-2-1/1
- Maximum capacity of H07.V.K 1.5 mm² flexible wire (filling factor: 0.6)
- With lateral through slots and rear perforations.
- Material: Rigid PVC
- Colour: RAL 7030 grey or RAL 5000 blue
- Standards: Compliance with standards VDE 0660/506 and DIN 43659

Supply:
8 units. Supplied in lengths of 2 m

AK2GD7550

AK2GA65

Characteristics	Width (mm)	Height (mm)	Color	References
Cable-duct	25	25	Grey	**AK2GD2525**
Cable-duct	25	50	Grey	**AK2GD2550**
Cable-duct	37.5	50	Grey	**AK2GD3750**
Cable-duct	37.5	75	Grey	**AK2GD3775**
Cable-duct	50	50	Grey	**AK2GD5050**
Cable-duct	50	75	Grey	**AK2GD5075**
Cable-duct	75	50	Grey	**AK2GD7550**
Cable-duct	75	75	Grey	**AK2GD7575**
Cable-duct	100	75	Grey	**AK2GD10075**
Cable-duct	125	75	Grey	**AK2GD12575**
Cable-duct	30	35	Blue	**AK2GA33**
Cable-duct	30	55	Blue	**AK2GA35**
Cable-duct	30	90	Blue	**AK2GA39**
Cable-duct	30	144	Blue	**AK2GA315**
Cable-duct	60	55	Blue	**AK2GA65**
Cable-duct	60	90	Blue	**AK2GA69**
Cable-duct	60	144	Blue	**AK2GA615**

Covers for cable-duct

- Temperature resistance: -5 ... +60°C
- Behaviour in fire: Material V0 according to UL 94
- Fire resistance: 960°C according to IEC 60695-2-1/1
- Maximum capacity of H07.V.K 1.5 mm² flexible wire (filling factor: 0.6)
- Replacement covers.
- Material: Rigid PVC
- Colour: RAL 7030 grey or RAL 5000 blue
- Standards: Compliance with standards VDE 0660/506 and DIN 43659

Supply:
8 units. Supplied in lengths of 2 m

AK2CD75


AK2CA6

Characteristics	Width (mm)	Height (mm)	Color	For Cable-duct Ref.	References
Covers for cable-duct	25	25	Grey	AK2GD2525	**AK2CD25**
Covers for cable-duct	25	50	Grey	AK2GD2550	**AK2CD25**
Covers for cable-duct	37.5	50	Grey	AK2GD3750	**AK2CD37**
Covers for cable-duct	37.5	75	Grey	AK2GD3775	**AK2CD37**
Covers for cable-duct	50	50	Grey	AK2GD5050	**AK2CD50**
Covers for cable-duct	50	75	Grey	AK2GD5075	**AK2CD50**
Covers for cable-duct	75	50	Grey	AK2GD7550	**AK2CD75**
Covers for cable-duct	75	75	Grey	AK2GD7575	**AK2CD75**
Covers for cable-duct	100	75	Grey	AK2GD10075	**AK2CD100**
Covers for cable-duct	125	75	Grey	AK2GD12575	**AK2CD125**
Covers for cable-duct	30	35	Blue	AK2GA33	**AK2CA3**
Covers for cable-duct	30	55	Blue	AK2GA35	**AK2CA3**
Covers for cable-duct	30	90	Blue	AK2GA39	**AK2CA3**
Covers for cable-duct	30	144	Blue	AK2GA315	**AK2CA3**
Covers for cable-duct	60	55	Blue	AK2GA65	**AK2CA6**
Covers for cable-duct	60	90	Blue	AK2GA69	**AK2CA6**
Covers for cable-duct	60	144	Blue	AK2GA615	**AK2CA6**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Retention bars

NSYCDRB

- Fixed between 2 cable-duct slats by a hinged screw, preventing cable dropout.
- They can be cut to length to adapt to the width of the ducting.
- Material: Flameproof high-impact polystyrene

Supply:
50 units. Reference by unit.
Order by multiples of 50 (50, 100, 150...)

Characteristics	References
Retention bars	**NSYCDRB**

S3D SM SF S3X SFX SDX PLA Ø 22 mm cable-duct support




NSYSPCP

- Installed on the door of the wall-mounting or floor-standing enclosure associated with Ø 22 mm elements.
- Material: Treated steel

Supply:
10 units. Reference by unit.
Order by multiples of 10 (10, 20, 30...)

Characteristics	References
Ø 22 mm cable-duct support	**NSYSPCP**

SM SF SD SMX SFX SDX PLA Cable-duct support on technical upright



NSYCDS

- Allows cable ducts to be installed on technical uprights, while increasing the usable surface of the equipment (up to 20 % according to the width of the cable duct).
- Material: Galvanised steel

Supply:
10 units. Reference by unit.
Order by multiples of 10 (10, 20, 30...)

Characteristics	References
Cable-duct support on technical upright	**NSYCDS**

Plastic cable-duct support



NSYSPC

- Clips onto the Telequick mounting plate or the 35 mm DIN rail.
- Includes a bolt for fixing the cable ducts through the 6.5 x 14 mm drill holes made in the back.
- The 2 functions, clipping and bolting, provide considerable time savings.
- Respects electrical insulation.
- Material: Black polyamide. Behaviour in fire: V0 according to UL 94

Supply:
20 units. Reference by unit.
Order by multiples of 20 (20, 40, 60...)

Characteristics	References
Plastic cable-duct support	**NSYSPC**

Label frame


NSYCDL

- In transparent plastic, clipping onto the slats of the cable ducts.
- Material: Polycarbonate

Supply:
50 units. Reference by unit.
Order by multiples of 50 (50, 100, 150...)
Paper labels supplied

Characteristics	References
Label frame	**NSYCDL**

Insulated-head screw

NSYSM10M5HP

- M5 x 10 mm slotted hexagonal head.
- Respects electrical insulation.

Supply:
100 units. Reference by unit.
Order by multiples of 100 (100, 200, 300...)

Characteristics	References
Insulated-head screw	**NSYSM10M5HP**

Cable-duct support with quick fixing system

NSYSPCD

- Fixing mode: By screws - upright location
- Material: Galvanised steel

Supply:
Set of 3

Characteristics	References
Cable-duct support with quick fixing system	**NSYSPCD**

10

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Terminal blocks

Characteristics			Connection technology					
								
Type of terminal block	Cross section area	Colour	Screw tech	Spring tech	Push-in tech	Miniature screw for 15 mm DIN rail	Miniature spring for 15 mm DIN rail	Miniature spring for direct mount
			References	References	References	References	References	References
Passthrough	2.5 mm² (2-Pts)	Grey	**NSYTRV22**	**NSYTRR22**	**NSYTRP22**	**NSYTRV22M**	**NSYTRR22M**	**NSYTRR22MF**
		Blue	**NSYTRV22BL**	**NSYTRR22BL**	**NSYTRP22BL**	**NSYTRV22MBL**	**NSYTRR22MBL**	**NSYTRR22MFBL**
		Orange	**NSYTRV22AR**	**NSYTRR22AR**	**NSYTRP22AR**	-	-	**NSYTRR22MFF***
	2.5 mm² (3 Pts)	Grey	-	**NSYTRR23**	**NSYTRP23**	-	-	-
		Blue	-	**NSYTRR23BL**	**NSYTRP23BL**	-	-	-
		Orange	-	**NSYTRR23AR**	**NSYTRP23AR**	-	-	-
	2.5 mm² (4 Pts, 1 Level)	Grey	-	**NSYTRR24**	**NSYTRP24**	-	**NSYTRR24M**	**NSYTRR24M**
		Blue	-	**NSYTRR24BL**	**NSYTRP24BL**	-	**NSYTRR24MBL**	**NSYTRR24MBL**
	2.5 mm² (4 Pts, 2 Levels)	Grey	**NSYTRV24D**	**NSYTRR24D**	**NSYTRP24D**	-	-	-
		Blue	**NSYTRV24DBL**	**NSYTRR24DBL**	**NSYTRP24DBL**	-	-	-
	4 mm² (2 Pts)	Grey	**NSYTRV42**	**NSYTRR42**	**NSYTRP42**	**NSYTRV42M**	-	-
		Blue	**NSYTRV42BL**	**NSYTRR42BL**	**NSYTRP42BL**	**NSYTRV42MBL**	-	-
		Orange	**NSYTRV42AR**	**NSYTRR42AR**	-	-	-	-
	4 mm² (3 Pts)	Grey	**NSYTRV43**	**NSYTRR43**	**NSYTRP43**	-	-	-
		Blue	**NSYTRV43BL**	**NSYTRR43BL**	**NSYTRP43BL**	-	-	-
		Orange	**NSYTRV43AR**	-	-	-	-	-
	4 mm² (4 Pts, 1 Level)	Grey	**NSYTRV44**	**NSYTRR44**	**NSYTRP44**	-	-	-
		Blue	**NSYTRV44BL**	**NSYTRR44BL**	**NSYTRP44BL**	-	-	-
	4 mm² (4 Pts, 2 Levels)	Grey	**NSYTRV44D**	**NSYTRR44D**	-	-	-	-
		Blue	**NSYTRV44DBL**	**NSYTRR44DBL**	-	-	-	-
	6 mm² (2 Pts)	Grey	**NSYTRV62**	**NSYTRR62**	-	-	-	-
		Blue	**NSYTRV62BL**	**NSYTRR62BL**	-	-	-	-
	10 mm² (2 Pts)	Grey	**NSYTRV102**	**NSYTRR102**	-	-	-	-
		Blue	**NSYTRV102BL**	**NSYTRR102BL**	-	-	-	-
	16 mm² (2 Pts)	Grey	**NSYTRV162**	**NSYTRR162**	-	-	-	-
		Blue	**NSYTRV162BL**	**NSYTRR162BL**	-	-	-	-
	150 mm² (2 Pts)	Grey	**NSYTRV1502BB**	-	-	**NSYTRV22MPE**	**NSYTRR22MPE**	-
Earth protection	2.5 mm² (2-Pts)	Green	**NSYTRV22PE**	**NSYTRR22PE**	**NSYTRP22PE**	-	-	-
	2.5 mm² (3 Pts)	Green	-	**NSYTRR23PE**	**NSYTRP23PE**	-	-	-
	2.5 mm² (4 Pts)	Green	-	**NSYTRR24PE**	**NSYTRP24PE**	-	-	-
	4 mm² (2 Pts)	Green	**NSYTRV42PE**	**NSYTRR42PE**	**NSYTRP42PE**	**NSYTRV42MPE**	-	-
	4 mm² (3 Pts)	Green	**NSYTRV43PE**	**NSYTRR43PE**	**NSYTRP43PE**	-	-	-
	4 mm² (4 Pts)	Green	**NSYTRV44PE**	**NSYTRR44PE**	**NSYTRP44PE**	-	-	-
	6 mm² (2 Pts)	Green	**NSYTRV62PE**	**NSYTRR62PE**	-	-	-	-
	10 mm² (2 Pts)	Green	**NSYTRV102PE**	**NSYTRR102PE**	-	-	-	-
	16 mm² (2 Pts)	Green	**NSYTRV162PE**	**NSYTRR162PE**	-	-	-	-
Knife disconnect	2.5 mm² (2-Pts)	Grey	**NSYTRV42ST** (1)	**NSYTRR22SC**	**NSYTRP22SC**	-	-	-
		Orange	**NSYTRV42STAR** (1)	**NSYTRR22SCAR**	-	-	-	-
	2.5 mm² (3 Pts)	Grey	-	**NSYTRR23SC**	**NSYTRP23SC**	-	-	-
		Orange	-	**NSYTRR23SCAR**	-	-	-	-
	2.5 mm² (2 Levels)	Grey	**NSYTRV42SCD** (1)	**NSYTRR24SCD**	-	-	-	-
Fuse disconnect	4 mm² (2 Pts) 5 x 20 mm fuse	Black	**NSYTRV42SF5**	-	-	-	-	-
		Black (12 V)	**NSYTRV42SF5LD** (2)	-	-	-	-	-
		Black (230 V)	**NSYTRV42SF5LA** (2)	-	-	-	-	-
Basic disconnect (3)	4 mm² (2 Pts)	Grey	**NSYTRV42TB**	**NSYTRR22TB**	**NSYTRP42TB**	-	-	-
Measuring transducer	6 mm² (2 Pts) disconnect	Grey/Orange	**NSYTRV62TTD**	-	-	-	-	-
	6 mm² (2 Pts)	Grey	**NSYTRV62TT**	-	-	-	-	-
		Green	**NSYTRV62TTPE**	-	-	-	-	

(1) 4 mm² terminal, with 2 test points
(2) With light indicator
(3) Fuse or component carrier not supplied.

* Grey terminal with flange.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

	Accessories					Cable ends	
Miniature spring for direct mount	End plate for screw TBs	End plate for spring TBs	End plate for push-in TBs	Plug-in bridge	Marking strips 10 characters	compatible with all technologies	
References	References	References	References	References	References	Wires Cross section area	References
NSYTRR22MP	NSYTRAC22	NSYTRACR22	NSYTRACR22	NSYTRAL22 NSYTRAL23 NSYTRAL24 NSYTRAL25 NSYTRAL210 NSYTRAL210BL NSYTRAL210GR NSYTRAL220	NSYTRAB510 NSYTRAB520 NSYTRAB530 NSYTRAB540 NSYTRAB550 ... NSYTRAB590 NSYTRAB5100 NSYTRAB51100	0.5 mm²	DZ5CE005
NSYTRR22MPBL	NSYTRAC22BL	NSYTRACR22BL	NSYTRACR22BL			0.5 mm²	DZ5CA005
-	-	-	-			0.75 mm²	DZ5CE007
-	-	NSYTRACR23	NSYTRACR23			0.75 mm²	DZ5CA007
-	-	NSYTRACR23BL	NSYTRACR23BL			1 mm²	DZ5CE010
-	-	-	-			1 mm²	DZ5CA010
NSYTRR24MP	-	NSYTRACR24	NSYTRACR24			1.5 mm²	DZ5CE015
NSYTRR24MPBL	-	NSYTRACR24BL	NSYTRACR24BL			1.5 mm²	DZ5CA015
-	NSYTRACE24	NSYTRACRE24	NSYTRACRE24			2.5 mm²	DZ5CE025
-	-	-	-			2.5 mm²	DZ5CA025
-	NSYTRAC22	NSYTRACR42	NSYTRACR42	NSYTRAL42 NSYTRAL43 NSYTRAL44 NSYTRAL45 NSYTRAL410 NSYTRAL410BL NSYTRAL410GR NSYTRAL420	NSYTRAB610 NSYTRAB620 NSYTRAB630 NSYTRAB640 NSYTRAB650 ... NSYTRAB690 NSYTRAB6100 NSYTRAB61100	4 mm²	DZ5CE042
-	NSYTRAC22BL	-	-			4 mm²	DZ5CA042
-	-	-	-			6 mm²	DZ5CE062
-	NSYTRAC23	NSYTRACR43	NSYTRACP43			6 mm²	DZ5CA062
-	-	-	-			10 mm²	DZ5CA102
-	-	-	-			16 mm²	DZ5CA162
-	NSYTRAC24	NSYTRACR44	NSYTRACP44			35 mm²	DZ5CA352
-	-	-	-			50 mm²	DZ5CA502
-	NSYTRACE24	NSYTRACRE44	-				
-	-	-	-				
-	NSYTRAC22	NSYTRACR62	-	NSYTRAL62	NSYTRAB810		
-	NSYTRAC22BL	-	-	NSYTRAL610	NSYTRAB820		
-	NSYTRAC22	NSYTRACR102	-	NSYTRAL102	NSYTRAB1010		
-	NSYTRAC22BL	-	-	-	NSYTRAB1020		
-	NSYTRAC162	NSYTRACR162	-	NSYTRAL162	NSYTRAB1010		
-	-	-	-	-	NSYTRAB1020		
-	NSYTRAC952	-	-	NSYTRAL1502			
-	NSYTRAC22	NSYTRACR22	NSYTRACR22	-			
-	-	NSYTRACR23	NSYTRACR23	-			
-	-	NSYTRACR24	NSYTRACR24	-			
-	NSYTRAC22	NSYTRACR42	NSYTRACR42	-			
-	NSYTRAC23	NSYTRACR43	NSYTRACP43	-			
-	NSYTRAC24	NSYTRACR44	NSYTRACP44	-			
-	NSYTRAC22	NSYTRACR62	-	-			
-	NSYTRAC22	NSYTRACR102	-	-			
-	NSYTRAC162	NSYTRACR162	-	-			
-	Included	NSYTRACR23	NSYTRACPK22	-			
-	Included	-	-	-			
-	-	NSYTRACR24	NSYTRACPK23	-			
-	-	-	-	-			
-	NSYTRACE24	Included	-	-			
-	Included	-	-	-			
-	Included	-	-	-			
-	Included	-	-	-			
-	Included	NSYTRACR23	NSYTRACR42	-			
-	NSYTRACT22	-	-	-			
-	NSYTRACT22	-	-	-			
	NSYTRACT22	-	-	-			

10

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

LED lamps

Note:
Dimensions, see page 321

Characteristics	Multi-Fixing LED Lamps	
	This LED lamps are designed to optimise the life time, consumption, space and accessibility inside the enclosure, as well as having three fixing option as standard.	
Colour	Black RAL 9005	
Ingress protection rating	IP20 according to IEC60529	
Standards	• IEC 60598 • UL 94: For plastic components • UL508A: Control Panel	• UL1598: Lamps • UL8750: LED for lighting • EN55015: EMC
Other characteristics	• Built-in switch • Power consumption: 10 W • Frequency: 50/60 Hz • Power factor: V AC lamps: 0.9 V DC lamps: 1 • Luminosity: 640 lm* • Light Temperature: 4000 K* • LED service life: 25000 h*	• Casing: Plastic UL94 V-0 • Degree of insulation: Class I - Lamps with socket Class II - Lamps without socket • Compliant with RoHS and Reach • Ambiance temperature: Operating: -16°C to +65°C (-3°F to +149°F) Storage: -10°C to +60°C (-14°F to +140°F) • Max. 2 Apms and 5 lamps in serial connection
Connections	• 3 m power black or orange cable with quick connector (Not supplied. See reference below) • 1.5 m interconnection black or orange cable with quick connectors (Not supplied. See reference below) According to the directive IEC 60204-1: • Black cables: Power circuits for switch or DC voltage. • Orange cables: External voltage that may be present even if the cabinet is turned off.	
Supply	• 1 lamp and fixing elements	

Lamp model	Lamps		Cables			
	Socket		Black cables		Orange cables	
		References	Power (3 m) References	Interconnection (1.5 m) References	Power (3 m) References	Interconnection (1.5 m) References
With socket 120 / 230 V AC	SCHUKO	**NSYLAMLDS**	**NSYLAM3M**	**NSYLAM1M**	**NSYLAM3MN**	**NSYLAM1MN**
With socket 120 / 230 V AC	UTE	**NSYLAMLDF**	**NSYLAM3M**	**NSYLAM1M**	**NSYLAM3MN**	**NSYLAM1MN**
With socket 120 / 230 V AC	British	**NSYLAMLDB**	**NSYLAM3M**	**NSYLAM1M**	**NSYLAM3MN**	**NSYLAM1MN**
With socket 120 V AC	USA	**NSYLAMLDU**	**NSYLAM3MUL**	**NSYLAM1MUL**	**NSYLAM3MULN**	**NSYLAM1MULN**
Without socket 120 / 230 V AC	– –	**NSYLAMLD**	**NSYLAM3M**	**NSYLAM1M**	**NSYLAM3MN**	**NSYLAM1MN**
Without socket 120 / 230 V AC	–		**NSYLAM3MUL**	**NSYLAM1MUL**	**NSYLAM3MULN**	**NSYLAM1MULN**
Without socket With presence detection 230 V AC	– –	**NSYLAMLDD**	**NSYLAM3M**	**NSYLAM1M**	**NSYLAM3MN**	**NSYLAM1MN**
Without socket With presence detection 230 V AC			**NSYLAM3MUL**	**NSYLAM1MUL**	**NSYLAM3MULN**	**NSYLAM1MULN**
Without socket - DC 24-48 V DC	– –	**NSYLAMLDVDC**	**NSYLAM3MDC**	-	-	-
Without socket - DC 24-48 V DC			**NSYLAM3MDCUL**	-	-	-

Rack for VDI

Supply:
supplied with fixing elements.

• 1 U, 19" rack. For lamp installation in VDI enclosures.

NSYLAM1U

Characteristics	References
Rack for VDI	**NSYLAM1U**

Fixing options

Fixing by sliding brackets



Magnetic fixing.



Fixing to DIN rail.



Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

LED lamps

3 pole connectors

NSYLAMACF

NSYLAMDCF

NSYLAMACM

NSYLAMDCM

- Designed to connect Multi-Fixing LED Lamps.
- Colour:
  AC: Black
  DC: Black (body) and brown (head)
- Ingress protection rating: IP20
- Rated current: 16 A
- Rated voltage: 250 V
- Strain relief: Yes
- Connection type for cabling: Screw connection
- Material: Polyamide
- Dimensions:
  Length: 53.2 mm
  Width: 23 mm
  Height: 13.8 mm

- **Connection data:**
  Cable diameter: 9 mm
  Cable diameter 2: 5.5 mm
  Cross section solid: 2.5 mm²
  Cross section solid 2: 0.5 mm²
  Connection cross section stranded (max.): 2.5 mm²
  Cross section stranded 2: 0.5 mm²

Characteristics	References	
3 pole female connectors AC model	**NSYLAMACF**	New
3 pole female connectors DC model	**NSYLAMDCF**	New
3 pole male connectors AC model	**NSYLAMACM**	New
3 pole male connectors DC model	**NSYLAMDCM**	New

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

LED lamps

Cost-effective LED lamps

- This LED lamp is designed to optimise the cost benefit relation and can be used in almost all enclosures respecting the dimensions.
  It can be interconnected using a single power source:
  5 W lamps: Max. 10 lamps interconnected,
  10 W lamps: Max. 5 lamps interconnected.
- Built-in switch
- Light Temperature: 4000 K*
- LED service life: 25000 h*
- Casing:
  Plastic for transparent cover and connectors
  Aluminium for body
- Degree of insulation: Class I
- Compliant with RoHS and Reach
- Ambiance temperature:
  Operating: -16°C to +65°C (-3°F to +149°F)
  Storage: -10°C to +60°C (-14°F to +140°F)
- Colour: Aluminium
- Ingress protection rating: IP20 according to IEC60529
- Standards: IEC 60598



Supply:
1 lamp and fixing elements
3 m connection cable with quick connector
1 m interconnection cable with quick connectors

* Approximate values.

NSYLAMT5LD1

Characteristics	Voltage (V)	Power (W)	Power factor	Frequency (Hz)	Luminous flux (lm)*	References
Cost-effective LED lamps	120/230 V AC	5	0.8	50-60	500	**NSYLAMT5LD1**
Cost-effective LED lamps	120/230 V AC	10	0.9	50-60	1100	**NSYLAMT5LD2**
Cost-effective LED lamps	24/48 V DC	5	1	-	470	**NSYLAMT5LD1VDC**

Portable LED lamp

- This LED portable lamp is designed to be installed as
- enclosure lamp or maintenance lamp bringing mobility,
- resistance, versatility and durability.
- Double function:
  internal enclosure lamp,
  maintenance lamp.
- E27 LED lamp
- Built-in recessed switch
- Light temperature: 4000 K*
- LED service life: 25000 h*
- Power cable 3 m long with male plug (European standard type)
- Casing: Plastic, UL94 V-0
- Degree of insulation: Class II
- Compliant with RoHS and Reach
- Ambiance temperature:
  Operating: -16°C to +65°C (-3°F to +149°F)
  Storage: -10°C to +60°C (-14°F to +140°F)
- Colour: Black RAL 9005
- Ingress protection rating: IP20 according to IEC60529
- Standards:
  IEC 60598
  UL 94: For plastic components



Supply:
1 lamp with 3 m power cable with European universal plug
1 fix base
Fixing elements

* Approximate values.

NSYLAMPORTLD

Characteristics	Voltage (V)	Power (W)	Power factor	Frequency (Hz)	Luminous flux (lm)*	References
Portable LED lamp	120/230 V AC	10	0.5	50-60	1100	**NSYLAMPORTLD**

Fixing options

Magnetic fixing.

Fixing by adapter brackets.

Use options

Fixing by adhesive or by screws.

Used on workbench.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Casters and feet for floor-standing enclosures

SM SF SD Transport casters*



NSYSTW

- Quick installation on plinths with heights of 100 and 200 mm, except the plinth for enclosure sets.
- They can be installed in front or side position.
- Clipping and fixing to the corner by screws.
- For use on flat surfaces.
- Height: 110 mm
- Maximum load: 200 kg

Supply:
4 transport casters
(2 with a blocking system)
and fixing elements

Characteristics	References
Transport casters	**NSYSTW**

SM SF SD Enclosure casters
SMX SFX SDX

NSYSW

- Double casters.
- Height: 92 mm.
- Diameter: 64 mm.
- Maximum load:
  135 kg per caster
  1000 kg when it is installed directly on the upright,
  400 kg when it is installed on the frame

Supply:
4 casters and fixing elements

Characteristics	References
Enclosure casters	**NSYSW**

SM SF SD Levelling feet
SMX SFX SDX

NSYSPSJ

- Height: 42 mm
- Material: Steel
- Maximum load: 400 kg

Supply:
Set of 4 floor feet

Characteristics	References
Levelling feet fixed	**NSYSPSJ**

SM SF SD Levelling feet
SMX SFX SDX

NSYSPRJ

- Height: 22 mm
- Maximum load: 400 kg

Supply:
Set of 4 floor feet

Characteristics	References
Levelling feet adjustable	**NSYSPRJ**

SM SF SD Hygienic stainless steel feet
SMX SFX SDX

NSYPHX200

- Hygienic feet specific for harsh environments.
- Adjustable: 140 to 200 mm.
- Material: 316L stainless steel
- Maximum load: 800 kg

Supply:
Set of 4 hygienic feet

Characteristics	References
Hygienic stainless steel feet	**NSYPHX200**

10

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Switches and pockets

S3D S3X Door switch for wall-mounting enclosures

NSYINLCRN

- Switch/commutator unit equipped with support and fixings for direct fixing to the enclosure.
- Can be used to control lighting, air-conditioning units, etc.
- It is not compatible with installing the 19" swing rack and the internal door.
- NC + NO contact, 10 A/500 V.

Supply:
1 door switch and fixing elements

Characteristics	References
Door switch for wall-mounting enclosures	**NSYINLCRN**

SM SF SFX Door switch for floor-standing enclosures

NSYDCM20

- The switch is fixed to the structure of the enclosure.
- Drilled M20 cable entry for cable gland.
- NC + NO contact, 10 A/500 V.

Supply:
1 door switch and fixing elements

Characteristics	For ranges	References
Door switch for floor-standing enclosures	SF and SFX	**NSYDCM20**
Door switch for floor-standing enclosures	SM	**NSYMDCM20**

SF SM Metal document pocket

NSYSDP6M

- Direct mounting on the reinforcement frame of the door.
- Adjustable depth with a pitch of 25 mm.
- Material: Steel
- Finish: Structured finish, epoxy polyester powder
- Colour: RAL 7035 grey



Supply:
1 metal document pocket and fixing elements

Characteristics	Width (mm)	References
Spacial SF/SM Metal document pocket	600	**NSYSDP6M**
Spacial SF/SM Metal document pocket	800	**NSYSDP8M**

SF SM Plastic document pocket



NSYDPA5

- Attachment by adhesive tape.
- Material: Polystyrene (PS)
- Colour: RAL 7035 grey (NSYDPA4: RAL 9001)



Note:
NSYDPA44 not compatible with 19" chassis or modular distribution.

Supply:
1 plastic document pocket

Characteristics	Doc. format	A (mm)	B (mm)	C (mm)	References
Spacial SF/SM Plastic document pocket	A5	174	188	22	**NSYDPA5**
Spacial SF/SM Plastic document pocket	A4	230	247	23	**NSYDPA4**
Spacial SF/SM Plastic document pocket	A4	234	278	40	**NSYDPA44**
Spacial SF/SM Plastic document pocket	A3	285	476	35	**NSYDPA3**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Door accessories for floor-standing enclosures

SF SM Folding support tray

NSYSDT5

NSYSDT8

- Adjustable horizontal support for laptop computers, documents or any other element.
- Installation on the reinforcement frame of the door.
- Can also be installed on the door cross rails.
- 4 positions: 45°, 60°, 75° and 90°.
- Maximum load: 30 kg
- Material: Steel
- Finish: Structured finish, epoxy polyester powder
- Colour: RAL 7035 grey



Supply:
1 folding support tray and fixing elements

Characteristics	Width (mm)	References
Spacial SF/SM-Folding support tray	500	**NSYSDT5**
Spacial SF/SM-Folding support tray	600	**NSYSDT6**
Spacial SF/SM-Folding support tray	800	**NSYSDT8**

Door cross rails



- Direct mounting cross rails on the profiles of the reinforcement frame of the door.
- Adjustable height with a pitch of 25 mm.
- Material: Galvanised steel
- Thickness: 20/10e mm

Supply:
2 cross rails and bag of fixings

NSYSDCR4

Characteristics	Width (B)	References
Door cross rails	400	**NSYSDCR4**
Door cross rails	500	**NSYSDCR5**
Door cross rails	600	**NSYSDCR6**
Door cross rails	800	**NSYSDCR8**
Door cross rails	1000	**NSYSDCR10**

SM Floor-standing door retainer

NSYSMDR

- Door blocker at the opening limit.
- It is fixed directly to the front frame of them enclosure and to the reinforcement frame of the door.
- It can be installed on doors that open both to the right and to the left.

Supply:
Door stop and fixing elements

Characteristics	Limit	References
Floor-standing door retainer	90°	**NSYSMDR**
Floor-standing door retainer, Compatible with SFX	90° and 120°	**NSYSMNDR**

SF Floor-standing door retainer




NSYSFMDR

- Door blocker at the opening limit.
- It is fixed directly to the front frame of them enclosure and to the reinforcement frame of the door.
- It can be installed on doors that open both to the right and to the left.

Supply:
Door stop and fixing elements

Characteristics	Limit	References
Floor-standing door retainer	90° and 120°	**NSYSFMDR**
Floor-standing door retainer	120°	**NSYSFNDR**

10

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Door accessories for wall-mounting enclosures

S3D S3X Wall-mounting door retainer Steel

To block the door in the open position.
- It is installed on enclosures with heights from 400 mm and widths from 300 mm.
- Door opening angle: 120°.
- Earthing connection of the enclosure by means of the reinforcement rail.
- Earthing accessories supplied with the enclosure (earth-connection wire to be ordered separately), see page 305.
- Material: Steel

Note:
Cannot be installed on 19" mounting plates or on enclosures equipped with internal door.

NSYAEDRSCST

Characteristics	References
Wall-mounting door retainer Steel	**NSYAEDRSCST**

S3D Wall-mounting door retainer Polyamide

To block the door in the open position.
- It is installed on the perforated rails of the enclosure doors at the required height.
- Material: Polyamide 6 (PA6)

Note:
It is only installed on enclosures with a height of less than 400 mm (no perforated rails).

NSYAEDRS3DPA6

Characteristics	References
Wall-mounting door retainer Polyamide	**NSYAEDRS3DPA6**

10

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Window for modular equipment

Fig. 1



Fig. 2



- They provide viewing and access to the inside of the enclosure while keeping the IP65 protection degree.
- Material: Transparent polycarbonate
- Ingress protection rating: IP65 according to IEC 60529

Supply:
1 window

NSYVA278M

NSYVA272MA

Characteristics	N.° of modules	Fig. n.°	A	B	C	References
Window for modular equipment, Low cover	2	1	78	60	15	**NSYVA272M**
Window for modular equipment, Low cover	4	1	78	95	15	**NSYVA274M**
Window for modular equipment, Low cover	6	1	78	130	15	**NSYVA276M**
Window for modular equipment, Low cover	8	1	78	165	15	**NSYVA278M**
Window for modular equipment, Low cover	10	1	78	200	15	**NSYVA2710M**
Window for modular equipment, Low cover	12	1	78	235	15	**NSYVA2712M**
Window for modular equipment, Low cover	16	2	195	165	13	**NSYVA2716M**
Window for modular equipment, Low cover	24 in 2 rows	2	196	235	13	**NSYVA2724M**
Window for modular equipment, High cover	2	1	78	60	25	**NSYVA272MA**
Window for modular equipment, High cover	4	1	78	95	25	**NSYVA274MA**
Window for modular equipment, High cover	6	1	78	130	25	**NSYVA276MA**
Window for modular equipment, High cover	8	1	78	165	25	**NSYVA278MA**
Window for modular equipment, High cover	10	1	78	200	25	**NSYVA2710MA**
Window for modular equipment, High cover	12	1	78	235	25	**NSYVA2712MA**

Plastic window

- Plastic window with hinged cover for installation on front panel.
- External dimensions: 213 x 133 mm.
- Internal dimensions of the window: 180 x 78 mm.
- Material:
  Cover: Polycarbonate
  Body: PVC
- Ingress protection rating: IP55 according to IEC 60529

Supply:
1 plastic window delivered with a drilling template

NSYMW10M

Characteristics	References
Plastic window	**NSYMW10M**

Plastic window for modular equipment

- Frame with transparent hinged cover for mounting modular switchgear on the front panel.
- Opening: 46 x 180 mm (10 modules).
- Material:
  Cover: Polycarbonate
  Body: PVC
- Ingress protection rating: IP55 according to IEC 60529

Supply:
1 modular front panel

NSYMW10MK

Characteristics	References
Plastic window for modular equipment	**NSYMW10MK**

Kit for fixing the switchgear

- The unit is delivered assembled.

Supply:
1 DIN rail and two supports.

NSYMW10MR

Characteristics	References
Kit for fixing the switchgear	**NSYMW10MR**

Mounting example

NSYMW10MK + NSYMW10MR.

10

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Control window





- To prevent accidental handling of the control units by any unauthorised person.
- Allows all the displayed information to be read without opening the door.
- Equipped with hinges for opening (180°).
- Closure by a n° 2233X lock.
- Indoor installation.
- Material: Aluminium frame and 3 mm acrylic window

Supply:
1 window, fixings
and instruction sheet

NSYCW33

Characteristics	Dimensions A (mm)	Dimensions B (mm)	References
Control window	300	300	**NSYCW33**
Control window	400	400	**NSYCW44**
Control window	400	500	**NSYCW45**
Control window	400	600	**NSYCW46**
Control window	500	400	**NSYCW54**
Control window	500	500	**NSYCW55**
Control window	500	600	**NSYCW56**
Control window	600	500	**NSYCW65**
Control window	600	600	**NSYCW66**
Control window	800	600	**NSYCW86**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Earthing accessories

Earthing strip

NSYECB1M153

- Perforated brass bar, 15 x 3 mm.
- 1 m long.
- 87 connection points, M5 drill holes

Supply:
1 earthing strip
and fixing elements

Characteristics	References
Earthing strip	**NSYECB1M153**

S3D S3X Fixing lugs for the earthing strip

NSYEDCOS





- They allow the mounting of an earthcollector rail or a DIN rail at the top and bottom of an enclosure.
- Mounting incompatible with certain accessories. Please consult us.
- Fixing: On holes made in the gutter of the enclosure.

Supply:
2 lugs and fixings.

Characteristics	References
Fixing lugs for the earthing strip	**NSYEDCOS**

SM SF SD SMX SFX SDX Central earthing point

NSYCEP

- Connects earthing braids and cables to the structure of the enclosure.
- The earth connection is made by means of the M8 x 18 mm bolt.
- Fixing: Fixing to the structure by means of self-tapping screws

Supply:
1 central earthing point, elements for fixing to the structure, and fixings for fixing to the bolt

Characteristics	References
Central earthing point	**NSYCEP**

Earth braids

NSYEB156D6

- They guarantee the earth connection for high frequencies, avoiding the disturbing electric currents that are produced.
- Material: Tinned copper.

Supply:
10 earth braids
(nuts and washers not included)

Characteristics	Section (mm²)	Terminal Ø (mm)	Length (mm)	Width (mm)	References
Earth braids	6	7	150	12	**NSYEB156D6**
Earth braids	10	6.5	150	17	**NSYEB1510D6**
Earth braids	16	8.5	155	17	**NSYEB1516D8**
Earth braids	25	8.5	200	27	**NSYEB2025D8**
Earth braids	50	8.5	200	33	**NSYEB2050D8**

Earth cables

NSYEL136D6

- Make it easier to install a safe earth connection, with a perfect contact, with optimised length.
- Material: Brass and copper alloy terminal, green and yellow PVC insulating sheath

Supply:
10 earth cables (nuts and washers not included). Reference by unit. Order by multiples of 10 (10, 20, 30...)

Characteristics	Section (mm²)	Terminal Ø (mm)	Length (mm)	References
Earth cables	6	6.4	130	**NSYEL136D6**
Earth cables	6	6.4	160	**NSYEL166D6**
Earth cables	6	8.3	160	**NSYEL166D8**
Earth cables	10	8.3	170	**NSYEL1710D6**
Earth cables	6	6.4	220	**NSYEL226D6**
Earth cables	6	13	220	**NSYEL226D13**
Earth cables	25	8.3	220	**NSYEL2225D8**
Earth cables	10	6.4	250	**NSYEL2510D6**
Earth cables	25	8.3	350	**NSYEL3525D8**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Paint accessories

Aerosol paint can

NSYBPA7032

- Air-drying paint.
- Content: 150 g.

Note:
Not available for destinations outside Europe.

Characteristics	References
Aerosol paint can, RAL 7032	**NSYBPA7032**
Aerosol paint can, RAL 7035 grey	**NSYBPA7035**

Paint touch-up

NSYTUP7032

- Paint for touching up with a brush.
- Air-drying paint.

Characteristics	References
Paint touch-up, RAL 7032	**NSYTUP7032**
Paint touch-up, RAL 7035 grey	**NSYTUP7035**

Renovation and anti graffiti paint

NSYAUPG1G

- Paint kit with 2 components (base 80 % + hardener 20 %)
- Specially designed for polyester enclosures, for their renovation and/or as prevention to allow easy removal of graffiti.
- Colour: RAL 7035 grey

Supply: NSYAUPG1G
The 1 kg reference includes 1 pot with 800 g of base paint and 200 g of hardener
(It is enough to paint a surface of around 5 m2)

Supply: NSYAUPG5G
The 5 kg reference includes 1 pot with 4 kg of base paint and 1 kg of hardener
(It is enough to paint a surface of around 25 m²)

Characteristics	References
Renovation and anti graffiti paint	**NSYAUPG1G**
Renovation and anti graffiti paint	**NSYAUPG5G**

- Solvent bottles to be used as a paint thinner or to clean brushes.

Supply:
1 kg

Characteristics	References
Renovation and anti graffiti paint solvent	**NSYAUPGS**

10

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Mounting plates for wall-mounting enclosures

Plain and silkscreened mounting plates





Only for 1000 x 800



From the size of 1000 x 1000



1. Left plate
2. Right plate
3. Central backstud
4. **NSYCRNGSDR** bracket (includes fixings)
5. M8 x 20 mm screw

Microperforated mounting plate



Telequick mounting plate



Joinable Telequick mounting plate







10

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Mounting plates for wall-mounting enclosures

Bakelite and polyester mounting plate



P = Height
S = Width

DIN rail chassis



Step slides for mounting plate



Step slides for 2 mounting plates in one enclosure



1. Left plate
2. Right plate
3. Central backstud
4. **NSYCRNGSDR** bracket (includes fixings)
5. **NSYSDRSDCR** slide bracket
6. M8 x 20 mm screw

Vertical rails for wall-mounting enclosures

Slides and brackets



Uprights



Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Mounting plates for floor-standing enclosures

Plain mounting plate



Partial mounting plate



Perforated mounting plate Telequick



1 Cut-outs 11 x 26 with a pitch of 15 x 30.

Examples of perforated mounting plate installation

- Perforated plate mounted on structure.



- Perforated plate mounted on technical vertical uprights.

- Perforated plate mounted on standard vertical uprights.

- Perforated plate mounted on cross rails.

Intermediate mounting plate



Reinforcement for mounting plate



10

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Mounting plate brackets for floor-standing enclosures

Dimensions

Brackets for fixing mounting plates in back-to-back position



Brackets for fixing intermediate mounting plates in back-to-back position



Mounting plates for floor-standing enclosures

Dimensions

Examples of combination

Length of joined Spacial SF enclosures (mm)	Example of Spacial SF enclosure combination width (mm) (B)	Example of combining mounting plates by width (mm)	Useful length (mm)
1200	1200	600 + 800	1192
1400	600 + 800	600 + 1000	1392
1600	2 x 800	800 + 1000	1592
1800	3 x 600	800 + 1200	1792
2000	2 x 1000	1000 + 1200	1992
2200	600 + 2 x 800	1200 + 1200	2192
2400	3 x 800	1600 + 1000	2392
2400	3 x 800	3 x 600 + 1000	2384
2600	2 x 1000 + 600	1600 + 1200	2592
2600	2 x 1000 + 600	3 x 600 + 1200	2584
2800	2 x 1000 + 800	4 x 800	2784
3000	3 x 1000	3 x 800 + 1000	2984
3200	2 x 1000 + 1200	3 x 800 + 1200	3184
3400	3 x 800 + 1000	800 + 3 x 1000	3384
3600	3 x 1200	4 x 1000	3584
3800	800 + 3 x 1000	600 + 3 x 1200	3784
4000	4 x 1000	800 + 3 x 1200	3984

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Uprights for floor-standing enclosures

Technical uprights



Standard uprights



Cross rails for floor-standing enclosures

Universal cross rails

40 mm (1 row)



65 mm (2 rows)

90 mm (3 rows)



Quick fixing cross rails

40 mm (1 row)



65 mm (2 rows)



90 mm (3 rows)



Light cross rails



Cross rail for Lütze chassis



Support for Lütze chassis



10

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Profiles for floor-standing enclosures

Vertical adaptation profiles



Horizontal adaptation profiles



10

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Symmetric mounting rail for the wall-mounting enclosures

Type A



Type B



Symmetric DIN rails for floor-standing enclosures



Asymmetric DIN rails for the floor-standing enclosures



Double-profile DIN rails

Type W



Type F



Serrated C-shaped rail for heavy loads



Symmetric C-shaped rails



Type	Dimensions (mm)								References
	A	J	C	D	E	F	G	H	
C20 Not perforated	21	11	10	1.5	5.5	-	-	-	**NSYCN20**
C20	21	11	10	1.5	5.5	5	6.2	15	**NSYCNT20**
C40 Not perforated	40	20	24	1.5	8	-	-	-	**NSYCN40**
C40	40	20	24	1.5	8	10	8.5	30	**NSYCNT40**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

2000 mm rails

Symmetric rails

Type A



Type B



Type C



Type D



Asymmetric DIN rails



Double-profile DIN rails



Connectors for symmetric C-shaped rails

Examples

Combinations with connectors for symmetric C-shaped rails

EMA connectors



Dimensions (mm)					References
A	B	C	D	E	
60	21.3	6	6.2	15	**NSYEMA20**
100	40.3	10	8.5	25	**NSYEMA40**

EVA connectors



Dimensions (mm)					References
A	B	C	D	E	
43	19	2	6.2	15	**NSYEVA20**
78	36	2.5	8.5	25	**NSYEVA40**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Connectors for symmetric C-shaped rails

UCA connectors



Dimensions (mm)							References
A	B	C	D	E	F	G	
21.3	60	21.3	6	2	6.2	15	**NSYUCA22**
40.3	116	40.3	10	2.5	8.5	25	**NSYUCA44**

UTA connectors



Dimensions (mm)							References
A	B	C	D	E	F	G	
21.3	21.5	53.5	8	2	6.2	15	**NSYUTA22**
21.3	40.5	72.5	8	2	6.2	15	**NSYUTA42**
40.3	40.5	81	10	2.5	8.5	25	**NSYUTA44**

ECA connectors



Dimensions (mm)								References
A	B	C	D	E	F	G	H	
21.3	21.5	8	2	6.2	15	6.2	15	**NSYECA22**
21.3	40.5	8	2	6.2	15	6.2	13	**NSYECA42**
40.3	40.5	10	2.5	8.5	25	8.5	25	**NSYECA44**

UR connectors



Dimensions (mm)						References
A	B	C	D	E	F	
60	18	2	20	15	5	**NSYUR20**
130	36	3	40	30	10	**NSYUR40**
130	55	3	40	30	10	**NSYUR60**

UT connectors



Dimensions (mm)						References
A	B	C	D	E	F	
54	54	2	20	20	5	**NSYUT20**
60	80	2	20	25	8	**NSYUT40**
80	110	2	20	29	10	**NSYUT60**

EN connectors

NSYEN20



NSYEN40



NSYEN60



Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Mounting Spacers

Hexagonal spacers



ETU modular spacers





Dimensions (mm)		Combination of spacers
Minimum height	Maximum height	References
53	53	**NSYETU48** + **NSYETU48**
63	63	**NSYETU48** + **NSYETU58**
85	85	**NSYETU48** + **NSYETU79**
124	124	**NSYETU48** + **NSYETU118**
73	73	**NSYETU58** + **NSYETU58**
94	94	**NSYETU58** + **NSYETU79**
134	134	**NSYETU58** + **NSYETU118**
84	84	**NSYETU79** + **NSYETU79**
124	124	**NSYETU79** + **NSYETU118**
164	164	**NSYETU118** + **NSYETU118**

Cable management Cable entries

Multi-C







NSYTSAM504SE



NSYTSAM638SE







NSYTSAM508SE



NSYTSAM6313SE

Position of the holes
on the circular cable entries
with diameters 50 and 63 mm

10

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Multi-R



Diagrams of dimensions and positions of the holes on a rectangular cable entry

NSYTSA2414SE



NSYTSA2417SE



NSYTSA2429SE



NSYTSA2422SE



NSYTSA2423SE



Multi-T

NSYAECPFLBP



NSYAECPFLT7



NSYAECPFLT25



NSYAECPFLT35



10

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Multi-H



Multi-F



Multi-CR



Cut-out for reference **NSYDCE24●●●**



Cut-out for reference **NSYDCE16●●●**

Multi-CS





Multi-CF



10

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Steel adapter plate for FL13 and FL21 membranes

FL13



NSYTLBFL

FL21



NSYTLCFL
NSYTLDFL
NSYTLEFL
NSYTLFFL
NSYTLGFL

FL21



NSYTLF2FL
NSYTLG2FL

FL21



NSYTLG4FL

Application example



Our membrane can be easily adapted to fit onto all our metallic enclosures using the adapter plate.

10

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Cable management Cable holding

Lower cable-guide cross rail



L-rail for fixing cables



Door cable-guide cross rail



Plastic cable support



Door cable-guide cross rails for wall-mounting enclosures



Cable management Ducts

10

Ø 22 mm cable-duct support



Cable-duct support on technical upright



Plastic cable-duct support



Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

LED lamps

Multi-Fixing LED Lamps



Fixing options

Fixing by sliding brackets

Magnetic fixing.

Fixing to DIN rail.

Cost-effective LED Lamps



Fixing options

Magnetic fixing

Fixing by adapter brackets

Portable LED lamp



Use options

Fixing by adhesive or by screws

Used on workbench

Casters and feet for floor-standing enclosures

Transport casters Only for Spacial SM, SF and SD



Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Switches and pockets

Door accessories Plastic document pocket



Door accessories Metal document pocket



Door accessories for floor-standing enclosures

Folding support tray



Door cross rails



10

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Door accessories Windows

Window for modular equipment

Fig. 1



Fig. 2



Plastic window for modular equipment

Mounting example

NSYMW10MK + NSYMW10MR.

Control window







Other accessories Earthing accessories

Fixing lugs for the earthing strip





Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Applicative and customised solutions

Contents

Solutions for electrical distribution	326
Terminal blocks	326
Modular wall-mounting enclosures	329
Accessories for modular floor-standing enclosures	333
Accessories for low voltage switchboards	340
Prisma functional system	364
Solutions for Motor Control Centres	384
Outdoor Heavy Duty enclosures	416
Seismic and nuclear enclosures	430
Electronic applications	452
Electromagnetic protected steel enclosures (EMC)	472
Enclosures for explosive atmospheres (ATEX)	480
Human-Machine Interface Control enclosure, PC rack and control desks	488
Variable speed drive flush-mounting kits	526
Automobile applications	530
Customised solutions	532

The **Spacial S3DB** enclosure is made to be equipped with terminal blocks.

It is ready to be equipped with a ladder mounting plate and a symmetrical DIN rail (to be ordered separately). The body does not have cable gland opening. The Spacial S3DB enclosure is the ideal coupling enclosure with FL21 cut-out.

Spacial S3DB

Vertical position

Horizontal position

Safety

Welding studs on door and body
(earth cables to be ordered separately).

Smart

Example of installation with the ladder mounting plate.

11

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Spacial S3DB

Body
Single-piece body, folded and welded. Front rail with double sheet thickness, guttershaped.
- Depth 150 mm
  The terminal enclosure can be installed vertically (the width becomes the height).
- Wall-mounting directly or by means of fixing lugs (to be ordered separately).
- 4 M8 x 25 shouldered backstuds.
- Body without cable gland openings.

Door
- Easily removable and reversible door, with 20 mm return with double sheet thickness granting excellent rigidity; Equipped with 2 hinges opening to 180°.
- Door opening to more than 180° for maximum accessibility (the door comes to rest on the body of the enclosure in top position).
- Maximum acceptable load on the door: 20 kg/m².
- Wall-mounting enclosure supplied with 3 mm double bar lock as standard.
- M6 x 16 earthing screw for equipotential connection between the door and the body of the enclosure.

Dedicated accessories
The terminal enclosure, with a depth of 150 mm, can be equipped:
- With 2 rails to be installed on the 4 M8 x 25 shouldered backstuds. See page 15.
- With a symmetrical rail to be installed on the rails.
- With a 6 mm² earth braid to be placed between the body and the door.
- It can also be equipped with a plain mounting plate, see page 240.

- Finish: Structured finish, epoxy polyester powder
- Colour: RAL 7035 grey
- Ingress protection rating: IP66 according to IEC 60529
- Mechanical protection rating: IK10 according to IEC 62262

For more details see page 328

NSYS3DB25315

Characteristics	Height (mm)	Width (mm)	Depth (mm)	References
Spacial S3DB	250	300	150	**NSYS3DB25315**
Spacial S3DB	250	400	150	**NSYS3DB25415**
Spacial S3DB	250	500	150	**NSYS3DB25515**
Spacial S3DB	300	300	150	**NSYS3DB3315**
Spacial S3DB	300	400	150	**NSYS3DB3415**
Spacial S3DB	300	500	150	**NSYS3DB3515**
Spacial S3DB	300	600	150	**NSYS3DB3615**
Spacial S3DB	400	300	150	**NSYS3DB4315**
Spacial S3DB	400	800	150	**NSYS3DB4815**
Spacial S3DB	500	400	150	**NSYS3DB5415**
Spacial S3DB	600	400	150	**NSYS3DB6415**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Spacial S3DB



A: Enclosure height
B: Enclosure width
C: Enclosure depth

1 With ladder mounting plate installed.
2 M6 x 17.5 mm earthing stud.
3 Stud centre-to-centre distance.
4 Centre-to-centre distance of the holes for direct fixing.
5 Drop-leaf door.

The provided dimensions are with the ladder mounting plate, which is the most commonly used accessory with this enclosure.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Modular wall-mounting enclosures

The **Spacial S3DM** enclosure for modular switchgear can be equipped with:

- a modular chassis (**NSYDLM•••**) with cut-out front panels for 24 to 234 modules according to the dimensions and references,
- a 6 mm² earth connection placed between the body and the door.

The enclosure can be equipped with accessories from the Spacial standard wall-mounting range.

Spacial S3DM

S3DM enclosure
(standard delivery).

S3DM enclosure equipped
with a DLM modular chassis.

Easily removable and reversible door

- With 20 mm return with double thickness granting excellent rigidity, opening to 120°, equipped with 2 or 3 invisible hinges.
- Three locking points for heights of more than 600 mm.
- Perforated rails on the hinge side of the door, with drill holes with a diameter of 4.2 mm in steps of 25 mm.

Dedicated accessories

- The DLM modular chassis consists of metal cut-out front panels which can clip on with any screws. Rigid structure made from galvanised steel. The depth of the chassis can be adjusted from 40 to 85 mm, between the rail and the front panel, allowing the installation of all types of devices.
- For enclosures with a depth of 150 mm, the chassis can be installed at the front or on the backstuds at the rear. It is possible to adjust its depth using the adjustable supports (**NSYSDCR••** type).
- It can also be equipped with a plain mounting plate, see **page 240**.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Modular wall-mounting enclosures

Spacial S3DM

- Single-piece body, folded and welded.
  Front rail with double sheet thickness, gutter-shaped.
- 4 M8 x 25 mm shouldered backstuds for installing chassis and step slides, leaving a space of 10 mm behind them.
- Cable gland plate (245 x 80) at the top and bottom of the enclosure, guaranteeing the maximum access surface (also available in plain door).
- Finish: Structured finish, epoxy polyester powder
- Colour: RAL 7035 grey
- Ingress protection rating: IP66 according to IEC 60529
- Mechanical protection rating: IK08 according to IEC 62262

Supply:
Wall-mounting enclosure supplied with 3 mm double bar lock as standard

NSYS3DM7515T

Characteristics	Height (mm)	Width (mm)	Depth (mm)	References
Spacial S3DM	400	300	150	**NSYS3DM4315T**
Spacial S3DM	500	400	150	**NSYS3DM5415T**
Spacial S3DM	600	400	150	**NSYS3DM6415T**
Spacial S3DM	600	600	150	**NSYS3DM6615T**
Spacial S3DM	700	500	150	**NSYS3DM7515T**
Spacial S3DM	800	600	150	**NSYS3DM8615T**
Spacial S3DM	1000	600	150	**NSYS3DM10615T**
Spacial S3DM	1000	800	150	**NSYS3DM10815T**



Front panel cut-out (see table below)

1 Front face of the modular chassis / front face of the door
2 Cable gland plates at the top and bottom of the enclosure.

Number of modules per chassis** (every 18 mm)

1 module = 2 steps = 18 mm



Chassis reference	NSYDLM24	NSYDLM48	NSYDLM48P	NSYDLM84P	NSYDLM66	NSYDLM88	NSYDLM84	NSYDLM112	NSYDLM168	NSYDLM240
Enclosure height (mm)	400	500	600	600	700	700	800	800	1000	1000
Enclosure width (mm)	300	400	400	600	500	500	600	600	600	800
Number of rows	2	3	3	3	3	4	3	4	6	6
Modules per row	12	16	16	28	22	22	28	28	28	39
Total n. of modules	24	48	48	84	66	88	84	112	168	234

Note:
References **NSYDLM48**, **NSYDLM48P** and **NSYDLM84P**, the central row cannot receive modules at the height of the lock (check our technical instructions) when installed at the front of the enclosure. In this case, 1 module is sealed up. ** DLM modular chassis. The provided dimensions are with the modular chassis, which is the most commonly used accessory with this enclosure.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Modular wall-mounting enclosures

DLM modular chassis

- The chassis consists of metal cut-out front panels, which can be clipped on without screws.
- The depth of the chassis can be adjusted from 40 to 85 mm, between the rail and the front panel, allowing the installation of all types of devices.
- Material: Rigid galvanised steel structure
- Finish: Structured finish, epoxy polyester powder
- Colour: RAL 7035 grey

Note:
1 module = 2 steps = 18 mm

NSYDLM24

Characteristics	Number of modules	Height (mm)	Width (mm)	References
DLM modular chassis	24	400	300	**NSYDLM24**
DLM modular chassis	48	500	400	**NSYDLM48**
DLM modular chassis	48	600	400	**NSYDLM48P**
DLM modular chassis	84	600	600	**NSYDLM84P**
DLM modular chassis	66	700	500	**NSYDLM66**
DLM modular chassis	88	700	500	**NSYDLM88**
DLM modular chassis	84	800	600	**NSYDLM84**
DLM modular chassis	112	800	600	**NSYDLM112**
DLM modular chassis	168	1000	600	**NSYDLM168**
DLM modular chassis	234	1000	800	**NSYDLM240**



Front panel cut-out


Detail A
Rail adjustment: 45 mm

Plain front panel

- Metal front panels to be clipped on without screws.
- Finish: Structured finish, epoxy polyester powder
- Colour: RAL 7035 grey

Supply:
2 plain front panel and fixings

NSYCTL300DLM

Characteristics	Width (mm)	References
Plain front panel	300	**NSYCTL300DLM**
Plain front panel	400	**NSYCTL400DLM**
Plain front panel	500	**NSYCTL500DLM**
Plain front panel	600	**NSYCTL600DLM**
Plain front panel	800	**NSYCTL800DLM**

Plain mounting plate

- Mounting plate for fixing non modular devices.
- Material: Galvanised steel
- Thickness: 20/10e mm

Supply:
2 plain chassis and fixings

NSYPMP300DLM

Characteristics	Width (mm)	References
Plain mounting plate	300	**NSYPMP300DLM**
Plain mounting plate	400	**NSYPMP400DLM**
Plain mounting plate	500	**NSYPMP500DLM**
Plain mounting plate	600	**NSYPMP600DLM**
Plain mounting plate	800	**NSYPMP800DLM**



Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Modular wall-mounting enclosures

DL modular chassis

- Dinimel chassis designed for devices with heights of 53 and 68 mm, which can be coupled directly to the enclosure plate-support bolts.
- Distance between device rail and protective cover plate: 45 mm.
- Material: Steel
- Finish: Metal protective cover plate
- Colour: RAL 7035 grey

Note:
For Spacial S3D please consult us
Depth 150 mm: For coupling to enclosures with a depth of 200 mm, the stand-offs (ref. **NSYEX608**) are to be ordered separately (4 per chassis).

NSYDLCR24

Characteristics	Height (mm)	Width (mm)	Depth (mm)	References
DL modular chassis	300	250	150	**NSYDLCR18**
DL modular chassis	400	300	150	**NSYDLCR24**
DL modular chassis	400	300	150	**NSYDLCR36**
DL modular chassis	500	400	150	**NSYDLCR48**
DL modular chassis	600	400	150/200	**NSYDLCR64**
DL modular chassis	600	500	150/200	**NSYDLCR88**
DL modular chassis	700	500	200	**NSYDLCR110**
DL modular chassis	800	600	200	**NSYDLCR135**



Dimension F: Distance from the protective cover plate to the inside of the door.
Dimension G: Distance from the device-support rail to the rear of the enclosure.

For coupling to the enclosures with normal or transparent door	Dimensions (mm)								
References	A	B	D	E	F	G	No. of 18 mm modules	No. of rows	Approx. weight (kg)
NSYDLCR18	255	205	162	120	41	51	18	2	1.2
NSYDLCR24	355	255	216	160	41	51	24	2	1.7
NSYDLCR36	355	255	216	110	41	51	36	3	1.7
NSYDLCR48	455	355	288	130	41	51	48	3	2.4
NSYDLCR64	555	355	288	130	41	51/101	64	4	3.3
NSYDLCR88	555	455	396	130	41	51/101	88	4	4.5
NSYDLCR110	655	455	396	125	41	101	110	5	5.1
NSYDLCR135	755	555	486	140	41	101	135	5	7.5

Note: For enclosures with transparent door, the F dimension is reduced by 4 mm

Blanking plate

- Blanking plate for full or partial covering of the circuit-breaker windows; it can easily be cut to the required size.
- Material: Plastic

NSYATP72M

Characteristics	Number of modules	Colour	Length (mm)	References
Blanking plate	4	RAL 7032	72	**NSYATP72G**
Blanking plate	4	RAL 7035 grey	72	**NSYATP72M**
Blanking plate	6	RAL 7035 grey	108	**NSYATP6DTM**
Blanking plate	24	RAL 7035 grey	432	**NSYATP24DTM**
Blanking plate	-	RAL 7035 grey	1100	**NSYATPUND**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Accessories for modular floor-standing enclosures

The modular distribution system is made up of a range of accessories prepared for forming electric panels with high distribution capacity.

The accessories are installed on a chassis mounted at the front of the enclosure, such as:

- cover plates for enclosures with widths of 600 and 800 mm, solid or cut-out in screwed-on or hinged versions. They cover 24 or 36 modules per row, depending on the width of the enclosure,
- material support rails, fixed or with adjustable depth,
- mounting plate supports for coupling non modular equipment,
- supports for fixing cable-distribution cable ducts.

Sets of accessories made up of material-supporting frames with chassis and cover plates are offered for the construction of double or busbar modular chassis. All the accessories of the individual chassis system can also be combined in the same way with the double chassis or with the chassis with busbar area.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Accessories for modular floor-standing enclosures

Single-chassis coupling set

- Chassis made up of vertical uprights and horizontal crossbars:
- Spacial SF: They are screwed to the front frame of the enclosure.
- Spacial SM: They are screwed to the front frame of the enclosure by means of the vertical adaptation profiles, see page 258.
- Easy access to the inside for component installation.
- Material: Steel
- Finish: Structured finish, epoxy polyester powder
- Colour: RAL 7035 grey

Note:
Installation example: See page 335.

Supply:
2 vertical uprights, 2 horizontal crossbars and fixing elements


NSYCSH126

Characteristics	Maximum no. of 18 mm modules	Height (mm)	Width (mm)	References
Single-chassis coupling set	144	1200	600	**NSYCSH126**
Single-chassis coupling set	216	1200	800	**NSYCSH128**
Single-chassis coupling set	192	1400	600	**NSYCSH146**
Single-chassis coupling set	288	1400	800	**NSYCSH148**
Single-chassis coupling set	216	1600	600	**NSYCSH166**
Single-chassis coupling set	324	1600	800	**NSYCSH168**
Single-chassis coupling set	240	1800	600	**NSYCSH186**
Single-chassis coupling set	360	1800	800	**NSYCSH188**
Single-chassis coupling set	288	2000	600	**NSYCSH206**
Single-chassis coupling set	432	2000	800	**NSYCSH208**

Double-chassis coupling set

- Mounting on enclosures with widths of 1200 and 1600 mm.
- Spacial SF: The double door enclosure adaptation kit is required for enclosure widths of 1200 and 1600 mm, see page 250.
- Spacial SM: They are screwed to the front frame of the enclosure by means of the vertical adaptation profiles, see page 258. For enclosures with a width of 1200 mm the top/bottom adjustment rails are necessary.
- Set made up of two modular chassis with an intermediate central upright.
- Material: Steel
- Finish: Structured finish, epoxy polyester powder
- Colour: RAL 7035 grey

Note:
Installation example: See page 335.

Supply:
2 single-chassis coupling sets, 1 intermediate central upright and fixing elements


NSYDCSH1412

Characteristics	Maximum no. of 18 mm modules	Set made up of columns with a width (mm)	Height (mm)	Width (mm)	References
Double-chassis coupling set	384	600 + 600	1200	800	**NSYDCSH1412**
Double-chassis coupling set	432	600 + 600	1400	800	**NSYDCSH1612**
Double-chassis coupling set	480	600 + 600	1600	800	**NSYDCSH1812**
Double-chassis coupling set	720	800 + 800	1800	600	**NSYDCSH1816**
Double-chassis coupling set	576	600 + 600	2000	600	**NSYDCSH2012**
Double-chassis coupling set	864	800 + 800	2000	800	**NSYDCSH2016**

Chassis-coupling set with zone for busbars

- Set for mounting on enclosures with widths of 1000 and 1200 mm.
- Spacial SF: They are screwed to the front frame enclosure.
- Spacial SM: They are screwed to the front frame of the enclosure by means of the vertical and horizontal adaptation profiles, see page 258.
- Assembly made up of a modular chassis with an intermediate central upright and a blanking cover plate for busbars (width 300 mm).
- Material: Steel
- Finish: Structured finish, epoxy polyester powder
- Colour: RAL 7035 grey

Note:
Installation example: See page 335.

Supply:
1 single-chassis coupling set, 1 intermediate central upright, 1 busbar blanking cover plate and fixing elements


NSYCSHB1410

Characteristics	Maximum no. of 18 mm modules	Set made up of columns with a width (mm)	Height (mm)	Width (mm)	References
Chassis-coupling set with zone for busbars	192	600 + 400	1400	1000	**NSYCSHB1410**
Chassis-coupling set with zone for busbars	288	800 + 400	1400	1200	**NSYCSHB1412**
Chassis-coupling set with zone for busbars	216	600 + 400	1600	1000	**NSYCSHB1610**
Chassis-coupling set with zone for busbars	324	800 + 400	1600	1200	**NSYCSHB1612**
Chassis-coupling set with zone for busbars	240	600 + 400	1800	1000	**NSYCSHB1810**
Chassis-coupling set with zone for busbars	360	800 + 400	1800	1200	**NSYCSHB1812**
Chassis-coupling set with zone for busbars	288	600 + 400	2000	1000	**NSYCSHB2010**
Chassis-coupling set with zone for busbars	432	800 + 400	2000	1200	**NSYCSHB2012**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Accessories for modular floor-standing enclosures

Combination of cut-out, screwed-on cover plates and single-chassis coupling set



Dimensions (mm)		No. of 18 mm modules	1 single-chassis coupling set	5 screwed-on cut-out cover plates	2 adjustment cover plates
H (A)	W (B)		References	References	References
1800	600	240	1 x **NSYCSH186**	5 x **NSYMUC306**	1 x **NSYADC16**

Single-chassis coupling set



Combination of cut-out, screwed-on cover plates and double-chassis coupling set



Dimensions (mm)			No. of 18 mm modules	1 double-chassis coupling set	12 screwed-on cut-out 300 mm cover plates	Double door enclosure adaptation kit
H (A)	W (B)	D (C)		References	References	References
2000	1200	500	576	1 x **NSYDCSH2012**	12 x **NSYMUC306**	**NSYSMP2D5**
2000	1600	500	864	1 x **NSYDCSH2016**	12 x **NSYMUC308**	-

Combination of cut-out, screwed-on cover plates and chassis-coupling set with busbar zone



Dimensions (mm)		No. of 18 mm modules	1 single-chassis coupling set	5 screwed-on cut-out cover plates	2 adjustment cover plates
H (A)	W (B)		References	References	References
1800	1000	240	1 x **NSYCSHB1810**	5 x **NSYMUC306**	1 x **NSYADC16**
1800	1200	360	1 x **NSYCSHB1812**	5 x **NSYMUC308**	1 x **NSYADC18**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Accessories for modular floor-standing enclosures

Plain cover plates

- Metal cover plates for protecting control devices.
- The cut-outs in non modular control devices is at user's request.
- Suitable by modules of 150 or 200 mm.
- Material: Steel
- Finish: Structured finish, epoxy polyester powder
- Colour: RAL 7035 grey

Versions:
- screwed-on plain cover plate,
- hinged plain cover plate.
- 120° opening with flat hinge.

Supply:
1 plain cover plate and fixing elements


NSYMPC156

Characteristics	Height (mm)	Width (mm)	References
Screwed-on plain cover plate	150	600	**NSYMPC156**
Screwed-on plain cover plate	150	800	**NSYMPC158**
Screwed-on plain cover plate	200	600	**NSYMPC206**
Screwed-on plain cover plate	200	800	**NSYMPC208**
Screwed-on plain cover plate	300	600	**NSYMPC306**
Screwed-on plain cover plate	300	800	**NSYMPC308**
Screwed-on plain cover plate	400	600	**NSYMPC406**
Screwed-on plain cover plate	400	800	**NSYMPC408**
Screwed-on plain cover plate	450	600	**NSYMPC456**
Screwed-on plain cover plate	450	800	**NSYMPC458**
Screwed-on plain cover plate	600	600	**NSYMPC606**
Screwed-on plain cover plate	600	800	**NSYMPC608**

Plain cover plates

- Metal cover plates for protecting control devices.
- The cut-outs in non modular control devices is at user's request.
- Suitable by modules of 150 or 200 mm.
- Material: Steel
- Finish: Structured finish, epoxy polyester powder
- Colour: RAL 7035 grey

Versions:
- screwed-on plain cover plate,
- hinged plain cover plate.
- 120° opening with flat hinge.

Supply:
1 plain cover plate and fixing elements


NSYMPCH156

Characteristics	Height (mm)	Width (mm)	References
Hinged plain cover plate	150	600	**NSYMPCH156**
Hinged plain cover plate	150	800	**NSYMPCH158**
Hinged plain cover plate	200	600	**NSYMPCH206**
Hinged plain cover plate	200	800	**NSYMPCH208**
Hinged plain cover plate	300	600	**NSYMPCH306**
Hinged plain cover plate	300	800	**NSYMPCH308**
Hinged plain cover plate	400	600	**NSYMPCH406**
Hinged plain cover plate	400	800	**NSYMPCH408**
Hinged plain cover plate	450	600	**NSYMPCH456**
Hinged plain cover plate	450	800	**NSYMPCH458**
Hinged plain cover plate	600	600	**NSYMPCH606**
Hinged plain cover plate	600	800	**NSYMPCH608**

Plain cover plates



11

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Accessories for modular floor-standing enclosures

Screwed-on cut-out cover plate

- Cut-out metal cover plates for modular switchgear (1 module = 18 mm).
- Suitable by modules of 150 or 200 mm.
- cover plates for 600 mm width enclosures: 24 modules per row,
- cover plates for 800 mm width enclosures: 36 modules per row.
- Material: Steel
- Finish: Structured finish, epoxy polyester powder
- Colour: RAL 7035 grey

Versions:
- screwed-on cut-out cover plate,
- hinged cut-out cover plate. 120° opening with flat hinge.

Supply:
1 cut-out cover plate and fixing elements


NSYMUC156

Characteristics	Maximum no. of 18 mm modules	No. of cut-outs	Height (mm)	Width (mm)	References
Screwed-on cut-out cover plate	24	1	150	600	**NSYMUC156**
Screwed-on cut-out cover plate	36	1	150	800	**NSYMUC158**
Screwed-on cut-out cover plate	24	1	200	600	**NSYMUC206**
Screwed-on cut-out cover plate	36	1	200	800	**NSYMUC208**
Screwed-on cut-out cover plate	48	2	300	600	**NSYMUC306**
Screwed-on cut-out cover plate	72	2	300	800	**NSYMUC308**
Screwed-on cut-out cover plate	48	2	400	600	**NSYMUC406**
Screwed-on cut-out cover plate	72	2	400	800	**NSYMUC408**
Screwed-on cut-out cover plate	72	3	450	600	**NSYMUC456**
Screwed-on cut-out cover plate	108	3	450	800	**NSYMUC458**
Screwed-on cut-out cover plate	72	3	600	600	**NSYMUC606**
Screwed-on cut-out cover plate	108	3	600	800	**NSYMUC608**

Hinged cut-out cover plate

- Cut-out metal cover plates for modular switchgear (1 module = 18 mm).
- Suitable by modules of 150 or 200 mm.
- cover plates for 600 mm width enclosures: 24 modules per row,
- cover plates for 800 mm width enclosures: 36 modules per row.
- Material: Steel
- Finish: Structured finish, epoxy polyester powder
- Colour: RAL 7035 grey

Versions:
- screwed-on cut-out cover plate,
- hinged cut-out cover plate. 120° opening with flat hinge.

Supply:
1 cut-out cover plate and fixing elements

NSYMUCH156

Characteristics	Maximum no. of 18 mm modules	No. of cut-outs	Height (mm)	Width (mm)	References
Hinged cut-out cover plate	24	1	150	600	**NSYMUCH156**
Hinged cut-out cover plate	36	1	150	800	**NSYMUCH158**
Hinged cut-out cover plate	24	1	200	600	**NSYMUCH206**
Hinged cut-out cover plate	36	1	200	800	**NSYMUCH208**
Hinged cut-out cover plate	48	2	300	600	**NSYMUCH306**
Hinged cut-out cover plate	72	2	300	800	**NSYMUCH308**
Hinged cut-out cover plate	48	2	400	600	**NSYMUCH406**
Hinged cut-out cover plate	72	2	400	800	**NSYMUCH408**
Hinged cut-out cover plate	72	3	450	600	**NSYMUCH456**
Hinged cut-out cover plate	108	3	450	800	**NSYMUCH458**
Hinged cut-out cover plate	72	3	600	600	**NSYMUCH606**
Hinged cut-out cover plate	108	3	600	800	**NSYMUCH608**

Cut-out cover plates



A = 150 and 200 mm



A = 300 and 400 mm



Cut-out at 200 mm when A = 600

Dimensions (mm)		
D	E	F
432	51.75	150
642	51.75	150
432	76.75	200
642	76.75	200
432	51.75	150
642	51.75	150
432	76.75	200
642	76.75	200



Screwed-on cover plate



Hinged cover plate

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Accessories for modular floor-standing enclosures

Adjustment cover plates

- Metal adjustment cover plates designed to complete the front of the modular chassis according to the combinations made by modules of 150 or 200 mm.
- Material: Steel
- Finish: Structured finish, epoxy polyester powder
- Colour: RAL 7035 grey

Supply:
2 adjustment cover plates and fixing elements

NSYADC16

Characteristics	Height (mm)	Width (mm)	References
Adjustment cover plates	50	600	**NSYADC16**
Adjustment cover plates	50	800	**NSYADC18**

Set of fixed rail with supports

- Set made up of a galvanised symmetric DIN rail, 35 x 15 mm, and fixed mounting supports, for the installation of modular devices or not.
- Material: Zinc-coated steel
- Fixing: Mounting by screws directly on the uprights of the chassis-coupling set

Maximum number of 18 mm modules:
- enclosure width 600 mm: 24 modules,
- enclosure width 800 mm: 36 modules.

Supply:
1 DIN rail, 2 fixed supports and fixing elements

NSYMFSC60

Characteristics	Width (mm)	References
Set of fixed rail with supports	600	**NSYMFSC60**
Set of fixed rail with supports	800	**NSYMFSC80**





Set of depth-adjustable rail with supports

- Set made up of a galvanised symmetric DIN rail, 35 x 15 mm, and depth adjustable mounting supports, for the installation of modular devices or not.
- Material: Zinc-coated steel
- Fixing: Mounting by screws directly on the uprights of the modular chassis-coupling set

Maximum number of 18 mm modules:
- enclosure width 600 mm: 24 modules,
- enclosure width 800 mm: 36 modules.

Supply:
1 DIN rail, 2 adjustable supports and fixing elements

NSYMFSC60D

Characteristics	Width (mm)	References
Set of depth-adjustable rail with supports	600	**NSYMFSC60D**
Set of depth-adjustable rail with supports	800	**NSYMFSC80D**





11

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Accessories for modular floor-standing enclosures

Cable duct fixing supports

- Supports for fixing cable-distribution gutters in the modular chassis.
- Allows the fixing of gutters in horizontal and vertical position on the same plane to facilitate cable distribution.
- Material: Zinc-coated steel

Fixing: Installation by screws directly on the rail supplied with the fixed or adjustable rail

Supply:
6 supports (3 on the right and 3 on the left) and fixing elements

NSYMCDFIX

Characteristics	References
Cable duct fixing supports	**NSYMCDFIX**



Reinforced plate supports

- Supports for fixing the partial mounting plate for small non modular equipment or material-supporting cross rails for heavy equipment. See partial mounting plate, page 246.
- Material: Zinc-coated steel

Fixing: Direct fixing by screws to the vertical uprights of the modular chassis-coupling set, and at the rear directly to the structure (Spacial SF) and on universal or quick fixing cross rails (see page 255) installed vertically in the back of the enclosure (Spacial SM)

Supply:
2 supports and fixing elements

NSYMPS30

Characteristics	No. of cut-outs (Ø 5.2 mm)	Depth (mm)	References
Reinforced plate supports	4	300	**NSYMPS30**
Reinforced plate supports	8	400	**NSYMPS40**
Reinforced plate supports	12	500	**NSYMPS50**
Reinforced plate supports	16	600	**NSYMPS60**
Reinforced plate supports	24	800	**NSYMPS80**



Fixed supports with no rail

Supply:
2 fixed supports and fixing elements.

NSYMFS1

Characteristics	References
Fixed supports with no rail	**NSYMFS1**

Adjustable supports with no rail

Supply:
2 adjustable supports and fixing elements

NSYMFS1D

Characteristics	References
Adjustable supports with no rail	**NSYMFS1D**

11

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Accessories for low voltage switchboards

Top busbar chamber

- Chamber which protects and supports the sets of horizontal bars.
- Enables new switchgear by tapping and isolates the sets of bars from the rest of the equipment.
- It is only installed at the top of the enclosure.
- Material: Steel
- Finish: Structured finish, epoxy polyester powder
- Colour: RAL 7035 grey
- Ingress protection rating: IP55 according to IEC 60529

Supply:
One structure of the busbar chamber as a kit
Two front panels
Reinforced coupling kit
One sealing gasket


NSYTBC336

Characteristics	Height (mm)	Width (mm)	Depth (mm)	References
Top busbar chamber	300	300	500	**NSYTBC335**
Top busbar chamber	300	300	600	**NSYTBC336**
Top busbar chamber	300	300	800	**NSYTBC338**
Top busbar chamber	300	400	500	**NSYTBC345**
Top busbar chamber	300	400	600	**NSYTBC346**
Top busbar chamber	300	400	800	**NSYTBC348**
Top busbar chamber	300	600	500	**NSYTBC365**
Top busbar chamber	300	600	600	**NSYTBC366**
Top busbar chamber	300	600	800	**NSYTBC368**
Top busbar chamber	300	800	500	**NSYTBC385**
Top busbar chamber	300	800	600	**NSYTBC386**
Top busbar chamber	300	800	800	**NSYTBC388**
Top busbar chamber	300	1000	500	**NSYTBC3105**
Top busbar chamber	300	1000	600	**NSYTBC3106**
Top busbar chamber	300	1000	800	**NSYTBC3108**
Top busbar chamber	300	1200	500	**NSYTBC3125**
Top busbar chamber	300	1200	600	**NSYTBC3126**
Top busbar chamber	300	1200	800	**NSYTBC3128**





Side panels for the top busbar chamber

- Set of two side panels for coupling with the busbar chamber.
- Captive screws.
- Material: Steel
- Finish: Structured finish, epoxy polyester powder
- Colour: RAL 7035 grey

Supply:
Two side panels and fixing elements

NSYSPBC35

Characteristics	Depth (mm)	References
Side panels for the top busbar chamber	500	**NSYSPBC35**
Side panels for the top busbar chamber	600	**NSYSPBC36**
Side panels for the top busbar chamber	800	**NSYSPBC38**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Side busbar chamber

- Protects and supports the sets of vertical bars.
- Enables new switchgear by tapping and isolates the sets of bars from the rest of the equipment.
- It can be installed on either of the two sides of the enclosure.
- Material: Steel
- Finish: Structured finish, epoxy polyester powder
- Colour: RAL 7035 grey
- Ingress protection rating: IP55 according to IEC 60529

Supply:
One structure of the busbar chamber
One roof
One rear panel
One door with handle (5 mm DB lock)

NSYSF18440

Characteristics	Height (mm)	Width (mm)	Depth (mm)	References
Side busbar chamber	1800	400	400	**NSYSF18440**
Side busbar chamber	1800	400	500	**NSYSF18450**
Side busbar chamber	1800	400	600	**NSYSF18460**
Side busbar chamber	2000	300	500	**NSYSF20350**
Side busbar chamber	2000	300	600	**NSYSF20360**
Side busbar chamber	2000	300	800	**NSYSF20380**
Side busbar chamber	2000	400	400	**NSYSF20440**
Side busbar chamber	2000	400	500	**NSYSF20450**
Side busbar chamber	2000	400	600	**NSYSF20460**
Side busbar chamber	2000	400	800	**NSYSF20480**
Side busbar chamber	2200	400	600	**NSYSF22460**

Side panels for the side busbar chamber

- Set of 2 side panels fixed to the outside.
- Captive screws.
- Material: Steel
- Finish: Structured finish, epoxy polyester powder
- Colour: RAL 7035 grey

Supply:
Two side panels with external fixing and fixing elements

NSY2SP184

Characteristics	Height (mm)	Width (mm)	Depth (mm)	References
Side panels	1800	400	400	**NSY2SP184**
Side panels	1800	400	500	**NSY2SP185**
Side panels	1800	400	600	**NSY2SP186**
Side panels	2000	300	500	**NSY2SP205**
Side panels	2000	300	600	**NSY2SP206**
Side panels	2000	300	800	**NSY2SP208**
Side panels	2000	400	400	**NSY2SP204**
Side panels	2000	400	500	**NSY2SP205**
Side panels	2000	400	600	**NSY2SP206**
Side panels	2000	400	800	**NSY2SP208**
Side panels	2200	400	600	**NSY2SP226**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Accessories for low voltage switchboards

630 A bar support

Spacial SF:
- support prepared for coupling directly to the structure of the enclosure.

Spacial SFX:
- a universal cross rail is needed, in some cases, to replace the 400 mm quick fixing cross rail.

Spacial SM:
- installation by means of a vertical adaptation profile and 40 mm universal cross rails (1 row).
- Maximum nominal rating 630 A.
- Determine according to the enclosed table the cross-section of the bars and the distance between supports, according to the nominal and short-circuit current respectively.

Supply:
One 630 A bar support, one 40 mm quick fixing cross rail and fixing elements

NSYBS400

Characteristics	Width (mm)	References
630 A bar support	400	**NSYBS400**
630 A bar support	500	**NSYBS500**
630 A bar support	600	**NSYBS600**
630 A bar support	800	**NSYBS800**



Nominal rating IP55 NR (A)	No. of barsper phase	Bar cross-section (mm)	Bar cross-section (mm²)	Maximum distance between bar supports according to the short-circuit current (mm) Icc kA							Neutral (mm)	Earth (mm)
				12	23	30	39	52	66	69		
200	1	12 x 5	60	525	525	525	400	250	-	-	-	-
250	1	12 x 5	75	575	575	575	450	325	-	-	-	-
320	1	20 x 5	100	600	600	600	475	350	150	-	12 x 5-10	-
390	1	25 x 5	125	600	600	600	475	350	150	-	12 x 5-10	6 x 3
440	1	30 x 5	150	650	650	650	650	525	400	350	20 x 5-10	10 x 3
500	1	20 x 10	200	675	675	675	525	350	150	-	25 x 5-10	10 x 6
600	1	30 x 10	300	675	675	675	600	475	325	275	30 x 5-10	10 x 6

630 A busbar end cover

- Busbar end protection.
- Fixing: Direct installation on the actual bar support (insulator)

Supply:
Two 630 A bar support plates and fixing elements

NSYBSC630

Characteristics	References
630 A busbar end cover	**NSYBSC630**

11

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Accessories for low voltage switchboards

630 A multi-stage bar support


04192

- Support for fixing bars with cross-sections: 15 x 5, 20 x 5, 32 x 5, 32 x 8.
- The orientation of the copper bars makes tightening easier and allows better circulation of the cables.
- It can be 3-pole or 4-pole, with gauges from 160 to 630 A.

Electrical characteristics:

- Rated peak withstand current Ipk (kA):
- - 30 kA for 160 A busbar,
- - 40 kA for 250 A busbar,
- - 55 kA for 400 A and 630 A busbar.
- Rated insulation voltage Ui = 750 V.
- Material: Insulating plastic
- Fixing: Mounting on mounting plates (see page 246) or cross rails (see page 255) M6 x 25 self-tapping screws are required for fixing on the cross rails, not included

Supply:
1 multi-stage bar support and fixing elements

Characteristics	References
630 A multi-stage bar support	**04192**







The following table shows:

- The cross-section of the bars that will be used according to the current-carrying capacity in the busbar.
- The distance between the bar supports that will be installed according to the rated short-time withstand current: Icw.

		Centre-to-centre distance of the supports (mm) Icw (kA eff/1 s)				
Rating (A)	Bar crosssection (mm)	10	13	15	20	25
160	15 x 5	450	–	–	–	–
250	20 x 5	450	450	–	–	–
400	32 x 5	450	450	450	300	300 I_{cw} (kA eff/0.6 s)
630	32 x 8	450	450	450	300	300

Screen for 630 A multi-stage busbar


04197

- Protects against direct contact from the front in the connections of the busbar.
- Length: 1500 mm.
- Fixing: Direct mounting on the actual support

Supply:
1 screen for multi-stage busbar and fixing elements

Characteristics	References
Screen for 630 A multi-stage busbar	**04197**

11

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Vertical bar support

- Support prepared for fixing bars in vertical position, mounted directly on the structure of the enclosure. Adjustable height with a pitch of 25 mm.
- For a nominal rating In ≥ 3000 A and ≤ 4000 A you must add one spacer ref. **04646**.

Supply:
2 insulating bar supports,
1 metal vertical support and fixing elements

NSYBVS400

Characteristics	Width / Depth (B) (mm)	References
Vertical bar support	400	**NSYBVS400**
Vertical bar support	500	**NSYBVS500**
Vertical bar support	600	**NSYBVS600**
Vertical bar support	800	**NSYBVS800**







Setting support

- Bottom support for bars in vertical position.
- It is fixed to the bottom frame of the enclosure.
- It is required for supporting the bars.
- It is not considered a bar support when calculating the number of supports

Supply:
1 insulating bar support,
1 metal vertical support and fixing elements

NSYAS400

Characteristics	Width / Depth (B) (mm)	References
Setting support	400	**NSYAS400**
Setting support	500	**NSYAS500**
Setting support	600	**NSYAS600**
Setting support	800	**NSYAS800**





11

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Horizontal bar support

- Support prepared for fixing bars in horizontal position.
- Direct mounting to the structure of the enclosure, on the vertical uprights, at any height, adjustable with a pitch of 25 mm.
- For a nominal rating $I_n \geq 3000$ A and ≤ 4000 A you must add one spacer ref. **04646**.

Supply:
2 insulating bar supports,
1 metal horizontal support and fixing elements

NSYBHS500

Characteristics	Width / Depth (B) (mm)	References
Horizontal bar support	500	**NSYBHS500**
Horizontal bar support	600	**NSYBHS600**
Horizontal bar support	800	**NSYBHS800**





Bar support arm

- Support without fixing to the enclosure, required to guarantee the distance between the bars.
- It is used on bars in both vertical and horizontal position.
- For a nominal rating $I_n \geq 3000$ A and ≤ 4000 A you must add one spacer ref. **04646**.

Supply:
2 insulating bar supports and fixing elements

NSYBSA

Characteristics	Width / Depth (B) (mm)	References
Bar support arm	500	**NSYBSA**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Overview of the offer Masterpact NT and NW

Circuit breakers

Ratings:

- Masterpact NT: 630 to 1600 A
- Masterpact NW: 800 to 4000 A.
- Circuit breakers type N1, H1, H2, H3, L1.
- Switch-disconnectors type NA, HA, HF, HH.
- 3 or 4 poles.
- Fixed or drawout versions.
- Option with neutral on the right.
- Protection derating.

Micrologic control units

Ammeter A and Energy E

- 2.0 basic protection
- 5.0 selective protection
- 6.0 selective + earth-fault protection
- 7.0 selective + earth-leakage protection (Only for ammeter A).

Power meter P

- 5.0 selective protection
- 6.0 selective + earth-fault protection
- 7.0 selective + earth-leakage protection

Harmonic meter H

- 5.0 selective protection
- 6.0 selective + earth-fault protection
- 7.0 selective + earth-leakage protection
- External sensor for earth-fault protection.
- Rectangular sensor for earth-leakage protection.
- Setting options (long-time rating plug):
- low setting 0.4 to 0.8 x Ir
- high setting 0.8 to 1 x Ir
- without long-time protection.
- External AD power-supply module.
- Battery module.

Power meter functions

Masterpact equipped with Micrologic 2 / 5 / 6 / 7 trip units offer type A (ammeter) or E (energy) metering functions as well as communication. Using Micrologic sensors and intelligence, Masterpact provides access to measurements of all the main electrical parameters on the built-in screen, on a dedicated FDM display unit or via the communication system.

Operating assistance functions

Integration of measurement functions provides operators with operating assistance functions including alarms tripped by user-selected measurement values, time-stamped event tables and histories, and maintenance indicators.

Communication

- COM option in Masterpact.
- Masterpact in a communication network.
- IFM: Modbus interface module.
- IFE: Ethernet interface module.
- I/O application module.
- Electrical Asset Manager.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Overview of the offer Masterpact MTZ

Circuit breakers

MTZ1
From 630 to 1600 A

MTZ2
From 800 to 4000 A

MicrologicTM X control units

2.0X | 5.0X | 6.0X | 7.0X
Only four references

Digital Modules

Protection

Measurement

Diagnostics and Maintenance

Five performance levels
N1, H1, H2, H3, L1



Masterpact MTZ1

Find all functions and technical characteristics in:
Masterpact MTZ catalogue
LVPED216026EN

11

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Accessories for low voltage switchboards

Masterpact support

Introduction

Installation of a Masterpact in a SF switchboard requires:
- Lateral cross rails (**NSYSQCR●●**, **NSYSUCR●●**) (See table below)
- 1 specific transversal Masterpact support (**NSYFXMN●●**) fixed to the lateral cross rails
- Bar supports to reduce bar movements due to constraints

Masterpact supports New

Dedicated offer to secure and facilitate Masterpact positioning in the switchboard
- Less distortion
- Reduced installation time
- Possibility to use bar CAD library

Masterpact supports W600

- Cut outs already defined
- Availlable in the Schneider CAD library
- Material: Galvanised steel
- Mounting instructions: Screwdriver: T30, Tightening torque: 4.5 Nm/39.82 lb-in

Supply:
1 support delivered with fixing elements
(self tapping screws M6/T30 + type 9/M6 cage nuts)

NSYFXMNT60F

Characteristics	Masterpact association	References
Masterpact MTZ1 and NT	Fixed	**NSYFXMNT60F**
Masterpact MTZ1 and NT	Withdrawable	**NSYFXMNWT60FW**
Masterpact MTZ2 and NW	Fixed	**NSYFXMNWT60FW**
Masterpact MTZ2 and NW	Withdrawable	**NSYFXMNWT60FW**

Masterpact supports W800

- Cut outs already defined
- Availlable in the Schneider CAD library
- Material: Galvanised steel
- Mounting instructions: Screwdriver: T30, Tightening torque: 4.5 Nm/39.82 lb-in

Supply:
1 support delivered with fixing elements
(self tapping screws M6/T30 + type 9/M6 cage nuts)

NSYFXMNT80F

Characteristics	Masterpact association	References
Masterpact MTZ1 and NT	Fixed	**NSYFXMNT80F**
Masterpact MTZ1 and NT	Withdrawable	**NSYFXMNT80W**
Masterpact MTZ2 and NW	Fixed	**NSYFXMNW80F**
Masterpact MTZ2 and NW	Withdrawable	**NSYFXMNW80W**

Associated cross rails

Supply:
2 cross rails and fixing elements (see cross rail section page 253 for more information)

- Material: Zinc-coated steel


NSYSUCR65●●

Characteristics	References
in Masterpact association: MTZ1 and NT	**NSYSUCR65●●**
in Masterpact association: MTZ2 and NW	**NSYSUCR90●●**

Associated cross rails

Supply:
2 cross rails and fixing elements (see cross rail section page 253 for more information)

- Material: Zinc-coated steel

NSYSQCR65●●

Characteristics	References
in Masterpact association: MTZ1 and NT	**NSYSQCR65●●**
in Masterpact association: MTZ2 and NW	**NSYSQCR90●●**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Accessories for low voltage switchboards

Bar supports

Supports for Masterpact MTZ1 and NT

- Fixing by screw with hexagonal head.
- Material: Metal support: Zinc-coated steel, Isolating supports: thermosetting coating

Supply:
2 insulating bar supports,
1 metal horizontal support and fixing element

NSYBHNT500

Characteristics	Width (mm)	References
Fixed support	500	**NSYBHNT500**
Fixed support	600	**NSYBHNT600**
Fixed support	800	**NSYBHNT800**

Supports for Masterpact MTZ1 and NT

- Fixing by screw with hexagonal head.
- Material: Isolating supports: Thermosetting coating

Supply:
2 insulating bar supports and fixing elements

NSYBSA70

Characteristics	References
Free support	**NSYBSA70**

Supports for Masterpact MTZ2 and NW

- Fixing by screw with hexagonal head.
- Material: Metal support: Zinc-coated steel, Isolating supports: thermosetting coating

Supply:
2 insulating bar supports,
1 metal horizontal support and fixing element

NSYBHNW600

Characteristics	Width (mm)	References
Fixed support	600	**NSYBHNW600**
Fixed support	800	**NSYBHNW800**

Supports for Masterpact MTZ2 and NW

- Fixing by screw with hexagonal head.
- Material: Isolating supports: Thermosetting coating

Supply:
2 insulating bar supports and fixing elements

04678

Characteristics	References
Free support	**04678**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Accessories for low voltage switchboards

Fast connection distribution blocks

	Linergy DX				
	63 A	63 A	125 A	160 A	160 A
Characteristics	**04040**	**04041**	**04045 + 04047**	**04046**	**04031**
	• Incoming through the top. • Clip-on to rail.	• Incoming through the bottom. • Clip-on to rail.	• Set of 4 • 35 mm² flexible connections, length 210 mm to be ordered separately (cat. no. 04047). • Clip-on to rail.	• Set of 4 prefabricated flexible connections supplied, for connection with an INS100/160 or NSA160 switch, installed on the right or left. • Clip-on to rail	Clip-on to rail.
Number of poles	4P		4P		1P
Total connection capacity (dia. for flexible cables)					
4 mm²	-		7		-
6 mm²	12 per phase + 12 neutral		3		6
10 mm²	-		2		-
16 mm²	-		1 tunnel terminal		6
25 mm²	4 tunnel terminals per phase + 1 neutral		-		-
35 mm²	-		1 tunnel terminal		-
70 mm²	-		-		1 tunnel terminal
Size in 9 mm- modules	8		12		4.5
Size in 18 mm- modules	4		6		2.5

Screw distribution blocks

	Linergy DS							Linergy BS		
	125 A	160 A	250 A	100 A	125 A		160 A	160 A	250 A	400 A
Characteristics	**LGY112510**	**LGY116013**	**LGY125014**	**LGY410028**	**LGY412548**	**LGY412560**	**LGY416048**	**04052**	**04053**	**04054**
	• Clip-on to rail.			• Clip-on to rail.				• To be screwed on back. • 13 M6 tapped holes + 4 plain holes of dia. 12.2 mm.		
Number of poles	1P			4P				4P		
Total connection capacity	10	13	14	4 x 7	4 x 12	4 x 15	4 x 12	4 + 13 (dia. for flexible cables: 50 mm²)		
Size in 9 mm- modules	3	4	5	8	14	20	18	-	-	-
Neutral terminal strip (optional)	-	-	-	LGYN1007	LGYN12512	LGYN12515	LGYN12512	-	-	-

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Accessories for low voltage switchboards

Quick device feeders

	Linergy FM: For cable links						
	63 A	80 A	160 A	200 A			
Characteristics	**04008**	**04000**	**04018**	**04012**	**04013**	**04014**	**04026**
	4P Cable to be used without ferrules.	4P -	4P Cable to be used without ferrules.	2P.	3P	4P	4P
Length in 9 mm- modules	24	48	24	48			72
Length in 18 mm- modules	12	24	12	24			36
Supply at incomming terminals	Enclosed terminals for cables up to 25 mm²	Enclosed terminals for flexible cables 6 to 25 mm² or rigid cables 10 to 35 mm²	Direct onto the row by cable 70 mm² with crimped lug, or flexible bar 20 x 3 from busbar with prefabricated connection				
Downstream connection capacity							
Max. 4 mm², Phase	6	-	-	-	-	-	-
Max. 4 mm², Neutral	4	-	-	-	-	-	-
Max. 6 mm², Phase	6	18	-	-	-	-	-
Max. 6 mm², Neutral	4	18	-	-	-	-	-
Max. 10 mm², Phase	-	-	18	12	36	36	54
Max. 10 mm², Neutral	-	-	9	12	-	18	27
Accessories included							
Pre-stripped copper connections	10 of 4 mm² + 6 of 6 mm² (L=100 mm)	12 blue + 12 black	12 of 10 mm² (L=100 mm)	24 of 10 mm²			36 of 10 mm²
Protective cover	-	-	For pads (IPxxB)	-	-	-	-
Screws and nuts	-	-	For pads	-	-	-	-

Linergy FM with upstream device

	Connection of Linergy FM with upstream device				
					
Characteristics	**04021 + 04150 insulating covers**	**04024**	**04029**	**04030**	**04743**
Upstream device	Linergy BW busbar	Multi-stage Linergy BS busbar	Rear Linergy BS busbar	Device 160 A	Busbar
Connection hardware	4P 200 A connection (supplied with fixing accessories)	4P 200 A connection (supplied with fixing accessories)	4P 200 A connection (supplied with fixing accessories)	4P 160 A connection for Linergy FM 1/2 row	200 A connection (20 x 3 mm) for Linergy FM

11

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Accessories for low voltage switchboards

Feeders for Compact NSX et INS

	Linergy FC	
	 Compact NSX100/250 and INS/INV250 - All controls, fixed and withdrawable	
Characteristics	**04407**	**04408**
	• Linergy FC without prefabricated connections: • The connection of a Linergy FC distribution block using pre-wired connectors or insulated flexible bars is not compatible with Form 2 partitioning (**04922**). In this case, use the form 2 restoration kit (**04924**). • For the connection, use insulated flexible bars, 32 x 8 mm (**04753**). Each connection must not be longer than 500 mm. This size is validated with Schneider Electric insulated flexible bars.	
Number of poles	3P	4 P
Connection to	Linergy BS, Linergy LGY or Linergy LGYE busbars	
Number of devices	4	3
Composition	Self-adhesive labels to mark the phases for connections to the busbars.	

Accessories



Tooth caps


04809

- The caps block off the reserve terminals on a Linergy FC distribution block.
- Made of an insulating material, they simply clip on from the front.

Characteristics	References
Tooth caps	**04809**

Mounting plate for Linergy FC

NSYMPLGYFC600

- Fixing with **NSYMPFIX** kit
- Material: Galvanised steel

Supply:
1 mounting plate

Characteristics	Width (mm)	References
Mounting plate for Linergy FC	600	**NSYMPLGYFC600**
Mounting plate for Linergy FC	800	**NSYMPLGYFC800**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Accessories for low voltage switchboards

Sigma safety terminals

- Safety terminals made from self-extinguishing Polyamide-6, with matt black base, MS-58 brass terminal (DIN 17660), tempered, zinc-plated and dichromated steel ring, and cover made from orange-coloured selfextinguishing polypropylene.
- Anti-shearing: The connection is made by means of a tightening mechanism, which distributes the pressure across the entire contact surface, avoiding friction and occasional stress that can damage the conductors.
- Unloosenable: The ring that surrounds the brass body guarantees that the pressure exerted by the actual conductors cannot open the terminal and loosen the connection.
- Full insulation: All the SIGMA "S" terminals are supplied with a terminal-covering cap, avoiding any accidental contact with live parts. All the gauges can be coupled together, forming strips of any length. Operating voltage: 500 V.



Note:
Each terminal accepts up to 2 conductors with the specified section.
20 units
(except for ref. **NSYS95100**: 10 units)

NSYS16

Characteristics	Section (mm²)	A	B	C	D	E	References
Sigma safety terminals	1 x 4	30	20	13	21	4	**NSYS04**
Sigma safety terminals	1 x 6	33	25	16	24	7	**NSYS06**
Sigma safety terminals	1 x 10	38	28	16	28	6	**NSYS10**
Sigma safety terminals	1 x 16	42	32	19	32	9	**NSYS16**
Sigma safety terminals	1 x 35	46	38	23	34	11	**NSYS2535**
Sigma safety terminals	1 x 50	52	45	27	40	15	**NSYS50**
Sigma safety terminals	1 x 70	55	50	30	40	15	**NSYS70**
Sigma safety terminals	1 x 100	58	54	33	40	20	**NSYS95100**

Bimetal terminals

- Terminals specially designed for the junction of cables on plates, their main application is in busbar connections. The bimetal terminals are made from a copper alloy, hot-stamped and tin plated, suitable for connecting a copper or aluminium conductor indistinctly (bimetal).

Supply:
4 bimetal terminals

NSYBBH29P

Characteristics	Main section (mm²)	Junction section (mm²)	References
Bimetal terminals	6-50	-	**NSYBBH29**
Bimetal terminals	6-50	-	**NSYBBH29C**
Bimetal terminals	10-95	-	**NSYBBH30**
Bimetal terminals	16-150	-	**NSYBBH31**
Bimetal terminals	50-240	-	**NSYBBH32**
Bimetal terminals	6-50	6-50	**NSYBBH29D**
Bimetal terminals	10-95	10-95	**NSYBBH30D**
Bimetal terminals	25-150	16-150	**NSYBBH31D**
Bimetal terminals	95-240	5-240	**NSYBBH32D**
Bimetal terminals	6-50	-	**NSYBBH29P**
Bimetal terminals	6-50	6-50	**NSYBBH29DPC**

Plate/cable terminals

Supply:
1 junction terminal

- Entry by plate and junction by cable, plate or terminal

Fig. 1

Fig. 2

Characteristics	Junction cable section (mm²)	Plate thickness (mm)	Fig.	References
Plate/cable terminals	1.5 to 16	5	2	**NSYBPCH516**
Plate/cable terminals	1.5 to 50	5	2	**NSYBPCH550**
Plate/cable terminals	16 to 120	5	2	**NSYBPCH5120**
Plate/cable terminals	1.5 to 16	10	1	**NSYBPCH1016**
Plate/cable terminals	1.5 to 50	10	1	**NSYBPCH1050**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Accessories for low voltage switchboards

Three pole junction terminals

Supply:
1 junction terminal

- Entry by plate and junction by cable (for busbars).

NSYBTE630TBT

Characteristics	Entry plate width	Entry plate thickness	Junction cable section	References
Three pole junction terminals	12/15/20/25/30 mm	5 to 10 mm	35 to 120 mm²	**NSYBTE630TBT**

Earthing strips

- For the junction of neutral and earth cables.
- Models **NSYRBL●●** (Fig. 3) for installation in boxes with insulating rear or by means of insulators, not supplied.
- Models **NSYRBLZ●●** (Fig. 4) with insulating plinth for fitting under pressure on 12 x 2 mm rail.

Supply:
10 earthing strips

Fig. 3


NSYRBL21656M

Fig. 4


NSYRBLZ21656

Fig. 4

NSYRBLZ21656

Characteristics	Number of terminals x section	Fig	References
Earthing strips	2 x 16 mm² + 5 x 6 mm²	3	**NSYRBL21656M**
Earthing strips	2 x 16 mm² + 8 x 6 mm²	3	**NSYRBL21686M**
Earthing strips	2 x 16 mm² + 14 x 6 mm²	3	**NSYRBL216146M**
Earthing strips	2 x 16 mm² + 29 x 6 mm²	3	**NSYRBL216296M**
Earthing strips	2 x 16 mm² + 5 x 6 mm²	4	**NSYRBLZ21656**
Earthing strips	2 x 16 mm² + 8 x 6 mm²	4	**NSYRBLZ21686**
Earthing strips	2 x 16 mm² + 14 x 6 mm²	4	**NSYRBLZ216146**
Earthing strips	2 x 16 mm² + 29 x 6 mm²	4	**NSYRBLZ216296**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Accessories for low voltage switchboards

Linergy LGYE - Horizontal profiles up to 4000 A

Installation in Spacial SF		Up to 1600 A					Up to 4000 A			
Linergy profiles, 2000 mm length		 630 A	 800 A	 1000 A	 1250 A	1600 A	 2000 A	2500 A	 3200 A	 4000 A
Permissible current for an ambient temperature of 35 °C around the switchboard	IP > 31	530 A	680 A	850 A	1050 A	1480 A	1650 A	2100 A	2800 A	3350 A
Number of profiles per phase		1								
Height available (mm)		150					150		200	
References		**04560**	**04561**	**04562**	**04563**	**04564**	**04565**	**04566**	**04567**	**04568**
Busbar supports		 Fixed support **NSYBHS●●**			Free support **NSYBSA**					
		2 supports shall mandatorily be fastened to the structure of the 800 mm wide Spacial SF cubicle. If the width is greater, add a NSYSUCR40●● cabinet cross rail to add a third fixed support. 1 support shall mandatorily be fastened to the structure of the cubicles of width 300 mm and 400 mm. If more supports are required, use free supports.								
Number of supports depending on Icw (kA rms/1 s)	⩽ 15	2 x **NSYBHS●●** *								
	⩽ 25	2 x **NSYBHS●●** *								
	⩽ 30	2 x **NSYBHS●●** *								
	⩽ 40	-		2 x **NSYBHS●●** *						
	⩽ 50	-			2 x **NSYBHS●●** *					
	⩽ 60	-			2+1 **		2 x **NSYBHS●●** *			
	⩽ 65	-				2+1 **				
	⩽ 75	-				2+1 **				
	⩽ 85	-				2+1 **				
	⩽ 100	-					2+4 ***			
References Fixed support		**NSYBHS●●**							**NSYBHS●●** + **04646**	
References Free support		**NSYBSA**							**NSYBSA** + **04646**	

* If spacing between supports > 800 mm add 1 **NSYBSA** free support.
** If spacing between supports > 300 mm add 1 **NSYBSA** free support.
*** If spacing between supports > 135 mm add 1 **NSYBSA** free support.

Joints	Up to 1600 A					Up to 4000 A			
	630 A	800 A	1000 A	1250 A	1600 A	2000 A	2500 A	3200 A	4000 A
References (3P)	**3x 04620**					**3x 04621**		**3x 04623**	
References (4P)	**4x 04620**					**4x 04621**		**4x 04623**	
Note: If insulation clearance < 20 mm add an insulating shield between the busbar and the metallic part of the cabinet.	 **04620**					 **04621**		 **04623**	

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Accessories for low voltage switchboards

Linergy BS - Horizontal busbars up to 4000 A

Installation in Spacial SF		Up to 1600 A				Up to 4000 A					
Copper without holes, 2000 mm length											
Permissible current for an ambient temp. of 35°C around the switchboard	IP > 31	750 A	900 A	1250 A	1600 A	1600 A	1800 A	2000 A	2500 A	2900 A	3340 A
Size of bars (mm)		60 x 5	80 x 5	60 x 5	80 x 5	80 x 10	50 x 10	60 x 10	80 x 10	100 x 10	120 x 10
Number of bars per phase		1	1	2	2	1	2	2	2	2	2
Height available (mm)		150									200
References		**04536**	**04538**	**04536**	**04538**	**04548**	**04545**	**04546**	**04548**	**04550**	**04552**
Busbar supports		Fixed support **NSYBHS●●**				Free support **NSYBSA**					
		2 supports shall mandatorily be fastened to the structure of the 800 mm wide Spacial SF cubicle. If the width is greater, add a **NSYSUCR40●●** cabinet cross rail to add a third fixed support. 1 support shall mandatorily be fastened to the structure of the cubicles of width 300 mm and 400 mm. If more supports are required, use free supports.									
Number of supports depending on Icw (kA rms/1 s)	⩽ 15	2 x **NSYBHS●●** *									
	⩽ 25	2+1 **	2 x **NSYBHS●●** *								
	⩽ 30	2+1 **		2 x **NSYBHS●●** *							
	⩽ 40	2+1 **				2 x **NSYBHS●●** *					
	⩽ 50	-	2+1 **					2 x **NSYBHS●●** *			
	⩽ 60	-				2+1 **					
	⩽ 65	-				2+1 **					
	⩽ 75	-				2+4 ***	2+1 **				
	⩽ 85	-				-		2+1 **			
References Fixed support		**NSYBHS●●**									**NSYBHS●●** + 04646
References Free support		**NSYBSA**									**NSYBSA** + 04646
		* If spacing between supports > 800 mm add 1 NSYBSA free support. ** If spacing between supports > 300 mm add 1 NSYBSA free support. *** If spacing between supports > 135 mm add 1 NSYBSA free support.									

Joints Installation dans Spacial SF	Up to 1600 A				Up to 4000 A					
	1 vertical bar per phase		2 vertical bars per phase		1 vert. bar per phase	2 vertical bars per phase				
Size of bars (mm)	60 x 5	80 x 5	60 x 5	80 x 5	80 x 10	50 x 10	60 x 10	80 x 10	100 x 10	120 x 10
References	**04640**	**04641**	**04640**	**04641**	**04641**	**04640**	**04640**	**04641**	**04641**	**04643**
Sliding joints with torque nut	 **04640**			 **04641**						

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Accessories for low voltage switchboards

Linergy LGY - Lateral profiles up to 1600 A

Installation in Spacial SF		L 300				
						
		630 A	**800 A**	**1000 A**	**1250 A**	**1600 A**
Permissible current for an ambient temp. of 35°C around the switchboard	IP ⩽ 31	590 A	760 A	950 A	1170 A	1480 A
Number of profiles per phase		1				
References		**04502**	**04503**	**04504**	**04505**	**04506**
Busbar supports		Fixed support **04651**		**Note:** An end stop must be fitted on the bottom support: **01109** (sold in lots of 12)		
 Only for depth cubicle ≥ 500 mm	**Number depending on I_{cw} (kA rms/1 s)**	⩽ 25	3			
		⩽ 30	-	3		
		⩽ 40	-	-	3	
		⩽ 50	-	-	4	
		⩽ 60	-	-	5	
		⩽ 65	-	-	-	5
		⩽ 75	-	-	-	7
		⩽ 85	-	-	-	8
References		**04651 + upright adapters NSYSFPA + NSYSUCR40●●**				
Connections to the Linergy BS horizontal busbar			**Note:** Supplied with mounting hardware. Reference include 1 connection only. Order 1 connection per phase.			
References according to horizontal busbar size	5 mm thick		**04634**		**04635**	
	10 mm thick	Width ⩽ 80 mm	**04636**			
	10 mm thick	Width > 80 mm	**04636 + 04642** **04638 + 04642**			
Connections to the Linergy LGYE horizontal busbar		 ⩽ 1600 A	**Note:** Supplied with mounting hardware. Reference include 1 connection only. Order 1 connection per phase.			
References (vertical connection)		**04602**				
References (vertical shifted connection)		**04603**				

11

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Accessories for low voltage switchboards

Linergy LGYE - Lateral profiles up to 4000 A

Installation in Spacial SF		L 300								
Linergy profile, 2000 mm length		 **630 A**	**800 A**	 **1000 A**	 **1250 A**	**1600 A**	 **2000 A**	**2500 A**	 **3200 A**	 **4000 A**
Permissible current for an ambient temperature of 35°C around the switchboard	IP > 31	530 A	680 A	850 A	1050 A	1480 A	1650 A	2100 A	2800 A	3350 A
Number of profiles per phase		1								
Height available (mm)		150					150		200	
References		**04560**	**04561**	**04562**	**04563**	**04564**	**04565**	**04566**	**04567**	**04568**
Busbar supports		Fixed support **NSYBVS●●**			Free support **NSYBSA**			Bottom support **NSYAS●●**		
		3 fixed supports are compulsory to hold the busbar in position. If more than 3 supports are needed, use free supports (in addition).								
 **Number depending on I_{cw} (kA rms/1 s)**	⩽ 30	3								
	⩽ 40	-		3+2 *			3			
	⩽ 50	-			3+2 *		3			
	⩽ 60	-			3+2 *				3	
	⩽ 65	-				3+2 *				
	⩽ 75	-				3+4 **			3+2 *	
	⩽ 85	-				3+4 **				
	⩽ 100	-						3+6 ***		
References Fixed support		**NSYBVS●●**							**NSYBHS●● + 04646**	
References Bottom support		**NSYAS●●**							**NSYAS●● + 04646**	
References Free support		**NSYBSA**							**NSYBSA + 04646**	
		* If spacing between supports > 400 mm add 1 **NSYBSA** free support. ** If spacing between supports > 250 mm add 1 **NSYBSA** free support. *** If spacing between supports > 130 mm add 1 **NSYBSA** free support.								
Wedging busbars in position		 Wedge fitted on bottom support					 Wedge fitted on bottom support			
		The bottom support **NSYAS●●** + **0465●** is used to place profiles and ensure they are in the correct position. It is not considered to be a busbar support.								
References		**04658** (set of 12 wedges)					**04659** (set of 12 wedges)			
Connections to the Linergy LGYE horizontal busbar		2000/2500 A 							3200/4000 A 	
		Supplied with mounting hardware. Reference include 1 connection only. Order 1 connection per phase.								
References (short connection)		**04604**							**04607**	
References (long connection)		**04605**								

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Accessories for low voltage switchboards

Linergy BS - Lateral flat busbars up to 3200 A

Installation in Spacial SF		Up to 1600 A				Up to 3200 A						
Pre-slotted copper, 1675 mm length												
Permissible current for an ambient temp. of 35°C around the switchboard	IP > 31	750 A	900 A	1250 A	1600 A	1080 A	1250 A	1600 A	1850 A	2000 A	2500 A	2820 A
Busbar cross-section (mm)		60 x 5	80 x 5	60 x 5	80 x 5	50 x 10	60 x 10	80 x 10	50 x 10	60 x 10	80 x 10	100 x 10
Number of profiles per phase		1		2		1			2			
References		**04516**	**04518**	**04516**	**04518**	**04525**	**04526**	**04528**	**04525**	**04526**	**04528**	**04550**
Busbar supports		Fixed support **NSYBVS●●**				Free support **NSYBSA**			Bottom support **NSYAS●●**			
		3 fixed supports are compulsory to hold the busbar in position. If more than 3 supports are needed, use free supports (in addition). The bottom wedge support is used to place the busbar and ensure it is in the correct position. It does not count as a busbar support.										
	**Number of supports depending on I_{cw} (kA rms/1 s)**	⩽ 15	3 *									
		⩽ 25	3+2 *		3 *							
		⩽ 30	3+2 *								3 *	
		⩽ 40	3+4		3+2 *							
		⩽ 50		3+4		3+2 *						
		⩽ 60				3+4					3+2 *	
		⩽ 65				3+4					3+2 *	
		⩽ 75					3+6		3+4			
		⩽ 85								3+4		
References Fixed support		**NSYBVS●●**										
References Bottom support		**NSYAS●●**										
References Free support		**NSYBSA**										
		* If spacing between supports > 350 mm add 1 NSYBSA free support.										
Connections to the Linergy BS horizontal busbar												
		For a busbar with 75 mm distance between bars, the bars must be completely covered. Staggered assembly points between one bar and the next, to maintain the necessary clearance distances.(3)				References **04636**, **04637**, **04638** are supplied individually: 1 connection per phase. Reference **04642** consists of 2 M8 x 140 screws which can replace the original M8 x 120 screws.						
												
		1 bar per phase		2 bars per phase		1 bar per phase			2 bars per phase			
		60 x 5	80 x 5	60 x 5	80 x 5	50 x 10	60 x 10	80 x 10	50 x 10	60 x 10	80 x 10	100 x 10
References depending on horizontal busbar size	Width ⩽ 80 mm	**04645**				**04636**		**04637**				**04645**
	Width > 80 mm	**04645**				**04636** + **04642**		**04637** + **04642**				**04645**

(1) Drill hole dimensions for 5 mm thick horizontal busbars.



Drill hole dimensions for 10 mm thick horizontal busbars.



11

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Accessories for low voltage switchboards

Linergy TB

Characteristics		PE conductor						
								
		Vertical PE conductor with Linergy LGY profile (W = 1670 mm)			Vertical PE conductor with Linergy BS busbar (W = 1675 mm)		Horizontal PE conductor with Linergy BS busbar	
Rated short-time current	**(Isc)**	≤ 65	> 65... ≤ 80	= 100	≤ 40	> 40	≤ 40	> 40
Permissible current	**(A)**	630	800	1250	-	-	-	-
Bar size	**(mm)**	-	-	-	25 x 5	50 x 5	25 x 5	50 x 5
Characteristics		-	-	-	Drilled flat bar Ø10.6 mm (one 10.6 mm hole every 25 mm along the entire length)	Drilled flat bar Ø10.6 mm (two 10.6 mm hole every 25 mm along the entire length)	-	-
References		**04502**	**04503**	**04505**	**04512**	**04515**	**04512**	**04512**

Connection between PE conductors


04672


04766



Characteristics	Composition	References
Connection plates for horizontal/vertical PE bars	2 copper angle brackets	**04672**
Linergy connection hardware	20 M8 bolts (W = 25 mm) + 20 nuts + 20 contact washers for connection to cable lugs or flexible bars	**04766**

PEN conductor


04656



Characteristics	References
Linergy TB PEN installation kit with LGY vertical profile	**04656**
1600 A connection 10 mm horizontal busbar with Linergy LGY profile	**04636**
Linergy LGYE vertical connection 1600 A	**04602**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Connection between device and busbars

- The flexible bars are determined taking into account the connected device, whatever the internal temperature of the switchboard.
- The bar sizes indicated below take into account the derating curves of devices.
- Width: 1800 mm
- Rated insulation voltage (Ui): 1000 V
- Maximum withstand temperature for the insulating material: 125 °C



04742

Characteristics	Size (mm)	References
NSX100	20 x 2	**04742**
NSX160/250	20 x 3	**04743**
NSX400	32 x 5	**04751**
NSX630	32 x 8	**04753**
FM 200 A Linergy	20 x 3	**04743**
FC 3P Linergy	32 x 8	**04753**
FC 4P Linergy	32 x 8	**04753**
Fupact 250	24 x 5	**04746**
Fupact 400	32 x 5	**04751**
Fupact 630	32 x 8	**04753**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Accessories for low voltage switchboards

Spacial SF IEC 61439-2 certified assemblies

Introduction

Because low-voltage switchboards must comply with the IEC 61439-2 standard, we have tested the most unfavourable and the most representative configurations (§ 10.10.2 of IEC 61439-1 ed2 2011) ranging up to 4000 A. We thus cover the entire product range, based on the Spacial SF universal assembly system, allowing you to thus comply with the requirements of the standard.

Whether you are an OEM or a panelbuilder, using universal enclosures and looking for flexibility and reliable assembly advice for integration of the equipment, you will find in this guide how to produce in optimal conditions an electrical switchboard fitted with Schneider Electric equipment.

To meet continuity of service and electrical safety requirements, we provide you with certificates based on assemblies tested with a third-party organization in accordance with the IEC 61439-2 standard, adopting the most commonly used configurations, which will help you to finalize your switchboard with complete confidence using useful, reliable and certain information that has been verified

These tests cover the entire Spacial SF range of dimensions and supplement our range of tested Spacial SFP enclosures based on the functional unit system of Prisma, and Spacial SFM for MCC applications. This guide is also an opportunity to give a reminder of the fundamental rules for use of an enclosure and for installation of equipment in Spacial SF.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Accessories for low voltage switchboards

Spacial SF IEC 61439-2 certified assemblies

Compatibility table

Dimensions			Intensity (A)				
Height (mm)	Width (mm)	Depth (mm)	≤ 800 A	≤ 1250 A	≤ 1600 A	≤ 2500 A	≤ 4000 A
1200	600	400	●				
	600	600	●				
	800	400	●				
	800	600	●				
1400	600	400	●	●			
	800	400	●	●			
1600	600	600	●	●			
	600	800	●	●			
	800	600	●	●			
	800	800	●	●			
1800	600	400	●	●	●		
	600	500	●	●	●		
	600	600	●	●	●	●	
	600	800	●	●	●	●	
	800	400	●	●	●		
	800	500	●	●	●		
	800	600	●	●	●	●	
	1000	400	●	●	●		
	1000	500	●	●	●		
	1000	600	●	●	●	●	
	1200	400	●	●	●		
	1200	500	●	●	●		
	1200	600	●	●	●	●	
2000	600	400	●	●	●		
	600	500	●	●	●		
	600	600	●	●	●	●	
	600	800	●	●	●	●	●
	800	400	●	●	●		
	800	500	●	●	●		
	800	600	●	●	●	●	
	800	800	●	●	●	●	●
	1000	400	●	●	●		
	1000	500	●	●	●		
	1000	600	●	●	●	●	
	1000	800	●	●	●	●	●
	1200	400	●	●	●		
	1200	500	●	●	●		
	1200	600	●	●	●	●	
	1200	800	●	●	●	●	●
	1600	400	●	●	●		
	1600	500	●	●	●		
	1600	600	●	●	●	●	
2200	600	600	●	●	●	●	
	600	800	●	●	●	●	●
	800	600	●	●	●	●	
	800	800	●	●	●	●	●
	1000	600	●	●	●	●	
	1200	600	●	●	●	●	
	1200	800	●	●	●	●	●

●: Certified dimensions for indicated intensity

How to assemble a Spacial SF switchboard
(Implementation of the standard IEC 61439) Technical guide
Ref : UE17MK01EN

IEC 61439-2 certification (IECEE CB scheme issued by DEKRA) is valid only once installation has been carried out, according to the recommendations indicated in the technical guide, "how to assemble a Spacial SF switchboard", with the Schneider Electric devices featured in this guide.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Prisma functional system

The Prisma functional system can be used for all types of low-voltage distribution switchboards up to 4000 A, in commercial and industrial environments.

Switchboard design is very simple

1. **A metal structure**
   made up of one or more frameworks combined side-by-side or back-to-back.
2. **A distribution system**
   positioned in a lateral compartment or at the rear of the cubicle are used to distribute electricity throughout the switchboard.
3. **Complete functional units**
   - dedicated mounting plate for device installation
   - front plate to block direct access to live parts
   - devices for on-site connections.

The functional units are modular and are arranged rationally, one on top of another, within the enclosure. The components of the Spacial SFP and those of the functional units in particular have been designed and tested taking into account device characteristics. This design approach ensures a high degree of reliability in system operation and optimum safety for personnel.

Advantages of Prisma system switchboards

1. **A safe electrical installation**
   The total compatibility of Schneider Electric devices with the Prisma system is a key advantage in ensuring a high level of installation dependability.
2. **An upgradeable electrical installation**
   Thanks to modular design, Spacial SFP switchboards can be modified easily to integrate new functional units as needed
3. **Total safety for personnel**
   Work in a switchboard must be carried out by authorised persons in compliance with all applicable safety regulations. To increase the safety of personnel, devices are installed behind protective front plates; Only the operating handles are accessible. Additional internal protection (partitions, barriers) is available to create form 2, form 3 and form 4 separation to protect against direct contacts with live parts.
   Terminal shields are mandatory for installation of Compact NSX and INS/INV devices in Prisma system enclosures.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Prisma functional system

Use of the components in the Prisma functional system ensures the creation of switchboards complying with standards IEC 62208, IEC 61439-2.



Mechanical characteristics

- Steel sheet metal.
- Structured finish, epoxy polyester powder.
- Grey colour RAL 7035.
- Can be dismantled.
- Can be combined side-by-side and back-to-back.
- Degree of protection: IP55 according to IEC 60529.
- Degree of protection against mechanical impacts: IK10 (IK08 for the glazed-door) according to IEC 62262.

Framework dimensions:
two widths:

- W 300: Cable compartment
  W 700: Device compartment or cable compartment

three depths:

- D500 up to 1600 A with incoming Masterpact NT and MTZ1 only
- D600 up to 1600 A with incoming Masterpact NT and MTZ1 only. Possibility to connect with cables from rear
- D800 up to 3200 A with incoming Masterpact NT and MTZ1 or NW and MTZ2. Possibility to connect to cables from rear or to connect to rear vertical busbars
- height: 2000 mm
- Enclosures for indoor installation.

Electrical characteristics

- Rated insulation level of main busbars: 1000 V.
- Rated operational current Ie: 4000 A.
- Rated peak withstand current Ipk: 220 kA.
- Rated short-time withstand current I_{cw}: 100 kA rms/1 second.
- Frequency: 50/60 Hz.

Electrical switchboards built using the Prisma functional system and Schneider Electric recommendations fully comply with international standard IEC 61439-2.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Prisma functional system

The forms according to IEC 61439-2
Decisions concerning the Form of separation and the degree of protection are the subject of an agreement between the manufacturer and the user.

The forms according to IEC 61439-2

In most installations, Spacial SFP cubicles do not require partitioning. In this case, the switchboard is a Form 1. Safety being one of its foremost goals, Schneider Electric offers options and features that go well beyond the recommendations of the standard.

The protection of life and property is a standard feature due to:

- front plates that require a tool to be removed
- keylocks on doors, some of which provide access to live parts
- the systematic installation of terminal shields on Compact NSX circuit breakers and Compact INS and INV switch-disconnectors
- covering of the upstream and downstream terminals on the incoming device so that operators are perfectly safe at all points in the switchboard when the incoming device is off (open).

What is more, Spacial SFP offers different levels of partitioning to create separations inside the cubicles and thus create Form 2b, 3b, 4a and 4b electrical switchboards. Electrical switchboards must meet the degree of protection IP2X to comply with standard IEC 61439-2.

Form 1



In most installations, Spacial SFP cubicles do not require partitioning. In this case, the switchboard is a Form 1.
Safety being one of its foremost goals, Schneider Electric offers options and features that go well beyond the recommendations of the standard.

Form 2b



- Terminals for external conductors separated from busbars.
- The functional units and the terminals are separated from the busbars.

Form 3b



- Terminals for external conductors separated from busbars.
- The functional units are separated from each other and from the busbars.
- The terminals are separated from the busbars, but not from each other.

Form 4a



Terminals for external conductors in the same compartment as the associated functional unit.

Form 4b



Terminals for external conductors not in the same compartment as the associated functional unit, but in individual, separate, enclosed protected spaces or compartments.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Life Is On Schneider Electric

Prisma functional system

Upgradeable Prisma functional units
Functional units include switchgear mounting plates, front plates, connection supports, barriers…

Masterpact
NW08 to NW40

Masterpact
NT06 to NT16

Masterpact
MTZ1 and MTZ2

Compact NSX
to 630 A

Compact NS
from 630b to 1600 A

Compact NS
to 3200 A

Easypact
from 100 to 630 A

Compact INS-
INV250-630 A

Compact INS-
INV630-2500 A

Source changeover
systems
Compact/Masterpact

Source changeover
systems Compact INS

Fupact from 32 to 1250 A



For more informations, see the catalogue Prisma P DESW016EN

11

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Linergy LGYE - Horizontal profiles up to 4000 A

Installation in Spacial SFP		Up to 1600 A					Up to 4000 A			
Linergy profile, 2000 mm length										
		630 A	**800 A**	**1000 A**	**1250 A**	**1600 A**	**2000 A**	**2500 A**	**3200 A**	**4000 A**
Permissible current for an ambient temperature of 35°C around the switchboard	IP ⩽ 31	630 A	800 A	1000 A	1250 A	1650 A	2000 A	2440 A	3200 A	3620 A
	IP > 31	530 A	680 A	850 A	1050 A	1480 A	1650 A	2100 A	2800 A	3350 A
Number of profiles per phase		1								
Total number of vertical modules (50 mm)		3					3		4	
References		**04560**	**04561**	**04562**	**04563**	**04564**	**04565**	**04566**	**04567**	**04568**
Busbar supports 		 Fixed support **04664**  Free support **NSYBSA** 2 fixed supports for Spacial SFP 700 wide frame are compulsory. 1 fixed support for 300/400 wide frame are compulsory. If more supports are needed, add free supports.								
In cubicle: W700 Busbar supports 75 mm distance between bars	**Number of supports depending on I_{cw} (kA rms/1 s)** ≤ 15	2								
	≤ 25	2								
	≤ 30	2								
	≤ 40	-		2						
	≤ 50	-			2					
	≤ 60	-			2+1		2			
	≤ 65	-				2+1				
	≤ 75	-				2+1				
	≤ 85	-				2+1				
	≤ 100	-					2+2			
References Fixed support		**04664**					**04664** + **04671** (order 1 per support)		**04664** + **04646** (sold in lots of 12 spacers)	
References Free support		**NSYBSA**					**NSYBSA** + **04671** (order 1 per support)		**NSYBSA** + **04646** (sold in lots of 12 spacers)	
In duct: W300 Busbar supports 75 mm distance between bars	**Number of supports depending on I_{cw} (kA rms/1 s)** ≤ 15	1								
	≤ 25	1								
	≤ 30	1								
	≤ 40	1								
	≤ 50	1								
	≤ 60	1								
	≤ 65	1 + 1								
	≤ 75	1 + 1								
	≤ 85	1 + 1								
	≤ 100	-					1 + 1			
References Fixed support		**04664**					**04664** + **04671** (order 1 per support)		**04664** + **04646** (sold in lots of 12 spacers)	
References Free support		**NSYBSA**					**NSYBSA** + **04671** (order 1 per support)		**NSYBSA** + **04646** (sold in lots of 12 spacers)	
Joints		Up to 1600 A					Up to 4000 A			
		630 A	**800 A**	**1000 A**	**1250 A**	**1600 A**	**2000 A**	**2500 A**	**3200 A**	**4000 A**
										
		04620		**04623**			**04624**			
References (3P)		3x **04620**					3x **04621**		3x **04623**	
References (4P)		4x **04620** + **04624**					4x **04621** + **04624**		4x **04623** + **04624**	
		Reference **04624** is compulsory when installing jointed Linergy LGYE 4P busbars and must be fitted where the frames meet. When installed at the bottom of a cubicle, the busbar must be partitioned.								

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Prisma functional system

Linergy LGYE - Horizontal profiles up to 4000 A

Installation in Spacial SFP		Up to 1600 A				Up to 4000 A					
Copper bar, 2000 mm length **Note:** When installed at the bottom of a cubicle, the busbar must be partitioned.											
Permissible current for an ambient temp. of 35 °C around the switchboard	IP ⩽ 31	800 A	1000 A	1400 A	1800 A	1800 A	2050 A	2300 A	2820 A	3300 A	3760 A
	IP > 31	750 A	900 A	1250 A	1600 A	1600 A	1850 A	2000 A	2500 A	2900 A	3340 A
Busbar cross-section (mm)		60 x 5	80 x 5	60 x 5	80 x 5	80 x 10	50 x 10	60 x 10	80 x 10	100 x 10	120 x 10
Number of busbars per phase		1	1	2	2	1	2	2	2	2	2
Total number of vertical modules (50 mm)		3									4
References		**04536**	**04538**	**04536**	**04538**	**04548**	**04545**	**04546**	**04548**	**04550**	**04552**
Busbar supports 		 Fixed support **04664**  Free support **NSYBSA** 2 fixed supports for Spacial SFP 700 wide frame are compulsory. 1 fixed support for 300/400 wide frame are compulsory. If more supports are needed, add free supports.									
In cubicle: W700 with 75 mm distance between bars	**Number of supports depending on I_{cw} (kA rms/1 s)** ≤ 15	2									
	≤ 25	2+1	2								
	≤ 30	2+1		2							
	≤ 40	2+1				2					
	≤ 50	-	2+1					2			
	≤ 60	-				2+1					
	≤ 65	-				2+1					
	≤ 75	-				2+2	2+1				
	≤ 85	-				-		2+1			
References Fixed support		**04664**				**04664**			**04664** + **04671**		
References Free support		**NSYBSA**				**NSYBSA**			**NSYBSA** + **04671**		
In duct: W300 with 75 mm distance between bars	**Number depending on I_{cw} (kA rms/1 s)** ≤ 30	1									
	≤ 50	1+1				1					
	≤ 85	-				2					
References (depending on depth) Fixed support		**NSYBHS500** (D500) or **NSYBHS600** (D600) or **NSYBHS800** (D800)				**NSYBHS500** (D500) or **NSYBHS600** (D600) or **NSYBHS800** (D800)			**NSYBHS500** (D500) or **NSYBHS600** (D600) or **NSYBHS800** (D800) + 04671		
References (depending on depth) Free support		**NSYBSA**				**NSYBSA**			**NSYBSA** + **04671**		
Joints		Up to 1600 A				Up to 4000 A					
		1 vertical bar per phase		2 vertical bars per phase		1 vert. bar per phase	2 vertical bars per phase				
Busbar cross-section (mm)		60 x 5	80 x 5	60 x 5	80 x 5	80 x 10	50 x 10	60 x 10	80 x 10	100 x 10	120 x 10
Sliding joints with self-breaking lock nut		 **04640**			 **04641**						
References		**04640**	**04641**	**04640**	**04641**	**04641**	**04640**	**04640**	**04641**	**04641**	**04643**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Linergy LGY - Lateral profiles up to 1600 A

In Spacial SFP duct		W300				
		 630 A	 800 A	 1000 A	 1250 A	 1600 A
Permissible current for an ambient temp. of 35°C around the switchboard	IP ⩽ 31	590 A	760 A	950 A	1170 A	1480 A
	IP > 31	590 A	760 A	950 A	1170 A	1480 A
Number of profiles per phase		1				
References		**04502**	**04503**	**04504**	**04505**	**04506**



Only for depth cubicle ≥ 500 mm



Fixed support 04651

Note:
An end stop must be fitted on the bottom support: 01109 (sold in lots of 12)

Number depending on I_{cw} (kA rms/1 s)	⩽ 25	3				
	⩽ 30	-	3			
	⩽ 40	-		3		
	⩽ 50	-			4	
	⩽ 60	-			5	
	⩽ 65	-				5
	⩽ 75	-				7
	⩽ 85	-				8
References		**04651 (set of 2 upright adapters NSYSFPA for installation in Spacial SFP cubicle)**				

Connections to the Linergy BS horizontal busbar



Note:
Supplied with mounting hardware. Reference include 1 connection only. Order 1 connection per phase.

References according to horizontal busbar size	5 mm thick		**04634**	**04635**
	10 mm thick	Width ⩽ 80 mm	**04636**	
	10 mm thick	Width > 80 mm	**04636** + **04642** **04638** + **04642**	

Connections to the Linergy LGYE horizontal busbar



Note:
Supplied with mounting hardware. Reference include 1 connection only. Order 1 connection per phase.

References (vertical connection)	**04602**
References (vertical shifted connection)	**04603**

(1) Dedicated connection 04603 for Linergy LGYE busbar in 150 mm duct with horizontal jointing.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Linergy LGYE - Lateral profiles up to 4000 A

In Spacial SFP duct		W300								
Linergy profile, 2000 mm length										
		630 A	**800 A**	**1000 A**	**1250 A**	**1600 A**	**2000 A**	**2500 A**	**3200 A**	**4000 A**
Permissible current for an ambient temperature of 35°C around the switchboard	IP <= 31	630 A	800 A	1000 A	1250 A	1650 A	2000 A	2440 A	3200 A	3620 A
	IP > 31	530 A	680 A	850 A	1050 A	1480 A	1650 A	2100 A	2800 A	3350 A
Length to cut for side mounting		1675 mm							1625 mm	
Number of profiles per phase		1								
Height available (mm)		150					150		200	
References		**04560**	**04561**	**04562**	**04563**	**04564**	**04565**	**04566**	**04567**	**04568**
										
		Fixed support **NSYBVS500**			Free support **NSYBSA**			Bottom support **NSYAS500**		
		3 fixed supports are compulsory to hold the busbar in position. If more than 3 supports are needed, use free supports (in addition).								
 **Number depending on I_{cw} (kA rms/1 s)**	≤ 30	3								
	≤ 40	-		3+2 *			3			
	≤ 50	-			3+2 *		3			
	≤ 60	-			3+2 *			3		
	≤ 65	-				3+2 *				
	≤ 75	-				3+4 **		3+2 *		
	≤ 85	-				3+4 **				
	≤ 100	-						3+6 ***		
References* 75 mm distance between bars	W300, D500	**NSYBVS500** (fixed) + **NSYBSA** (free) + **NSYAS500** (spacer) (1)								
References* 75 mm distance between bars	W300, D600	**NSYBVS600** (fixed) + **NSYBSA** (free) + **NSYAS600** (spacer) (1)								
References* 75 mm distance between bars	W300, D800	**NSYBVS800** (fixed) + **NSYBSA** (free) + **NSYAS800** (spacer) (1)								
References* 115 mm distance between bars	W300, D800	**NSYBVS800L** (fixed) + **04678** (free) + **NSYAS800L** (spacer) (1)								
* References of supports depending on distance between bars and duct depth		(1) If using a 100 x 10 bars, add a pack of screws ref. **04671** for each fixed support and free support.								
Wedging busbars in position										
		Wedge fitted on bottom support **04658**					Wedge fitted on bottom support **04659**			
		The bottom support is used to place profiles and ensure they are in the correct position. It is not considered to be a busbar support.								
References Bottom support		**04663**							**04666** + **04661**	
References Wedge		**04658**					**04659**			
Connections to the Linergy LGYE horizontal busbar		2000/2500 A							3200/4000 A	
										
		Supplied with mounting hardware. Reference include 1 connection only. Order 1 connection per phase.								
References (short connection)		**04604**							**04607**	
References (long connection)		**04605**								

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Linergy BS - Lateral flat busbars up to 3200 A

In Spacial SFP duct		W300 D500/600/800 up to 1600 A				W300 D500/600/800 up to 3200 A						
Pre-slotted copper, 1675 mm length 												
Permissible current for an ambient temp. of 35°C around the switchboard	IP ≤ 31	800 A	1000 A	1400 A	1800 A	1200 A	1400 A	1800 A	2050 A	2300 A	2820 A	3200 A
	IP > 31	750 A	900 A	1250 A	1600 A	1080 A	1250 A	1600 A	1850 A	2000 A	2500 A	2820 A
Busbar cross-section (mm)		60 x 5	80 x 5	60 x 5	80 x 5	50 x 10	60 x 10	80 x 10	50 x 10	60 x 10	80 x 10	100 x 10
Number of profiles per phase		1		2		1			2			
References		**04516**	**04518**	**04516**	**04518**	**04525**	**04526**	**04528**	**04525**	**04526**	**04528**	**04550 (1)**
Busbar supports 		3 fixed supports are compulsory to hold the busbar in position. If more than 3 supports are needed, use free supports (in addition). The bottom wedge support is used to place the busbar and ensure it is in the correct position. It does not count as a busbar support.										
Number of supports depending on I_{cw} (kA rms/1 s)	≤ 15	3 *										
	≤ 25	3+2 *			3 *							
	≤ 30	3+2 *									3 *	
	≤ 40	3+4		3+2 *								
	≤ 50		3+4			3+2 *						
	≤ 60					3+4					3+2 *	
	≤ 65					3+4					3+2 *	
	≤ 75						3+6		3+4			
	≤ 85									3+4		
References* 75 mm distance betw. bars	W300, D500	**NSYBVS500** (fixed) + **NSYBSA** (free) + **NSYAS500** (spacer) (2)										
References* 75 mm distance betw. bars	W300, D600	**NSYBVS600** (fixed) + **NSYBSA** (free) + **NSYAS600** (spacer) (2)										
References* 75 mm distance betw. bars	W300, D800	**NSYBVS800** (fixed) + **NSYBSA** (free) + **NSYAS800** (spacer) (2)										
References* 115 mm distance betw. bars	W300, D800	**NSYBVS800L** (fixed) + **04678** (free) + **NSYAS800L** (spacer) (2)										
* References. of supports depending on distance between bars and duct depth		(1) Copper bar without holes. (2) If using a 100 x 10 bars, add a pack of screws ref. **04671** for each fixed support and free support.										
Connections to the Linergy BS horizontal busbar												
		For a busbar with 75 mm distance between bars, the bars must be completely covered. Staggered assembly points between one bar and the next, to maintain the necessary clearance distances.(3)				References **04636**, **04637**, **04638** are supplied individually: 1 connection per phase. Reference **04642** consists of 2 M8 x 140 screws which can replace the original M8 x 120 screws.						
												
		1 bar per phase		2 bars per phase		1 bar per phase			2 bars per phase			
		60 x 5	80 x 5	60 x 5	80 x 5	50 x 10	60 x 10	80 x 10	50 x 10	60 x 10	80 x 10	100 x 10
References depending on horizontal busbar size	≤ 80 mm	**04645**				**04636**		**04637**	**04637**			**04645**
	> 80 mm	**04645**				**04636** + **04642**		**04637** + **04642**	**04637** + **04642** **04638** + **04642**			**04645**

(1) Drill hole dimensions for 5 mm thick horizontal busbars.



Drill hole dimensions for 10 mm thick horizontal busbars.



11

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Linergy LGYE - Rear profiles up to 1600 A

At the rear of a Spacial SFP cubicle		W700				
		 **630 A**	 **800 A**	 **1000 A**	 **1250 A**	 **1600 A**
Permissible current for an ambient temp. of 35 °C around the switchboard	IP ⩽ 31	680 A	840 A	1040 A	1290 A	1650 A
	IP > 31	590 A	760 A	950 A	1170 A	1480 A
Number of profiles per phase		1				
References		**04502**	**04503**	**04504**	**04505**	**04506**
Busbar supports		 Fixed support **04652**				
	Number depending on I_{cw} (kA rms/1 s) ⩽ 25	3				
	⩽ 30		4			
	⩽ 40			5		
	⩽ 50				7	
			**Note:** An end stop must be fitted on the bottom support **01109** (sold in lots of 12)			
References		**04652**				
Connections to the Linergy BS horizontal flat busbar		 **04635** connection to 5 mm thick horizontal busbar		 **04636** connection to 10 mm thick horizontal busbar		
		Fixings supplied, order 1 connection per phase. For part of the connection, flexible insulated busbars are needed.				
References according to horizontal busbar size	5 mm thick	**04635**				
	10 mm thick — Width ⩽ 80 mm	**04636**				
	10 mm thick — Width > 80 mm	**04636** + **04642**				
Connections to the Linergy LGYE horizontal flat busbar		 **04602** connection to the Linergy LGYE horizontal flat busbar				
		Fixings supplied, order 1 connection per phase. For part of the connection, flexible insulated busbars are needed.				
References		**04602**				

11

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Linergy BS - Rear flat busbars up to 1600 A

At the rear of a Spacial SFP cubicle		W700					
Pre-slotted copper, 1670 mm length		**800 A**	**1000 A**	**1400 A**	**1000 A**	**1200 A**	**1600 A**
Permissible current for an ambient temperature of 35 °C around the switchboard	IP ⩽ 31	800 A	1000 A	1400 A	-	-	-
	IP > 31	750 A	900 A	1250 A	1080 A	1250 A	1600 A
Busbar cross-section (mm)		60 x 5	80 x 5	60 x 5	50 x 10	60 x 10	80 x 10
Number of busbars per phase		1		2	1		
References		**04516**	**04518**	**04516**	**04525**	**04526**	**04528**
Busbar supports		 Fixed busbar support **04653**		 Busbar free support **NSYBSA**		 Mounting chocks **04669**	
		3 fixed supports ref. **04653** are compulsory to keep the busbar vertical. If more than 3 supports are needed, use free support ref. **NSYBSA** (in addition). Metal shim ref. **04669** (sold in lots of 100), 5 mm thick, is screwed onto the busbar. It rests on a fixed support and is used to wedge the busbar in position.					
							
		Wedging: 1 busbar/phase					
							
		Wedging: 2 busbars/phase					
 **Number depending on I_{cw} (kA rms/1 s)**	⩽ 15	3			3		
	⩽ 25	3+2			3		
	⩽ 30	3+2			3+2		
	⩽ 40	3+4		3+2	3+2		
	⩽ 50		3+4		3+2		
	⩽ 60				3+4		
	⩽ 65				3+4		
	⩽ 75					3+6	
	⩽ 85						
References		**04653** (fixed) + **NSYBSA** (free) + **04669** (spacer)					
Connections to the Linergy BS horizontal flat busbar		 **04635** connection to horizontal busbar 5 mm thick			 **04636** connection to horizontal busbar 10 mm thick		
		For part of the connection, flexible insulated busbars are needed. References **04635**, **04636** are supplied individually = 1 connection per phase. Reference **04642** consists of 2 M8 x 140 screws which can replace the original M8 x 120 screws.					
References according to horizontal busbar size	5 mm thick		**04635**				
	10 mm thick	Width ⩽ 80 mm	**04636** (1)				
	10 mm thick	Width > 80 mm	**04636** + **04642** (1)				
		(1) To be made.					

11

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Linergy LGYE - Accessories

Linergy screw

- Sold in lots of 20: 20 screws + 20 nuts + 20 contact washers, class 8.8. The screws slide into the profile and are then locked in the desired position.







Characteristics		AD	References
Steel plain washers	M8 sold in lots of 20	20 mm	**04772**
	M8 sold in lots of 20	24 mm	**04773**
	M8 sold in lots of 20	28 mm	**04774**
Brass plain washers	M8 sold in lots of 20 for connection of ≤ 25 mm² lugs to Linergy	20 mm	**04775**
Identification	12 clip-on supports + N, L1, L2, L3, PE, PEN labels		**04794**
	Linergy LGYE busbar screw plate kit after sales service		**01130**

M8 bolts


04782

- Set of 20 bolts + 20 nuts + 40 contact washers.

Characteristics	References
Linergy BS, 20 bolts 8.8 class, M8 x 20	**04782**
Linergy BS, 20 bolts 8.8 class, M8 x 25	**04783**
Linergy BS, 20 bolts 8.8 class, M8 x 30	**04784**
Linergy BS, 20 bolts 8.8 class, M8 x 35	**04785**
Linergy BS, 20 bolts 8.8 class, M8 x 40	**04786**
Linergy BS, 20 bolts 8.8 class, M8 x 45	**04787**
Linergy BS, 20 bolts 8.8 class, M8 x 50	**04788**

Torque nuts

04759

- Can be used to obtain the correct tightening torque (28 Nm) recommended by then manufacturer, without using a torque wrench. Torque nuts may be used for all electrical connections.

Characteristics	References
20 M8 torque nuts	**04759**

Voltage tap-offs


04229

- For small lugs (on low-current cables or measurement tap-offs), insert a conducting washer (ref. **04775**) between the busbar and the lug.

Characteristics	References
20 M10 voltage tap-offs for two 6.35 mm tab connectors	**04229**

Connections on Linergy LGYE and LGY


04766

04768

04769

Characteristics	InA	bar	Utilisation	References
Use the 25 mm Linergy screw	0 A to 630 A	Cable Insulated flexible bar	Recommended	**04766**
Use the 39 mm Linergy screw is only compatible with Linergy LGY.	0 A to 630 A	Cable Insulated flexible bar	Possible	**04767**
Use the 25 mm Linergy screw	800 A to 1250 A	5 mm thick bar	Recommended	**04766**
Use the 39 mm Linergy screw is only compatible with Linergy LGY.	800 A to 1250 A	5 mm thick bar	Possible	**04767**
Use the flat plate screw with 2 studs	800 A to 1250 A	5 mm thick bar	Possible	**04768**
Use the flat plate screw with 2 studs	1600 A to 2500 A	5 or 10 mm thick bar	Recommended	**04768**
Use the 39 mm Linergy screw is only compatible with Linergy LGY.	1600 A to 2500 A	5 or 10 mm thick bar	Possible	**04767**
Use the flat plate screw with 3 studs	3200 A to 4000 A	10 mm thick bar	Recommended	**04769**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Form 1 partitioning

Presentation:
Decisions concerning the Form of separation and the degree of protection are the subject of an agreement between the manufacturer and the user.



The protection of life and property is ensured by the systematic installation of terminal shields on Compact NSX circuit breakers and on Compact INS and INV switch-disconnectors (see the pages on the functional units).

IIn most installations, Spacial SFP cubicles do not require partitioning. In this case, the switchboard is a Form 1. Safety being one of its foremost goals, Schneider Electric offers options and features that go well beyond the recommendations of the standard.

The protection of life and property is a standard feature due to:

- front plates that require a tool to be removed
- keylocks on doors, some of which provide access to live parts
- the systematic installation of terminal shields on Compact NSX circuit breakers and Compact INS and INV switch-disconnectors.

What is more, Spacial SFP offers different levels of partitioning to create separations inside the cubicles and thus create Form 2b, 3b, 4a and 4b electrical switchboards.

Electrical switchboards must meet the degree of protection IP2X to comply with standard IEC 61439-2.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Form 2b partitioning

Note:
when the busbars are at the bottom of the cubicle, gland plates are mandatory.

Separation of busbars from the functional units:
- protection against contact with live parts upstream of the outgoing circuits
- protection against penetration of foreign solid bodies.

Lateral partitioning; Form 2 restoration for side-barrier cut-out


06545



Characteristics	References
Lateral partitioning • Vertical barrier made of insulating slats. • Can be installed on both sides of Linergy and flat busbars. • The space between the slats is sufficient for prefabricated connections (one copper bar, 5 or 10 mm thick, or insulated flexible bars) or for cables up to 35 mm², while maintaining the degree of protection IP2X compliance with standard IEC 60695.2.1 concerning withstand to fire.	**06545**
Form 2 restoration for side-barrier cut-out • This kit enables passage of the connection between a device > 1600 A (NW, INS) and lateral vertical busbars. • It is made up of an insulated plate (six modules H 300 mm) that can be cut as required, supplied with supports and the necessary hardware.	**04924**

Partitioning extension


06541



• For the Spacial SFP system switchboards 600 and 800 mm depth, a partitioning extension is required.

Characteristics	References
D600	**06541**
D800	**06543**

Front and rear barrier


06540



Characteristics	References
• Front protection is realized by the association of the door W300 and this barrier. Metallic barrier, composed of 2 parts H850, pre-cut at both ends. • Rear protection, a barrier is required at the rear of the busbar compartment in cubicles that are 800, 1000 and 1300 mm deep.	**06540**

Inter-cubicle partitioning


06555

• Metal partition, used to separate two adjacent cubicles.
• It is made up of two panels, each 850 mm high.
• The top and bottom ends have knock-outs for horizontal busbars.
• Supplied with the necessary supports and hardware, the partition is mounted on the framework and does not hinder installation of the functional mounting plates.



Characteristics	References
D500	**06555**
D600	**06555** + **06541**
D800	**06555** + **06543**

Partitioning of horizontal busbars

• Set of two barriers (front and rear), plus a slotted rear panel for efficient natural convection in the switchboard.
• The set can be used to partition horizontal busbars installed at the top or bottom of the cubicle.
• The space required for the busbars is not increased.


06560


06570

Characteristics	References
3M-busbar, W300, D500	**06560**
3M-busbar, W300, D600	**06561**
3M-busbar, W300, D800	**06563**
4M-busbar, W300, D500 or D600 or D800	**06568**
3M-busbar, W700, D500 or D600 or D800	**06570**
4M-busbar, W700, D500 or D600 or D800	**06567**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Form 3b partitioning

Separation of busbars from the functional units and separation of all functional units from one another.
Separation of the terminals for external conductors from the functional units, but not from each other.
- protection against contact with live parts
- reduction in the risk of faults between the functional units (propagation of electrical arcs, etc.).



Front connection

- A horizontal metal partition can be used to physically separat functional units from one another.


04901

Characteristics	References
Horizontal metal partition, W650 mm	**04901**

Front connection

- It is fixed at the rear by a support (two uprights) secured to the framework (500 mm deep) or to the intermediate uprights (800 mm deep frameworks).


04943

Characteristics	References
Rear support for partitions, W650 mm	**04943**



Front connection

- A set of brackets can be used to install partial Form 3 partitioning in the cubicle.
- It does not take up any useful space in the switchboard.

03583

Characteristics	References
6 universal angle brackets	**03583**



Rear connection

- Vertical partitions (two cat. no. per functional unit)


04955

Characteristics	References
3 to 4 modules	**04955**
5 to 6 modules	**04956**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Form 4 partitioning

Separation of busbars from the functional units and separation of all functional units from one another, including the terminals for external conductors which are an integral part of the functional unit.

- Protection against contacts with live parts and reduction in the risk of faults between the functional units (propagation of electrical arcs, etc.).
- Form 4a: Terminal for external conductors in the same compartment as the associated.
- Form 4b: Terminals for external conductors not in the same compartment as the associated functional unit, but in individual, separate, enclosed protected spaces or compartments.

Form 4a partition for front connection



- a backplate (one cat. no. per cubicle) made up to two metal half panels mounted on the rear supports for Form 3 partitions. This backplate is not indispensable for 500 mm deep frameworks.

Characteristics	References
Form 4a backplate (one cat. no. per cubicle)	**04946**



04946

Form 4a gland plate



- a plastic gland plate that can be easily cut out (one for each functional unit) and is mounted on the framework.

Characteristics	References
3 or 4 modules	**04951**
5 or 6 modules	**04952**



04951

Form 4b partition



- a cover with metallic gland plates that can be easily cut out on the side and bottom. It is available in two heights:

Characteristics	References
3 to 5 modules	**06600**
4 to 6 modules	**06601**



06600

Connection transfer assembly,3 to 5 modules, 250 A

- transfert assembly without connection to simplyfied the cable installation.

Characteristics	References
3P	**06606**
4P	**06607**



06606

Connection transfer assembly, 4 to 6 modules, 630 A

- transfert assembly without connection to simplyfied the cable installation.

Characteristics	References
3P	**06604**
4P	**06605**



06604

11

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Prisma functional system Selection guide

Common characteristics

- Roof characteristics:
  - equipped with a factory-mounted polyurethane (PUR) gasket
  - supplied with mounting hardware
  - with markings for clear identification of cable-running zones
- The cables compartment can be mounted on the right or left.
- Can be combined side-by-side or back-to-back.
- Receive the IP55 cover panels.

Mounting	W700			W300		
						
Depth	**D500**	**D600**	**D800**	**D500***	**D600**	**D800**
Assembled enclosures H2000 Plain door	**NSYSFP20750**	**NSYSFP20760**	**NSYSFP20780**	**NSYSF20350**	**NSYSF20360**	**NSYSF20380**
Assembled enclosures H2000 Glazed door	**NSYSFP20750T**	**NSYSFP20760T**	**NSYSFP20780T**	-	-	-
Adapter uprights for busbar installation in vertical on Linergy LGY	-	-	-	**NSYSFPA**	**NSYSFPA + NSYSUCR40200**	**NSYSFPA + NSYSUCR40200**
Side panel (Set of 2)** 	**NSY2SP205**	**NSY2SP206**	**NSY2SP208**	**NSY2SP205**	**NSY2SP206**	**NSY2SP208**
Hinged front plate support frame*** 	**08566**	**08566**	**08566**	-	-	-

* For cables and to install Linergy LGYE, BS busbar.
** An earthing braid must be installed between the lateral panels and the frame.
*** Reversible for left or right-hand opening.

Accessories

Width			W700			W300		
Depth			**D500**	**D600**	**D800**	**D500**	**D600**	**D800**
	Plinth H100*	Front and rear cross-pieces	**NSYSPF7100**	**NSYSPF7100**	**NSYSPF7100**	**NSYSPF3100**	**NSYSPF3100**	**NSYSPF3100**
		Lateral cross-pieces	**NSYSPS5100**	**NSYSPS6100**	**NSYSPS8100**	**NSYSPS5100**	**NSYSPS6100**	**NSYSPS8100**
	Plinth H200*	Front and rear cross-pieces	**NSYSPF7200**	**NSYSPF7200**	**NSYSPF7200**	**NSYSPF3200**	**NSYSPF3200**	**NSYSPF3200**
		Lateral cross-pieces	**NSYSPS5200**	**NSYSPS6200**	**NSYSPS8200**	**NSYSPS5200**	**NSYSPS6200**	**NSYSPS8200**
	1 entrie gland-plates		**NSYEC751**	**NSYEC761**	**NSYEC781**	**NSYEC351**	**NSYEC651**	**NSYEC381**

* The plinth is made up of two catalogue numbers: Front and rear cross-pieces + lateral cross-pieces.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Coupling kit

- side-by-side combination
- back-to-back combination: - D500+D500, D800+D500
- Back to back association must be shipped individually and combined during on-site installation


NSYSFBK19

Characteristics	References
Spacial SF coupling kit for SF enclosures equipped with swinging 19" rack, IP55	**NSYSFBK19**

4 lifting rings

- Use a set of lifting rings for each framework for one framework (W700 mm) containing devices

NSYSFEB

Characteristics	References
Spacial SF M12 lifting eyebolt, galvanized cast steel	**NSYSFEB**

4 lifting brackets

- When two cubicles with devices have been combined, use a lifting beam.


NSYSFELB

Characteristics	References
Set of 4 Spacial SF lifting bracket, zinc coated steel	**NSYSFELB**

Set of 20 screws + M6 nuts

06461

Characteristics	References
20 Screws et nuts M6	**06461**

Earthing wire, 6 mm²

The wire is equipped with a 4 mm diameter lug at one end and a 6 mm diameter lug on the other.
The earthing wire is used to earth:

- a door or wicket door with devices
- a front-plate support frame equipped with switchgear in a cubicle.

08911

Characteristics	References
Earthing Wire 6 mm	**08911**

Earthing braid

- An earthing braid must be installed between the roof and the frame.
- For NSYEL166D8: Length 160 mm, Section 6 mm², Terminal 8.3 mm.
- For NSYEL3525D8: Length 350 mm, Section 25 mm², Terminal 8.3 mm.

NSYEL166D8

Characteristics	References
Earth leads section 6 mm², length 160 mm	**NSYEL166D8**
Earth leads section 25 mm², length 350 mm	**NSYEL3525D8**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Seismic application 3G withstand

Note:
incoming by pre-frabricated bus-bar truncking is forbidden for seismic application.

Seismic plinth H100 mm

1600 A configuration *	Height (mm)	Width (mm)	Depth (mm)	References
Spacial SFP	2000	700	350	**NSYS5GPC75**
Busbar duct	2000	300	350	**NSYS5GPC35**
configuration 3200 A	Height (mm)	Width (mm)	Depth (mm)	References
Spacial SFP	2000	700	450	**NSYS5GPC78**
Busbar duct	2000	800	450	**NSYS5GPC38**

* Not compatible for depth 600 mm.

Ground fastening

Front connection
(example: Device cubicle W700 mm + compartment W300 mm)



Rear connection D1000
(example: Device cubicle + compartment D500 + D500 mm)



Rear connection D1300
(example: Device cubicle + compartment D800 + D500 mm)



● compulsory fixing point
● optional fixing point

8.8-class screws: Screw M10 TH
+ washers (external Ø 25 mm, thickness 3 mm)
+ CS contact washers Ø 10 mm.

11

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Prisma functional system Dimensions

Cubicles

Profile



Cover panels, plain or transparent door, lateral panel



Standard plinth



Gland plates

W300



W700



Functional system in Spacial SFP switchboards, cubicle mounting

D500, D600, D800



Ground fastening, Busbars mounting, Lateral vertical busbars

1600 A



2000 A



2500 A



3200 A



11

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Compartmentalised enclosure for Motor Control Centres

SFM

Fixed compartmentalised swithchboards for Motor Control Centres

The Spacial SFM compartmentalised functional fixed system can be used for motor control centres in industrial environments (IP54).
It has been tested taking into account device characteristics.
This ensures a high degree of reliability in system operation and optimum safety.
Devices can be mounted on universal mounting plates on a workcut-out to simplify installation in the switchboard.

Fixed functional system for Motor Control

The fixed functional system for Motor Control Centres is designed for installation of motor starters up to 250 kW.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Motor protection

In addition to the motor power and the starter type (direct, reversing, star-delta…), 4 main criteria have to be taken into account when choosing a motor starter:
- the operational voltage,
- the type of thermal protection, electro-mechanical or electronical,
- the type of magnetic protection, according to the switchboard's Isc,
- the type of installation, according to the required availability level.

Operational voltage

Network's operational voltage is a decisive parameter in the choice of motor protection. Indeed, the operational voltage will have an impact on the device's performances and the installation constraints.
For instance, the voltage will influence:
- the breaking performances,
- the safety areas.

Isolation capacity



Lifetime





Motor protection

Protecting the motors to extend their lifetime
- Overheating in electrical motors is caused by copper and ferro-magnetic losses:
  - the current I is proportional to the motor's load. Copper losses are proportional to I² (stator and rotor),
  - hysteresis cycles in ferro-magnetic materials and the induced Foucault currents cause overheating, which is in particular proportional to frequency.
- The consequence of abnormal overheatings is a reduced isolation capacity of the materials, thus leading to a significant shortening of the motor lifetime, as shown in the opposite diagram.
- In continuous or semi-continuous processes, availability is a major issue. It is therefore decisive to observe accurately the operating conditions of the motors.
- Motor protection relays are the components dedicated to this task. They provide various levels of accuracy and functionalities, in order to meet the expectations of the process manager.

Supervising finely the motors to improve process availability
- An electrical motor transforms electrical energy in mechanical energy. When the voltage, current and frequency change, the speed and torque of the motor change too. And conversely, any changes in charge have a direct impact on the electrical parameters.
- Electromechanical thermal relays protect the motor against overloads.
- Electronical relays protect the motor against overloads, on the basis of very sophisticated and highly accurate thermal patterns.
  - These relays are able to make out several cases of motor overload, and to transmit the information, thus allowing the operator to have a better understanding of the true nature of the problem,
  - These relays report for many complementary parameters, providing useful informations to the operator, therefore giving him the opportunity to avoid motor stops, or to re-start quickly if a stop has occurred.

Examples:
- motor under-load can be the signal of a pump cavitation,
- phase inversion can be the indication of a maintenance error, that should be hard to diagnose without that sign.
  - In addition to the observation of currents, the electronical relays can monitor the voltage, and consequently the power and the power factor. They can also watch the leakage currents and measure the actual coil temperature whenever it has a built-in sensor. All these informations give an additional level of anticipation and shrewdness to help coping with problems.
  - Finally, electronical relays can take on information-processing functions, like state and faults statistics. They are also able to suggest logical solutions, and to react in a process-specific way.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Motor protection

Magnetic protection: Circuit-breakers and fuses

Schneider Electric have chosen to put forward circuit-breakers each time it is possible, as they have advantages in terms of maintenance and capacity of quick re-operating.

The advantages of magnetic circuit breakers over fuses are listed below:

- universal solution that can be exported to all countries, unlike the fuses, which standards are not coordinated,
- reduced dimensions,
- limited temperature rise,
- faster maintenance,
- no risk of over-rating the fuse cartridge (causing the motor destruction) or underrating (untimely tripping).

Spacial SFM: A combination for control motor starter



Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Life Is On Schneider Electric

Coordination

Type 1 coordination



Type 2 coordination



Total coordination



Coordination, what is it about?

A "motor starter" can be made up of 1, 2, or 3 different devices. They have to be coordinated in a way they ensure an optimal operation of the installation.

Aims of coordination

In case of a fault, the coordination's purposes are:

- to protect of the people and the equipment,
- to permit continuity of service,
- to reduce maintenance costs (manpower and replacement equipment).

Types of coordination as per IEC 60947-4-1

- Type 1 coordination: Basic solution
  - no continuity of service,
  - important maintenance costs in case of a fault (manpower and equipment).
- Type 2 coordination: Solution ensuring continuity of service
  - reduced machine shutdown time,
  - reduced cost of replacement equipment.
- Total coordination: Withdrawable solutions as per IEC 60947-6-2:
  - no damage nor resetting of devices following a fault,
  - installation immediate return to operation.

Schneider Electric's choice as regards coordination

For applications in Spacial SFM high availability switchboard, Schneider Electric has accepted:

> type 2 coordination on grounds of:

- a low cost for repairing the equipment,
- a reduced machine shutdown time,

and dismissed:

> type 1 coordination and non-coordoned feeders because of:

- an expensive return to operation,
- a long machine shutdown time.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Motor starter solutions

2-component motor starter

Thermomagnetic circuit-breaker + contactor

Advantages

- Very economic solutions.
- Suitable for all types of diagrams.
- Manual reset following a thermal fault.
- Type 2 coordination.

Applications

- Manufacturing and continuous and semi-continuous processes.

3-component motor starter

Advantages

- Wide choice of solutions.
- Suitable for all types of diagrams.
- Manual or automatic reset following a thermal fault.
- 2 starting classes (10 and 20).
- Type 2 coordination.
- Segregation of thermal and magnetic faults.

Magnetic circuit-breaker + contactor + thermal protection

- For manufacturing and continuous and semi-continuous processes.

Switch-disconnector fuse + contactor + thermal protection

- For all types of machines.
- For manufacturing and continuous and semi-continuous processes.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Presentation

The Spacial SFM compartmentalised enclosures system used for MCC are based on the Spacial SF range.
They offer the same functions:

- Different possible configurations, combined side-by-side or back-to-back.
- The built-in partial doors and panels design allow to meet the required degree of protection.

And the same advantages:

- Save time through all assembly phases.
- Enclosure robustness.

Modularity and Versatility

They offer 36 vertical modules, each 50 mm high, of useful space.
They have 4 different enclosure dimensions and 2 additional chambers for distribution busbars or cabling management. They can also be coupled with Spacial SFP for power distribution switchboards.

The functional system

A metal structure

The switchboard is made up of one or more frameworks combined side-by-side or back-to-back, on which a complete selection of cover panels and partial doors can be mounted.
They are used to build IP54 configurations and see ClimaSys offer options for ventilation.
Electrical continuity is achieved using earthing braids.
Plain partial doors are reversible for quick left or right-hand mounting by a single person, 120° opening.
The robustness of the locking system allows naturally the good alingment of the assembly. From 1 to 4 locking points system with 5 mm double bar insert as standard supply with possibility to replace it by other shape insert.

A distribution system

Vertical busbars positioned in a lateral compartment and horizontal busbars are used to distribute electricity throughout the switchboard.

Complete functional units

The functional unit need to be composed by:

- motor control and protection devices,
- a dedicated plain mounting plate for device installation,
- up to form 4b thanks to the gland boxes for the terminal isolation on the back of the switchboard or on the side of the cabling chamber,
- devices for on-site connections.

The functional units are modular and designed for installation one on top of another. The system includes everything required for functional unit mounting, supply and onsite connection. The components of the Spacial SFM compartmentalised system and those of the functional units in particular have been designed and tested taking into account device characteristics. This design approach ensures a high degree of reliability in system operation and optimum safety for personnel. Electrical switchboards built using Schneider Electric recommendations fully comply with international standard IEC 61439-2 and IEC 62208.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Withstand to the most demanding environements

- IP54 degree of protection for the dusty and/or damp industrial environments.
- Seismic withstand.
- Optional forced ventilation for environments with ambient temperatures hotter than 45°C or for devices sith considerable heat loss (see ClimaSys offer options).

Type tested

Spacial SFM compartmentalised is totally type-tested in accordance with IEC 61439-2.

- Certified by independant lab.
- As well as by a permanent control in Schneider Electric test laboratories.

Type-tests are carried out:

- temperature-rise limit,
- dielectric properties,
- short-circuit withstand,
- effectiveness of the protective circuit,
- conformity of the clearance and creepage distances,
- mechanical operation,
- degree of protection.

Partitioning

Partitioning is essential to ensure the utmost protection of the installation and personnel carrying out work in the switchboard.
Used in conjunction with the standard protection (terminal shields, factory-built connections), partitioning prevents any direct contact with live parts.

Form 2b



- Terminals for external conductors separated from busbars.
- The functional units and the terminals are separated from the busbars.

Form 3b



Separation of busbars from the functional units and separation of all functional units from one another. Separation of the terminals for external conductors from the functional units, but not from each other.

- Protection against contact with live parts.
- Reduction in the risk of faults between the functional units (propagation of electrical arcs, etc.).

Form 4a



Terminals for external conductors in the same compartment as the associated functional unit.

Form 4b



Terminals for external conductors not in the same compartment as the associated functional unit, but in individual, separate, enclosed protected spaces or compartments.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Fix enclosures

General data	
Applications	MCC
Standards	IEC 61439-2
Internal	No
Seismic	3G
Installation	Indoor

Mechanical data	
Cable inlet	Top / Bottom
Access	Front / Rear Side
IP	54
IK	10
Form	4b type 7
Withdrability	FFF
Dimensions	H 2000 / W 600 and 800 / D 600 and 800
Color	RAL 7035 grey

Electrical data	
Insulation voltage (Ui)	1000 V
Voltage rating(Ue)	415 V
Coordination	Type 2
Frequency	50/60 Hz
Auxiliary circuit voltage	230 V
Degree of pollution	3
Rated current (IP>31)	2500 A (with Copper and Linergy)
Short circuit (I_{cw} - 1s)	85 kA

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Mounting plates for fixed MCC switchboards

Motor control functional units

The plain mounting plates can be used to install all the devices making up an MCC motor starter on a single support.

Easy installation

Motor feeders can be prepared on a bench making the cut-outs needed. The quick fixing system allows to hold the mounting plate during device installation and wiring. The mounting plate can be fixed on the side partitions in adjustable depth with a pitch of 50 mm.

Switchboard upgradeability

- Functional units with form partitioning 3b and 4b.
- Sides and Rear accessibility.
- Separation panels with pre-cuts for cable glands ref. **01215**.

Functional unit reliability

- 3 to 24 module (150 to 1200 mm) mounting plates are installed in 600 and 800 mm wide cubicles.
- Capacity of Spacial SFM cubicles: 36 modules (50 mm each).
- Cables are run in dedicated 300 or 400 mm wide lateral compartments.



Plain mounting plates

Dimension of the compartment				
Number of modules	Height (mm)	Width (mm)	Mounting plate	Fixing kit
3M	150	600	**NSYMP3M6**	**NSYMPFIX**
3M	150	800	**NSYMP3M8**	
4M	200	600	**NSYMP4M6**	
4M	200	800	**NSYMP4M8**	
5M	250	600	**NSYMP5M6**	
5M	250	800	**NSYMP5M8**	
6M	300	600	**NSYMP6M6**	
6M	300	800	**NSYMP6M8**	
8M	400	600	**NSYMP8M6**	
8M	400	800	**NSYMP8M8**	
9M	450	600	**NSYMP9M6**	
9M	450	800	**NSYMP9M8**	
12M	600	600	**NSYMP12M6**	
12M	600	800	**NSYMP12M8**	
16M	800	600	**NSYMP16M6**	
16M	800	800	**NSYMP16M8**	
18M	900	600	**NSYMP18M6**	
18M	900	800	**NSYMP18M8**	
20M	1000	600	**NSYMP20M6**	
20M	1000	800	**NSYMP20M8**	
24M	1200	600	**NSYMP24M6**	
24M	1200	800	**NSYMP24M8**	

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

2-component motor starter

2-component motor starter Direct on line and reversing GV2, GV3 and GV7

Selection of recommended combinations

GV2							
Iq (kA)		Motor characteristics		Motor starter solution		Mounting plate Number of modules (1M = 50 mm)	
Without limiter	With GV1L3	P_{max} (kW)	I_{max} (A)	Circuit breaker	Contactor (1)	DOL	Reversing
85	-	0.18	0.6	GV2-P04	LC1D09	3M	3M
85	-	0.25	0.9	GV2-P05	LC1D09	3M	3M
85	-	0.37	1.1	GV2-P06	LC1D09	3M	3M
85	-	0.55	1.5	GV2-P06	LC1D09	3M	3M
85	-	0.75	1.8	GV2-P07	LC1D09	3M	3M
85	-	1.1	2.6	GV2-P08	LC1D09	3M	3M
85	-	1.5	3.4	GV2-P08	LC1D09	3M	3M
85	-	2.2	4.8	GV2-P10	LC1D09	3M	3M
85	-	3	6.5	GV2-P14	LC1D09	3M	3M
85	-	4	8.2	GV2-P14	LC1D18	3M	3M
50	85	5.5	11	GV2-P16	LC1D25	3M	3M
50	85	7.5	14	GV2-P20	LC1D25	3M	3M
50	85	10	19	GV2-P21	LC1D32	3M	3M
50	85	11	21	GV2-P22	LC1D32	3M	3M
50	85	15	28	GV2-P32	LC1D32	3M	3M
50	-	18.5	34	GV3-P40	LC1D50A	3M	4M
50	-	22	40	GV3-P50	LC1D50A	3M	4M
50	-	30	55	GV3-P65	LC1D65	3M	4M
70	-	15	28	GV7-RS40	LC1D40	3M	6M
70	-	18.5	34	GV7-RS40	LC1D50	3M	6M
70	-	22	40	GV7-RS50	LC1D80	3M	6M
70	-	30	55	GV7-RS80	LC1D80	3M	6M
70	-	37	66	GV7-RS80	LC1D80	3M	6M
70	-	45	80	GV7-RS100	LC1D115	4M	9M
70	-	55	100	GV7-RS150	LC1D150	6M	9M
70	-	75	135	GV7-RS150	LC1F185	9M	12M
70	-	90	160	GV7-RS220	LC1F225	9M	12M
70	-	110	200	GV7-RS220	LC1F265	9M	12M

(1) 2xLC1-D for reversing

Plain mounting plates

Dimension of the compartment			Mounting plate	Fixing kit
Number of modules	Height (mm)	Width (mm)	References	References
3M	150	600	**NSYMP3M6**	**NSYMPFIX**
3M	150	800	**NSYMP3M8**	
4M	200	600	**NSYMP4M6**	
4M	200	800	**NSYMP4M8**	
6M	300	600	**NSYMP6M6**	
6M	300	800	**NSYMP6M8**	
9M	450	600	**NSYMP9M6**	
9M	450	800	**NSYMP9M8**	
12M	600	600	**NSYMP12M6**	
12M	600	800	**NSYMP12M8**	

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

3-component motor starter

3-component motor starter Direct on line and reversing GV2 and GV3

Ue	IP	Ambiant temperature
415 V	≤ IP54	35°C

Selection of recommended combinations

Iq (kA)		Motor characteristics		Motor starter solution			Mounting plate Number of modules (1M = 50 mm)	
Without limiter	With LA9LB920	P_{max} (kW)	I_{max} (A)	Circuit breaker	Contactor (1)	Thermal relay	DOL	Reversing
85	-	0.18	0.6	GV2-L04	LC1D09	LRD04	3M	3M
85	-	0.25	0.9	GV2-L05	LC1D09	LRD05	3M	3M
85	-	0.37	1.1	GV2-L06	LC1D09	LRD06	3M	3M
85	-	0.55	1.5	GV2-L06	LC1D09	LRD06	3M	3M
85	-	0.75	1.8	GV2-L07	LC1D09	LRD07	3M	3M
85	-	1.1	2.6	GV2-L08	LC1D09	LRD08	3M	3M
85	-	1.5	3.4	GV2-L08	LC1D09	LRD08	3M	3M
85	-	2.2	4.8	GV2-L10	LC1D09	LRD10	3M	3M
85	-	3	6.5	GV2-L14	LC1D09	LRD12	3M	3M
85	-	4	8.2	GV2-L14	LC1D18	LRD14	3M	3M
50	85	5.5	11	GV2-L16	LC1D25	LRD16	3M	3M
50	85	7.5	14	GV2-L20	LC1D25	LRD21	3M	3M
50	85	10	19	GV2-L21	LC1D32	LRD22	3M	3M
50	85	11	21	GV2-L22	LC1D32	LRD22	3M	3M
50	85	13	24	GV2-L32	LC1D32	LRD32	3M	3M
50	-	18.5	34	GV3-L40	LC1D50A	LRD340	3M	4M
50	-	22	40	GV3-L50	LC1D50A	LRD350	3M	4M
50	-	26	49	GV3-L65	LC1D65A	LRD365	3M	4M

(1) 2xLC1-D for reversing

Selection of the mounting plate

Dimension of the compartment			Mounting plate	Fixing kit
Number of modules	Height (mm)	Width (mm)	References	References
3M	150	600	**NSYMP3M6**	**NSYMPFIX**
3M	150	800	**NSYMP3M8**	
4M	200	600	**NSYMP4M6**	
4M	200	800	**NSYMP4M8**	

11

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

3-component motor starter

3-component motor starter Direct on line and reversing NS80H and NSX

Ue	IP	Ambiant temperature
415 V	≤ IP54	35°C

Selection of recommended combinations

Iq (kA)	Motor characteristics		Motor starter solution			Mounting plate Number of modules (1M = 50 mm)	
	P_{max} (kW)	I_{max} (A)	Circuit breaker	Contactor (1)	Thermal relay	DOL	Reversing
70	18.5	34	NS80H-MA	LC1D50	LRD3355	3M	6M
70	22	40	NS80H-MA	LC1D50	LRD3357	3M	6M
70	30	55	NS80H-MA	LC1D65	LRD3359	3M	6M
70	37	66	NS80H-MA	LC1D80	LRD3363	3M	6M
NSX...F = 36 kA NSX...N = 50 kA NSX...H = 70 kA NSX...S = 85 kA NSX400L = 150 kA NSX630L = 150 kA	18.5	34	NSX100 MA	LC1D80	LRD3355	3M	6M
	22	40	NSX100 MA	LC1D80	LRD3357	3M	6M
	30	55	NSX100 MA	LC1D80	LRD3359	3M	6M
	37	64	NSX100 MA	LC1D80	LRD3363	3M	6M
	45	80	NSX100 MA	LC1D115	LR9D5367	6M	9M
	55	100	NSX160 MA	LC1D150	LR9D5369	6M	9M
	75	135	NSX160 MA	LC1F185	LR9F5369	9M	12M
	90	160	NSX250 MA	LC1F225	LR9F5371	9M	12M
	100	187	NSX250 MA	LC1F265	LR9F5371	9M	12M
	132	230	NSX400 1.3-M	LC1F330	LR9F7375	12M	16M
	160	270	NSX400 1.3-M	LC1F330	LR9F7375	12M	16M
	200	361	NSX630 1.3-M	LC1F500	LR9F7379	16M	16M
	220	380	NSX630 1.3-M	LC1F500	LR9F7379	16M	16M
	250	430	NSX630 1.3-M	LC1F500	LR9F7379	16M	16M

(1) 2xLC1-D for reversing

Selection of the mounting plate

Dimension of the compartment			Mounting plate	Fixing kit
Number of modules	Height (mm)	Width (mm)	References	References
3M	150	600	**NSYMP3M6**	**NSYMPFIX**
3M	150	800	**NSYMP3M8**	
6M	300	600	**NSYMP6M6**	
6M	300	800	**NSYMP6M8**	
9M	450	600	**NSYMP9M6**	
9M	450	800	**NSYMP9M8**	
12M	600	600	**NSYMP12M6**	
12M	600	800	**NSYMP12M8**	
16M	800	600	**NSYMP16M6**	
16M	800	800	**NSYMP16M8**	

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

3-component motor starter

2-component motor starter Star-delta GV2, GV3 and GV7

Ue	IP	Ambiant temperature
415 V	≤ IP54	35°C

Selection of recommended combinations

Iq (kA)		Motor characteristics		Motor starter solution		Mounting plate Number of modules (1M = 50 mm)
Without limiter	With GV1L3	P_{max} (kW)	I_{max} (A)	Circuit breaker	Contactor	Star-delta
85	-	0,37	1,1	GV2-P06	3xLC1D09	4M
85	-	0,55	1,5	GV2-P06	3xLC1D09	4M
85	-	0,75	1,8	GV2-P07	3xLC1D09	4M
85	-	1,1	2,6	GV2-P08	3xLC1D09	4M
85	-	1,5	3,4	GV2-P08	3xLC1D09	3M
85	-	2,2	4,8	GV2-P10	3xLC1D18	4M
85	-	3	6,5	GV2-P14	3xLC1D18	3M
85	-	4	8,2	GV2-P14	3xLC1D18	4M
50	85	5,5	11	GV2-P16	3xLC1D25	4M
50	85	7,5	14	GV2-P20	3xLC1D25	4M
50	85	10	19	GV2-P21	3xLC1D32	5M
50	85	11	21	GV2-P22	3xLC1D32	4M
35	85	15	28	GV2-P32	3xLC1D32	4M
50	-	18,5	34	GV3-P40	3xLC1D50A	5M
50	-	22	40	GV3-P50	3xLC1D50A	5M
50	-	30	55	GV3-P65	3xLC1D65A	5M
70	-	15	28	GV7-RS40	3xLC1D80	9M
70	-	18,5	34	GV7-RS40	3xLC1D50	9M
70	-	22	40	GV7-RS50	3xLC1D80	9M
70	-	30	55	GV7-RS80	3xLC1D80	9M
70	-	45	80	GV7-RS100	3xLC1D115	12M
70	-	55	100	GV7-RS150	3xLC1D150	12M
70	-	75	135	GV7-RS150	3xLC1F185	16M
70	-	90	160	GV7-RS220	3xLC1F225	16M
70	-	110	200	GV7-RS220	3xLC1F265	16M

Selection of the mounting plate

Dimension of the compartment			Mounting plate	Fixing kit
Number of modules	Height (mm)	Width (mm)	References	References
3M	150	600	**NSYMP3M6**	**NSYMPFIX**
3M	150	800	**NSYMP3M8**	
4M	200	600	**NSYMP4M6**	
4M	200	800	**NSYMP4M8**	
5M	250	600	**NSYMP5M6**	
5M	250	800	**NSYMP5M8**	
9M	450	600	**NSYMP9M6**	
9M	450	800	**NSYMP9M8**	
12M	600	600	**NSYMP12M6**	
12M	600	800	**NSYMP12M8**	
16M	800	600	**NSYMP16M6**	
16M	800	800	**NSYMP16M8**	

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

3-component motor starter

3-component motor starter Star-delta GV2 and GV3

Ue	IP	Ambiant temperature
415 V	≤ IP54	35°C

Selection of recommended combinations

Iq (kA)		Motor characteristics		Motor starter solution			Mounting plate Number of modules (1M = 50 mm)
Without limiter	With LA9LB920	P_{max} (kW)	I_{max} (A)	Circuit breaker	Contactor	Thermal relay	Star-delta
85	-	0,37	1,1	GV2-L06	3xLC1D09	LRD06	4M
85	-	0,55	1,5	GV2-L06	3xLC1D09	LRD06	4M
85	-	0,75	1,8	GV2-L07	3xLC1D09	LRD07	4M
85	-	1,1	2,6	GV2-L08	3xLC1D09	LRD08	4M
85	-	1,5	3,4	GV2-L08	3xLC1D09	LRD08	4M
85	-	2,2	4,8	GV2-L10	3xLC1D18	LRD10	4M
85	-	3	6,5	GV2-L14	3xLC1D18	LRD12	4M
85	-	4	8,2	GV2-L14	3xLC1D18	LRD14	4M
50	85	5,5	11	GV2-L16	3xLC1D25	LRD16	4M
50	85	7,5	14	GV2-L20	3xLC1D25	LRD21	4M
50	85	10	19	GV2-L21	3xLC1D32	LRD22	4M
50	85	11	21	GV2-L22	3xLC1D32	LRD22	4M
35	85	15	24	GV2-L32	3xLC1D32	LRD32	4M
50	-	18,5	34	GV3-L40	3xLC1D50A	LRD340	5M
50	-	22	40	GV3-L50	3xLC1D50A	LRD350	5M
50	-	30	49	GV3-L65	3xLC1D65A	LRD365	5M

Selection of the mounting plate

Dimension of the compartment			Mounting plate	Fixing kit
Number of modules	Height (mm)	Width (mm)	References	References
4M	200	600	**NSYMP4M6**	**NSYMPFIX**
4M	200	800	**NSYMP4M8**	
5M	250	600	**NSYMP5M6**	
5M	250	800	**NSYMP5M8**	

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

3-component motor starter

3-component motor starter Star-delta NS80H and NSX

Ue	IP	Ambiant temperature
415 V	≤ IP54	35°C

Selection of recommended combinations

Iq (kA)	Motor characteristics		Motor starter solution			Mounting plate Number of modules (1M = 50 mm)
	P_{max} (kW)	I_{max} (A)	Circuit breaker	Contactor	Thermal relay	Star-delta
70	18.5	34	NS80H-MA	3xLC1D50	LRD3355	9M
70	22	40	NS80H-MA	3xLC1D50	LRD3357	9M
70	30	55	NS80H-MA	3xLC1D65	LRD3359	9M
70	37	66	NS80H-MA	3xLC1D80	LRD3363	9M
NSX...F = 36 kA NSX...N = 50 kA NSX...H = 70 kA NSX...S = 85 kA NSX400L = 150 kA NSX630L = 150 kA	18.5	34	NSX100 MA	3xLC1D80	LRD3355	9M
	22	40	NSX100 MA	3xLC1D80	LRD3357	9M
	30	55	NSX100 MA	3xLC1D80	LRD3359	9M
	37	64	NSX100 MA	3xLC1D80	LRD3363	9M
	45	80	NSX100 MA	3xLC1D115	LR9D5367	12M
	55	100	NSX160 MA	3xLC1D150	LR9D5369	12M
	75	135	NSX160 MA	3xLC1F185	LR9F5369	16M
	90	160	NSX250 MA	3xLC1F225	LR9F5371	16M
	110	187	NSX250 MA	3xLC1F265	LR9F5371	16M
	132	230	NSX400 1.3-M	3xLC1F330	LR9F7375	20M
	160	270	NSX400 1.3-M	3xLC1F330	LR9F7375	20M
	200	361	NSX630 1.3-M	3xLC1F500	LR9F7379	24M
	220	380	NSX630 1.3-M	3xLC1F500	LR9F7379	24M
	250	430	NSX630 1.3-M	3xLC1F500	LR9F7379	24M

Selection of the mounting plate

Dimension of the compartment			Mounting plate	Fixing kit
Number of modules	Height (mm)	Width (mm)	References	References
9M	450	600	**NSYMP9M6**	**NSYMPFIX**
9M	450	800	**NSYMP9M8**	
12M	600	600	**NSYMP12M6**	
12M	600	800	**NSYMP12M8**	
16M	800	600	**NSYMP16M6**	
16M	800	800	**NSYMP16M8**	
20M	1000	600	**NSYMP20M6**	
20M	1000	800	**NSYMP20M8**	
24M	1200	600	**NSYMP24M6**	
24M	1200	800	**NSYMP24M8**	

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Linergy LGYE-LGY
a breakthrough in busbar systems

Safe, reliable, flexible, and flexible with the highest level of performance

The Linergy LGYE-LGY busbar system now includes horizontal busbars, for greater electrical switchboard enclosure performance, reliability, and costeffectiveness.

Manufactured using a revolutionary process, patented Linergy busbars are unique on the market, taking your electrical switchboard installations a giant leap into the future.

Discover how Linergy LGYE-LGY can place the next generation of low-voltage switchboards in your hands.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Innovative technology from an energy expert you can trust

Patented Linergy LGYE-LGY is backed by Schneider Electric's decades of expertise in electrical distribution systems and is certified IEC 61439-2 compliant by ASEFA.



Linergy unique profile
was designed with the ratings you need, a commitment to performance backed by regular testing up to 4000 A.

Heat is dissipated by conduction
and radiation for performance only a market leader can bring you.



Linergy LGYE-LGY busbars
performances are identical or better than traditional all Linergy BS busbars.

Unlike tin-plated aluminum busbars, rugged Linergy LGYE-LGY
busbars are resistant to scratching during assembly to ensure optimal connection quality and reliability.

11

High Velocity Oxy-Fuel, unique on the busbar market
Patented Linergy LGYE-LGY uses a supersonic high-temperature coating process for a robust copper contact surface.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

A revolutionary design for greater efficiency

The Linergy line now includes horizontal busbars, helping you achieve better electrical switchboard performance while optimizing busbar layout and facilitating assembly.

Schneider ElectricTM has drawn upon 30 years of expertise in electrical distribution systems and a decade of hands-on experience with the proven and reliable Linergy line of products. It brings you a revolutionary design featuring a high-quality copper contact surface that delivers even better results than traditional Linergy BS-to-Linergy BS connections. Linergy LGYE-LGY busbars offer a number of benefits to help you enhance performance and boost your competitiveness.

Lightweight

Linergy is half the weight of equivalentrated Linergy BS bars for more fuel-efficient transport, easier handling, and smoother installation.

Higher-capacity

A single Linergy LGYE bar can withstand ratings up to 2500 A. It would take two or three Linergy BS bars per pole to achieve similar ratings.

Robust and flexible

Linergy LGYE bars are extruded for a unique profile that includes both closed and ribbed sections, improving rigidity, thermal dissipation, and resistance to short circuits, with a shortcircuit withstand capacity (I_{cw}) of 85 kA/1s for SFM and 100 kA / 1s for Spacial SFP.

> Linergy LGYE is 50% lighter than Linergy BS

Reduce costs and assembly times over Linergy BS busbars

Attractive

The revolutionary copper contact strips, anodized aluminum surface, and unique shapes give a modern appearance and a soft touch.

IEC standards-compliant

The latest standards were factored in from the early design stages to ensure that temperatures are kept below the IEC61439-2 standard requirements, for optimal performance regardless of the switchboard configuration.

Environmentally-friendly

Instead of increasingly-scarce copper, Linergy LGYE is made from 70% recycled raw materials offering the same performance as primary raw materials.

Cost-effective

Linergy LGYE-LGY helps you achieve cost savings now and provides protection against fluctuating copper prices in the future, plus all the advantages of a raw material that is easy to purchase and store.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Linergy accessories are also evolving!

Linergy LGYE is a full-featured busbar system that includes all the connections, screws, bolts, isolating supports, and other accessories you need for drill-free assembly.





Panel builders, we've thought of everything to make your life easier!

- Linergy LGYE-LGY busbars are lightweight, making them easy to transport and handle in the workshop.
- With Linergy LGYE-LGY, you can continue to use the familiar Spacial SFP busbar supports you already know for Linergy BS bars. There's no new system to learn.
- Linergy LGYE-LGY offers single bars for each rating, making handling during installation faster and more convenient.
- Linergy LGYE-LGY bars are fast and easy to position without drilling, thanks to a sliding bolt and track system.
- Linergy screws let you add extra outgoing connections without drilling new holes or dismounting previous connections or busbar supports, saving you time and giving you greater flexibility in the event of last-minute changes.
- Linergy LGYE-LGY busbars offer a unique shape with no sharp edges for safer, smoother handling and installation the bars simply slide right in to the busbar supports.
- Existing Linergy LGY vertical busbars are easy to connect to Linergy LGYE with ready-toinstall accessories like vertical connectors.
- Linergy materials are easy to recycle via well-established aluminum recycling services already in use for materials like aluminum cans, coffee capsules, door and window frames, and engine blocks.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Linergy also offers the most advanced busbar solutions while remaining simple.



Linergy LGYE / LGY /BS

Power busbars

- Solutions available up to 2500 A for Spacial SFM up to 4 000 A for Spacial SFP.
- Connection everywhere without drilling (with LGY and LGYE profile).

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Lateral Linergy busbars up to 1600 A

Busbar calculation

The following table indicates:

- the catalogue numbers of the bars to be used, depending on the permissible current level in the busbars,
- the number of supports required, depending on the rated short-time withstand current (I_{cw} in kA rms / 1 second).

Linergy busbars	Permissible current at 35 °C for switchboard		No. of supports I_{cw} (kA effrms / 1 s)								References
	IP ≤ 31	IP > 31	≤ 25	≤ 30	≤ 40	≤ 50	≤ 60	≤ 65	≤ 75	≤ 85	
Linergy 630	680	590	3								**04502**
Linergy 800	840	760	3	3							**04503**
Linergy 1000	1040	950	3	3	3						**04504**
Linergy 1250	1290	1170	3	3	3	4	5				**04505**
Linergy 1600	1650	1480	3	3	3	4	5	5	7	8	**04506**

Note: The permissible current values for the busbars are given for an ambient temperature of 35°C around the switchboard. The bottom support also maintains the bars in position. Each catalogue number represents one bar.

Busbar selection

Linergy busbars, L = 1670 mm

Cat. no. selection: See the table below.

Each bar is supplied with a stop for the bottom support.





Bar 630 A.
04502



Bar 800 A.
04503



Bar 1000 A.
04504



Bar 1250 A.
04505



Bar 1600 A.
04506

Busbars up to 1600 A.

The bottom support is used in wedging busbars in position.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Linergy LGY - Lateral profiles up to 1600 A

In Spacial SFP duct		W300				
Linergy profile, 1670 mm length		 **630 A**	 **800 A**	 **1000 A**	 **1250 A**	 **1600 A**
Permissible current for an ambient temp. of 35°C around the switchboard	IP ⩽ 31	680 A	840 A	1040 A	1290 A	1650 A
	IP > 31	590 A	760 A	950 A	1170 A	1480 A
Number of profiles per phase		1				
References		**04502**	**04503**	**04504**	**04505**	**04506**



The bottom wedge support is used to place the busbar and ensure it is in the correct position. It is count as a busbar support (included in the number of supports).

Fixed support **04651**

Note:
An end stop must be fitted on the bottom support: **01109** (sold in lots of 12)

Number depending on I_{cw} (kA rms/1 s)	⩽ 25	3				
	⩽ 30	-	3			
	⩽ 40	-		3		
	⩽ 50	-			4	
	⩽60	-			5	
	⩽ 65	-				5
	⩽ 75	-				7
Only for depth cubicle ⩾ 500 mm	⩽ 85	-				8
References		**04651** (set of 2 upright adapters **NSYSFPA** and set of 2 40 mm universal cross rail **NSYSUCR40200** for installation in Spacial SF busbar chamber)				

Connections to the Linergy BS horizontal busbar



Note:
Supplied with mounting hardware.
Reference include 1 connection only.
Order 1 connection per phase.

References according to horizontal busbar size	5 mm thick	**04634**	**04635**
	10 mm thick, width ⩽ 80 mm	**04636**	

Connections to the Linergy LGYE horizontal busbar



Note:
Supplied with mounting hardware.
Reference include 1 connection only.
Order 1 connection per phase.

References (vertical connection)	**04602**
References (vertical shifted connection)	**04603**

11

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Linergy LGYE - Horizontal profiles up to 2500 A

Note:
For accessories, see page 409.

Installation in Spacial SFM compartmentalised			Up to 1600 A					Up to 2500 A	
Linergy profile, 2000 mm length									
			630 A	**800 A**	**1000 A**	**1250 A**	**1600 A**	**2000 A**	**2500 A**
Permissible current for an ambient temp. of 35°C around the switchboard			530 A	680 A	850 A	1050 A	1480 A	1650 A	2100 A
Number of profiles per phase			1						
Total number of vertical modules (50 mm)			3					3	
References			**04560**	**04561**	**04562**	**04563**	**04564**	**04565**	**04566**
Busbar supports			 Fixed support		 Free support				
			2 fixed supports for Spacial SF wide cublicle are compulsory according compartment depth (400 or 500 mm). 1 fixed support for Spacial SF 300/400 wide chamber are compulsory. Fixed directly on framework. If more supports are needed, add free supports.						
In cubicle SFM: W600/800 Busbar supports 75 mm distance between bars	**Number of supports depending on I_{cw} (kA rms/1 s)**	≤ 15	2						
		≤ 25	2						
		≤ 30	2						
		≤ 40	-	2					
		≤ 50	-		2				
		≤ 60	-			2+1		2	
		≤ 65	-				2+1		
		≤ 75	-				2+1		
		≤ 85	-				2+1		
References Fixed support		D400	**NSYMBHS4**						
References Fixed support		D500	**NSYMBHS5**						
References Free support			**NSYBSA**						
In busbar chamber SF: W300/400 Busbar supports 75 mm distance between bars	**Number of supports depending on I_{cw} (kA rms/1 s)**	≤ 15	1						
		≤ 25	1						
		≤ 30	1						
		≤ 40	-	1					
		≤ 50	-		1				
		≤ 60	-		1				
		≤ 65	-			1 + 1			
		≤ 75	-			1 + 1			
		≤ 85	-			1 + 1			
References Fixed support		D600	**NSYBHS600**					**NSYBHS600**	
References Fixed support		D800	**NSYBHS800**					**NSYBHS800**	
References Free support			**NSYBSA**					**NSYBSA**	
Joints			Up to 1600 A					Up to 2500 A	
			630 A	800 A	1000 A	1250 A	1600 A	2000 A	2500 A
			 **04620**					 **04621**	
References 3P			3x **04620**					3x **04621**	
References 4P			4x **04620**					4x **04621**	

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Linergy BS - Lateral flat busbars up to 2500 A

In Spacial SF busbar chamber		W300 D500/600/800, up to 1600 A				W300 D500/600/800, up to 2500 A					
Pre-slotted copper, 1675 mm length 											
Permissible current for an ambient temp. of 35°C around the switchboard	IP > 31	750 A	900 A	1250 A	1600 A	1080 A	1250 A	1600 A	1850 A	2000 A	2500 A
Busbar cross-section (mm)		60 x 5	80 x 5	60 x 5	80 x 5	50 x 10	60 x 10	80 x 10	50 x 10	60 x 10	80 x 10
Number of busbars per phase		1		2		1			2		
References		**04516**	**04518**	**04516**	**04518**	**04525**	**04526**	**04528**	**04525**	**04526**	**04528**
Busbar supports 		3 fixed supports are compulsory to hold the busbar in position. If more than 3 supports are needed, use free supports (in addition). The bottom wedge support is used to place the busbar and ensure it is in the correct position. It does not count as a busbar support.									
Number of supports depending on I_{cw} (kA rms/1 s)	≤ 15	3				3					
	≤ 25	3+2			3	3					
	≤ 30	3+2				3+2					3
	≤ 40	3+4		3+2		3+2					
	≤ 50		3+4			3+2					
	≤ 60					3+4					3+2
	≤ 65					3+4					3+2
	≤ 75						3+6		3+4		
	≤ 85									3+4	
References* Spacial SF busbar chamber 75 mm distance between bars	W300, D600	**NSYBVS600** (fixed) + **NSYBSA** (free) + **NSYAS600** (end stop support)									
	W300, D800	**NSYBVS800** (fixed) + **NSYBSA** (free) + **NSYAS800** (end stop support)									
		* References of supports depending on distance between bars and busbar chamber depth									
Connections to the Linergy BS horizontal busbar											
		For a busbar with 75 mm distance between bars, the bars must be completely covered. Staggered assembly points between one bar and the next, to maintain the necessary clearance distances.(1) 				References **04636**, **04637** are supplied individually: 1 connection per phase. Reference **04642** consists of 2 M8 x 140 screws which can replace the original M8 x 120 screws.					
		1 vertical bar per phase		2 vertical bars per phase		1 vertical bar per phase			2 vertical bars per phase		
		60 x 5	80 x 5	60 x 5	80 x 5	50 x 10	60 x 10	80 x 10	50 x 10	60 x 10	80 x 10
References*	≤ 80 mm	**04645**				**04636**		**04637**	**04637**		
		* References of the connection piece depending on horizontal busbar size									

(1) Drill hole dimensions for 5 mm thick horizontal busbars.



Drill hole dimensions for 10 mm thick horizontal busbars.



11

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Linergy BS - Horizontal flat busbars up to 2500 A

Note:
When installed at the bottom of a cubicle, the busbar must be partitioned.

Installation in Spacial SFM compartmentalised			Hasta 1600 A				Hasta 2500 A			
Copper bar, 2000 mm length										
Permissible current for an ambient temp. of 35°C around the switchboard			750 A	900 A	1250 A	1600 A	1600 A	1850 A	2000 A	2500 A
Busbar cross-section (mm)			60 x 5	80 x 5	60 x 5	80 x 5	80 x 10	50 x 10	60 x 10	80 x 10
Number of busbars per phase			1	1	2	2	1	2	2	2
Total number of vertical modules (50 mm)			3							
References			**04536**	**04538**	**04536**	**04538**	**04548**	**04545**	**04546**	**04548**
Busbar supports 			 Fixed support		 Free support					
			2 fixed supports for Spacial SF wide cublicle are compulsory according compartment depth (400 or 500 mm). 1 fixed support for Spacial SF 300/400 wide chamber are compulsory. Fixed directly on framework. If more supports are needed, add free supports.							
In cubicle SFM: W600/800 with 75 mm distance between bars	**Number of supports depending on I_{cw} (kA rms/1 s)**	≤ 15	2							
		≤ 25	2+1	2						
		≤ 30	2+1		2					
		≤ 40	2+1				2			
		≤ 50	-	2+1					2	
		≤ 60	-				2+1			
		≤ 65	-				2+1			
		≤ 75	-				2+2	2+1		
		≤ 85	-				-		2+1	
References Fixed support			**NSYMBHS4** (D400) or **NSYMBHS5** (D500)							
References Free support			**NSYBSA**							
In busbar chamber SF: W300/400 with 75 mm distance between bars	**Number depending on I_{cw} (kA rms/1 s)**	≤ 30	1							
		≤ 50	1+1				1			
		≤ 85	-				2			
References* Fixed support			**NSYBHS600** (D600) or **NSYBHS800** (D800)				**NSYBHS600** (D600) or **NSYBHS800** (D800)			
References* Free support			**NSYBSA**				**NSYBSA**			
			* References depending on depth							

Joints, Installation in Spacial SFP		Up to 1600 A				Up to 2500 A			
		1 vertical bar per phase		2 vertical bars per phase		1 vert. bar per phase	2 vertical bars per phase		
Busbar cross-section (mm)		60 x 5	80 x 5	60 x 5	80 x 5	80 x 10	50 x 10	60 x 10	80 x 10
Sliding joints with self-breaking lock nut		 **04640**			 **04641**				
References		**04640**	**04641**	**04640**	**04641**	**04641**	**04640**	**04640**	**04641**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Linergy LGYE - Accessories

Linergy screw

- Sold in lots of 20: 20 screws + 20 nuts + 20 contact washers, class 8.8. The screws slide into the profile and are then locked in the desired position.







Characteristics		AD	References
Steel plain washers	M8 sold in lots of 20	20 mm	**04772**
	M8 sold in lots of 20	24 mm	**04773**
	M8 sold in lots of 20	28 mm	**04774**
Brass plain washers	M8 sold in lots of 20 for connection of ≤ 25 mm² lugs to Linergy	20 mm	**04775**
Identification	12 clip-on supports + N, L1, L2, L3, PE, PEN labels		**04794**
	Linergy LGYE busbar screw plate kit after sales service		**01130**

M8 bolts


04782

- Set of 20 bolts + 20 nuts + 40 contact washers.

Characteristics	References
Linergy BS, 20 bolts 8.8 class, M8 x 20	**04782**
Linergy BS, 20 bolts 8.8 class, M8 x 25	**04783**
Linergy BS, 20 bolts 8.8 class, M8 x 30	**04784**
Linergy BS, 20 bolts 8.8 class, M8 x 35	**04785**
Linergy BS, 20 bolts 8.8 class, M8 x 40	**04786**
Linergy BS, 20 bolts 8.8 class, M8 x 45	**04787**
Linergy BS, 20 bolts 8.8 class, M8 x 50	**04788**

Torque nuts

04759

- Can be used to obtain the correct tightening torque (28 Nm) recommended by then manufacturer, without using a torque wrench. Torque nuts may be used for all electrical connections.

Characteristics	References
20 M8 torque nuts	**04759**

Voltage tap-offs


04229

- For small lugs (on low-current cables or measurement tap-offs), insert a conducting washer (ref. **04775**) between the busbar and the lug.

Characteristics	References
20 M10 voltage tap-offs for two 6.35 mm tab connectors	**04229**

Connections on Linergy LGYE and LGY


04766

04768

04769

Characteristics	I_nA	bar	Utilisation	References
Use the 25 mm Linergy screw	0 A to 630 A	Cable Insulated flexible bar	Recommended	**04766**
Use the 39 mm Linergy screw is only compatible with Linergy LGY.	0 A to 630 A	Cable Insulated flexible bar	Possible	**04767**
Use the 25 mm Linergy screw	800 A to 1250 A	5 mm thick bar	Recommended	**04766**
Use the 39 mm Linergy screw is only compatible with Linergy LGY.	800 A to 1250 A	5 mm thick bar	Possible	**04767**
Use the flat plate screw with 2 studs	800 A to 1250 A	5 mm thick bar	Possible	**04768**
Use the flat plate screw with 2 studs	1600 A to 2500 A	5 or 10 mm thick bar	Recommended	**04768**
Use the 39 mm Linergy screw is only compatible with Linergy LGY.	1600 A to 2500 A	5 or 10 mm thick bar	Possible	**04767**
Use the flat plate screw with 3 studs	3200 A to 4000 A	10 mm thick bar	Recommended	**04769**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Partitioning Form 2

Partitioning Form 2

Separation of busbars from the functional units:
- protection against contact with live parts upstream of the outgoing circuits,
- protection against penetration of foreign solid bodies.

Note:
when the busbars are at the bottom of the cubicle, gland plates are mandatory.

	Lateral partitioning	Rear partitioning
		
Diagrams		
		
Characteristics	• Set of 2 vertical metallic separation which guarantees good insulation of the sides of the compartment (IP2x). • Top and bottom ends have knock-outs for installation of horizontal busbars and pre-cuts of 40 x 70 mm for cable glands using grommets ref **01215** when Form 4b is required. • Partition extension required for D800 mm. • Direct fixing on structure of enclosure.	• Vertical metallic separation which guarantee good insulation of the back of the compartment (IP2x). • Pre-cuts of 40 x 70 mm for cable glands using grommets ref **01215** when Form 4b is required on back installation. • Direct fixing on structure of enclosure.
References	D600: **NSYMSC206** D800: **NSYMSC206** + **NSYMSC202** + **NSYSUCR40200**	W600: **NSYMBC206** W800: **NSYMBC208**

	Front and Rear busbar barrier	Horizontal busbar barriers	
			
Diagrams			
			
		W600 / **W800**	**W300** / W400
Characteristics	• Front protection is realized by the association of the door W300 and this barrier. Metallic barrier, composed of 2 parts H850, pre-cut at both ends • Rear protection is realized by the association of the back panel of the enclosure.	• Horizontal protection by the association of slotted front barrier and horizontal partition for efficient natural convection in the switchboard. • The set can be used to partition horizontal busbar at the top or bottom of the cubicle. • The space required for the busbars is not increased.	• Set of 2 slotted barriers (front and rear), plus horizontal panel to be used when busbars cross the cable chamber.
References	W300: **06540** W400: **NSYVPF2B4**	D600 (1): **NSYHPF2B3M64** D800 (1): **NSYHPF2B3M65** D600 (1): **NSYHPF2B3M84** D800 (1): **NSYHPF2B3M85**	D600: **06561** D800: **06563** D600: **NSYHPF2B3M4** D800: **NSYHPF2B3M4**

(1) For an enclosure with depth of 600 mm the compartment depth is 400 mm. For an enclosure with depth of 800 mm the compartment depth is 500 mm

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Partitioning Form 3

Accessorie for partitioning Form 2

	External claddings
	
Intermediate Crossbar	
Characteristics	• It is mounted between partial doors, guaranteeing good sealing. • To be used in the absence of the partition tray. • Direct fixing to the structure. • Available in 2 widths (mm).
Supply	• 2 crossbars with fixing elements
References	W600: **NSYMIC6** W800: **NSYMIC8**

Partitioning Form 3

Separation of busbars from the functional units and separation of all functional units from one another.
Separation of the terminals for external conductors from the functional units, but not from each other.

- protection against contact with live parts
- reduction in the risk of faults between the functional units (propagation of electrical arcs, etc.).

	Form 3 partitioning	
		
Horizontal partitioning	**W600**	**W800**
Characteristics	• A horizontal metal partition to separate functional units from one another and guarantees insulation of the compartments (IP2x). • It is fixed to the front uprights of the enclosure and the side partitions. • Quick fixing system with intermediate crossbar to ensure the degree of protection of the partial doors. • Order by multiples of 2 (2, 4, 6…).	
References	D600 (1): **NSYMTR64** D800 (1): **NSYMTR65**	D600 (1): **NSYMTR84** D800 (1): **NSYMTR85**

(1) For an enclosure with depth of 600 mm the compartment depth is 400 mm. For an enclosure with depth of 800 mm the compartment depth is 500 mm.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Partitioning Form 4

Partitioning Form 4

Separation of busbars from the functional units and separation of all functional units from one another, including the terminals for external conductors which are an integral part of the functional unit:

- Protection against contacts with live parts and reduction in the risk of faults between the functional units (propagation of electrical arcs, etc.).
- Form 4a: Terminal for external conductors in the same compartment as the associated.
- Form 4b: Terminals for external conductors not in the same compartment as the associated functional unit, but in individual, separate, enclosed protected spaces or compartments.

	Form 4b boxes					
						
Characteristics	• Metallic plain box composed by 2 parts that can be easily installed for side or rear connection to separate the terminals for external conductors of the functional unit. • Quick fixing system on the side or on the back partition. • Available in 6 heights:					
References	3M: **NSYBF4B3M**	4M: **NSYBF4B4M**	5M: **NSYBF4B5M**	6M: **NSYBF4B6M**	8M: **NSYBF4B8M**	9M: **NSYBF4B9M**

Rail support bracket

Telequick

SM | **SF** | **SD** | **SMX** | **SFX** | **SDX**

- Bracket for fixing rails at an angle of 45°.
- Material: Zinc-coated steel
- Spacial SF: Mounted on the structure and/or mounting plates
- Spacial SM: Mounted on the bottom mounting rail and/ or mounting plates

NSYFB45

Characteristics	References
Rail support bracket	**NSYFB45**

Other universal common accessories

	Mounting and Cable management acc.	
		
References	See on Universal Enclosure catalogue	

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Selection of Spacial enclosures

Common characteristics

- Spacial SFM framework with compartmentalised system that can be combined side-by-side with busbar and cable chambers.
- Receive the cover panels and partial doors IP54.
- Material: Steel.
- Finish: Painted with epoxy polyester resin.
- Colour: RAL 7035 grey.
- Possibility to order it assembled or kit supply.

	Assembled supply		Kit supply	
				
Compartmentalised enclosure	**W600**	**W800**	**W600**	**W800**
Characteristics	• Structure: Top and bottom frame and vertical uprights H2000 mm. • Useful height for doors H1800 mm /36M, when are installed the top and bottom fix panels for modularity (mandatory for installation of partial doors). • Equipped with removable roof, external fixing rear panel and top and bottom fixed panels (H100 mm) to allow modularity of partial doors. • 4 dimensions available.			
References	D600: **NSYSF20660M** D800: **NSYSF20680M**	D600: **NSYSF20860M** D800: **NSYSF20880M**	-	-
Vertical uprights H2000 mm	-	-	**NSYSFV20**	**NSYSFV20**
Top and Bottom frame with roof	-	-	D600: **NSYSFC66** D800: **NSYSFC68**	D600: **NSYSFC86** D800: **NSYSFC88**
Rear panel	-	-	**NSYBP206**	**NSYBP208**
Fixed panels for modularty H100 mm /2M (intermediate crossbars included)	-	-	See table below	See table below

	Front Fix panel for modularity		Frontal partial doors		Side panels	
External claddings	**W600**	**W800**	**W600**	**W800**	**D600**	**D800**
Characteristics	• Top and bottom fix panel to obtain modularity required to install partial doors. • If there is no horizontal partitioning on top or bottom, the intermediate cross-bar has to be ordered separately, ref. NSYMIC6 (W600 mm) or NSYMIC8 (W800 mm). • 2M fixed panels are delivered as standard for the compartmentalized enclosure. Possibility to order it separately for Spacial SFM framework in kit supply. • Available in 2 heights(M) Heights according modularity (1M = 50 mm).		• Plain partial door with lock 5 mm double bar insert. • They are fixed to the uprights of the frame-work by means of hinges. • Drilling template for uprights ref. NSYMDT (Only 1 drilling template by order is needed). • Opening to right or left. • 1, 2 or 4 locking points according different heights. • Possibility to replace locking insert (see page 415). • Available in following heights(M) Heights according modularity (1M = 50 mm).		• Set of 2 side panels fixed to the outside of the enclosure. • Captive screws pre-mounted on • the panels. • Available in 2 depths (mm).	
References	2M: **NSYMFP2M6** 5M: **NSYMFP5M6**	2M: **NSYMFP2M8** 5M: **NSYMFP5M8**	3M: **NSYMPD3M6** 4M: **NSYMPD4M6** 5M: **NSYMPD5M6** 6M: **NSYMPD6M6** 8M: **NSYMPD8M6** 9M: **NSYMPD9M6** 12M: **NSYMPD12M6** 16M: **NSYMPD16M6** 18M: **NSYMPD18M6** 20M: **NSYMPD20M6** 24M: **NSYMPD24M6**	3M: **NSYMPD3M8** 4M: **NSYMPD4M8** 5M: **NSYMPD5M8** 6M: **NSYMPD6M8** 8M: **NSYMPD8M8** 9M: **NSYMPD9M8** 12M: **NSYMPD12M8** 16M: **NSYMPD16M8** 18M: **NSYMPD18M8** 20M: **NSYMPD20M8** 24M: **NSYMPD24M8**	**NSY2SP206**	**NSY2SP208**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Selection of Spacial enclosures

Selection of Spacial enclosures for Motor Control Centres

	Assembled supply		Kit supply	
Busbar and cabling chambers	**W300**	**W400**	**W300**	**W400**
Characteristics	• Structure: Top and bottom frame and vertical uprights H2000 mm. • Equipped with removable roof, external fixing rear panel and front plain door with 4 point locking system with handle and DB 5 mm insert. • 4 dimensions available.			
References	D600: **NSYSF20360** D800: **NSYSF20380**	D600: **NSYSF20460** D800: **NSYSF20480**	-	-
Vertical uprights H2000 mm	-	-	**NSYSFV20**	**NSYSFV20**
Top and Bottom frame with roof	-	-	D600: **NSYSFC36** D800: **NSYSFC38**	D600: **NSYSFC46** D800: **NSYSFC48**
Rear panel	-	-	**NSYBP203**	**NSYBP204**
Front plain door	-	-	**NSYSFD203**	**NSYSFD204**

11

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Spacial accessories

Other composition accessories

			Cable gland plates			Plinth (100 mm height)		Plinth (200 mm height)	
									
H (mm)	W (mm)	D (mm)	Plain	1 entry	2 entries	Front kit	Side kit	Front kit	Side kit
2000	600	600	NSYEC66	NSYEC661	NSYEC662	NSYSPF6100	NSYSPS6100	NSYSPF6200	NSYSPS6200
2000	600	800	NSYEC68	NSYEC681	NSYEC682	NSYSPF6100	NSYSPS8100	NSYSPF6200	NSYSPS8200
2000	800	600	NSYEC86	NSYEC861	NSYEC862	NSYSPF8100	NSYSPS6100	NSYSPF8200	NSYSPS6200
2000	800	800	NSYEC88	NSYEC881	NSYEC882	NSYSPF8100	NSYSPS8100	NSYSPF8200	NSYSPS8200
2000	300	600	NSYEC36	NSYEC361	-	NSYSPF3100	NSYSPS6100	NSYSPF3200	NSYSPS6200
2000	300	800	-	NSYEC381	-	NSYSPF3100	NSYSPS8100	NSYSPF3200	NSYSPS8200
2000	400	600	NSYEC64	NSYEC461	-	NSYSPF4100	NSYSPS6100	NSYSPF4200	NSYSPS6200
2000	400	800	NSYEC84	NSYEC481	-	NSYSPF4100	NSYSPS8100	NSYSPF4200	NSYSPS8200

	Coupling kit	4 lifting eyebolts	4 lifting brackets	Earth braids	Earthing cables
					
	NSYSFBK19	NSYSFEB	NSYSFELB	NSYEB1516D8	NSYEL166D8
Characteristics	• Side-by-side combination. • Back-to-back combination (Back to back association must be shipped individually and combined during on-site installation).	• Use a set of lifting eyebolts rings for each framework (1).	• When two cubicles with devices have been combined, use a lifting brackets. (2)	**NSYEB1516D8:** • Length 155 mm, • Section 16 mm², • Terminal 8.5 mm. **NSYEB2025D8:** • Length 200 mm, • Section 25 mm², • Terminal 8.5 mm. **NSYEB2050D8:** • Length 200 mm, • Section 50 mm², • Terminal 8.5 mm.	**NSYEL166D8:** • Length 160 mm, • Section 6 mm², • Terminal 8.3 mm. **NSYEL2225D8:** • Length 220 mm, • Section 25 mm², • Terminal 8.3 mm. **NSYEL3525D8:** • Length 350 mm, • Section 25 mm², • Terminal 8.3 mm.
References	**NSYSFBK19**	**NSYSFEB**	**NSYSFELB**	**NSYEB1516D8** **NSYEB2025D8** **NSYEB2050D8**	**NSYEL166D8** **NSYEL2225D8** **NSYEL3525D8**

(1) For 2 columns:



(2) For 3 columns:



● Lifting eyebolts

▬ Lifting brackets

For more than 3 colomuns, lenghts > 1600 mm, see Lifting bars options on Universal Enclosures catalogue.

Locks for partial doors

Possibility to replace standard insert by one from the table below (CRN range) and by keeping the standard latch.

Type of lock		Insert references	Key references	
	3 mm double bar	NSYTDBCRN*		NSYLDB5
	6 mm	NSYTC6CRN		NSYLC7
	7 mm	NSYTC7CRN		NSYLC7
	8 mm	NSYTC8CRN		NSYLC8
	6.5 mm	NSYTT6CRN		NSYLT8
	7 mm	NSYTT7CRN		NSYLT8
	8 mm	NSYTT8CRN		NSYLT8

* Delivered with 1 metal key.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Outdoor Heavy Duty enclosures

Thalassa PHD is suitable for outdoor public areas thanks to its multiple virtues:
- pressure and shock resistant (IEC 61439-5: 2010),
- anti-posting thanks to its special ribbed-surface door,
- insulated (ready to be Class II according to IEC 61439-1: 2011).

This range can be configured according to your needs

4 differents services available:

Assemble to order

Mounting of standard accessories

Painting

Machining

Green Premium™

Tough

- PHD: Heavy Duty polyester reinforced with a double layer of fiberglass. Ultra-resistant, anti-vandalism.



Upper ventilation module

- The newly engineered roof ventilation accessory
- helps to prevent creation of condensation
- (one of the causes of corrosion).



Heavy Duty accessories

- Dedicated accessories to resist outdoor, harsh environments.

Anti-vandalism

- PHD and SFHD: The handle with keylock
- and additional padlock hole (padlock not included)
- helps to secure the equipment inside.
- It is standard equipment.

Simplicity

- Installation simplified: Easy to be lifted with up to 1000 kg-loaded equipment. HD lifting accessories also available.

Fully equipped

Standard, pre-installed equipment includes:
- a curved canopy to avoid water stagnation
- a door retainer to keep the door open even with strong wind or when a vehicle passes by
- an aluminium cable gland plate to easily drill holes and avoid corrosion
- a document pocket to stock your documents in a practical place..



Thermal management solutions

- 3 ventilation architectures studied to help protect the equipment installed inside from overheating and humidity.

See page 532 for details or consult our web site www.se.com

Prolonged exposure to UV radiation, wind and rain can cause aesthetics changes in the external surface of the enclosure.
Without affecting the technical properties according to IEC 62208.
For long exposure applications, it is recommended to use painted enclosures available through the P&S offer.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

According to Reach and RoHs & Halogen free

Polyester outdoor Heavy Duty enclosures

Steel outdoor Heavy Duty enclosures

Characteristics	Wall-mounting enclosure	Floor-standing enclosure	Wall-mounting enclosure	Floor-standing enclosure
	Outdoor Heavy Duty (HD) enclosures made of polyester insulating material. Suitable to be installed in public areas thanks to its features: • anti-pressure and shock resistant • anti-posting • insulated.		Outdoor Heavy Duty (HD) enclosures made of coated steel. Suitable to be installed in private areas with harsh environments thanks to its capacity to resist: • corrosion (up to C4H level according ISO 12944:1999) • UV.	
Material	HD Polyester reinforced with fiberglass to meet the standard EN 439-5		HD steel with anti-corrosive coating	
Finish	-		Structured finish, 100 % polyester powder	
Colour	RAL 7035 grey		RAL 7035 grey	
Conditions of use	Outdoor and/or harsh environments		Outdoor and/or harsh environments	
Temperature range	-40...80°C		-40...80°C	
Ingress protection rating	IP65 according to IEC 60529	IP55 according to IEC 60529	IP66 according to IEC 60529	IP55 according to IEC 60529
Mechanical protection rating	IK10 according to IEC 62262		IK10 according to IEC 62262	
Standards	IEC 61439-5: 2010, IEC 62208: 2011, IEC 61439-1: 2011, IEC 61969-3: 2011, IEC 60297-3-100: 2009		IEC 61439-5: 2010, IEC 62208: 2011, IEC 61969-3: 2011, IEC 60297-3-100: 2009, ISO 12.944: 1999 (C4H)	
Certifications	See table page 428		See table page 428	
Fixing	On wall by means of optional wall fixing accessory	2 options for installation on floor: • with floor fixing kit **NSYMF2PLAZ4** or **NSYMF2PLAZ6** for integrated plinth (50 mm) • with additional ZZ plinths • (ventilated or non-ventilated) available as accessory • (200 mm) (see page 419)	• On wall by means of optional stainless steel wall fixing lugs • On post by means of optional HD post fixing device	• Directly on floor by means of optional plinth (see page 423)
Maximum load according to IEC 62208	500 kg		200 kg	1000 kg
Other characteristics	• Fire resistant (EN 1794-2:2011) • Lifting possible from top with eyebolt accessory • New dedicated ventilation solutions to be integrated in roof, lateral or plinth. 3 ventilation architectures proposed (see page 426 and 427)		New dedicated ventilation solutions to be integrated in roof, side or plinth	
Options	Plain door or ribbed door		-	
Supply	• Curved canopy • Handle with keylock (1242E type) and padlock • Door retainer • Plastic document pocket (A4 size)	• Curved canopy • Integrated plinth • Handle with keylock (1242E type) and padlock • Aluminium cable gland plate • Door retainer • Plastic document pocket (A4 size)	• Curved canopy • 3 mm double bar lock • Plastic document pocket (A4 size) • Door retainer • Aluminium cable gland plate	• Curved canopy • Rear panel • Handle with keylock (1242E type) and padlock • Aluminium cable gland plate • Door retainer • Plastic document pocket (A4 size)

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Outdoor Heavy Duty enclosures

Polyester outdoor Heavy Duty enclosures

- Outdoor Heavy Duty (HD) enclosures made of polyester insulating material. Suitable to be installed in public areas thanks to its features: Anti-pressure and shock resistant, anti-posting, insulated.
- Material: HD Polyester reinforced with fiberglass to meet the standard EN 439-5
- Colour: RAL 7035 grey
- Conditions of use: Outdoor and/or harsh environments
- Temperature range: -40...80°C
- Mechanical protection rating: IK10 according to IEC 62262
- Standards: IEC 61439-5: 2010, IEC 62208: 2011, IEC 61439-1: 2011, IEC 61969-3: 2011, IEC 60297-3-100: 2009
- Certifications: See table page 428
- Maximum load according to IEC 62208: 500 kg
- Other characteristics: Fire resistant (EN 1794-2:2011), Lifting possible from top with eyebolt accessory, new dedicated ventilation solutions to be integrated in roof, lateral or plinth. 3 ventilation architectures proposed (see page 426 and 427)
- Options: Plain door or ribbed door

Wall-mounting enclosure

NSYPHDT553

- Ingress protection rating: IP65 according to IEC 60529
- Fixing: On wall by means of optional wall fixing accessory

Supply:
Curved canopy
Handle with keylock (1242E type) and padlock
Door retainer
Plastic document pocket (A4 size)

Characteristics	Door type	No. of doors	Dimensions (H x W x D)	References
Wall-mounting enclosure	Anti-posting	1	538 x 500 x 320	**NSYPHDT553**
Wall-mounting enclosure	Anti-posting	1	788 x 500 x 320	**NSYPHDT753**
Wall-mounting enclosure	Plain	1	538 x 500 x 320	**NSYPHDT553P**
Wall-mounting enclosure	Plain	1	788 x 500 x 320	**NSYPHDT753P**

Floor-standing enclosure

- Ingress protection rating: IP55 according to IEC 60529
- Fixing: 2 options for installation on floor:
- with floor fixing kit **NSYMF2PLAZ4** or **NSYMF2PLAZ6** for integrated plinth (50 mm)
- with additional ZZ plinths (ventilated or non-ventilated) available as accessory (200 mm) (see page 419)

Supply:
Curved canopy
Integrated plinth
Handle with keylock (1242E type) and padlock
Aluminium cable gland plate
Door retainer
Plastic document pocket (A4 size)

NSYPHDZT774

NSYPHDZT774P

Characteristics	Door type	No. of doors	Dimensions (H x W x D)	References
Floor-standing enclosure	Anti-posting	1	843 x 750 x 420	**NSYPHDZT774**
Floor-standing enclosure	Anti-posting	1	843 x 750 x 620	**NSYPHDZT776**
Floor-standing enclosure	Anti-posting	1	1093 x 500 x 420	**NSYPHDZT1054**
Floor-standing enclosure	Anti-posting	1	1093 x 750 x 420	**NSYPHDZT1074**
Floor-standing enclosure	Anti-posting	1	1343 x 500 x 420	**NSYPHDZT1254**
Floor-standing enclosure	Anti-posting	1	1343 x 750 x 420	**NSYPHDZT1274**
Floor-standing enclosure	Anti-posting	1	1343 x 750 x 620	**NSYPHDZT1276**
Floor-standing enclosure	Anti-posting	2	1343 x 1250 x 420	**NSYPHDZT12124**
Floor-standing enclosure	Anti-posting	2	1343 x 1250 x 620	**NSYPHDZT12126**
Floor-standing enclosure	Anti-posting	1	1593 x 750 x 420	**NSYPHDZT1574**
Floor-standing enclosure	Anti-posting	1	1593 x 750 x 620	**NSYPHDZT1576**
Floor-standing enclosure	Anti-posting	2	1593 x 1250 x 420	**NSYPHDZT15124**
Floor-standing enclosure	Anti-posting	2	1593 x 1250 x 620	**NSYPHDZT15126**
Floor-standing enclosure	Anti-posting	2 Vertical	2093 x 750 x 420	**NSYPHDZT2074**
Floor-standing enclosure	Plain	1	843 x 750 x 420	**NSYPHDZT774P**
Floor-standing enclosure	Plain	1	843 x 750 x 620	**NSYPHDZT776P**
Floor-standing enclosure	Plain	1	1093 x 500 x 420	**NSYPHDZT1054P**
Floor-standing enclosure	Plain	1	1093 x 750 x 420	**NSYPHDZT1074P**
Floor-standing enclosure	Plain	1	1343 x 500 x 420	**NSYPHDZT1254P**
Floor-standing enclosure	Plain	1	1343 x 750 x 420	**NSYPHDZT1274P**
Floor-standing enclosure	Plain	1	1343 x 750 x 620	**NSYPHDZT1276P**
Floor-standing enclosure	Plain	2	1343 x 1250 x 420	**NSYPHDZT12124P**
Floor-standing enclosure	Plain	2	1343 x 1250 x 620	**NSYPHDZT12126P**
Floor-standing enclosure	Plain	1	1593 x 750 x 420	**NSYPHDZT1574P**
Floor-standing enclosure	Plain	1	1593 x 750 x 620	**NSYPHDZT1576P**
Floor-standing enclosure	Plain	2	1593 x 1250 x 420	**NSYPHDZT15124P**
Floor-standing enclosure	Plain	2	1593 x 1250 x 620	**NSYPHDZT15126P**
Floor-standing enclosure	Plain	2 Vertical	2093 x 750 x 420	**NSYPHDZT2074P**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Outdoor Heavy Duty enclosures

Eyebolts

NSYPLHD

- Top lifting accessory for polyester outdoor Heavy Duty enclosure.
- Maximum load per enclosure: 500 kg.
- Material: Galvanised cast steel

Supply:
4

Characteristics	References
Eyebolts	**NSYPLHD**

Wall fixing accessory

NSYFMPHD

- Wall fixing support for polyester outdoor Heavy Duty enclosure.
- No change in ingress protection rate.
- Maximum load per enclosure: 180 kg
- Material: Zinc coated steel
- Finish: Zinc coating

Supply:
4

Characteristics	References
Wall fixing accessory	**NSYFMPHD**

Floor fixing kit

NSYMF2PLAZ4

- To fix the enclosure on the floor without a plinth.
- Material: Steel
- Finish: Insulating coating
- Installation: On dry concrete

Supply:
1

Characteristics	Depth (mm)	References
Floor fixing kit	420	**NSYMF2PLAZ4**
Floor fixing kit	620	**NSYMF2PLAZ6**

Ventilated ZZ plinth 200 mm


NSYZZ254VHD

- Height: 200 mm.
- The front part can be removed with a 1242 key.
- Includes a polyester anti-insect filter.
- Material: Glass-reinforced polyester
- Colour: RAL 7035 grey

Note:
The coupling kit **NSYMUPLA●●●** is not applicable for enclosures using ZZ or ZH type plinths.

Supply:
1

Characteristics	Dimensions (W x D)	References
Ventilated ZZ plinth 200 mm	500 x 420	**NSYZZ254VHD**
Ventilated ZZ plinth 200 mm	750 x 420	**NSYZZ274VHD**
Ventilated ZZ plinth 200 mm	750 x 620	**NSYZZ276VHD**
Ventilated ZZ plinth 200 mm	1250 x 420	**NSYZZ2124VHD**
Ventilated ZZ plinth 200 mm	1250 x 620	**NSYZZ2126VHD**

ZZ plinth 200 mm

NSYZZ254G

- Height: 200 mm.
- The front and back plates can only be removed from the inside.
- It is provided with one or two reinforcement cross rails, adjustable to adapt to the position of the cables.
- Material: Glass-reinforced polyester
- Colour: RAL 7035 grey

Note:
The coupling kit **NSYMUPLA●●●** is not applicable for enclosures using ZZ or ZH type plinths.

Supply:
1

Characteristics	Depth (mm)	References
ZZ plinth 200 mm	500 x 420	**NSYZZ254G**
ZZ plinth 200 mm	750 x 420	**NSYZZ274G**
ZZ plinth 200 mm	750 x 620	**NSYZZ276G**
ZZ plinth 200 mm	1250 x 420	**NSYZZ2124G**
ZZ plinth 200 mm	1250 x 620	**NSYZZ2126G**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Outdoor Heavy Duty enclosures

Plain mounting plate

- The enclosures with height of ≥ 1000 mm have intermediate bosses to fix the mounting plate (M8 inserts, ref. **NSYTEX8**, to be ordered separately).
- Material: Galvanised steel

Installation:

- Direct installation on M8 inserts at the rear of the enclosure or on step slides for depth adjustment (see page 224)
- In the 2-door enclosures, it is possible to install 1 complete mounting plate or 2 individual mounting plates

Supply:
1

NSYPMM55

Characteristics	Dimensions (H x W)	References
Plain mounting plate	538 x 500	**NSYPMM55**
Plain mounting plate	788 x 500	**NSYPMM75**
Plain mounting plate	843 x 750	**NSYPMM77**
Plain mounting plate	1093 x 500	**NSYPMM105**
Plain mounting plate	1093 x 750	**NSYPMM107**
Plain mounting plate	1343 x 500	**NSYPMM125**
Plain mounting plate	1343 x 750	**NSYPMM127**
Plain mounting plate	1343 x 1250	**NSYPMM1212**
Plain mounting plate	1583 x 750	**NSYPMM157**
Plain mounting plate	1583 x 1250	**NSYPMM1512**
Plain mounting plate (or 2 x **NSYPMM107**)	2093 x 750	**NSYPMM207**

Roof ventilation module

- Ventilation module to enable airing from the top of the enclosure (H = 95 mm).
- Material: Steel with anti-corrosive coating (C4H according ISO 12.944: 1999)
- Finish: Structured finish, 100 % polyester powder
- Colour: RAL 7035 grey

Supply:
1

NSYPCVR54HD

Characteristics	Dimensions (W x D)	References
Roof ventilation module	500 x 420	**NSYPCVR54HD**
Roof ventilation module	750 x 420	**NSYPCVR74HD**
Roof ventilation module	750 x 620	**NSYPCVR76HD**
Roof ventilation module	1250 x 420	**NSYPCVR124HD**
Roof ventilation module	1250 x 620	**NSYPCVR126HD**

Anti burglary accessory

- Anti burglary accessory for polyester outdoor Heavy Duty in accordance with ENV 1627-1630:2011 class 2.
- It keeps the Insulation Class II according to IEC 61439-1:2011.
- Material: Steel with anti-corrosive coating (C4H according ISO 12.944: 1999)
- Finish: Structured finish, 100 % polyester powder
- Colour: RAL 7035 grey
- Installation: Easy installation on the outside of the enclosure

Supply:
1

NSYBGN774HD

Characteristics	Dimensions (H x W x D)	References
Anti burglary accessory	843 x 750 x 420	**NSYBGN774HD**
Anti burglary accessory	843 x 750 x 620	**NSYBGN776HD**
Anti burglary accessory	1093 x 500 x 420	**NSYBGN1054HD**
Anti burglary accessory	1093 x 750 x 420	**NSYBGN1074HD**
Anti burglary accessory	1343 x 500 x 420	**NSYBGN1254HD**
Anti burglary accessory	1343 x 750 x 420	**NSYBGN1274HD**
Anti burglary accessory	1343 x 750 x 620	**NSYBGN1276HD**
Anti burglary accessory	1343 x 1250 x 420	**NSYBGN12124HD**
Anti burglary accessory	1343 x 1250 x 620	**NSYBGN12126HD**
Anti burglary accessory	1593 x 750 x 420	**NSYBGN1574HD**
Anti burglary accessory	1593 x 750 x 620	**NSYBGN1576HD**
Anti burglary accessory	1593 x 1250 x 420	**NSYBGN15124HD**
Anti burglary accessory	1593 x 1250 x 620	**NSYBGN15126HD**
Anti burglary accessory	2093 x 750 x 420	**NSYBGN2074HD**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Outdoor Heavy Duty enclosures

Steel outdoor HD enclosures

- Outdoor Heavy Duty (HD) enclosures made of coated steel.
- Suitable to be installed in private areas with harsh environments thanks to its capacity to resist: corrosion (up to C4H level according ISO 12944:1999), UV
- Material: HD steel with anti-corrosive coating
- Finish: Structured finish, 100 % polyester powder
- Colour: RAL 7035 grey
- Conditions of use: Outdoor and/or harsh environments
- Temperature range: -40...80°C
- Mechanical protection rating: IK10 according to IEC 62262
- Standards: IEC 61439-5: 2010, IEC 62208: 2011, IEC 61969-3: 2011, IEC 60297-3-100: 2009, ISO 12.944: 1999 (C4H)
- Certifications: See table **page 428**
- Other characteristics: New dedicated ventilation solutions to be integrated in roof, side or plinth

Supply:
Curved canopy
Plastic document pocket (A4 size)
Door retainer
Aluminium cable gland plate

Wall-mounting enclosure

- Ingress protection rating: IP66 according to IEC 60529
- Fixing: On wall by means of optional stainless steel wall fixing lugs, on post by means of optional HD post fixing device
- Maximum load according to IEC 62208: 200 kg

Supply:
3 mm double bar lock

NSYS3HD3215

Characteristics	Dimensions (H x W x D)	References
Wall-mounting enclosure	343 x 200 x 180	**NSYS3HD3215**
Wall-mounting enclosure	448 x 300 x 230	**NSYS3HD4320**
Wall-mounting enclosure	548 x 400 x 230	**NSYS3HD5420**
Wall-mounting enclosure	653 x 400 x 280	**NSYS3HD6425**
Wall-mounting enclosure	658 x 600 x 330	**NSYS3HD6630**
Wall-mounting enclosure	753 x 500 x 280	**NSYS3HD7525**
Wall-mounting enclosure	858 x 600 x 330	**NSYS3HD8630**
Wall-mounting enclosure	862 x 800 x 430	**NSYS3HD8840**
Wall-mounting enclosure	1062 x 600 x 430	**NSYS3HD10640**
Wall-mounting enclosure	1062 x 800 x 430	**NSYS3HD10840**

Floor-standing enclosure

- Ingress protection rating: IP55 according to IEC 60529
- Fixing: Directly on floor by means of optional plinth
- Maximum load according to IEC 62208: 1000 kg

Supply:
Rear panel
Handle with keylock (1242E type) and padlock

NSYSFHD12640

Characteristics	Dimensions (H x W x D)	References
Floor-standing enclosure	1262 x 600 x 430	**NSYSFHD12640**
Floor-standing enclosure	1262 x 800 x 430	**NSYSFHD12840**
Floor-standing enclosure	1262 x 1200 x 430	**NSYSFHD1212402D**
Floor-standing enclosure	1281 x 600 x 630	**NSYSFHD12660**
Floor-standing enclosure	1281 x 800 x 630	**NSYSFHD12860**
Floor-standing enclosure	1281 x 1200 x 630	**NSYSFHD1212602D**
Floor-standing enclosure	1662 x 800 x 430	**NSYSFHD16840**
Floor-standing enclosure	1662 x 1200 x 430	**NSYSFHD1612402D**
Floor-standing enclosure	1681 x 600 x 630	**NSYSFHD16660**
Floor-standing enclosure	1681 x 800 x 630	**NSYSFHD16860**
Floor-standing enclosure	1681 x 1200 x 630	**NSYSFHD1612602D**
Floor-standing enclosure	2062 x 800 x 430	**NSYSFHD20840**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Outdoor Heavy Duty enclosures

Side panels for floor-standing enclosures

- Side panel fixing for SFHD.
- Material: Steel with anti-corrosive coating (C4H according ISO 12.944: 1999)
- Finish: Structured finish, 100 % polyester powder
- Colour: RAL 7035 grey

Supply:
2 side panels with fixing elements and sealing gasket

NSY2SPHD124

Characteristics	Dimensions (H x D)	References
Side panels, external fixing	1262 x 430	**NSY2SPHD124**
Side panels, external fixing	1281 x 630	**NSY2SPHD126**
Side panels, external fixing	1662 x 430	**NSY2SPHD164**
Side panels, external fixing	1681 x 630	**NSY2SPHD166**
Side panels, external fixing	2060 x 430	**NSY2SPHD204**
Side panels, internal fixing	1262 x 430	**NSY2SPIHD124**
Side panels, internal fixing	1281 x 630	**NSY2SPIHD126**
Side panels, internal fixing	1662 x 430	**NSY2SPIHD164**
Side panels, internal fixing	1681 x 630	**NSY2SPIHD166**
Side panels, internal fixing	2060 x 430	**NSY2SPIHD204**

Stainless steel wall fixing lugs





Vertical position



Horizontal position

A: Enclosure height
B: Enclosure width

- Set of 4 wall fixing lugs.
- Mounted directly on the rear of the enclosure, either in horizontal or vertical position.
- Wall-enclosure separation of 12 mm.
- Do not use for dynamic loads.
- Maximum load: 250 kg

Supply:
Supplied with fixing screws and pre-mounted sealing gaskets

NSYAEFPFXSC

Characteristics	References
Wall fixing lugs, 304L stainlesssteel, for outdoor enclosure	**NSYAEFPFXSC**

Heavy Duty padlockable double lock, for wall-mounting enclosures

- Easy mounting instead of the standard lock.
- Material: Zamak
- Finish: Anti-corrosive coating

Supply:
Delivered with 3 mm double bar metal key

NSYAEDLPADS3DHD

Characteristics	References
Heavy Duty padlockable double lock	**NSYAEDLPADS3DHD**

11

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Life Is On Schneider Electric

Outdoor Heavy Duty enclosures

Stainless steel plinths 200 mm

- Material: Stainless steel AISI 304L
- Finish: Scotch-Brite® brushing

Installation: For wall-mounting enclosure: It is necessary to order separately the plinth fixing kit (ref. **NSYAPFXWM**) composed by fixing hardware and drilling template, for floor-standing enclosure: Mounting in the holes for fixing the enclosures to the floor

Ventilated plinths, front and rear kit

Supply: 1 kit

- The front and rear of the plinth consists of 4 corners with 2 panels.

NSYSPFVX6200

Characteristics	Width (mm)	References
Ventilated plinths, front and rear kit	600	**NSYSPFVX6200**
Ventilated plinths, front and rear kit	800	**NSYSPFVX8200**
Ventilated plinths, front and rear kit	1200	**NSYSPFVX12200**

Ventilated plinths, lateral kit

Supply: 1 kit

- They are fixed to the corner of the plinth by fixing screws.

NSYSPLVX4200SF

Characteristics	Depth (mm)	References
Ventilated plinths, for wall-mounting enclosure	330	**NSYSPLVX3200**
Ventilated plinths, for wall-mounting enclosure	430	**NSYSPLVX4200**
Ventilated plinths, for floor-standing enclosure	430	**NSYSPLVX4200SF**
Ventilated plinths, for floor-standing enclosure	630	**NSYSPLVX6200SF**

Standard plinths, front and rear kit

Supply: 1 kit

- The front and rear of the plinth consists of 4 corners with 2 panels.

NSYSPFX6200

Characteristics	Width (mm)	References
Plinth height 200 mm, Kit (4 corners + front and back), AISI 304L	600	**NSYSPFX6200**
Plinth height 200 mm, Kit (4 corners + front and back), AISI 304L	800	**NSYSPFX8200**
Plinth height 200 mm, Kit (4 corners + front and back), AISI 304L	1200	**NSYSPFX12200**

Standard plinths, lateral kit

Supply: 1 kit

- They are fixed to the corner of the plinth by fixing screws.

NSYSPSX3200

Characteristics	Depth (mm)	References
Standard plinths height 200 mm, for wall-mounting enclosure, AISI 304L	330	**NSYSPSX3200**
Standard plinths height 200 mm, for wall-mounting enclosure, AISI 304L	430	**NSYSPSX4200**
Standard plinths height 200 mm, for floor-standing enclosure, AISI 304L	430	**NSYSPSX4200SF**
Standard plinths height 200 mm, for floor-standing enclosure, AISI 304L	630	**NSYSPSX6200SF**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Outdoor Heavy Duty enclosures

Plain mounting plate

(1) Plate with reversible dimensions; It can be installed in enclosures with inverted dimensions. Example: Plate ref. NSYMM64 can be used for the following enclosures: H 600 x W 400 mm or H 400 x W 600 mm. For plain and silkscreened mounting plates: In wall-mounting enclosures with widths of 1000 and 1200 mm, it is possible to install 2 mounting plates at different depths using an additional central step slide **NSYSDRSDCR●●●** (more information on page 243). unting plate and fixing elements

Supply:
1 mounting plate and fixing elements

- Material: Galvanised steel

NSYMM32

NSYMP126

Characteristics	Dimensions (H x W)	References
Plain mounting plate, for wall-mounting enclosure	300 x 200	**NSYMM32**
Plain mounting plate, for wall-mounting enclosure	500 x 400	**NSYMM54**
Plain mounting plate, for wall-mounting enclosure	600 x 400	**NSYMM64**
Plain mounting plate, for wall-mounting enclosure	600 x 600	**NSYMM66**
Plain mounting plate, for wall-mounting enclosure	700 x 500	**NSYMM75**
Plain mounting plate, for wall-mounting enclosure (1)	800 x 600	**NSYMM86**
Plain mounting plate, for wall-mounting enclosure	800 x 800	**NSYMM88**
Plain mounting plate, for wall-mounting enclosure	1000 x 600	**NSYMM106**
Plain mounting plate, for wall-mounting enclosure (1)	1000 x 800	**NSYMM108**
Plain mounting plate, for floor-standing enclosure	1200 x 600	**NSYMP126**
Plain mounting plate, for floor-standing enclosure	1200 x 800	**NSYMP128**
Plain mounting plate, for floor-standing enclosure	1200 x 1200	**NSYMP1212**
Plain mounting plate, for floor-standing enclosure	1600 x 600	**NSYMP168**
Plain mounting plate, for floor-standing enclosure	1600 x 800	**NSYMP1612**
Plain mounting plate, for floor-standing enclosure	1600 x 1200	**NSYMP166**
Plain mounting plate, for floor-standing enclosure	2000 x 800	**NSYMP208**

Roof ventilation module

- Ventilation module to enable airing from the top of the enclosure (H = 95 mm).
- Material: Steel with anticorrosive coating
- Finish: Structured finish, 100 % polyester powder
- Colour: RAL 7035 grey

Supply:
1

NSYS3CVR84HD

Characteristics	For enclosure dimensions (W x D)	References
Roof ventilation module, for wall-mounting enclosure	600 x 430	**NSYS3CVR64HD**
Roof ventilation module, for wall-mounting enclosure	800 x 430	**NSYS3CVR84HD**
Roof ventilation module, for floor-standing enclosure	600 x 430	**NSYSFCVR64HD**
Roof ventilation module, for floor-standing enclosure	600 x 630	**NSYSFCVR66HD**
Roof ventilation module, for floor-standing enclosure	800 x 430	**NSYSFCVR84HD**
Roof ventilation module, for floor-standing enclosure	800 x 630	**NSYSFCVR86HD**
Roof ventilation module, for floor-standing enclosure	1200 x 430	**NSYSFCVR124HD**
Roof ventilation module, for floor-standing enclosure	1200 x 630	**NSYSFCVR126HD**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Life Is On Schneider Electric

Outdoor Heavy Duty enclosures

Ventilation system Heavy duty

Fanbox



- Free flow rate: 550 m³/h (50/60 Hz).
- Minimal depth inside the enclosure (90 mm).
- Allows multiple cooling architectures (see page 426 and 427).
- Material: Plastic
- Colour: RAL 7016 dark grey

Supply:
1 (grille not included)

NSYCVF550M24FB

Characteristics	Voltage	References
Fanbox	24 V DC	**NSYCVF550M24FB**
Fanbox	24 V DC	**NSYCVF550M48FB**
Fanbox	115 V AC	**NSYCVF550M115FB**
Fanbox	230 V AC	**NSYCVF550M230FB**

Filter

- Replacement G3 M1 type synthetic filter for HD metal grille.
- Dimensions: 215 x 215 mm.
- Material: 100 % polyester fibres
- Colour: White

Supply:
5

NSYCAF223T

Characteristics	Height (mm)	Width (mm)	Depth (mm)	Cut-out (mm)	References
G3 M1 synthetic fine filters	268	248	18	223 x 223	**NSYCAF223T**

Roof filter for fanbox

- Roof G2 round synthetic filter designed to cover the fanbox. Covers completely the fanbox and helps to protect it from dust and humidity. Mandatory for fanbox installation in the Roof ventilation module for IP55 configurations.
- Material: 100 % polyester fibres
- Colour: White

Supply:
1

NSYCAF190

Characteristics	References
Roof filter for fanbox	**NSYCAF190**

IP55 HD Metal Grille



- Slim grille (35 mm external depth).
- Includes a G3 M1
- Material: Steel with anti-corrosive coating + plastic PA6 / GF25 for fixing frame
- Finish: Structured finish, 100 % polyester powder
- Colour: RAL 7035 grey
- Ingress protection rating: IP55 according to IEC 60529
- Mechanical protection rating: IK10 according to IEC 62262

Supply:
1 grille delivered with G3 M1 type synthetic filter (215 x 215 mm) and fixings

NSYCAG223LFHD

Characteristics	References
IP55 HD Metal Grille	**NSYCAG223LFHD**

Anti-vandalism kit for HD metal grille

Note:
not compatible with **NSYSPLA150**

- Fixings that help to prevent to open the grille from the outside with standard tools (EN 1627-1630:2011 Class 2).
- Quick installation without tools.
- Material: Steel with anticorrosive coating + plastic for fixing screws

Supply:
4 grip knob
4 clip nuts

NSYCAAPVHD

Characteristics	References
Anti-vandalism kit for HD metal grille	**NSYCAAPVHD**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Outdoor Heavy Duty enclosures



1 IP55 metal grille
2 Fanbox



2 Fanbox
3 Roof ventilated module

	S-Line				T-Line				
Architecture benefits	• Most common and competitive architecture • Maximum heat dissipation to extract 800 W-1000 W • ΔT° of 5°C • Easy access to mount-dismount fanbox • Air flow in horizontal axis				• High capacity of extraction calories up to 1500 W • Noise level with 1 fan: 55 dB when installed inside the upper ventilation module • ΔT° of 5°C • Air flow in vertical axis				
	IP55 metal grille		Fanbox		IP55 metal grille		Fanbox (1 filter NSYCAF190 for each Fanbox)	Roof ventilation module	
	Door	Side	Door	Side	Door	Side			
Polyester outdoor HD enclosure									
References	Amount to be installed				Amount to be installed				References
NSYPHDT553	-	-	-	-	-	-	-	-	-
NSYPHDT553P	-	-	-	-	-	-	-	-	-
NSYPHDT753	-	-	-	-	-	-	-	-	-
NSYPHDT753P	1 to 2	-	1 to 2	-	1 to 2	-	-	-	-
NSYPHDZT774	-	1 to 2	-	1 to 2	-	1 to 2	1 to 2	1	**NSYPCVR74HD**
NSYPHDZT774P	1 to 2	1 to 2	1 to 2	1 to 2	1 to 2	1 to 2	1 to 2	1	**NSYPCVR74HD**
NSYPHDZT776	-	1 to 2	-	1 to 2	-	1 to 2	1 to 2	1	**NSYPCVR76HD**
NSYPHDZT776P	1 to 2	1 to 2	1 to 2	1 to 2	1 to 2	1 to 2	1 to 2	1	**NSYPCVR76HD**
NSYPHDZT1054	-	1	-	1	-	1	1	1	**NSYPCVR54HD**
NSYPHDZT1054P	1 to 2	1	1 to 2	1	1 to 2	1	1	1	**NSYPCVR54HD**
NSYPHDZT1074	-	1 to 2	-	1 to 2	-	1 to 2	1 to 2	1	**NSYPCVR74HD**
NSYPHDZT1074P	1 to 4	1 to 2	1 to 4	1 to 2	1 to 4	1 to 2	1 to 2	1	**NSYPCVR74HD**
NSYPHDZT12124	-	1 to 3	-	1 to 3	-	1 to 3	1 to 3	1	**NSYPCVR124HD**
NSYPHDZT12124P	1 to 4	1 to 3	1 to 4	1 to 3	1 to 4	1 to 3	1 to 3	1	**NSYPCVR124HD**
NSYPHDZT12126	-	1 to 3	-	1 to 3	-	1 to 3	1 to 3	1	**NSYPCVR126HD**
NSYPHDZT12126P	1 to 4	1 to 3	1 to 4	1 to 3	1 to 4	1 to 3	1 to 3	1	**NSYPCVR126HD**
NSYPHDZT1254	-	1	-	1	-	1	1	1	**NSYPCVR54HD**
NSYPHDZT1254P	1 to 3	1	1 to 3	1	1 to 3	1	1	1	**NSYPCVR54HD**
NSYPHDZT1274	-	1 to 2	-	1 to 2	-	1 to 2	1 to 2	1	**NSYPCVR74HD**
NSYPHDZT1274P	1 to 4	1 to 2	1 to 4	1 to 2	1 to 4	1 to 2	1 to 2	1	**NSYPCVR74HD**
NSYPHDZT1276	-	1 to 2	-	1 to 2	-	1 to 2	1 to 2	1	**NSYPCVR76HD**
NSYPHDZT1276P	1 to 4	1 to 2	1 to 4	1 to 2	1 to 4	1 to 2	1 to 2	1	**NSYPCVR76HD**
NSYPHDZT15124	-	1 to 3	-	1 to 3	-	1 to 3	1 to 3	1	**NSYPCVR124HD**
NSYPHDZT15124P	1 to 4	1 to 3	1 to 4	1 to 3	1 to 4	1 to 3	1 to 3	1	**NSYPCVR124HD**
NSYPHDZT15126	-	1 to 3	-	1 to 3	-	1 to 3	1 to 3	1	**NSYPCVR126HD**
NSYPHDZT15126P	1 to 4	1 to 3	1 to 4	1 to 3	1 to 4	1 to 3	1 to 3	1	**NSYPCVR126HD**
NSYPHDZT1574	-	1 to 2	-	1 to 2	-	1 to 2	1 to 2	1	**NSYPCVR74HD**
NSYPHDZT1574P	1 to 4	1 to 2	1 to 4	1 to 2	1 to 4	1 to 2	1 to 2	1	**NSYPCVR74HD**
NSYPHDZT1576	-	1 to 2	-	1 to 2	-	1 to 2	1 to 2	1	**NSYPCVR76HD**
NSYPHDZT1576P	1 to 4	1 to 2	1 to 4	1 to 2	1 to 4	1 to 2	1 to 2	1	**NSYPCVR76HD**
NSYPHDZT2074	-	1 to 2	-	1 to 2	-	1 to 2	1 to 2	1	**NSYPCVR74HD**
NSYPHDZT2074P	1 to 4	1 to 2	1 to 4	1 to 2	1 to 4	1 to 2	1 to 2	1	**NSYPCVR74HD**
Steel outdoor HD enclosure									
NSYS3HD8630	1 to 2	-	1 to 2	-	1 to 2	-	-	-	-
NSYS3HD8840	1 to 2	1 to 2	1 to 2	1 to 2	1 to 2	1 to 2	1 to 2	1	**NSYS3CVR84HD**
NSYS3HD10640	1 to 2	1 to 2	1 to 2	1 to 2	1 to 2	1 to 2	1	1	**NSYS3CVR64HD**
NSYS3HD10840	1 to 4	1 to 2	1 to 4	1 to 2	1 to 4	1 to 2	1 to 2	1	**NSYS3CVR84HD**
NSYSFHD12640	1 to 3	1 to 3	1 to 3	1 to 3	1 to 3	1 to 3	1	1	**NSYSFCVR64HD**
NSYSFHD12660	1 to 3	1 to 3	1 to 3	1 to 3	1 to 3	1 to 3	1	1	**NSYSFCVR66HD**
NSYSFHD12840	1 to 4	1 to 3	1 to 4	1 to 3	1 to 4	1 to 3	1 to 2	1	**NSYSFCVR84HD**
NSYSFHD12860	1 to 4	1 to 3	1 to 4	1 to 3	1 to 4	1 to 3	1 to 2	1	**NSYSFECA66HD**
NSYSFHD16660	1 to 4	1 to 4	1 to 4	1 to 4	1 to 4	1 to 4	1	1	**NSYSFCVR66HD**
NSYSFHD16840	1 to 4	1 to 4	1 to 4	1 to 3	1 to 4	1 to 3	1 to 2	1	**NSYSFCVR84HD**
NSYSFHD16860	1 to 4	1 to 4	1 to 4	1 to 4	1 to 4	1 to 4	1 to 2	1	**NSYSFECA66HD**
NSYSFHD20840	1 to 4	1 to 4	1 to 4	1 to 4	1 to 4	1 to 4	1 to 2	1	**NSYSFCVR84HD**
NSYSFHD1212402D	1 to 4	1 to 3	1 to 4	1 to 2	1 to 4	1 to 2	1 to 3	1	**NSYSFCVR124HD**
NSYSFHD1212602D	1 to 4	1 to 3	1 to 4	1 to 3	1 to 4	1 to 2	1 to 3	1	**NSYSFCVR126HD**
NSYSFHD1612402D	1 to 4	1 to 4	1 to 4	1 to 3	1 to 4	1 to 3	1 to 3	1	**NSYSFCVR124HD**
NSYSFHD1612602D	1 to 4	1 to 4	1 to 4	1 to 3	1 to 4	1 to 3	1 to 3	1	**NSYSFCVR126HD**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.



2 Fanbox
3 Roof ventilated module
4 Ventilated plinths
5 IP54 grille

This table helps to configure thermal architectures, but it is highly recommended to use ProClima Software to ensure the right thermal solution according to the selected architecture.

I-Line

- Integrated architecture particularly suitable for public areas
- High capacity of extraction calories up to 1500 W
- Noise level with 1 fan: 55 dB when installed inside the upper ventilation module
- Good extraction flow rate power
- Air flow in vertical axis

IP54 outlet grille (**NSYCAG223LPF** + G3 filter **NSYCAF223T**)		Ventilated plinths		Fanbox (1 filter **NSYCAF190** for each Fanbox)		Roof ventilation module
Amount to be installed		References		Amount to be installed		References
-	-	-	-	-	-	-
-	-	-	-	-	-	-
-	-	-	-	-	-	-
-	-	-	-	-	-	-
1 to 2	1	**NSYZZ274VHD**	-	1 to 2	1	**NSYPCVR74HD**
1 to 2	1	**NSYZZ274VHD**	-	1 to 2	1	**NSYPCVR74HD**
1 to 2	1	**NSYZZ276VHD**	-	1 to 2	1	**NSYPCVR76HD**
1 to 2	1	**NSYZZ276VHD**	-	1 to 2	1	**NSYPCVR76HD**
1	1	**NSYZZ254VHD**	-	1	1	**NSYPCVR54HD**
1	1	**NSYZZ254VHD**	-	1	1	**NSYPCVR54HD**
1 to 2	1	**NSYZZ274VHD**	-	1 to 2	1	**NSYPCVR74HD**
1 to 2	1	**NSYZZ274VHD**	-	1 to 2	1	**NSYPCVR74HD**
1 to 3	1	**NSYZZ2124VHD**	-	1 to 3	1	**NSYPCVR124HD**
1 to 3	1	**NSYZZ2124VHD**	-	1 to 3	1	**NSYPCVR124HD**
1 to 3	1	**NSYZZ2126VHD**	-	1 to 3	1	**NSYPCVR126HD**
1 to 3	1	**NSYZZ2126VHD**	-	1 to 3	1	**NSYPCVR126HD**
1	1	**NSYZZ254VHD**	-	1	1	**NSYPCVR54HD**
1	1	**NSYZZ254VHD**	-	1	1	**NSYPCVR54HD**
1 to 2	1	**NSYZZ274VHD**	-	1 to 2	1	**NSYPCVR74HD**
1 to 2	1	**NSYZZ274VHD**	-	1 to 2	1	**NSYPCVR74HD**
1 to 2	1	**NSYZZ276VHD**	-	1 to 2	1	**NSYPCVR76HD**
1 to 2	1	**NSYZZ276VHD**	-	1 to 2	1	**NSYPCVR76HD**
1 to 3	1	**NSYZZ2124VHD**	-	1 to 3	1	**NSYPCVR124HD**
1 to 3	1	**NSYZZ2124VHD**	-	1 to 3	1	**NSYPCVR124HD**
1 to 3	1	**NSYZZ2126VHD**	-	1 to 3	1	**NSYPCVR126HD**
1 to 3	1	**NSYZZ2126VHD**	-	1 to 3	1	**NSYPCVR126HD**
1 to 2	1	**NSYZZ274VHD**	-	1 to 2	1	**NSYPCVR74HD**
1 to 2	1	**NSYZZ274VHD**	-	1 to 2	1	**NSYPCVR74HD**
1 to 2	1	**NSYZZ276VHD**	-	1 to 2	1	**NSYPCVR76HD**
1 to 2	1	**NSYZZ276VHD**	-	1 to 2	1	**NSYPCVR76HD**
1 to 2	1	**NSYZZ274VHD**	-	1 to 2	1	**NSYPCVR74HD**
1 to 2	1	**NSYZZ274VHD**	-	1 to 2	1	**NSYPCVR74HD**

1	1	**NSYSPFVX6200**	**NSYSPSX3200**	-	-	-
1 to 2	1	**NSYSPFVX8200**	**NSYSPLVX4200**	1 to 2	1	**NSYS3CVR84HD**
1	1	**NSYSPFVX6200**	**NSYSPLVX4200**	1	1	**NSYS3CVR64HD**
1	1	**NSYSPFVX8200**	**NSYSPLVX4200**	1 to 2	1	**NSYS3CVR84HD**
1	1	**NSYSPFVX6200**	**NSYSPLVX4200**	1	1	**NSYSFCVR64HD**
1	1	**NSYSPFVX6200**	**NSYSPLVX6200**	1	1	**NSYSFCVR66HD**
1 to 2	1	**NSYSPFVX8200**	**NSYSPLVX4200**	1 to 2	1	**NSYSFCVR84HD**
1 to 2	1	**NSYSPFVX8200**	**NSYSPLVX6200**	1 to 2	1	**NSYSFECA66HD**
1	1	**NSYSPFVX6200**	**NSYSPLVX6200**	1	1	**NSYSFCVR66HD**
1 to 2	1	**NSYSPFVX8200**	**NSYSPLVX4200**	1 to 2	1	**NSYSFCVR84HD**
1 to 2	1	**NSYSPFVX8200**	**NSYSPLVX6200**	1 to 2	1	**NSYSFECA66HD**
1 to 2	1	**NSYSPFVX8200**	**NSYSPLVX4200**	1 to 2	1	**NSYSFCVR84HD**
1 to 3	1	**NSYSPFVX12200**	**NSYSPLVX4200**	1 to 3	1	**NSYSFCVR124HD**
1 to 3	1	**NSYSPFVX12200**	**NSYSPLVX6200**	1 to 3	1	**NSYSFCVR126HD**
1 to 3	1	**NSYSPFVX12200**	**NSYSPLVX4200**	1 to 3	1	**NSYSFCVR124HD**
1 to 3	1	**NSYSPFVX12200**	**NSYSPLVX6200**	1 to 3	1	**NSYSFCVR126HD**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Outdoor Heavy Duty enclosures

POLYESTER Thalassa PHD				
Test description	Standard	Standard title	Certification	Declaration
IP55, IK10, lifting: 500 kg max. (IP65 for wall-mounting)	IEC 62208: 2011	Empty enclosures for low-voltage switchgear and controlgear assemblies - General requirements	●	-
Class II Insulation	IEC 61439-1: 2011	Low-voltage switchgear and controlgear assemblies Part 1: General rules	-	✓
Strength of materials and parts	IEC 61439-5: 2010	Low-voltage switchgear and controlgear assemblies Part 5: Assemblies for power distribution in public networks	●	-
Corrosion resistance C4H. It affects the painted accessories (ventilated roof, anti-burglary kit). All other metallic parts have special treatment to pass the same test.	ISO 12.944: 1999	Paints and varnishes-corrosion protection of steel structures by protective paint systems Part 6: laboratory performance testing methods	-	✓
Climatic test, Biological Test, Resistance against chemically and mechanical active substances. Mechanical test, Lifting and stifness test	IEC 61969-3: 2011	Electronic "Mechanical structures for electronic equipment - Outdoor enclosures" Part 3: Environmental requirements, tests and safety aspects	●	-
Space for electronics	IEC 60297-3-100: 2009	Mechanical structures for electronic equipment Dimensions of mechanical structures of the 482.6 mm (19 in) series - Part 3-100: Basic dimensions of front panels, subracks, chassis, racks and cabinets	-	✓
Dimensional	EIA-310-E	Cabinets, Racks, Panels, and associated equipment	-	✓
Fire resistance	EN 1794-2:2011	Vandalism: Fire resistance	-	✓
Posting	Internal test	Door anti-posting internal test	-	✓
Single door: types 1, 2, 3, 3R, 4, 4X, 5, 12 and 13 Double door: types 1, 2, 3, 3R, 5, 12 and 13	UL 508 A: 2007	Standard for Industrial Control Panels	●	-
Spacial SFHD (floor-standing enclosures)				
IP55, IK10, lifting: 1000 kg max.	IEC 62208: 2011	Empty enclosures for low-voltage switchgear and controlgear assemblies - General requirements	●	-
Strength of materials and parts	IEC 61.439-5: 2010	Low-voltage switchgear and controlgear assemblies Part 5: Assemblies for power distribution in public networks	●	-
Corrosion resistance C4H	ISO 12.944: 1999	Paints and varnishes-corrosion protection of steel structures by protective paint systems Part 6: laboratory performance testing methods	●	-
Climatic test, Biological Test, Resistance against chemically and mechanical active substances. Mechanical test, Lifting and stifness test	IEC 61969-3: 2011	Electronic "Mechanical structures for electronic equipment - Outdoor enclosures" Part 3: Environmental requirements, tests and safety aspects	●	-
Space for electronics	IEC 60297-3-100: 2009	Mechanical structures for electronic equipment Dimensions of mechanical structures of the 482.6 mm (19 in) series - Part 3-100: Basic dimensions of front panels, subracks, chassis, racks and cabinets	-	✓
Dimensional	EIA-310-E	Cabinets, Racks, Panels, and associated equipment	-	✓
Single door: Types 1, 3R, 12, 12K Double door: Types 1, 3R, 12, 12K	UL 508 A: 2007	Standard for Industrial Control Panels	●	-
Spacial S3HD (wall-mounting enclosures)				
IP66, IK10, lifting: 200 kg max.	IEC 62208: 2011	Empty enclosures for low-voltage switchgear and controlgear assemblies - General requirements	●	-
Strength of materials and parts	IEC 61.439-5: 2010	Low-voltage switchgear and controlgear assemblies Part 5: Assemblies for power distribution in public networks	●	-
Corrosion resistance C4H	ISO 12.944: 1999	Paints and varnishes-corrosion protection of steel structures by protective paint systems Part 6: Laboratory performance testing methods	●	-
Climatic test, Biological Test, Resistance against chemically and mechanical active substances. Mechanical test, Lifting and stifness test	IEC 61969-3: 2011	Electronic "Mechanical structures for electronic equipment - Outdoor enclosures" Part 3: Environmental requirements, tests and safety aspects	●	-
Space for electronics	IEC 60297-3-100: 2009	Mechanical structures for electronic equipment Dimensions of mechanical structures of the 482.6 mm (19 in) series - Part 3-100: Basic dimensions of front panels, subracks, chassis, racks and cabinets	-	✓
Dimensional	EIA-310-E	Cabinets, Racks, Panels, and associated equipment	-	✓
Single door: Types 1, 2, 3, 3R, 4, 4X. 5, 12 and 13	UL 508 A: 2007	Standard for Industrial Control Panels	●	-

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Outdoor Heavy Duty enclosures

Test description	Standard	Standard title	Certification	Declaration
HD ACCESSORIES HD THERMAL Management, Fanbox				
NSYCVF Series are intended for mounting on the flat surface of a Type 12 or 12K enclosure	UL 508A CAN/CSA-C22.2 No. 14, CAN/CSA C22.2 No. 94-M91 CAN/CSA C22.2 No. 73	Industrial Control Panels Industrial Control Equipment Special Purpose Enclosures Electrically Equipped Machine Tools	●	-
IP55 HD Metal grille (NSYCAG223LFHD)				
IP55 (in conditions of use)	IEC 60529: 2013	Degrees of protection provided by enclosures (IP Code)	-	✓
Corrosion resistance C4H	ISO 12.944: 1999	Paints and varnishes-corrosion protection of steel structures by protective paint systems - part 6: Laboratory performance testing methods	●	-
Anti-vandalism kit for HD metal grille (NSYCAAPVHD)				
Resistance Class 2	ENV 1627:2011	Burglar resistance - Requirements and classification	●	-
Upper ventilation module (PHD / SFHD / S3HD)				
IP55 (in conditions of use)	IEC 60529: 2013	Degrees of protection provided by enclosures (IP Code)		✓
Corrosion resistance at level C4H	ISO 12.944: 1999	Paints and varnishes-corrosion protection of steel structures by protective paint systems Part 6: Laboratory performance testing methods	●	-
HD POLYESTER ENCLOSURES **Anti burglary accessory (NSYBGN•••HD)**				
Resistance Class 2	ENV 1627:2011	Burglar resistance - Requirements and classification	●	-
Corrosion resistance at level C4H	ISO 12.944: 1999	Paints and varnishes-corrosion protection of steel structures by protective paint systems Part 6: Laboratory performance testing methods	●	-
ZZ plinths (NSYZZ••• and NSYZZ•••VHD)				
ZZ Plinth: IP44 (in conditions of use) Ventilated ZZ Plinth: IP43 (in conditions of use)	IEC 60.529:2013	Degrees of protection provided by enclosures (IP Code)	-	✓
Eyebolts (NSYPLHD)				
Maximum load 500 kg	IEC 62208: 2011	Empty enclosures for low-voltage switchgear and controlgear assemblies - General requirements	-	✓
HD STEEL ENCLOSURES **Stainless steel plinths (NSYSPFVX••• / NSYSPLVX••• / NSYSPSX••• / NSYSPSX•••)**				
Ventilated plinth: IP20 (in conditions of use) Standard plinth: IP30 (in conditions of use)	IEC 60.529:2013	Degrees of protection provided by enclosures (IP Code)	-	✓

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Seismic and nuclear enclosures

SF S3D

The seismic risk

New

No point of the globe is immune to an earthquake.
However, the probability of being subjected to an earthquake of a given intensity varies from one location to another.
The map below, taken from IEC 60721-2-6 (Figure 5), shows the distribution of the seismic risk on the 5 continents.



Spacial enclosures and the seismic constraint

Spacial standard range solutions

The Spacial standard offers have been qualified for use in areas subject to medium intensity earthquakes (ground acceleration ≤ 3 m/s²).
For details of the seismic resistance of the standard offers, see in each chapter for the following offers:

- S3D, CRN, CRNG et 19" wall mounting enclosures,
- SBM industrial boxes,
- SF enclosures (automation and monitoring/control),
- SFP enclosures (functional system for low-voltage electricity distribution),
- 19" SF enclosures (pivoting rack).

Enclosures for strong earthquakes

In order to meet the requirements of high-seismic zones (ground acceleration ≥ 4 m/s²), Schneider Electric has developed 3 offers:

- floor-standing enclosures SF 6G and SFP 5G,
- wall-mounting enclosure S3D 6G,
- wall-mounting enclosure S3D 6G K3 meeting the requirements of the nuclear power industry specified by EDF (Electricité de France) and the ASN (Agence de Sûreté Nucléaire).

Certifications

All tests have been performed according to the following technical regulations:

- IEC 60068-3-3 (first edition): International standard. Environmental testing – Part 3 : Guidance – Seismic test methods for equipment
- CRT 91-C-112-00: Seismic resistance of equipment Generic provisions for bi-axial testing using accelerograms
- IEC 60980: Recommended practices for seismic qualification of electrical equipment of the safety system for nuclear generating stations

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Seismic and nuclear enclosures

SF S3D



Geology Equivalence between scales characterizing the earthquake		
MSK	Richter	IEC 60068-3-3 (ground acc.)
<VIII	< 5.5	2 m/s²
VIII to IX	≥ 5.5 and ≤ 7	3 m/s²
>IX	> 7	5 m/s²

Civil engineering Example acceleration levels on the floor of a building (RRS)	
All types of building (IEC 60068-3-3)	EDF specification for nuclear power plant. Anticipating the possible rise in the RRS level in a subsequent revision of CRT 91 C 112.
6 m/s²	
9 m/s²	10 m/s² - 8 m/s²
15 m/s²	20 m/s² - 24 m/² *

Equipment performance tested according to CRT 91 C 112 00



Products	Floor part acc	Strong part acc
SFP 5G	20 m/s²	50 m/s²
SF 6G*	30 m/s²	50 m/s²
S3D 6G*	30 m/s²	55 m/s²



Products	Floor part acc	Strong part acc
SFP 5G	20 m/s²	40 m/s²
SF 6G*	30 m/s²	60 m/s²
S3D 6G*	30 m/s²	80 m/s²

Technical information

New

Seismic standards

There is no single international standard. The standards depend on each country/zone and are linked to civil engineering standards.

The main ones are:

- International Building Code (I.B.C. Ex UBC)
- IEC 60068-3-3,
- EDF specification CRT 91C11200 (ex-HN-20-E-53)
- GR CORE 63 Telcordia

The Spacial enclosures have been tested according to standards IEC 60068-3-3 and CRT 91-C-112-00.
CRT 91-C-112-00 is one of the most restrictive specifications, and for which it is therefore more difficult to obtain certification.

To define the seismic resistance of equipment, it is necessary to take into account the geological characteristics of the earthquake and the behavior of the building, and compare these with the equipment's seismic performance.

Definitions

Ground acceleration: Ground acceleration resulting from an earthquake.
Note: In practice, ground acceleration can be broken down into horizontal and vertical components.
Floor acceleration: Ground acceleration measured on a particular floor in a building (at the location of an equipment item).
Note: In practice, floor acceleration can be broken down into horizontal and vertical components.
Required response spectrum (RRS): Representation of the amplification of the ground acceleration caused by the structure or equipment according to the wave frequency. Used for determining equipment dimensions and qualifying the equipment.
Test response spectrum (TRS): Representation of the amplification of tested products during tests on vibrating table.

Two parts are defined in the response spectra:

- **Floor part:** On the product zone in contact with the vibrating table there is no amplification of the acceleration. The acceleration value recorded for the spectrum is that measured on the ground.
- **Strong part:** The acceleration value recorded for the spectrum is the maximum amplified acceleration expected at the center of gravity of the equipment. This is not a measurable quantity but a mathematical representation.

Conclusion: The TRS values are to be compared with the RRS values. If they are greater, the equipment will resist the effects of the earthquake.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Seismic and nuclear enclosures

The **Spacial SF 6G** enclosures have been designed to withstand earthquakes corresponding to UBC Zone 4.

New

Spacial SF 6G for seismic risks

SF

Panel mounting

- 12 fastening points by M6 screws per panel..

Security locking system

- Seismic locking system.
- Special connecting rods and handle to prevent any accidental door opening under severe vibration conditions.

Plinths

- Enhanced mechanical strength (monobloc structure).
- Assembled on the enclosure.
- Floor fixing: 10 fastening points by M12 screws.



Multi-purpose corners

- To strengthen the enclosure and respond to seismic risks.
- To strengthen fastening of the side panels and rear panel.
- To fasten the door connecting rods.

11

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Seismic and nuclear enclosures

Spacial SF 6G for seismic risks

NSYSF6G20680

- Enclosures designed to be installed in UBC Zone 4.
- They have been tested with a plain mounting plate and 19" rack.
- Integrated plinth.
- Material: Steel
- Ingress protection rating: IP55 according to IEC 60529
- Mechanical protection rating: IK10 according to IEC 62262
- Maximum load: 80 kg/m² on plain mounting plate, in compliance with the IEC 61587-2 standard
- Standards: IEC 62208 (enclosure) - IEC 60068-3-3 (seismic methods to apply for materials)
- Certifications: 6G certification as per CRT 91-C-112-00 (EDF) - UL 508 types 1, 3R, 12

Supply:
Framework
- 1 upper frame with roof
- 1 lower frame
- 1 rear panel
- 4 uprights
- 8 multi-purpose reinforcement corners
- 8 cross rails fastened to the framework contributing to the seismic resistance (3 left, 3 right, 2 rear)

Plinth
- Monobloc base 4 mm thick, 100 mm high

Door
- Plain door with EDF 1600 captive key lock
- 3 fastening points with connecting rods
- Door hinges on right (opposite direction available on request)

Coupling
- Possibility to couple SF 6G enclosures with the coupling kits ref. **NSYSFBK19** + **NSYSFBKR**
- Possibility to couple plinth with the ref. **NSYPLK6G**

Characteristics	Height (mm)	Width (mm)	Depth (mm)	References	
Spacial SF 6G	2000	600	800	**NSYSF6G20680**	New
Spacial SF 6G	2000	800	600	**NSYSF6G20860**	New
Spacial SF 6G	2000	800	800	**NSYSF6G20880**	New

Side panels


NSY6G2SP204

- Enclosures designed to be installed in UBC Zone 4.
- They have been tested with a plain mounting plate and 19" rack.
- Integrated plinth.
- Material: Steel
- Installation: 12 fastening points

Supply:
2 side panels and fasteners

Characteristics	Height (mm)	Depth (mm)	References	
Side panel	2000	400	**NSY6G2SP204**	New
Side panel	2000	600	**NSY6G2SP206**	New
Side panel	2000	800	**NSY6G2SP208**	New

Mounting plate

NSYMP206

- Material: Galvanised steel
- Installation: Mounting plate to be installed with **NSYSFPB6G** fastening kit + **NSYHLCR●●** cross rails

Supply:
1 mounting plate and sliding shoes

Characteristics	Height (mm)	Depth (mm)	References	
Mounting plate	2000	600	**NSYMP206**	New
Mounting plate	2000	800	**NSYMP208**	New

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Seismic and nuclear enclosures

Rails for heavy load

NSYHLCR40

- Material: Zinc-coated steel

Supply:
2 cross rails and fixing elements

Characteristics	Depth (mm)	References
Rails for heavy load	400	**NSYHLCR40** New
Rails for heavy load	600	**NSYHLCR60** New
Rails for heavy load	800	**NSYHLCR80** New

Reinforced fixing kit for mounting plate


NSYSFPB6G

- Material: Steel

Supply:
6 anti-vibration supports
4 mounting brackets
4 supports
2 connectors and fixing elements

Characteristics	References
Reinforced fixing kit for mounting plate	**NSYSFPB6G** New

Trim cap for SF 6G panels

NSYCSP6G

- Material: Plastic

Supply:
50 units

Characteristics	References
Trim cap for SF 6G panels	**NSYCSP6G** New

19" fixed uprights


NSYRCK42

- Uprights designed to be assembled on enclosures 800 mm wide
- and 800 mm deep.
- Material: Zinc-coated steel
- Fixing: To fasten the 19" uprights, it is necessary to use the fixing kit **NSYRCK19KIT6G**

Note:
For a 19" seismic configuration, 4 uprights must be used

Supply:
2 uprights and fasteners,

Characteristics	References
19" fixed uprights	**NSYRCK42** New

19" fixed uprights


NSYRCK19KIT6G

- Material: Steel

Supply:
4 cross rails
8 fastening brackets
4 reinforcements
Fixing elements

Characteristics	References
19" fixed uprights	**NSYRCK19KIT6G** New

Optional locks for cubicle

NSYAEDLEDF9K33

- With captive key.
- Material: Polyamide handle, metal connecting rods and cam

Supply:
3-point lock with
1 lock button and
1 cremone bolt

Characteristics	References
Optional lock for cubicle, EDF 900	**NSYAEDLEDF9K33** New
Optional lock for cubicle, EDF 1300	**NSYAEDLEDF13K33** New
Optional lock for cubicle, EDF 1400	**NSYAEDLEDF14K33** New
Optional lock for cubicle, 1242E	**NSYAEDL1242K33** New
Optional lock for cubicle, 405E	**NSYAEDL405K33** New
Optional lock for cubicle, 455E	**NSYAEDL455K33** New

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Seismic and nuclear enclosures

Local seismic standards: Conformity with acceleration severity levels

Standards	Specifications
EDF book of technical rules **CRT 91C11200**	"Large equipment" MRI RRS: **Horizontal:** Floor acceleration = 2 g Amplified max. acceleration at center of gravity = 5 g **Vertical:** Floor acceleration = 2.4 g Amplified max. acceleration at center of gravity = 6 g
EAK 2000 Greece	Seismic risk zone: IV Importance category: S4
ENDESA 1986	All seismic categories Ground acceleration = 0.5 g
RPA 99 2003 Algeria	All types of soil class Ground acceleration factor A = 0.36 Behavior factor R = 2 Quality factor Q = 1.35
Core GR 63	Zone 4
Turkish Seismic Code 2009	All types of site class Importance factor = 1.5 Ground acceleration factor: A0 = 0.4
GOST 17516.1-90 Russia	Civil market: MSK intensity 9, level 3. Nuclear market: MSK intensity 9, level 2.
IEEE 693-2005	High level
Eurocode 8	All soil types agR = 3 m/s² Importance factor = 1.3

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Seismic and nuclear enclosures

Spacial SF 6G for seismic risks

Busbar compartment enclosure, available depths

Height	Width			
	300	400	600	800
2200	-	600	-	-
2000	500 / 600 / 800	400 / 500 / 600 / 800	-	-
1800	-	400 / 500 / 600	-	-
1600	-	-	-	-
1400	-	-	-	-
1200	-	-	-	-

Enclosure equipped with plain mounting plate, available depths

Height	Width			
	300	400	600	800
2200	-	-	600 / 800	600 / 800
2000	-	-	500	500
1800	-	-	400 / 500 / 600 / 800	400 / 500 / 600
1600	-	-	600 / 800	600 / 800
1400	-	-	400	400
1200	-	-	400 / 600	400 / 600

Enclosure equipped with 19" fixed rack, available depths

Height	Width			
	300	400	600	800
2200	-	-	-	800
2000	-	-	-	-
1800	-	-	-	600
1600	-	-	-	800
1400	-	-	-	-
1200	-	-	-	-

Note:
Special dimensions available on demand

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Seismic and nuclear enclosures

Spacial SF 6G for seismic risks

Cut-outs



Top view



Note:
Customization areas guaranteeing 6G resistance

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Seismic and nuclear enclosures

The **Spacial SF 6G** enclosures have been designed to withstand earthquakes corresponding to UBC Zone 4.

Spacial SF 6G for seismic risks

SF

Panel mounting
- 12 fastening points by M6 screws per panel..

Security locking system
- Seismic locking system.
- Special connecting rods and handle to prevent any accidental door opening under severe vibration conditions.

Plinths
- Enhanced mechanical strength (monobloc structure).
- Assembled on the enclosure.
- Floor fixing: 10 fastening points by M12 screws.

Multi-purpose corners
- To strengthen the enclosure and respond to seismic risks.
- To strengthen fastening of the side panels and rear panel.
- To fasten the door connecting rods.

Security locking system
- Seismic locking system.
- Special connecting rods and handle to prevent any accidental door opening under severe vibration conditions.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Seismic and nuclear enclosures

Spacial SFP 5G for seismic risks

Enclosure with plain door

NSYSFP5G20750

- Enclosures designed to be installed in UBC Zone 4.
- Monobloc base to enhance the structure's mechanical strength.
- 2 configurations with devices have been tested: 1600 A and 3200 A.
- Material: Steel
- Ingress protection rating: IP55 according to IEC 60529
- Mechanical protection rating: IK10 according to IEC 62262
- Maximum load: 350 kg for configuration 1800 A, 450 kg for configuration 3200 A
- Standards: IEC 62208 (enclosure) - IEC 60068 (seismic methods to apply for materials)
- Certifications: 5G certification as per CRT 91-C-112-00 (EDF) - UL 508 types 1, 3R, 12

Note:
NB:
- The width (300 mm) of the Spacial SFP 5G cubicle for the busbar duct is not compatible with the Spacial SF 5G cubicle.
- The customer must ensure good cubicle/base connection.

Supply:
Framework
- Reinforcing cross for improved structural strength
- 4 uprights fitted with Rivkle nuts

Characteristics	Configuration (A)	Height (mm)	Width (mm)	Depth (mm)	References
Enclosure with plain door	1600	2000	700	500	**NSYSFP5G20750**
Enclosure with plain door	3200	2000	700	800	**NSYSFP5G20780**

Compartment for busbars with plain door

Characteristics	Configuration (A)	Height (mm)	Width (mm)	Depth (mm)	References
Compartment for busbars with plain door	1600	2000	300	500	**NSYSF5G20350**
Compartment for busbars with plain door	3200	2000	300	800	**NSYSF5G20380**

Side panels

Characteristics	Height (mm)	Depth (mm)	References
Side panels	2000	500	**NSY5G2SP205**
Side panels	2000	800	**NSY5G2SP208**

100 mm plinth

Characteristics	Width (mm)	Depth (mm)	References
100 mm plinth	700	500	**NSYS5GPC75**
100 mm plinth	300	500	**NSYS5GPC35**
100 mm plinth	700	800	**NSYS5GPC78**
100 mm plinth	300	800	**NSYS5GPC38**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Seismic and nuclear enclosures

Spacial SFP 5G for seismic risks

Local seismic standards: Conformity with acceleration severity levels Standards or specifications	Specifications
EDF book of technical rules CRT 91C11200	**Required response spectrum:** **Horizontal:** • Floor acceleration = 1 g • Amplified max. acceleration at center of gravity = 5 g **Vertical:** • Floor acceleration = 0.8 g • Amplified max. acceleration at center of gravity = 4 g
EAK 2000 Greece	Seismic risk zone: IV Importance category: S4
ENDESA 1986	All seismic categories Ground acceleration = 0.5 g
RPA 99 2003 Algeria	All types of soil class Ground acceleration factor A = 0.36 Behavior factor R = 2 Quality factor Q = 1.35
Core GR 63	Zone 4
Turkish Seismic Code 2009	All types of site class Importance factor = 1.5 Ground acceleration factor: A0 = 0.4
GOST 17516.1-90 Russia	Civil market: MSK intensity 9, level 2. Nuclear market: MSK intensity 9, level0.
IEEE 693-2005	High level
Eurocode 8	All soil types agR = 3 m/s² Importance factor = 1.3

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Seismic and nuclear enclosures

SF enclosures for seismic risks Compatibility of accessories

Accessories Trade references impacted	Description	SF 6G compatibility	SFP 5G compatibility (Prisma system)	Comments
NSYSDT●	Folding mounting shelf	Please contact us	Compatible	• Depends on size
NSYSDP●M	Metal document holder	Please contact us	Compatible	Depends on size
NSYDPA●●	Plastic document holder	Compatible	Compatible	-
NSYMP●●●	Mounting plate	Compatible	-	Position 200 mm mini from the rear panel
NSYSUCR●●	Universal cross rail	Compatible	-	-
NSYSQCR●●	Quick cross rail	Compatible	-	-
NSYSICR●●	Integrated cross rail	Compatible	-	-
NSYHLCR●●	Cross rail for heavy loads	Compatible	-	-
NSYSLCR●●	Light cross rail	Compatible	-	-
NSYFXT●●●●	Fixed Trays	Compatible	-	-
NSYSPMP●	Partial plain mounting plate	Compatible	-	-
NSYSTMP●●	Telequick mounting plate	Compatible	-	-
NSYSDCR●●	Door cable-guide cross rail	Compatible	Compatible	Select the smaller-sized cross rail

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Seismic and nuclear enclosures

Spacial S3D 6G cubicles are designed to withstand earthquakes up to UBC zone 4.

Strength

Panel thickness:

- Casing + door: 20/10 mm;
- Entry flange: 15/10 mm.

Reinforced mounting plate

- Mounting plate reinforcement.
- Increased number of attachment points.

Security locking system

- EDF 1600 security locking system with captive key.

Wall mounting

- Reinforced bracket for wall mounting.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Seismic and nuclear enclosures

Spacial S3D 6G solutions for seismic risks

- Seismic applications up to UBC zone 4.
- Material: Steel
- Ingress protection rating: IP65 according to IEC 60529
- Mechanical protection rating: IK10 according to IEC 62262
- Maximum load: 80 kg/m² on plain mounting plate, 250 kg on 19" fixed uprights in compliance with the IEC 61587-2 standard
- Standards: IEC 62208 (enclosure) - IEC 60068-3-3 (seismic methods to apply for materials)
- Certifications: 6G certification as per CRT 91-C-112-00 (EDF)

Supply:
Body
- Monobloc casing (cross structure). Gutter-shaped front profile. Flat back
- M6 x 16 earthing screws and earth strap for equipotential connection between the cubicle door and casing
- Entry flange
- Maximum load: 10 kg

Door
- Plain door with EDF 1600 captive key lock
  - H < 600: 1 fastening point
  - H ≥ 600: 3 fastening points
- Non-reversible door (for reversibility, please contact us)
- M6 x 16 earthing screws and earth strap for equipotential connection between the cubicle door and casing
- 120° door opening
- Maximum load: 10 kg

Mounting plate
- Mounting plate galvanized before mounting
- Maximum load: 80 kg/m²
- Two wall mounting brackets

NSYS3D6G32515P

Characteristics	Height (mm)	Width (mm)	Depth (mm)	References
Spacial S3D seismic plain door with mount.plate	300	250	150	**NSYS3D6G32515P**
Spacial S3D seismic plain door with mount.plate	400	300	200	**NSYS3D6G4320P**
Spacial S3D seismic plain door with mount.plate	600	500	250	**NSYS3D6G6525P**
Spacial S3D seismic plain door with mount.plate	700	500	250	**NSYS3D6G7525P**
Spacial S3D seismic plain door with mount.plate	800	600	300	**NSYS3D6G8630P**
Spacial S3D seismic plain door with mount.plate	1200	800	400	**NSYS3D6G12840P**

Locks for cubicle

- ≤ H 600
- With captive key.
- Material: Zamak lock and metal cam

Supply:
1- or 3-point lock with 1 lock button and 1 cremone bolt

NSYAEDLEDF9K31

Characteristics	Key lock	References
Lock for cubicle	EDF 900	**NSYAEDLEDF9K31**
Lock for cubicle	EDF 1300	**NSYAEDLEDF13K31**
Lock for cubicle	EDF 1400	**NSYAEDLEDF14K31**
Lock for cubicle	1242E	**NSYAEDL1242K31**
Lock for cubicle	405E	**NSYAEDL405K31**
Lock for cubicle	455E	**NSYAEDL455K31**

Locks for cubicle

- > H 600
- With captive key.
- Material: Polyamide handle, metal connecting rods and cam

Supply:
3-point lock with 1 lock button and 1 cremone bolt

NSYAEDLEDF9K33

Characteristics	Key lock	References
Lock for cubicle	EDF 900	**NSYAEDLEDF9K33**
Lock for cubicle	EDF 1300	**NSYAEDLEDF13K33**
Lock for cubicle	EDF 1400	**NSYAEDLEDF14K33**
Lock for cubicle	1242E	**NSYAEDL1242K33**
Lock for cubicle	405E	**NSYAEDL405K33**
Lock for cubicle	455E	**NSYAEDL455K33**

Padlocking lug

- Securing of cubicle access.
- Material: White galvanized steel

NSYAEDLPADS3DK3

Characteristics	References
Padlocking lug	**NSYAEDLPADS3DK3**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Seismic and nuclear enclosures

Local seismic standards: Conformity with acceleration severity levels

Standards	Specifications
EDF book of technical rules CRT 91C11200	**Large equipment" MRI RRS:** **Horizontal:** • Floor acceleration = 2 g • Amplified max. acceleration at center of gravity = 5 g **Vertical:** • Floor acceleration = 2.4 g • Amplified max. acceleration at center of gravity = 6 g
EAK 2000 Greece	Seismic risk zone: IV Importance category: S4
ENDESA 1986	All seismic categories Ground acceleration = 0.5 g
RPA 99 2003 Algeria	All types of soil class Ground acceleration factor A = 0.36 Behavior factor R = 2 Quality factor Q = 1.35
Core GR 63	Zone 4
Turkish Seismic Code 2009	All types of site class Importance factor = 1.5 Ground acceleration factor: A0 = 0.4
GOST 17516.1-90 Russia	Civil market: MSK intensity 9, level 3. Nuclear market: MSK intensity 9, level 2.
IEEE 693-2005	High level
Eurocode 8	All soil types agR = 3 m/s² Importance factor = 1.3

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Table of Compatibility of accessories in 6G seismic S3D cubicles

Accessories		Compatibility	Comments	Trade references impacted
	19" rack	Limited	Conditions: Drilling by customization department to be provided for	**NSYVDM●●●●**
	Door switch	Limited	Conditions: Drilling by customization department to be provided for	**NSYINLCRN**
	Diagram holder	Yes	-	**NSYDPA●●**
	Lifting rings	Limited	Conditions: Drilling by customization department to be provided for	**NSYAELYTCRG8**

Comment: None of the accessories is certified 6G.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

The Spacial S3D 6G K3 cubicle meets K3 requirements in accordance with RCCE 2012.

Strength

Panel thickness:

- Casing + door: 20/10 mm;
- Entry flange: 15/10 mm.

Reinforced mounting plate

- Mounting plate reinforcement.
- Increased number of attachment points.

Decontaminatable smooth paint, PID 100 series

- In compliance with CCTR 91.C.031.06 Two coats of paint (minimum thickness: 60 µ).
- Epoxy polyester powder, PID 100 series.
- PIA-PIC 100 on request.



Earth continuit

- Earth continuity between the interior and exterior of the cubicle is provided by 2 opposite welded studs (external earth screw principle).



Security locking system

- EDF 1600 security locking system with captive key.

Wall mounting

- Reinforced bracket for wall mounting.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Seismic and nuclear enclosures

Spacial S3D 6G K3 solutions for nuclear applications

Seismic application for nuclear power station.
- Material: Steel
- Ingress protection rating: IP65 according to IEC 60529
- Mechanical protection rating: IK10 according to IEC 62262
- Standards: IEC 62208 - IEC 60068-3-3 (seismic methods to apply for materials)
- Certifications: 6G certification as per CRT 91-C-112-00 (EDF)
- Meets K3 requirements in accordance with RCCE 2012
- EDF reference documents:
- CCTR paint and FNP file;
- RCC-E: Electrical equipment construction code;
- Packaging technical specification;
- "PMUC" (products and materials used in nuclear generating stations)

Supply:
Body
- Monobloc casing (cross structure). Gutter-shaped front profile. Flat back
- M6 x 16 earthing screws and earth strap for equipotential connection between the cubicle door and casing
- Entry flange
- Maximum load: 10 kg

Door
- Plain door with EDF 1600 captive key lock
  - H < 600: 1 fastening point
  - H ≥ 600: 3 fastening points
- Non-reversible door (for reversibility, please contact us)
- M6 x 16 earthing screws and earth strap for equipotential connection between the cubicle door and casing
- 120° door opening
- Maximum load: 10 kg

Mounting plate
- Mounting plate galvanized before mounting
- Maximum load: 80 kg/m²
- Two wall mounting brackets

NSYS3D32515PK3

Characteristics	Height (mm)	Width (mm)	Depth (mm)	References
Spacial S3D seismic plain door with mount.plate	300	250	150	**NSYS3D32515PK3**
Spacial S3D seismic plain door with mount.plate	400	300	200	**NSYS3D4320PK3**
Spacial S3D seismic plain door with mount.plate	600	500	250	**NSYS3D6525PK3**
Spacial S3D seismic plain door with mount.plate	700	500	250	**NSYS3D7525PK3**
Spacial S3D seismic plain door with mount.plate	800	600	300	**NSYS3D8630PK3**
Spacial S3D seismic plain door with mount.plate	1200	800	400	**NSYS3D12840PK3**

Locks for cubicle

- ≤ H 600
- With captive key.
- Material: Zamak lock and metal cam

Supply:
1- or 3-point lock with 1 lock button and 1 cremone bolt

NSYAEDLEDF9K31

Characteristics	Key lock	References
Lock for cubicle	EDF 900	**NSYAEDLEDF9K31**
Lock for cubicle	EDF 1300	**NSYAEDLEDF13K31**
Lock for cubicle	EDF 1400	**NSYAEDLEDF14K31**
Lock for cubicle	1242E	**NSYAEDL1242K31**
Lock for cubicle	405E	**NSYAEDL405K31**
Lock for cubicle	455E	**NSYAEDL455K31**

Locks for cubicle

- > H 600
- With captive key.
- Material: Polyamide handle, metal connecting rods and cam

Supply:
3-point lock with 1 lock button and 1 cremone bolt

NSYAEDLEDF9K33

Characteristics	Key lock	References
Lock for cubicle	EDF 900	**NSYAEDLEDF9K33**
Lock for cubicle	EDF 1300	**NSYAEDLEDF13K33**
Lock for cubicle	EDF 1400	**NSYAEDLEDF14K33**
Lock for cubicle	1242E	**NSYAEDL1242K33**
Lock for cubicle	405E	**NSYAEDL405K33**
Lock for cubicle	455E	**NSYAEDL455K33**

Padlocking lug

- Securing of cubicle access.
- Material: White galvanized steel

NSYAEDLPADS3DK3

Characteristics	References
Padlocking lug	**NSYAEDLPADS3DK3**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Seismic and nuclear enclosures

Table of Compatibility of accessories in 6G seismic S3D cubicles

Accessories		Compatibility	Comments	Trade references impacted
	19" rack	Limited	Conditions: Drilling by customization department to be provided for	**NSYVDM●●●●**
	Door switch	Limited	Conditions: Drilling by customization department to be provided for	**NSYINLCRN**
	Diagram holder	Yes	-	**NSYDPA●●**
	Lifting rings	Limited	Conditions: Drilling by customization department to be provided for	**NSYAELYTCRG8**

Comment: None of the accessories is certified 6G.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Seismic and nuclear enclosures

Special dimensions

Height	Width					
	250	300	400	500	600	800
1200	-	-	-	-	200/250/300/400	200/250/300/400
1000	-	-	-	-	200/250/300/400	200/250/300/400
800	-	-	200/250/300	200/250/300	200/250/400	200/250/300
700	-	-	200/250/300	200/300	200/250/300/400	-
600	-	-	200/250/300	200/300	200/250/300/400	-
500	200	150/200/250	200/250/300	200/250/300	-	-
400	150/200	150/250	-	-	-	-
300	150/200	150/200/250	-	-	-	-

Note:
We meet the K3 requirements as per RCCE 2012 for the special dimensionsmentioned below. These dimensions appear in the Reference File.

Cut-outs

Customization areas ensuring K3 certification

Door



Entry flange



Depth	A
150	65
200	82
250	98
300	115
400	148

Casing

Bottom view



Hinge side view



Closing lock side view



Top view



Note:
We meet the K3 requirements as per RCCE 2012 for the cut-outs mentioned below.These cut-outs appear in the Reference File.

11

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Seismic and nuclear enclosures

Paints

AFNOR / RAL	Colors of PIA-PID 100 series	Colors of PIC 100 series
AFNOR	1550	1550
AFNOR	1570	1570
AFNOR	2550	2550
AFNOR	2570	2570
RAL	1003	1003
RAL	5005	5005
RAL	5024	5024
RAL	7036	7036

Note:
Referencing of the following paints in the FNP (national paint file):
Others colors available: Consult us.

Packaging

Note:
We can produce a special corrosion protection packaging (Gardac type).

S3D



Our range of Spacial 3D nuclear cubicles meets the K3 requirements of RCCE 2012. The Schneider Electric cubicle production plant has established processes to ensure K3 certification.

Establishment of a line architecture adapted to the requirements mentioned in RCCE 2012, implying:

- Hold points;
- Check points;
- Control of "AIP" activities that are important for protection

Manufacturing completion report with:

- Declaration of conformity.
- Monitoring document.
- Report and test report.

Establishment of a Particular Quality Assurance Plan (PQAP)

Reference documents for the nuclear industry:

- RCC-E, CCTR, FNP, packaging technical specification, "PMUC" (products and materials used in nuclear generating stations), SGAQ-2013-03, Arrêté INB 2012

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Seismic and nuclear enclosures

S3D

Nuclear safety has 3 objectives

Control reactivity	Cool the fuel	Confine radioactive products

Technical choices and safety rules

The technical choices and safety rules are stipulated by the operator with full responsibility relative to the French nuclear safety authority (ASN) (representing the state) depending on the location in the installation and whether or not they form part of the safety circuits. The products undergo tests to ensure their operation in accidental conditions.

A safety circuit consists of several equipment items. Their certification depends on their location. Equipment interfacing between the core and the other buildings is always K1 (risk of radioactive leakage).



Certifications necessary to work in the nuclear industry

2 certifications are necessary to work in the nuclear industry

1• Product and equipment certifications imply demanding performances validated by technical documents and by tests. In the event of a change in the product, it must be explained and justified that the initial certification is maintained.

2• Certifications of industrial organizations and services related to products and equipment.

The products equipping French nuclear facilities in this catalogue comply with the RCC-E 2012 standard.

Terminology of equipment classifications used in nuclear power stations



EIP: Equipment Important for Protection.
IPDE: Important for operating availability.
CDS: Safety-classified.
Schneider is concerned only by E1 (elec. classification).

Tests corresponding to specific classifications for EIP equipment

- K3 > ref. tests + functional operating limits + ageing + earthquake
- K3AD > K3 + environmental resistance (irradiation, heat, spraying)
- K2 > K3 + resistance to ageing irradiation (250 Kgy)
- K1 > K2 + resistance to accidental irradiation (600 Kgy) + ADR
- AG > K1 reinforced only for EPR power stations

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Electronic application

Spacial VDM

This range can be configured according to your needs

4 differents services available

Assemble to order

Mounting of standard accessories

Painting

Machining

Spacial SF



Spacial S3D



Practical

- Cable gland plates at top and bottom:
- on the rear part (2-body enclosure),
- on the body (1-body enclosure).

Simplified installation

- Pre-installed fixed or swing rack; Earth connection placed between the door and the body; The enclosure is ready to use; The cardboard packaging can be reused after cabling.



Suitable metal enclosure

- Enclosure prepared for the installation of standard 19" racks in professional telecommunication, voice, data and electronic facilities, by means of 19" fixed and swing racks, see **page 462**.

See page 532 for details or consult our web site www.se.com

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Electronic application

Spacial VDM 19"

- Single-piece body, folded and welded.
  Front rail with double sheet thickness, gutter-shaped.
- Perforated rails on the door, with drill holes of Ø 4.2 mm in steps of 25 mm.
- Transparent door, Securit® glass, easily removable and reversible, with 20 mm return with double thickness granting excellent rigidity, opening to 120°, equipped with 2 or 3 invisible hinges. Three closure points for heights of more than 600 mm.
- Polyurethane gasket.
- 6 mm² earth connection placed between the door and the body of the enclosure.
- Material: Steel
- Finish: Structured finish, epoxi-polyester powder
- Colour: RAL 7035 grey
- Ingress protection rating: IP66 according to IEC 60529
- Mechanical protection rating: IK08 according to IEC 62262

Supply:
Wall-mounting enclosure supplied with 3 mm double bar lock as standard

Fixed rack

NSYVDM5U4F

- Maximum load: 3 kg per unit

Characteristics	Number of U	Height (mm)	Width (mm)	Depth (mm)	References
Fixed rack, 1-body	5	300	600	400	**NSYVDM5U4F**
Fixed rack, 1-body	8	400	600	400	**NSYVDM8U4F**
Fixed rack, 1-body	10	500	600	400	**NSYVDM10U4F**
Fixed rack, 1-body	14	700	600	400	**NSYVDM14U4F**
Fixed rack, 1-body	17	800	600	400	**NSYVDM17U4F**

Swing rack

Other characteristics:
- Enclosure in 2 pieces: Body + door
- Cable gland plate at the bottom of the enclosure
- Fixed rack depth-adjustable in steps of 25 mm using the step slides

NSYVDM4U4P

- Maximum load: 3 kg per unit

Characteristics	Number of U	Height (mm)	Width (mm)	Depth (mm)	References
Swing rack, 1-body	4	300	600	400	**NSYVDM4U4P**
Swing rack, 1-body	7	400	600	400	**NSYVDM7U4P**
Swing rack, 1-body	9	500	600	400	**NSYVDM9U4P**
Swing rack, 1-body	13	700	600	400	**NSYVDM13U4P**
Swing rack, 1-body	16	800	600	400	**NSYVDM16U4P**

Fixed rack

Other characteristics:
Rear
- Depth: 150 mm
- Internal attachment point for fixing various supports
- Hinges and locking system with the body
- Cable gland plate at the top and bottom on the rear part

Body
- Usable depth of 183 or 283 mm
- Two 19" uprights made from treated steel, installed 65 mm back from the front panel
- Intermediate body installed on the rear with 120° hinge

NSYVD2M5U4

- Maximum load: 2 kg per unit

Characteristics	Number of U	Height (mm)	Width (mm)	Depth (mm)	References
Fixed rack, 2-bodies	5	300	600	380	**NSYVD2M5U4**
Fixed rack, 2-bodies	5	300	600	480	**NSYVD2M5U5**
Fixed rack, 2-bodies	8	400	600	380	**NSYVD2M8U4**
Fixed rack, 2-bodies	8	400	600	480	**NSYVD2M8U5**
Fixed rack, 2-bodies	10	500	600	380	**NSYVD2M10U4**
Fixed rack, 2-bodies	10	500	600	480	**NSYVD2M10U5**
Fixed rack, 2-bodies	14	700	600	380	**NSYVD2M14U4**
Fixed rack, 2-bodies	14	700	600	480	**NSYVD2M14U5**
Fixed rack, 2-bodies	17	800	600	380	**NSYVD2M17U4**
Fixed rack, 2-bodies	17	800	600	480	**NSYVD2M17U5**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Electronic application

Spacial S3D Empty enclosure

- Single-piece body (cross-shaped structure). Gutter-shaped front profile with double fold. Flat rear.
- Cable gland plate with marking for easy drilling and to guarantee the maximum access surface; Delivered with the enclosure. This plate is flush with the body of the enclosure.
- Glazed door, 4 mm-thick Securit® glass, easily removable and reversible, with 20 mm return with double thickness granting excellent rigidity, opening to 120°, equipped with 2 or 3 invisible hinges (From the height of 800 mm).
- Material: Steel
- Finish: Structured finish, epoxy polyester powder
- Colour: RAL 7035 grey
- Ingress protection rating according to IEC 60529: IP66 for the single-door enclosures, IP55 for the double door enclosures
- Mechanical protection rating according to IEC 62262: IK10 for the plain-door enclosures, IK08 for the glazed-door enclosures
- Maximum load: 50 kg/m²
- Fixing: Direct wall-mounting (4 Ø 10 holes for the sealing plugs guaranteeing the IP) or with the help of fixing lugs installed from the outside (to be ordered separately, see page 51)
- Other characteristics: For heights from 600 mm, three locking points with linkage, with a single control point. Simple reversal of linkage

A handle is delivered which provides 2 functions:

- operating key
- tool for loosening the stud protection caps.

This handle can be solidly attached to the locking system by means of a captive element
Perforated rails on the door, with drill holes with a diameter of 4.2 mm in steps of 25 mm:

- 2 vertical rails from the height of 400 mm
- 2 vertical rails and 2 horizontal rails from the width of 800 mm

Note:
Door opening to 180°
with optional hinges (page 60)

Supply:
Wall-mounting enclosure supplied with 3 mm double bar lock as standard

Glazed door

NSYS3D4620T

Characteristics	Fixed rack	Swing rack	Height (mm)	Width (mm)	Depth (mm)	References
Glazed door	NSYVDM8UF	NSYVDM7UP	400	600	200	**NSYS3D4620T**
Glazed door	NSYVDM8UF	NSYVDM7UP	400	600	250	**NSYS3D4625T**
Glazed door	NSYVDM12UF	NSYVDM11UP	600	600	200	**NSYS3D6620T**
Glazed door	NSYVDM12UF	NSYVDM11UP	600	600	250	**NSYS3D6625T**
Glazed door	NSYVDM12UF	NSYVDM11UP	600	600	300	**NSYS3D6630T**
Glazed door	NSYVDM12UF	NSYVDM11UP	600	600	400	**NSYS3D6640T**
Glazed door	NSYVDM17UF	NSYVDM16UP	800	600	200	**NSYS3D8620T**
Glazed door	NSYVDM17UF	NSYVDM16UP	800	600	250	**NSYS3D8625T**
Glazed door	NSYVDM17UF	NSYVDM16UP	800	600	300	**NSYS3D8630T**
Glazed door	NSYVDM17UF	NSYVDM16UP	800	600	400	**NSYS3D8640T**
Glazed door	NSYVDM21UF	NSYVDM20UP	1000	600	250	**NSYS3D10625T**
Glazed door	-	-	1000	600	300	**NSYS3D10630T**
Glazed door	NSYVDM21UF	NSYVDM20UP	1000	600	400	**NSYS3D10640T**
Glazed door	-	NSYVDM20U8P	1000	800	250	**NSYS3D10825T**
Glazed door	-	NSYVDM20U8P	1000	800	300	**NSYS3D10830T**
Glazed door	-	NSYVDM20U8P	1000	800	400	**NSYS3D10840T**
Glazed door	-	NSYVDM25U8P	1200	800	300	**NSYS3D12830T**
Glazed door	-	NSYVDM25U8P	1200	800	400	**NSYS3D12840T**

Plain door

NSYS3D4620

Characteristics	Fixed rack	Swing rack	Height (mm)	Width (mm)	Depth (mm)	References
Plain door	NSYVDM8UF	NSYVDM7UP	400	600	200	**NSYS3D4620**
Plain door	NSYVDM8UF	NSYVDM7UP	400	600	250	**NSYS3D4625**
Plain door	NSYVDM12UF	NSYVDM11UP	600	600	200	**NSYS3D6620**
Plain door	NSYVDM12UF	NSYVDM11UP	600	600	250	**NSYS3D6625**
Plain door	NSYVDM12UF	NSYVDM11UP	600	600	300	**NSYS3D6630**
Plain door	NSYVDM12UF	NSYVDM11UP	600	600	400	**NSYS3D6640**
Plain door	NSYVDM17UF	NSYVDM16UP	800	600	200	**NSYS3D8620**
Plain door	NSYVDM17UF	NSYVDM16UP	800	600	250	**NSYS3D8625**
Plain door	NSYVDM17UF	NSYVDM16UP	800	600	300	**NSYS3D8630**
Plain door	NSYVDM17UF	NSYVDM16UP	800	600	400	**NSYS3D8640**
Plain door	NSYVDM21UF	NSYVDM20UP	1000	600	250	**NSYS3D10625**
Plain door	-	-	1000	600	300	**NSYS3D10630**
Plain door	NSYVDM21UF	NSYVDM20UP	1000	600	400	**NSYS3D10640**
Plain door	-	NSYVDM20U8P	1000	800	250	**NSYS3D10825**
Plain door	-	NSYVDM20U8P	1000	800	300	**NSYS3D10830**
Plain door	-	NSYVDM20U8P	1000	800	400	**NSYS3D10840**
Plain door	-	NSYVDM25U8P	1200	800	300	**NSYS3D12830**
Plain door	-	NSYVDM25U8P	1200	800	400	**NSYS3D12840**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Electronic application

Spacial S3D Fixed rack (The racks are to be ordered separately)

- 19" fixed chassis composed by 2 19" uprights with fixing hardware.
- Thickness: 20/10e mm.
- Material: Galvanized steel
- Maximum load: 3 kg per unit

Note:
Adjustable in depth by fixing on the step slides in accessories (see page 48).

NSYVDM8UF

Characteristics	Number of U	Height (mm)	Width (mm)	Depth (mm)	References
Fixed rack	8	400	600	200	**NSYVDM8UF**
Fixed rack	8	400	600	250	**NSYVDM8UF**
Fixed rack	12	600	600	200	**NSYVDM12UF**
Fixed rack	12	600	600	250	**NSYVDM12UF**
Fixed rack	12	600	600	300	**NSYVDM12UF**
Fixed rack	12	600	600	400	**NSYVDM12UF**
Fixed rack	17	800	600	200	**NSYVDM17UF**
Fixed rack	17	800	600	250	**NSYVDM17UF**
Fixed rack	17	800	600	300	**NSYVDM17UF**
Fixed rack	17	800	600	400	**NSYVDM17UF**
Fixed rack	21	1000	600	250	**NSYVDM21UF**
Fixed rack	21	1000	600	400	**NSYVDM21UF**

Spacial S3D Swing rack (The racks are to be ordered separately)

- 19" swing chassis opening to 120° with closure by 3 mm double bar insert.
- Material: Steel
- Finish: Epoxy polyester powder
- Colour: RAL 7035 grey
- Maximum load: 3 kg per unit

NSYVDM7UP

Characteristics	Number of U	Height (mm)	Width (mm)	Depth (mm)	References
Swing rack	7	400	600	200	**NSYVDM7UP**
Swing rack	7	400	600	250	**NSYVDM7UP**
Swing rack	11	600	600	200	**NSYVDM11UP**
Swing rack	11	600	600	250	**NSYVDM11UP**
Swing rack	11	600	600	300	**NSYVDM11UP**
Swing rack	11	600	600	400	**NSYVDM11UP**
Swing rack	16	800	600	200	**NSYVDM16UP**
Swing rack	16	800	600	250	**NSYVDM16UP**
Swing rack	16	800	600	300	**NSYVDM16UP**
Swing rack	16	800	600	400	**NSYVDM16UP**
Swing rack	20	1000	600	250	**NSYVDM20UP**
Swing rack	20	1000	600	400	**NSYVDM20UP**
Swing rack	20	1000	800	250	**NSYVDM20U8P**
Swing rack	20	1000	800	300	**NSYVDM20U8P**
Swing rack	20	1000	800	400	**NSYVDM20U8P**
Swing rack	25	1200	800	300	**NSYVDM25U8P**
Swing rack	25	1200	800	400	**NSYVDM25U8P**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Electronic application

Spacial SF 19" electronic enclosure

- Structure: Top and bottom frame and vertical uprights.
- Transparent front door with Securit® glass.
- Plain rear door.
- Standard locking system with handle and 5 mm double bar insert.
- Removable roof.
- External fixing side panels double folded to increase their rigidity with captive fixing screws that reduce installation time.
- In enclosures with widths of 600 and 800 mm, it is possible to install fixed or swing racks, to be ordered separately.
- Material: Steel
- Finish: Structured finish, epoxy polyester powder
- Colour: RAL 7035 grey
- Certifications: UL 508A Types 1, 12 and CUL

For more details see page 470



NSYSF12660E

Characteristics	Height (mm)	Width (mm)	Depth (mm)	References
Spacial SF 19" electronic enclosur	1200	600	600	**NSYSF12660E**
Spacial SF 19" electronic enclosur	1200	600	800	**NSYSF12680E**
Spacial SF 19" electronic enclosur	1200	800	600	**NSYSF12860E**
Spacial SF 19" electronic enclosur	1200	800	800	**NSYSF12880E**
Spacial SF 19" electronic enclosur	2000	600	600	**NSYSF20660E**
Spacial SF 19" electronic enclosur	2000	600	800	**NSYSF20680E**
Spacial SF 19" electronic enclosur	2000	800	600	**NSYSF20860E**
Spacial SF 19" electronic enclosur	2000	800	800	**NSYSF20880E**
Spacial SF 19" electronic enclosur	2000	800	1000	**NSYSF208100E**
Spacial SF 19" electronic enclosur	2200	600	600	**NSYSF22660E**
Spacial SF 19" electronic enclosur	2200	600	800	**NSYSF22680E**
Spacial SF 19" electronic enclosur	2200	600	1000	**NSYSF226100E**
Spacial SF 19" electronic enclosur	2200	800	600	**NSYSF22860E**
Spacial SF 19" electronic enclosur	2200	800	800	**NSYSF22880E**
Spacial SF 19" electronic enclosur	2200	800	1000	**NSYSF228100E**

Single ventilated door for 19" racks

- Door designed to achieve natural ventilation of the enclosure.
- Installation on enclosures with a width of 800 mm, equipped with centred fixed or swing racks. Opening of 120°.
- Standard locking system with handle and 5 mm double bar insert.
- Material: Steel
- Finish: Structured finish, epoxy polyester powder
- Colour: RAL 7035 grey

Supply:
1 ventilated door for racks

NSYPCVD126

Characteristics	Height (mm)	Width (mm)	References
Single ventilated door	1200	600	**NSYPCVD126**
Single ventilated door	1200	800	**NSYPCVD128**
Single ventilated door	1400	800	**NSYPCVD148**
Single ventilated door	1600	800	**NSYPCVD168**
Single ventilated door	1800	800	**NSYPCVD188**
Single ventilated door	2000	600	**NSYPCVD206**
Single ventilated door	2000	800	**NSYPCVD208**
Single ventilated door	2200	600	**NSYPCVD226**
Single ventilated door	2200	800	**NSYPCVD228**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Electronic application

Front and rear plinths

- The front and rear of the plinth consists of 4 corners with 2 or 4 panels.
- Material: Folded sheet steel, corner with a thickness of 25/10e mm
- Finish: Epoxy polyester paint
- Colour: RAL 7022 grey
- Ingress protection rating: IP30 according to IEC 60529
- Mechanical protection rating: IK10 according to IEC 62262

Note:
For more information, see page 96

Supply:
Height 100 mm: 4 corners, 2 panels (front and rear), 4 corner covers and fixing elements. Height 200 mm: 4 corners, 4 panels (2 front and 2 rear), 4 corner covers and fixing elements

NSYSPF6100

NSYSPF6200

Characteristics	Width (mm)	Height (mm)	References
Front plinths for Spacial	600	100	**NSYSPF6100**
Front plinths for Spacial	800	100	**NSYSPF8100**
Front plinths for Spacial	600	200	**NSYSPF6200**
Front plinths for Spacial	800	200	**NSYSPF8200**

Plinth side panels

- They are fixed to the corner of the plinth by 2 fixing screws.
- Folded sheet steel
- Finish: Epoxy polyester paint
- Colour: RAL 7022 grey
- Ingress protection rating: IP30 according to IEC 60529
- Mechanical protection rating: IK10 according to IEC 62262

Supply:
Height 100 mm: 2 side panels, 4 corner covers and fixing elements. Height 200 mm:
4 side panels (height of 100 mm, 2 for each side), 4 corner covers and fixing elements

NSYSPS6100

NSYSPS6200

Characteristics	Depth (mm)	Height (mm)	References
Side plinths for Spacial	600	100	**NSYSPS6100**
Side plinths for Spacial	800	100	**NSYSPS8100**
Side plinths for Spacial	1000	100	**NSYSPS10100**
Side plinths for Spacial	600	100	**NSYSPS6100**
Side plinths for Spacial	800	100	**NSYSPS8100**
Side plinths for Spacial	1000	100	**NSYSPS10100**
Side plinths for Spacial	600	200	**NSYSPS6200**
Side plinths for Spacial	800	200	**NSYSPS8200**
Side plinths for Spacial	1000	200	**NSYSPF10200**
Side plinths for Spacial	600	200	**NSYSPS6200**
Side plinths for Spacial	800	200	**NSYSPS8200**
Side plinths for Spacial	1000	200	**NSYSPF10200**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Electronic application

Ventilated front plinth

- The front and rear of the ventilated plinth is made up of 4 corners with 2 front panels.
- Material: Folded sheet steel, corner with a thickness of 25/10e mm
- Finish: Structured finish, epoxy polyester powder
- Colour: RAL 7022 grey
- Ingress protection rating: IP20 according to IEC 60529
- Mechanical protection rating: IK10 according to IEC 62262

Supply:
Height 100 mm: 4 corners, 2 ventilated panels (front and rear), 4 corner covers and fixing elements

NSYSPFV6100

Characteristics	Height (mm)	Width (mm)	References
Ventilated front plinth for Spacial SF-SM	100	600	**NSYSPFV6100**
Ventilated front plinth for Spacial SF-SM	100	800	**NSYSPFV8100**

Ventilated side panels

- They are fixed to the corner of the plinth by fixing screws.
- Material: Folded sheet steel
- Finish: Structured finish, epoxy polyester powder
- Colour: RAL 7022 grey
- Ingress protection rating: IP20 according to IEC 60529
- Mechanical protection rating: IK10 according to IEC 6226

Supply:
Height 100 mm: 2 ventilated side panels, 4 corner covers and fixing elements

NSYSPV6100

Characteristics	Height (mm)	Depth (mm)	References
Ventilated side panels for Spacial SF-SM	100	600	**NSYSPV6100**
Ventilated side panels for Spacial SF-SM	100	800	**NSYSPV8100**

Plain cable gland plate



- The design of the compact cable gland plate, coupled with the use of the sealing gasket **NSYCEK** enable the maximum dust/water tightness.
- Material: Galvanised steel
- Thicknesses: 15/10e mm

Supply:
Plain plate and fixing elements


NSYEC66

Characteristics	(B) Width (mm)	(C) Depth (mm)	References
Spacial SF Plain cable gland plate	600	600	**NSYEC66**
Spacial SF Plain cable gland plate	600	800	**NSYEC68**
Spacial SF Plain cable gland plate	600	1000	**NSYEC610**
Spacial SF Plain cable gland plate	800	600	**NSYEC86**
Spacial SF Plain cable gland plate	800	800	**NSYEC88**
Spacial SF Plain cable gland plate	800	1000	**NSYEC810**

Plate with 1 entry



Enclosures of 300 and 400 mm width.



Enclosures of 600, 800, 1000 and 1200 mm width.

Supply:
Plate with 1 entry; Self-extinguishing polyurethane adhesive gasket with cross-section of 15 x 25 mm (guarantees good sealing) and fixing elements

- Facilitates the entry of cables thanks to a longitudinal opening.
- Material: Galvanised steel
- Thicknesses: 15/10e mm

NSYEC661

Characteristics	(B) Width (mm)	(C) Depth (mm)	References
Spacial SF Plate with 1 entry	600	600	**NSYEC661**
Spacial SF Plate with 1 entry	600	800	**NSYEC681**
Spacial SF Plate with 1 entry	600	1000	**NSYEC6101**
Spacial SF Plate with 1 entry	800	600	**NSYEC861**
Spacial SF Plate with 1 entry	800	800	**NSYEC881**
Spacial SF Plate with 1 entry	800	1000	**NSYEC8101**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Life Is On Schneider Electric

Electronic application

Plate with 2 entries



- Cable entry for very deep enclosures (600 and 800 mm).
- Two longitudinal openings allowing a large number of cables through.
- Material: Galvanised steel
- Thicknesses: 15/10^{e} mm

Supply:
1 plate with 2 entries; Polyurethane adhesiv gasket with cross-section of 15 x 25 mm (guarantee good sealing) and fixing elements

NSYEC662

Characteristics	(B) Width (mm)	(C) Depth (mm)	References
Spacial SF Plate with 2 entries	600	600	**NSYEC662**
Spacial SF Plate with 2 entries	600	800	**NSYEC682**
Spacial SF Plate with 2 entries	600	1000	**NSYEC6102**
Spacial SF Plate with 2 entries	800	600	**NSYEC862**
Spacial SF Plate with 2 entries	800	800	**NSYEC882**
Spacial SF Plate with 2 entries	800	1000	**NSYEC8102**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Electronic application

Actassi plain plate for roof

- Removable plate made from folded sheet steel, to be installed on roof ref. **NSYSRSYS8•**.
- Option of installing roof elevators for aeration, ref. **NSYEX206**, and cable glands.
- Material: Steel
- Finish: Structured finish, epoxy polyester powder
- Colour: RAL 7035 grey

Supply:
1 plain plate and fixing elements

Characteristics	References
Actassi plain plate for roof	**NSYTSPC450**

NSYTSPC450

Actassi plate with brush gasket for roof

- Removable folded sheet steel plate, equipped with a gasket with cable gland brush, to be installed on roof ref. **NSYSRSYS8•**.
- Optional installation of roof elevators for aeration, ref. **NSYEX206**, and cable gland plates.
- Material: Steel
- Finish: Structured finish, epoxy polyester powder
- Colour: RAL 7035 grey

Supply:
1 plate with brush gasket and fixing elements

Characteristics	References
Actassi plate with brush gasket for roof	**NSYTSP450**

NSYTSP450

Actassi ventilated plate for roof

- Removable plate made from folded sheet steel, to be installed on roof ref. **NSYSRSYS8•**.
- Optional installation of roof elevators for aeration, ref.**NSYEX206**, cable gland plates and fans.
- Material: Steel
- Finish: Structured finish, epoxy polyester powder
- Colour: RAL 7035 grey

Supply:
1 ventilated plate and fixing elements

Characteristics	References
Actassi ventilated plate for roof	**NSYTSPV450**

NSYTSPV450

Roof plate elevators for aeration

- Columns with a height of 20 mm.
- Fixing: Between the roofplate and the roof.

Supply:
100 units. Reference by unit.
Order by multiples of 100 (100, 200, 300…).

Characteristics	References
Roof plate elevators for aeration	**NSYEX206**

NSYEX206

11

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Electronic application

Actassi plain cable gland plate

For more details see page 470

- Material: Galvanised steel
- Fixing: Fixing on the outside of the roof and bottom support plate
  Can be combined with other types of cable gland plates

Supply:
1 plain cable gland plate and fixing elements

NSYEC440

Characteristics	References
Actassi plain cable gland plate	**NSYEC440**

Actassi cable gland plate with brush

- Material: Galvanised steel
- Fixing: Fixing on the outside of the roof and bottom support plate
  Can be combined with other types of cable gland plates

Supply:
1 cable gland plate with brush and fixing elements

NSYECP440

Characteristics	References
Actassi cable gland plate with brush	**NSYECP440**

Actassi self-ventilated cable gland plate

- Material: Galvanised steel
- Fixing: Fixing on the outside of the roof and bottom support plate
  Can be combined with other types of cable gland plates

Supply:
1 self-ventilated cable gland plate and fixing elements


NSYECAV440

Characteristics	References
Actassi self-ventilated cable gland plate	**NSYECAV440**

Actassi ventilation plate with or without fans, symbol diameter before 120 mm

- Fixing: Fixing on the outside of the roof and bottom support plate
  Can be combined with other types of cable gland plates
- Other characteristics: Sound level: 34 dB (A)

Supply:
1 cable gland plate with or without fans, 2-m power cord (version with fans) and fixing elements
Versions with 2 or 3 fans: Each of them has an output capacity of 170 m³/h, 220 V-50/60 Hz, installed and wired to a terminal strip. A 2-m power cord is supplied connected

NSYECVT3440

Characteristics	Description	References
Actassi ventilation plate with or without fans, symbol diameter before 120 mm	No fans, 3 positions	**NSYECVT3440**
Actassi ventilation plate with or without fans, symbol diameter before 120 mm	With 3 fans	**NSYECVT3V440**
Actassi ventilation plate with or without fans, symbol diameter before 120 mm	No fans, 2 positions	**NSYECVT2440**
Actassi ventilation plate with or without fans, symbol diameter before 120 mm	With 2 fans	**NSYECVT2V440**

Actassi ventilated support with filter

- Fixing: To be mounted on the cable gland plate with or without fan or on the self-ventilated cable gland plate.
- Colour: RAL 9011

Supply:
1 mounting support and filter

NSYFECVT440

Characteristics	References
Actassi ventilated support with filter	**NSYFECVT440**

Spare filter for Actassi ventilated support

Supply:
5 units


NSYCEFILS

Characteristics	References
Spare filter for Actassi ventilated support	**NSYCEFILS**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Electronic application

Ventilated roof

NSYSVR606

- Roof for providing natural ventilation for the enclosure, with IP30 protection.
- Height: An extra 63 mm in relation to the structure.
- Material: Steel
- Finish: Structured finish, epoxy polyester powder
- Colour: RAL 7035 grey

For more details see page 470

Supply:
1 ventilated roof and fixing elements

Characteristics	Width (mm)	Depth (mm)	References
Spacial SF Ventilated roof	600	600	**NSYSVR606**
Spacial SF Ventilated roof	600	800	**NSYSVR608**
Spacial SF Ventilated roof	800	600	**NSYSVR806**
Spacial SF Ventilated roof	800	800	**NSYSVR808**

Partial 19" fixed rack

- Rack designed for coupling in enclosures with a width of 600 mm.
- Adjustable depth with a pitch of 25 mm.
- Material: Zinc-coated steel
- Maximum load: 2 kg/U

Installation:
Spacial SF:
- Installation at the top front of the enclosure, no cross rails needed (1)
- Depth adjustment of the partial rack: two cross rails need to be installed, see page 255
- For installation at any other height, four cross rails are required (2)

Spacial SM:
- At the front of the enclosure (1): Install two front vertical adaptation profiles, see page 258
- For depth adjustment (2): Install two front vertical adaptation profiles, see page 258 and two rear vertical 40 mm (1 row) cross rails and four cross rails, see page 255


(1) (2)

Supply:
2 uprights and fixing elements

NSYRCKP4

Characteristics	No. of units	Height (mm)	References
Partial 19" fixed rack	4	200	**NSYRCKP4**
Partial 19" fixed rack	8	400	**NSYRCKP8**
Partial 19" fixed rack	12	600	**NSYRCKP12**
Partial 19" fixed rack	17	800	**NSYRCKP17**
Partial 19" fixed rack	21	1000	**NSYRCKP21**
Partial 19" fixed rack	26	1200	**NSYRCKP26**

19" fixed rack


NSYRCK24

- Rack designed for installation in enclosures with a width of 600 mm.
- Adjustable depth with a pitch of 25 mm.
- Material: Zinc-coated steel
- Maximum load: 400 kg

Installation:
Spacial SF:
- direct fixing on the structure of the enclosures:
- for installation on enclosures with a width of 800 mm, use the 19" fixed-rack support brackets,
- to reinforce the rigidity of the uprights in enclosures with a width of 800 mm, it is advisable to use the central fixing kit, for enclosure heights above 1800 mm, ref. **NSYRCK19KIT**.

Spacial SM:
- fixing on the top/bottom adjustment rails.



Supply:
2 uprights and fixing elements

Characteristics	No. of units	Height (mm)	References
19" fixed rack	24	1200	**NSYRCK24**
19" fixed rack	29	1400	**NSYRCK29**
19" fixed rack	33	1600	**NSYRCK33**
19" fixed rack	38	1800	**NSYRCK38**
19" fixed rack	42	2000	**NSYRCK42**
19" fixed rack	47	2200	**NSYRCK47**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Life Is On Schneider Electric

Electronic application

Support brackets for 19" fixed rack with a width of 800 mm

- Support brackets for coupling the fixed rack to enclosures with a width of more than 600 mm.
- They allow the depth of the fixed rack to be adjusted with a pitch of 25 mm.
- The fixed amounts are delivered in pairs.
- Material: Zinc-coated steel
- Maximum load: 400 kg



Supply:
4 support brackets and fixing elements

NSYRCKS6

Characteristics	Depth (mm)	References
Support brackets for 19" fixed rack	600	**NSYRCKS6**
Support brackets for 19" fixed rack	800	**NSYRCKS8**
Support brackets for 19" fixed rack	1000	**NSYRCKS10**

Side plates of the centred fixed rack for a width of 800 mm

- Side plates for coupling to the fixed rack in enclosures with a width of 800 mm.
- Direct installation on the rack by screws.
- The fixed amounts are delivered in pairs.
- Material: Steel
- Finish: Structured finish, epoxy polyester powder
- Colour: RAL 7035 grey

Supply:
2 side plates and fixing elements

NSYRC12

Characteristics	Height (mm)	References
Side plates of the centred fixed rack	1200	**NSYRC12**
Side plates of the centred fixed rack	1400	**NSYRC14**
Side plates of the centred fixed rack	1600	**NSYRC16**
Side plates of the centred fixed rack	1800	**NSYRC18**
Side plates of the centred fixed rack	2000	**NSYRC20**
Side plates of the centred fixed rack	2200	**NSYRC22**

Central fixing kit

- To reinforce the rigidity of the 19" fixed racks in enclosures with a width of 800 mm.
- Fixing to the enclosure by cross rails or light cross rails installed depthwise. See page 256.
- Material: Zinc-coated steel



Supply:
2 supports and fixing elements

NSYRCK19KIT

Characteristics	References
Central fixing kit	**NSYRCK19KIT**

11

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Electronic application

Partial 19" swing rack for 600 and 800 mm enclosures

- Rack for coupling to enclosures with widths of 600 and 800 mm.
- In enclosures with a width of 800 mm, the rack can be installed centred or offcentre.
- Maximum opening: 120°.
- Reversible opening direction: Left/right.
- Locking system, top and bottom, with 5 mm double bar key.
- The 6 and 9 units racks only with bottom lock.
- Maximum equipment installation depth: 180 mm, in enclosures with a width of 600 mm.
- Material: Zinc-coated steel

Installation:

Spacial SF:

- To install at the front at any height of the enclosure: directly to the framework by rack fixing elements
- For depth adjustment: Install two (for top height) or four (for any height) 65 mm (2 rows) cross rails, see page 255

Spacial SM:

- To install at the front at any height of the enclosure: install two front vertical adaptation profiles, see page 258
- For depth adjustment: Install two front vertical adaptation profiles, see page 258 and two rear vertical 40 mm cross rails and four 65 mm (2 rows) cross rails, see page 255
- Maximum load: 2 kg/U



For more details see page 471

(1) Optional installation in enclosures with height of 1200 mm.

Supply:
1 partial 19" swing rack

NSYRSWP6

Characteristics	No. of units (H)	Height (mm)	References
Partial 19" swing rack	6	355	**NSYRSWP6**
Partial 19" swing rack	9	468	**NSYRSWP9**
Partial 19" swing rack	12	601	**NSYRSWP12**
Partial 19" swing rack	15	735	**NSYRSWP15**
Partial 19" swing rack	18	868	**NSYRSWP18**
Partial 19" swing rack (1)	21	1002	**NSYRSWP21**

Partial 19" swing rack support for 600 and 800 mm enclosures

- Supports for coupling the partial swing rack to enclosures with widths of 600 and 800 mm.
- Height or depth adjustment, with a pitch of 25 mm, by two 65 mm (2 rows) universal cross rails and a 19" multiple bracket, ref. **NSYMBR19**.
- Spacial SF: Direct fixing to the structure.
- Spacial SM: Fixing to the enclosure by means of the vertical adaptation profile, see page 258.
- Material: Zinc-coated steel

Installation:

- Installation of the rack in centred or off-centre position, for enclosures with a width of 800 mm



Supply:
2 supports and fixing elements

NSYRSWSP6

Characteristics	Width (mm)	References
Partial 19" swing rack support	600	**NSYRSWSP6**
Partial 19" swing rack support	800	**NSYRSWSP8**

19" multiple bracket

- Bracket for fixing 65 mm universal cross rails (2 rows), depthwise, to position the partial 19" swing rack in any direction, up and down and/or depthwise.
- Material: Zinc-coated steel.

Supply:
4 brackets and fixing elements

NSYMBR19

Characteristics	Width (mm)	References
19" multiple bracket	600	**NSYMBR19**

11

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Electronic application

19" swing rack for 600 mm enclosures


NSYRSW627

- To be coupled to enclosures with widths of 600 mm.
- Can be moved depthwise with a pitch of 25 mm.
- Reversible opening direction: Left/right.
- Locking system, top and bottom, with 5 mm double bar key.
- Maximum opening: 130°.
- Maximum equipment installation depth: 180 mm.

Fixing to the enclosure structure:

Spacial SF:

- fixing to the enclosure structure.

Spacial SM:

- fixing to the enclosure on top/bottom adjustment rails.

Components:

- Zinc-coated steel central structure.
- Mounting cross rail on structure made from steel painted with epoxy polyester resin, textured RAL 7035 grey. Fixed to the central structure by screws.



For more details see page 471

Supply:
1 19" swing rack with no panels

Characteristics	No. of units (H)	Height (mm)	References
19" swing rack	27	1400	**NSYRSW627**
19" swing rack	31	1600	**NSYRSW631**
19" swing rack	36	1800	**NSYRSW636**
19" swing rack	40	2000	**NSYRSW640**
19" swing rack	45	2200	**NSYRSW645**

19" swing rack for 800 mm enclosures, off-centre

NSYRSW27

- To be coupled to enclosures with widths of 800 mm.
- Can be moved depthwise with a pitch of 25 mm.
- Reversible opening direction: Left/right.
- Locking system, top and bottom, with 5 mm double bar key.
- Maximum opening: 130° (possibility of opening to 180° using 180° hinges).
- Material: Zinc-coated steel and steel painted
- Maximum load: 3.75 kg/unit with a max of 150 kg

Installation:

- Spacial SF - SM
- other mounting options: Consult us

Maximum equipment installation depth:

- Off-centre 19" swing rack: 470 mm
- Centred 19" swing rack: 390 mm

Fixing to the enclosure structure:

- Spacial SF: Fixing to the entire height of the enclosure structure.
- Spacial SM: Fixing to the enclosure on top/bottom adjustment rails.

Components:

- Zinc-coated steel central structure.
- Mounting cross rail on structure made from steel painted with epoxypolyester resin, textured RAL 7035 grey.
- Fixed to the central structure by screws.
- Side plate made from steel painted with epoxy polyester resin, textured RAL 7035 grey. Fixed to the central structure by screws.



For more details see page 471

Supply:
Centred and off-centre 19" swing rack: hinged rack, 800 mm swing rack supports, side plates with locking system double bar and fixing elements

Characteristics	No. of units (H)	Height (mm)	References
19" swing rack, off-centre	27	1400	**NSYRSW27**
19" swing rack, off-centre	31	1600	**NSYRSW31**
19" swing rack, off-centre	36	1800	**NSYRSW36**
19" swing rack, off-centre	40	2000	**NSYRSW40**
19" swing rack, off-centre	45	2200	**NSYRSW45**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Electronic application

19" swing rack for 800 mm enclosures, centred

NSYRSW27

- To be coupled to enclosures with widths of 800 mm.
- Can be moved depthwise with a pitch of 25 mm.
- Reversible opening direction: Left/right.
- Locking system, top and bottom, with 5 mm double bar key.
- Maximum opening: 130° (possibility of opening to 180° using 180° hinges).
- Material: Zinc-coated steel and steel painted
- Maximum load: 3.75 kg/unit with a max of 150 kg

Installation:
- Spacial SF - SM
- other mounting options: Consult us

Maximum equipment installation depth:
- Off-centre 19" swing rack: 470 mm
- Centred 19" swing rack: 390 mm

Fixing to the enclosure structure:
- **Spacial SF:** Fixing to the entire height of the enclosure structure.
- **Spacial SM:** Fixing to the enclosure on top/bottom adjustment rails.

Components:
- Zinc-coated steel central structure.
- Mounting cross rail on structure made from steel painted with epoxypolyester resin, textured RAL 7035 grey.
- Fixed to the central structure by screws.
- Side plate made from steel painted with epoxy polyester resin, textured RAL 7035 grey. Fixed to the central structure by screws.



For more details see page 471

Supply:
Centred and off-centre 19" swing rack: hinged rack, 800 mm swing rack supports, side plates with locking system double bar and fixing elements

Characteristics	No. of units (H)	Height (mm)	References
19" swing rack, centred	27	1400	**NSYRSWC27**
19" swing rack, centred	31	1600	**NSYRSWC31**
19" swing rack, centred	36	1800	**NSYRSWC36**
19" swing rack, centred	40	2000	**NSYRSWC40**
19" swing rack, centred	45	2200	**NSYRSWC45**

180° hinge

NSYRSWH180

- Hinge for installation on centred and off-centre 19" swing racks.
- Allows the swing rack to be opened to 180°.
- Fixing by M8 screws directly to the swing rack.
- Material: Zamak 5

Maximum equipment installation depth:
off-centre 19" swing rack: 425 mm,
centred 19" swing rack: 345 mm.



Supply:
2 hinges and fixing elements

Characteristics	References
180° hinge	**NSYRSWH180**

11

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Life Is On Schneider Electric

Electronic application

1 U / 3 U support



- Support prepared for installing equipment 1 U or 3 U high.
- Designed with quick locking for easy installation.
- **Spacial SF:** Direct fixing to the structure.
- **Spacial SM:** Fixing to the enclosure by means of the vertical adapter section, see page 258.
- Material Zinc-coated steel

For more details see page 471

Supply:
4 1 U/3 U supports (2 units right and 2 units left) and fixing elements



NSYRC1U

Characteristics	References
1 U / 3 U support	**NSYRC1U**

19" partial single slides



- Rails for installation on fixed or swing racks.
- Direct fixing on the structure of the enclosure, by quick locking.
- Material: Zinc-coated steel
- Thickness: 12/10e mm
- Maximum load: 15 kg

Supply:
2 rails and fixing elements

NSYGB140

Characteristics	References
19" partial single slides	**NSYGB140**

Fixing of cable ducts on 19" racks



- Allows vertical fixing of cable ducts for cable guide.
- Service depth: 150 mm.
- Fixed by quick locking to the 19" rack profile.
- Material: Zinc-coated steel

Supply:
3 units and fixing elements

NSYRCDFIX

Characteristics	References
Fixing of cable ducts on 19" racks	**NSYRCDFIX**

Rear cable-guide support



- Supports used for installation on the rear of the swing racks.
- Suitable for fixing cable-guide accessories.
- Allow vertical fixing of cable ducts: Adjustable depth with a pitch of 44.45 mm.
- Material: Zinc-coated steel

Supply:
2 cable-guide supports, crossbar and fixing elements

NSYRCSUP15

Characteristics	Service depth (mm)	References
Rear cable-guide support	150	**NSYRCSUP15**
Rear cable-guide support	250	**NSYRCSUP25**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Electronic application

120° mechanical retainer

NSYRCDR12

- Retainer for installation on the swing racks.
- Maximum opening: 120°.

Fixing:
Direct fixing to the rack support and the 19" rack

Supply:
1 mechanical door stop and fixing elements

Characteristics	References
120° mechanical retainer	**NSYRCDR12**

180° pneumatic retainer

NSYRCDR18

- Retainer for installation on the swing racks installed with 180° hinges, in enclosures with a depth of 600, 800 or 1000 mm.
- Maximum opening: 180°.

Fixing:
Spacial SF:
fixing to the base of the structure and to the rack.
Spacial SM:
direct fixing to the rack support and to the 19" rack.

Supply:
1 pneumatic door stop and fixing elements

Characteristics	References
180° pneumatic retainer	**NSYRCDR18**

Switch for swing 19" rack

NSYRCINT

- Switch for direct fixing on the bottom or top support of the swing rack.
- M20 connection.
- Open + closed contact, 10 A/500 V.

Supply:
1 19" rack switch and fixing elements

Characteristics	References
Switch for swing 19" rack	**NSYRCINT**

Fixings for 19" rack

- They allow 19" accessories to be mounted.
- Caged nut compatible with 8.5 x 8.5 mm and 9.5 x 9.5 mm holes.

NSYGFR95M63

Characteristics	Batch of	References
M6 screws + washers + nuts	30	**NSYGFR95M63**
M6 x 16 screws and washers	50	**NSYGFR166P**
M6 caged nuts	100	**NSYCN9M625**
M6 screws + washers + nuts	50	**NSYGFR95M65**
M5 screws + washers + nuts	50	**NSYGFR95M55**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Electronic application

1-body 19" enclosure

Fixed chassis



Swing chassis



Fixed chassis mounted on the step slides





Cable gland plate 495 x 220 mm.

H (bars) (mm)	J (travel) (mm)
200	100
250	150
300	200
400	300

19"-Schrank mit 2 Korpus



A (mm)	C (mm)	C1 (mm)	References
300	373	183	**NSYVD2M5U4**
400	373	183	**NSYVD2M5U5**
500	373	183	**NSYVD2M8U4**
700	373	183	**NSYVD2M8U5**
800	373	183	**NSYVD2M10U4**
300	473	283	**NSYVD2M10U5**
400	473	283	**NSYVD2M14U4**
500	473	283	**NSYVD2M14U5**
700	473	283	**NSYVD2M17U4**
800	473	283	**NSYVD2M17U5**

Cable gland plate S3D type dimensions 245 x 80 mm.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Electronic application

Spacial SF 19" electronic enclosure



Ventilated roof



Examples of possible combinations

Cable gland plates for the roof

Spacial SF dimensions		Combination 1	Combination 2
Width (mm)	Depth (mm)		
600/800	600		
600/800	800		
600/800	1000		

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Life Is On Schneider Electric

Electronic application

Partial 19" swing rack for 600 and 800 mm enclosures



Partial 19" swing rack for enclosures with a width of 600 mm.



Partial 19" swingrack, off-centreand centred, forenclosures with awidth of 800 mm.

19" swing rack for 600 mm enclosures



19" swing racks for 800 mm enclosures



1 U / 3 U support



Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Electromagnetic protected steel enclosures

Electromagnetic interference

Introduction

LV networks are highly polluted and subject to a large number of aggressions. Electrotechnical equipment and in particular electronic devices, that are increasingly numerous and process ever lower signals, must withstand a harsh electromagnetic environment. At the same time availability requirements, whether for production, management or commerce, are increasingly great.

Definition

Any electromagnetic phenomenon capable of impairing the performance of a device, equipment or system, etc.
An electromagnetic disturbance can be electromagnetic noise, an unwanted signal or a change in the propagation medium itself.
An electromagnetic disturbance, as its name suggests, consists of an electric field $\vec{E}$ generated by a potential difference and a magnetic field $\vec{H}$ difference caused by the flow of a current I along a conductor.
"Unwanted" electromagnetic interference is simply an unwanted electrical signal that is added to the useful signal. This unwanted signal is propagated by conduction in conductors and by radiation in air, etc.





Example of devices generating interference



The regulations

The standards define electromagnetic compatibility (EMC) as "the ability of a device, equipment or a system to function satisfactorily in its electromagnetic environment without introducing intolerable disturbances to that environment or to other equipment".

Classification

In an electrical switchboard, the signals coming from these sources of disturbance will coexist with more sensitive devices. These signals may be classified as follows (Sources: IEC 61000-5-2 and IEC 60364-4-44 standards):

Class	Examples
1 Sensitive	• Low-level circuits with analog outpout units, sensors… • Instrument circuits (probe, sensors…)
2 Not very sensitive	• Control/command circuits with resistive load • Digitalized low-level circuits (Bus…) • Low-level circuits with on-off output unit (sensors…) • Low-level direct power supply
3 Not very disturber	• Control/command circuits with inductive load (relay, contactors, coils, inverter…) with adapted protection • Alternating power supply • Main power supply connected to power devices
4 Disturber	• Welding machines • Power circuit • Drive, switch mode power supplies…

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Electromagnetic protected steel enclosures

How to obtain EMC

Rules to be followed: General description

The electromagnetic interference generated by devices is classified in 2 categories according to its frequency:
- Low frequency (up to 30 MHz): Interference conducted by sensor cables;
- High frequency (above 1 MHz): Interference radiated by a device.

The rules to be followed concern the selection and installation of the electrical installation's components. Overall, they break down as follows:

Conducted interferences
- Importance of the choice of architecture for the power supplies and associated protective devices.
- Use of a filter.

Radiated interferences
- Importance of the choice of installation rules: grounding, length and cross section of cables, cabling rules, choice of cable tray, connections, choice and installation of the enclosure.
- Use of filters.

Connect the shielding

- This connection can remove interference to earth.

The decision to connect one or both ends to earth means priority is given to protection against low or high frequencies:
- at a single end, 50 Hz stray currents cannot flow, moderate HF protection;
- at both ends, possible presence of 50 Hz current, but the barrier against higher frequencies is strengthened.

Isolation transformers

Isolation transformers are used to guard against high-frequency disturbances generated by the network power supply (primary circuit). An electrostatic shield is connected to earth by a short link. This link must be free of paint and any other insulating material. Physical separation of the cables of the primary circuit (network power supply) and those of the secondary circuit (power distribution) is also essential.

Earth connection of metal raceways

Increasing the efficiency of the shielding on highly disturbing cables

The radiation from a shielded variable speed drive/motor connecting cable will be further reduced if it runs in a closed metal raceway or, even better, in a metal conduit. The raceway and tube need to be connected to earth at either end.

Enclosures

The interfering and sensitive components, cables etc. should be installed in separate enclosures or located at some distance from each other.

Note:
For further information, consult your local sales office or our educational leaflet entitled "Electromagnetic compatibility" - ref. **UE17MK08FR**.

Connect the shielding



Example 1
Shielding connected to frame earth by a wire (pigtail) and no mechanical fastener.
Arrangement to be avoided.

Example 2
Shielding connected to frame earth over its entire circumference, but no mechanical fastener.
Acceptable arrangement.

Example 3
Shielding connected to frame earth over its entire circumference, and a mechanical fastener.
Recommended arrangement.

Isolation transformers



Earth connection of metal raceways



Enclosures



Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Electromagnetic protected steel enclosures

EMC offer of Schneider Electric

This range can be configured according to your needs

4 differents services available:

Assemble to order

Mounting of standard accessories

Painting

Machining

Spacial S3HF wall-mounting enclosure IP55 IK10

From H 400 x W 300 x D 200 to H 1200 x W 800 x D 300 mm

- Metal monobloc enclosures constructed from special ALU-ZINC 150 sheet.
- Body constructed from single folded and welded sheet.
- The enclosure surface, comprising 55 % aluminium ensures good reflection of radiated electromagnetic interference.
- Ingress protection rating: IP55.
- Mechanical protection rating: IK10.
- Structured finish, exclusively epoxy polyester paint on the outside
- RAL 7035 grey colour.

Spacial SFHF suitable enclosure IP55 IK10

From H 1800 x W 600 x D 600 to H 2200 x W 800 x D 800 mm

- Metal, extendable enclosure constructed thanks to a closed triangular profile, door and panel from special ALU-ZINC 150 sheet. The enclosure surface, comprising 55 % aluminium ensures good reflection of radiated electromagnetic interference.
- Ingress protection rating: IP55.
- Mechanical protection rating: IK10.
- Structured finish, exclusively epoxy polyester paint on the outside
- RAL 7035 grey colour.

See page 532 for details or consult our web site www.se.com

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Attenuation of electromagnetic interference

The next illustrations indicates the attenuation (dB) curves related to the frequency (MHz).

Attenuation of the Spacial S3HF enclosure





The presence of 55 % aluminium on the surface of the sheet metal ensures good reflection of electromagnetic waves.

Attenuation of the Spacial SFHF suitable enclosure

Enclosure is tested with its sides panels and earth braids mounted on all claddings (Test performed following IEC 61587-3).



Attenuation curves

Horizontal attenuation — Vertical attenuation

Trend curves (polynomial of order 6)

Horizontal attenuation — Vertical attenuation

11

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Electromagnetic protected steel enclosures

Spacial S3HF

- Single-piece metal enclosures made from special sheets of ALUZINC 150.
- The presence of 55 % aluminium on the surface of the sheet metal ensures good reflection of electromagnetic waves.

Body

- single-piece body, folded and welded,
- entirely sealed body with no cable entry and no opening,
- equipped with four shouldered backstuds allowing direct fixing of the mounting plate,
- its low resistivity promotes earth continuity,
- direct fixing or using wall fixing lugs, ref. **NSYPFCR** (to be ordered separately).

Door

- the special body-door gasket (IP + EMC) provides, in addition to water and dust tightness, electric continuity between the door and the body of the enclosure,
- the metal lock with earth continuity helps improve the general shielding,
- an earthing braid added to the enclosure between the body and the door guarantees a good earth connection and, consequently, good electromagnetic compatibility,
- 3 mm double bar lock as standard delivery (if a 405 key is needed it is possible to mount ref. **NSYCLL405CRN**).
- Other sizes: Consult us.
- Finish: Structured finish, epoxy polyester powder (inside not painted)
- Colour: RAL 7035 grey
- Ingress protection rating: IP55 according to IEC 60529
- Mechanical protection rating: IK10 according to IEC 62262
- Certifications and declarations: UL, CE declaration
- Fixing: Fixing lugs, ref. **NSYPFCR** to be ordered separately (1 set of 4 lugs)

For more details see page 479

Supply:
Enclosure delivered with galvanised mounting plate.

NSYS3HF4320P

Characteristics	Fig.	Weight (kg)	Width (mm)	Height (mm)	Depth (mm)	References
Spacial S3HF	1	7.5	300	400	200	**NSYS3HF4320P**
Spacial S3HF	2	13.0	400	600	200	**NSYS3HF6420P**
Spacial S3HF	2	20.5	600	600	250	**NSYS3HF6625P**
Spacial S3HF	2	32.8	600	800	300	**NSYS3HF8630P**
Spacial S3HF	2	53.2	800	1000	300	**NSYS3HF10830P**

Support bracket for enclosure with anti-tilt kit and reinforcement

- The support bracket is used when the enclosure cannot be hung from a wall or a post.
- Suitable for outdoor use.
- Maximum enclosure dimensions: 1000 x 800 x 300 mm.
- Floor attachment by standard M12 fastenings.
- Material: Steel
- Finish: Painted
- Colour: RAL 7035 grey
- Maximum load: 120 kg

NSYCOCNS1400

Characteristics	Height (mm)	References
Support bracket for enclosure with anti-tilt kit and reinforcement	1400	**NSYCOCNS1400**
Support bracket for enclosure with anti-tilt kit and reinforcement	1800	**NSYCOCNS1800**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Electromagnetic protected steel enclosures

Spacial SFHF

Structure
- galvanised steel structure,
- top and bottom frame, vertical upright.

Claddings
- enclosure with screwed panels (on side and rear) and front plain door (with reinforcement frame) made from Aluzinc steel,
- side panels have to be ordered separately,
- special gasket (IP + EMC) between body, door and panels.
- Finish: Epoxy polyester paint on the outside (inside not painted)
- Colour: RAL 7035 grey
- Ingress protection rating: IP55
- Mechanical protection rating: IK10
- Certifications: RoHS compliant
- Dimensions manufacturing on demand

Note:
Only available on demand.
For more details see page 479

Supply:
- 1 single plain door with door-reinforcement frame (double door on request, please consult us).
- Left or right opening to 120°.
- Delivered with standard locking system handle and 5 mm double bar insert.
- 1 rear panel screwed from the outside.
- 1 removable roof.
- 1 part cable gland plate with special gasket (IP + EMC).

NSYSFHF18660

Characteristics	Height (mm)	Width (mm)	Depth (mm)	References
Spacial SFHF	1800	600	600	
Spacial SFHF	1800	800	400	
Spacial SFHF	1800	800	600	
Spacial SFHF	2000	600	400	
Spacial SFHF	2000	600	600	
Spacial SFHF	2000	600	800	
Spacial SFHF	2000	600	1000	
Spacial SFHF	2000	800	400	
Spacial SFHF	2000	800	600	
Spacial SFHF	2000	800	800	
Spacial SFHF	2000	800	1000	
Spacial SFHF	2200	600	600	
Spacial SFHF	2200	800	600	
Spacial SFHF	2200	800	800	

Side panel

- Finish: Epoxy polyester paint on the outside (inside not painted)
- Colour: RAL 7035 grey
- Dimensions manufacturing on demand

Note:
Only available on demand.

Characteristics	Height (mm)	Width (mm)	References
Side panel	1800	600	
Side panel	1800	400	
Side panel	2000	400	
Side panel	2000	600	
Side panel	2000	800	
Side panel	2000	1000	
Side panel	2200	600	
Side panel	2200	800	

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Electromagnetic protected steel enclosures

All mounting accessories are compatible with the SF and SM standard range.
- Mounting plate (see page 245).
- Rails (see page 253).
- 19" frame (fixed and swinging) (see page 462).



Earth braids

- They guarantee the earth connection for high frequencies, avoiding the disturbing electric currents that are produced.
- Material: Tinned copper.

Supply:
10 earth braids (nuts and washers not included)

NSYEB156D6

Characteristics	Section (mm²)	Terminal Ø (mm)	Length (mm)	Width (mm)	References
Earth braids	6	6.5	150	12	**NSYEB156D6**
Earth braids	10	6.5	150	17	**NSYEB1510D6**
Earth braids	16	8.5	155	17	**NSYEB1516D8**
Earth braids	25	8.5	200	27	**NSYEB2025D8**
Earth braids	50	8.5	200	33	**NSYEB2050D8**

EMC coupling kit

- Used to join enclosures side-by-side or depthwise. Special gasket for EMC solution.
- Attenuation level is decreased by 5 db when enclosures are joined (please consult us).
- Ingress protection rating: IP55.

NSYSFHFBK184

Characteristics	Height (mm)	Depth (mm)	References
EMC coupling kit	1800	400	**NSYSFHFBK184**
EMC coupling kit	1800	600	**NSYSFHFBK186**
EMC coupling kit	2000	400	**NSYSFHFBK204**
EMC coupling kit	2000	600	**NSYSFHFBK206**
EMC coupling kit	2000	800	**NSYSFHFBK208**
EMC coupling kit	2000	1000	**NSYSFHFBK2010**
EMC coupling kit	2200	600	**NSYSFHFBK226**
EMC coupling kit	2200	800	**NSYSFHFBK228**

EMC cable gland with contact spring

- Thread type: Metric EN 60423, other types are available on demand
- Material: Nickel-plated brass, neoprene gasket
- Ingress protection rating: IP66
- Flame resistance: V2 depending on UL94
- Temperature range: -20°C to + 100°C
- Cable type: Unshielded

Supply:
The cable glands are supplied with nuts.
Pack of 10 (M12 and M16), of 5 (M20 and M25), of 4 (M32 and M40)

NSYCGHF12

Characteristics	Ø	Ø min/max	Drill Ø	TD	TL	Wrench width	References	
New EMC cable gland with contact spring	M12	3/6.5	12 to 12.2	12	6	14	**NSYCGHF12**	New
New EMC cable gland with contact spring	M16	5/10	16 to 16.2	16	7	20	**NSYCGHF16**	New
New EMC cable gland with contact spring	M20	6/12	20 to 20.2	20	8	22	**NSYCGHF20**	New
New EMC cable gland with contact spring	M25	11/17	25 to 25.2	25	8	27	**NSYCGHF25**	New
New EMC cable gland with contact spring	M32	15/21	32 to 32.3	32	8	34	**NSYCGHF32**	New
New EMC cable gland with contact spring	M40	19/28	40 to 40.3	40	9	43	**NSYCGHF40**	New

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Electromagnetic protected steel enclosures

Spacial S3HF

Fig. 1



Fig. 2



A: Height.
B: Width.
C: Depth.

* Model 1200 x 800.

Spacial SFHF





A: Height.
B: Width.
C: Depth.



Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Industrial environments, equipment rooms

Spacial S3DEX steel enclosure

The Spacial S3DEX steel enclosure is certified by the LCIE with no. LCIE 02ATEX0037U (component certification).

- Ten sizes: From 300 x 200 x 150 mm to 1000 x 800 x 300 mm.
- Degree of protection: IP66.
- Ambient temperature limits: -20°C ≤ Ta ≤ +40°C.
- Resistance to external mechanical impacts: IK10.
- Structured finish, epoxy polyester powder paint, RAL 7035 grey colour.

Personnel safety

- Blind nut for external earth connection.

- The 4 fixing holes are blocked by 4 crimped blind nuts.

- Earthing studs welded to the door and inside the body.



Label

- Example of specific ATEX marking (description: **Page 635**).

Robust

- The chassis is mounted on four 10 mm shouldered backstuds.



Easy handling

- Reusable, eco-friendly packaging.
- No sharp corners.

In accordance with the ATEX directive

- The enclosures bear the marking shown **page 635**.
- The enclosures offer a degree of protection of IP66 according to EN 60629, reaching the highest dust protection according to ATEX standards.
- The certification of our production sites and inspection procedures guarantees the observance and regularity of the quality level.

Protective of all applications in ATEX II2 or II3 areas

- surface installations with occasional or accidental
- thanks to ATEX-certified steel.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Enclosures for explosive atmospheres

ATEX cubicles from Schneider Electric

Steel

Steel enclosures

- All the wall-mounting enclosures presented in this brochure comply with standards for protection against the potential risk of explosion in atmospheres charged with gas (G) or dust (D).
- The Schneider Electric offer, designed to be used in group II, is classified as category 2.

Protection of equipment against explosions			ATEX	
Group *	Category	Level	Probability	Zone
I	M1	Very high	Permanent	0 / 20
I	M2	High	Occasional	1 / 21
II	1	Very high	Permanent	0 / 20
II	2	High	Occasional	1 / 21
II	3	Normal	Accidental	2 / 22

* I = equipment designed to be used in the mining and quarrying industries
II = equipment designed to be used in surface industries

Zone of application of Schneider Electric ATEX wall-mounting enclosures.

- Category 2 products can be used as category 3.

Our products are certified:

- for gaseous atmospheres: In enhanced safety "e" (Ex e) but not in explosion-proof safety "d" (Ex d);
- for dusty atmospheres: In protection by enclosure "t" or "tb".
- The wall-mounting enclosures offer a degree of protection IP66 according to IEC 60529, exceeding the recommendations of the ATEX directive.
- Certification of our production sites and inspection procedures guarantees observance and consistency of the quality level.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Potentially explosive atmospheres (or ATEX)



Explosion hexagon

Process leading to an explosion in an explosive atmosphere

For an explosion to occur, six conditions must be met simultaneously (see explosion hexagon opposite). The process is as follows:

- mix combustible substances (gases, dusts) with air whose oxygen acts as combustion agent;
- dose combustible products and combustion agents in precise proportions; you thus obtain a potentially explosive atmosphere;
- confine the explosive atmosphere thus obtained in a place conducive to explosion;
- place it in contact with an ignition source having sufficient energy to cause an explosion.

ATEX regulations

Two EU directives and an international standard regulate potentially explosive atmospheres:

- The objective of the two EU directives (the so-called ATEX directives) is to enhance protection from explosions by making various technical and organizational measures compulsory:
- the 2014/34/EU directive (a revision of the 94/9/EC directive) came into application on 20 April 2016. It describes the requirements that must be met by protection devices and systems, and the conformity assessment procedures;
- the 99/92/EC directive, a labour relations supplement to the preceding one, presents the minimum requirements to be met to improve the protection of workers liable to be exposed to ATEX-related risks.

- An IEC international standard harmonized with the European standard EN:
- IEC 60079: electrical equipment for potentially explosive gaseous atmospheres.

Definition

Product directive 2014/34/UE:
defines the manufacturers' obligations.

Personal protection directive 99/92/CE:
defines the users' obligations.

Degree of protection:
In hazardous areas, equipment is required to offer a minimum degree of protection of IP54, but it can be tested or certified with a higher degree of protection.

Classification

Locations liable to be in the presence of an explosive atmosphere have been classified according to 2 criteria:

- the probability assessed on a scale comprising 3 levels;
- the nature of the combustible product.

The following 6 ATEX zones are obtained:

Probability of an explosive atmosphere	Gas / Vapour or mist	Dust
Place in which an explosive atmosphere is present **constantly**, or for long periods or frequently	Zone 0	Zone 20
Place in which an explosive atmosphere is likely to occur **occasionally** in normal operation	Zone 1	Zone 21
Place in which an explosive atmosphere is not likely to occur in normal operation or, if it does occur, will persist for a **short period** only	Zone 2	Zone 22





Equipment installed in an explosive atmosphere zone must be protected against the risk of explosion. Three levels of protection have been defined, corresponding to the three probabilities of existence of an explosive atmosphere. They are broken down into 5 categories depending on the type of industry.

Protection of equipment against explosions			ATEX	
Group *	Category	Level	Probability	Zone
I	M1	Very high	Permanent	0 / 20
I	M2	High	Occasional	1 / 21
II	1	Very high	Permanent	0 / 20
II	2	High	Occasional	1 / 21
II	3	Normal	Accidental	2 / 22

* I = equipment designed to be used in the mining and quarrying industries
II = equipment designed to be used in surface industries

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Protection of electrical equipment

The standards have defined various methods of protection for electrical equipment depending on whether it is located in gaseous or dusty explosive atmospheres.

Electrical equipment		ATEX	Methods of protection	
CENELEC	IEC		Symbol	Title
EN 50015	IEC 60079-6	G, D	o	Immersion in oil
EN 50016	IEC 60079-2	G, D	p	Enclosures with internal overpressure
EN 50017	IEC 60079-5	G, D	q	Filling with powder product
EN 60079-1	IEC 60079-1	G, D	d	Explosion-proof enclosures
EN 60079-7	IEC 60079-7	G, D	e	Enhanced safety "e"
EN 50020	IEC 60079-11	G, D	i	Intrinsic safety
EN 60079-15	IEC 60079-15	G, D	n	Product design
EN 60079-31	IEC 60079-31	G, D	tD	Protection by enclosure "t"

G = gas / vapour or mist
D = dust

ATEX certification of electrical switchboards

- Since 1 July 2003, the European Union has made it compulsory to use certified equipment (electrical or non-electric) when it is to be installed in areas where the atmosphere is potentially explosive.
- The certification must be established by an approved organization in accordance with the 2014/34/EU directive.
- The organization certifies that the product complies with the health and safety requirements defined in the European directive and the international standards.
- The certificate indicates, via the marking, the product's category and accordingly the zone and the atmosphere in which it can be used.
- Cubicles are certified as components. They will be assembled with other ATEX components (electrical, pneumatic, hydraulic, etc.), to form an end solution which must itself be ATEX certified and covered by a declaration of conformity.



Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Spacial S3DEX

Protection for users
- Earthing: The Spacial S3DEX steel cubicles are provided with M6 x 16 earth studs welded to the casing and door for equipotential connection. Earth strap to be ordered separately.
- Closing: Above a height of 600 mm the cubicles are provided with three fastening points with connecting rods, with a single control point preventing the cubicles from being left half-open.

Casing
- Monobloc casing (cross structure). Gutter-shaped front profile.
- 4 bottom shoulder studs M8 x 25 for mounting the chassis and notched bars to provide a space of 10 mm at the rear.

Door
- Standard fastening by 3 mm double bar lock
- Polyurethane door seal
- Double-thickness 20 mm return conferring excellent rigidity;
- 2 invisible hinges (3 above H = 800 mm) facilitate dismounting and reversibility of the door. Opening angle: 120°
- Maximum load: 50 kg/m².
- Pierced sections on the door, with holes of diameter 4.2 mm every 25 mm for mounting accessories:
- 2 vertical sections as of H = 400 mm;
- 2 vertical sections and 2 horizontal sections as of L = 800 mm.

Specific ATEX features
- 4 fastening holes stopped up by 4 crimped blind nuts.
- One crimped M8 blind nut for an external frame earth link (strap not provided)
- Ambient temperature: -20°C ≤ Ta ≤ +40°C
- Marking: See page 635.
- Material: Steel
- Finish: Structured finish, epoxi-polyester powder
- Colour: RAL 7035 grey
- Ingress protection rating: IP66 (enclosures with single door) according to IEC 60529
- Mechanical protection rating: IK10 (enclosures with plain door) according to IEC 62262
- Fixing: Wall fixing lugs:
  Passivated zinc-coated steel: Reference **NSYAEFPFSC**
  304L stainless steel: Reference **NSYAEFPFXSC**

NSYS3DEX3215

Characteristics	Height (mm)	Width (mm)	Depth (mm)	References
Spacial S3DEX	300	200	150	**NSYS3DEX3215**
Spacial S3DEX	300	300	200	**NSYS3DEX3320**
Spacial S3DEX	400	300	200	**NSYS3DEX4320**
Spacial S3DEX	400	400	200	**NSYS3DEX4420**
Spacial S3DEX	500	400	200	**NSYS3DEX5420**
Spacial S3DEX	600	400	250	**NSYS3DEX6425**
Spacial S3DEX	600	600	250	**NSYS3DEX6625**
Spacial S3DEX	700	500	250	**NSYS3DEX7525**
Spacial S3DEX	800	600	300	**NSYS3DEX8630**
Spacial S3DEX	1000	800	300	**NSYS3DEX10830**

The accessories of the Spacial standard wall-mounting enclosures can be installed in the Spacial S3DEX wall-mounting enclosures.
However, plastic accessories should not be used, due to the risk of a static charge.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Mounting plate Plain

NSYMM32

Characteristics	Height (mm)	Width (mm)	References
Mounting plate Plain	300	200	**NSYMM32**
Mounting plate Plain	300	300	**NSYMM33**
Mounting plate Plain	308	255	**NSYMM3025**
Mounting plate Plain	400 / 430	300 / 330	**NSYMM43**
Mounting plate Plain	400	400	**NSYMM44**
Mounting plate Plain	500 / 530	400 / 430	**NSYMM54**
Mounting plate Plain	600 / 647	400 / 436	**NSYMM64**
Mounting plate Plain	600	600	**NSYMM66**
Mounting plate Plain	700 / 747	500 / 536	**NSYMM75**
Mounting plate Plain	800 / 847	600 / 636	**NSYMM86**
Mounting plate Plain	1000 / 1056	800 / 852	**NSYMM108**

Mounting plate Silkscreened

NSYMS43

Characteristics	Height (mm)	Width (mm)	References
Mounting plate Silkscreened	400 / 430	300 / 330	**NSYMS43**
Mounting plate Silkscreened	400	400	**NSYMS44**
Mounting plate Silkscreened	500 / 530	400 / 430	**NSYMS54**
Mounting plate Silkscreened	600 / 647	400 / 436	**NSYMS64**
Mounting plate Silkscreened	600	600	**NSYMS66**
Mounting plate Silkscreened	700 / 747	500 / 536	**NSYMS75**
Mounting plate Silkscreened	800 / 847	600 / 636	**NSYMS86**

Mounting plate Microperforated


NSYMF33

Characteristics	Height (mm)	Width (mm)	References
Mounting plate Microperforated	300	300	**NSYMF33**
Mounting plate Microperforated	400 / 430	300 / 330	**NSYMF43**
Mounting plate Microperforated	400	400	**NSYMF44**
Mounting plate Microperforated	500 / 530	400 / 430	**NSYMF54**
Mounting plate Microperforated	600 / 647	400 / 436	**NSYMF64**
Mounting plate Microperforated	600	600	**NSYMF66**
Mounting plate Microperforated	700 / 747	500 / 536	**NSYMF75**
Mounting plate Microperforated	800 / 847	600 / 636	**NSYMF86**
Mounting plate Microperforated	1000 / 1056	800 / 852	**NSYMF108**

Mounting plate Telequick

NSYMR32

Characteristics	Height (mm)	Width (mm)	References
Mounting plate Telequick	300	200	**NSYMR32**
Mounting plate Telequick	300	300	**NSYMR33**
Mounting plate Telequick	308	255	**NSYMR3025**
Mounting plate Telequick	400 / 430	300 / 330	**NSYMR43**
Mounting plate Telequick	500 / 530	400 / 430	**NSYMR54**
Mounting plate Telequick	600 / 647	400 / 436	**NSYMR64**
Mounting plate Telequick	600	600	**NSYMR66**
Mounting plate Telequick	700 / 747	500 / 536	**NSYMR75**
Mounting plate Telequick	800 / 847	600 / 636	**NSYMR86**
Mounting plate Telequick	1000 / 1056	800 / 852	**NSYMR108**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Enclosures for explosive atmospheres

Mixed symmetrical chassis

NSYMD33

Characteristics	Height (mm)	Width (mm)	References
Mixed symmetrical chassis	300	300	**NSYMD33**
Mixed symmetrical chassis	400	300	**NSYMD43**
Mixed symmetrical chassis	500	400	**NSYMD54**
Mixed symmetrical chassis	600	400	**NSYMD64**
Mixed symmetrical chassis	600	600	**NSYMD66**
Mixed symmetrical chassis	700	500	**NSYMD75**
Mixed symmetrical chassis	800	600	**NSYMD86**
Mixed symmetrical chassis	1000	800	**NSYMD108**

Step slides

NSYSDCR200

Characteristics	Depth (mm)	References
Step slides	200	**NSYSDCR200**
Step slides	200	**NSYDPLM200**
Step slides	250	**NSYSDCR250**
Step slides	250	**NSYDPLM250**
Step slides	300	**NSYSDCR300**
Step slides	300	**NSYDPLM300**
Step slides	350	**NSYDPLM350**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Enclosures for explosive atmospheres

1-door enclosure



Detail 1 Detail 2

Detail 4
4 crimped blind nuts for direct fixing of the fixing lugs





1 4 M8 x 25 mm backstuds.
2 2 M6 x 17.5 mm earthing studs.
3 Stud centre-to-centre distance.
4 Crimped blind nut centre-to-centre distance.
5 Blind nut for external earth.

A: Height
B: Width
C: Depth



Detail 5
1 crimped blind nut for the external earth



Perforated rails on the door



Enclosure (8)		Perforated rails on the door (mm)			
Height (A) (mm)	Width (B) (mm)	Vertical F	Vertical D	Horizontal E	Horizontal C
400	300	320	237	-	-
400	400	320	337	-	-
600	400	370	337	-	-
600	600	370	537	-	-
700	500	470	437	-	-
800	600	570	537	-	-
1000	800	770	737	620	949

6 Perforations with a pitch of 25 mm.
7 1 M6 x 17.5 mm earthing stud.
8 The doors of enclosures with dimensions less than 800 x 600 mm do not have horizontal wire guides.

11

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Human-Machine Interface Solutions

Indoor non-clean industrial environment

Steel

Control enclosure with suspension system

Control Desks

PC racks

Demanding industrial environment

Stainless steel

Control Desks

PC racks

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Human-Machine Interface

S3CM



See page 490

Spacial S3CM Control enclosure with suspension system

The Spacial S3CM offer for human-machine interface combines robustness with aesthetics and ergonomics. Consist of:

- control enclosure,
- a keyboard-box,
- a suspension system of arms and joints, for a fixed or rotating solutions, and support accessories.

SD

See page 497

Spacial SD Control desks

The range of Spacial SD control desks provides all the functions required of a workstation intended for industrial and infrastructure applications. Spacial SD offers two clearly differentiated solutions:

- the SD Compact control desk,
- the SD Control desk with console.

The range has protection ratings of IP55 and IK10, which guarantee the safety and the protection of the installed devices.

SF

See page 512

Spacial SF suitable PC rack

The Spacial SF PC rack is designed to protect and control computer equipment in an industrial environments. Access to the various functions and working heights, guaranteeing optimum comfort. The roof and panels, fixed from the inside, prevent access by unauthorised personnel.

SDX

See page 498

Spacial SDX Control desks

The Spacial SDX range of control desks offers all the functions required to set up a control station that meets the industrial or infrastructural needs of applications in harsh environments or in the food and beverage sector. Easy to implement, compatible with dialogue components, guaranteeing the security and protection of control devices, these control desks, with their range of dimensions, meet the strictest needs of their users.

SMX

See page 516

Spacial SMX monobloc PC rack

The stainless steel monobloc PC racks have been especially designed to protect computer equipment installed in corrosive or specially environments that require washing or exposure to sprays of liquid. Access to the various functions and working heights, guaranteeing optimum comfort.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Human-Machine Interface

The Spacial S3CM offer for human-machine dialogue consists of:

control enclosures, a box-keyboard, a system of arms and joints fixed or rotating, accessories.
The global dialogue system combines robustness with aesthetics and ergonomics.

This range can be configured according to your needs

4 differents services available:

Assemble to order

Mounting of standard accessories

Painting

Machining



Human-Machine Interface Solutions

Robust

2 tube sizes in extruded steel, 50 and 80 mm square, thickness 40/10e mm.
Top wall reinforced by a plate with a thickness of 30/10e mm.

Easy

Easy access to the equipment by a rear door, opening to 120°.
Direct installation of accessories on the enclosure frame rail:
- vertical document support,
- keyboard support,
- laptop computer support.

A box-keyboard is installed directly on the enclosure.

Aesthetics

Extruded aluminium rail frame.
RAL 7040 paint: Frame.
RAL 7035 grey paint: Enclosure.
Customisation to your image or the aesthetics of your machine: Consult us.

Flexibility

Flexibility

Ergonomics

Frame designed for handling the enclosure and facilitating the usage by the operator.

See page 532 for details or consult our web site www.se.com

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Human-Machine Interface

Every model is suitable for tubes with a square section of:
- 50 mm for medium loads,
- 80 mm for heavy loads

(see selection table on **page 492**).

Steps to choose the suspension system (medium or heavy loads)

1 - Define the total load of the system*: a + b + enclosure + installed equipment (Y axis).
2 - Define the length of arm L (X axe).
3 - Define the configuration:

Suspension system without intermediate joint.





Suspension system with intermediate joint.





* The load (a + b + enclosure + installed equipment) must be less than the maximum load.

Example



1 - Total load (kg) = 80 kg.
2 - Length (L) = 1200 mm.
3 - Suspension system without intermediate joint.

Recommended system
> Medium loads Ø 50.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Human-Machine Interface

Enclosure dimensions (mm)				Tube section U 50 mm	Tube section U 80 mm
	H (mm)	W (mm)	D (mm)	References	References
	300	300	200	**NSYS3CM303020**	-
	300	400	200	**NSYS3CM304020**	-
	400	400	200	**NSYS3CM404020**	-
	400	600	250	**NSYS3CM406025***	-
	500	500	250	**NSYS3CM505025**	-
	600	600	200	**NSYS3CM606020***	-
	600	800	300	-	**NSYS3CM608030**
	800	600	300	-	**NSYS3CM806030***

Tube		Tube section U 50 mm	Tube section U 80 mm
	Length (m)	References	References
	0.5	**NSYCMT5005**	**NSYCMT8005**
	1	**NSYCMT5010**	**NSYCMT8010**
	1.5	**NSYCMT5015**	**NSYCMT8015**
	2	**NSYCMT5020**	**NSYCMT8020**

Fixing on support (steel material)		Tube section U 50 mm	Tube section U 80 mm
		References	References
	1 Fixed base	**NSYCMUMR50**	**NSYCMUMR80**
	2 Wall fixing with joint	**NSYCMUMA50**	**NSYCMUMA80**
	3 Rotating straight fitting	**NSYCMUMC50**	**NSYCMUMC80**

Inter-tube fitting (aluminium material)		Tube section U 50 mm	Tube section U 80 mm
		References	References
	4 Horizontal inter-tube joint	**NSYCMUIA50**	**NSYCMUIA80**
	5 Fixed bracket	**NSYCMUTC50**	**NSYCMUTC80**

Fixing on enclosure (aluminium material)		Tube section U 50 mm	Tube section U 80 mm
		References	References
	6 Rotating fixing on enclosure	**NSYCMUCR50**	**NSYCMUCR80**
	7 Rotating fixing in bracket on enclosure	**NSYCMUCC50**	**NSYCMUCC80**
	8 Tilting fixing on enclosure	**NSYCMUCP50**	**NSYCMUCP80 (1)**

* Enclosure equipped with a cable gland plate.
(1) Installation on an enclosure D300 requires plate ref. NSYCMUCPAD87 (see page 496).

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.



Fixing on support
2 See page 495

Inter-tube fitting
5 See page 496

Fixing on enclosure
6 See page 496



Fixing on support
1 See page 495

Inter-tube fitting

Fixing on enclosure
6 See page 496



Fixing on support
1 See page 495

Inter-tube fitting
4 See page 495

Fixing on enclosure
7 See page 496



Fixing on support
1 See page 495

Inter-tube fitting

Fixing on enclosure
6 See page 496



Fixing on support
3 See page 495

Inter-tube fitting
5 See page 496

Fixing on enclosure
6 See page 496



Fixing on support
1 See page 495

Inter-tube fitting

Fixing on enclosure
8 See page 496

11

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Spacial S3CM

The control enclosures consist of:
A steel body equipped with:
- reinforcement plate: The top wall is reinforced by a plate (3 mm) and pierced with a hole Ø 54 or 87 mm (according to the reference) to allow hanging installation of the enclosure,
- 4 welded studs on the 2 inner vertical walls, for fixing the rails,
- 2 rails (with drill holes) for installing equipment,
- a rear door, opening to 120° and closing with double bar lock.

(1) Enclosure equipped with a cable gland plate

An aluminium front face (2.5 mm thick):
- this surface is protected on both sides by a plastic film, allowing the installation of the dialogue elements,
- a trim frame made from 4 extruded-aluminium rails.
- Structured finish, epoxy polyester powder, RAL 7040 grey colour (other colours on demand).
- The design of these rails takes into account the accessory mounting functions (lamp, document support, keyboard support, laptop support, etc.), the ergonomics for handling the enclosure and its overall aesthetics.
- Finish: Structured finish, epoxy polyester powder
- Colour: RAL 7035 grey
- Ingress protection rating: IP54 according to IEC 60529
- Mechanical protection rating: IK10 according to IEC 62262

For more details see page 518

NSYS3CM303020

Characteristics	Enclosure load (kg)	Tube section (mm)	Height (mm)	Width (mm)	Depth (mm)	References
HMI encl. Spacial S3CM	8.6	50	300	300	200	**NSYS3CM303020**
HMI encl. Spacial S3CM	9.5	50	300	400	200	**NSYS3CM304020**
HMI encl. Spacial S3CM	11.4	50	400	400	200	**NSYS3CM404020**
HMI encl. Spacial S3CM (1)	17.9	50	400	600	250	**NSYS3CM406025**
HMI encl. Spacial S3CM	20.2	50	500	500	250	**NSYS3CM505025**
HMI encl. Spacial S3CM (1)	26.5	50	600	600	200	**NSYS3CM606020**
HMI encl. Spacial S3CM	34.9	80	600	800	300	**NSYS3CM608030**
HMI encl. Spacial S3CM (1)	33.6	80	800	600	300	**NSYS3CM806030**

Human-Machine Interface Specific accessories

Box-keyboard for control enclosure

- The box is installed on the control enclosures with a width of 600 mm. It then has an angle of 120° with its front face. All the accessories required for installation are delivered with 2 brackets and 1 trim rail, 1 hose for cable entry.

The box for the consists of:
- a steel body, structured finish, epoxy polyester powder, RAL 7035 grey colour, with a screwed cover, an aluminium front face (2.5 mm thick) for installing a keyboard,
- a trim frame made from 2 extruded-aluminium rails guaranteeing ergonomic handling of the box and the aesthetics of the unit. The frame and the front face are delivered assembled. Structured finish, epoxypolyester powder, RAL 7040 grey colour.
- Ingress protection rating: IP54
- Mechanical protection rating: IK10
- Weight: 8 kg

For more details see page 519

NSYCMT2560110

Characteristics	Height (mm)	Width (mm)	References
Box-keyboard for control enclosure	250	600	**NSYCMT2560110**

Support

- Installation on the left or right rail of the frame of the control enclosure.
- Material: Sheet steel
- Finish: Structured finish, epoxy polyester powder
- Colour: RAL 7035 grey
- Thickness: 15/10e mm

For more details see page 519

NSYCMBPT

Characteristics	References
Support for Keyboard	**NSYCMBPT**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Tube

The tubes are available in:
- 2 sizes: Square of 50 and 80 mm,
- 4 lengths: 0.5, 1, 1.5 and 2 m
- Material: Extruded steel
- Finish: structured finish, powder
- Colour: RAL 7035 grey
- Thickness: 40/10e mm

NSYCMT5005

Characteristics	Square (mm)	Length (m)	Weight (kg/m)	References
Tube	50	0.5	6.5	**NSYCMT5005**
Tube	50	1	6.5	**NSYCMT5010**
Tube	50	1.5	6.5	**NSYCMT5015**
Tube	50	2	6.5	**NSYCMT5020**
Tube	80	0.5	10.5	**NSYCMT8005**
Tube	80	1	10.5	**NSYCMT8010**
Tube	80	1.5	10.5	**NSYCMT8015**
Tube	80	2	10.5	**NSYCMT8020**

Fixed base

- Support foot for direct horizontal or vertical connection.
- Material: Moulded steel
- Colour: RAL 7040 grey

For more details see page 520

NSYCMUMR50

Characteristics	Square (mm)	Weight (kg)	References
Fixed base	50	3.25	**NSYCMUMR50**
Fixed base	80	7	**NSYCMUMR80**

Wall fixing with joint

- Device allowing rotation through 170° of a horizontal tube, with a square section of 50 or 80 mm, and its fixing on a vertical surface.
- Protection by bellows, RAL 7035 grey colour.
- Possibility of passing cables through the inside of the joint.
- Material: Moulded steel
- Colour: RAL 7040 grey

For more details see page 520

NSYCMUMA50

Characteristics	Square (mm)	Weight (kg)	References
Wall fixing with joint	50	4.35	**NSYCMUMA50**
Wall fixing with joint	80	9.45	**NSYCMUMA80**

Rotating straight fitting

- Device allowing the fixing and rotation through 295° of tubes, with a square section of 50 or 80 mm, in horizontal position.
- Without blocking the chosen position.
- Fixing by 4 screws, not included.
- Material: Moulded steel
- Colour: RAL 7040 grey

For more details see page 520

NSYCMUMC50

Characteristics	Square (mm)	Weight (kg)	References
Rotating straight fitting	50	5.4	**NSYCMUMC50**
Rotating straight fitting	80	15.7	**NSYCMUMC80**

Horizontal inter-tube joint

- Device allowing the linking and rotation through 170° of 2 horizontal tubes, with a square section of 50 or 80 mm.
- Protection by bellows, RAL 7035 grey colour.
- Possibility of passing cables through the inside of the joint.
- Material: Moulded steel
- Colour: RAL 7040 grey

For more details see page 520

NSYCMUIA50

Characteristics	Square (mm)	Weight (kg)	References
Horizontal inter-tube joint	50	4.25	**NSYCMUIA50**
Horizontal inter-tube joint	80	10	**NSYCMUIA80**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Adapter part for enclosure D300 / Ø 80 mm


NSYCMUCPAD87

Characteristics	Square (mm)	Weight (kg)	References
Adapter part for enclosure D300 / Ø 80 mm	80	0.5	**NSYCMUCPAD87**

Fixed bracket

- Our system of tubes and joints, fixed or rotating, enables all the solutions to respond to the installation needs of the control enclosures for human-machine dialogue.
- Device allowing the combination and fixing of a horizontal tube with a vertical tube.
- Material: Aluminium
- Colour: RAL 7040 grey

For more details see page 521

NSYCMUTC50

Characteristics	Square (mm)	Weight (kg)	References
Fixed bracket	50	1.35	**NSYCMUTC50**
Fixed bracket	80	2.4	**NSYCMUTC80**

Rotating fixing on enclosure

- Device allowing the fixing and rotation through 300° of tubes, with a square section of 50 or 80 mm, in vertical position.
- System for blocking in the chosen position.
- Fixing through the support surface by 4 screws.
- Material: Aluminium
- Colour: RAL 7040 grey

For more details see page 521

NSYCMUCR50

Characteristics	Square (mm)	Weight (kg)	References
Rotating fixing on enclosure	50	1.25	**NSYCMUCR50**
Rotating fixing on enclosure	80	3.1	**NSYCMUCR80**

Rotating fixing in bracket on enclosure

- Devices allowing the fixing and rotation through 300° of tubes, with a square section of 50 or 80 mm, in horizontal position.
- System for blocking in the chosen position.
- Fixing through the support surface by 4 screws.
- Material: Aluminium
- Colour: RAL 7040 grey

For more details see page 521

NSYCMUCC50

Characteristics	Square (mm)	Weight (kg)	References
Rotating fixing in bracket on enclosure	50	2	**NSYCMUCC50**
Rotating fixing in bracket on enclosure	80	6.55	**NSYCMUCC80**

Tilting fixing on enclosure

- This fixing allows the enclosures to be tilted up to 30°.
- System for blocking in the chosen position.
- It is installed on enclosures with depths of 200 and 250 mm.
- The installation on enclosures with a depth of 300 mm requires an adapter plate.
- Material: Aluminium + PA
- Colour: RAL 7040 grey + PA black

For more details see page 521

NSYCMUCP50

Characteristics	Square (mm)	Weight (kg)	References
Tilting fixing on enclosure	50	2.98	**NSYCMUCP50**
Tilting fixing on enclosure	80	3.10	**NSYCMUCP80**

Adapter for signalling beacon

- It is installed on fixed brackets ref. NSYCMUTC50 and NSYCMUTC80.
- Material: Aluminium.
- Finish: Structured finish, powder.
- Colour: RAL 7040 grey

For more details see page 521

NSYCMACS50

Characteristics	Square (mm)	Weight (kg)	References
Adapter for signalling beacon	50	0.025	**NSYCMACS50**
Adapter for signalling beacon	80	0.08	**NSYCMACS80**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Human-Machine Interface

The range of **Spacial SD** control desks provides all the functions required of a workstation intended for industrial and infrastructure applications.

This range can be configured according to your needs

4 differents services available:

Assemble to order

Mounting of standard accessories

Painting

Machining

Steel control desks

Accessibility

There are two versions of the Compact control desk:

- Front accessibility: Designed for straight-forward solutions.
- Front and rear accessibility through a removable panel: Enables the installation of two adjoining plates and to work at the rear. The control desk with console offers full accessibility, since it is fully accessible from the rear thanks to the 3-point closure door it includes. For Spacial SD, the accessibility which allows quick and easy work is one of its main priorities. For this reason, its design excludes the central upright.

Convenience

The possibility of connecting the modular control desk to the modular consoles affords multiple combinations. The opening direction of the door can be changed quickly thanks to the included hinges.

Easy

The console opens easily and safely thanks to the installed pneumatic opening lid stays. Cable entry is optimised because all the models of the range include a cable gland plate with two adjustable parts.

Compatibility

Furthermore, the Spacial SD control desk is compatible with most of the accessories of the Spacial SF and SM ranges.

See page 532 for details or consult our web site www.se.com

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Human-Machine Interface

The association of a monobloc control desk with one or more consoles enables all combinations. Complete accessibility to the inside of the control desk thanks to its design without intermediate crossbars.

This range can be configured according to your needs

4 differents services available:

Assemble to order

Mounting of standard accessories

Painting

Machining

Examples of associations

Consoles and control desks



Multiple combinations available.

Stainless steel control desks



Hygiene

The high quality of the standard finish enables very easy maintenance while avoiding contamination. The hygienic feet made from 316L stainless steel, adjustable between 140 mm and 200 mm height, make it easier to clean under the enclosures.



Compatibility with the other ranges

Stainless steel accessories:

- plinths, locks.

Accessories of the steel control desks offer:

- mounting plate, pneumatic opening stay, etc.

Resistance to corrosion

High resistance to corrosion. 304L and 316L stainlesssteels provide the best solutions for applications in extremely demanding environments.

Convenient

The desk lid and the console are equipped with pneumatic opening stays (opening to 75°) allowing complete access to the inside and preventing sudden falls of the console or the hinged cover. Equipped with adjustment rails for adjusting the depth of the mounting plate. Removable rear panel.

See page 532 for details or consult our web site www.se.com

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Human-Machine Interface

Compact control desk

- This range is available in 4 widths with fixed rear panel.
- Full accessibility is provided from the front (no central upright).
- Easy removable and reversible door opening to 120°.
- Locking by 3 mm doublebar lock (other inserts or cylinders also available, to be ordered separately, see page 507).
- Desk lid equipped with a pneumatic opening stay.
- Opens to 75°. Perforated reinforcement rails with a pitch of 25 mm.
- Control desk equipped with adjustment rails with a pitch of 25 mm and brackets allowing adjustment of the mounting plate depth.
- Cable gland plate with 2 adjustable parts, with polyurethane gasket.
- M8 x 18 mm earthing bolt for equipotential connection between the door and the body.
- Material: Welded folded steel
- Finish: Structured finish, epoxy polyester powder
- Colour: RAL 7035 grey
- Thickness: 15/10e mm
- Ingress protection rating according to IEC 60529: IP55
- Mechanical protection rating according to IEC 62262: IK10

NSYSD6

Options:
It can also be equipped with a mounting plate, see page 509

For more details see page 522

Characteristics	No. doors	Width (mm)	Height (mm)	Depth (mm)	References
Compact control desk	1	600	1000	469	**NSYSD6**
Compact control desk	1	800	1000	469	**NSYSD8**
Compact control desk	2	1000	1000	469	**NSYSD10**
Compact control desk	2	1200	1000	469	**NSYSD12**

Control desk with console

- Full accessibility is provided from the front and rear.
- Easy removable and reversible front door, opening to 120°.
- Locking by two-point locks with 3 mm double bar insert.
- Desk lid equipped with a pneumatic opening stay. Opens to 75°.
- Perforated reinforcement rails with a pitch of 25 mm for quick installation of cables and cable ducts.
- Locking by two-point locks with 3 mm double bar insert.
- Hinged console cover equipped with a pneumatic opening stay.
- Opens to 75°.
- Locking by two-point locks with 3 mm double bar insert.
- Easy removable and reversible rear door, opening to 120°.
- Locking by three-point lock with flat escutcheon, 5 mm double bar insert.
- One entry cable gland plate, with polyurethane gasket.
- Control desk equipped with adjustment rails with a pitch of 25 mm
- and brackets allowing adjustment of the mounting plate depth.
- M8 x 18 mm earthing bolt for equipotential connection between the door and the body.
- Material: Welded folded steel
- Finish: Structured finish, epoxy polyester powder
- Colour: RAL 7035 grey
- Thickness: 15/10e mm
- Ingress protection rating according to IEC 60529: IP55
- Mechanical protection rating according to IEC 62262: IK10

NSYSDF88

Options:
Plinth options see page 505.
It can also be equipped with a mounting plate, see page 509.
Locking system: Other inserts or cylinders also available, see page 507.
The console can support the installation of a 14" screen with an optional PC support plate, see page 509.

For more details see page 522

Characteristics	No. Front doors	No. Rear doors	No. cable gland plates	Width (mm)	Height (mm)	Depth (mm)	References
Control desk with console	1	1	1	800	1400	845	**NSYSDF88**
Control desk with console	1	1	1	800	1400	1045	**NSYSDF810**
Control desk with console	2	2	1	1000	1400	845	**NSYSDF108**
Control desk with console	2	2	1	1000	1400	1045	**NSYSDF1010**
Control desk with console	2	2	1	1200	1400	845	**NSYSDF128**
Control desk with console	2	2	1	1200	1400	1045	**NSYSDF1210**
Control desk with console	2	2	2	1600	1400	845	**NSYSDF168**
Control desk with console	2	2	2	1600	1400	1045	**NSYSDF1610**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

SD Compact control desk with rear panel

- Removable rear panel. It enables the installation of two mounting plates back-to-back, allowing the installation of a large number of devices, while ensuring full accessibility from the front and the rear.
- At the top, these control desks are equipped with cable entry cut-outs, that allows the installation of one or more modular consoles.
- Easy removable and reversible door, opening to 120°.
- Locking by 3 mm doublebar lock (other inserts or cylinders also available, to be ordered separately, see page 507).
- Desk lid equipped with a pneumatic opening stay.
- Opens to 75°. Perforated reinforcement rails with a pitch of 25 mm.
- Top cable entry cut-outs covered by a entire blanking cover.
- Control desk equipped with adjustment rails with a pitch of 25 mm and brackets allowing adjustment of the mounting plate depth.
- Cable gland plate with 2 adjustable parts, with polyurethane gasket.
- M8 x 18 mm earthing screw for equipotential connection between the door and the body.
- Material: Welded folded steel
- Finish: Structured finish, epoxy polyester powder paint
- Colour: RAL 7035 grey
- Thickness: 15/10^{e} mm
- Ingress protection rating according to IEC 60529: IP55
- Mechanical protection rating according to IEC 62262: IK10

Options:
Modular consoles to be installed on top of compact control desk. See details and combinations page 501. It can also be equipped with a mounting plate, see page 509.

For more details see page 523

NSYSD6R

Characteristics	No. doors	Width (mm)	Height (mm)	Depth (mm)	References
Compact control desk with rear panel	1	600	1000	600	**NSYSD6R**
Compact control desk with rear panel	1	800	1000	600	**NSYSD8R**
Compact control desk with rear panel	2	1000	1000	600	**NSYSD10R**
Compact control desk with rear panel	2	1200	1000	600	**NSYSD12R**

SDX Compact control desk with rear panel

- Removable rear panel. It enables the installation of two mounting plates back-to-back, allowing the installation of a large number of devices, while ensuring full accessibility from the front and the rear.
- At the top, these control desks are equipped with cable entry cut-outs, that allows the installation of one or more modular consoles.
- Easy removable and reversible door, opening to 120°.
- Locking by 3 mm doublebar lock (other inserts or cylinders also available, to be ordered separately, see page 507).
- Desk lid equipped with a pneumatic opening stay.
- Opens to 75°. Perforated reinforcement rails with a pitch of 25 mm.
- Top cable entry cut-outs covered by a entire blanking cover.
- Control desk equipped with adjustment rails with a pitch of 25 mm and brackets allowing adjustment of the mounting plate depth.
- Cable gland plate with 2 adjustable parts, with polyurethane gasket.
- M8 x 18 mm earthing screw for equipotential connection between the door and the body.
- Material: 304L stainless steel
- Finish: Scotch-Brite® brushed finish
- Thickness: 15/10^{e} mm
- Ingress protection rating according to IEC 60529: IP55
- Mechanical protection rating according to IEC 62262: IK10

Options:
Stainless steel modular consoles to be installed on top of compact control desk. See details and combinations page 501. It can also be equipped with a mounting plate, see page 509.

For more details see page 523

NSYSDX6

Characteristics	No. doors	Width (mm)	Height (mm)	Depth (mm)	References
Compact control desk with rear panel	1	600	1000	500	**NSYSDX6**
Compact control desk with rear panel	1	800	1000	500	**NSYSDX8**
Compact control desk with rear panel	2	1000	1000	500	**NSYSDX10**
Compact control desk with rear panel	2	1200	1000	500	**NSYSDX12**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Human-Machine Interface

SD Modular consoles

- Hinged modular console cover equipped with a pneumatic opening stay.
- Opens to 75°. Locking of the hinged modular console cover by two 3 mm double bar locks (other inserts or barrels also available, to be ordered separately, see page 507).
- Screw fixed rear panel equipped with step slides in the version with a depth of 300 mm.
- Material: Welded folded steel
- Finish: Structured finish, epoxy polyester powder
- Colour: RAL 7035 grey
- Thickness: 15/10e mm
- Ingress protection rating: IP55 according to IEC 60529
- Mechanical protection rating: IK10 according to IEC 62262

Options:
The link between the control desk and the modular console requires, in certain cases, the addition of one or several blanking covers (to be ordered separately).
Optional galvanised mounting plate.

NSYSDC42

Characteristics	No. of cable entry cut-outs	Width (mm)	Height (mm)	Depth (mm)	References
Modular consoles	2	400	483	200	**NSYSDC42**
Modular consoles	2	400	483	300	**NSYSDC43**
Modular consoles	3	600	483	200	**NSYSDC62**
Modular consoles	3	600	483	300	**NSYSDC63**

SDX Modular consoles

- Hinged modular console cover equipped with a pneumatic opening stay.
- Opens to 75°. Locking of the hinged modular console cover by two 3 mm double bar locks (other inserts or barrels also available, to be ordered separately, see page 507).
- Screw fixed rear panel equipped with step slides in the version with a depth of 300 mm.
- Material: 304L stainless steel
- Finish: Scotch-Brite® brushed finish
- Thickness: 15/10e mm
- Ingress protection rating: IP55 according to IEC 60529
- Mechanical protection rating: IK10 according to IEC 62262

Options:
The link between the control desk and the modular console requires, in certain cases, the addition of one or several blanking covers (to be ordered separately).
Optional galvanised mounting plate.

NSYSDCX42

Characteristics	No. of cable entry cut-outs	Width (mm)	Height (mm)	Depth (mm)	References
Modular consoles	2	400	483	200	**NSYSDCX42**
Modular consoles	2	400	483	300	**NSYSDCX43**
Modular consoles	3	600	483	200	**NSYSDCX62**
Modular consoles	3	600	483	300	**NSYSDCX63**

SD Blanking cover

- To conceal the free space of the control desk when the width of the console or consoles is less than the width of the control desk.
- In any case, it is necessary to previously remove the top plate delivered with the control desk.
- Material: Steel
- Finish: Structured finish, epoxy polyester powder
- Colour: RAL 7035 grey
- Thickness: 15/10e mm
- Fixing: Fixing by screws

NSYRP2

Characteristics	Width (mm)	Height (mm)	References
Blanking cover	200	40	**NSYRP2**

SDX Blanking cover

- To conceal the free space of the control desk when the width of the console or consoles is less than the width of the control desk.
- In any case, it is necessary to previously remove the top plate delivered with the control desk.
- Material: 304L stainless steel
- Thickness: 15/10e mm
- Fixing: Fixing by screws

NSYRPX2

Characteristics	Width (mm)	Height (mm)	References
Blanking cover	200	40	**NSYRPX2**

11

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Human-Machine Interface

Mounting plates for modular consoles

- Steel mounting plates can be installed at the back of modular consoles (F).
- Material: 304L Galvanized Steel



Example installation of a mounting plate in a console depth 200 mm.



Example installation of a mounting plate in a console depth 300 mm.

NSYMM44

Characteristics	Modular console Width (mm)	Fixing centre-to-centre distance (mm) Height (mm)	Width (mm)	References
Mounting plate	400	325	325	**NSYMM44**
Mounting plate	600	625	325	**NSYMM64**



NSYMF44

Characteristics	Modular console Width (mm)	Fixing centre-to-centre distance (mm) Height (mm)	Width (mm)	References
Mounting plate Microperforated	400	325	325	**NSYMF44**
Mounting plate Microperforated	600	625	325	**NSYMF64**

NSYMR44

Characteristics	Modular console Width (mm)	Fixing centre-to-centre distance (mm) Height (mm)	Width (mm)	References
Mounting plate Telequick	400	325	325	**NSYMR44**
Mounting plate Telequick	600	625	325	**NSYMR64**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Human-Machine Interface

Combination examples of modular consoles installation		Compact control desk		Modular console		Blanking cover	
600		Spacial SD	Spacial SDX	Spacial SD	Spacial SDX	Spacial SD	Spacial SDX
		**NSYSD6R**	**NSYSDX6**	**NSYSDC42** / **NSYSDC43**	**NSYSDCX42** / **NSYSDCX43**	**NSYRP2**	**NSYRPX2**
		NSYSD6R	**NSYSDX6**	**NSYSDC62** / **NSYSDC63**	**NSYSDCX62** / **NSYSDCX63**	-	-

800		Spacial SD	Spacial SDX	Spacial SD	Spacial SDX	Spacial SD	Spacial SDX
		**NSYSD8R**	**NSYSDX8**	**NSYSDC42** / **NSYSDC43**	**NSYSDCX42** / **NSYSDCX43**	2 x **NSYRP2**	2 x **NSYRPX2**
		NSYSD8R	**NSYSDX8**	2 x **NSYSDC42** / 2 x **NSYSDC43**	2 x **NSYSDCX42** 2 x **NSYSDCX43**	-	-
		**NSYSD8R**	**NSYSDX8**	**NSYSDC62** / **NSYSDC63**	**NSYSDCX62** / **NSYSDCX63**	**NSYRP2**	**NSYRPX2**

1000		Spacial SD	Spacial SDX	Spacial SD	Spacial SDX	Spacial SD	Spacial SDX
		**NSYSD10R**	**NSYSDX10**	**NSYSDC42** / **NSYSDC43**	**NSYSDCX42** / **NSYSDCX43**	3 x **NSYRP2**	3 x **NSYRPX2**
		NSYSD10R	**NSYSDX10**	**NSYSDC62** / **NSYSDC63**	**NSYSDCX62** / **NSYSDCX63**	2 x **NSYRP2**	2 x **NSYRPX2**
		NSYSD10R	**NSYSDX10**	**NSYSDC62** / **NSYSDC63**	**NSYSDCX62** / **NSYSDCX63**	2 x **NSYRP2**	2 x **NSYRPX2**
		NSYSD10R	**NSYSDX10**	**NSYSDC42** + **NSYSDC62** / **NSYSDC43** + **NSYSDC63**	**NSYSDCX42** + **NSYSDCX62** / **NSYSDCX43** + **NSYSDCX63**	-	-

1200		Spacial SD	Spacial SDX	Spacial SD	Spacial SDX	Spacial SD	Spacial SDX
		**NSYSD12R**	**NSYSDX12**	**NSYSDC42** / **NSYSDC43**	**NSYSDCX42** / **NSYSDCX43**	4 x **NSYRP2**	4 x **NSYRPX2**
		NSYSD12R	**NSYSDX12**	**NSYSDC62** / **NSYSDC63**	**NSYSDCX62** / **NSYSDCX63**	3 x **NSYRP2**	3 x **NSYRPX2**
		**NSYSD12R**	**NSYSDX12**	**NSYSDC62** / **NSYSDC63**	**NSYSDCX62** / **NSYSDCX63**	3 x **NSYRP2**	3 x **NSYRPX2**
		NSYSD12R	**NSYSDX12**	2 x **NSYSDC62** / 2 x **NSYSDC63**	2 x **NSYSDCX62** / 2 x **NSYSDCX63**	-	-
		NSYSD12R	**NSYSDX12**	**NSYSDC42** + **NSYSDC62** / **NSYSDC43** + **NSYSDC63**	**NSYSDCX42** + **NSYSDCX62** / **NSYSDCX43** + **NSYSDCX63**	**NSYRP2**	**NSYRPX2**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Floor

SD SDX

For more information, see page 96.

Front and rear plinth



Characteristics	NSYSPF6100	NSYSPFX6100
	• The front and rear of the plinth consists of 4 corners with 2 or 4 panels.	
Material	Folded sheet steel, corner with a thickness of 25/10e mm	304L stainless steel
Finish	Painted with epoxy polyester resin	-
Colour	RAL 7022 grey	-
Ingress protection rating	IP30	IP30
Mechanical protection rating	IK10	IK10
Supply	• Height 100 mm: 4 corners, 2 panels (front and rear), 4 corner covers and fixing elements • Height 200 mm: 4 corners, 4 panels (2 front and 2 rear), 4 corner covers and fixing elements • The use of 304L stainless steel plinths on an SD control desk requires an earthing cable reference **NSYEL226D13** (description page 305) to be ordered separatly.	

Control desk references	Plinths references			
Compact control desks with fixed rear panel	100 mm	200 mm	100 mm	200 mm
References	References	References	References	References
NSYSD6	**NSYSPF6100**	**NSYSPF6200**	**NSYSPFX6100**	**NSYSPFX6200**
NSYSD8	**NSYSPF8100**	**NSYSPF8200**	**NSYSPFX8100**	**NSYSPFX8200**
NSYSD10	**NSYSPF10100**	**NSYSPF10200**	**NSYSPFX10100**	**NSYSPFX10200**
NSYSD12	**NSYSPF12100**	**NSYSPF12200**	**NSYSPFX12100**	**NSYSPFX12200**

Compact control desks with removable rear panel Sheet steel	100 mm	200 mm	100 mm	200 mm
References	References	References	References	References
NSYSD6R	**NSYSPF6100**	**NSYSPF6200**	**NSYSPFX6100**	**NSYSPFX6200**
NSYSD8R	**NSYSPF8100**	**NSYSPF8200**	**NSYSPFX8100**	**NSYSPFX8200**
NSYSD10R	**NSYSPF10100**	**NSYSPF10200**	**NSYSPFX10100**	**NSYSPFX10200**
NSYSD12R	**NSYSPF12100**	**NSYSPF12200**	**NSYSPFX12100**	**NSYSPFX12200**

Compact control desks with removable rear panel Stainless steel	100 mm	200 mm	100 mm	200 mm
References	References	References	References	References
NSYSDX6	-	-	**NSYSPFX6100**	**NSYSPFX6200**
NSYSDX8	-	-	**NSYSPFX8100**	**NSYSPFX8200**
NSYSDX10	-	-	**NSYSPFX10100**	**NSYSPFX10200**
NSYSDX12	-	-	**NSYSPFX12100**	**NSYSPFX12200**

Control desk with console	100 mm	200 mm	100 mm	200 mm
References	References	References	References	References
NSYSDF88	**NSYSPF8100**	**NSYSPF8200**	-	-
NSYSDF108	**NSYSPF10100**	**NSYSPF10200**	-	-
NSYSDF128	**NSYSPF12100**	**NSYSPF12200**	-	-
NSYSDF168	**NSYSPF16100**	**NSYSPF16200**	-	-
NSYSDF810	**NSYSPF8100**	**NSYSPF8200**	-	-
NSYSDF1010	**NSYSPF10100**	**NSYSPF10200**	-	-
NSYSDF1210	**NSYSPF12100**	**NSYSPF12200**	-	-
NSYSDF1610	**NSYSPF16100**	**NSYSPF16200**	-	-

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Plinth side panels

NSYSPS4100SD	NSYSPSX5100
• They are fixed to the corner of the plinth by 2 fixing screws.	
Folded sheet steel	304L stainless steel
Painted with epoxy polyester resin	-
RAL 7022 grey	-
IP30	IP30
IK10	IK10

- Height 100 mm: 2 side panels, 4 corner covers and fixing elements
- Height 200 mm: 4 side panels (height of 100 mm, 2 for each side), 4 corner covers and fixing elements
- The use of 304L stainless steel plinths on an SD control desk requires an earthing cable reference **NSYEL226D13** (description **page 305**) to be ordered separately.

100 mm References	200 mm References	100 mm References	200 mm References
NSYSPS4100SD	**NSYSPS4200SD**	**NSYSPSX5100**	**NSYSPSX5200**
NSYSPS4100SD	**NSYSPS4200SD**	**NSYSPSX5100**	**NSYSPSX5200**
NSYSPS4100SD	**NSYSPS4200SD**	**NSYSPSX5100**	**NSYSPSX5200**
NSYSPS4100SD	**NSYSPS4200SD**	**NSYSPSX5100**	**NSYSPSX5200**

100 mm References	200 mm References	100 mm References	200 mm References
NSYSPS5100SD	**NSYSPS5200SD**	**NSYSPSX5100**	**NSYSPSX5200**
NSYSPS5100SD	**NSYSPS5200SD**	**NSYSPSX5100**	**NSYSPSX5200**
NSYSPS5100SD	**NSYSPS5200SD**	**NSYSPSX5100**	**NSYSPSX5200**
NSYSPS5100SD	**NSYSPS5200SD**	**NSYSPSX5100**	**NSYSPSX5200**

100 mm References	200 mm References	100 mm References	200 mm References
-	-	**NSYSPSX5100**	**NSYSPSX5200**
-	-	**NSYSPSX5100**	**NSYSPSX5200**
-	-	**NSYSPSX5100**	**NSYSPSX5200**
-	-	**NSYSPSX5100**	**NSYSPSX5200**

100 mm References	200 mm References	100 mm References	200 mm References
NSYSPS4100SD	**NSYSPS4200SD**	-	-
NSYSPS4100SD	**NSYSPS4200SD**	-	-
NSYSPS4100SD	**NSYSPS4200SD**	-	-
NSYSPS4100SD	**NSYSPS4200SD**	-	-
NSYSPS6100SD	**NSYSPS6200SD**	-	-
NSYSPS6100SD	**NSYSPS6200SD**	-	-
NSYSPS6100SD	**NSYSPS6200SD**	-	-
NSYSPS6100SD	**NSYSPS6200SD**	-	-

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Door

Pneumatic opening stay

- Holds the desk lid in open position at an angle of 75°.

Nominal load per stay (N)	Max. load on lid (kg)	Control desk references				Standard supply stay
		With fixed rear panel References	With removable rear panel Sheet steel References	With removable rear panel Stainless steel References	With console References	References
244	13	NSYSD6	NSYSD6R	NSYSDX6	NSYSDF88	NSYPLS24
244	13	NSYSD8	NSYSD8R	NSYSDX8	NSYSDF810	NSYPLS24
300	11	-	-	-	NSYSDF168	NSYPLS30
300	11	-	-	-	NSYSDF1610	NSYPLS30
300	15	NSYSD12	NSYSD12R	NSYSDX12	NSYSDF128	NSYPLS30
300	15	-	-	-	NSYSDF1210	NSYPLS30
300	17	NSYSD10	NSYSD10R	NSYSDX10	NSYSDF108	NSYPLS30
300	17	-	-	-	NSYSDF1010	NSYPLS30

Pneumatic opening stay

Supply:
delivered with fixings

- Holds the desk lid in open position at an angle of 75°.

NSYPLS24

Characteristics	Nominal load per stay (N)	Max. load on lid (kg)	References
Pneumatic opening stay	244	13	**NSYPLS24**
Pneumatic opening stay	300	17	**NSYPLS30**

11

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Shape inserts

Possibility to replace the standard shape insert:
- 8 mm triangular insert,
- 8 mm male square insert,
- 7 mm male square insert.
- Material: Zamack

NSYTT8CRN

Characteristics	References
8 mm triangular insert	**NSYTT8CRN**
8 mm male square insert	**NSYTC8CRN**
7 mm male square insert	**NSYTC7CRN**

Escutcheon with key lock

- Insert breakage torque: 15 daN.
- Material: Polyamide PA 6 material charged with 30 % fibreglass
- Colour: RAL 7011 grey
- Mechanical protection rating according to IEC 62262: IK10
- Fire resistance: 650°C

NSYML405SD

Characteristics	References
405E key	**NSYML405SD**

Pivoting handle

- To be installed on the rear door of Control desk with console, replacing the flat escutcheon supplied as standard.
- Ergonomic locking system with pivoting handle (delivered without insert).
- Broad range of inserts for covering the greatest variety of needs (shape inserts, DIN cylinders, KABA, ASSA).
- Changing the opening direction to right / left thanks to the symmetric design of the lock unit (no linkages to be removed).
- Lock unit supported by 2 screws.
- Material: PA 6 charged with 30 % fibreglass
- Colour: RAL 7011 grey
- Mechanical protection rating according to IEC 62262: IK10
- Fire resistance: 650°C

NSYSDH

Characteristics	References
Without insert	**NSYSDH**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Shape inserts


NSYINS61

Characteristics	References
6 mm square insert	**NSYINS61**
Female 6 mm square insert	**NSYINS6G1**
7 mm square insert	**NSYINS71**
8 mm square insert	**NSYINS81**
Female 8 mm square insert	**NSYINS8G1**
6.5 mm triangular insert	**NSYINT61**
7 mm triangular insert	**NSYINT71**
8 mm triangular insert	**NSYINT81**
9 mm triangular insert	**NSYINT91**
10 mm triangular insert	**NSYINT101**
10 mm keyless hexagonal insert	**NSYINH31**
3 mm double bar insert	**NSYINDB31**
5 mm double bar insert	**NSYINDB51**
Daimler Benz insert	**NSYINBENZ1**
Fiat insert	**NSYINFIAT1**
Keyless USA slot insert	**NSYINUSA1**
Crown insert	**NSYINCW1**

Push button

NSYINPULSD

Characteristics	References
Push button	**NSYINPULSD**

Cylindrical barrels


NSYIN405E1

Characteristics	References
405E key lock	**NSYIN405E1**
421E key lock	**NSYIN421E1**
455 key lock	**NSYIN4551**
1242E key lock	**NSYIN1242E1**
1332E key lock	**NSYIN1332E1**
2124E key lock	**NSYIN2124E1**
2131A key lock	**NSYIN2131A1**
2132A key lock	**NSYIN2132A1**
2331A key lock	**NSYIN2331A1**
2433A key lock	**NSYIN2433A1**
2452E key lock	**NSYIN2452E1**
3113A key lock	**NSYIN3113A1**
3122E key lock	**NSYIN3122E1**
3123A key lock	**NSYIN3123A1**
3131A1 key lock	**NSYIN3131A1**
3133A key lock	**NSYIN3133A1**
3422E key lock	**NSYIN3422E1**
3432E key lock	**NSYIN3432E1**
6101 key lock	**NSYIN6101**
EDF1300 key lock	**NSYINF1301**
EDF1400 key lock	**NSYINF1401**
Michelin 8079 keyless lock	**NSYINICHEL8791**
Michelin 8133 keyless lock	**NSYINICHEL8131**
Michelin 8376 keyless lock	**NSYINICHEL8371**
E1 keyless lock	**NSYINE11**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Human-Machine Interface

Compact control desks



NSYPMP8560

Characteristics	Width (mm)	Surface (dm²)	References
Mounting plate plain	600	42	**NSYPMP8560**
Mounting plate plain	800	59	**NSYPMP8580**
Mounting plate plain	1000	76	**NSYPMP85100**
Mounting plate plain	1200	93	**NSYPMP85120**

Control desk with console



NSYPMP4580

Characteristics	Width (mm)	Surface (dm²)	References
Mounting plate plain	800	31	**NSYPMP4580**
Mounting plate plain	1000	40	**NSYPMP45100**
Mounting plate plain	1200	77	**NSYPMP45120**
Mounting plate plain	1600	67	**NSYPMP45160**

Control desk with console



NSYPMP8580

Characteristics	Width (mm)	Surface (dm²)	References
Mounting plate plain	800	49	**NSYPMP8580**
Mounting plate plain	1000	63	**NSYPMP85100**
Mounting plate plain	1200	77	**NSYPMP85120**
Mounting plate plain	1600	105	**NSYPMP85160**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Human-Machine Interface

Compact control desks

NSYMP148


NSYSTMP6080



Characteristics	Width (mm)	Surface (dm²)	References
Mounting plate plain	800	90	**NSYMP148**
Mounting plate plain	1000	116	**NSYMP1410**
Mounting plate plain	1200	142	**NSYMP1412**
Mounting plate Telequick (2 items needed)	800	84	**NSYSTMP6080**
Mounting plate Telequick (2 items needed)	1000	108	**NSYSTMP60100**
Mounting plate Telequick (2 items needed)	1200	132	**NSYSTMP60120**

Compact control desks

NSYSPMP4080



Characteristics	Width (mm)	Surface (dm²)	References
Mounting plate plain	800	28	**NSYSPMP4080**
Mounting plate plain	1000	36	**NSYSPMP40100**
Mounting plate plain	1200	44	**NSYSPMP40120**
Mounting plate plain	1600	60	**NSYSPMP40160**

Fixing brackets

- Set of 4 fixing brackets.
- Depth adjustment on 25 mm pitch.
- Included as standard with desk (all versions).
- To be ordered separately when required for installation of two back to back mounting plates in control desks with rear access.
- Material: Galvanised steel
- Thickness: 40/10^{e} mm
- Maximum load: 250 kg

NSYMPBSD

Characteristics	For desk width (mm)	References
Fixing brackets	600	**NSYMPBSD**
Fixing brackets	800	**NSYMPBSD**
Fixing brackets	1000	**NSYMPBSD**
Fixing brackets	1200	**NSYMPBSD**
Fixing brackets	1600	**NSYMPBSD**

Adjustment rails and fixing brackets

- Set of 4 rails and 4 fixing brackets.
- To install a plain mounting plate or a Telequick mounting plate, either at the top or across the height of the monobloc control desk with console.
- For positioning 2 plates (back to back), order fixing brackets ref. **NSYMPBSD**.

NSYMPB4SD

Characteristics	For control desks with console Depth (mm)	References
Adjustment rails and fixing brackets	400	**NSYMPB4SD**
Adjustment rails and fixing brackets	600	**NSYMPB6SD**

11

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Technical uprights

- Set of 2 equipment uprights.
- Support for fixing Telequick mounting plates and rails.
- Material: Zinc-coated
- Thickness: 20/10e mm

NSYTVR8

Characteristics	For control desk height (mm)	Centre-to-centre distance (mm)	References
Technical uprights	1000	650	**NSYTVR8**
Technical uprights	1400	1250	**NSYTVR14**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Human-Machine Interface

The **Spacial SF** PC rack is designed to protect and control computer equipment in an industrial environments.

This range can be configured according to your needs

4 differents services available:

Assemble to order

Mounting of standard accessories

Painting

Machining

Steel PC racks

Convenience

- Anti-glare glazed door designed for viewing until 25.5" screens.
- Cable entry made easier by a cable-land plate in 2 pieces.



Simple

The Spacial SF design allows enclosures to be coupled in any direction, adapting to all installation surfaces.

Ergonomics

- Access to the various functions and working heights, guaranteeing optimum comfort.
- Partial doors delimit the access to each function with a 3 mm double bar lock.
- Built-in screen and CPU support.
- Built-in keyboard and mouse support.

Detail of 5 mm DB lock on rear door.

Locking system

- Locking system with flat escutcheon, made from polyamide 6 with 30 % fibreglass, RAL 9005 black, with 5 mm double bar insert for the plain rear door, and small flat escutcheon with 3 mm double bar insert for the partial front doors.



Robust

- Spacial SF structure formed from a single 1.5 mm galvanised steel section, with a high moment of inertia.
- Vertical uprights joined with top and bottom frames, screwed together with connections of sintered steel.
- Panels built into the structure.

See page 532 for details or consult our web site www.se.com

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Spacial SF PC rack

NSYSF16660PC

- Partial door for PC screen, with Securit® anti-glare glass.
- Plain partial door for CPU (enclosures with height of 1800 mm).
- Hinged plain door for keyboard.
- Plain partial door for optional installation of A4 printer support.
- Partial front doors opening to the right.
- Plain rear door, reversible opening direction (right or left).
- Roof and side panels fixed from the inside.
- Cable gland plate with 1 entry.
- Finish: Structured finish, epoxy polyester powder
- Colour: RAL 7035 grey
- Ingress protection rating according to IEC 60529: IP40
- Mechanical protection rating according to IEC 62262: IK10
- Certifications: UL 508A Types 1, 12 and CUL



For more details see page 523

Characteristics	No. of compartments	Height (mm)	Width (mm)	Depth (mm)	References
Spacial SF PC rack	3	1600	600	600	**NSYSF16660PC**
Spacial SF PC rack	3	1600	600	800	**NSYSF16680PC**
Spacial SF PC rack	4	1800	600	600	**NSYSF18660PC**
Spacial SF PC rack	4	1800	600	800	**NSYSF18680PC**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Human-Machine Interface

Front and rear plinths

NSYSPF6100

NSYSPF6200

- The front and rear of the plinth consists of 4 corners with 2 or 4 panels.
- Material: Folded sheet steel, corner with a thickness of 25/10e mm
- Finish: Structured finish, epoxy polyester powder
- Colour: RAL 7022 grey
- Ingress protection rating: IP30 according to IEC 60529
- Mechanical protection rating: IK10 according to IEC 62262

Supply:
Height 100 mm: 4 corners, 2 panels (front and rear), 4 corner covers and fixing elements
Height 200 mm: 4 corners, 4 panels (2 front and 2 rear), 4 corner covers and fixing elements

Characteristics	Height (mm)	Width (mm)	References
Front plinths for Spacial	100	600	**NSYSPF6100**
Front plinths for Spacial	200	600	**NSYSPF6200**

Plinth side panels

NSYSPS6100

NSYSPS6200

- They are fixed to the corner of the plinth by 2 fixing screws.
- Material: Folded sheet steel
- Finish: Structured finish, epoxy polyester powder
- Colour: RAL 7022 grey
- Ingress protection rating: IP30 according to IEC 60529
- Mechanical protection rating: IK10 according to IEC 62262

Supply:
Height 100 mm: 2 side panels, 4 corner covers and fixing elements
Height 200 mm: 4 side panels (height of 100 mm, 2 for each side), 4 corner covers and fixing elements

Characteristics	Height (mm)	Depth (mm)	References
Side plinths for Spacial	100	600	**NSYSPS6100**
Side plinths for Spacial	100	800	**NSYSPS8100**
Side plinths for Spacial	200	600	**NSYSPS6200**
Side plinths for Spacial	200	800	**NSYSPS8200**

Fixed Trays

NSYFXT6060

- Optional installation of a supplement fixed or telescopic tray directly on structure or on cross rails.
- Acceptable load: 150 kg for fixed trays and 50 kg for telescopic rails, both evenly distributed.
- Installation: On structure / On cross rails

For more details and other options on Mounting: See page 259.

Characteristics	Width (mm)	Depth (mm)	References
Fixed Tray	600	600	**NSYFXT6060**

Universal cross rail 40 mm (1 row)


NSYSUCR4060

Characteristics	Enclosure Depth (mm)	References
Universal cross rail 40 mm (1 row)	600	**NSYSUCR4060**
Universal cross rail 40 mm (1 row)	800	**NSYSUCR4080**

Telescopic rails

NSYTTG60

Characteristics	Enclosure Depth (mm)	References
Telescopic rails	600	**NSYTTG60**
Telescopic rails	800	**NSYTTG60**

Handle for telescopic trays

NSY1TH

- Handle designed for easy extraction of the sliding trays.
- Material: Polyamide 6 (black)

Supply:
2 units and fixing elements

Characteristics	References
Handle for telescopic trays	**NSY1TH**

11

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Locks for partial doors

Locks to replace the 3 mm double bar lock supplied with the partial doors.

Models:

- Transformation of lock with shape inserts, triangular 6.5 mm and square 6 mm.
- Lock with 2233X key for partial doors.
- Lock with 2233X key, exclusive for hinged keyboard door.

Supply:
Lock with shape inserts, triangular 6.5 mm and square 6 mm: Metal body, shape insert and safety washer.
Lock with 2233X key for partial doors: metal body, insert, bolt, safety washer and key.
Lock with 2233X key, exclusive for hinged keyboard door: Metal body, insert, special bolt, safety washer and key.

NSYMLT6

Characteristics	References
With 6.5 mm triangular insert for partial and hinged door	**NSYMLT6**
With 6 mm square insert for partial and hinged door	**NSYMLS6**
With 2233X key for partial door	**NSYML23**
With 2233X key for hinged keyboard door	**NSYMLCD23**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Human-Machine Interface

The stainless steel monobloc PC racks have been especially designed to protect computer equipment installed in corrosive or specially environments that require washing or exposure to sprays of liquid.

This range can be configured according to your needs

4 differents services available:

Assemble to order

Mounting of standard accessories

Painting

Machining

Stainless steel monobloc PC racks

Convenience

- Anti-glare glazed door designed for viewing 14" and 17" screens by removing part of the silkscreen printing.
- Cable entry made easier by a cable gland plate (at the rear) in 2 pieces.

Ergonomic

- Partial doors delimit the access to each function with a 3 mm double bar lock.
- Access to the various functions and working heights, guaranteeing optimum comfort.
- Built-in screen and CPU support.
- Built-in mouse support.

Sealing

- IP55, even with the keyboard drawer open, thanks to the pivoting Plexiglas shutter.

Hygiene

- The high quality of the standard finish enables very easy maintenance while avoiding contamination.
- The hygienic feet made from 316L stainless steel, adjustable between 140 mm and 200 mm height, make it easier to clean under the enclosures, ref. NSYPHX200. More information on page 153.

Optional accessories

- Shelf mounted on telescopic rails.

Resistance to corrosion

- High resistance to corrosion. 304L and 316L stainlesssteels provide the best solutions for applications in extremely demanding environments.

See page 532 for details or consult our web site www.se.com

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

304L stainless steel PC racks

NSYSMX16660PC

Composition
- Top and bottom partial doors on the front side.
- Pivoting panel for the keyboard.
- Plain rear door.

Monitor-screen compartment
- The anti-glare glazed door is designed for viewing screens:
- 14" as standard, vv 17" by removing a part of the silkscreen printing.
- The height of the monitor support can be adjusted.
- The monitor shelf can withstand a maximum weight of 50 kg.

CPU / keyboard compartment
- The keyboard fixed to the inside becomes operational by tilting the central panel.
- The CPU is placed on a height-adjustable shelf, visible and accessible through a pivoting, transparent shutter.

Optional accessories
- Hygienic feet H 200 mm: **NSYPHX200**.
- Shelf installed on a sliding rail, with adjustable height.
- Telescopic tray: **NSYTTG60**.
- Material: Monobloc structure in 304L stainless steel sheet, micro-beaded finish. Can be made in 316L stainless steel on request
- Ingress protection rating according to IEC 60529: IP55, even with the keyboard drawer open
- Mechanical protection rating according to IEC 62262: IK10



A: 1600 / 1800
B: 690 / 890
1 Screwed shelf, adjustable height.
2 Sealed case for keyboard.

Characteristics	Height (mm)	Width (mm)	Depth (mm)	References
304L stainless steel PC racks	1600	600	600	**NSYSMX16660PC**
304L stainless steel PC racks	1800	600	600	**NSYSMX18660PC**

Plinth

- Material: Stainless steel, AISI 304L
- Finish: Scotch-Brite® brushing, to guarantee the durability in application where the contact with the floor increase the risk of corrosion
- Installation: It is necessary to order separately the plinth fixing kit (ref. **NSYAPFXWM**) composed by fixing elements and drilling jig

Front and rear plinths

NSYSPFX6100

Supply:
4 corners, 2 panels (front and rear), 4 corner covers and fixing elements

Characteristics	Height (mm)	Width (mm)	References
Front and rear plinths	100	600	**NSYSPFX6100**

Side plinths

NSYSPSX6100

Supply:
2 side panels, 4 corner covers and fixing elements

Characteristics	Height (mm)	Depth	References
Side plinths	100	600	**NSYSPSX6100**

Front and rear plinths


NSYSPFX6200

Supply:
4 corners, 2 panels (front and rear), 4 corner covers and fixing elements

Characteristics	Height (mm)	Width (mm)	References
Front and rear plinths	200	600	**NSYSPFX6200**

Side plinths

NSYSPSX6200

Supply:
2 side panels, 4 corner covers and fixing elements

Characteristics	Height (mm)	Depth	References
Side plinths	200	600	**NSYSPSX6200**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

HMI encl. Spacial S3CM







A: Height.
B: Width.
C: Depth.

W600 enclosure + box-keyboard installation



1 Cable gland plate.

Figure 1
Enclosure depth from 200 to 250



Figure 2
Enclosure depth 300



Enclosure dimensions (mm)								Cable gland plate	Ø Top hole (mm)	Fig.	Enclosure References
Height (mm)	Width (mm)	Depth (mm)	D	F	G	H	J				
300	300	200	162	262	262	100	45	-	54	1	**NSYS3CM303020**
300	400	200	162	362	262	100	45	-	54	1	**NSYS3CM304020**
400	400	200	262	362	362	100	45	-	54	1	**NSYS3CM404020**
400	600	250	262	562	362	125	75	●	54	1	**NSYS3CM406025***
500	500	250	362	462	462	125	75	-	54	1	**NSYS3CM505025**
600	600	200	462	562	562	100	45	●	54	1	**NSYS3CM606020***
600	800	300	462	762	562	150	100	-	87	2	**NSYS3CM608030**
800	600	300	662	562	762	150	100	●	87	2	**NSYS3CM806030***

* Enclosure equipped with a cable gland plate.

Perforated rails installed on lateral studs.

Detail of the reinforcement plate.

Rear door with double bar lock.

Fixing of the trim frame by screws.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Human-Machine Interface

Box-keyboard for control enclosure





Detail from the installation of the box-keyboard on the control enclosure.

Support

Laptop computer



Keyboard



11

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Human-Machine Interface

Suspension system

Dimensions (mm) Ø A	50 mm square	80 mm square	50 mm square	80 mm square	50 mm square	80 mm square	50 mm square	80 mm square
B	42	72	92	115	50	74	42	72
C	105	134	118	160	68	98	236	320
D	11	11	42	72	42	72	67	94
E	125	173	85	130	30	45	148	190
F	152	201	11	11	96	144	-	-
G	-	-	148	190	96	141.5	-	-
H	72	111	80	115	134	195.5	-	-
I	97	126	130	175	140	210	-	-
J	-	-	55	90	120	180	-	-
K	-	-	68	103	9	13	-	-
L	110	140	105	150	55	84	-	-
S	15	16	-	-	-	-	-	-

Fixed base





Wall fixing with joint





Rotating straight fitting





Horizontal inter-tube joint





11

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Suspension system

Dimensions (mm) Ø A	50 mm square	80 mm square	50 mm square	80 mm square	50 mm square	80 mm square	50 mm square	80 mm square
B	46	56	42	72	46	56	55	55
C	60	83	115	145	60	83	100	100
D	60	83	96	139	147	190	44	44
E	46	56	52.3	85	96	139	121	121
F	42	70	58	87	42	72	182	182
G	144	193	-	-	154	208.5	50	50
H	-	-	-	-	42	70	100	100
I	-	-	-	-	58	87	50	50
M	-	-	M6	M8	M6	M8	-	-

Fixed bracket



Rotating fixing on enclosure



Rotating fixing in bracket on enclosure



Tilting fixing on enclosure



Adapter for signalling beacon



11

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Human-Machine Interface

Compact control desk

1 door



2 doors





Cable gland plate clearance dimensions (mm)	
Width	Maximum opening.
B-280	56

Common side view.
(1) Useful clearance.

Compact control desks with rear panel

1 door



2 doors





Cable gland plate clearance dimensions (mm)	
Width	Maximum opening.
B-280	56

Adjustment of the depth of the mounting plate (mm)		
Depth	Min.	Max.
a	42	392
b	129	479

Common side view.
(1) Useful clearance.

11

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Life Is On Schneider Electric

Human-Machine Interface

SDX Compact control desks with rear panel

1 door



2 doors





Cable gland plate clearance dimensions (mm)	
Width	Maximum opening.
B-280	370

Adjustment of the depth of the mounting plate (mm)		
Depth	Min.	Max.
a	45	395
b	126	476

Common side view.
(1) Useful clearance.

SD Control desk with console

1 door



2 doors





Cable gland plate clearance dimensions (mm)	
Width	Maximum opening.
B-280	56

Notes	
1	1 entry cable gland plate
2	Maximum opening of the hinged desk lid: 75°
3	Maximum opening of the hinged console cover: 75°
4	Optional mounting plate installation, see page 509

Common side view.
(1) Useful clearance.

SD SDX Modular console



Depth 200 mm



Depth 300 mm



(1) Useful clearance.
(2) Same dimensions for the rear panel.

11

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Human-Machine Interface

Spacial SF PC rack



PC rack with a height of 1800 mm.



PC rack with a height of 1600 mm.

304L stainless steel PC racks





(1) Screwed shelf, adjustable height.
(2) Sealed case for keyboard.

A	D
1600	690
1800	890

11

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Life Is On Schneider Electric

Variable speed drive flush-mounting kits

The variable speed drive flushmounting kits have been designed to isolate the power part, which is an important source of heat. They are mounted in the Spacial range of steel enclosures (floor-standing and wall-mounting enclosures) and have been approved for Altivar Process variable speed drives in the ATV630 and ATV930 ranges (power range: 0.75 to 45 kW at 200/240 V, 0.75 to 90 kW at 380/480 V).

The kits are available in five sizes and offer two methods of mounting variable speed drives:
- slide-rail mounting for sizes 1, 2 and 3
- bracket mounting for sizes 4 and 5.

The kits can be installed:
- at the back of the enclosure.
This installation provides full thermal insulation

- inside the enclosure on a mounting plate.
This installation may require the addition of a thermal control.

Tightness

- IP55 according to IEC 60529 with polyurethane seal provided.

Configured offer

Services

Possibility of cut-outs (enclosure and frame) by Schneider Electric: No risk of corrosion and cuts (cut-out made before painting).

Ease of installation

- Set of slide-rails allowing the variable speed drive to be mounted quickly and efficiently.

Strength

- The rigidity of the kit allows it to be installed on Spacial S3D, SF and SM enclosures.

Earth continuity

- Earth continuity is ensured by tightening the M6 nuts associated with pin washers.

Maintenance of the variable speed drive fan (kit sizes 4 and 5)

- Easy front panel maintenance for fan servicing.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Variable speed drive flush-mounting kits

Note:
Dimensions, see page 529

Sizes 1, 2 and 3

Sizes 4 and 5

Characteristics	Mounting kits	
	Variable speed drive installation kits allowing the hot part to be isolated.	
Material	Steel	
Finish	Structured finish, epoxy polyester powder	
Colour	RAL 7035 grey	
Ingress protection rating according to IEC 60529	IP55	
Certifications	UL 508A types 1, 3R and 12	
Supply	**Sizes 1, 2 and 3:** • Painted steel plate with cut-out fitted with two slide-rails + adhesive seal + 7 to 9 M6 studs for kit mounting • Protection seal profile supplied for frame cut-out • Enclosure drilling template	**Sizes 4 and 5:** • Painted steel plates with cut-out fitted with painted mounting brackets + screws and nuts for fixing the brackets and the kit • Protection seal supplied for frame cut-out

Dimensions (mm)			Sizes	Compatibilities						
					Variable speed drives					Kits
					ATV340 380/480 V	ATV630 200/240 V	380/480 V	ATV930 200/240 V	380/480 V	
H	L	P		Enclosures	References	References	References	References	References	References
360	235	22	1	S3D, SF, SM	-	**ATV630U07M3**	**ATV630U07N4**	**ATV930U07M3**	**ATV930U07N4**	**NSYPTDS1**
360	235	22	1	S3D, SF, SM	-	**ATV630U15M3**	**ATV630U15N4**	**ATV930U15M3**	**ATV930U15N4**	-
360	235	22	1	S3D, SF, SM	-	**ATV630U22M3**	**ATV630U22N4**	**ATV930U22M3**	**ATV930U22N4**	-
360	235	22	1	S3D, SF, SM	-	**ATV630U30M3**	**ATV630U30N4**	**ATV930U30M3**	**ATV930U30N4**	-
360	235	22	1	S3D, SF, SM	-	**ATV630U40M3**	**ATV630U40N4**	**ATV930U40M3**	**ATV930U40N4**	-
360	235	22	1	S3D, SF, SM	-	-	**ATV630U55N4**	-	**ATV930U55N4**	-
420	265	22	2	S3D, SF, SM	-	**ATV630U55M3**	**ATV630U75N4**	**ATV930U55M3**	**ATV930U75N4**	**NSYPTDS2**
420	265	22	2	S3D, SF, SM	-		**ATV630D11N4**	-	**ATV930D11N4**	-
555	295	22	3	S3D, SF, SM	-	**ATV630U75M3**	**ATV630D15N4**	**ATV930U75M3**	**ATV930D15N4**	**NSYPTDS3**
555	295	22	3	S3D, SF, SM	-	**ATV630D11M3**	**ATV630D18N4**	**ATV930D11M3**	**ATV930D18N4**	-
555	295	22	3	S3D, SF, SM	-	-	**ATV630D22N4**	-	**ATV930D22N4**	-
800	385	151.5	4	SF, SM	**ATV340D30N4E**	**ATV630D15M3**	**ATV630D30N4**	**ATV930D15M3**	**ATV930D30N4**	**NSYPTDS4**
800	385	151.5	4	SF, SM	**ATV340D37N4E**	**ATV630D18M3**	**ATV630D37N4**	**ATV930D18M3**	**ATV930D37N4**	-
800	385	151.5	4	SF, SM	-	**ATV630D22M3**	**ATV630D45N4**	**ATV930D22M3**	**ATV930D45N4**	-
975	427	205.5	5	SF, SM	**ATV340D45N4E**	**ATV630D30M3**	**ATV630D55N4**	**ATV930D30M3**	**ATV930D55N4**	**NSYPTDS5**
975	427	205.5	5	SF, SM	**ATV340D55N4E**	**ATV630D37M3**	**ATV630D75N4**	**ATV930D37M3**	**ATV930D75N4**	-
975	427	205.5	5	SF, SM	**ATV340D75N4E**	**ATV630D45M3**	**ATV630D90N4**	**ATV930D45M3**	**ATV930D90N4**	-

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Variable speed drive flush-mounting kits

Wall-mounting enclosure fixing lug

NSYAEFPFPTD





- Material: Painted steel
- Colour: RAL 7035 grey
- Maximum load: 105 kg

Supply:
Set of 4 lugs and brackets + fasteners

Characteristics	Variable speed drive flush-mounting kits	References
Spacial - kit of fixing brackets for WM enclosures with flush mounting drive	NSYPTDS1, NSYPTDS2, NSYPTDS3	**NSYAEFPFPTD**

11

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Variable speed drive flush-mounting kits

Spacial S3D, SF and SM dimensions

NSYPTDS1



NSYPTDS2



NSYPTDS3



NSYPTDS4



NSYPTDS5



11

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Automobile application

The door of the "incoming" enclosure is interlocked by the control of the main switch or circuit breaker. A built-in interlocking system with runner rods prevents the opening of the "outgoing" enclosure doors. Access is only allowed when the main switch or circuit breaker is in "O" position and the main door is open. Manual activation of the rods unlocks the other doors and allows access.

Designed to be associated with certain circuit breakers or switches:
– Square D (9422 A1).
– Schneider Electric.

The system is limited for configurations up to 4 columns.



1 Activation for secondary doors.
2 Interlocking for secondary doors.

Secure

- The built-in secure interlocking system for the door (on demand) of the "incoming"/"outgoing" enclosures allows Spacial SF enclosures to be adapted to the requirements of the American car industry.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Life Is On Schneider Electric

Automobile application

Interlocking for main door


NSYSLCKP

System for unlocking the main door adapted to the switches:
- Allen Bradley (1494 VH11).
- Square D (9422 A1).
- Siemens (FH0H).
- Schneider Electric.

Unlocks the main door when the switch is in the open position "O".
The main door interlocking system requires the ordering of both references:
1 Activation for secondary doors.
2 Interlocking for secondary doors.
- Material: Steel
- Finish: Zinc-coated

Note:
The fixed panel in this example must be ordered through our customised service.

Supply:
2 brackets for fixing the configured panel, interlocking elements, switch and fixings. Configured panel and switch not included.

Characteristics	References
Interlocking for main door	**NSYSLCKP**

Activation for secondary doors


NSYSODS

- System installed in the main enclosure.
- Activated by manual operation, preventing the opening of the secondary enclosures connected to one another by runner rods.
- It has a secure function which consists of a part that forces the system into the position in which the secondary enclosures are locked in order to lock the main door.
- Material: Mechanism: Zinc-coated steel, Activation handle: Black plastic

Supply:
Elements for activating the main door and fixings.
For the complete function, both activation
1 and interlocking systems
2 need to be ordered.

Characteristics	References
Activation for secondary doors	**NSYSODS**

Interlocking for secondary doors


NSYSLCKS6

- System for interlocking the outgoing enclosures connected to one another by runner rods that lock their doors.
- Material: Steel
- Finish: Zinc-coated
- Fixing: Fixing to the structure of the enclosures by screws

Supply:
Elements for interlocking the secondary doors and fixings.
For the complete function, both activation
1 and interlocking systems
2 need to be ordered according to the enclosure Larg..

Characteristics	Width (mm)	References
Interlocking for secondary doors	**600**	**NSYSLCKS6**
Interlocking for secondary doors	**800**	**NSYSLCKS8**
Interlocking for secondary doors	**1000**	**NSYSLCKS10**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

The customised solutions

Introduction

Standard enclosure
+
Standard accessories
+
Services
=
Configured solution

Configured:

The configured offer is a standard offer enriched by 4 services

The customized solutions either Configured or Specific, uses existing ranges from Universal Enclosures standard offer as a base for its development. Depending on the modifications to be done upon enclosures and/or accessories, they could affect the certification/declarations of conformity existing in the standard ranges. Additional certifications and declarations of conformity for customized solutions, must be defined under request prior as part of offering specification stage.

Assemble to order

- Change the configuration composition (panels, doors…)
- Merge and assemble several enclosures (applicable to for Spacial SF and Thalassa PLA)

+ Enclosure composition 100 % according to customer needs
+ Easy process to assemble cubicels and associate them.

Machining

- Cut outs made before painting to ensure optimum corrosion withstand.
- Almost any shape of cut-outs are possible on the enclosure body, door, gland plate or mounting plate.
- Enclosure delivered ready to install

Painting

- Enclosure painting color selection (choice of 12 RAL colours)
- Choice of different coatings to be adapted to the need (e.g.: Zing)

+ Epoxy powder polyester painting ensures the best protection
+ Totally customized

Mounting of standard accessories

- Factory mounting of most of the accessories, such as mounting plates, plinth, canopy..etc)

+ Enclosure ready to be equipped

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

The customised solutions

Spacial.conf configuration tool

Spacial.conf is the configuration tool to be used to place your order. It gives you several benefits:

Consistency and error free
- Built-in accessories compatibility matrix
- Up-to-date list price in every country (where deployed)
- One configurator for configurable offers
- Compatibility between enclosure and accessories

Autonomy and facility
- Online configurator, easy handling and immediate usage.
- Illustrated products help you in your choice
- FAQ information for faster understanding

Information back-up
- Links to dxf drawing download
- Links to data sheet
- Configurations can be saved and shared thanks to a unique smart code.

Your order in 5 steps with Spacial.conf:

1 - Select country and language
- 12 countries deployed
- 5 languages available English, French, Spanish, German, Russian.
- Global international version available.

2 - Select enclosure
- Select product range
- Select material
- Select enclosure type

3 - Select accessories
- Composition accessories
- Mounting accessories
- Thermal accessories

4 - Select services
- Mounting
- Machining
- Painting
- Assembly

5 - Validation and send offer
- Order summary
- Send order to get quotation confirmation from local sales representative

Have a smartphone or a tablet? Scan this

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

The customised solutions

Introduction



20 experts

specialized on different materials and different products

Engineered to order. (ETO)

The engineered to order offer allows you to have a tailor-made product

ETO main characteristics

Solutions with:

- Cut out, special colors, specific dimensions, welding, special adaptation…,
- Packaging and delivery can also be adapted to the project,
- Technical, quantities limitations and lead time are defined case by case by P&S quotation team, complexity.
- Co-engineer your solution with our design and engineering team (20 experts entirely dedicated to your specific needs).

Examples of Specific solution

- Special dimension
- Cut-outs on the body and the doors

- Cable entry and door adaptation
- Special door shape

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

The customised solutions

What to take into account

This page will help you define your needs for enclosure and streamline your design process.

Step 1

Environment in which you'll install the enclosure(s)

- Installation indoor or outdoor?
- installation outdoor undershelter?
- Clean or not clean environement?
- IP required?
- IK required?

Step 2

Application(s) needs of your enclosure(s)

- Certification nedeed? UL? ATEX?
- Declaration of conformity?, NEMA?, Marine?, Seismic?, other...

Step 3

Enclosure(s) description

- Wall mounted or floor standing?
- Type of enclosure's installation?
- Total weight of equipments in the enclosure?
- Design: Color / coating / finish / dimension?
- Body components' adaptations: Cable entry / mounting plate?
- Thermal management adaptations?
- Other accessories adaptations?
- Additional information: Labeling / packaging / logistic?

Step 4

Business profile

- Total quantity of enclosures needed and quantity per batch?
- Frequency of your order: Single order / repeat order?
- Delivery time and method demand?
- Stock needs?
- Other comments?

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Thermal management system

Life Is On Schneider Electric

Thermal management system ClimaSys

Introduction

Presentation	538
ClimaSys Smart Ventilation Systems New	544
ClimaSys CV Ventilation Systems	558
ClimaSys CA Natural airing	574
ClimaSys CE Exchangers	576
ClimaSys CU Cooling Units	588
ClimaSys CRS Ultra thin resistance heaters	606
ClimaSys CR Resistance Heaters	608
ClimaSys CC Thermal Control	612
ClimaSys DT Dataloggers	616
Method to determine a thermal management solution	620

Thermal management system

Thermal problems in enclosures

Evolution of the electrical switchboard

An electrical switchboard is an assembly formed of the following components:

- The enclosure;
- Switchgear and controlgear;
- Electrical conductors; And
- Miscellaneous functions (indications, controls, information processing).

It has evolved in three directions:

- Enclosures increasingly made of insulating materials;
- Switchgear and controlgear incorporating more and more electronics which concentrates a growing number of functions in an increasingly small volume;
- An increasingly high filling rate.

Industrial safety studies, a concept which covers:

- The safety of personnel and equipment;
- The availability of electric power;

show that this is one of the critical points of all industrial and service-sector activities. Its operation must therefore be perfectly under control; And this control must concern not only the operation of its components but also their operating conditions in a given environment.

Temperature and humidity in the enclosure

Analysis of the malfunctions and stoppages of an electrical installation shows that they are mostly of thermal origin: Temperature too high or too low inside the enclosure.

The rise in the average temperature, which may exceed the limits tolerated by the equipment, can be explained by the changes in electrical switchboards:

- Use of insulating materials for the enclosure, which limits heat removal;
- Widespread adoption of electronics and a higher filling rate increase the temperature.

This overheating may concern only certain areas: Hot spots.

The excessively low temperature is due to installation of the electrical switchboard in a very cold environment. It can cause the formation of condensation, a phenomenon which is harmful for the equipment.

Consequences

The presence of humidity or an excessively high temperature inside the enclosure can cause numerous malfunctions:

- Nuisance tripping of protective devices;
- Fire inside the enclosure;
- Burns for the users;
- Premature equipment ageing;

The consequence of these malfunctions is an increase in the installation's operating costs:

- Maintenance costs,
- Costs entailed by stoppage of the installation.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Thermal management system

Solution: Thermal management

Objective

The thermal management solution adopted shall:

- Maintain the temperature and the humidity level inside the enclosure at values corresponding to normal operation of the equipment.
- Establish a uniform temperature to help prevent hot spots.

Choice of solution

The products constituting the thermal management solution are chosen by producing the thermal balance of the installation. This comprises 2 parts:

- Thermal balance inside the enclosure;
- Evaluation of the climatic conditions (temperature, humidity level) or environmental conditions (pollution) of the place in which the electrical switchboard is located.

The Schneider Electric solutions

With the ClimaSys range Schneider Electric proposes a comprehensive offer meeting all needs:

- Airing
- Cooling
- Heating
- Regulating
- Homogenizing (air circulation)

Schneider Electric also proposes a thermal design software program, ProClima, which produces the thermal balance and proposes one or more thermal management solutions.

Characteristics	Smart Climasys	Climasys			
Cooling^	New Smart ventilation systems	 Forced ventilation systems	 Air-air exchangers	 Air-water exchangers	 Cooling units
Heating		 Resistance heaters			
Controlling	New Smart thermal control accessories	 Thermal control accessories			
Thermal Data	 Diagnostic tools	 Effi clima software		 Proclima software	

12
CV

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Thermal management system

				
	Homogenize	**Cool**	**Cool**	**Cool**
Solution	Air circulation	Natural ventilation	Forced ventilation	Air-air exchanger
Description	Stirring fan inside the enclosure	Air circulation achieved by installing grids (side or roof-mounted) with or without filter, or by elevating the roof.	A fan (with or without filter) sucks fresh air from outside to inside the enclosure, thereby creating a slight overpressure which causes removal of the hot air through an outlet grid. The air circulation homogenizes the temperature and the over-pressure helps prevent dust from entering. Side or roof mounting. Can be combined with a thermostat.	Cooling system provided with an aluminum exchange coil to separate the internal and external air circuits, two centrifugal fans to blow in the air circuits, and a thermostat to regulate the temperature in the enclosure. Side or roof mounting.
Use	Help prevent hot spots	Low power to be dissipated. Dusty environment	High power to be dissipated. Dusty and non-hazardous environment. Help prevent hot spots.	Medium power to be dissipated. Corrosive environment (food processing industry). Relatively cold environment (about 25°C).
Temperature conditions Ta = ambient temperature (outside the enclosure) Td = desired temperature inside the enclosure	None	Td > Ta + 5°C	Td > Ta + 5°C 3°C < Ta ≤ 35°C	Td > Ta + 10°C
Independent internal and external air circuits?	No	No	No	Yes
Advantages	• Uniform temperature inside the enclosure	• Very economical solution • No maintenance • Easy, fast installation.	• Economical solution • Easy maintenance • Easy, fast installation • Uniform temperature inside the enclosure • Guaranteed level of protection: IP55 (IP54 for roof models).	• Easy maintenance (no filter) • Far lower maintenance frequency than for fans • IP55 guaranteed.
Disadvantages		• Low power dissipated • Reduction in the degree of protection IP • Risk of ingress of particles and dust if no filter.	• Internal temperature always higher than the external temperature • Maintenance required: Change of filters.	• Internal temperature always higher than the external temperature.
Illustration		 Outlet grids	 Fans	 Air-air exchangers

12
CV

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

		
Cool	**Cool**	**Heat**
Air-water exchanger	Cooling unit	Heating resistor
Cooling system provided with an exchange coil supplied with cold water and separated from the internal air circuit, a centrifugal fan for the air circuit, and a thermostat to regulate the temperature in the enclosure. Side mounting.	Operates like a heat pump: A condenser removes to the ambient air the calories absorbed by an evaporator. The air inside the enclosure is thus cooled and dried. Side, floor, roof and floor-standing mounting.	The heating resistors Help prevent the formation of condensation and help ensure an ideal temperature inside the enclosure.
Large quantity of heat to be removed. Difficult environments (cement plant, production lines, greasy workshops, etc.) or humid environments (sewage plant, bottling factory, etc.). Do not discharge calories into the environment.	Highly polluted environment but which permits the use of a filter for external protection of the cooling unit.	To heat the inside of the enclosure and help prevent condensation.
Ta > Td	Ta > Td and Ta ≤ 55°C	Ta < Td
Yes	Yes	-
• Internal temperature independent of the external temperature • Security system against any leaks • Calories dissipated outside • Guaranteed level of protection: IP55.	• Internal temperature independent of the external temperature • Uniform temperature inside the enclosure. • Guaranteed level of protection: IP54 for roof and big cooling models, IP55 for side models and the SLIM range • Use of an ecological gas. • Installation of a system from removal of condensation water from the evaporator	• Small size (1.6 mm thick for the ultra-thin version) • Low surface temperature (< 70°C for insulated version, 75°C for aluminum version) • Uniform temperature inside the enclosure with the version equipped with a fan.
• There must be a cold water circuit of stable temperature and flow rate • Installation of special piping.	• Water condensation evaporation unit integrated in side mounting models from 0.6 kW to 4 kW • Maintenance required: Change of filters.	
Air-water exchangers	Cooling units	Heating resistors

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Thermal management system

Large range of fans:
flow rate efficiency, high protection rating, quick installation and easier maintenance to secure all the applications.

Ventilation Systems



Easy maintenance
Quick filter replacement
- Quick, easy and safe replacement of the filter installed in the fan, even during operation.

Certifications
- UL

Quality of the components
Selection of the motors
- Improved flow rate and longer service life.
- Large range of input voltages available on all the motors delivered as standard, with alternating 50/60 Hz or direct current.

Optimised flow rate: average increase of 50 %
- Maximum use of surface.
- Minimum loss of pressure.

Easy installation
Quick installation
- Safe, reliable fixing with the assisted fixing device and the system of multi-thickness fixing-clips.
- Easy to invert.
- To operate as extractors, all the motors can be inverted by simply removing four screws.

Innovation

New

Smart ventilation systems
The smartest way to keep critical equipment cool
- Intelligent filter.
- Adaptable to any new or existing enclosures.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

High protection rating: IP54 as standard



1 Fixing guide

- To centre the body of the fan on the wall of enclosure.
- To correct machining faults.
- To facilitate the correct operation of the fixing "clips".



2 Multi-thickness fixing-clips

- To help guarantee easy and reliable fixing of the ventilation system.
- With a thickness of 0.8 to 4.5 mm, with no fixings.

3 Inclined profile of the grille

- To help protect the filter against vertical spraying: each slat is protected by the slat above it, the external dimensions remain small.



4 IP54-55

- A patented system allows the evacuation of water absorbed by the filter,
- in particular during high-pressure spraying.

6 Hot-fitted sealing gasket

- The polyurethane gasket, hot cast, helps guarantee a long-lasting seal.

6 Effective system for retaining the filter

- The system for holding the synthetic filter in the cavity of the filter holder helps guarantee a protection rating of IP54, in the most difficult conditions.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

ClimaSys Smart Ventilation System

Innovation Problems generated by dirty filters

60% of installations face quality issues caused by dirty filters



Efficient Inefficient

Lifespan reduces

Equipment

> Product malfunction or breakdown of the panel

- Overheating issues
- Conductivity issues due to dust
- Damage to internal moving parts

> Reduced lifespan of installed equipment

> Low energy efficiency of the panel

- Overconsumption of the fan

> Safety issues

- Risk of fi re/burning

All these issues are due to the presence of dust and/or ventilation malfunction; They can be avoided with the use of a smart ventilation system.

⚠ HEALTH OF EQUIPMENT = FILTER'S DUST LEVEL

The concept of the ClimaSys Smart Ventilation System (CSVS)

The ClimaSys Smart Ventilation System is a smart, closely integrated network that makes your life easier.

90% savings on filter maintenance

> Use corrective and predictive maintenance of the ventilation system to:

- Improve CAPEX and OPEX of the installation
- Improve maintenance and operation of the installation
- Improve peace of mind

Improve maintenance cost for new and already existing installations.

> Functions of the CSVS systems:

Detect general poor health of the enclosure by monitoring:
- Input/output temperature

Detect fan issues by monitoring:
- Air flow temperature
- Current level, consumed energy
- Blade speed measurement
- Used and remaining (approximate) lifespan

Detect grid fi lter issues:
- Air flow temperature
- Dust level (0% clean – 100% dirty)
- Number of replacements
- Remaining time before next replacement

12 CV

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Thermal management system

Innovation

The technical solution

2 sensors…

Dust Sensor
(patented)
NSYCCAFSDUST

Composed of an optical sensor which detects the filter dirt level + temperature sensor

Fan Sensor
NSYCCARPM

Composed of:
RPM sensor to control fan rotation and transported air temperature Toroidal sensor to measure fan consumption

… connected to a controller which relays information and alarms

Filterstat™ Controller ClimaSys CC DG **NSYCCOFST•••V**

Information displayed on Filterstat's controller screen

- **Detect general poor health of enclosure by monitoring:**
  - Input/output temperature
- **Detect fan issues by monitoring:**
  - Air flow temperature
  - Current level, consumed energy
  - Blade speed measurement
  - Used and remaining (approximate) lifespan
- **Detect grid filter issues:**
  - Air flow temperature
  - Dust level (0% clean – 100% dirty)
  - Number of replacements
  - Remaining time before next replacement

The alarms
The system offers different types of alarms for notification when something is not right:
Alarms
Dust filter alarm: Filter capacity is below from a user-defined level. 0%-60% (Green LED Colour), 60%-80% (Orange LED Colour), >80% (Flashing Red LED Colour)
No electricity supply to fan: Fan is running (there is an rpm reading but the current sensor shows a 0 mA reading).
Fan rpm slow: Fan speed is below a user-predefined level.
Fan flaps blocked: Consumption in a fan is detected but the rpm speed is zero.
Over-temperature alarm on airflow: Fan exceeds a user-defined threshold.
Over-temperature or down-temperature alarm: On inlet or outlet air from grids.
Fan lifespan over: The fan lifetime has almost expired and should be replaced (front LEDs light up purple).
Δt deviation: Δt deviation is greater that a user-predefined threshold.
Remote sensor not connected/broken: A device in the network is disconnected.

Thermal network architecture

> The greenfield solution for new installations

We offer a range of digital devices that can be connected together and optionally also to a remote supervisor.
See page 546

> The brownfield kit for retrofit installations

It is easy to upgrade an existing installation to a digital one.
See page 547

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Thermal management system

Innovation Build your greenfield solution for a new installation

The nucleus of the system is the ClimaSys Filterstat™ controller that collects information from filter and fan sensors across all of your enclosures.

Easy product selection
with the Proclima selection tool

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Select your Smart Fan

1

See details page 550

Select your Smart Grid

2

See details page 549

New ClimaSys Smart Grids Offer

Complete Smart Grid that includes:
- a Dust Sensor
- a Smart Filter G2,
  G3 smart filter to be order separately (see page 549).

Grid cut-out (mm²)	References
92x92	**NSYCAG92DG**
125x125	**NSYCAG125DG**
223x223	**NSYCAG223DG**
291x291	**NSYCAG291DG**

Select your controller and potential thermal hubs to digitalize more than 1 enclosure

3

See details page 552

Filterstat Controllers (4 ports) and thermal hubs (8 ports)

- Trim frame IP55 for installing the Filterstat Controller and thermal
- Hub on enclosure doors, side panels etc.

Voltage (V)	References
30 V AC/DC	**NSYCCOFST30V**
90-250 V AC	**NSYCCOFST90250V**
30 V AC/DC	**NSYCCOFSEM8U1**
90-250 V AC	**NSYCCOFSEM8U2**

Modular frame IP55

Material and colour	References
same as controller	**NSYCCOFR55**

Select your communication cables

4

See details page 553

Filterstat communication cable

Black unshielded cable with 2 connectors on each side.
Material: PVC.

Length (mm)	References
500	**NSYCCA50MFST**
1000	**NSYCCA100MFST**
1500	**NSYCCA150MFST**
2000	**NSYCCA200MFST**
3000	**NSYCCA300MFST**
4000	**NSYCCA400MFST**
5000	**NSYCCA500MFST**

⚠ Control devices (thermostat, hygrostat, hygrotherm) must be ordered separately.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Thermal management system

Innovation Select your brownfield kit for an existing installation

To digitalize an existing installation, order the appropriate brownfield kit:

Suitable for existing enclosures with fan at the bottom and grid at the top (lateral or door)

Brownfield kits

- 2 units external covers grey smokey grids
- 2 units smart filters (2 Filter Mat G2 + 2 dust sensors)
- 1 unit Filterstat Controller (90-250 V, 50 Hz-60 Hz)
- 3 cables
- 1 rpm + toroidal sensor
- Other equipment: 10 stickers and retainer flaps mini-tool kit

Dimensions Grid cut-out size (mm)	Cable size (m)	References
92 x 92	0.5	**NSYCCFSBRKIT92**
125 x 125	1	**NSYCCFSBRKIT125**
223 x 223	1.5	**NSYCCFSBRKIT223**
291 x 291	2	**NSYCCFSBRKIT291**

12
CV

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

... or select brownfield components separately:

	External Smart Grids	External smokey grids	Smart filters		
	External grids equipped with G2 filter and Dust Sensor to be installed in an existing grid support.	External grids to be installed in an existing grid support or used as spare part. Smart filter and Dust sensor to be ordered separately.	Set of 5 Smart filters for replacement on Smart Fans and Smart Grids. See details page 554.		
Dimensions Grid cut-out size (mm)	References	References	Filter type		References
92 x 92	**NSYCAG92DGC**	**NSYCAG92BPC**	M1	G2	**NSYCAF92DG**
125 x 125	**NSYCAG125DGC**	**NSYCAG125BPC**	M1	G2	**NSYCAF125DG**
125 x 125	**NSYCAG125DGC**	**NSYCAG125BPC**	M1	G3	**NSYCAF125G3DG**
223 x 223	**NSYCAG223DGC**	**NSYCAG291BPC**	M1	G2	**NSYCAF223DG**
223 x 223	**NSYCAG223DGC**	**NSYCAG291BPC**	M1	G3	**NSYCAF223G3DG**
291 x 291	**NSYCAG291DGC**	**NSYCAG223BPC**	M1	G2	**NSYCAF291DG**
291 x 291	**NSYCAG291DGC**	**NSYCAG223BPC**	M1	G3	**NSYCAF291G3DG**

	Dust Sensor	10 stickers and retainer flaps mini-tool kit	Fan Sensor
	Individual Dust Sensor ready to be implemented on any existing ClimaSys CV fan or ClimaSys CA grids in the brownfield installation or used as spare part.	Tool kit for digitalizing fans in brownfield installations without opening fan motor rear grids.	Individual Fan Sensor ready to be implemented on any existing fan in the brownfield installation or used as spare part.
References	**NSYCCAFSDUST**	**NSYCCABLK**	**NSYCCARPM**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Thermal management system

- Characteristics: The Smart fans are equipped with an axial motor, a protective housing on the front, rear surfaces, and a Smart filter with Dust sensor and a Fan sensor with infrared technology. The external smokey grid displays the status of the ventilation functions through the LED colours of the Dust sensor. This Smart filter can be replaced for maintenance during operation without risk of contact with the rotating element.
- Material of external grids: Injected thermoplastic (ASA PC). self-extinguishing according to UL 94 V-0.
- Colour of external grids: Smokey black RAL 9005
- Conditions of use: The external temperature must not exceed 30°C and must be more than 5°C lower than the temperature required in the enclosure. The Smart filters that equip the Smart fans must be replaced when the alarm is triggered Filterstat controller (see more details page 545)
  Storage Temperature: -40…+ 70°C
- Ingress protection rating (according to IEC 60529): IP54
- Mechanical protection rating (according to IEC 62262): IK08
- Installation: The cut-out template supplied with the device avoids the need for marking and helps protect the surface of the enclosure during handling.
- Options: For maintenance replacement of Smart filters please see spare parts references, page 549

Free flow rate with standard filter (m³/h)	Flow rate with outlet grille(s) (m³/h)		Voltage range (nominal voltage)	Absorbed power (max. intensity)	Noise level	External dimensions (cut-out)	Weight	Operating temperature	Max. static pressure
	1	2							
34 (50 Hz) 35 (60 Hz)	21 (50 Hz) 22 (60 Hz)	29 (50 Hz)	150 V...250 V (230 V)	4.5/4.8 W (0.16/0.17 A)	40/41 dB (A)	137 x 117 x 49 (92 x 92)	0.220 kg	-10...+ 70°C	29 Pa
34 (50 Hz) 35 (60 Hz)	23 (50 Hz) 24 (60 Hz)	35 (50 Hz)	75 V...125 V (115 V)	3.3/3.5 W (0.16/0.16 A)	40/41 dB (A)	137 x 117 x 49 (92 x 92)	0.220 kg	-10...+ 70°C	29 Pa
74 (50 Hz) 87 (60 Hz)	52 (50 Hz) 61 (60 Hz)	60 (50 Hz)	175 V...253 V (230 V)	17/15 W (0.121/0.097 A)	46/49 dB (A)	170 x 150 x 62 (125)	0.780 kg	-20…+60°C	50 Pa
68 (50 Hz) 81 (60 Hz)	54 (50 Hz) 63 (60 Hz)	62 (50 Hz)	75 V...126 V (115 V)	16/15 W (0.207/0.179 A)	46/49 dB (A)	170 x 150 x 62 (125)	0.780 kg	-20…+60°C	50 Pa
142 (50 Hz) 170 (60 Hz)	130 (50 Hz) 151 (60 Hz)	138 (50 Hz) 152 (60 Hz)	175 V...253 V (230 V)	16.3/14.3 W (0.12/0.94 A)	50/51 dB (A)	268 x 248 x 104 (223 x 223)	1.140 kg	-20…+60°C	50 Pa
151 (50 Hz) 173 (60 Hz)	130 (50 Hz) 151 (60 Hz)	138 (50 Hz) 156 (60 Hz)	75 V...126 V (115 V)	15.5/14.4 W (0.20/0.18 A)	50/51 dB (A)	268 x 248 x 104 (223 x 223)	1.140 kg	-20…+60°C	50 Pa
259 (50 Hz) 307 (60 Hz)	209 (50 Hz) 251 (60 Hz)	218 (50 Hz)	145 V...253 V (230 V)	36/37 W (0.17/0.16 A)	55/56 dB (A)	268 x 248 x 116 (223 x 223)	1.3 kg	-10...+ 70°C	158 Pa
259 (50 Hz) 307 (60 Hz)	209 (50 Hz) 251 (60 Hz)	221 (50 Hz)	75 V...126 V (115 V)	36/36 W (0.35/0.32 A)	55/56 dB (A)	268 x 248 x 116 (223 x 223)	1.3 kg	-10…+70°C	158 Pa
502 (50 Hz) 526 (60 Hz)	412 (50 Hz) 448 (60 Hz)	420 (50 Hz)	207 V...244 V (230 V)	68/85 W (0.52/0.370 A)	59/59 dB (A)	336 x 316 x 161 (291 x 291)	3.2 kg	-15…+60°C	140 Pa
522 (50 Hz) 526 (60 Hz)	425 (50 Hz) 417 (60 Hz)	434 (50 Hz)	103 V...122 V (115 V)	65/83 W (0.60/0.72 A)	59/59 dB (A)	336 x 316 x 161 (291 x 291)	3.2 kg	-15…+60°C	140 Pa
638 (50 Hz) 603 (60 Hz)	500 (50 Hz) 462 (60 Hz)	528 (50 Hz)	207 V...244 V (230 V)	150/195 W (0.65/0.85 A)	76/75 dB (A)	336 x 316 x 162 (291 x 291)	4.1 kg	-15…+60°C	170 Pa
783 (50 Hz) 744 (60 Hz)	643 (50 Hz) 442 (60 Hz)	654 (50 Hz)	103 V...122 V (115 V)	145/182 W (1.279/1.6 A)	78/77 dB (A)	336 x 316 x 162 (291 x 291)	4.1 kg	-15…+60°C	170 Pa
731 (50 Hz) 603 (60 Hz)	598 (50 Hz) 368 (60 Hz)	609 (50 Hz)	396 V...466 V (400 V)	126/126 W (0.226/0.232 A)	77/75 dB (A)	336 x 316 x 162 (291 x 291)	4.1 kg	-15…+60°C	170 Pa

How to identify whether your ClimaSys CV fan has been upgraded to install the CSVS solution?

Your installation			Installation of CVS solution	
Greenfield		NSYCV●●●DG	☑	It's possible to install the CSVS solution
Brownfield		NSYCV●●●LPF	☒	You need to order **NSYCCABLK**
		NSYCV●●●LPF	☑	It's possible to install the CSVS solution

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Type of connection				
by cable ★ Forced ventilation fan 38 m³/h	by faston (1) Forced ventilation fan 85 m³/h	by faston (1) Forced ventilation fan 165 m³/h	by faston (1) Forced ventilation fan 300 m³/h	by terminal block Forced ventilation fan 560-850 m³/h
NSYCVF38M230DG New	-	-	-	-
NSYCVF38M115DG New	-	-	-	-
-	**NSYCVF85M230DG** New	-	-	-
-	**NSYCVF85M115DG** New	-	-	-
-	-	**NSYCVF165M230DG** New	-	-
-	-	**NSYCVF165M115DG** New	-	-
-	-	-	**NSYCVF300M230DG** New	-
-	-	-	**NSYCVF300M115DG** New	-
-	-	-	-	**NSYCVF560M230DG** New
-	-	-	-	**NSYCVF560M115DG** New
-	-	-	-	**NSYCVF850M230DG** New
-	-	-	-	**NSYCVF850M115DG** New
-	-	-	-	**NSYCVF850M400DG** New

(1) Fan models with connection are delivered with the connection cord included (2 metres).

★ Warning: The fan **NSYCVF38M230DG** and **NSYCVF38M115DG** MUST NOT be connected to a power conversion module, an inverter or UPS type of power supply !

High-visibility LED indicators

Dust filter alarm
0%-60%

Dust filter alarm
60%-80%

Dust filter alarm
>80%

Fan lifespan
ended

PING function
Identification of the sensor on the panel
(flashing blue color)

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Thermal management system

Filterstat Controllers (4 ports) and thermal hubs (8 ports)

- Trim frame IP55 for installing the Filterstat Controller and thermal
- Hub on enclosure doors, side panels etc.

NSYCCOFST30V

Characteristics	Voltage	References
Filterstat Controllers	30 V AC/DC	**NSYCCOFST30V** New
Filterstat Controllers	90-250 V AC	**NSYCCOFST90250V** New

NSYCCOFSEM8U1

Characteristics	Voltage	References
Thermal Hub	30 V AC/DC	**NSYCCOFSEM8U1** New
Thermal Hub	90-250 V AC	**NSYCCOFSEM8U2** New

Modular frame IP55

NSYCCOFR55

Characteristics	References
Modular frame	**NSYCCOFR55** New

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Thermal management system

Filterstat communication cable

- Black unshielded cable with 2 connectors on each side.
- Material: PVC.

NSYCCA50MFST

Characteristics	References
Filterstat communication cable	**NSYCCA50MFST** New
Filterstat communication cable	**NSYCCA100MFST** New
Filterstat communication cable	**NSYCCA150MFST** New
Filterstat communication cable	**NSYCCA200MFST** New
Filterstat communication cable	**NSYCCA300MFST** New
Filterstat communication cable	**NSYCCA400MFST** New
Filterstat communication cable	**NSYCCA500MFST** New

Brownfield kits

NSYCCFSBRKIT92

Characteristics	Grid cut-out size (mm)	Cable size (m)	References
Brownfield kit	92 x 92	0.5	**NSYCCFSBRKIT92** New
Brownfield kit	125 x 125	1	**NSYCCFSBRKIT125** New
Brownfield kit	223 x 223	1.5	**NSYCCFSBRKIT223** New
Brownfield kit	291 x 291	2	**NSYCCFSBRKIT291** New

Smart ventilation systems

NSYCVF38M115DG

Characteristics	References
Smart ventilation systems, 38 m³/h 115 V IP54	**NSYCVF38M115DG** New
Smart ventilation systems, 38 m³/h 230 V IP54	**NSYCVF38M230DG** New
Smart ventilation systems, 85 m³/h 115 V IP54	**NSYCVF85M115DG** New
Smart ventilation systems, 85 m³/h 230 V IP54	**NSYCVF85M230DG** New
Smart ventilation systems, 165 m³/h 115 V IP54	**NSYCVF165M115DG** New
Smart ventilation systems, 165 m³/h 230 V IP54	**NSYCVF165M230DG** New
Smart ventilation systems, 300 m³/h 115 V IP54	**NSYCVF300M115DG** New
Smart ventilation systems, 300 m³/h 230 V IP54	**NSYCVF300M230DG** New
Smart ventilation systems, 560 m³/h 115 V IP54	**NSYCVF560M115DG** New
Smart ventilation systems, 582 m³/h 230 V IP54	**NSYCVF560M230DG** New
Smart ventilation systems, 850 m³/h 115 V IP54	**NSYCVF850M115DG** New
Smart ventilation systems, 850 m³/h 230 V IP54	**NSYCVF850M230DG** New
Smart ventilation systems, 850 m³/h 400 V IP54	**NSYCVF850M400DG** New

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Thermal management system

Smart Grid systems

Complete Smart Grids

- a Dust Sensor
- a SmartFilter G2
- Material: Injected thermoplastic (PC), self-extinguishing according to UL 94 V-0
- Colour: Smokey black RAL 9005
- Ingress protection rating (according to IEC 60529): IP54

NSYCAG92DG

Characteristics	Height (mm)	Width (mm)	Depth (mm)	Cut-out (mm)	References
Complete Smart Grid	137	117	13	92 x 92	**NSYCAG92DG** New
Complete Smart Grid	170	150	15	125 x 125	**NSYCAG125DG** New
Complete Smart Grid	268	248	18	223 x 223	**NSYCAG223DG** New
Complete Smart Grid	336	316	18	291 x 291	**NSYCAG291DG** New

External Smart Grids (without internal grid systems)

- External grids equipped with G2 Smart filter and Dust Sensor to be installed in an existing grid support.
- Material: Injected thermoplastic (PC), self-extinguishing according to UL 94 V-0
- Colour: Smokey black RAL 9005
- Ingress protection rating (according to IEC 60529): IP54

NSYCAG92DGC

Characteristics	Height (mm)	Width (mm)	Depth (mm)	Cut-out (mm)	References
External Smart Grid	137	117	13	92 x 92	**NSYCAG92DGC** New
External Smart Grid	170	150	15	125 x 125	**NSYCAG125DGC** New
External Smart Grid	268	248	18	223 x 223	**NSYCAG223DGC** New
External Smart Grid	336	316	18	291 x 291	**NSYCAG291DGC** New

External smokey grids (external cover only)

- External grids to be installed in an existing grid support or used as spare part.
- Smart filter and Dust sensor to be ordered separately.
- Material: Injected thermoplastic (PC), self-extinguishing according to UL 94 V-0
- Colour: Smokey black RAL 9005
- Ingress protection rating (according to IEC 60529): IP54

NSYCAG92BPC

Characteristics	Height (mm)	Width (mm)	Depth (mm)	Cut-out (mm)	References
External Smart Grid	137	117	13	92 x 92	**NSYCAG92BPC** New
External Smart Grid	170	150	15	125 x 125	**NSYCAG125BPC** New
External Smart Grid	268	248	18	223 x 223	**NSYCAG291BPC** New
External Smart Grid	336	316	18	291 x 291	**NSYCAG223BPC** New

Smart filters

- Set of 5 Smart filters for replacement on Smart Fans and Smart Grids. For fans and grilles.
- Material: Polyester.
- Filters according to ISO 16890.
- Colour: White with green lettering

NSYCAF92DG

Characteristics	Height (mm)	Width (mm)	Cut-out (mm)	References
External Smart Grid, G2 M1 filters	137	117	92 x 92	**NSYCAF92DG** New
External Smart Grid, G2 M1 filters	170	150	125 x 125	**NSYCAF125DG** New
External Smart Grid, G2 M1 filters	268	248	223 x 223	**NSYCAF223DG** New
External Smart Grid, G2 M1 filters	336	316	291 x 291	**NSYCAF291DG** New
External Smart Grid, G3 M1 filters	170	150	125 x 125	**NSYCAF125G3DG** New
External Smart Grid, G3 M1 filters	268	248	223 x 223	**NSYCAF223G3DG** New
External Smart Grid, G3 M1 filters	336	316	291 x 291	**NSYCAF291G3DG** New

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Thermal management system

Dust Sensor

- Individual Dust Sensor ready to be implemented on any existing ClimaSys CV fan or ClimaSys CA grids in the brownfield installation or used as spare part.

NSYCCAFSDUST

Characteristics	References
Dust Sensor	**NSYCCAFSDUST** New

Fan Sensor

- Individual Fan Sensor ready to be implemented on any existing fan in the brownfield installation or used as spare part.

NSYCCARPM

Characteristics	References
Fan Sensor	**NSYCCARPM** New

10 stickers and retainer flaps mini-tool kit

- Tool kit for digitalizing fans in brownfield installations without opening fan motor rear grids.


NSYCCABLK

Characteristics	References
10 stickers and retainer flaps mini-tool kit	**NSYCCABLK** New

Anti-vandalism kit

NSYCAAPV



- Helps prevent the grid from being opened from the outside.
- The unlocking thumbwheel is accessed from the inside of the enclosure.
- Colour: RAL 7011

Supply:
Minor packaging 2

Characteristics	References
Anti-vandalism kit	**NSYCAAPV** New

Filter Pocket

NSYDPA5



- Fixed by adhesive tape
- Material: Polystyrene (PS)
- Colour: RAL 7035 grey (NSYDPA4: RAL 9001)

(1) Not compatible with 19" chassis or modular distribution installation.

Supply:
1 plastic document pocket

Characteristics	Smart filter references	Dimensions			References
		A (mm)	B (mm)	C (mm)	
Pocket A5	NSYCAF92•DG and NSYCAF125•DG	137	117	13	**NSYDPA5**
Pocket A4	NSYCAF223•DG	170	150	15	**NSYDPA4**
Pocket A4 (1)	NSYCAF223•DG	268	248	18	**NSYDPA44**
Pocket A3	NSYCAF291•DG	336	316	18	**NSYDPA3**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

ClimaSys (CSVS) General wiring diagram



Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Thermal management system Forced ventilation

- Characteristics: The fans comprise an axial motor, a protective housing on the front and rear surfaces and a filter designed to retain dust particles. This filter can be replaced during operation without risk of contact with the rotating element.
- Material external grids: Injected thermoplastic (ASA PC). self-extinguishing according to UL 94 V-0
- Colour external grids: RAL 7035 grey as standard
- Conditions of use: The external temperature must not exceed 30°C and must be more than 5°C lower than the temperature wanted in the enclosure. The filters that equip the fans must be cleaned and replaced regularly. The ambient air must be relatively clean and overfrequent filter replacement should be avoided. Bear in mind the pressure losses caused by the outlet element (grille with filter, ventilation louvre or simple opening) when determining the fan flow rate Storage Temperature: -40…+ 70°C
- Ingress protection rating (according to IEC 60529): IP54
- Mechanical protection rating (according to IEC 62262): IK08
- Installation: The cut-out template supplied with the device avoids the need for marking and helps protect the surface of the enclosure during handling
- Options: The device can be equipped with a filter that provides even more efficient protection for your sensitive facilities against dust particles

Free flow rate with standard filter (m^3/h)	Flow rate with outlet grille(s) (m^3/h)		Voltage range (nominal voltage)	Absorbed power (max. intensity)	Noise level	External dimensions (cut-out)	Weight	Operating temperature	Max. static pressure
	1	2							
38 (50 Hz) 39 (60 Hz)	25 (50 Hz) 26 (60 Hz)	33 (50 Hz)	150 V...250 V (230 V)	4.5/4.8 W (0.16/0.17 A)	40/41 dB (A)	137 x 117 x 49 (92 x 92)	0.220 kg	-10...+ 70°C	29 Pa
38 (50 Hz) 39 (60 Hz)	27 (50 Hz) 28 (60 Hz)	35 (50 Hz)	75 V...125 V (115 V)	3.3/3.5 W (0.16/0.16 A)	40/41 dB (A)	137 x 117 x 49 (92 x 92)	0.220 kg	-10...+ 70°C	29 Pa
58	39	47	10 V...27.6 V (24 V DC)	3.6 W (0.18 A)	40/41 dB (A)	137 x 117 x 49 (92 x 92)	0.230 kg	-10...+ 70°C	29 Pa
44	34	41	36 V...56 V (48 V DC)	3.6 W (70 mA)	40/41 dB (A)	137 x 117 x 49 (92 x 92)	0.230 kg	-10...+ 70°C	29 Pa
85 (50 Hz) 98 (60 Hz)	63 (50 Hz) 72 (60 Hz)	71 (50 Hz)	175 V...253 V (230 V)	17/15 W (0.121/0.097 A)	46/49 dB (A)	170 x 150 x 62 (125)	0.780 kg	-20…+60°C	50 Pa
79 (50 Hz) 92 (60 Hz)	65 (50 Hz) 74 (60 Hz)	73 (50 Hz)	75 V...126 V (115 V)	16/15 W (0.207/0.179 A)	46/49 dB (A)	170 x 150 x 62 (125)	0.780 kg	-20…+60°C	50 Pa
80	57	77	10 V...27.6 V (24 V DC)	7.6 W (0.30 A)	46/49 dB (A)	170 x 150 x 62 (125)	0.480 kg	-10...+ 70°C	50 Pa
79	59	68	25 V...55.2 V (48 V DC)	8 W (0.173 A)	46/49 dB (A)	170 x 150 x 62 (125)	0.480 kg	-10...+ 70°C	50 Pa
165 (50 Hz) 193 (60 Hz)	153 (50 Hz) 171 (60 Hz)	161 (50 Hz) 175 (60 Hz)	175 V...253 V (230 V)	16.3/14.3 W (0.12/0.94 A)	50/51 dB (A)	268 x 248 x 104 (223 x 223)	1.140 kg	-20…+60°C	50 Pa
164 (50 Hz) 193 (60 Hz)	153 (50 Hz) 171 (60 Hz)	161 (50 Hz) 179 (60 Hz)	75 V...126 V (115 V)	15.5/14.4 W (0.20/0.18 A)	50/51 dB (A)	268 x 248 x 104 (223 x 223)	1.140 kg	-20…+60°C	50 Pa
188	171	179	10 V...27.6 V (24 V DC)	8 W (0.3 A)	50/51 dB (A)	268 x 248 x 104 (223 x 223)	0.810 kg	-10...+ 70°C	50 Pa
193	171	179	25 V...55.2 V (48 V DC)	8.7 W (0.18 A)	50/51 dB (A)	268 x 248 x 104 (223 x 223)	0.810 kg	-10...+ 70°C	50 Pa
302 (50 Hz) 350 (60 Hz)	260 (50 Hz) 307 (60 Hz)	268 (50 Hz)	145 V...253 V (230 V)	36/37 W (0.17/0.16 A)	55/56 dB (A)	268 x 248 x 116 (223 x 223)	1.3 kg	-10...+ 70°C	158 Pa
302 (50 Hz) 350 (60 Hz)	263 (50 Hz) 307 (60 Hz)	271 (50 Hz)	75 V...126 V (115 V)	36/36 W (0.35/0.32 A)	55/56 dB (A)	268 x 248 x 116 (223 x 223)	1.3 kg	-10…+70°C	158 Pa
262	221	229	12 V...30 V (24 V DC)	13 W (0.53 A)	55/56 dB (A)	268 x 248 x 103.4 (223 x 223)	1.1 kg	-10...+ 70°C	158 Pa
247	210	218	25 V...60 V (48 V DC)	11 W (0.24 A)	55/56 dB (A)	268 x 248 x 103.4 (223 x 223)	1.1 kg	-10…+70°C	158 Pa
562 (50 Hz) 586 (60 Hz)	473 (50 Hz) 477 (60 Hz)	481 (50 Hz)	207 V...244 V (230 V)	68/85 W (0.52/0.370 A)	59/59 dB (A)	336 x 316 x 161 (291 x 291)	3.2 kg	-15…+60°C	140 Pa
582 (50 Hz) 586 (60 Hz)	485 (50 Hz) 477 (60 Hz)	494 (50 Hz)	103 V...122 V (115 V)	65/83 W (0.60/0.72 A)	59/59 dB (A)	336 x 316 x 161 (291 x 291)	3.2 kg	-15…+60°C	140 Pa
838 (50 Hz) 803 (60 Hz)	718 (50 Hz) 568 (60 Hz)	728 (50 Hz)	207 V...244 V (230 V)	150/195 W (0.65/0.85 A)	76/75 dB (A)	336 x 316 x 162 (291 x 291)	4.1 kg	-15…+60°C	170 Pa
983 (50 Hz) 944 (60 Hz)	843 (50 Hz) 642 (60 Hz)	854 (50 Hz)	103 V...122 V (115 V)	145/182 W (1.279/1.6 A)	78/77 dB (A)	336 x 316 x 162 (291 x 291)	4.1 kg	-15…+60°C	170 Pa
931 (50 Hz) 803 (60 Hz)	798 (50 Hz) 568 (60 Hz)	809 (50 Hz)	396 V...466 V (400 V)	126/126 W (0.226/0.232 A)	77/75 dB (A)	336 x 316 x 162 (291 x 291)	4.1 kg	-15…+60°C	170 Pa

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Type of connection				
by cable Forced ventilation fan 38 m³/h	by faston [1] Forced ventilation fan 85 m³/h	by faston [1] Forced ventilation fan 165 m³/h	by faston [1] Forced ventilation fan 300 m³/h	by terminal block Forced ventilation fan 560-850 m³/h
NSYCVF38M230PF ★	-	-	-	-
NSYCVF38M115PF ★	-	-	-	-
NSYCVF38M24DPF	-	-	-	-
NSYCVF38M48DPF	-	-	-	-
-	**NSYCVF85M230PF**	-	-	-
-	**NSYCVF85M115PF**	-	-	-
-	**NSYCVF85M24DPF**	-	-	-
-	**NSYCVF85M48DPF**	-	-	-
-	-	**NSYCVF165M230PF**	-	-
-	-	**NSYCVF165M115PF**	-	-
-	-	**NSYCVF165M24DPF**	-	-
-	-	**NSYCVF165M48DPF**	-	-
-	-	-	**NSYCVF300M230PF**	-
-	-	-	**NSYCVF300M115PF**	-
-	-	-	**NSYCVF300M24DPF**	-
-	-	-	**NSYCVF300M48DPF**	-
-	-	-	-	**NSYCVF560M230PF**
-	-	-	-	**NSYCVF560M115PF**
-	-	-	-	**NSYCVF850M230PF**
-	-	-	-	**NSYCVF850M115PF**
-	-	-	-	**NSYCVF850M400PF**

[1] Fan models with connection are delivered with the connection cord included (2 metres).

★ Warning: The fan **NSYCVF38M230PF** and **NSYCVF38M115PF** MUST NOT be connected to a power conversion module, an inverter or UPS type of power supply !

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Thermal management system

Ventilation Systems, IP54 outlet grilles

- Delivered with G2 M1 synthetic standard filter according to ISO 16890.
- Material: Injected thermoplastic (ASA PC), self-extinguishing according to UL 94 V-0
- Colour: RAL 7035 grey
- Ingress protection rating (according to IEC 60529): IP54

NSYCAG92LPF

Characteristics	Height (mm)	Width (mm)	Depth (mm)	Cut-out (mm)	References
IP54 outlet grilles	137	117	13	92 x 92	**NSYCAG92LPF**
IP54 outlet grilles	170	150	15	125 x 125	**NSYCAG125LPF**
IP54 outlet grilles	268	248	18	223 x 223	**NSYCAG223LPF**
IP54 outlet grilles	336	316	18	291 x 291	**NSYCAG291LPF**

IP54 outlet grilles

- Cover for changing the colour of the standard gille RAL 7035 grey to RAL 7032.
- Material: Injected thermoplastic (ASA PC), self-extinguishing according to UL 94 V-0
- Colour: RAL 7032
- Ingress protection rating (according to IEC 60529): IP54

NSYCAG92LPC

Characteristics	Height (mm)	Width (mm)	Depth (mm)	Cut-out (mm)	References
IP54 outlet grilles	137	117	13	92 x 92	**NSYCAG92LPC**
IP54 outlet grilles	170	150	15	125 x 125	**NSYCAG125LPC**
IP54 outlet grilles	268	248	18	223 x 223	**NSYCAG223LPC**
IP54 outlet grilles	336	316	18	291 x 291	**NSYCAG291LPC**

Filters

Supply:
- G2 M1 synthetic standard filters, Filters for greasy environments G2 M1, G3 M1 synthetic fine filters: 5 units
- Stainless steel anti-insect filters: 1 unit

- For fans and grilles.
- Filters according to ISO 16890.

NSYCAF223T

Characteristics	Height (mm)	Width (mm)	Cut-out (mm)	References
G2 M1 synthetic standard filters	137	117	92 x 92	**NSYCAF92**
G2 M1 synthetic standard filters	170	150	125 x 125	**NSYCAF125**
G2 M1 synthetic standard filters	268	248	223 x 223	**NSYCAF223**
G2 M1 synthetic standard filters	336	316	291 x 291	**NSYCAF291**
Filters for greasy environments G2 M1	170	150	125 x 125	**NSYCAF125O**
Filters for greasy environments G2 M1	268	248	223 x 223	**NSYCAF223O**
Filters for greasy environments G2 M1	336	316	291 x 291	**NSYCAF291O**
G3 M1 synthetic fine filters	170	150	125 x 125	**NSYCAF125T**
G3 M1 synthetic fine filters	268	248	223 x 223	**NSYCAF223T**
G3 M1 synthetic fine filters	336	316	291 x 291	**NSYCAF291T**
Stainless steel anti-insect filters	137	117	92 x 92	**NSYCAF92M**
Stainless steel anti-insect filters	170	150	125 x 125	**NSYCAF125M**
Stainless steel anti-insect filters	268	248	223 x 223	**NSYCAF223M**
Stainless steel anti-insect filters	336	316	291 x 291	**NSYCAF291M**

Anti-vandalism kit

NSYCAAPV



- Helps prevent the grid from being opened from the outside.
- The unlocking thumbwheel is accessed from the inside of the enclosure.
- Colour: RAL 7011

Supply:
Minor packaging 2

Characteristics	References
Anti-vandalism kit	**NSYCAAPV** New

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

ClimaSys CV, Accessories

Covers IP55

- This solution helps protect the fan or the grille from any direct sprays.
- The cover is the preferred solution to help guarantee the following:
  - an efficient air flow for cooling,
  - IP55 rating.
- Material: 2 materials available:
  - steel painted with epoxy polyester powder (RAL 7035 grey) for outdoor applications
  - stainless steel 304L for food and beverage applications
- Ingress protection rating (according to IEC 60529): IP55
- Mechanical protection rating (according to IEC 62262): IK10
- Certifications: UL 508A
- Installation: Double insulation maintained if installed in an insulated enclosure. The cover is placed over the fan or the grille with a filter located at the bottom of the cover to help prevent the entry of particles. Easy access to the filter: Only two screws needed. When mounting: Remove the external part of the fan or the grille as well as the filter.

(1) Values given for a fan powered at 230 V. For other voltages, the values are similar



Supply:
It is necessary to order 1 fan + 1 grille + 2 covers to have a complete system

NSYCAP125LZF

Characteristics	Flow rate (m³/h) with cover (1)		Dimensions		References
	Free	With 1 outlet grille	External (mm)	Cut-out (mm)	
Steel painted RAL 7035 grey	74	53	240 x 180 x 60	125 x 125	**NSYCAP125LZF**
Steel painted RAL 7035 grey	110	82	350 x 305 x 80	223 x 223	**NSYCAP223LZF**
Steel painted RAL 7035 grey	165	123	350 x 305 x 80	223 x 223	**NSYCAP223LZF**
Steel painted RAL 7035 grey	316	265	430 x 373 x 105	291 x 291	**NSYCAP291LZF**
Steel painted RAL 7035 grey	502	430	430 x 373 x 105	291 x 291	**NSYCAP291LZF**
Stainless steel 304L	74	53	240 x 180 x 60	125 x 125	**NSYCAP125LXF**
Stainless steel 304L	110	82	350 x 305 x 80	223 x 223	**NSYCAP223LXF**
Stainless steel 304L	165	123	350 x 305 x 80	223 x 223	**NSYCAP223LXF**
Stainless steel 304L	316	265	430 x 373 x 105	291 x 291	**NSYCAP291LXF**
Stainless steel 304L	502	430	430 x 373 x 105	291 x 291	**NSYCAP291LXF**

Spare filter for cover

Supply:
Emb. mineur 5 p

NSYCAF125L55

Characteristics	Flow rate (m³/h) with cover (1)		Dimensions		References
	Free	With 1 outlet grille	External (mm)	Cut-out (mm)	
Spare filter for cover	74	53	240 x 180 x 60	125 x 125	**NSYCAF125L55**
Spare filter for cover	110	82	350 x 305 x 80	223 x 223	**NSYCAF223L55**
Spare filter for cover	165	123	350 x 305 x 80	223 x 223	**NSYCAF223L55**
Spare filter for cover	316	265	430 x 373 x 105	291 x 291	**NSYCAF291L55**
Spare filter for cover	502	430	430 x 373 x 105	291 x 291	**NSYCAF291L55**

Characteristics				Fan	Grille
Flow rate (m³/h) with cover (1)		Dimensions (mm)		RAL 7035 grey	RAL 7035 grey
Free	With 1 outlet grille	External	Cut-out	References	References
74	53	240 x 180 x 60	125 x 125	**NSYCVF85M230PF**	**NSYCAG125LPF**
110	82	350 x 305 x 80	223 x 223	**NSYCVF165M230PF**	**NSYCAG223LPF**
165	123	350 x 305 x 80	223 x 223	**NSYCVF300M230PF**	**NSYCAG223LPF**
316	265	430 x 373 x 105	291 x 291	**NSYCVF560M230PF**	**NSYCAG291LPF**
502	430	430 x 373 x 105	291 x 291	**NSYCVF850M230PF**	**NSYCAG291LPF**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Thermal management system

Ventilation system Heavy duty

Fanbox



- Free flow rate: 550 m3/h (50/60 Hz).
- Minimal depth inside the enclosure (90 mm).
- Allows multiple cooling architectures (see page 564 and 565).
- Material: Plastic
- Colour: RAL 7016 dark grey

Supply:
1 (grille not included)

NSYCVF550M24FB

Characteristics	Voltage	References
Fanbox	24 V DC	**NSYCVF550M24FB**
Fanbox	24 V DC	**NSYCVF550M48FB**
Fanbox	115 V AC	**NSYCVF550M115FB**
Fanbox	230 V AC	**NSYCVF550M230FB**

IP55 HD Metal Grille



- Slim grille (35 mm external depth).
- Includes a G3 M1
- Material: Steel with anti-corrosive coating + plastic PA6 / GF25 for fixing frame
- Finish: Structured finish, 100 % polyester powder
- Colour: RAL 7035 grey
- Ingress protection rating: IP55 according to IEC 60529
- Mechanical protection rating: IK10 according to IEC 62262

Supply:
1 grille delivered with G3 M1 type synthetic filter (215 x 215 mm) and fixings

NSYCAG223LFHD

Characteristics	References
IP55 HD Metal Grille	**NSYCAG223LFHD**

Roof filter for fanbox (extraction mode)

- Roof G2 round synthetic filter designed to cover the fanbox. Covers completely the fanbox and helps to protect it from dust and humidity. Mandatory for fanbox installation in the Roof ventilation module for IP55 configurations.
- Material: 100 % polyester fibres
- Colour: White

Supply:
1

NSYCAF190

Characteristics	References
Roof filter for fanbox	**NSYCAF190**

Filter

- Replacement G3 M1 type synthetic filter for HD metal grille.
- Dimensions: 215 x 215 mm.
- Material: 100 % polyester fibres
- Colour: White

Supply:
5

NSYCAF223T

Characteristics	Height (mm)	Width (mm)	Depth (mm)	Cut-out (mm)	References
G3 M1 synthetic fine filters	268	248	18	223 x 223	**NSYCAF223T**

Anti-vandalism kit for HD metal grille

Comment:
not compatible with **NSYSPLA150**

- Fixings that help to prevent to open the grille from the outside with standard tools (EN 1627-1630:2011 Class 2).
- Quick installation without tools.
- Material: Steel with anticorrosive coating + plastic for fixing screws

Supply:
4 grip knob
4 clip nuts

NSYCAAPVHD

Characteristics	References
Anti-vandalism kit for HD metal grille	**NSYCAAPVHD**

12
CV

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Life Is On Schneider Electric

Thermal management system



1 IP55 metal grille
2 Fanbox



2 Fanbox
3 Roof ventilated module

	S-Line				T-Line			
Architecture benefits	• Most common and competitive architecture • Maximum heat dissipation to extract 800 W-1000 W • ΔT° of 5°C • Easy access to mount-dismount fanbox • Air flow in horizontal axis				• High capacity of extraction calories up to 1500 W • Noise level with 1 fan: 55 dB when installed inside the upper ventilation module • ΔT° of 5°C • Air flow in vertical axis			
	IP55 metal grille		Fanbox		IP55 metal grille		Fanbox (1 filter NSYCAF190 for each Fanbox)	Roof ventilation module
	Door	Side	Door	Side	Door	Side		

Polyester outdoor HD enclosure									
References	Amount to be installed				Amount to be installed				References
NSYPHDT553	-	-	-	-	-	-	-	-	-
NSYPHDT553P	-	-	-	-	-	-	-	-	-
NSYPHDT753	-	-	-	-	-	-	-	-	-
NSYPHDT753P	1 to 2	-	1 to 2	-	1 to 2	-	-	-	-
NSYPHDZT774	-	1 to 2	-	1 to 2	-	1 to 2	1 to 2	1	**NSYPCVR74HD**
NSYPHDZT774P	1 to 2	1 to 2	1 to 2	1 to 2	1 to 2	1 to 2	1 to 2	1	**NSYPCVR74HD**
NSYPHDZT776	-	1 to 2	-	1 to 2	-	1 to 2	1 to 2	1	**NSYPCVR76HD**
NSYPHDZT776P	1 to 2	1 to 2	1 to 2	1 to 2	1 to 2	1 to 2	1 to 2	1	**NSYPCVR76HD**
NSYPHDZT1054	-	1	-	1	-	1	1	1	**NSYPCVR54HD**
NSYPHDZT1054P	1 to 2	1	1 to 2	1	1 to 2	1	1	1	**NSYPCVR54HD**
NSYPHDZT1074	-	1 to 2	-	1 to 2	-	1 to 2	1 to 2	1	**NSYPCVR74HD**
NSYPHDZT1074P	1 to 4	1 to 2	1 to 4	1 to 2	1 to 4	1 to 2	1 to 2	1	**NSYPCVR74HD**
NSYPHDZT12124	-	1 to 3	-	1 to 3	-	1 to 3	1 to 3	1	**NSYPCVR124HD**
NSYPHDZT12124P	1 to 4	1 to 3	1 to 4	1 to 3	1 to 4	1 to 3	1 to 3	1	**NSYPCVR124HD**
NSYPHDZT12126	-	1 to 3	-	1 to 3	-	1 to 3	1 to 3	1	**NSYPCVR126HD**
NSYPHDZT12126P	1 to 4	1 to 3	1 to 4	1 to 3	1 to 4	1 to 3	1 to 3	1	**NSYPCVR126HD**
NSYPHDZT1254	-	1	-	1	-	1	1	1	**NSYPCVR54HD**
NSYPHDZT1254P	1 to 3	1	1 to 3	1	1 to 3	1	1	1	**NSYPCVR54HD**
NSYPHDZT1274	-	1 to 2	-	1 to 2	-	1 to 2	1 to 2	1	**NSYPCVR74HD**
NSYPHDZT1274P	1 to 4	1 to 2	1 to 4	1 to 2	1 to 4	1 to 2	1 to 2	1	**NSYPCVR74HD**
NSYPHDZT1276	-	1 to 2	-	1 to 2	-	1 to 2	1 to 2	1	**NSYPCVR76HD**
NSYPHDZT1276P	1 to 4	1 to 2	1 to 4	1 to 2	1 to 4	1 to 2	1 to 2	1	**NSYPCVR76HD**
NSYPHDZT15124	-	1 to 3	-	1 to 3	-	1 to 3	1 to 3	1	**NSYPCVR124HD**
NSYPHDZT15124P	1 to 4	1 to 3	1 to 4	1 to 3	1 to 4	1 to 3	1 to 3	1	**NSYPCVR124HD**
NSYPHDZT15126	-	1 to 3	-	1 to 3	-	1 to 3	1 to 3	1	**NSYPCVR126HD**
NSYPHDZT15126P	1 to 4	1 to 3	1 to 4	1 to 3	1 to 4	1 to 3	1 to 3	1	**NSYPCVR126HD**
NSYPHDZT1574	-	1 to 2	-	1 to 2	-	1 to 2	1 to 2	1	**NSYPCVR74HD**
NSYPHDZT1574P	1 to 4	1 to 2	1 to 4	1 to 2	1 to 4	1 to 2	1 to 2	1	**NSYPCVR74HD**
NSYPHDZT1576	-	1 to 2	-	1 to 2	-	1 to 2	1 to 2	1	**NSYPCVR76HD**
NSYPHDZT1576P	1 to 4	1 to 2	1 to 4	1 to 2	1 to 4	1 to 2	1 to 2	1	**NSYPCVR76HD**
NSYPHDZT2074	-	1 to 2	-	1 to 2	-	1 to 2	1 to 2	1	**NSYPCVR74HD**
NSYPHDZT2074P	1 to 4	1 to 2	1 to 4	1 to 2	1 to 4	1 to 2	1 to 2	1	**NSYPCVR74HD**

Steel outdoor HD enclosure									
NSYS3HD8630	1 to 2	-	1 to 2	-	1 to 2	-	-	-	-
NSYS3HD8840	1 to 2	1 to 2	1 to 2	1 to 2	1 to 2	1 to 2	1 to 2	1	**NSYS3CVR84HD**
NSYS3HD10640	1 to 2	1 to 2	1 to 2	1 to 2	1 to 2	1 to 2	1	1	**NSYS3CVR64HD**
NSYS3HD10840	1 to 4	1 to 2	1 to 4	1 to 2	1 to 4	1 to 2	1 to 2	1	**NSYS3CVR84HD**
NSYSFHD12640	1 to 3	1 to 3	1 to 3	1 to 3	1 to 3	1 to 3	1	1	**NSYSFCVR64HD**
NSYSFHD12660	1 to 3	1 to 3	1 to 3	1 to 3	1 to 3	1 to 3	1	1	**NSYSFCVR66HD**
NSYSFHD12840	1 to 4	1 to 3	1 to 4	1 to 3	1 to 4	1 to 3	1 to 2	1	**NSYSFCVR84HD**
NSYSFHD12860	1 to 4	1 to 3	1 to 4	1 to 3	1 to 4	1 to 3	1 to 2	1	**NSYSFECA66HD**
NSYSFHD16660	1 to 4	1 to 4	1 to 4	1 to 4	1 to 4	1 to 4	1	1	**NSYSFCVR66HD**
NSYSFHD16840	1 to 4	1 to 4	1 to 4	1 to 3	1 to 4	1 to 3	1 to 2	1	**NSYSFCVR84HD**
NSYSFHD16860	1 to 4	1 to 4	1 to 4	1 to 4	1 to 4	1 to 4	1 to 2	1	**NSYSFECA66HD**
NSYSFHD20840	1 to 4	1 to 4	1 to 4	1 to 4	1 to 4	1 to 4	1 to 2	1	**NSYSFCVR84HD**
NSYSFHD1212402D	1 to 4	1 to 3	1 to 4	1 to 2	1 to 4	1 to 2	1 to 3	1	**NSYSFCVR124HD**
NSYSFHD1212602D	1 to 4	1 to 3	1 to 4	1 to 3	1 to 4	1 to 2	1 to 3	1	**NSYSFCVR126HD**
NSYSFHD1612402D	1 to 4	1 to 4	1 to 4	1 to 3	1 to 4	1 to 3	1 to 3	1	**NSYSFCVR124HD**
NSYSFHD1612602D	1 to 4	1 to 4	1 to 4	1 to 3	1 to 4	1 to 3	1 to 3	1	**NSYSFCVR126HD**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.



2 Fanbox
3 Roof ventilated module
4 Ventilated plinths
5 IP54 grille

This table helps to configure thermal architectures, but it is highly recommended to use ProClima Software to help ensure theright thermal solution according to the selected architecture.

I-Line

- Integrated architecture particularly suitable for public areas
- High capacity of extraction calories up to 1500 W
- Noise level with 1 fan: 55 dB when installed inside the upper ventilation module
- Good extraction flow rate power
- Air flow in vertical axis

IP54 outlet grille (NSY-CAG223LPF + G3 filter NSYCAF223T)		Ventilated plinths		Fanbox (1 filter NSYCAF190 for each Fanbox)		Roof ventilation module	
Amount to be installed		References		Amount to be installed		References	
-	-	-	-	-	-	-	
-	-	-	-	-	-	-	
-	-	-	-	-	-	-	
-	-	-	-	-	-	-	
1 to 2	1	**NSYZZ274VHD**	-	1 to 2	1	**NSYPCVR74HD**	
1 to 2	1	**NSYZZ274VHD**	-	1 to 2	1	**NSYPCVR74HD**	
1 to 2	1	**NSYZZ276VHD**	-	1 to 2	1	**NSYPCVR76HD**	
1 to 2	1	**NSYZZ276VHD**	-	1 to 2	1	**NSYPCVR76HD**	
1	1	**NSYZZ254VHD**	-	1	1	**NSYPCVR54HD**	
1	1	**NSYZZ254VHD**	-	1	1	**NSYPCVR54HD**	
1 to 2	1	**NSYZZ274VHD**	-	1 to 2	1	**NSYPCVR74HD**	
1 to 2	1	**NSYZZ274VHD**	-	1 to 2	1	**NSYPCVR74HD**	
1 to 3	1	**NSYZZ2124VHD**	-	1 to 3	1	**NSYPCVR124HD**	
1 to 3	1	**NSYZZ2124VHD**	-	1 to 3	1	**NSYPCVR124HD**	
1 to 3	1	**NSYZZ2126VHD**	-	1 to 3	1	**NSYPCVR126HD**	
1 to 3	1	**NSYZZ2126VHD**	-	1 to 3	1	**NSYPCVR126HD**	
1	1	**NSYZZ254VHD**	-	1	1	**NSYPCVR54HD**	
1	1	**NSYZZ254VHD**	-	1	1	**NSYPCVR54HD**	
1 to 2	1	**NSYZZ274VHD**	-	1 to 2	1	**NSYPCVR74HD**	
1 to 2	1	**NSYZZ274VHD**	-	1 to 2	1	**NSYPCVR74HD**	
1 to 2	1	**NSYZZ276VHD**	-	1 to 2	1	**NSYPCVR76HD**	
1 to 2	1	**NSYZZ276VHD**	-	1 to 2	1	**NSYPCVR76HD**	
1 to 3	1	**NSYZZ2124VHD**	-	1 to 3	1	**NSYPCVR124HD**	
1 to 3	1	**NSYZZ2124VHD**	-	1 to 3	1	**NSYPCVR124HD**	
1 to 3	1	**NSYZZ2126VHD**	-	1 to 3	1	**NSYPCVR126HD**	
1 to 3	1	**NSYZZ2126VHD**	-	1 to 3	1	**NSYPCVR126HD**	
1 to 2	1	**NSYZZ274VHD**	-	1 to 2	1	**NSYPCVR74HD**	
1 to 2	1	**NSYZZ274VHD**	-	1 to 2	1	**NSYPCVR74HD**	
1 to 2	1	**NSYZZ276VHD**	-	1 to 2	1	**NSYPCVR76HD**	
1 to 2	1	**NSYZZ276VHD**	-	1 to 2	1	**NSYPCVR76HD**	
1 to 2	1	**NSYZZ274VHD**	-	1 to 2	1	**NSYPCVR74HD**	
1 to 2	1	**NSYZZ274VHD**	-	1 to 2	1	**NSYPCVR74HD**	

1	1	**NSYSPFVX6200**	**NSYSPSX3200**	-	-	-
1 to 2	1	**NSYSPFVX8200**	**NSYSPLVX4200**	1 to 2	1	**NSYS3CVR84HD**
1	1	**NSYSPFVX6200**	**NSYSPLVX4200**	1	1	**NSYS3CVR64HD**
1	1	**NSYSPFVX8200**	**NSYSPLVX4200**	1 to 2	1	**NSYS3CVR84HD**
1	1	**NSYSPFVX6200**	**NSYSPLVX4200**	1	1	**NSYSFCVR64HD**
1	1	**NSYSPFVX6200**	**NSYSPLVX6200**	1	1	**NSYSFCVR66HD**
1 to 2	1	**NSYSPFVX8200**	**NSYSPLVX4200**	1 to 2	1	**NSYSFCVR84HD**
1 to 2	1	**NSYSPFVX8200**	**NSYSPLVX6200**	1 to 2	1	**NSYSFECA66HD**
1	1	**NSYSPFVX6200**	**NSYSPLVX6200**	1	1	**NSYSFCVR66HD**
1 to 2	1	**NSYSPFVX8200**	**NSYSPLVX4200**	1 to 2	1	**NSYSFCVR84HD**
1 to 2	1	**NSYSPFVX8200**	**NSYSPLVX6200**	1 to 2	1	**NSYSFECA66HD**
1 to 2	1	**NSYSPFVX8200**	**NSYSPLVX4200**	1 to 2	1	**NSYSFCVR84HD**
1 to 3	1	**NSYSPFVX12200**	**NSYSPLVX4200**	1 to 3	1	**NSYSFCVR124HD**
1 to 3	1	**NSYSPFVX12200**	**NSYSPLVX6200**	1 to 3	1	**NSYSFCVR126HD**
1 to 3	1	**NSYSPFVX12200**	**NSYSPLVX4200**	1 to 3	1	**NSYSFCVR124HD**
1 to 3	1	**NSYSPFVX12200**	**NSYSPLVX6200**	1 to 3	1	**NSYSFCVR126HD**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Thermal management system

EMC ventilation Systems

EMC IP54 fan

- To effectively protect the equipment against electromagnetic disruptions, the EMC fan is equipped with:
  - a steel frame covering the plastic elements (self-extinguishing ABS according to standard UL94 V0),
  - a metal grille attached to the frame,
  - a beryllium gasket helping guarantee conductivity between the perimeter of the fan unit and the enclosure.
- Ingress protection rating (according to IEC 60529): IP54

For more details see page 570

NSY17990

Characteristics	Flow rate (m³/h)	Voltage (V)	Dimensions External (mm)	Cut-out (mm)	References
EMC IP54 fan	61	230	145 x 145 x 70	126 x 126	**NSY17990**
EMC IP54 fan	156	230	252 x 252 x 97	224 x 224	**NSY17991**
EMC IP54 fan	480	230	320 x 320 x 150	292 x 292	**NSY17992**

EMC IP54 outlet grille

- Grille equipped with:
  - a steel frame covering the plastic elements (self-extinguishing ABS according to standard UL 94 V-0),
  - a metal grille attached to the frame,
  - a beryllium gasket helping guarantee conductivity between the perimeter of the grille and the enclosure.
- Ingress protection rating (according to IEC 60529): IP54

NSY17996

Characteristics	Dimensions External (mm)	Cut-out (mm)	References
EMC IP54 outlet grille	145 x 145 x 70	126 x 126	**NSY17996**
EMC IP54 outlet grille	252 x 252 x 97	224 x 224	**NSY17997**
EMC IP54 outlet grille	320 x 320 x 150	292 x 292	**NSY17998**

EMC IP55 cover

- This solution helps guarantee protection against electromagnetic disruptions and helps guarantee IP55.
- The EMC cover is installed on the fans or standard IP54 outlet grilles.
- The cover, made from painted sheet steel for outdoor, completely covers the fan or outlet grille.
- Conductivity is obtained by means of:
  - a conductive coating (2 Ω),
  - a conductive copper braid.
- Colour: RAL 7035 grey
- Ingress protection rating (according to IEC 60529): IP55
- Mechanical protection rating (according to IEC 62262): IK10
- Certifications: UL 508A Type 3R

(1) Values given for a fan powered at 230 V. For other voltages, the values are similar



NSYCAP223LE

Characteristics	Flow rate (m³/h) with cover (1)		Dimensions		References
	Free	With 1 outlet grille	External (mm)	Cut-out (mm)	
Sheet steel painted for outdoor applications, RAL 7035 grey	110	82	350 x 305 x 80	223 x 223	**NSYCAP223LE**
Sheet steel painted for outdoor applications, RAL 7035 grey	165	123	350 x 305 x 80	223 x 223	**NSYCAP223LE**
Sheet steel painted for outdoor applications, RAL 7035 grey	316	265	430 x 373 x 105	291 x 291	**NSYCAP291LE**
Sheet steel painted for outdoor applications, RAL 7035 grey	502	430	430 x 373 x 105	291 x 291	**NSYCAP291LE**

Dimensions of IP54 and EMC covers



Dimensions (mm)								Cover references		
A	B	C	D	E	F	G	No. of fixing points	IP55		EMC
180	240	49	49	49	157	182	4	**NSYCAP125LZF**	**NSYCAP125LXF**	**NSYCAP125LE**
305	350	61	61	61	283	280	8	**NSYCAP223LZF**	**NSYCAP223LXF**	**NSYCAP223LE**
373	430	73	73	73	351	348	8	**NSYCAP291LZF**	**NSYCAP291LXF**	**NSYCAP291LE**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Life Is On Schneider Electric

Thermal management system

Spare filter for cover

(1) Values given for a fan powered at 230 V. For other voltages, the values are similar

Supply:
Emb. mineur 5 p

NSYCAF125L55

Characteristics	Flow rate (m³/h) with cover (1)		Dimensions		References
	Free	With 1 outlet grille	External (mm)	Cut-out (mm)	
Spare filter for cover	74	53	240 x 180 x 60	125 x 125	**NSYCAF125L55**
Spare filter for cover	110	82	350 x 305 x 80	223 x 223	**NSYCAF223L55**
Spare filter for cover	165	123	350 x 305 x 80	223 x 223	**NSYCAF223L55**
Spare filter for cover	316	265	430 x 373 x 105	291 x 291	**NSYCAF291L55**
Spare filter for cover	502	430	430 x 373 x 105	291 x 291	**NSYCAF291L55**

Fan

(1) Values given for a fan powered at 230 V. For other voltages, the values are similar

- Colour: RAL 7035 grey

NSYCVF85M230PF

Characteristics	Flow rate (m³/h) with cover (1)		Dimensions		References
	Free	With 1 outlet grille	External (mm)	Cut-out (mm)	
Fan	74	53	240 x 180 x 60	125 x 125	**NSYCVF85M230PF**
Fan	110	82	350 x 305 x 80	223 x 223	**NSYCVF165M230PF**
Fan	165	123	350 x 305 x 80	223 x 223	**NSYCVF300M230PF**
Fan	316	265	430 x 373 x 105	291 x 291	**NSYCVF560M230PF**
Fan	502	430	430 x 373 x 105	291 x 291	**NSYCVF850M230PF**

Grille

(1) Values given for a fan powered at 230 V. For other voltages, the values are similar

- Colour: RAL 7035 grey

NSYCAG125LPF

Characteristics	Flow rate (m³/h) with cover (1)		Dimensions		References
	Free	With 1 outlet grille	External (mm)	Cut-out (mm)	
Grille	74	53	240 x 180 x 60	125 x 125	**NSYCAG125LPF**
Grille	110	82	350 x 305 x 80	223 x 223	**NSYCAG223LPF**
Grille	165	123	350 x 305 x 80	223 x 223	**NSYCAG223LPF**
Grille	316	265	430 x 373 x 105	291 x 291	**NSYCAG291LPF**
Grille	502	430	430 x 373 x 105	291 x 291	**NSYCAG291LPF**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Thermal management system

Fans by components

Fans

- Free flow without filter or grille: 170 m3/h.
- Two models according to the input voltage: 230 and 115 V, 50-60 Hz.
- Ingress protection rating: IP20 according to IEC 60529.
- Options: IP20 outlet grille (ABS, black) and filter (black polyurethane foam).



NSYCVF65M115PF

Characteristics	Flow rate (m³/h)	Voltage (V)	References
Fan	65	115	**NSYCVF65M115PF**
Fan	65	230	**NSYCVF65M230PF**

Fan accessories

NSYCAF108

Characteristics	Dimensions External (mm)	References
Outlet grille	124 x 124 x 11	**NSYCAG108LP**
Filter	-	**NSYCAF108**

Ventilation kit

- Ingress protection rating: IP33 according to IEC 60529.
- Mechanical protection rating: IK10 according to IEC 62262.
- Overall flow rate: 54 m³/h.



Supply:
- one 120 x 120 x 38 mm fan, 230 V - 50/60 Hz, free flow rate 170 m³/h,
- two 120 x 120 mm metal grilles, RAL 7035 grey,
- two 115 x 98 mm anti-insect filters, stainless steel 304L wire Ø 0.32 mm braided,
- 1.07 mm meshes,
- 1 power cord,
- the fixings required for installation.

NSYCVF54M230MM2

Characteristics	Flow rate (m³/h)	Voltage (V)	References
Ventilation kit	54	230	**NSYCVF54M230MM2**

Top hood with fan and cover

- Ingress protection rating: IP54 according to IEC 60529.
- Certification: UL.
- Installation: Installation and removal from the outside.
- Electric power: 85 W.
- Noise level: 64 dB (A).

Comment:
Flow rate measured without counter-pressure

Supply:
delivered with fixings and connection terminal block.

NSYCVF570M115MF

Characteristics	Weight (kg)	Flow rate (m³/h)	Voltage (V)	References
Top hood with fan and cover	5.8	570	115	**NSYCVF570M115MF**
Top hood with fan and cover	5.8	575	230	**NSYCVF575M230MF**

Fan motor



NSYCVF156M230

NSYCVF156M115

- Turbine-type fan motor for ventilation/extraction.

Characteristics	Flow rate (m³/h)	Voltage (V/Hz)	Absorbed power (W)	Noise level (dB)	External dimensions (mm)	References
Fan motor	156	230/50-60	17/15	42	120 x 120 x 38	**NSYCVF156M230**
Fan motor	156	115/50-60	17/15	42	120 x 120 x 38	**NSYCVF156M115**
Fan motor	35	230/50-60	16/14	32	80 x 80 x 25	**NSYCVF35M230**
Fan motor	35	115/50-60	16/14	32	80 x 80 x 25	**NSYCVF35M115**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Thermal management system

Fans by components

Outlet grille

- Outlet filter kit for enclosure ventilation.
- For coupling to fans **NSYCVF156M●●●** and **NSYCVF35M●●●**.

NSYCAG114LPF

Characteristics	External dimensions (mm)	References
Outlet grille	120 x 120 x 38	**NSYCAG114LPF**
Outlet grille	80 x 80 x 25	**NSYCAG78LPF**

Rear protective grille

- Protective grille for enclosure fan motor
- For coupling to fans **NSYCVF156M●●●** and **NSYCVF35M●●●**

NSYCVA114M

NSYCVA78M

Characteristics	External dimensions (mm)	References
Rear protective grille	120 x 120 x 38	**NSYCVA114M**
Rear protective grille	80 x 80 x 25	**NSYCVA78M**

Fan connection cable

- For coupling to the connection terminal of the fan motors.

NSYCVAC100

Characteristics	References
Fan connection cable, length = 1 m	**NSYCVAC100**

Circulating for internal forced convection

Circulation fan

User protection according to DIN 31001.
Dimensions:
- Fan: 119 x 119 x 38 mm.
- Collar: Length: 140 mm; Fixing centre-to-centre distance: 130 mm.
- Installation on ball-bearing.

Comment:
(1) Free flow.

NSYCVF170M115

Characteristics	Flow rate (m^3/h) (1)	Voltage (V)	Weight. (kg)	P (W)	dB (A)	References
Circulation fan	170	115	0.82	17	41	**NSYCVF170M115**
Circulation fan	170	230	0.82	17	41	**NSYCVF170M230**

Tangential fan, 19'' 2 U

Comment:
(1) Flow rate measured without counter-pressure.

Supply:
delivered with fixings and connection terminal block.

- Air is sucked in from the front, filtered and forced vertically through the equipment.

NSYAVG2U300

Characteristics	Flow rate (m^3/h) (1)	Voltage (V)	P (W)	References
Tangential fan, 19'' 2 U	300	230 (50-60 Hz)	37	**NSYAVG2U300**

Comment:
Flow rate measured without counter-pressure.
(1) Direct current.

Supply:
Delivered without connection cord

- Increases the speed of upward air circulation, in particular between trays with cards.
- Frontal operation LED.
- It is advisable to install slides, ref. **NSYGB140** to guarantee optimal support of the fan.

NSYAVD1U480

NSYAVD1U970

Characteristics	Flow rate (m^3/h)	Voltage (V)	No.	Weight. (kg)	P (W)	I (mA)	dB (A)	Depth (mm)	References
Circulation fan, 19'' 1 U D210	486	230	3	3.3	45	300	43	208	**NSYAVD1U480**
Circulation fan, 19'' 1 U D330	972	230	6	5.5	90	600	44	330	**NSYAVD1U970**
Circulation fan, 19'' 1 U D452	1458	230	9	7.8	135	900	45	452	**NSYAVD1U1450**
Circulation fan, 19'' 1 U D210 (1)	552 (2)	48 (DC)	3	3.3	21.3	330	43	208	**NSYAVD1U550M48**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Thermal management system

Smart ventilation systems

Fan 38 m³/h

Comment: Adding the Dust Sensor will decrease the flow rate by nearly 10%.

⚠ ★ Warning: The fan **NSYCVF38M230DG** and **NSYCVF38M115DG** and **NSYCVF38M230PF** MUST NOT be connected to a power conversion module, an inverter or UPS type of power supply !

Flow curves





Fan 85 m³/h

Comment: Adding the Dust Sensor will decrease the flow rate by nearly 5%.

Flow curves





Fan 165 m³/h

Comment: Adding the Dust Sensor will decrease the flow rate by nearly 5%.

Flow curves





Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Thermal management system

Smart ventilation systems

Fan 300 m³/h

Comment: Adding the Dust Sensor will decrease the flow rate by nearly 5%.

Flow curves





Fan 560-850 m³/h

Comment: Adding the Dust Sensor will decrease the flow rate by nearly 5%.

Flow curves





Flow curves



References	A	B
NSYCVF560M230PF	225	160.5
NSYCVF560M115PF	225	160.5
NSYCVF850M230PF	280	162
NSYCVF850M115PF	280	162

12
CV

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Thermal management system

EMC IP54 fan



Dimensions of IP54 and EMC covers



Dimensions (mm)								Cover references		
A	B	C	D	E	F	G	No. of fixing points	IP55		EMC
180	240	49	49	49	157	182	4	**NSYCAP125LZF**	**NSYCAP125LXF**	**NSYCAP125LE**
305	350	61	61	61	283	280	8	**NSYCAP223LZF**	**NSYCAP223LXF**	**NSYCAP223LE**
373	430	73	73	73	351	348	8	**NSYCAP291LZF**	**NSYCAP291LXF**	**NSYCAP291LE**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Life Is On Schneider Electric

Natural airing

Metal louvre plate, rectangular



- Material: Steel
- Structured finish, epoxy polyester powder, RAL 7035 grey
- Ingress protection rating (according to IEC 60529): IP20
- Installation: On the sides of the enclosure. Fixing by screws.

Supply:
1 metal louvre and fixing elements

NSYCAG110X46M

Characteristics	A (mm)	B (mm)	C (mm)	D (mm)	E (mm)	F (mm)	G (mm)	H (mm)	R (mm)	References
Metal louvre plate, rectangular	144	62	36	110	-	-	110	46	10	**NSYCAG110X46M**
Metal louvre plate, rectangular	208	90	72	94	190	-	180	62	18	**NSYCAG180X62M**
Metal louvre plate, rectangular	244	90	72	130	226	-	216	62	18	**NSYCAG216X62M**
Metal louvre plate, rectangular	345	118	100	231	327	115.5	317	90.5	30	**NSYCAG317X91M**
Metal louvre plate, rectangular	345	148	130	231	327	115.5	317	120	30	**NSYCAG317X120M**
Metal louvre plate, rectangular	445	148	130	267	427	148.5	417	120	30	**NSYCAG417X120M**

Metal louvre plate, square



Supply:
One metal louvre

- Ingress protection rating (according to IEC 60529): IP23

NSYCAG104X95LM

Characteristics	Dimensions (mm)	A (mm)	B (mm)	C (mm)	Slot width (mm)	No. of slots	References
Metal louvre plate, square	120 x 120	95	90	104.8	90	5	**NSYCAG104X95LM**
Metal louvre plate, square	160 x 160	110	130	140	100	5	**NSYCAG130X110LM**
Metal louvre plate, square	220 x 220	190	170	200	180	5	**NSYCAG170X190LM**

Anti-insect filters for metal louvre plate, square

- Material: Stainless steel 304L Ø 0.32 mm wire mesh, of 1.07 mm, thickness 0.6 mm
- Ingress protection rating (according to IEC 60529): IP33
- Installation: Between the enclosure and the metal louvre

Supply:
One anti-insect filter

NSYCAF104X95X

Characteristics	External dimensions (mm)	Weight	References
Anti-insect filters for metal louvre plate, square	98 x 115	0.8 kg/m²	**NSYCAF104X95X**
Anti-insect filters for metal louvre plate, square	133 x 158	0.8 kg/m²	**NSYCAF130X110X**
Anti-insect filters for metal louvre plate, square	197 x 215	0.8 kg/m²	**NSYCAF170X190X**

Roof elevators



Allow the roof to be raised, providing natural airing.

- Material: Zinc-coated steel
- They are screwed onto the structure of SF enclosures at the roof fixing point

Supply:
4 elevators

NSYRE26

Characteristics	Top elevation (mm)	References
Roof elevators	26	**NSYRE26**
Roof elevators	60	**NSYRE60**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Natural airing

Hood for natural airing



Natural airing device for coupling to the top of metal floor-standing enclosures.
Solution for combining with the ventilation slots.

- Material: Steel
- Finish: Structured finish, epoxy polyester powder, RAL 7035 grey
- Ingress protection rating (according to IEC 60529): IP54
- Installation: Fixing to the top by means of caged nuts and special screws

Supply:
1 hood for natural airing and fixing elements

NSYCAC228RMF

Characteristics	Weight	References
Hood for natural airing	4.6 (kg)	**NSYCAC228RMF**
Spare filter	–	**NSYCAF228R**

Plastic ventilation louvres

Four models available according to IP rating, in vertical position.

Supply:
References by unit. Order by multiples of 2 units (2, 4, 6, etc)

NSYCAG45LP

NSYCAG35LP

NSYCAG38LP

NSYCAG33LP

NSYCAG19LP

Characteristics	Ingress protection rating	Cut-out Ø (mm)	References
Plastic ventilation louvres	IP22	45.5	**NSYCAG45LP**
Plastic ventilation louvres	IP30/44	35	**NSYCAG35LP**
Plastic ventilation louvres	IP45	38	**NSYCAG38LP**
Plastic ventilation louvres	IP44	33	**NSYCAG33LP**
	IP45	19	**NSYCAG19LP**

Sealed anti-condensation valve

Controls the pressure to avoid condensation following an internal temperature increase.

- Material: PA6-V2, acrylic co-polymer membrane, water and oil repellent
- Ingress protection rating: IP68
- Temperature of use: -40… +105°C

NSYCAG12LPH2

Characteristics	Cut-out Ø (mm)	Permeability	Pressure difference	Minor pack.	References
Sealed anti-condensation valve	M12	16 litres/h	ΔP < 1 bar	10	**NSYCAG12LPH1**
Sealed anti-condensation valve	M12	120 litres/h	ΔP < 0.1 bar	10	**NSYCAG12LPH2**

12
CA

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Thermal management system

Choose air-air exchangers to take advantage of cooler ambient temperatures, such as food and beverage plants, to evacuate large amounts of heat while helping guarantee the independence of the internal and external air circuits.

Air-air exchangers: A new range energy efficient



Higher efficiency through improved design

- With an updated external grill design, and by positioning cooling closer to critical equipment, such as speed drives, ClimaSys now provides better flow, better cooling, and higher energy efficiency

Faster installation

- A number of design improvements reduce installation time. Mounting requires single cut-outs and a minimum of screws. Wiring is accomplished with smart interconnects

Simplicity saves you time

- Our free ProClima thermal calculation software makes specification simple and fast. A new thermal solutions module integrates calculation for cooling and control devices, helping you maximize the energy efficiency of your systems.

Protection

- All side-mounted models are IP55 internally according to EN 60529.

New certifications and declarations

- CE
- EAC

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Thermal management system

Air-air exchangers, side-mounting models

Characteristics	Side-mounting models			
	• The air-air exchanger can be used in heavily polluted environments provided that the ambient temperature is at least 10°C lower than the internal temperature wanted. • Main components: Thermostat adjustment system, exchange cassette, fans for internal and external circuits of the enclosure.			
Material	Painted zinc-coated steel			
Colour	RAL 7035 grey			
Ingress protection rating (according to IEC 60529)	IP55			
Certifications and declarations	CE, EAC			
Installation	Indoor. For outdoor applications or other cover finitions, please consult us.			
Cooling characteristics				
Specific power	22 W/K	36 W/K	50 W/K	80 W/K
Air flow of the internal circuit (enclosure)	280 m³/h	570 m³/h	600 m³/h	1050 m³/h
Air flow of the external circuit (ambient)	280 m³/h	570 m³/h	600 m³/h	1050 m³/h
Thermostat type	-	Mechanical	Mechanical	Mechanical
Temperature setting range	-	+5 … +60°C	+5 … +60°C	+5 … +60°C
Temperature range external circuit (ambient)	-5 … +55°C	-5 … +55°C	-5 … +55°C	-5 … +55°C
Type of fluid	Air	Air	Air	Air
Electric characteristics				
Input voltage	1 x 230 V / 50-60 Hz	1 x 230 V / 50-60 Hz	1 x 230 V / 50-60 Hz	1 x 230 V / 50-60 Hz
Rated Intensity	0.5 A	0.7 A	0.7 A	1.1 A
Power consumption absorved	72 W	160 W	160 W	240 W
Thermal protection recommended (fuse)	T1 A	T1 A	T1 A	T2 A
Physical characteristics				
External dimensions (H x W x D)	413 x 189 x 149 mm	771 x 316 x 103 mm	771 x 316 x 103 mm	1260 x 317 x 148 mm
Protection degree IP internal /external (according to IEC 60529)	IP55 / IP22	IP55 / IP22	IP55 / IP22	IP55 / IP22
Noise level	59 dB	62 dB	62 dB	64 dB
Weight of unit	7 kg	10 kg	10 kg	17 kg
References				
	NSYCEA22E	**NSYCEA36**	**NSYCEA50**	**NSYCEA80**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Thermal management system

Choose air-water exchangers for especially difficult environments where there is no external air circuit available but a stable cold-water circuit can be supplied.

Air-water exchangers: For highly polluted environments



Many mounting options give you the right fit

- Air-water exchangers offer roof and side mounting options.

Certifications and declarations

- UL,
- CE.
- EAC

15 kW

Extended ratings to meet any challenge

- Provide options for up to 15 kW of cooling power, among the world's highest power ratings for air-water exchangers.

Protection

- All side -mounting models are IP55 type protected internally and externally according EN 60529. Top-mounting models are IP54.

New material options adapt to any application

- Air-water exchangers can be provided in the same material as electrical enclosures for (for example stainless steel) a homogeneous appearance and thermal performance.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Thermal management system

Air-water exchangers, side-mounting models

Characteristics	Side-mounting models				
	• Main components: Thermostat adjustment system, Exchange cassette, fans for internal circuits of the enclosure, protection device against possible leaks. • Eyebolts included in all models.				
Material	RAL 7035 grey painted zinc-coated steel or stainless steel				
Ingress protection rating (according to IEC 60529)	IP55				
Certifications and declarations	• CE declaration • UL (only references ending with UL) • EAC				
Installation	Indoor. For outdoor applications or other cover finitions, please consult us.				
Cooling characteristics					
Cooling power W10A35	1000 W	1750 W	2500 W	3500 W	4500 W
Hydraulic circuit maximum pressure	5 bar	5 bar	5 bar	5 bar	5 bar
Internal airflow	330 m³/h	570 m³/h	860 m³/h	1050 m³/h	1450 m³/h
Thermostat type	Mechanical	Mechanical	Mechanical	Mechanical	Mechanical
Temperature setting range	+20 … +46°C	+20 … +46°C	+20 … +46°C	+20 … +46°C	+20 … +46°C
Temperature range external circuit (ambient)	+1 … +70°C	+1 … +70°C	+1 … +70°C	+1 … +70°C	+1 … +70°C
Type of fluid	Filtered water or glicolised water	Filtered water or glicolised water	Filtered water or glicolised water	Filtered water or glicolised water	Filtered water or glicolised water
Water flow	150 l/h	150 l/h	500 l/h	500 l/h	500 l/h
Pressure drop	0.1 bar	0.1 bar	0.3 bar	0.2 bar	0.2 bar
Hydraulic connection	3/8" G	1/2" G	1/2" G	1/2" G	1/2" G
Electric characteristics					
Input voltage	1 x 230 V / 50-60 Hz*	1 x 230 V / 50-60 Hz*	1 x 230 V / 50-60 Hz*	1 x 230 V / 50-60 Hz*	1 x 230 V / 50-60 Hz*
Rated Intensity	0.17 A	0.36 A	0.33 A	0.55 A	0.71 A
Power consumption absorved W10A35	29 W	75 W	80 W	130 W	160 W
Thermal protection recommended (fuse)	T2 A	T2 A	T2 A	T2 A	T2 A
Physical characteristics					
External dimensions (H x W x D)	450 x 310 x 115 mm	901 x 398 x 137 mm	901 x 398 x 137 mm	1148 x 398 x 163 mm	1148 x 398 x 163 mm
Protection degree IP internal / external (according to IEC 60529)	IP55 / IP55	IP55 / IP55	IP55 / IP55	IP55 / IP55	IP55 / IP55
Noise level	55 dB (A)	58 dB (A)	58 dB (A)	64 dB (A)	69 dB (A)
Weight of unit	12 kg	18 kg	19 kg	29 kg	30 kg
References					
Steel	**NSYCEW1K**	**NSYCEW1K8**	**NSYCEW2K5**	**NSYCEW3K5**	**NSYCEW4K5**
Stainless steel	**NSYCEWX1K**	**NSYCEWX1K8**	**NSYCEWX2K5**	**NSYCEWX3K5**	**NSYCEWX4K5**
Steel UL	**NSYCEW1KUL**	**NSYCEW1K8UL**	**NSYCEW2K5UL**	**NSYCEW3K5UL**	**NSYCEW4K5UL**
Stainless steel UL	**NSYCEWX1KUL**	**NSYCEWX1K8UL**	**NSYCEWX2K5UL**	**NSYCEWX3K5UL**	**NSYCEWX4K5UL**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Thermal management system

Side-mounting model

Characteristics	Side-mounting models		
	• Main components: Thermostat adjustment system, Exchange cassette, fans for internal circuits of the enclosure, protection device against possible leaks. • Eyebolts included in all models.		
Material	RAL 7035 grey painted zinc-coated steel or stainless steel		
Ingress protection rating (according to IEC 60529)	IP55		
Certifications and declarations	• CE declaration • UL (only references ending with UL) • EAC		
Installation	Indoor. For outdoor applications or other cover finitions, please consult us.		
Cooling characteristics			
Cooling power W10A35	6000 W	6000 W	10000 W
Hydraulic circuit maximum pressure	5 bar	8 bar	8 bar
Internal airflow	1450 m³/h	1450 m³/h	2420 m³/h
Thermostat type	Mechanical	Mechanical	Mechanical
Temperature setting range	+20 … +46°C	+20 … +46°C	+20 … +46°C
Temperature range external circuit (ambient)	+1 … +70°C	+1 … +70°C	+1 … +70°C
Type of fluid	Filtered water or glicolised water	Filtered water or glicolised water	Filtered water or glicolised water
Water flow	800 l/h	800 l/h	2000 l/h
Pressure drop	0.5 bar	0.5 bar	3.5 bar
Hydraulic connection	1/2" G	1/2" G	3/4" G
Electric characteristics			
Input voltage	1 x 230 V / 50-60 Hz*	2 x 400-440 V / 50-60 Hz	1 x 230 V / 50-60 Hz
Rated Intensity	0.71 A	0.4 A	1.2 A
Power consumption absorved W10A35	160 W	170 W	260 W
Thermal protection recommended (fuse)	T2 A	T1 A	T2 A
Physical characteristics			
External dimensions (H x W x D)	1500 x 450 x 163 mm	1500 x 450 x 163 mm	1932 x 797 x 206 mm
Protection degree IP internal / external (according to IEC 60529)	IP55 / IP55	IP55 / IP55	IP55 / IP55
Noise level	69 dB (A)	69 dB (A)	70 dB (A)
Weight of unit	40 kg	42 kg	90 kg
References			
Steel	**NSYCEW6K**	**NSYCEW6K2P4**	**NSYCEW10K**
Stainless steel	**NSYCEWX6K**	**NSYCEWX6K2P4**	**NSYCEWX10K**
Steel UL	**NSYCEW6KUL**	-	-
Stainless steel UL	**NSYCEWX6KUL**	-	-

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Side-mounting model

Top Mounting model

			Top Mounting model
			IP54
10000 W	15000 W	15000 W	2500 W
8 bar	8 bar	8 bar	5 bar
2420 m³/h	2900 m³/h	2900 m³/h	750 m³/h
Mechanical	Mechanical	Mechanical	Mechanical
+20 … +46°C	+20 … +46°C	+20 … +46°C	+20 … +46°C
+1 … +70°C	+1 … +70°C	+1 … +70°C	+1 … +70°C
Filtered water or glicolised water	Filtered water or glicolised water	Filtered water or glicolised water	Filtered water or glicolised water
2000 l/h	2000 l/h	2000 l/h	500 l/h
3.5 bar	4.8 bar	4.8 bar	0.3 bar
3/4" G	3/4" G	3/4" G	1/2" G
2 x 400-440 V / 50-60 Hz	1 x 230 V / 50-60 Hz	2 x 400-440 V / 50-60 Hz	1 x 230 V / 50-60 Hz
0.75 A	1.4 A	0.9 A	0.30 A
280 W	320 W	420 W	65 W
T2 A	T4 A	T2 A	T2 A
1932 x 797 x 206 mm	1932 x 797 x 206 mm	1932 x 797 x 206 mm	270 x 400 x 542 mm
IP55 / IP55	IP55 / IP55	IP55 / IP55	IP54 / IP55
70 dB (A)	72 dB (A)	70 dB (A)	58 dB (A)
90 kg	92 kg	92 kg	19 kg
NSYCEW10K2P4	**NSYCEW15K**	**NSYCEW15K2P4**	**NSYCEW2K5R**
NSYCEWX10K2P4	**NSYCEWX15K**	**NSYCEWX15K2P4**	-
-	-	-	-
-	-	-	-

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Thermal management system

Accessories



Characteristics	Air-air and air-water exchangers CE		Air-air and air-water exchangers UL / CE		Retrofit panel	
	Steel	Stainless steel	Steel	Stainless steel		
					Panel that enable to mount a new ClimaSys CE units by replacement of old Schneider Electric cooling systems.	
Material					Metal painted	
Colour					RAL 7035 grey	
Supply					1 unit	
References Air- air exchangers					Retrofit panel	Old Schneider Electric cooling system
Side-mounting models	**NSYCEA36**	-	-	-	**NSYCEARTFIT36**	**NSYCEA35W230VL** **NSYCEA35W230VLE**
	NSYCEA50	-	-	-	-	-
	NSYCEA80	-	-	-	**NSYCEARTFIT80**	**NSYCEA70W230VL**
Air-water exchangers						
Side-mounting models	**NSYCEW1K**	**NSYCEWX1K**	**NSYCEW1KUL**	**NSYCEWX1KUL**	-	-
	NSYCEW1K8	**NSYCEWX1K8**	**NSYCEW1K8UL**	**NSYCEWX1K8UL**	-	-
	NSYCEW2K5	**NSYCEWX2K5**	**NSYCEW2K5UL**	**NSYCEWX2K5UL**	**NSYCEWRTFIT2K5**	**NSYCEW2100W230VL**
	NSYCEW3K5	**NSYCEWX3K5**	**NSYCEW3K5UL**	**NSYCEWX3K5UL**	**NSYCEWRTFIT3K5**	**NSYCEW3150W230VL**
	NSYCEW4K5	**NSYCEWX4K5**	**NSYCEW4K5UL**	**NSYCEWX4K5UL**	-	-
	NSYCEW6K	**NSYCEWX6K**	**NSYCEW6KUL**	**NSYCEWX6KUL**	-	-
	NSYCEW6K2P4	**NSYCEWX6K2P4**	-	-	-	-
	NSYCEW10K	**NSYCEWX10K**	-	-	-	-
	NSYCEW10K2P4	**NSYCEWX10K2P4**	-	-	-	-
	NSYCEW15K	**NSYCEWX15K**	-	-	-	-
	NSYCEW15K2P4	**NSYCEWX15K2P4**	-	-	-	-
Top-mounting model	**NSYCEW2K5R**	-	-	-	-	-

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Life Is On Schneider Electric

Thermal management system

Air-air exchangers, side-mounting models

NSYCEA22E



NSYCEA36 / NSYCEA50



NSYCEA80



Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Life Is On Schneider Electric

Thermal management system

Air-water exchangers, side-mounting models

Performance curves

P (Btu/h) w



NSYCEW●●1K●●



Performance curves

P (Btu/h) w



NSYCEW●●1K8●● – NSYCEW●●2K5●●



P (Btu/h) w



P = Cooling power
Ta= Inlet water temperature
Ti= Desired internal temperature of the enclosure

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Thermal management system

Air-water exchangers, side-mounting models

Performance curves

NSYCEW●●3K5●● – NSYCEW●●4K5●●







Performance curves

NSYCEW●●6K●●







P = Cooling power
Ta= Inlet water temperature
Ti= Desired internal temperature of the enclosure

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Thermal management system

Air-water exchangers, side-mounting models

Performance curves

P (Btu/h) w



P (Btu/h) w



NSYCEW●●3K5●● – NSYCEW●●4K5●●



Performance curves

P (Btu/h) w



NSYCEW●●6K●●



P = Cooling power
Ta= Inlet water temperature
Ti= Desired internal temperature of the enclosure

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

12
CU

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Thermal management system

Choose cooling units for harsh environments, where ambient temperatures can reach up to 55°C.
The unit's integrated alarm system will signal you in the event of any operational anomaly.

Cooling units: For a high ambient temperature

Several mounting solutions

- Three models: Roof mode, floor model, side model. There is also a SLIM model which permits a space saving and perfect integration on the doors of control panels.

15 kW

Large range of power levels

- Provide options for up to 15 kW of cooling power.

+/- 1.5°C

Precision of temperature control

- All ClimaSys cooling units are provided with a precise electronic control system by thermostat which gives them high cooling precision (+/- 1.5°C).

Enhanced protection

- An internal grid of a new design helps protect the components and personnel during operation of the equipment while at the same time facilitating cleaning and maintenance.

Broad temperature range for outdoor enclosures

- The outdoor version can withstand extreme environments, with an operating temperature range of -20°C to +55°C.

Speed of access to information

- The new screen offers fast access to the configuration parameters and information from the sensors located in the enclosure (does not apply to heavy-duty outdoor enclosures)

Certifications and declarations

- UL,
- CE.
- EAC

New materials

- Stainless steel and painted galvanized steel for the outside dedicated to clean, hygienic environments such as food and beverage production plants.

Simplicity

- No tools needed to replace the filter. It just takes a few seconds.

12
CU

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Thermal management system

Cooling units

Characteristics	Side-mounting models			
	• Respect for the environment by using environmentally friendly gas R134a (HFC). • Electronic thermostats in all models. • Alarm signal for door contact included in all models. • Eyebolts included. • The external filter, not included as standard, is strongly recommended for harsh environments. • Digital screen. • Evaporation condensation water unit integrated from 800 W to 15 kW.			
Material	RAL 7035 grey painted zinc-coated steel or stainless steel			
Certifications and declarations	• CE declaration • UL (only references ending with UL) • EAC			
Installation	Indoor			
Cooling characteristics				
Cooling power L35-L35 according to EN 14511	300 W (1024 Btu/h)	380 W (1297 Btu/h)	640 W (2184 Btu/h)	820 W (2798 Btu/h)
Cooling power L35-L50 according to EN 14511	150 W (512 Btu/h)	240 W (819 Btu/h)	470 W (1604 Btu/h)	680 W (2320 Btu/h)
Air flow of the internal circuit (enclosure)	280 m³/h	280 m³/h	330 m³/h	330 m³/h
Air flow of the external circuit (ambient)	280 m³/h	280 m³/h	570 m³/h	570 m³/h
Thermostat type	Electronic	Electronic	Electronic	Electronic
Temperature range internal circuit (enclosure)	+20 … +46°C	+20 … +46°C	+20 … +46°C	+20 … +46°C
Maximum outside temperature	+55°C	+55°C (+50°C)*	+55°C (+50°C)*	+55°C (+50°C)*
Temperature range external circuit (ambient)	+5 … +55°C*	+5 … +55°C* (+5 … +50°C)*	+5 … +55°C* (+5 … +50°C)*	+5 … +55°C* (+5 … +50°C)*
Type of cooling gas	R134a	R134a	R134a	R134a
Cooling gas weight	0.13 kg	0.16 kg	0.23 kg	0.23 kg
Maximum pressure cooling circuit	25 bar	26 bar (28 bar)**	25 bar (28 bar)**	25 bar (28 bar)**
External filter	Optional, see page 601	Optional, see page 601	Optional, see page 601	Optional, see page 601
Electric characteristics				
Input voltage	1 x 230 V / 50-60 Hz	1 x 230 V / 50-60 Hz**	1 x 230 V / 50-60 Hz**	1 x 230 V / 50-60 Hz**
Starting / Rated Intensity	4.2 A / 1.5 A	6.0 A / 1.6 A	8.1 A / 2.1 A	10.8 A / 2.6 A
Power consumption absorved L35-L35 according to EN 14511	270 W	280 W	400 W	440 W
Power consumption absorved L35-L50 according to EN 14511	310 W	330 W	470 W	490 W
Energy efficiency ratio (EER) L35-L35	1.1	1.4	1.6	1.9
Thermal protection recommended (fuse)	T4 A	T4 A	T6 A	T6 A
Physical characteristics				
External dimensions (H x W x D)	340 x 525 x 135 mm	460 x 285 x 180 mm	606 x 316 x 212 mm	783 x 348 x 215 mm
Protection degree IP internal /external according to IEC 60529	IP55 / IP34	IP55 / IP34	IP55 / IP34	IP55 / IP34
Noise level	61 dB	60 dB	65 dB	65 dB
Weight of unit	17 kg	17 kg	21 kg	27 kg
References				
Steel	**NSYCU300H**	**NSYCU400**	**NSYCU600**	**NSYCU800**
Stainless steel	-	**NSYCUX400**	**NSYCUX600**	**NSYCUX800**
Steel UL	-	**NSYCU400UL**	**NSYCU600UL**	**NSYCU800UL**
Stainless steel UL	-	-	**NSYCUX600UL**	**NSYCUX800UL**

* 50°C at 60 Hz.
** Certification UL only 60 Hz.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

	1000 W (3412 Btu/h)	1000 W (3412 Btu/h)	1250 W (4265 Btu/h)	1250 W (4265 Btu/h)	1600 W (5459 Btu/h)	1600 W (5459 Btu/h)	2000 W (6824 Btu/h)
	790 W (2696 Btu/h)	790 W (2696 Btu/h)	910 W (3105 Btu/h)	910 W (3105 Btu/h)	1230 W (4197 Btu/h)	1230 W (4197 Btu/h)	1510 W (5152 Btu/h)
	330 m³/h	330 m³/h	570 m³/h	570 m³/h	570 m³/h	570 m³/h	860 m³/h
	570 m³/h	570 m³/h	860 m³/h	860 m³/h	1050 m³/h	1050 m³/h	1050 m³/h
	Electronic	Electronic	Electronic	Electronic	Electronic	Electronic	Electronic
	+20 … +46°C	+20 … +46°C	+20 … +46°C	+20 … +46°C	+20 … +46°C	+20 … +46°C	+20 … +46°C
	+55°C (+50°C)*	+55°C (+50°C)*	+55°C (+50°C)*	+55°C	+55°C (+50°C)*	+50°C*	+55°C (+50°C)*
	+5 … +55°C* (+5 … +50°C)*	+5 … +50°C (+5 … +50°C)*	+5 … +55°C* (+5 … +50°C)*	+5 … +50°C	+5 … +55°C* (+5 … +50°C)*	+5 … +50°C	+5 … +55°C* (+5 … +50°C)*
	R134a	R134a	R134a	R134a	R134a	R134a	R134a
	0.23 kg	0.23 kg	0.38 kg	0.38 kg	0.45 kg	0.45 kg	0.54 kg
	25 bar (28 bar)**	25 bar (28 bar)**	25 bar (28 bar)**	25 bar	25 bar (28 bar)**	25 bar (28 bar)**	25 bar (28 bar)**
	Optional, see page 601	Optional, see page 601	Optional, see page 601	Optional, see page 601	Optional, see page 601	Optional, see page 601	Optional, see page 601
	1 x 230 V / 50-60 Hz**	2 x 400-440 V / 50-60 Hz 2 x 400-460 V / 50-60 Hz**	1 x 230 V / 50-60 Hz**	2 x 400-440 V / 50-60 Hz	1 x 230 V / 50-60 Hz**	2 x 400-440 V / 50-60 Hz 2 x 460 V / 60 Hz**	1 x 230 V / 50-60 Hz**
	10.5 A / 3 A	8 A / 2 A	11 A / 3.8 A	8.5 A / 2.8 A	18 A / 5.4 A	11 A / 2.9 A	24 A / 6.5 A
	570 W	590 W	650 W	650 W	850 W	840 W	1080 W
	650 W	670 W	760 W	770 W	970 W	960 W	1290 W
	1.8	1.7	1.9	1.9	1.9	1.9	1.9
	T6 A	T4 A	T6 A	T4 A	T10 A	T6 A	T10 A
	783 x 348 x 215 mm	783 x 348 x 215 (+58) mm	999 x 405 x 237 mm	999 x 405 x 237 mm	999 x 405 x 237 mm	999 x 405 x 237 mm	999 x 405 x 237 mm
	IP55 / IP34	IP55 / IP34	IP55 / IP34	IP55 / IP34	IP55 / IP34	IP55 / IP34	IP55 / IP34
	65 dB	65 dB	65 dB	65 dB	65 dB	65 dB	65 dB
	28 kg	29 kg	38 kg	40 kg	40 kg	42 kg	52 kg
	NSYCU1K	**NSYCU1K2P4**	**NSYCU1K2**	**NSYCU1K22P4**	**NSYCU1K6**	**NSYCU1K62P4**	**NSYCU2K**
	NSYCUX1K	**NSYCUX1K2P4**	**NSYCUX1K2**	**NSYCUX1K22P4**	**NSYCUX1K6**	**NSYCUX1K62P4**	**NSYCUX2K**
	NSYCU1KUL	**NSYCU1K2P4UL**	**NSYCU1K2UL**	**-**	**NSYCU1K6UL**	**NSYCU1K62P4UL**	**NSYCU2KUL**
	NSYCUX1KUL	**NSYCUX1K2P4UL**	**NSYCUX1K2UL**	**-**	**NSYCUX1K6UL**	**NSYCUX1K62P4UL**	**NSYCUX2KUL**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Thermal management system

Cooling units

Characteristics	Side-mounting models			Floor-standing models
	Alarm signal for door contact included in all models. Eyebolts included. The external filter, not included as standard, is strongly recommended for harsh environments.			
Material	RAL 7035 grey painted zinc-coated steel or stainless steel			
Certifications and declarations	CE declaration UL (only references ending with UL) EAC			
Installation	Indoor			
Cooling characteristics				
Cooling power L35-L35 according to EN 14511	2000 W (6824 Btu/h)	2900 W (9895 Btu/h)	3850 W (13137 Btu/h)	5800 W (19790 Btu/h)
Cooling power L35-L50 according to EN 14511	1510 W (5152 Btu/h)	2250 W (7677 Btu/h)	2870 W (9793 Btu/h)	4350 W (14843 Btu/h)
Air flow of the internal circuit (enclosure)	860 m³/h	1450 m³/h	1450 m³/h	1450 m³/h
Air flow of the external circuit (ambient)	1050 m³/h	1450 m³/h	1450 m³/h	2900 m³/h
Thermostat type	Electronic	Electronic	Electronic	Electronic
Temperature range internal circuit (enclosure)	+20 … +46°C (+45°C)*	+20 … +46°C (+45°C)*	+20 … +46°C (+45°C)*	+20 … +46°C
Maximum outside temperature	+50°C (+45°C)	+50°C (+45°C)	+50°C (+45°C)	+50°C
Temperature range external circuit (ambient)	+5 … +50°C (+5 … +45°C)*	+5 … +50°C (+5 … +45°C)*	+5 … +50°C (+5 … +45°C)*	+10 … +50°C
Type of cooling gas	R134a	R134a	R134a	R407c
Cooling gas weight	0.59 kg	0.84 kg	1.14 kg	1.8 kg
Maximum pressure cooling circuit	25 bar (28 bar)*	25 bar (28 bar)*	25 bar (28 bar)*	27 bar
External filter	Optional, see page 601	Optional, see page 601	Optional, see page 601	Polyurethane filter standard
Electric characteristics				
Input voltage	3 x 400 V / 50-60 Hz 3 x 460 V / 60 Hz*	3 x 400 V / 50-60 Hz 3 x 460 V / 60 Hz*	3 x 400 V / 50-60 Hz 3 x 460 V / 60 Hz*	3 x 400 V / 50 Hz
Starting / Rated Intensity	10 A / 2.5 A	14 A / 2.6 A	18 A / 3.6 A	21.7 A / 5.9 A
Power consumption absorved L35-L35 according to EN 14511	970 W	1220 W	1780 W	2340 W
Power consumption absorved L35-L50 according to EN 14511	1150 W	1440 W	2050 W	3880 W
Energy efficiency ratio (EER) L35-L35	2.1	2.4	2.2	2.5
Thermal protection recommended (fuse)	T6 A	T6 A	T8 A	T8 A
Physical characteristics				
External dimensions (H x W x D)	999 x 405 x 237 mm	1270 x 500 x 336 mm	1270 x 500 x 336 mm	2000 x 600 x 380 mm
Protection degree IP internal /external according to IEC 60529	IP55 / IP34	IP55 / IP34	IP55 / IP34	IP54 / IP34
Noise level	65 dB	70 dB	70 dB	72 dB
Weight of unit	54 kg	84 kg	85 kg	150 kg
References				
Steel	**NSYCU2K3P4**	**NSYCU3K3P4**	**NSYCU4K3P4**	**NSYCU6K3P4**
Stainless steel	**NSYCUX2K3P4**	**NSYCUX3K3P4**	**NSYCUX4K3P4**	-
Steel UL	**NSYCU2K3P4UL**	**NSYCU3K3P4UL**	**NSYCU4K3P4UL**	-
Stainless steel UL	**NSYCUX2K3P4UL**	**NSYCUX3K3P4UL**	**NSYCUX4K3P4UL**	-

* Certification UL only 60 Hz..

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

	6050 W (20643 Btu/h)	7600 W (25932 Btu/h)	7950 W (27126 Btu/h)	9400 W (32074 Btu/h)	9850 W (33610 Btu/h)	14800 W (50500 Btu/h)	15150 W (51694 Btu/h)
	4350 W (14843 Btu/h)	5700 W (19449 Btu/h)	5930 W (20234 Btu/h)	7000 W (23885 Btu/h)	7350 W (25079 Btu/h)	11300 W (38557 Btu/h)	11600 W (39581 Btu/h)
	1450 m³/h	2900 m³/h	2900 m³/h	2900 m³/h	2900 m³/h	4300 m³/h	4300 m³/h
	2900 m³/h	2900 m³/h	2900 m³/h	2900 m³/h	2900 m³/h	5800 m³/h	5800 m³/h
	Electronic	Electronic	Electronic	Electronic	Electronic	Electronic	Electronic
	+20 … +46°C	+20 … +46°C	+20 … +46°C	+20 … +46°C	+20 … +46°C	+20 … +46°C	+20 … +46°C
	+50°C	+50°C	+50°C	+50°C	+50°C	+55°C	+55°C
	+10 … +50°C	+10 … +50°C	+10 … +50°C	+10 … +45°C	+10 … +45°C	+10 … +50°C	+10 … +50°C
	R407c	R134a	R134a	R134a	R134a	R410a	R410a
	1.8 kg	2.8 kg	2.8 kg	2.3 kg	2.3 kg	3.5 kg	3.5 kg
	27 bar	27 bar	27 bar	27 bar	27 bar	39 bar	39 bar
	Polyurethane filter standard	Polyurethane filter standard	Polyurethane filter standard	Polyurethane filter standard	Polyurethane filter standard	Polyurethane filter standard	Polyurethane filter standard
	3 x 460 V / 60 Hz	3 x 400 V / 50 Hz	3 x 460 V / 60 Hz	3 x 400 V / 50 Hz	3 x 460 V / 60 Hz	3 x 400 V / 50 Hz	3 x 460 V / 60 Hz
	23.5 A / 6.8 A	43.8 A / 7.2 A	44.5 A / 7.9 A	30.7 A / 9.1 A	32.5 A / 10.3 A	49 A / 11 A	51 A / 11.8 A
	2920 W	3530 W	4210 W	3850 W	4380 W	5750 W	6580 W
	4520 W	4270 W	5340 W	5400 W	6340 W	6900 W	7760 W
	2.1	2.2	1.9	2.4	2.2	2.6	2.3
	T8 A	T10 A	T10 A	T18 A	T18 A	T20 A	T20 A
	2000 x 600 x 380 mm	2000 x 800 x 380 mm	2000 x 800 x 380 mm	2000 x 800 x 380 mm	2000 x 800 x 380 mm	2000 x 800 x 550 mm	2000 x 800 x 550 mm
	IP54 / IP34	IP54 / IP34	IP54 / IP34	IP54 / IP34	IP54 / IP34	IP54 / IP34	IP54 / IP34
	72 dB	72 dB	72 dB	77 dB	77 dB	67 dB	67 dB
	150 kg	160 kg	160 kg	180 kg	180 kg	240 kg	240 kg
	NSYCU6K3P460	**NSYCU8K3P4**	**NSYCU8K3P460**	**NSYCU10K3P4**	**NSYCU10K3P460**	**NSYCU15K3P4**	**NSYCU15K3P460**
	-	-	-	-	-	-	-
	-	-	-	-	-	-	-
	-	-	-	-	-	-	-

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Thermal management system

Cooling units

Characteristics	Roof-mounting models		
	• Respect for the environment by using environmentally friendly gas R134a (HFC). • Integrated water condensation exit system. • Alarm signal for door contact included in all models. • Eyebolts included. • The external filter, not included as standard, is strongly recommended for harsh environments.		
Material	RAL 7035 grey painted zinc-coated steel or stainless steel.		
Certifications and declarations	• CE declaration • UL (only references ending with UL) • EAC		
Installation	Indoor		
Cooling characteristics			
Cooling power L35-L35 according to EN 14511	410 W (1399 Btu/h)	820 W (2798 Btu/h)	1150 W (3924 Btu/h)
Cooling power L35-L50 according to EN 14511	240 W (819 Btu/h)	680 W (2320 Btu/h)	900 W (3071 Btu/h)
Air flow of the internal circuit (enclosure)	235 m³/h	570 m³/h	570 m³/h
Air flow of the external circuit (ambient)	330 m³/h	860 m³/h	1010 m³/h
Thermostat type	Electronic	Electronic	Electronic
Temperature range internal circuit (enclosure)	+20 … +46°C	+20 … +46°C	+20 … +46°C
Maximum outside temperature	+55°C (+50°C)*	+55°C (+50°C)*	+55°C (+50°C)*
Temperature range external circuit (ambient)	+5 … +55°C* (+5 … +50°C)*	+5 … +55°C* (+5 … +50°C)*	+5 … +55°C* (+5 … +50°C)*
Type of cooling gas	R134a	R134a	R134a
Cooling gas weight	0.17 kg	0.31 kg	0.63 kg
Maximum pressure cooling circuit	28 bar	25 bar (28 bar)**	25 bar (28 bar)**
External filter	Optional, see page 601	Optional, see page 601	Optional, see page 601
Electric characteristics			
Input voltage	1 x 230 V / 50-60 Hz**	1 x 230 V / 50-60 Hz**	1 x 230 V / 50-60 Hz**
Starting / Rated Intensity	4 A / 1.5 A	12 A / 2.9 A	11 A / 3.2 A
Power consumption absorved L35-L35 according to EN 14511	230 W	510 W	550 W
Power consumption absorved L35-L50 according to EN 14511	290 W	560 W	660 W
Energy efficiency ratio (EER) L35-L35	1.8	1.6	2.1
Thermal protection recommended (fuse)	T4 A	T6 A	T6 A
Physical characteristics			
External dimensions (H x W x D)	264 x 486 x 259 mm	340 x 600 x 340 mm	415 x 567 x 401 mm
Protection degree IP internal /external according to IEC 60529	IP54 / IP34	IP54 / IP34	IP54 / IP34
Noise level	65 dB	65 dB	65 dB
Weight of unit	18 kg	23 kg	40 kg
References			
Steel	**NSYCU400R**	**NSYCU800R**	**NSYCU1K2R**
Stainless steel	**NSYCUX400R**	**NSYCUX800R**	**NSYCUX1K2R**
Steel UL	**NSYCU400RUL**	**NSYCU800RUL**	**NSYCU1K2RUL**

* 50°C at 60 Hz.
** Certification UL only 60 Hz.
*** For cooling units greater than 65 kg we recommend to place universal cross rails NSYSUCR4060 or NSYSUCR4080.

Device for dissipating condensation water (external installation)

- Device allowing the evacuation of condensation water from the internal battery (evaporator).
- Supplied with stainless steel support.
- Power supply:

Operating voltage ±10%				
Voltage	Starting current	Thermal protection recommended	Evaporation capacity	Resistance type
230 V~	2.9 A	T 3 A	200 cl/h	PTC
115 V~	5.8 A	T 6 A	200 cl/h	PTC







Heat sink

NSYCUAD

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

	1550 W (5289 Btu/h)	2050 W (6995 Btu/h)	2050 W (6995 Btu/h)	2900 W (9895 Btu/h)	3850 W (13137 Btu/h)
	1200 W (4095 Btu/h)	1560 W (5323 Btu/h)	1560 W (5323 Btu/h)	2250 W (7677 Btu/h)	2870 W (9793 Btu/h)
	860 m³/h	1050 m³/h	1050 m³/h	860 m³/h	1450 m³/h
	1820 m³/h	1820 m³/h	1820 m³/h	3410 m³/h	3410 m³/h
	Electronic	Electronic	Electronic	Electronic	Electronic
	+20 … +46°C	+20 … +46°C	+20 … +46°C	+20 … +46°C	+20 … +46°C
	+55°C	+55°C (+50°C)**	+50°C (+45°C)**	+50°C (+45°C)**	+50°C (+45°C)**
	+5 … +55°C* (+5 … +50°C)*	+5 … +55°C*	+5 … +50°C (+5 … +45°C)**	+5 … +50°C (+5 … +45°C)**	+5 … +50°C (+5 … +45°C)**
	R134a	R134a	R134a	R134a	R134a
	0.54 kg	0.55 kg	0.55 kg	1.20 kg	1.60 kg
	25 bar (28 bar)**	25 bar	25 bar (28 bar)**	25 bar (28 bar)**	25 bar (28 bar)**
	Optional, see page 601	Optional, see page 601	Optional, see page 601	Optional, see page 601	Optional, see page 601
	1 x 230 V / 50-60 Hz**	1 x 230 V / 50-60 Hz	3 x 400 V / 50-60 Hz 3 x 460 V / 60 Hz*	3 x 400 V / 50-60 Hz 3 x 460 V / 60 Hz*	3 x 400 V / 50-60 Hz 3 x 460 V / 60 Hz*
	18 A / 4.5 A	24 A / 6 A	10 A / 1.9 A	15.7 A / 2.5 A	17 A / 3.6 A
	810 W	1150 W	990 W	1210 W	1790 W
	930 W	1250 W	1190 W	1450 W	2010 W
	1.9	1.8	2.1	2.4	2.2
	T10 A	T10 A	T6 A	T6 A	T6 A
	415 x 567 x 401 mm	415 x 567 x 401 mm	415 x 567 x 401 mm	496 x 797 x 492 mm	496 x 797 x 492 mm
	IP54 / IP34	IP54 / IP34	IP54 / IP34	IP54 / IP34	IP54 / IP34
	65 dB	65 dB	65 dB	75 dB	75 dB
	44 kg	50 kg	52 kg	83 kg***	86 kg***
	NSYCU1K5R	**NSYCU2KR**	**NSYCU2K3P4R**	**NSYCU3K3P4R**	**NSYCU4K3P4R**
	NSYCUX1K5R	**NSYCUX2KR**	**NSYCUX2K3P4R**	**NSYCUX3K3P4R**	**NSYCUX4K3P4R**
	NSYCU1K5RUL	**-**	**NSYCU2K3P4RUL**	**NSYCU3K3P4RUL**	**NSYCU4K3P4RUL**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Thermal management system

Outdoor Heavy Duty cooling units





Characteristics	Side-mounting models		
	• Respect for the environment by using environmentally friendly gas R134a (HFC). • Mechanical thermostats in all models. • Eyebolts included. • The external filter, not included as standard. The metallic filter is strongly recommended. • Metalic canopy as standard. • Anti-corrosive protection (class C3H). • Inside components, including the condenser, coated with anti-corrosive protection.		
Material	RAL 7035 grey painted zinc-coated steel		
Certifications and declarations	• CE declaration • EAC		
Installation	Indoor or outdoor		
Cooling characteristics			
Cooling power L35-L35 according to EN 14511	380 W (1297 Btu/h)	640 W (2184 Btu/h)	820 W (2798 Btu/h)
Cooling power L35-L50 according to EN 14511	240 W (819 Btu/h)	470 W (1604 Btu/h)	680 W (2320 Btu/h)
Air flow of the internal circuit (enclosure)	280 m³/h	330 m³/h	330 m³/h
Air flow of the external circuit (ambient)	280 m³/h	570 m³/h	570 m³/h
Thermostat type	Mechanic	Mechanic	Mechanic
Temperature range internal circuit (enclosure)	+20 … +50°C	+20 … +50°C	+20 … +50°C
Maximum outside temperature	+55°C	+55°C	+55°C
Temperature range external circuit (ambient)	-20 … +55°C	-20 … +55°C	-20 … +55°C
Type of cooling gas	R134a	R134a	R134a
Cooling gas weight	0.16 kg	0.26 kg	0.28 kg
Maximum pressure cooling circuit	26 bar	25 bar	25 bar
External filter	Optional, see metalic filter on page 601	Optional, see metalic filter on page 601	Optional, see metalic filter on page 601
Electric characteristics			
Input voltage	1 x 230 V / 50-60 Hz	1 x 230 V / 50-60 Hz	1 x 230 V / 50-60 Hz
Starting / Rated Intensity	6.0 A / 1.6 A	8.1 A / 2.1 A	10.8 A / 2.6 A
Power consumption absorved L35-L35 according to EN 14511	280 W	400 W	440 W
Power consumption absorved L35-L50 according to EN 14511	330 W	470 W	490 W
Energy efficiency ratio (EER) L35-L35	1.4	1.6	1.9
Thermal protection recommended (fuse)	T4 A	T6 A	T6 A
Physical characteristics			
External dimensions (H x W x D)	573 x 300 x 205 mm	718 x 331 x 235 mm	875 x 363 x 239 mm
Protection degree IP internal /external according to IEC 60529	IP55 / IP34	IP55 / IP34	IP55 / IP34
Noise level	60 dB	65 dB	65 dB
Weight of unit	17 kg	21 kg	27 kg
References			
	NSYCUHD400	**NSYCUHD600**	**NSYCUHD800**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.



1000 W (3412 Btu/h)	1000 W (3412 Btu/h)	1600 W (5459 Btu/h)	1600 W (5459 Btu/h)	2000 W (6824 Btu/h)	2900 W (9895 Btu/h)	3850 W (13137 Btu/h)
790 W (2696 Btu/h)	790 W (2696 Btu/h)	1230 W (4197 Btu/h)	1230 W (4197 Btu/h)	1510 W (5152 Btu/h)	2250 W (7677 Btu/h)	2870 W (9793 Btu/h)
330 m³/h	330 m³/h	570 m³/h	570 m³/h	860 m³/h	1450 m³/h	1450 m³/h
570 m³/h	570 m³/h	1050 m³/h	1050 m³/h	1050 m³/h	1450 m³/h	1450 m³/h
Mechanic	Mechanic	Mechanic	Mechanic	Mechanic	Mechanic	Mechanic
+20 … +50°C	+20 … +50°C	+20 … +50°C	+20 … +50°C	+20 … +50°C	+20 … +50°C	+20 … +50°C
+55°C	+55°C	+55°C	+55°C	+55°C	+55°C	+55°C
-20 … +55°C	-20 … +50°C	-20 … +55°C	-20 … +50°C	-20 … +55°C	-20 … +50°C	-20 … +50°C
R134a	R134a	R134a	R134a	R134a	R134a	R134a
0.27 kg	0.27 kg	0.46 kg	0.46 kg	0.65 kg	0.84 kg	1.14 kg
25 bar	25 bar	25 bar	25 bar	25 bar	25 bar	25 bar
Optional, see metalic filter on page 601	Optional, see metalic filter on page 601	Optional, see metalic filter on page 601	Optional, see metalic filter on page 601	Optional, see metalic filter on page 601	Optional, see metalic filter on page 601	Optional, see metalic filter on page 601
1 x 230 V / 50-60 Hz	2 x 400-440 V / 50-60 Hz	1 x 230 V / 50-60 Hz	2 x 400-440 V / 50-60 Hz	3 x 400 V / 50-60 Hz	3 x 400 V / 50-60 Hz	3 x 400 V / 50-60 Hz
10.5 A / 3 A	8 A / 2 A	18 A / 5.3 A	11 A / 2.9 A	10 A / 2.5 A	14 A / 2.6 A	18 A / 3.6 A
570 W	590 W	820 W	840 W	970 W	1220 W	1780 W
650 W	670 W	940 W	960 W	1150 W	1440 W	2050 W
1.8	1.7	2.0	1.9	2.1	2.4	2.2
T6 A	T4 A	T10 A	T6 A	T6 A	T6 A	T8 A
895 x 363 x 239 mm	895 x 363 x 239 (+58) mm	1009 x 415 x 261 mm	1009 x 415 x 261 mm	1009 x 415 x 261 mm	1416 x 512 x 365 mm	1416 x 512 x 365 mm
IP55 / IP34	IP55 / IP34	IP55 / IP34	IP55 / IP34	IP55 / IP34	IP55 / IP34	IP55 / IP34
65 dB	65 dB	65 dB	65 dB	65 dB	70 dB	70 dB
28 kg	29 kg	40 kg	42 kg	54 kg	84 kg	85 kg
NSYCUHD1K	**NSYCUHD1K2P4**	**NSYCUHD1K6**	**NSYCUHD1K62P4**	**NSYCUHD2K3P4**	**NSYCUHD3K3P4**	**NSYCUHD4K3P4**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Thermal management system

Slim cooling units

Characteristics	Side-mounting models			
	• Respect for the environment by using environmentally friendly gas R134a (HFC). • Electronical thermostat included. • 3 mounting positions (surface, half-flush and flush). • Alarm Signal for contact door. • Eyebolts included.			
Material	RAL 7035 grey painted zinc-coated steel or stainless steel			
Certifications and declarations	• CE declaration • UL • EAC			
Installation	• Indoor • There is one unique cut-out for all mounting positions and all slim models			
Cooling characteristics				
Cooling power L35-L35 according to EN 14511	1100 W (3753 Btu/h)	1100 W (3753 Btu/h)	1500 W (5118 Btu/h)	1500 W (5118 Btu/h)
Cooling power L35-L50 according to EN 14511	860 W (2934 Btu/h)	860 W (2934 Btu/h)	1150 W (3924 Btu/h)	1150 W (3924 Btu/h)
Air flow of the internal circuit (enclosure)	860 m³/h	860 m³/h	860 m³/h	860 m³/h
Air flow of the external circuit (ambient)	860 m³/h	860 m³/h	860 m³/h	860 m³/h
Thermostat type	Electronic	Electronic	Electronic	Electronic
Temperature range internal circuit (enclosure)	+20 … +46°C	+20 … +46°C	+20 … +46°C	+20 … +46°C
Maximum outside temperature	+50°C	+50°C	+50°C	+50°C
Temperature range external circuit (ambient)	+5 … +50°C	+5 … +50°C	+5 … +50°C	+5 … +50°C
Type of cooling gas	R134a	R134a	R134a	R134a
Cooling gas weight	0.5 kg	0.5 kg	0.46 kg	0.46 kg
Maximum pressure cooling circuit	28 bar	28 bar	28 bar	28 bar
External circuit filter	Optional, see page 601	Optional, see page 601	Optional, see page 601	Optional, see page 601
Electric characteristics				
Input voltage	1 x 230 V / 50-60 Hz*	2 x 400-460 V / 50-60 Hz*	1 x 230 V / 50-60 Hz*	2 x 400-460 V / 50-60 Hz*
Starting / Rated Intensity	11 A / 4.8 A	8.5 A / 2.7 A	18 A / 5.7 A	11 A / 3.2 A
Power consumption absorved L35-L35 according to EN 14511	660 W	660 W	840 W	840 W
Power consumption absorved L35-L50 according to EN 14511	790 W	790 W	970 W	970 W
Energy efficiency ratio (EER) L35-L35	1.7	1.7	1.8	1.8
Thermal protection recommended (fuse)	T6 A	T4 A	T10 A	T6 A
Physical characteristics				
External dimensions (H x W x D)	1696 x 495 x 195 mm	1696 x 495 x 195 mm	1696 x 495 x 195 mm	1696 x 495 x 195 mm
Protection degree IP internal /external according to IEC 60529	IP55 / IP34	IP55 / IP34	IP55 / IP34	IP55 / IP34
Noise level	64 dB	64 dB	66 dB	66 dB
Weight of unit	50 kg	52 kg	55 kg	57 kg
References				
Steel UL	**NSYCUS1K1UL**	**NSYCUS1K12P4UL**	**NSYCUS1K5UL**	**NSYCUS1K52P4UL**
Stainless steel UL	**NSYCUSX1K1UL**	**NSYCUSX1K12P4UL**	**NSYCUSX1K5UL**	**NSYCUSX1K52P4UL**

* Certification UL only 60 Hz.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

	2000 W (6824 Btu/h)	2000 W (6824 Btu/h)	2500 W (8530 Btu/h)	2500 W (8530 Btu/h)	3200 W (10919 Btu/h)	3200 W (10919 Btu/h)
	1550 W (5289 Btu/h)	1550 W (5289 Btu/h)	1850 W (6312 Btu/h)	1850 W (6312 Btu/h)	2500 W (8530 Btu/h)	2500 W (8530 Btu/h)
	860 m³/h	860 m³/h	1450 m³/h	1450 m³/h	1450 m³/h	1450 m³/h
	1050 m³/h	1050 m³/h	1450 m³/h	1450 m³/h	1450 m³/h	1450 m³/h
	Electronic	Electronic	Electronic	Electronic	Electronic	Electronic
	+20 … +46°C	+20 … +46°C	+20 … +46°C	+20 … +46°C	+20 … +46°C	+20 … +46°C
	+50°C	+50°C	+50°C	+50°C	+50°C	+50°C
	+5 … +50°C	+5 … +50°C	+5 … +50°C	+5 … +50°C	+5 … +50°C	+5 … +50°C
	R134a	R134a	R134a	R134a	R134a	R134a
	0.51 kg	0.59 kg	1.2 kg	1.2 kg	0.85 kg	1.25 kg
	28 bar	28 bar	28 bar	28 bar	28 bar	28 bar
	Optional, see page 601	Optional, see page 601	Optional, see page 601	Optional, see page 601	Optional, see page 601	Optional, see page 601
	1 x 230 V / 60 Hz	3 x 400 V / 50-60 Hz (3 x 460 V / 60 Hz)*	1 x 230 V / 60 Hz	3 x 400 V / 50-60 Hz (3 x 460 V / 60 Hz)*	1 x 230 V / 60 Hz	3 x 400 V / 50-60 Hz (3 x 460 V / 60 Hz)*
	24 A / 6.5 A	10 A / 2.1 A	35 A / 10.5 A	14 A / 2.9 A	37 A / 10.5 A	18 A / 3.1 A
	1020 W	1060 W	1340 W	1270 W	1720 W	1650 W
	1160 W	1270 W	1580 W	1510 W	2000 W	1980 W
	2.0	1.9	1.9	2.0	1.9	1.9
	T10 A	T6 A	T16 A	T6 A	T16 A	T6 A
	1696 x 495 x 195 mm	1696 x 495 x 195 mm	1696 x 495 x 235 mm	1696 x 495 x 235 mm	1696 x 495 x 235 mm	1696 x 495 x 235 mm
	IP55 / IP34	IP55 / IP34	IP55 / IP34	IP55 / IP34	IP55 / IP34	IP55 / IP34
	67 dB	67 dB	69 dB	69 dB	69 dB	69 dB
	63 kg	65 kg	80 kg	82 kg	81 kg	83 kg
	NSYCUS2KUL	**NSYCUS2K3P4UL**	**NSYCUS2K5UL**	**NSYCUS2K53P4UL**	**NSYCUS3K2UL**	**NSYCUS3K23P4UL**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Thermal management system

Accessories

Characteristics	Cooling units IEC			Cooling units UL	
	Steel	Stainless steel	Outdoor	Steel	Stainless steel
Material					
Colour					
Installation					
Supply					
References Cooling units					
Side-mounting models	NSYCU300H	-	-	-	-
	NSYCU400	NSYCUX400	NSYCUHD400	NSYCU400UL	-
	NSYCU600	NSYCUX600	NSYCUHD600	NSYCU600UL	NSYCUX600UL
	NSYCU800	NSYCUX800	NSYCUHD800	NSYCU800UL	NSYCUX800UL
	NSYCU1K	NSYCUX1K	NSYCUHD1K	NSYCU1KUL	NSYCUX1KUL
	NSYCU1K2P4	NSYCUX1K2P4	NSYCUHD1K2P4	NSYCU1K2P4UL	NSYCUX1K2P4UL
	NSYCU1K2	NSYCUX1K2	-	NSYCU1K2UL	NSYCUX1K2UL
	NSYCU1K22P4	NSYCUX1K22P4	-	-	-
	NSYCU1K6	NSYCUX1K6	NSYCUHD1K6	NSYCU1K6UL	NSYCUX1K6UL
	NSYCU1K62P4	NSYCUX1K62P4	NSYCUHD1K62P4	NSYCU1K62P4UL	NSYCUX1K62P4UL
	NSYCU2K	NSYCUX2K	-	NSYCU2KUL	NSYCUX2KUL
	NSYCU2K3P4	NSYCUX2K3P4	NSYCUHD2K3P4	NSYCU2K3P4UL	NSYCUX2K3P4UL
	NSYCU3K3P4	NSYCUX3K3P4	NSYCUHD3K3P4	NSYCU3K3P4UL	NSYCUX3K3P4UL
	NSYCU4K3P4	NSYCUX4K3P4	NSYCUHD4K3P4	NSYCU4K3P4UL	NSYCUX4K3P4UL
Floor-standing models	NSYCU6K3P4	-	-	-	-
	NSYCU6K3P460	-	-	-	-
	NSYCU8K3P4	-	-	-	-
	NSYCU8K3P460	-	-	-	-
	NSYCU10K3P4	-	-	-	-
	NSYCU10K3P460	-	-	-	-
	NSYCU15K3P4	-	-	-	-
	NSYCU15K3P460	-	-	-	-
Roof-mounting model	NSYCU400R	NSYCUX400R	-	NSYCU400RUL	-
	NSYCU800R	NSYCUX800R	-	NSYCU800RUL	-
	NSYCU1K2R	NSYCUX1K2R	-	NSYCU1K2RUL	-
	NSYCU1K5R	NSYCUX1K5R	-	NSYCU1K5RUL	-
	NSYCU2K3P4R	NSYCUX2K3P4R	-	NSYCU2K3P4RUL	-
	NSYCU2KR	NSYCUX2KR	-	-	-
	NSYCU3K3P4R	NSYCUX3K3P4R	-	NSYCU3K3P4RUL	-
	NSYCU4K3P4R	NSYCUX4K3P4R	-	NSYCU4K3P4RUL	-
Slim model	-	-	-	NSYCUS1K1UL	NSYCUSX1K1UL
	-	-	-	NSYCUS1K12P4UL	NSYCUSX1K12P4UL
	-	-	-	NSYCUS1K5UL	NSYCUSX1K5UL
	-	-	-	NSYCUS1K52P4UL	NSYCUSX1K52P4UL
	-	-	-	NSYCUS2KUL	NSYCUSX2KUL
	-	-	-	NSYCUS2K3P4UL	NSYCUSX2K3P4UL
	-	-	-	NSYCUS2K5UL	NSYCUSX2K5UL
	-	-	-	NSYCUS2K53P4UL	NSYCUSX2K53P4UL
	-	-	-	NSYCUS3K2UL	NSYCUSX3K2UL
	-	-	-	NSYCUS3K23P4UL	NSYCUSX3K23P4UL

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

	Filters		**Canopy for ClimaSys CU**	**Internal deflector**	**Retrofit panel**	
	Plastic filter not recommended for outdoor models.	Metalic filter recommended for outdoor models.	This canopy is highly recommended for harsh indoor environments to protect from ingress of dust.	Deflects the air inside the enclosure.	Panel that enable to mount a new ClimaSys CU units by replacement of old Schneider Electric cooling systems.	
	Polyurethane	Micro-stretched aluminium	Painted zinc coated	Zinc coated	Metal painted	
	Black	-	RAL 7035 grey	RAL 7035 grey	RAL 7035 grey	
	Indoor	Indoor or outdoor	Indoor	Indoor or outdoor	Indoor	
	5 units	1 unit	1 unit	1 unit with fixing elements	1 unit	
						Old Schneider Electric cooling system
	-	-	-	-	-	-
	NSYCUF400	**NSYCUFX400**	**NSYCUCN400HD**	**NSYCUD400**	**NSYCURFT400**	**NSYCU240W230VL** **NSYCU370W230VL**
	NSYCUF600	**NSYCUFX600**	**NSYCUCN600HD**	**NSYCUD600**	-	-
	NSYCUF800T1K	**NSYCUFX800T1K**	**NSYCUCN800T1KHD**	**NSYCUD800T1K**	**NSYCURFT800T1K**	**NSYCU760W230VL**
	NSYCUF800T1K	**NSYCUFX800T1K**	**NSYCUCN800T1KHD**	**NSYCUD800T1K**	**NSYCURFT800T1K**	**NSYCUE1100W230L**
	NSYCUF800T1K	**NSYCUFX800T1K**	**NSYCUCN800T1KHD**	**NSYCUD1K2T2K**	**NSYCURFT800T1K**	**NSYCU1K**
	NSYCUF1KT2K	**NSYCUFX1K2T2K**	**NSYCUCN1K2T2KHD**	**NSYCUD1K2T2K**	-	-
	NSYCUF1KT2K	**NSYCUFX1K2T2K**	**NSYCUCN1K2T2KHD**	**NSYCUD1K2T2K**	-	-
	NSYCUF1KT2K	**NSYCUFX1K2T2K**	**NSYCUCN1K2T2KHD**	**NSYCUD1K2T2K**	**NSYCURFT1K6T2K**	**NSYCUE1400W230L** **NSYCU1650W230VL**
	NSYCUF1KT2K	**NSYCUFX1K2T2K**	**NSYCUCN1K2T2KHD**	**NSYCUD1K2T2K**	**NSYCURFT1K6T2K**	**NSYCUE1400W400L**
	NSYCUF1KT2K	**NSYCUFX1K2T2K**	**NSYCUCN1K2T2KHD**	**NSYCUD1K2T2K**	-	-
	NSYCUF1KT2K	**NSYCUFX1K2T2K**	**NSYCUCN1K2T2KHD**	**NSYCUD1K2T2K**	**NSYCURFT1K6T2K**	**NSYCU1800W400VL** **NSYCUE1800W400L**
	NSYCUF3KT4K	**NSYCUFX3KT4K**	**NSYCUCN3KT4KHD**	**NSYCUD3KT4K**	**NSYCURFT3KT4K**	**NSYCU2500W400VL**
	NSYCUF3KT4K	**NSYCUFX3KT4K**	**NSYCUCN3KT4KHD**	**NSYCUD3KT4K**	**NSYCURFT3KT4K**	**NSYCU4000W400VL**
	NSYCUF6K	**NSYCUFX6K**	-	-	-	-
	NSYCUF6K	**NSYCUFX6K**	-	-	-	-
	NSYCUF8KT10K	**NSYCUFX8KT10K**	-	-	-	-
	NSYCUF8KT10K	**NSYCUFX8KT10K**	-	-	-	-
	NSYCUF8KT10K	**NSYCUFX8KT10K**	-	-	-	-
	NSYCUF8KT10K	**NSYCUFX8KT10K**	-	-	-	-
	NSYCUF15K	**NSYCUFX15K**	-	-	-	-
	NSYCUF15K	**NSYCUFX15K**	-	-	-	-
	NSYCUF400R	**NSYCUFX400R**	-	-	-	-
	NSYCUF800R	**NSYCUFX800R**	-	-	**NSYCURFT800R**	**NSYCU760W230VR**
	NSYCUF1K2T2KR	**NSYCUFX1K2T2KR**	-	-	**NSYCURFT1K2T2K**	**NSYCU1050W230VR**
	NSYCUF1K2T2KR	**NSYCUFX1K2T2KR**	-	-	**NSYCURFT1K2T2K**	**NSYCUE1400W230R** **NSYCU1460W230VR** **NSYCU1650W230VR**
	NSYCUF1K2T2KR	**NSYCUFX1K2T2KR**	-	-	**NSYCURFT1K2T2K**	**NSYCUE1800W400R** **NSYCU2000W400VR**
	NSYCUF1K2T2KR	**NSYCUFX1K2T2KR**	-	-	-	-
	NSYCUF3KT4KR	**NSYCUFX3KT4KR**	-	-	**NSYCURFT3K**	**NSYCU2450W400VR** **NSYCU3100W400VR**
	NSYCUF3KT4KR	**NSYCUFX3KT4KR**	-	-	-	-
	NSYCUF1K1T2KS	**NSYCUFX1K1T2KS**	-	**NSYCUD1K1T1K5**	-	**NSYCUB1100W230S**
	NSYCUF1K1T2KS	**NSYCUFX1K1T2KS**	-	**NSYCUD1K1T1K5**	-	**NSYCUB1100W400S**
	NSYCUF1K1T2KS	**NSYCUFX1K1T2KS**	-	**NSYCUD1K1T1K5**	-	**NSYCUB1500W230S**
	NSYCUF1K1T2KS	**NSYCUFX1K1T2KS**	-	**NSYCUD1K1T1K5**	-	**NSYCUB1500W400S**
	NSYCUF1K1T2KS	**NSYCUFX1K1T2KS**	-	**NSYCUD1K1T1K5**	-	**NSYCUB2200W230S**
	NSYCUF1K1T2KS	**NSYCUFX1K1T2KS**	-	**NSYCUD1K1T1K5**	-	**NSYCUB2200W400S**
	NSYCUF1K1T2KS	**NSYCUFX1K1T2KS**	-	**NSYCUD1K1T1K5**	-	**NSYCUB2700W230S**
	NSYCUF1K1T2KS	**NSYCUFX1K1T2KS**	-	**NSYCUD1K1T1K5**	-	**NSYCUB2700W400S**
	NSYCUF1K1T2KS	**NSYCUFX1K1T2KS**	-	**NSYCUD1K1T1K5**	-	**NSYCUB2700W230S**
	NSYCUF1K1T2KS	**NSYCUFX1K1T2KS**	-	**NSYCUD1K1T1K5**	-	**NSYCUB2700W400S**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Thermal management system

Side-mounting models: Dimensions and cut-outs



NSYCU300H



NSYCU●●400●●



NSYCU●●600●●



NSYCU●●800●● - NSYCU●●1K●●

Units of measurement are mm

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Thermal management system

Side-mounting models: Dimensions and cut-outs



NSYCU●●1K2●● - NSYCU●●1K6●● - NSYCU●●2K●●



NSYCU●●3K3P4●● - NSYCU●●4K3P4●●

Units of measurement are mm

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Thermal management system

Top-mounting models: Dimensions and cut-outs



NSYCU●●400R●●



NSYCU●●800R●●



NSYCU●●1K2R●● - NSYCU●●1K5R●● - NSYCU●●2K●●R●●



NSYCU●●3K3P4R●● - NSYCU●●4K3P4R●●

Units of measurement are mm

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Life Is On Schneider Electric

Thermal management system

Top-mounting models: Dimensions and cut-outs



NSYCUS●1K1● - NSYCUS●1K5● - NSYCUS●2K●



NSYCUS2K5UL

Units of measurement are mm

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Thermal management system

Ultra thin resistance heaters have been designed to resolve condensation problems in the most complex installations.
Is your enclosure short of space?
Does your mounting plate make it impossible to install a conventional heater?
Do you not want to take out the equipment?
Discover the benefits of this new offer and its numerous mounting solutions.





Small size (thickness = 1.6 mm)

- The space saving available for the equipment compared with a conventional resistor can be up to 30%.



Numerous positions for installation

- These heaters are so slim and flexible they can be installed in a variety of positions:
- Vertically on side panels
- On the mounting plate.

Heat and safety

- The heat is distributed over the whole surface and does not exceed 70°C. This temperature allows devices next to the heater to be handled safely.

Energy efficiency

- Ultra thin resistance heaters are ohmic: They therefore have a low starting current.

Multiple options for fixing

- Innovative quick fixing system using Velcro pads (no need for a tool!) or with basic fixing accessories (screw + spacer). These systems make it easy to move the heater if necessary.

No interference emissions

- These resistors can be installed near electronic equipment to help guarantee optimum heat.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Life Is On Schneider Electric

Thermal management system

Other characteristics Electrical circuit diagram

					
5 mounting solutions:	On a Telequick mounting plate	On plain or micro-perforated mounting plate with fixing hardware	On DIN rail	On plain mounting plate with selfadhesive Velcro pads	On wall with self-adhesive Velcro pads
	A Telequick mounting plate, ref. **NSYMR●●●●** B Telequick nuts, ref. **AF1EA●**, supplied with the mounting kit	A Mounting plate, ref. **NSYMM●●●●** B Fixing hardware included in the mounting kit	A Mounting plate, ref. **NSYMM●●●●** B Symmetrical DIN rail, ref. **NSYSDR●●●●** C Clip-on nuts, ref. **AF1CG●**, supplied with the mounting kit	A Mounting plate, ref. **NSYMM●●●●** B Self-adhesive Velcro pad and plastic fixings supplied with the mounting kit	A Self-adhesive Velcro pads and plastic fixings supplied in the mounting kit

Characteristics	PB502046	PB502047	PB502048	PB502049	PB502522
	Flexible, ultra thin resistance heaters to be installed inside the enclosure				
Material	Silicon reinforced with fibreglass				
Colour	Red (heaters), black (wires)				
Certifications	VDE, LR				
Supply	• 6 self-adhesive Velcro pads • 6 plastic fixings • 4 Telequick nuts • 4 clip-on nuts • Fixing hardware				

Ultra thin resistance heaters

Flexible, ultra thin resistance heaters to be installed inside the enclosure
- Material: Silicon reinforced with fibreglass
- Colour: Red (heaters), black (wires)
- Certifications: VDE, LR

Comment:
Ultra thin resistance heaters can be manufactured with different dimensions and power ratings than those indicated above. Please contact us.

NSYCRS10W120V

Characteristics	Power (W)	Voltage (V)	Inrush current (A)	Height (mm)	Width (mm)	Depth (mm)	References
Ultra thin resistance heaters	10	120	0.08	110	140	1.6	**NSYCRS10W120V**
Ultra thin resistance heaters	10	240	0.04	110	140	1.6	**NSYCRS10W240V**
Ultra thin resistance heaters	25	120	0.21	110	230	1.6	**NSYCRS25W120V**
Ultra thin resistance heaters	25	240	0.10	110	230	1.6	**NSYCRS25W240V**
Ultra thin resistance heaters	50	120	0.42	200	320	1.6	**NSYCRS50W120V**
Ultra thin resistance heaters	50	240	0.21	200	320	1.6	**NSYCRS50W240V**
Ultra thin resistance heaters	100	120	0.83	260	440	1.6	**NSYCRS100W120V**
Ultra thin resistance heaters	100	240	0.42	260	440	1.6	**NSYCRS100W240V**
Ultra thin resistance heaters	200	120	1.67	380	650	1.6	**NSYCRS200W120V**
Ultra thin resistance heaters	200	240	0.83	380	650	1.6	**NSYCRS200W240V**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Thermal management system

The resistance heaters help prevent the formation of condensation and help guarantee the ideal temperature for the correct operation of the electronic components in the enclosure.

Insulated PTC heaters



Large range of power levels

- 2 versions: By natural convection and with fan.
- AC or DC power supply.
- 7 power levels, from 10 W to 550 W.

Easy installation and connection

- Reduced dimensions.
- Quick electric connection by terminal board.
- No maintenance required.
- Direct clipping onto a 35 mm DIN rail.

Innovating design

Safety

- The protection helps prevent direct contact with the aluminium radiator.
- Electric protection device with terminal block cover.
- Equipped with a PTC-type heater.
- Surface temperature lower than 70°C.

Models with fan

- The heaters equipped with a fan help ensure circulation of the air and a uniform temperature inside the enclosure.
- High-flow, silent fan.

High thermal efficiency

- The configuration of the aluminium profile produces a "chimney" effect: high natural convection.
- Low power consumption thanks to self-control of the PTC-type heater.

Certifications

- CE marking.
- Range compliant with UL and VDE.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Thermal management system

Aluminium PTC heaters



Models with fan

- Models of 250 to 400 W with fan.

Connection cables

- The 10 and 20 W heaters are equipped with a 2 x 0.75 x 300 mm power cord.

Quick fixing

- The resistance heaters are fixed by means of fixing clips to a 35 mm DIN rail.

Connection terminal boards

- Heaters with a power of more than 20 W are equipped with a connection terminal board.

Large range of power levels

- 8 power levels, from 10 W to 400 W.

Resistance heaters equipped with a PTC-type sensor

The resistance heaters for electrical and electronic enclosures are equipped with PTC-type heating devices (Positive Temperature Coefficient). Thanks to these heaters:

- The surface temperature stabilises at 75°C when the ambient temperature is -5°C.
- Power consumption is reduced.

Improved convection

- The design of the profile of the resistance heaters produces a "chimney" effect, leading to increased natural convection and maintaining an even temperature inside the enclosure.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Thermal management system

Insulated PTC resistance heaters

- Compact resistance heater helping prevent the formation of condensation or frost.
- Designed to help ensure good natural convection and high thermal efficiency.
- Material: Extruded aluminium body
- Conditions of use: The heaters must be installed with a thermal controller (see selection table on page 612 and 613) to control the temperature or the humidity inside the enclosure
- The enclosure must be sealed to help prevent the entry of air from the outside
- An electrical protection device must be installed on the supply side of the unit
- Operating position: Vertical
- Operating temperature: -40…+70°C; -10…+158°F
- Surface temperature: <70°C, except for the top protection grille
- Ingress protection rating: IP20
- Certifications: VDE and UL, Cover: UL 94 V-0 plastic, Class II (double insulated)
- Mounting: By clip on a 35 mm DIN rail

NSYCR10WU2C

NSYCR50WU2C



Characteristics	Heating power at 0°C (W)	Voltage (V)	Electric connection	References
Insulated PTC resistance heater	10	12-24 DC	2 poles, 2.5 mm²	**NSYCR10WU2C**
Insulated PTC resistance heater	10	110-250 AC	2 poles, 2.5 mm²	**NSYCR10WU1C**
Insulated PTC resistance heater	20	12-24 DC	2 poles, 2.5 mm²	**NSYCR20WU2C**
Insulated PTC resistance heater	20	110-250 AC	2 poles, 2.5 mm²	**NSYCR20WU1C**
Insulated PTC resistance heater	55	12-24 DC	4 poles, 2.5 mm²	**NSYCR50WU1C**
Insulated PTC resistance heater	55	110-250 AC	4 poles, 2.5 mm²	**NSYCR50WU2C**
Insulated PTC resistance heater	55	270-420 AC	4 poles, 2.5 mm²	**NSYCR50WU1C**
Insulated PTC resistance heater	100	12-24 DC	4 poles, 2.5 mm²	**NSYCR50WU3C**
Insulated PTC resistance heater	100	110-250 AC	4 poles, 2.5 mm²	**NSYCR100WU2C**
Insulated PTC resistance heater	100	270-420 AC	4 poles, 2.5 mm²	**NSYCR100WU1C**
Insulated PTC resistance heater	147	12-24 DC	4 poles, 2.5 mm²	**NSYCR100WU3C**
Insulated PTC resistance heater	147	110-250 AC	4 poles, 2.5 mm²	**NSYCR150WU2C**

Insulated ventilated PTC heaters

- Compact resistance heater helping prevent the formation of condensation or frost.
- Designed to help ensure good natural convection and high thermal efficiency.
- Material: Extruded aluminium body
- Conditions of use: The heaters must be installed with a thermal controller (see selection table on page 612 and 613) to control the temperature or the humidity inside the enclosure
- The enclosure must be sealed to help prevent the entry of air from the outside
- An electrical protection device must be installed on the supply side of the unit
- Operating position: Vertical
- Operating temperature: -40…+70°C; -10…+158°F
- Surface temperature: Max. 50°C in the enclosure, 100°C on the top protection grille, (for an ambient temperature of 20°C / 68°F)
- Ingress protection rating: IP20
- Certifications: VDE and UL, Cover: UL 94 V-0 plastic, Class II (double insulated)
- Mounting: By clip on a 35 mm DIN rail

NSYCR170W230VVC



Characteristics	Heating power at 0°C (W)	Voltage (V)	Electric connection	References
Insulated ventilated PTC heater	177	230 AC / 50-60 HZ	2 poles, 2.5 mm²	**NSYCR170W230VVC**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Thermal management system

Aluminium PTC heaters

- Extruded aluminium body.
- Surface temperature limited to 75°C when the ambient temperature is -5°C.
- Heaters equipped with a power cable with a length of 500 mm with silicon insulation, or with a connection terminal block.

Conditions of use:

- The heaters must be installed with a thermal controller to control the temperature or the humidity inside the enclosure
- The enclosure must be sealed to help prevent the entry of air from the outside
- An electrical protection device must be installed on the supply side of the unit

NSYCR10WU1

NSYCR250W115VV

Characteristics	Power (W)	Voltage (V)	References
Aluminium PTC heater	10	12-24 DC	**NSYCR10WU1**
Aluminium PTC heater	10	110-250 AC	**NSYCR10WU2**
Aluminium PTC heater	20	12-24 DC	**NSYCR20WU1**
Aluminium PTC heater	20	110-250 AC	**NSYCR20WU2**
Aluminium PTC heater	20	270-420 AC	**NSYCR20WU3**
Aluminium PTC heater	55	12-24 DC	**NSYCR55WU1**
Aluminium PTC heater	55	110-250 AC	**NSYCR55WU2**
Aluminium PTC heater	55	270-420 AC	**NSYCR55WU3**
Aluminium PTC heater	90	12-24 DC	**NSYCR100WU1**
Aluminium PTC heater	90	110-250 AC	**NSYCR100WU2**
Aluminium PTC heater	90	270-420 AC	**NSYCR100WU3**
Aluminium PTC heater	150	12-24 DC	**NSYCR150WU1**
Aluminium PTC heater	150	110-250 AC	**NSYCR150WU2**
Aluminium PTC heater	150	270-420 AC	**NSYCR150WU3**
Aluminium PTC heater with fan	250	115 AC	**NSYCR250W115VV**
Aluminium PTC heater with fan	250	230 AC	**NSYCR250W230VV**
Aluminium PTC heater with fan	400	115 AC	**NSYCR400W115VV**
Aluminium PTC heater with fan	400	230 AC	**NSYCR400W230VV**
Resistive heater	200	115 AC	**NSYCRS200W115V**
Resistive heater	200	230 AC	**NSYCRS200W230V**

Thermofan

NSYCRP1W120VTVC

Combination of a resistance heater and an axial motor to help ensure uniform heating of the enclosure.

- Fixing by clip on a DIN rail.
- Thermostat adjustable from 0...+60°C.
- Visual operation indicator.



Characteristics	Power (W)	Voltage (V)	References
Thermofan	350/550	120 AC	**NSYCRP1W120VTVC**
Thermofan	350/550	230 AC	**NSYCRP1W230VTVC**

Fixing accessories

NSYCRAF

NSYCRAFD

Characteristics	Supply	References
Fixing accessories	Set of 5 studs	**NSYCRAF**
Fixing accessories	Set of 5 studs and DIN rail	**NSYCRAFD**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Thermal management system

Mechanical thermostats

	 Thermostat with NC contact	 Thermostat with NO contact	Thermostat with NO/NC contact	Double Thermostat
Characteristics	**NSYCCOTHC (NSYCCOTHCF)**	**NSYCCOTHO (NSYCCOTHOF)**	**NSYCCOTHI (NSYCCOTHIF)**	**NSYCCOTHD (NSYCCOTHDF)**
	Thermostat with NC Contact: • to control the stopping of a resistance heater when the temperature exceeds the displayed value. **Thermostat with NO Contact:** • to control the starting up of a fan when the temperature exceeds the displayed maximum value, • to control the temperature inside the enclosure by only starting up the fan when necessary, thus increasing the service life of the fan and reducing the clogging of the filter.			
Colour button	Red	Blue	Black	Red and blue
Ingress protection rating	IP20	IP20	IP20	IP20
Sensor element	Bimetal	Bimetal	Bimetal	Bimetal
Contact	NC, forced rupture	NC, forced rupture	Inverse,forced rupture	NO / NC, forced rupture
Contact resistance	< 10 mΩ	< 10 mΩ	< 10 mΩ	< 10 mΩ
Service life	> 100,000 cycles	> 100,000 cycles	> 100,000 cycles	> 100,000 cycles
Switching capacity	• 250 V AC; 10 A (resistive load) • 120 V AC; 15 A (resistive load) • 250 V AC/120 V AC 2 A (inductive load cos ϕ = 0.6) • 30 W DC	• 250 V AC; 10 A (resistive load) • 120 V AC; 15 A (resistive load) • 250 V AC/120 V AC 2 A (inductive load cos ϕ = 0.6) • 30 W DC	• 250 V AC; 10 A (resistive load)	• 250 V AC; 10 A (resistive load) • 120 V AC; 15 A (resistive load) • 250 V AC/120 V AC 2 A (inductive load cos ϕ = 0.6) • 30 W DC
Max interrupting capacity with direct current	NC	NO	250 V AC 4 A (inductive load cos ϕ = 0.6) 30 W DC	NA
Connection	Two 2.5 mm² terminals	Two 2.5 mm² terminals	Four 2.5 mm² terminals	Six 2.5 mm² terminals
Mounting	By clip on 35 mm DIN rail	By clip on 35 mm DIN rail	By clip on 35 mm DIN rail	By clip on 35 mm DIN rail
Enclosure	UL 94 V-0 plastic, light grey	UL 94 V-0 plastic, light grey	UL 94 V-0 plastic, light grey	UL 94 V-0 plastic, light grey
Dimensions	60 x 33 x 43 mm	60 x 33 x 43 mm	67 x 50 x 44 mm	60 x 33 x 43 mm
Weight	40 g	40 g	100 g	40 g
Mounting position	Indifferent	Indifferent	Indifferent	Indifferent
Operating temperature	-20...+80°C (-4...+176°F)	-20...+80°C (-4...+176°F)	-20...+80°C (-4...+176°F)	-20...+80°C (-4...+176°F)
Hysteresis	7°K	7°K	7°K	7°K
Temperature setting range	0...+60°C	0...+60°C	+5...+60°C	0...+60°C
Display	°C (°F)	°C (°F)	°C (°F)	°C (°F)
Max. command intensity	10 A 250 V	10 A 250 V	(NO) 5 A (NC) 10 A	(NO) 5 A (NC) 10 A

Thermal control

Mechanical and electronic thermostats

- Large range of temperature control.
- Small dimensions.
- Easily accessible terminals.

Operational temperature range

- For mechanical thermostats: 0°C ... +60°C
- For electronic thermostats: -40°C ... +80°C

LED screen

- Screen visible even in the dark.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Electronic thermostats with LED screen

	Electronic thermostat With LED screen	Electronic hygrotherm With LED screen	Electronic hygrostat With LED screen
Characteristics	**NSYCCOTH30VID NSYCCOTH120VID NSYCCOTH230VID**	**NSYCCOHYT30VID NSYCCOHYT120VID NSYCCOHYT230VID**	**NSYCCOHY30VID NSYCCOHY120VID NSYCCOHY230VID**
	Electronic temperature controller	Electronic temperature and humidity controller	Electronic humidity controller
Ingress protection rating	IP20	IP20	IP20
Certification	UL / UR	UL / UR	UL / UR
Internal sensor element	Temperature sensor	Temperature sensor and humidity sensor	Humidity sensor
Contact	Free with zero potential	Free with zero potential	Free with zero potential
Connection	2 x 2.5 mm² (input voltage) + 2 relays (2 x 2.5 mm² + 2 x 2.5 mm²)	2 x 2.5 mm² (input voltage) + 2 relays (2 x 2.5 mm² + 2 x 2.5 mm²)	2 x 2.5 mm² (input voltage) + 1 relay (2 x 2.5 mm²)
Mounting	4 different methods: By DIN rail, Spacial SF profile, on VDI cross rail or on mounting plate		
Enclosure	UL 94 V-0 plastic, light grey	UL 94 V-0 plastic, light grey	UL 94 V-0 plastic, light grey
Operating temperature	-40°C…+70°C	-40°C…+70°C	-40°C…+70°C
Hysteresis	Programmed 2°K	Programmed 2 K and 3 %	3 %
Temperature setting range	-40°C…+80°C	-40°C…+80°C	-40°C…+80°C
Humidity setting range	-	20 %…80 %	20 %…80 %
Display	°C or °F	°C or °F or % RH	% RH
Max. command intensity	8 (5) A 230 V AC / 5 A 30 V DC	8 (5) A 230 V AC / 5 A 30 V DC	8 (5) A 230 V AC / 5 A 30 V DC

The new quick fixing systems



- On 35 mm DIN rail.



- On Spacial upright.



- On cross rail.



- On mounting plate.

Certifications and declarations

- UL
- CE

12
CC

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Thermal management system

Mechanical thermostats

- Ingress protection rating according to IEC 60529: IP20
- Sensor element: Bimetal
- Contact resistance: < 10 mΩ
- Service life: > 100,000 cycles
- Mounting: By clip on 35 mm DIN rail
- Enclosure: UL 94 V-0 plastic, light grey
- Mounting position: Indifferent
- Operating temperature: -20...+80°C (-4...+176°F)
- Hysteresis: 7 K

Thermostat with NC contact

NSYCCOTHC

- Colour button: Red
- Contact: NC, forced rupture
- Switching capacity: 250 V AC; 10 A (resistive load)
  120 V AC; 15 A (resistive load)
  250 V AC/120 V AC 2 A (inductive load cos = 0.6)
  30 W DC
- Max interrupting capacity with direct current: NC
- Connection: Two 2.5 mm² terminals
- Weight: 40 g
- Temperature setting range: 0...+60°C



Characteristics	Display	Max. command intensity	Dimensions (H x W x D)	References
Thermostat with NC contact	°C	10 A 250 V	60 x 33 x 43 mm	**NSYCCOTHC**
Thermostat with NC contact	°F	10 A 250 V	60 x 33 x 43 mm	**NSYCCOTHCF**

Thermostat with NO contact

NSYCCOTHO

- Colour button: Blue
- Contact: NO, forced rupture
- Switching capacity: 250 V AC; 10 A (resistive load)
  120 V AC; 15 A (resistive load)
  250 V AC/120 V AC 2 A (inductive load cos = 0.6)
  30 W DC
- Max interrupting capacity with direct current: NO
- Connection: Two 2.5 mm² terminals
- Weight: 40 g
- Temperature setting range: 0...+60°C



Characteristics	Display	Max. command intensity	Dimensions (H x W x D)	References
Thermostat with NO contact	°C	10 A 250 V	60 x 33 x 43 mm	**NSYCCOTHO**
Thermostat with NO contact	°F	10 A 250 V	60 x 33 x 43 mm	**NSYCCOTHOF**

Thermostat with NO/NC contact

NSYCCOTHI

Colour button: Black
Contact: Inverse,forced rupture
Switching capacity: 250 V AC; 10 A (resistive load)
Max interrupting capacity with direct current: 250 V AC 4 A
(inductive load cos = 0.6) 30 W DC
Connection: Four 2.5 mm² terminals
Weight: 100 g
Temperature setting range: +5...+60°C



Characteristics	Display	Max. command intensity	Dimensions (H x W x D)	References
Thermostat with NO/NC contact	°C	(NO) 5 A (NC) 10 A	67 x 50 x 44 mm	**NSYCCOTHI**
Thermostat with NO/NC contact	°F	(NO) 5 A (NC) 10 A	67 x 50 x 44 mm	**NSYCCOTHIF**

Double Thermostat

NSYCCOTHD

- Colour button: Red and blue
- Contact: NO / NC, forced rupture
- Switching capacity: 250 V AC; 10 A (resistive load)
  120 V AC; 15 A (resistive load)
  250 V AC/120 V AC 2 A (inductive load cos = 0.6)
  30 W DC
- Max interrupting capacity with direct current: NA
- Connection: Six 2.5 mm² terminals
- Weight: 40 g
- Temperature setting range: 0...+60°C



Characteristics	Display	Max. command intensity	Dimensions (H x W x D)	References
Double Thermostat	°C	(NO) 5 A (NC) 10 A	60 x 33 x 43 mm	**NSYCCOTHD**
Double Thermostat	°F	(NO) 5 A (NC) 10 A	60 x 33 x 43 mm	**NSYCCOTHDF**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Thermal management system

Electronic thermostats

- Ingress protection rating according to IEC 60529: IP20
- Certification: UL / UR
- Contact resistance: Free with zero potential
- Mounting: 4 different methods: By DIN rail, Spacial SF profile, on VDI cross rail or on mounting platel
- Enclosure: UL 94 V-0 plastic, light grey
- Operating temperature: -40°C…+70°C
- Hysteresis: 7 K
- Max. command intensity: Motor: 4 / 13.1 A, FLA / LRA, 250 Vac Resistive load: 4 A, 250 Vdc

Electronic thermostats, with LED screen

NSYCCOTH30VID



- Internal sensor element: Temperature sensor
- Connection: 2 x 2.5 mm² (input voltage) + 2 relays (2 x 2.5 mm² + 2 x 2.5 mm²)
- Hysteresis: Programmed 2 K
- Temperature setting range: -40°C…+80°C

Characteristics	Display	Voltage (type of current)	References
Electronic thermostats, with LED screen	°C or °F	9-30 V (AC/DC)	**NSYCCOTH30VID**
Electronic thermostats, with LED screen	°C or °F	90-140 V (AC)	**NSYCCOTH120VID**
Electronic thermostats, with LED screen	°C or °F	200-240 V (AC)	**NSYCCOTH230VID**

Electronic hygrotherm

NSYCCOHYT30VID



- Internal sensor element: Temperature sensor and humidity sensor
- Connection: 2 x 2.5 mm² (input voltage) + 2 relays (2 x 2.5 mm² + 2 x 2.5 mm²)
- Hysteresis: Programmed 2 K and 3 %
- Temperature setting range: -40°C…+80°C
- Humidity setting range: 20 %…80 %

Characteristics	Display	Voltage (type of current)	References
Electronic hygrotherm	°C or °F or % RH	9-30 V (AC/DC)	**NSYCCOHYT30VID**
Electronic hygrotherm	°C or °F or % RH	90-140 V (AC)	**NSYCCOHYT120VID**
Electronic hygrotherm	°C or °F or % RH	200-240 V (AC)	**NSYCCOHYT230VID**

Electronic hygrostat

NSYCCOHY30VID



- Internal sensor element: Humidity sensor
- Connection: 2 x 2.5 mm² (input voltage) + 1 relay (2 x 2.5 mm²)
- Hysteresis: 3 %
- Humidity setting range: 20 %…80 %

Characteristics	Display	Voltage (type of current)	References
Electronic hygrostat	% RH	9-30 V (AC/DC)	**NSYCCOHY30VID**
Electronic hygrostat	% RH	90-140 V (AC)	**NSYCCOHY120VID**
Electronic hygrostat	% RH	200-240 V (AC)	**NSYCCOHY230VID**

External temperature sensor (double insulation)

Sensor operation or reading range: -40°C…+150°C. Thermostat installation tips: The thermostat should be installed at the top of the enclosure (the hottest place). See the various operating modes of each thermostat to choose the one that best meets your needs. Hygrostat installation tips: The hygrostat should be installed at the bottom of the enclosure. 60% RH is the optimum value in the enclosure.

- Ingress protection rating: IP67
- Fixing: On DIN rail, on Spacial SF profile, on VDI cross rail, on mounting plate

NSYCCASTE

Characteristics	Length of cable supplied	References
External temperature sensor	3 m	**NSYCCASTE**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Thermal management system

Thermal conditions: A hot topic for enclosures

Temperature, humidity, and dew point all affect the performance of your electrical and electronic enclosures. Problem is, unless these environments are sized properly, thermal conditions will compromise reliability, safety, and efficiency, as well as the lifetime of your panels.
The precise knowledge of the thermal conditions is therefore indispensable to choose the most appropriate thermal management solution.

Threats to performance arise when:

Real environmental conditions are not known

Specifications are oversized

Excessive loads over-consume energy



How to use ClimaSys DT

Installation type	Need What do you want to do?		
Greenfield		New Project	Determine enclosure sizing needs and the correct thermal solution
Brownfield		Power Dissipation verification	Measure the dissipation power of the installation in watts (enclosure without thermal solution installed)
Brownfield		Electronics Health Test	Verify that there are no hot/ cold spots
Brownfield		Thermal Solution Test	Measure the efficiency of the existing thermal solution in a certain period of time
Brownfield		Humidity/ Condensation Test	Measure the risk of high humidity or condensation inside the enclosure

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Life Is On Schneider Electric

ClimaSys DT: The solution to optimize the size of your enclosure

With ClimaSys DT dataloggers and EffiClima software, you can know with maximum accuracy the temperature evolution, humidity levels, and dew point inside and outside your control panels. This data can then be analyzed with ProClima thermal software to determine the optimal thermal solution for each of your control panel installations.

ClimaSys dataloggers

Measure and track thermal data.

EffiClima software

Translates data into a report on temperature, humidity, and dew point

ProClima software



Proposes the right thermal management solution based on the data variables.

Selection of the dataloggers			
Variables to measure	**How many dataloggers needed?**	**Model**	**Recommended installation**
• T outside • HR outside	1	DTH reference NSYDTEF32TRH	
• T outside • T inside	2	DTT reference NSYDTEF32T or DT mini reference NSYDTEFSMT	
• T inside	1	DTT reference NSYDTEF32T or DT mini reference NSYDTEFSMT	
• T outside • T inside	2	DTT reference NSYDTEF32T or DT mini reference NSYDTEFSMT	 Check Ventilation Check Cooling
• T inside • T outside • HR inside/ outside	2	DTH reference NSYDTEF32TRH	

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Thermal management system

ClimaSys DT (Diagnostic Tools) dataloggers are an easy-to-use solution that enables users to:

- Access accurate and reliable thermal measurement data in design, commissioning, and exploitation phases
- Track fast or slow measurements
- Maintain continuity of service
- Optimize installations
- Detect hot and cold spots, and avoid condensation problems
- Determine if ventilation/cooling is possible.

ClimaSys DTT

- ClimaSys DT model records the temperature.

Advantages

ClimaSys DTT

- Time stamp/start/stop with magnet key
- Low power consumption for extended two-year battery life
- Easy data download to PC via USB connection
- USB firmware update
- QR code on dataloggers for easy online access to data sheets, videos, and other technical information

Download EffiClima and ProClima free software

Discover more

ClimaSys DT video of the concept

e-brochure



Get maximum control panel performance and reliability Thermal management solutions for critical electrical and electronic enclosures **UE16MK06EN**

12
DT

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Thermal management system

Dataloggers

- Colour: Translucid
- Display Type: LCD display
- Operating temperature: -40°C…80°C
- Standard: EN 12830
- Declaration: CE
- Fixing mode: Clip-on support
- Connector type: USB
- Data recording: 32 K
- Temperature Setting (Accuracy): -40°C…80°C (±0.3°C)
- Battery Type (Lifespam): Lithium CR2032 3 V (Maximum 2 years)
- Composition: 1

Temperature recorder, DT

- Ingress protection rating according to IEC 60529: IP67

NSYDTEF32T

Characteristics	Temperature Resolution	Dimensions (H x W x D)	References
Temperature recorder	0.03°C	111 x 32 x 26	**NSYDTEF32T**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Thermal management system

Method to determine a thermal management solution

Here is a simple method to help you choose a thermal solution.
This method does not take into account the humidity level outside the enclosure.

Thermal balance

1 - Characteristics of the enclosure

Position of the enclosure according to IEC 890 ratio		Formula for calculating S (m²)	Example Spacial reference NSYSF20840
	Accessible from every side	S = 1.8 x H x (W + D) + 1.4 x W x D	Height = 2000 Width = 800 Depth = 400 Installation method: Suitable enclosure placed against a wall. **S = 4.128 m²**
	Placed against a wall	S = 1.4 x W x (H + D) + 1.8 x D x H	
	On the end when suited	S = 1.4 x D x (H + W) + 1.8 x W x H	
	On the end when suited, placed against a wall	S = 1.4 x H x (W + D) + 1.4 x W x D	
	In the middle when suited	S = 1.8 x W x H + 1.4 x W x D + D x H	
	In the middle when suited, placed against a wall	S = 1.4 x W x (H + D) + D x H	
	In the middle when suited, placed against a wall with the top covered	S = 1.4 x W x H + 0.7 x W x D + D x H	
		S = m²	

2 - Thermal power dissipated by the operational components

Calculated as the sum of the power dissipated by each of the installed components. If these are not known, use the ProClima software.		Assume that the switchgear dissipates 800 W.
	Pd = W	**Pd = 800 W**

3 - Temperatures outside the enclosure

		The temperature conditions are as follows:
Maximum ambient temperature.	**Te_{max} = °C**	**Te_{max} = 35°C**
Minimum ambient temperature.	**Te_{min} = °C**	**Te_{min} = 15°C**

4 - Average desired internal temperatures

They are defined by the nature of the components and the characteristics of the environment air		
Maximum internal temperature	**Tid_{max} = °C**	**Tid_{max} = 40°C**
Minimum internal temperature (maximum value between the dew point temperature and the minimum operating temperature of the devices)	**Tid_{min} = °C**	**Tid_{min} = 29°C**

5 - Temperature inside the enclosure without thermal management system

Max. internal temperature: $Tfi_{max} = \frac{Pd}{K \times S} Te_{max}$	**Tfi_{max} = °C**	**Tfi_{max} = 70°C**
Min. internal temperature: $Tfi_{min} = \frac{Pd}{K \times S} Te_{min}$	**Tfi_{min} = °C**	**Tfi_{min} = 50°C**
or K = 5.5 W/m²/°C for an enclosure made of painted sheet steel K = 3.5 W/m²/°C for a polyester enclosure K = 3.7 W/m²/°C for a stainless steel enclosure		

Calculation of thermal management power (Psyst)

a. Cooling systems:
Psyst = Pd - K x S (Tid_{max} - Te_{max}) = 686 w

b. Resistances:
Electrical installation operating constantly
Psyst = K x S (Tid_{min} - Te_{min}) - Pd

Electrical installation operating discontinuously
Psyst = K x S (Tid_{min} - Te_{min})

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Thermal management system

Method to determine a thermal management solution

Choice of solution

1 - Cooling Condition: Calculated temperature + 5°C > Temperature wanted.

Conditions Cooling	Solution	Advantages	Constraints
Temperature wanted in the enclosure at least 5°C higher than the ambient temperature **Tid_{max} ≥ Temin + 5 °C**	Oversize the enclosure.	Economical. No maintenance. Easy to implement. IP of the installation maintained.	Relatively small savings. Larger overall dimensions.
	Natural airing (installation of ventilation air inlets).	Very economical. No maintenance. Easy, fast installation.	Quantity of heat removed small and dependent on the layout of the components. Deterioration of the IP (ingress of dust).
	Forced ventilation.	Economical. Easy to implement. Large quantity of heat removed. Temperature control possible.	Regular maintenance of filters IP slightly degraded. Ambient temperature ≤ 35°C.
	Air-air exchanger.	Easy to implement. Easy to maintain. IP of the installation maintained. Regulated temperature.	Regular filter maintenance.
Temperature Tid_{max} wanted in the enclosure 5°C less than the ambient temperature Te_{max}. **Tid_{max} - 5 °C≥ Te_{max}**	Cooling unit.	Easy to implement. Large quantity of heat removed irrespective of the ambient temperature. IP of the installation maintained. Regulated temperature.	Regular filter maintenance Ambient temperature ≤ 55°C. Installation of a system for removal of condensation water from the evaporator.
	Air-water exchanger.	Easy to implement. Large quantity of heat removed irrespective of the ambient temperature. IP of the installation maintained. Regulated temperature.No filter to be maintained.	Need for a water circuit. Consumption if supplied with town water.

$$\text{Flow rate } (m^3/h) = Ø = \frac{Psyst}{(Tid_{max} - Te_{max})} \times 3.1\ (m^3/h)$$

$$\text{Flow rate } (W/K) = Ø = \frac{Psyst}{(Tid_{max} - Te_{max})\ (W/K)}$$

2 - Heating

If the calculated temperature is less than the temperature wanted, the inside of the enclosure must be heated. The solution is to use heating resistors.
They can maintain the temperature above the dew point and thus help prevent any risk of condensation.
To maintain a uniform temperature inside the enclosure and thus help prevent hot spots, Schneider Electric proposes a heating resistor equipped with a fan.

3 - Homogenize

Objective: Help prevent hot spots.
Solution: Stirring fan.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Technical guides and spare parts

Introduction

Enclosures and thermal management systems certifications	624
International enclosure standard	625
Selection of enclosures	627
Degrees of protection provided by enclosures	628
Classification of electrical equipment enclosures according to NEMA and UL	629
Polyester base coating properties	631
Properties of the plastic materials	633
Description of the marking label affixed to ATEX certified wall-mounting enclosures	635
Spare parts - Selection table	636
Spare parts ClimaSys	648

Enclosures and thermal management systems certifications Technical annexes

Range	Assemblies alone					Equipped assemblie system
	Empty assemblies for low-voltage switchgear	Standards for industrial equipment and UL classification	Marine environment classification or approval for protection and resistance to vibrations	Enclosures installed in a potentially explosive atmosphere	Outdoor Heavy Duty enclosures	Low-voltage switchgear and controlgear assemblies
	Standard/Directive					
	IEC 62208	**UL508A and CAN CSA C22-2 no. 14**	**Rules of certifying bodies**	**European directive no. 2014/34/UE EN60079-0 / EN60079-7 EN60079-3 / EN60529**	**IEC 61439-5 ISO 12944-6 IEC 61969-3**	**IEC61439-1&2**
Spacial						
SBM	●	●	● ●			
S3D	● ● (6)	●	● ● ●			
CRN	● (6)	●	●			
CRNG	● (6)	●	●			
S3DEX		●		●		
S3HF		●				
S3HD	● (6)	●			●	
S3CM		●				
SM	● ● (6)	●	●			
SF	● ● (6)	●	● ●			●
SFHD	● ● (6)	●			●	●
SFP/PH	● (6)					●
SFM						●
S3X	●	●	●			
SMX	●	●	● (3)			
SFX	● (3)	●	● (3)			
Thalassa						
TBS/TBP	●	● (1)				
PLS	●	●				
PLM	● ● (6)	●	●			
PLA	● ● (6)	●	●			
PLAT	● ● (6)					
PLAZ	● ● (6)					
PLAZT	● ● (6)					
PLD						
PHD	● (6)				● (2)	
ClimaSys (4)						
CV		●				
CU		●				
CE		●				
CR		● (5)				
CC		●				

(1) Only TBP.
(2) ISO 12944-6 only applies to the Spacial enclosures.
(3) Only for 1 door versions
(4) EAC compliant
(5) The insulated and aluminium resistance heaters of 12-24 V DC and 270-420 V AC are not certified
(6) Certificate by DEKRA
For other certifications and declarations of conformity, please consult us.

Official certification body

Bureau Veritas	LCIE (Bureau Veritas)	Bureau Veritas Marine Division	TUV Rheinland Group	Underwriters Laboratories	Laboratorio Oficial J.M. Madariaga	DNV-GL	Lloyd´s Register	Dekra	Asefa
●	●	●	●	●	●	●	●	●	●

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

International enclosure standards

The main 10 functions of standard IEC 61439

For each of the following 10 functions, the standard IEC 61439 requires design verifications from the system manufacturer - mainly through type-tests defined in IEC 62208 - and routine verifications on each panel from the Panel Builder to achieve 3 basic goals: Safety, continuity of service and compliance with end-user requirements.

Safety

Voltage stresses withstand capability

- To withstand long term voltages, and transient and temporary overvoltages according to the insulation coordination principles and requirements.

Current-carrying capability

To help protect against burns and to withstand temperature rise:

- when any circuit is continuously loaded, alone, to the specified current
- when the assembly is loaded to the specified current according to the specified load pattern (between circuits and/or as a function of the time).

Short-circuit withstand capability

- To withstand the stresses resulting from the prospective short-circuit current and from the associated data (High forces between conductors, temp. rise in a very short time, air ionization, overpressure).

Protection against electric shock

- Hazardous-live-parts not to be accessible (basic protection).
- Accessible conductive parts not to become hazardous-live (fault protection).

Protection against risk of fire or explosion

- Resistance to internal glowing elements.

Comment: Protection of persons, and optional protection of the assembly, against arcing due to internal fault can be specified through a "special test" according to IEC 61641.

Continuity of service

Maintenance and modification capability

Capability to preserve continuity of supply without impairing safety during assembly maintenance or modification.

- Electrical condition of the assembly or various circuits.
- Speed of exchange of the functional units.
- Test facilities…

Electro-Magnetic compatibility

To properly function (immunity) and not to generate EM disturbances (emission) in specified environmental conditions:

- Industrial networks or locations (Environment A).
- Domestic, commercial, and light industrial locations (Environment B).

Compliance with end-user requirements

Capability to operate the electrical installation

To properly function, according to:

- the electrical diagram of the overall system and related information (voltages, coordination…),
- the specified operating facilities (e.g. free or restricted access to Man Machine Interfaces, isolation of the outgoing circuits…).

Capability to be installed on site

- To withstand handling, transport, storage… and installation constraints.
- Capability to be erected and connected (type of enclosure, type, material and cross sectional areas of external conductors).

Protection of the assembly against mechanical and atmospheric environmental conditions

- Presence of water or solid foreign bodies (IP according to IEC 60529).
- External mechanical impacts (optional IK according to IEC 62262).
- Indoor or outdoor installation (humidity, UV).

Both the point of arrival of energy and a device for distribution to the site applications, the LV switchboard is the intelligence of the system, central to the electrical installation.

It plays an essential role in the availability of electric power, while meeting the needs of personal and property safety. Its definition, design and installation are based on precise rules; There is no place for improvisation. The IEC 61439 standard aims to better define "low-voltage switchgear and controlgear assemblies", helping ensure that the specified performances are reached. It specifies in particular:

- the responsibilities of each player, distinguishing those of the original equipment manufacturer; the organization that performed the original design and associated verification of an assembly in accordance with the standard, and of the assembly manufacturer - the organization taking responsibility for the finished assembly
- the design and verification rules, constituting a benchmark for product certification All the component parts of the electrical switchboard are concerned by the IEC 61439 standard. Equipment produced in accordance with the requirements of this switchboard standard helps ensure the safety and reliability of the installation.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

International enclosure standards

Comment:
European standard EN 62208 is identical to IEC 62208. European countries publish this standard according to the body in each country (for example BS EN 62208 in the UK).

Empty enclosures for low-voltage switchgear and controlgear assemblies. General rules.

Application
For empty enclosures before adding the user's switchgear, in the condition as supplied by the manufacturer.

Field of application
Demands for testing the enclosures to be used as part of the switchgear assemblies for voltages of less than 1000 V alternating current and 1500 V direct current in accordance with IEC 61439.

Information supplied by the manufacturer
- Commercial trademark of the manufacturer: Schneider Electric.
- Mechanical characteristics, materials, conditions for use.
- Conditions for use: Ambient air temperature for outdoor installations: -25 to +40°C.
- Atmospheric conditions for outdoor installations: The humidity can temporarily reach 100% at a temperature of 25°C.
- Transport and storage conditions: From -25 to +55°C; For limited periods not exceeding 24 h: Up to +70°C.



Standard tests of standard IEC 62208

- Static loads: Test 1.25 x maximum admissible load during 1 hour.
- Lifting: Applicable to enclosures with lifting accessories.
- Axial loads of metal inserts: 500 N for 10 seconds for M8 inserts.
- IK code: Test according to standard IEC 62262 with pendulum impact tester. After testing, the enclosure keeps its IP rating.
- IP rating: Test according to standard IEC 60529. Degree of protection against access to dangerous parts and the penetration of solid bodies and against the penetration of water.
- Thermal stability at a temperature of 70 °C: 7 days.
- Resistance to heat: Ball test at 70 °C.
  Information required for enclosures made from insulating material.
- Resistance to abnormal heat and to fire: Glow wire test according to IEC 60695-2-10 and IEC 60695-2-11.
  Information required for enclosures made from insulating material.
- Dielectric strength: 5000 V
  Information required for enclosures made from insulating material.
- Protection circuit continuity for metal enclosures: Resistance not to exceed 0.1 ohm.
- Weather resistance: Duration 500 h (cycle: Rain 5 minutes + UV lamp 25 minutes).

Corrosion resistance:
For indoor enclosures:
- 6 cycles of 24 hours of the damp heat test at 40 °C and relative humidity of 95%.
- 2 cycles of 24 hours of the salt mist test at 35 °C.

For outdoor enclosures:
2 identical 12 day periods. Each one with:
- 5 cycles of 24 hours of the damp heat test at 40 °C and relative humidity of 95%.
- 7 cycles of 24 hours of the salt mist test at 35 °C.

Our empty enclosures are marked CE according to the Low-Voltage Directive (LVD). It is the responsibility of the final equipment manufacturer to respect regulations in force.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Selection of enclosures

Selection according to the IP protection degrees

The degrees of protection, explained on the next page, is an important element when selecting the enclosures.
The following table shows the protection degrees of the enclosures.

Name	Range	IP43	IP44	IP54	IP55	IP65	IP66
Metal industrial boxes	Spacial SBM						●
Metal derivation boxes	Spacial SDB				●		
Steel wall-mounting enclosures	Spacial S3D				● (1)		●
Steel modular distribution wall-mounting enclosures	Spacial S3DM						●
Terminal wall-mounting enclosures	Spacial S3DB						●
Steel wall-mounting enclosures	Spacial S3HF				●		
Steel wall-mounting enclosures	Spacial CRN						●
Steel wall-mounting enclosures	Spacial CRNG				● (1)		●
EMC steel floor-standing enclosures	Spacial SFHF				●		
HMI control enclosures	Spacial S3CM			●			
ATEX steel wall-mounting enclosures	Spacial S3DEX						●
Steel outdoor wall-mounting enclosures	Spacial S3HD						●
Stainless steel wall-mounting enclosures	Spacial S3X				● (1)		●
Seismic and nuclear enclosures	Spacial S3D6G / Spacial S3D6GK3					●	
Terminal enclosures with FL21 cut-out	Spacial S3DBFL					● (6)	
Steel floor-standing enclosures	Spacial SM				●		
Steel suitable enclosures	Spacial SF				●		
Steel outdoor floor-standing enclosures	Spacial SFHD				●		
Stainless steel floor-standing enclosures	Spacial SMX				●		●
Stainless steel suitable enclosures	Spacial SFX				● (1)		●
Functional steel floor-standing enclosures	Spacial SFP				●		
Steel control desks	Spacial SD				●		
Stainless steel control desks	Spacial SDX				●		
Thermoplastic industrial boxes	Thalassa TBS-TBP				● (4)		● (5)
Polyester modular boxes	Thalassa PLS						●
Polyester wall-mounting enclosures	Thalassa PLM						●
Polyester outdoor wall-mounting enclosures	Thalassa PHD					●	
Polyester floor-standing enclosures	Thalassa PLA (2)		●	●		●	
Polyester floor-standing enclosures	Thalassa PLD	●		● (3)			
Polyester outdoor floor-standing enclosures	Thalassa PHD				●		

(1) Double door.
(2) Different IP depending on the version. See introduction in Thalassa section: PLA: IP65, PLAT / PLAZT: IP44, PLAZ / PLAT / PLAZT with grille: IP54.
(3) With gasket.
(4) Button boxes.
(5) Universal boxes.
(6) With membrane mounted.

The universal offer

> 3 Material solutions

Steel

Stainless steel

Plastic and Polyester

Selection according to the environment

The location of the enclosures and the physical, chemical and climatic conditions to which they are exposed will determine the model to be used.

- Steel enclosures are particularly well suited to indoor use in industrial environments.
- Stainless steel enclosures are particularly well suited to corrosive environments or areas where specific hygiene demands are applicable.
- Polyester enclosures are particularly well suited to severe corrosive atmospheres, indoors or outdoors..

Enclosures made from insulating materials help guarantee total insulation, reducing electric hazards for persons.
The main characteristics of the plastic materials of our enclosures and their chemical strength are given on page 633.

Further help for making the selection is given by the NEMA or UL classification of the enclosure, see page 630.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Degrees of protection provided by enclosures

- The degrees of protection provided by the enclosures are defined by standards IEC 60529 (IP) and IEC 62262 (IK).
- Degrees of protection are indicated by the letters IP followed by two characteristic numerals. The numerals show the degree of protection offered by the enclosure against access to dangerous parts, the penetration of of solid bodies (1st numeral), and against the penetration of liquids (2nd numeral).
- The protection against external mechanical impact is indicated by the letters IK followed by a characteristic group numeral.

Comment:
Many EN European standards are harmonised with international IEC standards.
This is the case with enclosure protection standards:
- EN 60529 = IEC 60529.
- EN 62262 = IEC 62262.

	IP	IK
First numeral Protection against solid bodies	Second numeral Protection against liquids	Mechanical protection
0 No protection	**0** No protection	**0** No protection
1 Protected against solid bodies larger than 50 mm (e.g.: Incidental contact with the hand)	**1** Protected against vertically falling water droplets (condensation)	**1** Impact energy: 0.150 Joules
2 Protected against solid bodies larger than 12 mm (e.g.: Finger contact)	**2** Protected against water droplets deflected at up to 15° from vertica	**2**  Impact energy: 0.200 Joules
3 Protected against solid bodies larger than 2.5 mm (tools, wires)	**3** Protected against rainwater at up to 60° from vertical	**3** Impact energy: 0.350 Joules
4 Protected against solid bodies larger than 1 mm (fine tools, small wires)	**4** ⚠ Protection against water spray from all directions	**4** Impact energy: 0.500 Joules
5  ❖ Protected against dust (no harmful deposits)	**5** ⚠⚠ Protected against low-pressure water jets from all directions	**5** Impact energy: 0.700 Joules
6 ❖ Totally dust tight	**6** Protected against powerful water jets from all directions	**6** Impact energy: 1.00 Joules
	7 ⬧⬧ Protected against the effects of immersion	**7** Impact energy: 2.00 Joules
	8  ⬧⬧ ... m Protected against prolonged effects of immersion under pressure	**8** Impact energy: 5.00 Joules
		9  Impact energy: 10.00 Joules
		10 Impact energy: 20.00 Joules

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Life Is On Schneider Electric

Classification of electrical

Classification of electrical equipment enclosures according to NEMA and UL

NEMA and UL are standardisation bodies, commonly recognised in North America, which have issued classifications of enclosures according to the protection offered in various environments.
These classifications are similar.
The 1st table below summarises this classification, which does not include potentially explosive areas.
The detailed recommendations of this classification are given on the next page.
The 2nd table indicates the classification of our enclosures.
These classifications appear in our UL certifications (see Certification technical annex on page 630).
Certification according to the UL classification helps guarantee the corresponding NEMA classification by equivalence.

Environment and protection	Classification											
	1	2	3	3R	3S	4	4X	5	6	6P	12	13
Indoor use	●	●	●	●	●	●	●	●	●	●	●	●
Outdoor use			●	●	●	●	●		●			
Incidental contact with the equipment	●	●	●	●	●	●	●	●	●	●	●	●
Dirt	●	●	●	●	●	●	●	●	●	●	●	●
Drips and gentle splashes of non-corrosive liquids		●	●	●	●	●	●	●	●	●	●	●
Rain, frost* and snow			●	●	●	●	●		●	●		
Frost**					●							
Dust, fibres and particles in suspension			●		●	●	●		●	●	●	●
Built-up dust, fibres and particles in suspension			●		●	●	●	●	●	●	●	●
Clouds of dust			●		●	●	●		●	●		
Splashes and jets of water						●	●		●	●		
Gentle splashes and leaks of oil or non-corrosive coolants											●	●
Drips, splashing and spraying of oil or non-corrosive coolants												●
Corrosive agents							●			●		
Occasional temporary immersion									●	●		
Occasional prolonged immersion										●		

* The operation of the external mechanisms is not required when the enclosure is covered with frost.
** The operation of the external mechanisms is required when the enclosure is covered with frost.

Enclosures		Type of protection (1)													
Name	Range	1	2	3	3R	3S	3X	3RX	3SX	4	4X	5	6	12	13
Metal industrial boxes	SBM									●	●				
HMI control enclosures	S3CM	●	●		●									●	●
Steel wall-mounting enclosures	S3D (1)	●	● (2)	● (2)	● (2)					● (2)	● (2)	●		●	●
Steel wall-mounting enclosures	S3HF	●	●	●	●									●	●
Steel outdoor wall-mounting enclosures	S3HD	●	●	●	●					●	●	●		●	●
Steel wall-mounting enclosures	CRN	●	●	●	●					●		●		●	●
Steel wall-mounting enclosures	CRNG	●	● (2)	● (2)	● (2)					● (2)	● (2)	● (2)		●	●
Stainless steel wall-mounting enclosures	S3X	●	● (2)	● (2)	● (2)					● (2)	● (2)	● (2)		●	● (2)
Steel floor-standing enclosures	SM	●	● (2)	● (2)	●					● (2)		● (2)		●	●
Polyester outdoor wall-mounting enclosures	PHD	●	●	●	●					● (2)	● (2)	●		●	●
Steel suitable enclosures	SF	●			●									●	
Steel outdoor floor-standing enclosures	SFHD	●			●									●	
Stainless steel floor-standing enclosures	SMX	●	● (2)	● (2)	● (2)					● (2)	● (2)	● (2)		●	●
Stainless steel floor-standing enclosures	SFX	● (2)	● (2)	● (2)	● (2)					● (2)	● (2)	● (2)			● (2)
Thermoplastic boxes	TBP	●		●		●				●	●				
Polyester modular boxes	PLS	●	●	●	●	●				●	●			●	●
Polyester wall-mounting enclosures	PLM	●	●	●	●	●				●	●	●		●	●
Polyester floor-standing enclosures	PLA	●	●	● (2)	● (2)	● (2)	● (2)	● (2)	● (2)			● (2)		●	●

(1) Also S3DM, S3DEX and S3DC.
(2) 1 door.

Components		Type of protection (5)											
Name	Range	1	2	3	3R	3S	4	4X	5	6	6P	12	13
Ventilation system	CV											●	
Thermal regulation system	CC	●											

(5) In some ranges the classification depends on the model and version. The detailed protection types are indicated in the UL certifications.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Classification of electrical equipment

Classification of electrical equipment enclosures according to NEMA and UL

Note:
The above recommendations aim to explain the NEMA and UL classifications, but are not the official texts of NEMA or UL.
The exact definitions provided by the Organisations are those of standards NEMA 250 and UL 50E.

The enclosures must protect the equipment against environmental conditions and help protect the personnel against the risk of incidental contact with the equipment. The following classifications (Type) are required according to the required uses and prescriptions:

Type	Use	Prescription
1	Indoor use	The enclosure provides protection for the personnel against incidental contact with the internal equipment and helps protect said equipment against dirt.
2	Indoor use	It provides protection for the personnel against incidental contact with the internal equipment and helps protect said equipment against dirt, drips and gentle splashes of non-corrosive liquids.
3	Indoor and outdoor use	The enclosure provides protection for the personnel against incidental contact with the internal equipment and helps protect said equipment against dirt, rain, sleet, snow, windblown and resists the formation of ice on the outside.
3R	Indoor and outdoor use	The enclosure provides protection for the personnel against incidental contact with the internal equipment and helps protect said equipment against dirt, rain, sleet, snow and resists the formation of ice on the outside.
3S	Indoor and outdoor use	The enclosure provides protection for the personnel against incidental contact with the internal equipment and helps protect said equipment against dirt, rain, sleet, snow and windblown dust. The external mechanism must continue to work even when layers of ice are formed.
3X	Indoor and outdoor use	The enclosure provides a degree of protection to personnel against access to hazardous parts; To provide a degree of protection of the equipment inside the enclosure against ingress of solid foreign objects (falling dirt and windblown dust); To provide a degree of protection with respect to harmful effects on the equipment due to the ingress of water (rain, sleet, snow); That provides an additional level of protection against corrosion and that will be undamaged by the external formation of ice on the enclosure.
3RX	Indoor and outdoor use	The enclosure provides a degree of protection to personnel against access to hazardous parts; To provide a degree of protection of the equipment inside the enclosure against ingress of solid foreign objects (falling dirt); To provide a degree of protection with respect to harmful effects on the equipment due to the ingress of water (rain, sleet, snow); That will be undamaged by the external formation of ice on the enclosure that provides an additional level of protection against corrosion.
3SX	Indoor and outdoor use	The enclosure provides a degree of protection to personnel against access to hazardous parts; To provide a degree of protection of the equipment inside the enclosure against ingress of solid foreign objects (falling dirt and windblown dust); To provide a degree of protection with respect to harmful effects on the equipment due to the ingress of water (rain, sleet, snow); That provides an additional level of protection against corrosion; And for which the external mechanism(s) remain operable when ice laden.
4	Indoor and outdoor use	The enclosure provides protection for the personnel against incidental contact with the internal equipment and helps protect said equipment against dirt, rain, sleet, snow, windblown dust, splashes and hose-directed water and resists the formation of frost on the outside.
4x	Indoor and outdoor use	The enclosure provides protection for the personnel against incidental contact with the internal equipment and helps protect said equipment against dirt, rain, sleet, snow, windblown dust, splashes, hose-directed water and resists corrosion and the formation of ice on the outside.
5	Indoor use	The enclosure provides protection for the personnel against incidental contact with the internal equipment and helps protect said equipment against dirt, settling airborne dust, lint, fibres, flyings, drips and gentle splashes of non-corrosive liquids.
6	Indoor and outdoor use	The enclosure provides protection for the personnel against incidental contact with the internal equipment and helps protect said equipment against dirt, rain, sleet, snow, hose-directed of water, the entry of water during occasional temporary submersion to a limited depth and resists the formation of ice on the outside.
6P	Indoor and outdoor use	The enclosure provides protection for the personnel against incidental contact with the internal equipment and helps protect said equipment against dirt, rain, sleet, snow, hose-directed water, the entry of water during prolonged submersion to a limited depth and resists corrosion and the formation of ice on the outside.
12	Indoor use (without knockouts)	The enclosure provides protection for the personnel against incidental contact with the internal equipment and helps protect said equipment against dirt, dust, fluff, fibres, particles in suspension, drips and gentle splashes of non-corrosive liquids as well as gentle splashes or leaks of oil and non-corrosive coolants.
13	Indoor use	The enclosure provides protection for the personnel against incidental contact with the internal equipment and helps protect said equipment against dirt, dust, lint, fibres flyings and the spraying, splashing, and seepage leaks of water, oil or non-corrosive coolants.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Coating properties

Polyester base coating properties



Product type

Thermosetting polyester resins based powder coating modified by epoxy resins and designed for decoration and to help prevent corrosion.
The performance of this coating is superior to conventional epoxy powders in terms of: Colour stability, temperature resistance and weather resistance.
Grey RAL 7035 grey; Appearance: Structured.

Mechanical properties

Test conditions: Steel samples with a thickness of 10/10^{e} mm.
Degreasing using biodegradable surface-active agents.
Film thickness: 60 microns.

Bonding (scratching and adhesive tape)	ISO 2409	≥ to Class 1
Ericksen stamping	ISO 1520	≥ 7 mm
Direct impact resistance	ISO 6272	> 1 kg/70 cm
Indirect impact resistance	ISO 6272	> 1 kg/20 cm
Bending around conical mandrel	ISO 6860 - ASTM D 522-88	Maximum cracking of 70 mm, without the paint coming loose

Chemical properties

Tests conducted at ambient temperature on phosphated samples covered with a 70 to 100 micron film:

Film intact.
Film attacked (blistering, yellowing, loss of gloss).

Number of months			2	4	6	8	10	12
Acid	Acetic	20 %						
	Sulphuric	30 %						
	Nitric	30 %						
	Phosphoric	30 %						
	Hydrochloric	30 %						
	Lactic	10 %						
	Citric	10 %						
Base	Soda	10 %						
	Ammonia	10 %						
Water	Distilled water							
	Sea water							
	Tap water							
	Diluted chloride bleach							
Solvents	Petrol							
	Higher alcohols							
	Aliphatics							
	Aromatics							
	Ketones-esters							
	Tri-perchlorethylene							

Physical properties

Temperature resistance: -40°C and 100 hours at +150°C (colour: White).
Gloss retention: Good.

Resistance to corrosion

Compliance with standard IEC 62208 for outdoor installations: 288 h of humid heat and 336 h of salt mist.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Coating properties

Polyester base coating properties

Nuclear decontamination
Applicable to colours RAL 7035 grey and AFNOR A550.
Standard NFT 30901. Percentage of decontamination for contamination by fission products. Please consult us for further details.

Accelerated aging
Standard IEC 62208: 500 h UV according to ISO 4892 (method A)
(adherence of the coating with minimum retention of 50% on the grid according to ISO 2409).

Fire behaviour
Class M1 (self-extinguishing material).
Class M0 (for coating on a metal base).

Manufacturing process



Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Properties of the plastic materials

Properties of the plastic materials Mechanical, electrical, physical and fire-resistance properties

Plastic materials generally used to manufacture our products:

- ABS.
- Polycarbonate.
- PVC (polyvinyl chloride).
- Bayblend® = PC + ABS.
- Polyester reinforced with fibreglass.
- Altuglas.
- Polypropylene.
- Polystyrene.
- Polyamide 6 and 12.
- SBS.

Specifications	Standards	Units	ABS	Polycarbonate	PVC	Bayblend®	Polyester	SBS
Mechanical properties								
Tensile strength	ISO 257	MPa	44	> 65	45	35	85	5
Tensile strain	ISO 527	%	12	> 110	120 bis 150	40	0	600
Impact resistance	ISO 179	kJ/m²	125	No breakage	25	No breakage	60	No breakage
Notching resistance	ISO 179	kJ/m²	19	25	20	25	50	-
Electrical properties								
Stress point	IEC 60112	-	-	250-300	> 600	> 550	> 600	-
Surface strength	IEC 60093	Ω	1015	> 1015	> 1013	> 1014	≥1012	> 1013
Dielectric strength	IEC 60243	kV/mm	16.5	> 30	30	24	18-20	20
Specific resistivity	IEC 60093	Ω³cm	1015	> 1016	≥ 1015	1016	≥ 1012	> 1016
Physical properties								
Softening temperature (Vicat B)	ISO 306	°C	95	145-150	79-80	115	(1)	80
Temperature resistance	-	°C	-40...+90	-50...+125	-20...+65	-35...+90	-50...+150	-40...+120
Water absorption	ISO 62	%	0.2 - 0.45	0.15	< 0.1	0.2	0.2	-
Specific weight	ISO 1183	kg/dm³	1.04	1.21	1.4	1.12	1.85	0.3 in 24 h
Fire resistance								
Oxygen index	ISO 4589	%	19	26	45-50	22	24.4	18
Glow wire resistance, 2 mm	IEC 60695-2-10	°C	650	960	960	750	960	750° (1.5 mm)
Glow wire resistance, 3 mm	IEC 60695-2-10	°C	650	960	960	750	960	NA

(1) No softening of the polyester.

Specifications	Standards	Units	Altuglas	Polypropylene	Polystyrene	Polyamide 6	Polyamide 12
Mechanical properties							
Tensile strength	ISO 257	MPa	30	35	24	40	30
Tensile strain	ISO 527	%	5	400	36	200	300
Impact resistance	ISO 179	kJ/m²	20	20	63	No breakage	No breakage
Notching resistance	ISO 179	kJ/m²	3	5	50	31.2	15
Electrical properties							
Stress point	IEC 60112	-	-	-	KB175	KB175	KB180
Surface strength	IEC 60093	Ω	≥ 1014	-	> 1013	1012	5 x 1010
Dielectric strength	IEC 60243	kV/mm	13-15	20	≤ 40	23	55
Specific resistivity	IEC 60093	Ω³cm	> 1015	> 1016	> 1015	1011	3 x 1011
Physical properties							
Softening temperature (Vicat B)	ISO 306	°C	120-122	75 (vicat A)	79	230	140
Temperature resistance	-	°C	-20...+80	-10...+80	-15...+60	-20...+100	-50...+125
Water absorption	ISO 62	%	< 0.5	0.1 in 24 h	0.1 in 24 h	1.6	1.5
Density	ISO 1183	kg/dm³	1.18	0.91	1.06	1.14	1.03
Fire resistance							
Oxygen index	ISO 4589	%	18.5	18	18	24	22
Glow wire resistance, 2 mm	IEC 60695-2-10	°C	-	650	650	750	650
Glow wire resistance, 3 mm	IEC 60695-2-10	°C	960	650	650	850	650

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Properties of the plastic materials

Properties of the plastic materials Resistance to chemical agents

Plastic materials generally used to manufacture our products:

- ABS.
- Polycarbonate.
- PVC (polyvinyl chloride).
- Bayblend® = PC + ABS.
- Polyester.
- Altuglas.
- Polypropylene.
- Polystyrene.
- Polyamide 6 and 12.
- SBS.

The table shows:
The concentration of the chemical agent in %;
- sat = saturation.

The resistance of the material:
- +: Resistant.
- O: Limited resistance.
- –: Not resistant.

Resistance to	ABS		Polycarbonate		PVC		Bayblend®		Polyester		Altuglas		Polypropylene		Polystyrene		Polyamide 6		Polyamide 12		SBS	
Acetone		–		–		–		–		–		O	100	+		–	100	+		+		+
Hydrochloric acid	15	+	10	+	30	+	20	+	30	+	sat	+	10	+		O	10	–	10	+	10	+
Citric acid			10	+	sat	+	10	+	100	+	sat	+	sat	+		+	10	O		+	10	+
Lactic acid	80	+	10	+	90	+	10	–	100	+	20	+	90	+		O	50 90	O –		+ +	sat	+
Nitric acid	30	+	10 100	+ –	50	+	10	+	20	+ +	10 100	+ –	25/ 50			O	2 10	O –		–	50	+
Phosphoric acid	85	+	100	+	sat	+		+	100	+	10 95	+ –	sat	+		O	2 10	O –	50	+		+
Sulphuric acid	50	+	50 100	+ –	96	+	30	+	70	+	30	+	96	+		O	3	–	10	+	96	+
Alcohol		O	96	+	96	+		–	50	O	50	O	96	+		+	96	O	96	+		+
Pure aniline		O		–	100	–		–		O		–	100	+			100	O	100	O		
Benzene		+	100	–		–		+		–		O	100	O			100	+		+		–
Liquid bromine			100	–		–		–					100	–					100	–		–
Liquid chlorine				-	100	-		-	sat	+		–	100	–			100	O		–	50	+
Sea water		+	100	+	100	+		+	100	+	100	+		–	100	+			100	+	sat	+
Petrol		+	100	+	100	O		–	100	+	100	O		–		–	100	+		+		–
Ether		–	100	O	100	–		–	100	O		+					100	+	100	+		–
Hexane		O		+		O		O		–			100	+			100	+	100	+		–
Oil and greases		+	100	+	100	+		O	100	+	100	O	100	+		–		+	100	+		–
Aromatic hydrocarbon		O		–		–		–		–		+	–			–		–		+		–
Fuel oil		O	100	O	100	+		–	100	+	100	–	100	+			100	+	100	+		–
Naphthalene					100	O		–	100	+	100	–	100	+			100	+	100	+		
Nitrobenzene		–		–	100	–		–				–	100	O				–		O		–
Phenol		–		–	sat	O		–	20	O		–	sat	+				–		–	10	O
Mineral salts				+		+		+		+		+		+						+		+
Iodine solution				O		–		+				–						+				
Toluene		–		–	100	–		–		+		O	100	O		–	100	+	100	+		–
Trichloroethylene		–		–	100	–		–		–		–	100	O		–	100	–	100	O		–
Urea			sat	+	sat	+		+					sat	+			10	+	sat	+	sat	O

Comment:
For other chemical agents, please contact us.
All this information is taken from the best sources and provided for information purposes only, with no commitment on our behalf.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Description of the marking label affixed

Description of the marking label affixed to ATEX certified wall-mounting enclosures

Spacial S3DEX



* with the dimensions

1 Product range

2

- **0163:** Identification No. of the notified body for application of the ATEX directive.
- **Ex:** Distinctive Community mark indicating that the product is authorized in explosive atmospheres.
- **II:** Industry Group (II = surface industry).
- **2:** Equipment category (2 = occasional presence, Zone 1 or 21).
- **GD:** Type of atmosphere (G= Gas and vapour or mist, D= Dust).

3

- **Ex:** Symbol indicating that the equipment corresponds to one or more protection methods standardized by Cénélec.
- **e:** Protection method used: e = enhanced safety (EN 60079-7).
- **IIC:** Gas group (hydrogen/acetylene).
- **Gb:** Protection method for non-electric equipment (check on power supply source). G = gas.

4

- **Ex:** Symbol indicating that the equipment corresponds to one or more protection methods standardized by Cénélec.
- **t:** Protection method used: t = protection by enclosure (EN 60079-31).
- **IIIC:** Dust group (conductive dust).
- **Db:** Protection method for non-electric equipment (check on power supply source). D = dust.

5 Name of the certification

- Name of the certification body + No. of the CE type certificate.

6 IP

- **IP66:** Degree of intrusion protection..

Download our ATEX certificates from our site.

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Spare parts Selection table

Steel industrial boxes SBM

NSYSBMABS4

Accessories	References
Bag of acces. SBM boxes 4 screws	**NSYSBMABS4**
Bag of acces. SBM boxes 6 screws	**NSYSBMABS6**

Steel wall-mounting enclosures S3D

NSYDS3D32

Doors	References
Plain door 300 x 200	**NSYDS3D32**
Plain door 300 x 250	**NSYDS3D325**
Plain door 300 x 300	**NSYDS3D33**
Plain door 300 x 400	**NSYDS3D34**
Plain door 400 x 300	**NSYDS3D43**
Plain door 400 x 400	**NSYDS3D44**
Plain door 400 x 600	**NSYDS3D46**
Plain door 500 x 300	**NSYDS3D53**
Plain door 500 x 400	**NSYDS3D54**
Plain door 500 x 500	**NSYDS3D55**
Plain door 600 x 400	**NSYDS3D64**
Plain door 600 x 500	**NSYDS3D65**
Plain door 600 x 600	**NSYDS3D66**
Plain door 600 x 800	**NSYDS3D68**
Plain door 700 x 500	**NSYDS3D75**
Plain door 800 x 600	**NSYDS3D86**
Plain door 800 x 800	**NSYDS3D88**
Plain door 800 x 1000	**NSYDS3D810**
Plain door 800 x 500 right	**NSYDS3D85R**
Plain door 800 x 500 left	**NSYDS3D85L**
Plain door 800 x 600 right	**NSYDS3D86R**
Plain door 800 x 600 left	**NSYDS3D86L**
Plain door 1000 x 600	**NSYDS3D106**
Plain door 1000 x 800	**NSYDS3D108**
Plain door 1000 x 1000	**NSYDS3D1010**
Plain door 1200 x 1000	**NSYDS3D1210**
Plain door 1000 x 500 right	**NSYDS3D105R**
Plain door 1000 x 500 left	**NSYDS3D105L**
Plain door 1000 x 600 right	**NSYDS3D106R**
Plain door 1000 x 600 left	**NSYDS3D106L**
Plain door 1200 x 600	**NSYDS3D126**
Plain door 1200 x 800	**NSYDS3D128**
Plain door 1200 x 500 right	**NSYDS3D125R**
Plain door 1200 x 500 left	**NSYDS3D125L**
Plain door 1200 x 600 right	**NSYDS3D126R**
Plain door 1200 x 600 left	**NSYDS3D126L**
Plain door 1400 x 500 right	**NSYDS3D145R**
Plain door 1400 x 500 left	**NSYDS3D145L**

Door accessories	References
Gasket double door encl.	**NSYGDD**
Set of 5 taps and latches	**NSYS3DTL**
Hinge 120°	**NSYAEDH120S3D**
Hinge 180°	**NSYAEDH180S3D**
Earthing accessories	**References**
Set of 500 earthing labels	**NSYSWMEL**
Fixing hardware cable gland plate	**References**
100 screws	**NSYS3DCGSB**
Standard screw bag	**NSYS3DCGPSTDSB**
Locking accessories	**References**
Set of 10 linkage guides	**NSYS3DLG**
Standard key DB3	**NSYAEDLS3DKDB3**
Lock + standard key DB3 neutral	**NSYAEDLS3DRLN**
3 point lock linkage H 600 mm	**NSYBTAS3D60**
3 point lock linkage H 700 mm	**NSYBTAS3D70**
3 point lock linkage H 800 mm	**NSYBTAS3D80**
3 point lock linkage H 1000 mm	**NSYBTAS3D100**
3 point lock linkage H 1200 mm	**NSYBTAS3D120**
3 point lock linkage H 1400 mm	**NSYBTAS3D140**
Lock with key type 3131A	**NSYAEDL3131AS3D**
3 point lock linkage (H = 650 mm)	**NSYBTAS3D65**
3 point lock linkage (H = 900 mm)	**NSYBTAS3D90**
Panels	**References**
50 caps for holes of hinges WM	**NSYSWMCH**
Set of 50 back plugs WM	**NSYSWMBP**

See page 532 for details or consult our web site www.se.com

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Spare parts Selection table

Steel wall-mounting enclosures S3DM

NSYS3DCGSB

Fixing hardware	References
100 screws cable gland plate	**NSYS3DCGSB**
Standard screw bag cable gland plate	**NSYS3DCGPSTDSB**
Earthing accessories	**References**
Set of 500 earthing labels	**NSYSWMEL**
Locking accessories	**References**
Set of 10 linkage guides	**NSYS3DLG**
Standard key DB3	**NSYAEDLS3DKDB3**
3 point lock linkage H 600 mm	**NSYBTAS3D60**
3 point lock linkage H 700 mm	**NSYBTAS3D70**
3 point lock linkage H 800 mm	**NSYBTAS3D80**
3 point lock linkage H 1000 mm	**NSYBTAS3D100**
Panels WM	**References**
50 caps for holes of hinges	**NSYSWMCH**
Set of 50 back plugs	**NSYSWMBP**

Steel wall-mounting enclosures S3DC

NSYSWMEL

Earthing accessories	References
Set of 500 earthing labels	**NSYSWMEL**
Locking accessories	**References**
Set of 10 linkage guides	**NSYS3DLG**
Standard lock enclosures	**NSYAEDLS3DC**
3 point lock linkage H 600 mm	**NSYBTAS3D60**
3 point lock linkage H 700 mm	**NSYBTAS3D70**
3 point lock linkage H 800 mm	**NSYBTAS3D80**
3 point lock linkage H 1000 mm	**NSYBTAS3D100**
3 point lock linkage H 1200 mm	**NSYBTAS3D120**
Panels WM	**References**
50 caps for holes of hinges	**NSYSWMCH**
Set of 50 back plugs	**NSYSWMBP**

Steel wall-mounting enclosures S3DB

NSYSWMEL

Earthing accessories	References
Set of 500 earthing labels	**NSYSWMEL**
Locking accessories	**References**
Standard key DB3	**NSYAEDLS3DKDB3**
Panels	**References**
50 caps for holes of hinges WM	**NSYSWMCH**
Set of 50 back plugs WM	**NSYSWMBP**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Spare parts Selection table

Steel wall-mounting enclosures CRN

NSYDCRN22

Doors	References
Plain door H 200 x W 200	**NSYDCRN22**
Plain door H 200 x W 300	**NSYDCRN23**
Plain door H 250 x W 200	**NSYDCRN2520**
Plain door H 300 x W 250	**NSYDCRN3025**
Plain door H 300 x W 300	**NSYDCRN33**
Plain door H 300 x W 400	**NSYDCRN34**
Plain door H 300 x W 450	**NSYDCRN3045**
Plain door H 400 x W 300	**NSYDCRN43**
Plain door H 400 x W 400	**NSYDCRN44**
Plain door H 400 x W 600	**NSYDCRN46**
Plain door H 500 x W 400	**NSYDCRN54**
Plain door H 500 x W 500	**NSYDCRN55**
Plain door H 600 x W 400	**NSYDCRN64**
Plain door H 600 x W 500	**NSYDCRN65**
Plain door H 600 x W 600	**NSYDCRN66**
Plain door H 600 x W 800	**NSYDCRN68**
Plain door H 700 x W 500	**NSYDCRN75**
Plain door H 800 x W 600	**NSYDCRN86**
Plain door H 800 x W 800	**NSYDCRN88**
Plain door H 1000 x W 600	**NSYDCRN106**
Plain door H 1000 x W 800	**NSYDCRN108**

Door accessories	References
Standard Spacial hinge	**NSYBICRN**
Earthing accessories	**References**
Set of 500 earthing labels	**NSYSWMEL**
Locking accessories	**References**
TCRE1 Lock	**NSYTCRE1**
TCRE12 Lock	**NSYTCRE12**
Platten	**References**
Set of 50 back plugs WM	**NSYSWMBP**
Fixing hardware	**References**
Screw bag for CRN cable gland plate	**NSYCRNCGPSTDSB**
Sealing	**References**
Adhesive sealing gasket 18 x 10 2M	**NSYADG2M**
Adhesive sealing gasket 18 x 10 3M	**NSYADG3M**
Adhesive sealing gasket 18 x 10 5M	**NSYADG5M**
Adhesive sealing gasket 18 x 10 20M	**NSYADG20M**

Steel wall-mounting enclosures CRNG

NSYDCRNG86

Doors	References
Plain door H 800 x W 600	**NSYDCRNG86**
Plain door left H 800 x W 500	**NSYDCRNG85L**
Plain door right H 800 x W 500	**NSYDCRNG85R**
Plain door left H 800 x W 600	**NSYDCRNG86L**
Plain door right H 800 x W 600	**NSYDCRNG86R**
Plain door H 1000 x W 600	**NSYDCRNG106**
Plain door H 1000 x W 800	**NSYDCRNG108**
Plain door left H 1000 x W 500	**NSYDCRNG105L**
Plain door right H 1000 x W 500	**NSYDCRNG105R**
Plain door right H 1000 x W 600	**NSYDCRNG106R**
Plain door left H 1000 x W 600	**NSYDCRNG106L**
Plain door right H 1000 x W 600	**NSYDCRNG106R**
Plain door left H 1000 x W 600	**NSYDCRNG106L**
Plain door H 1200 x W 600	**NSYDCRNG126**
Plain door H 1200 x W 600	**NSYDCRNG126**
Plain door H 1200 x W 800	**NSYDCRNG128**
Plain door H 1200 x W 800	**NSYDCRNG128**
Plain door right H 1200 x W 500	**NSYDCRNG125R**
Plain door left H 1200 x W 500	**NSYDCRNG125L**
Plain door right H 1200 x W 500	**NSYDCRNG125R**
Plain door left H 1200 x W 500	**NSYDCRNG125L**
Plain door H 1200 x W 600	**NSYDCRNG126R**
Plain door left H 1200 x W 600	**NSYDCRNG126L**
Plain door H 1200 x W 600	**NSYDCRNG126R**
Plain door left H 1200 x W 600	**NSYDCRNG126L**
Plain door right H 1400 x W 500	**NSYDCRNG145R**
Plain door left H 1400 x W 500	**NSYDCRNG145L**

Doors	References
Glazed door H 800 x W 600	**NSYDCRNG86T**
Glazed door H 1000 x W 600	**NSYDCRNG106T**
Glazed door H 1000 x W 800	**NSYDCRNG108T**
Glazed door H 1000 x W 1000	**NSYDCRNG1010T**
Glazed door H 1200 x W 600	**NSYDCRNG126T**
Glazed door H 1200 x W 600	**NSYDCRNG126T**
Glazed door H 1200 x W 800	**NSYDCRNG128T**
Glazed door H 1200 x W 800	**NSYDCRNG128T**
Door accessories	**References**
Hinge 120°	**NSYAEDH120S3D**
Hinge 180°	**NSYAEDH180S3D**
Locking accessories	**References**
3 point lock linkage for Spacial CRNG (H = 800 mm)	**NSYBTACRNG80**
3 point lock linkage for Spacial CRNG (H = 1000 mm)	**NSYBTACRNG100**
3 point lock linkage for Spacial CRNG (H = 1200 mm)	**NSYBTACRNG120**
3 point lock linkage for Spacial CRNG (H = 1400 mm)	**NSYBTACRNG140**
Earthing accessories	**References**
Set of 500 earthing labels	**NSYSWMEL**
Fixing hardware cable gland plate	**References**
100 screws	**NSYS3DCGSB**
Standard screw bag	**NSYS3DCGPSTDSB**
Panels	**References**
50 caps for holes of hinges WM	**NSYSWMCH**
Set of 50 back plugs WM	**NSYSWMBP**
Others accessories	**References**
Screw bag for CRN cable gland plate	**NSYCRNCGPSTDSB**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Spare parts Selection table

Steel floor-standing enclosures SF

NSYSFD207

Doors	References
Spacial SFP plain door H 2000 x W 700 mm	**NSYSFD207**
Spacial SFP transparent door H 2000 x W 700 mm	**NSYSFD207T**
Door accessories	**References**
Set of 4 Hinges and fixing elements	**NSYDHSF**
Double door stoppers (2 pieces)	**NSYTDSSF2D**
Locking accessories	**References**
Locking system for enclosures 1 single door version 1200H (right side door for double door version)	**NSYLCK12SF**
Locking system for enclosures 1 single door version 1400H	**NSYLCK14SF**
Locking system for enclosures 1 single door version 1600H (right side door for double door version)	**NSYLCK16SF**
Locking system for enclosures 1 single door version 1800H (right side door for double door version)	**NSYLCK18SF**
Locking system for enclosures 1 single door version 2000H (right side door for double door version)	**NSYLCK20SF**
Locking system for enclosures 1 single door version 2200H (right side door for double door version)	**NSYLCK22SF**
Door locking system toothed washer	**NSYLCKWSF**
Handle neutral trim	**NSYSFHNTRIM**
Handle SF	**NSYSFHS1**

Fixing hardware	References
Captive screws for panels external fixing	**NSYCSSF**
Plinth accessories	**References**
H 100 mm Plastic covers for plinth corners	**NSYPC100**
H 200 mm Plastic covers for plinth corners	**NSYPC200**
Installation accessories	**References**
Set of 2 quick cross rails 120 x 400 mm	**NSYSQCR12040**
Set of 2 quick cross rails 120 x 500 mm	**NSYSQCR12050**
Set of 2 quick cross rails 120 x 600 mm	**NSYSQCR12060**
Set of 2 quick cross rails 120 x 800 mm	**NSYSQCR12080**
Panels	**References**
Spacial SFP back panel H 2000 x W 700 mm	**NSYBP207**

NSYRSF35

NSYRSF35L

Roof	New roof (expanded)	Old roof (integrated)
Roof W 300 x D 500 mm	**NSYRSF35L**	**NSYRSF35**
Roof W 300 x D 600 mm	**NSYRSF36L**	**NSYRSF36**
Roof W 300 x D 800 mm	**NSYRSF38L**	**NSYRSF38**
Roof W 400 x D 400 mm	**NSYRSF44L**	**NSYRSF44**
Roof W 400 x D 500 mm	**NSYRSF45L**	**NSYRSF45**
Roof W 600 x D 400 mm	**NSYRSF64L**	**NSYRSF64**
Roof W 600 x D 500 mm	**NSYRSF65L**	**NSYRSF65**
Roof W 600 x D 600 mm	**NSYRSF66L**	**NSYRSF66**
Roof W 800 x D 400 mm	**NSYRSF84L**	**NSYRSF84**
Roof W 800 x D 500 mm	**NSYRSF85L**	**NSYRSF85**
Roof W 800 x D 600 mm	**NSYRSF86L**	**NSYRSF86**
Roof W 800 x D 800 mm	**NSYRSF88L**	**NSYRSF88**
Roof W 1000 x D 400 mm	**NSYRSF104L**	**NSYRSF104**
Roof W 1000 x D 500 mm	**NSYRSF105L**	**NSYRSF105**
Roof W 1000 x D 600 mm	**NSYRSF106L**	**NSYRSF106**
Roof W 1000 x D 800 mm	**NSYRSF108L**	**NSYRSF108**
Roof W 1200 x D 400 mm	**NSYRSF124L**	**NSYRSF124**
Roof W 1200 x D 500 mm	**NSYRSF125L**	**NSYRSF125**
Roof W 1200 x D 600 mm	**NSYRSF126L**	**NSYRSF126**
Roof W 1200 x D 800 mm	**NSYRSF128L**	**NSYRSF128**
Roof W 1600 x D 400 mm	**NSYRSF164L**	**NSYRSF164**
Roof W 1600 x D 500 mm	**NSYRSF165L**	**NSYRSF165**
Roof W 1600 x D 600 mm	**NSYRSF166L**	**NSYRSF166**

"New roof" accessory	References
Fix roof off-center bracket	**NSYRSFBLR**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Spare parts Selection table

Steel floor-standing enclosures SM

NSYSMEC1041

Cable gland plates	References
1 entry W 1000 x D 400 mm	**NSYSMEC1041**
1 entry W 1000 x D 300 mm	**NSYSMEC1031**
1 entry W 1000 x D 500 mm	**NSYSMEC1051**
1 entry W 600 x D 300 mm	**NSYSMEC631**
1 entry W 600 x D 400 mm	**NSYSMEC641**
1 entry W 600 x D 500 mm	**NSYSMEC651**
1 entry W 600 x D 600 mm	**NSYSMEC661**
1 entry W 800 x D 300 mm	**NSYSMEC831**
1 entry W 800 x D 400 mm	**NSYSMEC841**
1 entry W 800 x D 500 mm	**NSYSMEC851**
1 entry W 800 x D 600 mm	**NSYSMEC861**
Doors	**Old roof integrated)**
Double plain door H 1200 x W 1000 mm	**NSYSMD12102D**
Double plain door H 1200 x W 1200 mm	**NSYSMD12122D**
Double plain door H 1400 x W 1000 mm	**NSYSMD14102D**
Double plain door H 1400 x W 1200 mm	**NSYSMD14122D**
Double plain door H 1600 x W 1000 mm	**NSYSMD16102D**
Double plain door H 1600 x W 1200 mm	**NSYSMD16122D**
Double plain door H 1800 x W 1600 mm	**NSYSMD18162D**

Door accessories	References
Set of 4 hinges and fixing elements	**NSYDHSF**
Spacial SM hinges and 2D door stop	**NSYDHSM2D**
Double door stoppers (2 pieces)	**NSYTDSSF2D**
Locking accessories	**References**
Locking system for enclosures 1 single door version 1200H (right side door for double door version)	**NSYLCK12SF**
Locking system for enclosures 1 single door version 1600H (right side door for double door version)	**NSYLCK16SF**
Locking system for enclosures 1 single door version 1800H (right side door for double door version)	**NSYLCK18SF**
Locking system for enclosures 1 single door version 2000H (right side door for double door version)	**NSYLCK20SF**
Locking system for enclosures 1 single door version 2200H (right side door for double door version)	**NSYLCK22SF**
Locking system for enclosures 1 single door version 1400H	**NSYLCK14SF**
Door locking system toothed washer	**NSYLCKWSF**
Handle neutral trim	**NSYSFHNTRIM**
Plinth accessories	**References**
H 100 mm Plastic covers for plinth corners	**NSYPC100**
H 200 mm Plastic covers for plinth corners	**NSYPC200**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Spare parts Selection table

Stainless steel enclosuresS3X (wall-mounting)

NSYDS3X1010L

Doors	References
Left door 304L 1000 x 1000 mm	**NSYDS3X1010L**
Left door 316L 1000 x 1000 mm	**NSYDS3X1010LH**
Right door 304L 1000 x 1000 mm	**NSYDS3X1010R**
Right door 316L 1000 x 1000 mm	**NSYDS3X1010RH**
Plain door 304L 1000 x 800 mm	**NSYDS3X108**
Plain door 316L 1000 x 800 mm	**NSYDS3X108H**
Left door 304L 1200 x 1000 mm	**NSYDS3X1210L**
Left door 316L 1200 x 1000 mm	**NSYDS3X1210LH**
Right door 304L 1200 x 1000 mm	**NSYDS3X1210R**
Right door 316L 1200 x 1000 mm	**NSYDS3X1210RH**
Plain door 304L 1200 x 800 mm	**NSYDS3X128**
Plain door 316L 1200 x 800 mm	**NSYDS3X128H**
Plain door 304L 300 x 200 mm	**NSYDS3X32**
Plain door 304L 300 x 250 mm	**NSYDS3X325**
Plain door 316L 300 x 250 mm	**NSYDS3X325H**
Plain door 316L300 x 200 mm	**NSYDS3X32H**
Plain door 304L 300 x 300 mm	**NSYDS3X33**
Plain door 316L 300 x 300 mm	**NSYDS3X33H**
Plain door 304L 400 x 300 mm	**NSYDS3X43**
Plain door 316L 400 x 300 mm	**NSYDS3X43H**
Plain door 304L 400 x 400 mm	**NSYDS3X44**
Plain door 316L 400 x 400 mm	**NSYDS3X44H**
Plain door 304L 400 x 600 mm	**NSYDS3X46**

Doors	References
Plain door 316L 400 x 600 mm	**NSYDS3X46H**
Plain door 304L 500 x 400 mm	**NSYDS3X54**
Plain door 316L 500 x 400 mm	**NSYDS3X54H**
Plain door 304L 600 x 400 mm	**NSYDS3X64**
Plain door 316L 600 x 400 mm	**NSYDS3X64H**
Plain door 304L 600 x 600 mm	**NSYDS3X66**
Plain door 316L 600 x 600 mm	**NSYDS3X66H**
Plain door 304L 700 x 500 mm	**NSYDS3X75**
Plain door 316L 700 x 500 mm	**NSYDS3X75H**
Plain door 304L 800 x 600 mm	**NSYDS3X86**
Plain door 316L 800 x 600 mm	**NSYDS3X86H**
Plain door 304L 800 x 800 mm	**NSYDS3X88**
Plain door 316L 800 x 800 mm	**NSYDS3X88H**
Transp. door 304L 1000 x 800 mm	**NSYDS3X108T**
Transp. door 304L 400 x 300 mm	**NSYDS3X43T**
Transp. door 304L 500 x 400 mm	**NSYDS3X54T**
Transp. door 304L 600 x 400 mm	**NSYDS3X64T**
Transp. door 304L 700 x 500 mm	**NSYDS3X75T**
Transp. door 304L 800 x 600 mm	**NSYDS3X86T**
Door accessories	**References**
Set of 2 hinges	**NSYHS3X**
Locking accessories	**References**
Locking system 1000 mm	**NSYLSS3X10**
Locking system 1200 mm	**NSYLSS3X12**

Stainless steel enclosuresSMX ((floor-standing)

NSYDSFX1410L

Doors	References
Left door 304L 1400 x 1000 mm	**NSYDSFX1410L**
Right door 304L 1400 x 1000 mm	**NSYDSFX1410R**
Door 304L 1600 x 800 mm	**NSYDSFX168**
Door 304L 1800 x 600 mm	**NSYDSFX186**
Left door 1800 x 1200 mm	**NSYDSFX1812L**
Left door 316L 1800 x 1200 mm	**NSYDSFX1812LH**
Right door 1800 x 1200 mm	**NSYDSFX1812R**
Right door 316L 1800 x 1200 mm	**NSYDSFX1812RH**
Door 304L 1800 x 800 mm	**NSYDSFX188**
Door 316L 1800 x 800 mm	**NSYDSFX188H**
Left door 304L 1800 x 1600 mm	**NSYDSFX1816L**
Left door 316L 1800 x 1600 mm	**NSYDSFX1816LH**
Right door 304L 1800 x 1600 mm	**NSYDSFX1816R**
Right door 316L 1800 x 1600 mm	**NSYDSFX1816RH**
Left door 2000 x 1000 mm	**NSYDSFX2010L**
Left door 316L 2000 x 1000 mm	**NSYDSFX2010LH**
Right door 2000 x 1000 mm	**NSYDSFX2010R**
Right door 316L 2000 x 1000 mm	**NSYDSFX2010RH**
Door 1800 x 800 mm	**NSYDSFX206**
Left door 2000 x 1200 mm	**NSYDSFX2012L**
Left door 316L 2000 x 1200 mm	**NSYDSFX2012LH**
Right door 2000 x 1200 mm	**NSYDSFX2012R**
Right door 316L 2000 x 1200 mm	**NSYDSFX2012RH**
Door 2000 x 800 mm	**NSYDSFX208**
Left door 2000 x 1600 mm	**NSYDSFX2016L**
Left door 316L 2000 x 1600 mm	**NSYDSFX2016LH**
Right door 2000 x 1600 mm SMX	**NSYDSFX2016R**
Right door 316L 2000 x 1600 mm	**NSYDSFX2016RH**

Locking system	References
Locking system H = 1400 mm	**NSYLSSFX14**
Locking system H = 1600 mm	**NSYLSSFX16**
Locking system H = 1800 mm	**NSYLSSFX18**
Locking system H = 2000 mm	**NSYLSSFX20**
Door accessories	**References**
Double door stoppers (2 pieces)	**NSYTDSSF2D**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Spare parts Selection table

Stainless steel enclosuresSFX (floor-standing)

NSYDSFX186

Doors	References
Door 304L 1800 x 600 mm	**NSYDSFX186**
Left door 1800 x 1200 mm	**NSYDSFX1812L**
Right door 1800 x 1200 mm	**NSYDSFX1812R**
Door 304L 1800 x 800 mm	**NSYDSFX188**
Left door 2000 x 1000 mm	**NSYDSFX2010L**
Right door 2000 x 1000 mm	**NSYDSFX2010R**
Door 1800 x 800 mm	**NSYDSFX206**
Left door 2000 x 1200 mm	**NSYDSFX2012L**
Right door 2000 x 1200 mm	**NSYDSFX2012R**
Door 2000 x 800 mm	**NSYDSFX208**
Left door 2000 x 1600 mm	**NSYDSFX2016L**
Right door 2000 x 1600 mm	**NSYDSFX2016R**

Door accessories	References
Set of 3 hinges	**NSYHSMX**
Double door stoppers (2 pieces)	**NSYTDSSF2D**
Locking accessories	**References**
Locking system H = 1400 mm	**NSYLSSFX14**
Locking system H = 1600 mm	**NSYLSSFX16**
Locking system H = 1800 mm	**NSYLSSFX18**
Locking system H = 2000 mm	**NSYLSSFX20**

Insulating materials PLA (floor-standing)

NSYDPLA55G

- For RAL 7035

Doors	References
Door 500 x 500 Lock handle type. Door opening 120°	**NSYDPLA55G**
Door 500 x 750 Lock handle type. Door opening 120°	**NSYDPLA57G**
Door 750 x 500 Lock handle type. Door opening 120°	**NSYDPLA75G**
Door 750 x 750 Lock handle type. Door opening 120°	**NSYDPLA77G**
Door 1000 x 500 Lock handle type. Door opening 120°	**NSYDPLA105G**
Door 1000 x 750 Lock handle type. Door opening 120°	**NSYDPLA107G**
Door 1250 x 500 Lock handle type. Door opening 120°	**NSYDPLA125G**
Door 1250 x 750 Lock handle type. Door opening 120°	**NSYDPLA127G**
Door 1500 x 500 Lock handle type. Door opening 120°	**NSYDPLA155G**
Door 1500 x 750 Lock handle type. Door opening 120°	**NSYDPLA157G**
Door 500 x 500 Lock handle type. Door opening 180° + Accessory bag 120° hinge	**NSYDPLA55HG**
Door 500 x 750 Lock handle type. Door opening 180° + Accessory bag 120° hinge	**NSYDPLA57HG**
Door 750 x 500 Lock handle type. Door opening 180° + Accessory bag 120° hinge	**NSYDPLA75HG**
Door 750 x 750 Lock handle type. Door opening 180° + Accessory bag 120° hinge	**NSYDPLA77HG**
Door 1000 x 500 Lock handle type. Door opening 180° + Accessory bag 120° hinge	**NSYDPLA105HG**
Door 1000 x 750 Lock handle type. Door opening 180° + Accessory bag 120° hinge	**NSYDPLA107HG**
Door 1250 x 500 Lock handle type. Door opening 180° + Accessory bag 120° hinge	**NSYDPLA125HG**
Door 1250 x 750 Lock handle type. Door opening 180° + Accessory bag 120° hinge	**NSYDPLA127HG**

- For RAL 7035

Doors	References
Door 1500 x 500 Lock handle type. Door opening 180° + Accessory bag 120° hinge	**NSYDPLA155HG**
Door 1500 x 750 Lock handle type. Door opening 180° + Accessory bag 120° hinge	**NSYDPLA157HG**
Door accessories	**References**
One hinge + axe for PLA (120° opening)	**NSYAEDPLA004**
Kit of axes of door PLAZT (180° opening)	**NSYAEDPLA005**
Rod guide inside the door PLA (set of 2)	**NSYAEDPLA001**
Rod guide on 1 door PLA (set of 2)	**NSYAEDPLA002G**
Rod guide on 2 doors PLA (set of 2)	**NSYAEDPLA003G**
Fixing hardware	**References**
Acc. bag for 1 door H = 500-1000 mm	**NSYASPLA001**
Acc. bag for 2 doorH = 1250-1500 mm	**NSYASPLA002**
Acc. bag for 2 door	**NSYASPLA003**
Locking accessories	**References**
Handle locking and rods H = 500 mm	**NSYVPLA5MG**
Handle locking and rods H = 750 mm	**NSYVPLA7MG**
Handle locking and rods H = 1000 mm	**NSYVPLA10MG**
Handle locking and rods H = 1250 mm	**NSYVPLA12MG**
Handle locking and rods H = 1500 mm	**NSYVPLA15MG**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Spare parts Selection table

Insulating materials PLM (wall-mounting)

NSYDPLM32G

• For RAL 7035

Complete door (door + lock system)	References
Door without locking for PLM32	**NSYDPLM32G**
Door without locking for 2 locks PLM3025	**NSYDPLM3025G**
Door without locking for PLM43	**NSYDPLM43G**
Door without locking for PLM54	**NSYDPLM54G**
Door without locking for PLM64	**NSYDPLM64G**
Door without locking for PLM75	**NSYDPLM75G**
Door without locking for PLM86	**NSYDPLM86G**
Door without locking for PLM108	**NSYDPLM108G**
Transp. door without locking for PLM32T	**NSYDPLM32TG**
Glazed door without locking for PLM3025T	**NSYDPLM3025TG**
Glazed door without locking for PLM43T	**NSYDPLM43TG**
Glazed door without locking for PLM54T	**NSYDPLM54TG**
Glazed door without locking for PLM64T	**NSYDPLM64TG**
Glazed door without locking for PLM75T	**NSYDPLM75TG**
Glazed door without locking for PLM86T	**NSYDPLM86TG**
Glazed door without locking for PLM108T	**NSYDPLM108TG**

Door accessories	References
Door hinge for NSYPLM32	**NSYAEDHPLM32**
Door hinge for NSYPLM3025 for 2 locks door	**NSYAEDHPLM3025**
Door hinge for NSYPLM43 to 86	**NSYAEDHPLM**
Door hinge for NSYPLM108	**NSYAEDHPLM108**
Rod guides (4 pieces) for PLM108	**NSYAEDPLM108**
Fixing hardware	**References**
Acc. bag NSYPLM32	**NSYASPLM32**
Acc. bag NSYPLM43 to 86	**NSYASPLM**
Locking accessories	**References**
Locking and rods for NSYPLM108	**NSYVPLM108**

Applicative and customised solutions: HMI SD

NSYCCSDF8

Doors	References
Desk lid W 600 mm	**NSYDLSD6**
Desk lid W 800 mm	**NSYDLSD8**
Desk lid W 1000 mm	**NSYDLSD10**
Desk lid W 1200 mm	**NSYDLSD12**
Desk lid for w/console W 800 mm	**NSYDLSDF8**
Desk lid for w/console W 1000 mm	**NSYDLSDF10**
Desk lid for w/console W 1200 mm	**NSYDLSDF12**
Desk lid for w/console W 1600 mm	**NSYDLSDF16**
Folding console cover W 800 mm	**NSYCCSDF8**
Folding console cover W 1000 mm	**NSYCCSDF10**
Folding console cover W 1200 mm	**NSYCCSDF12**
Folding console cover W 1600 mm	**NSYCCSDF16**

Door accessories	References
Hinges compact control desk	**NSYHSD**
Hinges control desk w/console	**NSYHSDF**
Locking accessories	**References**
Standard handle in RAL 7011	**NSYSDH**
Lock w/DB 3 mm for frontal doors	**NSYFDLSD**
Lock w/DB 3 mm desk lids and covers	**NSYDLLSDF**
Flat escutcheon with DB 5 mm	**NSYSDFLOCKDB5**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Spare parts Selection table

Applicative and customised solutions: HMI

Door accessories	References
Locking system	**NSYLSSDX**

Applicative and customised solutions: S3CM

Doors	References
Plain door H 200 x W 200	**NSYDCRN22**
Plain door H 200 x W 300	**NSYDCRN23**
Plain door H 250 x W 200	**NSYDCRN2520**
Plain door H 300 x W 250	**NSYDCRN3025**
Plain door H 300 x W 300	**NSYDCRN33**
Plain door H 300 x W 400	**NSYDCRN34**
Plain door H 300 x W 450	**NSYDCRN3045**
Plain door H 400 x W 300	**NSYDCRN43**
Plain door H 400 x W 400	**NSYDCRN44**
Plain door H 400 x W 600	**NSYDCRN46**
Plain door H 500 x W 500	**NSYDCRN55**
Plain door H 600 x W 600	**NSYDCRN66**
Plain door H 600 x W 800	**NSYDCRN68**
Plain door H 800 x W 600	**NSYDCRN86**

Door accessories	References
Standard Spacial hinge	**NSYBICRN**
Earthing accessories	**References**
Set of 500 earthing labels	**NSYSWMEL**

Applicative and customised solutions: EMC, S3HF

NSYSWMEL

Earthing accessories	References
Set of 500 earthing labels	**NSYSWMEL**
Locking accessories	**References**
Standard Locking system	**NSYAEDLS3HFDB3**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Spare parts Selection table

Applicative and customised solutions: ATEX S3DEX

NSYDS3D32

Doors	References
Plain door 300 x 200	**NSYDS3D32**
Plain door 300 x 300	**NSYDS3D33**
Plain door 400 x 300	**NSYDS3D43**
Plain door 400 x 400	**NSYDS3D44**
Plain door 500 x 400	**NSYDS3D54**
Plain door 600 x 400	**NSYDS3D64**
Plain door 600 x 600	**NSYDS3D66**
Plain door 700 x 500	**NSYDS3D75**
Plain door 800 x 600	**NSYDS3D86**
Plain door 1000 x 800	**NSYDS3D108**
Earthing accessories	**References**
Set of 500 earthing labels	**NSYSWMEL**

Locking accessories	References
Set of 10 linkage guides	**NSYS3DLG**
Standard key DB3	**NSYAEDLS3DKDB3**
3 point lock linkage H 600 mm	**NSYBTAS3D60**
3 point lock linkage H 700 mm	**NSYBTAS3D70**
3 point lock linkage H 800 mm	**NSYBTAS3D80**
3 point lock linkage H 1000 mm	**NSYBTAS3D100**
Panels	**References**
50 caps for holes of hinges WM	**NSYSWMCH**
Set of 50 back plugs WM	**NSYSWMBP**

Outdoor Heavy Duty enclosures Thalassa PHD

NSYPPC74HD

Plain doors (door + lock + hinges + door retainer)	Unic door or right door References	Left door References
H 538 x W 500	**NSYDPHD55P**	-
H 788 x W 500	**NSYDPHD75P**	-
H 843 x W 750	**NSYDPHD77P**	-
H 1093 x W 500	**NSYDPHD105P**	-
H 1093 x W 750	**NSYDPHD107P**	-
H 1343 x W 500	**NSYDPHD125P**	-
H 1343 x W 750	**NSYDPHD127P**	-
H 1343 x W 1250	**NSYDPHD127P**	**NSYDPHD125LP**
H 1593 x W 750	**NSYDPHD157P**	-
H 1593 x W 1250	**NSYDPHD157P**	**NSYDPHD155LP**
H 2093 x W 750	2 x **NSYDPHD107P**	-
Ribbed doors (door + lock + hinges + door retainer)	**References**	**References**
H 538 x W 500	**NSYDPHD55R**	-
H 788 x W 500	**NSYDPHD75R**	-
H 843 x W 750	**NSYDPHD77R**	-
H 1093 x W 500	**NSYDPHD105R**	-
H 1093 x W 750	**NSYDPHD107R**	-
H 1343 x W 500	**NSYDPHD125R**	-
H 1343 x W 750	**NSYDPHD127R**	-
H 1343 x W 1250	**NSYDPHD127R**	**NSYDPHD125LR**
H 1593 x W 750	**NSYDPHD157R**	-
H 1593 x W 1250	**NSYDPHD157R**	**NSYDPHD155LR**
H 2093 x W 750	2 x **NSYDPHD107R**	-

Aluminium cable gland plate	References
For enclosure W 750 x D 420	**NSYPPC74HD**
For enclosure W 750 x D 620	**NSYPPC76HD**
For enclosure W 500 x D 420	**NSYPPC54HD**
For enclosure W 1250 x D 420	**NSYPPC54HD** + **NSYPPC74HD**
For enclosure W 1250 x D 620	**NSYPPC56HD** + **NSYPPC76HD**
Screws and nuts for PHD gland plate (10 units)	**NSYPPCPHDSN**
Door accessories	**References**
Set of 4 complete hinges for PHD	**NSYAEDPHD**
Locking accessories	**References**
Complete lock system for PHD H 500	**NSYVPHD5**
Complete lock system for PHD H 750	**NSYVPHD7**
Complete lock system for PHD H 1000	**NSYVPHD10**
Complete lock system for PHD H 1250	**NSYVPHD12**
Complete lock system for PHD H 1500	**NSYVPHD15**
Complete lock system for PHD H 2000	2 x **NSYVPHD10**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Spare parts Selection table

Outdoor Heavy Duty enclosures Spacial S3HD

NSYTLAUHD

Heavy duty cable gland plate for enclosure	References
H 343 x W 200 x D 180	**NSYTLAUHD**
H 448 x W 300 x D 230	**NSYTLCUHD**
H 548 x W 400 x D 230	**NSYTLDUHD**
H 653 x W 400 x D 280	**NSYTLDUHD**
H 658 x W 600 x D 330	**NSYTLGUHD**
H 753 x W 500 x D 280	**NSYTLEUHD**
e H 858 x W 600 x D 330	**NSYTLGUHD**
H 862 x W 800 x D 430	2 x **NSYTLDUHD**
H 1062 x W 600 x D 430	**NSYTLGUHD**
H 1062 x W 800 x D 430	2 x **NSYTLDUHD**
Door	**References**
Door 300 x 200 S3HD, without handle	**NSYDS3HD32**
Door 400 x 300 S3HD, without handle	**NSYDS3HD43**
Door 500 x 400 S3HD, without handle	**NSYDS3HD54**
Door 600 x 400 S3HD + linkage locking syst	**NSYDS3HD64**
Door 600 x 600 S3HD + linkage locking syst	**NSYDS3HD66**
Door 700 x 500 S3HD + linkage locking syst	**NSYDS3HD75**
Door 800 x 600 S3HD + linkage locking syst	**NSYDS3HD86**
Door 800 x 800 S3HD + linkage locking syst	**NSYDS3HD88**
Door 1000 x 600 S3HD + linkage locking syst	**NSYDS3HD106**
Door 1000 x 800 S3HD + linkage locking syst	**NSYDS3HD108**

Hinge	References
S3HD hinge	**NSYAEDH120S3HD**
Canopy	**References**
Canopy for S3HD 200 (W) x 150 (P)	**NSYTJ2015HD**
Canopy for S3HD 300 (W) x 200 (P)	**NSYTJ3020HD**
Canopy for S3HD 400 (W) x 200 (P)	**NSYTJ4020HD**
Canopy for S3HD 400 (W) x 250 (P)	**NSYTJ4025HD**
Canopy for S3HD 600 (W) x 300 (P)	**NSYTJ6030HD**
Canopy for S3HD 500 (W) x 250 (P)	**NSYTJ5025HD**
Canopy for S3HD 800 (W) x 400 (P)	**NSYTJ8040HD**
Canopy for S3HD 600 (W) x 400 (P)	**NSYTJ6040HD**
Lock	**References**
Lock S3HD DB 3 mm (Escutcheon+cam+washer)	**NSYAEDLS3HDRL**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Spare parts Selection table

Outdoor Heavy Duty enclosures Spacial SFHD

NSYSFECA64HD

Heavy duty cable gland plate for enclosure	References
H 1262 x W 600 x D 430	**NSYSFECA64HD**
H 1262 x W 800 x D 430	**NSYSFECA64HD**
H 1262 x W 1200 x D 430	2 x **NSYSFECA64HD**
H 1281 x W 600 x D 630	**NSYSFECA66HD**
H 1281 x W 800 x D 630	**NSYSFECA66HD**
H 1281 x W 1200 x D 630	2 x **NSYSFECA66HD**
H 1662 x W 800 x D 430	**NSYSFECA64HD**
H 1662 x W 1200 x D 430	2 x **NSYSFECA64HD**
H 1681 x W 600 x D 630	**NSYSFECA66HD**
H 1681 x W 800 x D 630	**NSYSFECA66HD**
H 1681 x W 1200 x D 630	2 x **NSYSFECA66HD**
H 2062 x W 800 x D 430	**NSYSFECA64HD**

Door	References
Plain door SFHD 1200 x 600 mm	**NSYSFDHD126**
Plain door SFHD 1200 x 800 mm	**NSYSFDHD128**
Plain door SFHD 1200 x 1200 mm	**NSYSFDHD12122D**
Plain door SFHD 1600 x 600 mm	**NSYSFDHD166**
Plain door SFHD 1600 x 800 mm	**NSYSFDHD168**
Plain door doble SFHD 1600 x 1200 mm	**NSYSFDHD16122D**
Plain door SFHD 2000 x 800 mm	**NSYSFDHD208**

Back Panel	References
SFHD 1200 x 600 mm	**NSYBPHD126**
SFHD 1200 x 800 mm	**NSYBPHD128**
SFHD 1200 x 1200 mm	**NSYBPHD12122D**
SFHD 1600 x 600 mm	**NSYBPHD166**
SFHD 1600 x 800 mm	**NSYBPHD168**
SFHD 1600 x 1200 mm	**NSYBPHD1612**
SFHD 2000 x 800 mm	**NSYBPHD208**

Canopy	References
SFHD 600 x 400 mm	**NSYSC64HD**
SFHD 600 x 600 mm	**NSYSC66HD**
SFHD 800 x 400 mm	**NSYSC84HD**
SFHD 800 x 600 mm	**NSYSC86HD**
SFHD 1200 x 400 mm	**NSYSC124HD**
SFHD 1200 x 600 mm	**NSYSC126HD**

Handle with 1242E cylindrical barrel	References
Handle SFHD 1242E	**NSYSFHS1HD**

Captive screws	References
Captive screws for Spacial SFHD panels	**NSYCSSFHD**

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Spare parts ClimaSys

Air-AIR exchangers

	Exchanger Battery	Fan (Fan + Capacitor)	Frontal Cover RAL 7035 grey	Thermostat	Mounting Kit (instruction + full seal + screws)
References	References	References	References	References	References
NSYCEA14E	NSYCUSP0030	NSYCUSP0042	NSYCUSP0076	-	NSYCUSP0111
NSYCEA22E	NSYCUSP0177	NSYCUSP0042	NSYCUSP0181	-	NSYCUSP0184
NSYCEA36	NSYCUSP0031	NSYCUSP0044	NSYCUSP0077	NSYCUSP0100	NSYCUSP0112
NSYCEA50	NSYCUSP0032	NSYCUSP0044	NSYCUSP0077	NSYCUSP0100	NSYCUSP0112
NSYCEA80	NSYCUSP0033	NSYCUSP0138	NSYCUSP0078	NSYCUSP0100	NSYCUSP0113

Air-WATER exchangers

	Exchanger Battery	Fan (Fan + Capacitor)	Frontal Cover RAL 7035 grey	Frontal Cover Stainless Steel
References	References	References	References	References
NSYCEW1K	NSYCUSP0034	NSYCUSP0043	NSYCUSP0079	-
NSYCEWX1K	NSYCUSP0034	NSYCUSP0043	-	NSYCUSP0094
NSYCEW1KUL	NSYCUSP0034	NSYCUSP0043	NSYCUSP0079	-
NSYCEWX1KUL	NSYCUSP0034	NSYCUSP0043	-	NSYCUSP0094
NSYCEW1K8	NSYCUSP0035	NSYCUSP0044	NSYCUSP0080	-
NSYCEWX1K8	NSYCUSP0035	NSYCUSP0044	-	NSYCUSP0095
NSYCEW1K8UL	NSYCUSP0035	NSYCUSP0044	NSYCUSP0080	-
NSYCEWX1K8UL	NSYCUSP0035	NSYCUSP0044	-	NSYCUSP0095
NSYCEW2K5	NSYCUSP0036	NSYCUSP0136	NSYCUSP0080	-
NSYCEWX2K5	NSYCUSP0036	NSYCUSP0136	-	NSYCUSP0095
NSYCEW2K5UL	NSYCUSP0036	NSYCUSP0136	NSYCUSP0080	-
NSYCEWX2K5UL	NSYCUSP0036	NSYCUSP0136	-	NSYCUSP0095
NSYCEW3K5	NSYCUSP0037	NSYCUSP0138	NSYCUSP0081	-
NSYCEWX3K5	NSYCUSP0037	NSYCUSP0138	-	NSYCUSP0096
NSYCEW3K5UL	NSYCUSP0037	NSYCUSP0138	NSYCUSP0081	-
NSYCEWX3K5UL	NSYCUSP0037	NSYCUSP0138	-	NSYCUSP0096
NSYCEW4K5	NSYCUSP0037	NSYCUSP0137	NSYCUSP0081	-
NSYCEWX4K5	NSYCUSP0037	NSYCUSP0137	-	NSYCUSP0096
NSYCEW4K5UL	NSYCUSP0037	NSYCUSP0137	NSYCUSP0081	-
NSYCEWX4K5UL	NSYCUSP0037	NSYCUSP0137	-	NSYCUSP0096
NSYCEW6K	NSYCUSP0038	NSYCUSP0137	NSYCUSP0082	-
NSYCEWX6K	NSYCUSP0038	NSYCUSP0137	-	NSYCUSP0097
NSYCEW6KUL	NSYCUSP0038	NSYCUSP0137	NSYCUSP0082	-
NSYCEWX6KUL	NSYCUSP0038	NSYCUSP0137	-	NSYCUSP0097
NSYCEW6K2P4	NSYCUSP0038	NSYCUSP0137	NSYCUSP0082	-
NSYCEWX6K2P4	NSYCUSP0038	NSYCUSP0137	-	NSYCUSP0097
NSYCEW10K	NSYCUSP0039	NSYCUSP0137	NSYCUSP0083	-
NSYCEWX10K	NSYCUSP0039	NSYCUSP0137	-	NSYCUSP0098
NSYCEW10K2P4	NSYCUSP0039	NSYCUSP0137	NSYCUSP0083	-
NSYCEWX10K2P4	NSYCUSP0039	NSYCUSP0137	-	NSYCUSP0098
NSYCEW15K	NSYCUSP0040	NSYCUSP0137	NSYCUSP0083	-
NSYCEWX15K	NSYCUSP0040	NSYCUSP0137	-	NSYCUSP0098
NSYCEW15K2P4	NSYCUSP0040	NSYCUSP0137	NSYCUSP0083	-
NSYCEWX15K2P4	NSYCUSP0040	NSYCUSP0137	-	NSYCUSP0098
NSYCEW2K5R	NSYCUSP0041	NSYCUSP0053	NSYCUSP0084	-

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Spare parts ClimaSys

	Air-WATER exchangers			
	Thermostat	Transformer	Solenoid Valve	Mounting Kit (instruction + full seal + screws)
References	References	References	References	References
NSYCEW1K	NSYCUSP0100	-	NSYCUSP0108	NSYCUSP0114
NSYCEWX1K	NSYCUSP0100	-	NSYCUSP0108	NSYCUSP0114
NSYCEW1KUL	NSYCUSP0175	-	NSYCUSP0176	NSYCUSP0114
NSYCEWX1KUL	NSYCUSP0175	-	NSYCUSP0176	NSYCUSP0114
NSYCEW1K8	NSYCUSP0100	-	NSYCUSP0109	NSYCUSP0124
NSYCEWX1K8	NSYCUSP0100	-	NSYCUSP0109	NSYCUSP0124
NSYCEW1K8UL	NSYCUSP0175	-	NSYCUSP0176	NSYCUSP0124
NSYCEWX1K8UL	NSYCUSP0175	-	NSYCUSP0176	NSYCUSP0124
NSYCEW2K5	NSYCUSP0100	-	NSYCUSP0109	NSYCUSP0124
NSYCEWX2K5	NSYCUSP0100	-	NSYCUSP0109	NSYCUSP0124
NSYCEW2K5UL	NSYCUSP0175	-	NSYCUSP0176	NSYCUSP0124
NSYCEWX2K5UL	NSYCUSP0175	-	NSYCUSP0176	NSYCUSP0124
NSYCEW3K5	NSYCUSP0100	-	NSYCUSP0109	NSYCUSP0115
NSYCEWX3K5	NSYCUSP0100	-	NSYCUSP0109	NSYCUSP0115
NSYCEW3K5UL	NSYCUSP0175	-	NSYCUSP0176	NSYCUSP0115
NSYCEWX3K5UL	NSYCUSP0175	-	NSYCUSP0176	NSYCUSP0115
NSYCEW4K5	NSYCUSP0100	-	NSYCUSP0109	NSYCUSP0115
NSYCEWX4K5	NSYCUSP0100	-	NSYCUSP0109	NSYCUSP0115
NSYCEW4K5UL	NSYCUSP0175	-	NSYCUSP0176	NSYCUSP0115
NSYCEWX4K5UL	NSYCUSP0175	-	NSYCUSP0176	NSYCUSP0115
NSYCEW6K	NSYCUSP0100	-	NSYCUSP0109	NSYCUSP0125
NSYCEWX6K	NSYCUSP0100	-	NSYCUSP0109	NSYCUSP0125
NSYCEW6KUL	NSYCUSP0175	-	NSYCUSP0176	NSYCUSP0125
NSYCEWX6KUL	NSYCUSP0175	-	NSYCUSP0176	NSYCUSP0125
NSYCEW6K2P4	NSYCUSP0100	NSYCUSP0107	NSYCUSP0109	NSYCUSP0125
NSYCEWX6K2P4	NSYCUSP0100	NSYCUSP0107	NSYCUSP0109	NSYCUSP0125
NSYCEW10K	NSYCUSP0100	-	NSYCUSP0110	NSYCUSP0116
NSYCEWX10K	NSYCUSP0100	-	NSYCUSP0110	NSYCUSP0116
NSYCEW10K2P4	NSYCUSP0100	NSYCUSP0107	NSYCUSP0110	NSYCUSP0116
NSYCEWX10K2P4	NSYCUSP0100	NSYCUSP0107	NSYCUSP0110	NSYCUSP0116
NSYCEW15K	NSYCUSP0100	-	NSYCUSP0110	NSYCUSP0116
NSYCEWX15K	NSYCUSP0100	-	NSYCUSP0110	NSYCUSP0116
NSYCEW15K2P4	NSYCUSP0100	NSYCUSP0107	NSYCUSP0110	NSYCUSP0116
NSYCEWX15K2P4	NSYCUSP0100	NSYCUSP0107	NSYCUSP0110	NSYCUSP0116
NSYCEW2K5R	NSYCUSP0100	-	NSYCUSP0109	NSYCUSP0117

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Spare parts ClimaSys

	Cooling units: Side mounting models				
	Evaporator Battery	Evaporator Fan (fan + capacitor)	Condenser Battery	Condenser Fan (fan + capacitor)	Compressor Kit
References	References	References	References	References	References
NSYCU300H	NSYCUSP0001	NSYCUSP0042	NSYCUSP0013	NSYCUSP0042	NSYCUSP0054
NSYCU400	NSYCUSP0002	NSYCUSP0042	NSYCUSP0014	NSYCUSP0042	NSYCUSP0055
NSYCU400UL	NSYCUSP0002	NSYCUSP0042	NSYCUSP0014	NSYCUSP0042	NSYCUSP0055
NSYCUX400	NSYCUSP0002	NSYCUSP0042	NSYCUSP0014	NSYCUSP0042	NSYCUSP0055
NSYCU600	NSYCUSP0003	NSYCUSP0043	NSYCUSP0015	NSYCUSP0044	NSYCUSP0056
NSYCUX600	NSYCUSP0003	NSYCUSP0043	NSYCUSP0015	NSYCUSP0044	NSYCUSP0056
NSYCU600UL	NSYCUSP0003	NSYCUSP0043	NSYCUSP0015	NSYCUSP0044	NSYCUSP0056
NSYCUX600UL	NSYCUSP0003	NSYCUSP0043	NSYCUSP0015	NSYCUSP0044	NSYCUSP0056
NSYCU800	NSYCUSP0004	NSYCUSP0043	NSYCUSP0016	NSYCUSP0044	NSYCUSP0057
NSYCUX800	NSYCUSP0004	NSYCUSP0043	NSYCUSP0016	NSYCUSP0044	NSYCUSP0057
NSYCU800UL	NSYCUSP0004	NSYCUSP0043	NSYCUSP0016	NSYCUSP0044	NSYCUSP0057
NSYCUX800UL	NSYCUSP0004	NSYCUSP0043	NSYCUSP0016	NSYCUSP0044	NSYCUSP0057
NSYCU1K	NSYCUSP0004	NSYCUSP0043	NSYCUSP0017	NSYCUSP0044	NSYCUSP0057
NSYCUX1K	NSYCUSP0004	NSYCUSP0043	NSYCUSP0017	NSYCUSP0044	NSYCUSP0057
NSYCU1KUL	NSYCUSP0004	NSYCUSP0043	NSYCUSP0017	NSYCUSP0044	NSYCUSP0057
NSYCUX1KUL	NSYCUSP0004	NSYCUSP0043	NSYCUSP0017	NSYCUSP0044	NSYCUSP0057
NSYCU1K2P4	NSYCUSP0004	NSYCUSP0043	NSYCUSP0017	NSYCUSP0044	NSYCUSP0057
NSYCUX1K2P4	NSYCUSP0004	NSYCUSP0043	NSYCUSP0017	NSYCUSP0044	NSYCUSP0057
NSYCU1K2P4UL	NSYCUSP0004	NSYCUSP0043	NSYCUSP0017	NSYCUSP0044	NSYCUSP0057
NSYCUX1K2P4UL	NSYCUSP0004	NSYCUSP0043	NSYCUSP0017	NSYCUSP0044	NSYCUSP0057
NSYCU1K2	NSYCUSP0005	NSYCUSP0044	NSYCUSP0018	NSYCUSP0136	NSYCUSP0058
NSYCUX1K2	NSYCUSP0005	NSYCUSP0044	NSYCUSP0018	NSYCUSP0136	NSYCUSP0058
NSYCU1K2UL	NSYCUSP0005	NSYCUSP0044	NSYCUSP0018	NSYCUSP0136	NSYCUSP0058
NSYCUX1K2UL	NSYCUSP0005	NSYCUSP0044	NSYCUSP0018	NSYCUSP0136	NSYCUSP0058
NSYCU1K22P4	NSYCUSP0005	NSYCUSP0044	NSYCUSP0018	NSYCUSP0136	NSYCUSP0058
NSYCUX1K22P4	NSYCUSP0005	NSYCUSP0044	NSYCUSP0018	NSYCUSP0136	NSYCUSP0058
NSYCU1K6	NSYCUSP0006	NSYCUSP0044	NSYCUSP0019	NSYCUSP0138	NSYCUSP0059
NSYCUX1K6	NSYCUSP0006	NSYCUSP0044	NSYCUSP0019	NSYCUSP0138	NSYCUSP0059
NSYCU1K6UL	NSYCUSP0006	NSYCUSP0044	NSYCUSP0019	NSYCUSP0138	NSYCUSP0059
NSYCUX1K6UL	NSYCUSP0006	NSYCUSP0044	NSYCUSP0019	NSYCUSP0138	NSYCUSP0059
NSYCU1K62P4	NSYCUSP0006	NSYCUSP0044	NSYCUSP0019	NSYCUSP0138	NSYCUSP0059
NSYCUX1K62P4	NSYCUSP0006	NSYCUSP0044	NSYCUSP0019	NSYCUSP0138	NSYCUSP0059
NSYCU1K62P4UL	NSYCUSP0006	NSYCUSP0044	NSYCUSP0019	NSYCUSP0138	NSYCUSP0059
NSYCUX1K62P4UL	NSYCUSP0006	NSYCUSP0044	NSYCUSP0019	NSYCUSP0138	NSYCUSP0059

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Spare parts ClimaSys

	Cooling units: Side mounting models				
	Evaporator Battery	Evaporator Fan (fan + capacitor)	Condenser Battery	Condenser Fan (fan + capacitor)	Compressor Kit
References	References	References	References	References	References
NSYCU2K	NSYCUSP0006	NSYCUSP0136	NSYCUSP0020	NSYCUSP0138	NSYCUSP0060
NSYCUX2K	NSYCUSP0006	NSYCUSP0136	NSYCUSP0020	NSYCUSP0138	NSYCUSP0060
NSYCU2KUL	NSYCUSP0006	NSYCUSP0136	NSYCUSP0020	NSYCUSP0138	NSYCUSP0139
NSYCUX2KUL	NSYCUSP0006	NSYCUSP0136	NSYCUSP0020	NSYCUSP0138	NSYCUSP0139
NSYCU2K3P4	NSYCUSP0006	NSYCUSP0136	NSYCUSP0020	NSYCUSP0138	NSYCUSP0061
NSYCUX2K3P4	NSYCUSP0006	NSYCUSP0136	NSYCUSP0020	NSYCUSP0138	NSYCUSP0061
NSYCU2K3P4UL	NSYCUSP0006	NSYCUSP0136	NSYCUSP0020	NSYCUSP0138	NSYCUSP0062
NSYCUX2K3P4UL	NSYCUSP0006	NSYCUSP0136	NSYCUSP0020	NSYCUSP0138	NSYCUSP0062
NSYCU3K3P4	NSYCUSP0007	NSYCUSP0137	NSYCUSP0021	NSYCUSP0137	NSYCUSP0062
NSYCUX3K3P4	NSYCUSP0007	NSYCUSP0137	NSYCUSP0021	NSYCUSP0137	NSYCUSP0062
NSYCU3K3P4UL	NSYCUSP0007	NSYCUSP0137	NSYCUSP0021	NSYCUSP0137	NSYCUSP0062
NSYCUX3K3P4UL	NSYCUSP0007	NSYCUSP0137	NSYCUSP0021	NSYCUSP0137	NSYCUSP0062
NSYCU4K3P4	NSYCUSP0007	NSYCUSP0137	NSYCUSP0022	NSYCUSP0137	NSYCUSP0063
NSYCUX4K3P4	NSYCUSP0007	NSYCUSP0137	NSYCUSP0022	NSYCUSP0137	NSYCUSP0063
NSYCU4K3P4UL	NSYCUSP0007	NSYCUSP0137	NSYCUSP0022	NSYCUSP0137	NSYCUSP0063
NSYCUX4K3P4UL	NSYCUSP0007	NSYCUSP0137	NSYCUSP0022	NSYCUSP0137	NSYCUSP0063
NSYCU6K3P4	-	-	-	-	-
NSYCU6K3P460	-	-	-	-	-
NSYCU8K3P4	-	-	-	-	-
NSYCU8K3P460	-	-	-	-	-
NSYCU10K3P4	-	-	-	-	-
NSYCU10K3P460	-	-	-	-	-
NSYCU15K3P4	-	-	-	-	-
NSYCU15K3P460	-	-	-	-	-

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Spare parts ClimaSys

	Cooling units and side mounting models				
	Frontal Cover RAL 7035 grey	Frontal Cover Stainless Steel	Thermostat	Transformer	Mounting Kit (instruction + full seal + screws)
References	References	References	References	References	References
NSYCU300H	NSYCUSP0066	-	NSYCUSP0099	-	NSYCUSP0118
NSYCU400	NSYCUSP0067	-	NSYCUSP0099	-	NSYCUSP0126
NSYCU400UL	NSYCUSP0067	-	NSYCUSP0144	-	NSYCUSP0126
NSYCUX400	-	NSYCUSP0085	NSYCUSP0099	-	NSYCUSP0126
NSYCU600	NSYCUSP0068	-	NSYCUSP0099	-	NSYCUSP0127
NSYCUX600	-	NSYCUSP0086	NSYCUSP0099	-	NSYCUSP0127
NSYCU600UL	NSYCUSP0068	-	NSYCUSP0144	-	NSYCUSP0127
NSYCUX600UL	-	NSYCUSP0086	NSYCUSP0144	-	NSYCUSP0127
NSYCU800	NSYCUSP0069	-	NSYCUSP0099	-	NSYCUSP0119
NSYCUX800	-	NSYCUSP0087	NSYCUSP0099	-	NSYCUSP0119
NSYCU800UL	NSYCUSP0069	-	NSYCUSP0144	-	NSYCUSP0119
NSYCUX800UL	-	NSYCUSP0087	NSYCUSP0144	-	NSYCUSP0119
NSYCU1K	NSYCUSP0069	-	NSYCUSP0099	-	NSYCUSP0119
NSYCUX1K	-	NSYCUSP0087	NSYCUSP0099	-	NSYCUSP0119
NSYCU1KUL	NSYCUSP0069	-	NSYCUSP0144	-	NSYCUSP0119
NSYCUX1KUL	-	NSYCUSP0087	NSYCUSP0144	-	NSYCUSP0119
NSYCU1K2P4	NSYCUSP0069	-	NSYCUSP0099	NSYCUSP0101	NSYCUSP0119
NSYCUX1K2P4	-	NSYCUSP0087	NSYCUSP0099	NSYCUSP0101	NSYCUSP0119
NSYCU1K2P4UL	NSYCUSP0069	-	NSYCUSP0144	NSYCUSP0173	NSYCUSP0119
NSYCUX1K2P4UL	-	NSYCUSP0087	NSYCUSP0144	NSYCUSP0173	NSYCUSP0119
NSYCU1K2	NSYCUSP0070	-	NSYCUSP0099	-	NSYCUSP0120
NSYCUX1K2	-	NSYCUSP0088	NSYCUSP0099	-	NSYCUSP0120
NSYCU1K2UL	NSYCUSP0070	-	NSYCUSP0144	-	NSYCUSP0120
NSYCUX1K2UL	-	NSYCUSP0088	NSYCUSP0144	-	NSYCUSP0120
NSYCU1K22P4	NSYCUSP0070	-	NSYCUSP0099	NSYCUSP0102	NSYCUSP0120
NSYCUX1K22P4	-	NSYCUSP0088	NSYCUSP0099	NSYCUSP0102	NSYCUSP0120
NSYCU1K6	NSYCUSP0070	-	NSYCUSP0099	-	NSYCUSP0120
NSYCUX1K6	-	NSYCUSP0088	NSYCUSP0099	-	NSYCUSP0120
NSYCU1K6UL	NSYCUSP0070	-	NSYCUSP0144	-	NSYCUSP0120
NSYCUX1K6UL	-	NSYCUSP0088	NSYCUSP0144	-	NSYCUSP0120
NSYCU1K62P4	NSYCUSP0070	-	NSYCUSP0099	NSYCUSP0103	NSYCUSP0120
NSYCUX1K62P4	-	NSYCUSP0088	NSYCUSP0099	NSYCUSP0103	NSYCUSP0120
NSYCU1K62P4UL	NSYCUSP0070	-	NSYCUSP0144	NSYCUSP0174	NSYCUSP0120
NSYCUX1K62P4UL	-	NSYCUSP0088	NSYCUSP0144	NSYCUSP0174	NSYCUSP0120

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Spare parts ClimaSys

	Cooling units and side mounting models				
	Frontal Cover RAL 7035 grey	Frontal Cover Stainless Steel	Thermostat	Transformer	Mounting Kit (instruction + full seal + screws)
References	References	References	References	References	References
NSYCU2K	NSYCUSP0070	-	NSYCUSP0099	-	NSYCUSP0120
NSYCUX2K	-	NSYCUSP0088	NSYCUSP0099	-	NSYCUSP0120
NSYCU2KUL	NSYCUSP0070	-	NSYCUSP0144	-	NSYCUSP0120
NSYCUX2KUL	-	NSYCUSP0088	NSYCUSP0144	-	NSYCUSP0120
NSYCU2K3P4	NSYCUSP0070	-	NSYCUSP0099	NSYCUSP0104	NSYCUSP0120
NSYCUX2K3P4	-	NSYCUSP0088	NSYCUSP0099	NSYCUSP0104	NSYCUSP0120
NSYCU2K3P4UL	NSYCUSP0070	-	NSYCUSP0144	NSYCUSP0147	NSYCUSP0120
NSYCUX2K3P4UL	-	NSYCUSP0088	NSYCUSP0144	NSYCUSP0147	NSYCUSP0120
NSYCU3K3P4	NSYCUSP0071	-	NSYCUSP0099	NSYCUSP0105	NSYCUSP0128
NSYCUX3K3P4	-	NSYCUSP0089	NSYCUSP0099	NSYCUSP0105	NSYCUSP0128
NSYCU3K3P4UL	NSYCUSP0071	-	NSYCUSP0144	NSYCUSP0148	NSYCUSP0128
NSYCUX3K3P4UL	-	NSYCUSP0089	NSYCUSP0144	NSYCUSP0148	NSYCUSP0128
NSYCU4K3P4	NSYCUSP0071	-	NSYCUSP0099	NSYCUSP0105	NSYCUSP0128
NSYCUX4K3P4	-	NSYCUSP0089	NSYCUSP0099	NSYCUSP0105	NSYCUSP0128
NSYCU4K3P4UL	NSYCUSP0071	-	NSYCUSP0144	NSYCUSP0148	NSYCUSP0128
NSYCUX4K3P4UL	-	NSYCUSP0089	NSYCUSP0144	NSYCUSP0148	NSYCUSP0128
NSYCU6K3P4	-	-	NSYCUSP0099	-	-
NSYCU6K3P460	-	-	NSYCUSP0099	-	-
NSYCU8K3P4	-	-	NSYCUSP0099	-	-
NSYCU8K3P460	-	-	NSYCUSP0099	-	-
NSYCU10K3P4	-	-	NSYCUSP0099	-	-
NSYCU10K3P460	-	-	NSYCUSP0099	-	-
NSYCU15K3P4	-	-	NSYCUSP0099	-	-
NSYCU15K3P460	-	-	NSYCUSP0099	-	-

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Spare parts ClimaSys

	Cooling units: Roof mount				
	Evaporator battery	Evaporator fan (fan + capacitor)	Condenser battery	Condenser fan (fan + capacitor)	Compressor kit
References	References	References	References	References	References
NSYCU400R	NSYCUSP0008	NSYCUSP0047	NSYCUSP0023	NSYCUSP0043	NSYCUSP0064
NSYCUX400R	NSYCUSP0008	NSYCUSP0047	NSYCUSP0023	NSYCUSP0043	NSYCUSP0064
NSYCU400RUL	NSYCUSP0008	NSYCUSP0047	NSYCUSP0023	NSYCUSP0043	NSYCUSP0172
NSYCU800R	NSYCUSP0009	NSYCUSP0044	NSYCUSP0024	NSYCUSP0136	NSYCUSP0065
NSYCUX800R	NSYCUSP0009	NSYCUSP0044	NSYCUSP0024	NSYCUSP0136	NSYCUSP0065
NSYCU800RUL	NSYCUSP0009	NSYCUSP0044	NSYCUSP0024	NSYCUSP0136	NSYCUSP0065
NSYCU1K2R	NSYCUSP0010	NSYCUSP0044	NSYCUSP0025	NSYCUSP0049	NSYCUSP0065
NSYCUX1K2R	NSYCUSP0010	NSYCUSP0044	NSYCUSP0025	NSYCUSP0049	NSYCUSP0065
NSYCU1K2RUL	NSYCUSP0010	NSYCUSP0044	NSYCUSP0025	NSYCUSP0049	NSYCUSP0065
NSYCU1K5R	NSYCUSP0010	NSYCUSP0136	NSYCUSP0026	NSYCUSP0049	NSYCUSP0059
NSYCUX1K5R	NSYCUSP0010	NSYCUSP0136	NSYCUSP0026	NSYCUSP0049	NSYCUSP0059
NSYCU1K5RUL	NSYCUSP0010	NSYCUSP0136	NSYCUSP0026	NSYCUSP0049	NSYCUSP0059
NSYCU2K3P4R	NSYCUSP0011	NSYCUSP0136	NSYCUSP0027	NSYCUSP0049	NSYCUSP0061
NSYCUX2K3P4R	NSYCUSP0011	NSYCUSP0136	NSYCUSP0027	NSYCUSP0049	NSYCUSP0061
NSYCU2K3P4RUL	NSYCUSP0011	NSYCUSP0136	NSYCUSP0027	NSYCUSP0049	NSYCUSP0062
NSYCU2KR	NSYCUSP0011	NSYCUSP0136	NSYCUSP0027	NSYCUSP0049	NSYCUSP0060
NSYCUX2KR	NSYCUSP0011	NSYCUSP0136	NSYCUSP0027	NSYCUSP0049	NSYCUSP0060
NSYCU3K3P4R	NSYCUSP0012	NSYCUSP0136	NSYCUSP0028	NSYCUSP0051	NSYCUSP0062
NSYCUX3K3P4R	NSYCUSP0012	NSYCUSP0136	NSYCUSP0028	NSYCUSP0051	NSYCUSP0062
NSYCU3K3P4RUL	NSYCUSP0012	NSYCUSP0136	NSYCUSP0028	NSYCUSP0051	NSYCUSP0062
NSYCU4K3P4R	NSYCUSP0012	NSYCUSP0137	NSYCUSP0029	NSYCUSP0051	NSYCUSP0063
NSYCUX4K3P4R	NSYCUSP0012	NSYCUSP0137	NSYCUSP0029	NSYCUSP0051	NSYCUSP0063
NSYCU4K3P4RUL	NSYCUSP0012	NSYCUSP0137	NSYCUSP0029	NSYCUSP0051	NSYCUSP0063

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Spare parts ClimaSys

	Cooling units: Roof mount				
	Frontal cover RAL 7035 grey	Frontal cover stainless steel	Thermostat	Transformer	Mounting Kit (instruction + full seal + screws)
References	References	References	References	References	References
NSYCU400R	NSYCUSP0072	-	NSYCUSP0099	-	NSYCUSP0121
NSYCUX400R	-	NSYCUSP0090	NSYCUSP0099	-	NSYCUSP0121
NSYCU400RUL	NSYCUSP0072	-	NSYCUSP0144	-	NSYCUSP0121
NSYCU800R	NSYCUSP0073	-	NSYCUSP0099	-	NSYCUSP0122
NSYCUX800R	-	NSYCUSP0091	NSYCUSP0099	-	NSYCUSP0122
NSYCU800RUL	NSYCUSP0073	-	NSYCUSP0144	-	NSYCUSP0122
NSYCU1K2R	NSYCUSP0074	-	NSYCUSP0099	-	NSYCUSP0129
NSYCUX1K2R	-	NSYCUSP0092	NSYCUSP0099	-	NSYCUSP0129
NSYCU1K2RUL	NSYCUSP0074	-	NSYCUSP0144	-	NSYCUSP0129
NSYCU1K5R	NSYCUSP0074	-	NSYCUSP0099	-	NSYCUSP0129
NSYCUX1K5R	-	NSYCUSP0092	NSYCUSP0099	-	NSYCUSP0129
NSYCU1K5RUL	NSYCUSP0074	-	NSYCUSP0144	-	NSYCUSP0129
NSYCU2K3P4R	NSYCUSP0074	-	NSYCUSP0099	NSYCUSP0104	NSYCUSP0129
NSYCUX2K3P4R	-	NSYCUSP0092	NSYCUSP0099	NSYCUSP0104	NSYCUSP0129
NSYCU2K3P4RUL	NSYCUSP0074	-	NSYCUSP0144	NSYCUSP0147	NSYCUSP0129
NSYCU2KR	NSYCUSP0074	-	NSYCUSP0099	-	NSYCUSP0129
NSYCUX2KR	-	NSYCUSP0092	NSYCUSP0099	-	NSYCUSP0129
NSYCU3K3P4R	NSYCUSP0075	-	NSYCUSP0099	NSYCUSP0106	NSYCUSP0123
NSYCUX3K3P4R	-	NSYCUSP0093	NSYCUSP0099	NSYCUSP0106	NSYCUSP0123
NSYCU3K3P4RUL	NSYCUSP0075	-	NSYCUSP0144	NSYCUSP0148	NSYCUSP0123
NSYCU4K3P4R	NSYCUSP0075	-	NSYCUSP0099	NSYCUSP0105	NSYCUSP0123
NSYCUX4K3P4R	-	NSYCUSP0093	NSYCUSP0099	NSYCUSP0105	NSYCUSP0123
NSYCU4K3P4RUL	NSYCUSP0075	-	NSYCUSP0144	NSYCUSP0148	NSYCUSP0123

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Spare parts ClimaSys

	Cooling units: Heavy duty				
	Evaporator battery	Evaporator fan (fan + capacitor)	Condenser battery	Condenser fan (fan + capacitor)	Compressor kit
References	References	References	References	References	References
NSYCUHD400	NSYCUSP0002	NSYCUSP0042	NSYCUSP0158	NSYCUSP0042	NSYCUSP0055
NSYCUHD600	NSYCUSP0003	NSYCUSP0043	NSYCUSP0159	NSYCUSP0044	NSYCUSP0056
NSYCUHD800	NSYCUSP0004	NSYCUSP0043	NSYCUSP0160	NSYCUSP0044	NSYCUSP0057
NSYCUHD1K	NSYCUSP0004	NSYCUSP0043	NSYCUSP0161	NSYCUSP0044	NSYCUSP0057
NSYCUHD1K2P4	NSYCUSP0004	NSYCUSP0043	NSYCUSP0161	NSYCUSP0044	NSYCUSP0057
NSYCUHD1K6	NSYCUSP0006	NSYCUSP0044	NSYCUSP0162	NSYCUSP0138	NSYCUSP0059
NSYCUHD1K62P4	NSYCUSP0006	NSYCUSP0044	NSYCUSP0162	NSYCUSP0138	NSYCUSP0059
NSYCUHD2K3P4	NSYCUSP0006	NSYCUSP0136	NSYCUSP0163	NSYCUSP0138	NSYCUSP0061
NSYCUHD3K3P4	NSYCUSP0007	NSYCUSP0137	NSYCUSP0164	NSYCUSP0137	NSYCUSP0062
NSYCUHD4K3P4	NSYCUSP0007	NSYCUSP0137	NSYCUSP0165	NSYCUSP0137	NSYCUSP0063

	Cooling units: Heavy duty			
	Frontal cover RAL 7035 grey	Thermostat	Transformer	Mounting Kit (instruction + full seal + screws)
References	References	References	References	References
NSYCUHD400	NSYCUSP0167	NSYCUSP0100	-	NSYCUSP0153
NSYCUHD600	NSYCUSP0168	NSYCUSP0100	-	NSYCUSP0154
NSYCUHD800	NSYCUSP0169	NSYCUSP0100	-	NSYCUSP0155
NSYCUHD1K	NSYCUSP0169	NSYCUSP0100	-	NSYCUSP0155
NSYCUHD1K2P4	NSYCUSP0169	NSYCUSP0100	NSYCUSP0101	NSYCUSP0155
NSYCUHD1K6	NSYCUSP0170	NSYCUSP0100	-	NSYCUSP0156
NSYCUHD1K62P4	NSYCUSP0170	NSYCUSP0100	NSYCUSP0103	NSYCUSP0156
NSYCUHD2K3P4	NSYCUSP0170	NSYCUSP0100	NSYCUSP0104	NSYCUSP0156
NSYCUHD3K3P4	NSYCUSP0171	NSYCUSP0100	NSYCUSP0105	NSYCUSP0157
NSYCUHD4K3P4	NSYCUSP0171	NSYCUSP0100	NSYCUSP0105	NSYCUSP0157

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Spare parts ClimaSys

	Cooling units: Slim				
	Evaporator battery	Evaporator fan (fan + capacitor)	Condenser battery	Condenser fan (fan + capacitor)	Compressor kit
References	References	References	References	References	References
NSYCUS1K1UL	NSYCUSP0130	NSYCUSP0136	NSYCUSP0133	NSYCUSP0136	NSYCUSP0059
NSYCUSX1K1UL	NSYCUSP0130	NSYCUSP0136	NSYCUSP0133	NSYCUSP0136	NSYCUSP0059
NSYCUS1K12P4UL	NSYCUSP0130	NSYCUSP0136	NSYCUSP0133	NSYCUSP0136	NSYCUSP0059
NSYCUSX1K12P4UL	NSYCUSP0130	NSYCUSP0136	NSYCUSP0133	NSYCUSP0136	NSYCUSP0059
NSYCUS1K5UL	NSYCUSP0131	NSYCUSP0136	NSYCUSP0133	NSYCUSP0138	NSYCUSP0059
NSYCUSX1K5UL	NSYCUSP0131	NSYCUSP0136	NSYCUSP0133	NSYCUSP0138	NSYCUSP0059
NSYCUS1K52P4UL	NSYCUSP0131	NSYCUSP0136	NSYCUSP0133	NSYCUSP0138	NSYCUSP0059
NSYCUSX1K52P4UL	NSYCUSP0131	NSYCUSP0136	NSYCUSP0133	NSYCUSP0138	NSYCUSP0059
NSYCUS2KUL	NSYCUSP0131	NSYCUSP0136	NSYCUSP0134	NSYCUSP0138	NSYCUSP0139
NSYCUSX2KUL	NSYCUSP0131	NSYCUSP0136	NSYCUSP0134	NSYCUSP0138	NSYCUSP0139
NSYCUS2K3P4UL	NSYCUSP0131	NSYCUSP0136	NSYCUSP0134	NSYCUSP0138	NSYCUSP0062
NSYCUSX2K3P4UL	NSYCUSP0131	NSYCUSP0136	NSYCUSP0134	NSYCUSP0138	NSYCUSP0062
NSYCUS2K5UL	NSYCUSP0132	NSYCUSP0137	NSYCUSP0135	NSYCUSP0137	NSYCUSP0140
NSYCUSX2K5UL	NSYCUSP0132	NSYCUSP0137	NSYCUSP0135	NSYCUSP0137	NSYCUSP0140
NSYCUS2K53P4UL	NSYCUSP0132	NSYCUSP0137	NSYCUSP0135	NSYCUSP0137	NSYCUSP0062
NSYCUSX2K53P4UL	NSYCUSP0132	NSYCUSP0137	NSYCUSP0135	NSYCUSP0137	NSYCUSP0062
NSYCUS3K2UL	NSYCUSP0132	NSYCUSP0137	NSYCUSP0135	NSYCUSP0137	NSYCUSP0141
NSYCUSX3K2UL	NSYCUSP0132	NSYCUSP0137	NSYCUSP0135	NSYCUSP0137	NSYCUSP0141
NSYCUS3K23P4UL	NSYCUSP0132	NSYCUSP0137	NSYCUSP0135	NSYCUSP0137	NSYCUSP0063
NSYCUSX3K23P4UL	NSYCUSP0132	NSYCUSP0137	NSYCUSP0135	NSYCUSP0137	NSYCUSP0063

	Cooling units: Slim						
	Frontal cover RAL 7035 grey	Frontal cover stainless steel	Thermostat	Transformer	Mounting kit (instruction + full seal + screws)	Metal frame kit (frame + seal + screws)	Metal frame kit stainless steel (frame + seal + screws)
References	References	References	References	References	References	References	References
NSYCUS1K1UL	NSYCUSP0142	-	NSYCUSP0144	-	NSYCUSP0149	NSYCUSP0152	NSYCUSP0166
NSYCUSX1K1UL	-	NSYCUSP0150	NSYCUSP0144	-	NSYCUSP0149	NSYCUSP0152	NSYCUSP0166
NSYCUS1K12P4UL	NSYCUSP0142	-	NSYCUSP0144	NSYCUSP0145	NSYCUSP0149	NSYCUSP0152	NSYCUSP0166
NSYCUSX1K12P4UL	-	NSYCUSP0150	NSYCUSP0144	NSYCUSP0145	NSYCUSP0149	NSYCUSP0152	NSYCUSP0166
NSYCUS1K5UL	NSYCUSP0142	-	NSYCUSP0144	-	NSYCUSP0149	NSYCUSP0152	NSYCUSP0166
NSYCUSX1K5UL	-	NSYCUSP0150	NSYCUSP0144	-	NSYCUSP0149	NSYCUSP0152	NSYCUSP0166
NSYCUS1K52P4UL	NSYCUSP0142	-	NSYCUSP0144	NSYCUSP0146	NSYCUSP0149	NSYCUSP0152	NSYCUSP0166
NSYCUSX1K52P4UL	-	NSYCUSP0150	NSYCUSP0144	NSYCUSP0146	NSYCUSP0149	NSYCUSP0152	NSYCUSP0166
NSYCUS2KUL	NSYCUSP0142	-	NSYCUSP0144	-	NSYCUSP0149	NSYCUSP0152	NSYCUSP0166
NSYCUSX2KUL	-	NSYCUSP0150	NSYCUSP0144	-	NSYCUSP0149	NSYCUSP0152	NSYCUSP0166
NSYCUS2K3P4UL	NSYCUSP0142	-	NSYCUSP0144	NSYCUSP0147	NSYCUSP0149	NSYCUSP0152	NSYCUSP0166
NSYCUSX2K3P4UL	-	NSYCUSP0150	NSYCUSP0144	NSYCUSP0147	NSYCUSP0149	NSYCUSP0152	NSYCUSP0166
NSYCUS2K5UL	NSYCUSP0143	-	NSYCUSP0144	-	NSYCUSP0149	NSYCUSP0152	NSYCUSP0166
NSYCUSX2K5UL	-	NSYCUSP0151	NSYCUSP0144	-	NSYCUSP0149	NSYCUSP0152	NSYCUSP0166
NSYCUS2K53P4UL	NSYCUSP0143	-	NSYCUSP0144	NSYCUSP0148	NSYCUSP0149	NSYCUSP0152	NSYCUSP0166
NSYCUSX2K53P4UL	-	NSYCUSP0151	NSYCUSP0144	NSYCUSP0148	NSYCUSP0149	NSYCUSP0152	NSYCUSP0166
NSYCUS3K2UL	NSYCUSP0143	-	NSYCUSP0144	-	NSYCUSP0149	NSYCUSP0152	NSYCUSP0166
NSYCUSX3K2UL	-	NSYCUSP0151	NSYCUSP0144	-	NSYCUSP0149	NSYCUSP0152	NSYCUSP0166
NSYCUS3K23P4UL	NSYCUSP0143	-	NSYCUSP0144	NSYCUSP0148	NSYCUSP0149	NSYCUSP0152	NSYCUSP0166
NSYCUSX3K23P4UL	-	NSYCUSP0151	NSYCUSP0144	NSYCUSP0148	NSYCUSP0149	NSYCUSP0152	NSYCUSP0166

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Index of references

0	Page
01130	375,409
03583	378
04000	351
04008	351
04012	351
04013	351
04014	351
04018	351
04021	351
04024	351
04026	351
04029	351
04030	351
04031	350
04040	350
04041	350
04045	350
04046	350
04047	350
04052	350
04053	350
04054	350
04150	351
04192	343
04197	343
04229	375,409
04407	352
04408	352
04502	357,360,370,373,404,405
04503	357,360,370,373,404,405
04504	357,370,373,404,405
04505	357,360,370,373,404,405
04506	357,370,373,404,405
04512	360
04515	360
04516	359,372,374,407
04518	359,372,374,407
04525	359,372,374,407
04526	359,372,374,407
04528	359,372,374,407
04536	356,369,408
04538	356,369,408
04545	356,369,408
04546	356,369,408
04548	356,369,408
04550	356,359,369,372
04552	356,369
04560	355,358,368,371,406
04561	355,358,368,371,406
04562	355,358,368,371,406
04563	355,358,368,371,406
04564	355,358,368,371,406
04565	355,358,368,371,406
04566	355,358,368,371,406
04567	355,358,368,371
04568	355,358,368,371
04602	357,370,373,405
04603	357,370
04604	358,371
04605	358,371

0	Page
04607	358,371
04620	355,368,406
04621	355,368,406
04623	355,368
04624	368
04634	357,370,405
04635	357,370,373,374,405
04636	357,359,370,372,373, 374, 405,407
04637	359,372,407
04638	357,359,370,372
04640	356,369,408
04641	356,369,408
04642	357,359,370,372,373,374,407
04643	356,369
04645	359,372,407
04646	355,356,358,368
04651	370
04653	374
04656	360
04658	358,371
04659	358,371
04661	371
04663	371
04664	368,369
04666	371
04669	374
04671	368,369,371,372
04672	360
04678	349,371,372
04742	361
04743	351,361
04746	361
04751	361
04753	361
04759	375,409
04766	375,409
04767	375,409
04768	375,409
04769	375,409
04772	375,409
04773	375,409
04774	375,409
04775	375,409
04782	375,409
04783	375,409
04784	375,409
04785	375,409
04786	375,409
04787	375,409
04788	375,409
04794	375,409
04809	352
04901	378
04924	377
04943	378
04946	379
04951	379
04952	379
04955	378

0	Page
04956	378
06461	381
06540	377,410
06541	377
06543	377
06545	377
06555	377
06560	377
06561	377,410
06563	377,410
06567	377
06568	377
06570	377
06600	379
06601	379
06604	379
06605	379
06606	379
06607	379
08566	380
08881	63,66,284
08892	63,66,284
08895	63,66,284
08897	63,66,284
08898	63,66,284
08899	63,66,284
08911	381

1	Page
13934	162

A	Page
AF1CF34	265,271
AF1CF56	265,271
AF1CG4	271
AF1CG5	271
AF1CG6	271
AF1EA3	242,270
AF1EA4	242,270
AF1EA5	242,270
AF1EA6	242,270
AF1GC4	265
AF1GC5	265
AF1GC6	265
AF1VA410	270
AF1VA416	270
AF1VA512	270
AF1VA518	270
AF1VA612	251,270
AF1VA618	251,270
AF1VC820	251,270
AK2CA3	292
AK2CA6	292
AK2CD100	292
AK2CD125	292
AK2CD25	292
AK2CD37	292
AK2CD50	292
AK2CD75	292
AK2GA315	292

Index of references

A	Page
AK2GA33	292
AK2GA35	292
AK2GA39	292
AK2GA615	292
AK2GA65	292
AK2GA69	292
AK2GD10075	292
AK2GD12575	292
AK2GD2525	292
AK2GD2550	292
AK2GD3750	292
AK2GD3775	292
AK2GD5050	292
AK2GD5075	292
AK2GD7550	292
AK2GD7575	292
AK2LA39	291
AK2LD01	291
AK2LD02	291
AM1DL201	264
AM1EA200	264
AM1EC200	263
AM1PA0670	241
AM1PA1270	241
AM1PA3015	241
AM1PA3020	241
AM1PA3050	241
AM1PA3070	241
AM1PA4030	241
AM1PA6040	241
AM1PA6050	241
AM1PA6060	241
AM1PA6070	241
AM1PA7050	241
AM1PA8060	241
AM1PA9050	241
AM1PA9060	241
AM1PA9070	241
ATV340D30N4E	527
ATV340D37N4E	527
ATV340D45N4E	527
ATV340D55N4E	527
ATV340D75N4E	527
ATV630D11M3	527
ATV630D11N4	527
ATV630D15M3	527
ATV630D15N4	527
ATV630D18M3	527
ATV630D18N4	527
ATV630D22M3	527
ATV630D22N4	527
ATV630D30M3	527
ATV630D30N4	527
ATV630D37M3	527
ATV630D37N4	527
ATV630D45M3	527
ATV630D45N4	527
ATV630D55N4	527
ATV630D75N4	527
ATV630D90N4	527

A	Page
ATV630U07M3	527
ATV630U07N4	527
ATV630U15M3	527
ATV630U15N4	527
ATV630U22M3	527
ATV630U22N4	527
ATV630U30M3	527
ATV630U30N4	527
ATV630U40M3	527
ATV630U40N4	527
ATV630U55M3	527
ATV630U55N4	527
ATV630U75M3	527
ATV630U75N4	527
ATV930D11M3	527
ATV930D11N4	527
ATV930D15M3	527
ATV930D15N4	527
ATV930D18M3	527
ATV930D18N4	527
ATV930D22M3	527
ATV930D22N4	527
ATV930D30M3	527
ATV930D30N4	527
ATV930D37M3	527
ATV930D37N4	527
ATV930D45M3	527
ATV930D45N4	527
ATV930D55N4	527
ATV930D75N4	527
ATV930D90N4	527
ATV930U07M3	527
ATV930U07N4	527
ATV930U15M3	527
ATV930U15N4	527
ATV930U22M3	527
ATV930U22N4	527
ATV930U30M3	527
ATV930U30N4	527
ATV930U40M3	527
ATV930U40N4	527
ATV930U55M3	527
ATV930U55N4	527
ATV930U75M3	527
ATV930U75N4	527
AX2DL01	252
AX2DL02	252
AZ1CA04	242

C	Page
C1F265	396,398

D	Page
DX1AP52	252
DZ5CA005	295
DZ5CA007	295
DZ5CA010	295
DZ5CA015	295
DZ5CA025	295
DZ5CA042	295

D	Page
DZ5CA062	295
DZ5CA102	295
DZ5CA162	295
DZ5CA352	295
DZ5CA502	295
DZ5CE005	295
DZ5CE007	295
DZ5CE010	295
DZ5CE015	295
DZ5CE025	295
DZ5CE042	295
DZ5CE062	295
DZ5ME5	265,271
DZ5ME8	265,271
DZ5ME9	265,271
DZ5MF6	244
DZ5MF8	244
DZ5MS10	252
DZ6MZ121	244
DZ6MZ151	244
DZ6MZ181	244
DZ6MZ211	244

G	Page
GV2-L04	394
GV2-L05	394
GV2-L06	394,397
GV2-L07	394,397
GV2-L08	394,397
GV2-L10	394,397
GV2-L14	394,397
GV2-L16	394,397
GV2-L20	394,397
GV2-L21	394,397
GV2-L22	394,397
GV2-L32	394,397
GV2-P04	393
GV2-P05	393
GV2-P06	393,396
GV2-P07	393,396
GV2-P08	393,396
GV2-P10	393,396
GV2-P14	393,396
GV2-P16	393,396
GV2-P20	393,396
GV2-P21	393,396
GV2-P22	393,396
GV2-P32	393,396
GV3-L40	394,397
GV3-L50	394,397
GV3-L65	394,397
GV3-P40	393,396
GV3-P50	393,396
GV3-P65	393,396
GV7-RS100	393,396
GV7-RS150	393,396
GV7-RS220	393,396
GV7-RS40	393,396
GV7-RS50	393,396
GV7-RS80	393,396

Index of references

I	Page
IK10	191,227
IMT34000	163
IMT34001	163
IMT34002	163
IMT34003	163
IMT34005	163
IMT34007	163
IMT34009	163
IMT36150	63,70,130,167,169,286
IMT36151	275
IMT36152	275
IMT36153	275
IMT36154	275
IMT36155	275
IMT36156	275
IMT36157	275
IMT36158	275
IMT36159	275
IMT36160	275
IMT36161	275
IMT36162	275
IMT36163	275
IMT36164	275
IMT36165	275
IMT36166	275
IMT36167	275
IMT36168	275
IMT36169	275
IMT36170	275
IMT36171	275
IMT36172	63,68,167,285
IMT36173	63,68,167,285
IMT36179	63,69,167,168,286
IMT36180	63,69,167,168,286
IMT36181	63,69,167,168,286
IMT36182	63,69,167,168,286
IMT36183	63,69,167,168,286
IMT36184	63,69,167,168,286
IMT36185	63,69,167,168,286
IMT46026	290
IMT46033	290
IMT46035	290
IMT46036	290
IMT46064	290
IMT46071	290
IMT46073	290
IMT46074	290
IMT46101	290
IMT46118	290
IMT46149	290
IMT46156	290
IMT46157	290
IMT46158	290
IMT46221	290
IMT46222	290
IMT46223	290
IMT46224	290
IMT46231	290
IMT46232	290
IMT46233	290

I	Page
IMT46234	290
IMT46248	290
IMT46286	290
IMT46293	290
IMT46918	290
IMT46919	290
IMT46921	290
IMT46922	290
IMT46923	290
IMT46924	290
IMT46926	290
IMT46927	290
IMT46968	290
IMT46969	290
IMT46970	290
IMT47000	290
IMT47001	290
IMT47002	290
IMT47004	290
IP44	191
ISM71071	63,68,167,285
ISM71072	63,68,167,285
ISM71073	63,68,167,285
ISM71074	63,68,167,285
ISM71501	63,70,130,167,169,286
ISM71502	63,70,130,167,169,286
ISM71503	63,70,130,167,169,286
ISM71504	63,70,130,167,169,286
ISM71505	63,70,130,167,169,286
ISM71506	63,70,130,167,169,286

L	Page
LC1D09	393,394,396,397
LC1D115	393,395,396,398
LC1D150	393,395,396,398
LC1D18	393,394,396,397
LC1D25	393,394,396,397
LC1D32	393,394,396,397
LC1D40	393
LC1D50	393,395,396,398
LC1D50A	393,394,396,397
LC1D65	393,395,398
LC1D65A	394,396,397
LC1D80	393,395,396,398
LC1F185	393,395,396,398
LC1F225	393,395,396,398
LC1F265	393,395
LC1F330	395,398
LC1F500	395,398
LGY112510	350
LGY116013	350
LGY125014	350
LGY410028	350
LGY412548	350
LGY412560	350
LGY416048	350
LR9D5367	395,398
LR9D5369	395,398
LR9F5369	395,398
LR9F5371	395,398

L	Page
LR9F7375	395,398
LR9F7379	395,398
LRD04	394
LRD05	394
LRD06	394
LRD07	394
LRD08	394
LRD10	394
LRD12	394
LRD14	394
LRD16	394
LRD21	394
LRD22	394
LRD32	394
LRD3355	395,398
LRD3357	395,398
LRD3359	395,398
LRD3363	395,398
LRD340	394
LRD350	394
LRD365	394

N	Page
NS80H-MA	395,398
NSX100MA	395,398
NSX160MA	395,398
NSX250MA	395,398
NSX4001.3-M	395,398
NSX6301.3-M	395,398
NSY17990	566
NSY17991	566
NSY17992	566
NSY17996	566
NSY17997	566
NSY17998	566
NSY1TH	259,514
NSY2SP124	18,20,88,90,93
NSY2SP125	20,90,93
NSY2SP126	18,20,88,90,93
NSY2SP128	20,90,93
NSY2SP144	18,20,88,90,93
NSY2SP145	20,90,93
NSY2SP146	20,90,93
NSY2SP148	20,90,93
NSY2SP164	20,90,93
NSY2SP165	20,90,93
NSY2SP166	18,20,88,90,93
NSY2SP168	18,20,88,90,93
NSY2SP184	18,20,88,90,93,341
NSY2SP185	18,20,88,90,93,341
NSY2SP186	18,20,88,90,93,341
NSY2SP188	18,20,88,90,93
NSY2SP204	18,21,88,91,93,341
NSY2SP205	18,21,88,91,93,341,380
NSY2SP206	18,21,88,91,93,341,380,413
NSY2SP208	18,21,88,91,93,341,380,413
NSY2SP224	21,91,93
NSY2SP225	21,91,93
NSY2SP226	18,21,88,91,93,341
NSY2SP228	18,21,88,91,93

Index of references

N	Page
NSY2SPHD124	422
NSY2SPHD126	422
NSY2SPHD164	422
NSY2SPHD166	422
NSY2SPHD204	422
NSY2SPI126	93
NSY2SPI185	93
NSY2SPI186	93
NSY2SPI188	93
NSY2SPI204	93
NSY2SPI205	93
NSY2SPI206	93
NSY2SPI208	93
NSY2SPI226	93
NSY2SPI228	93
NSY2SPIHD124	422
NSY2SPIHD126	422
NSY2SPIHD164	422
NSY2SPIHD166	422
NSY2SPIHD204	422
NSY2SPX184	23,152
NSY2SPX204	23,152
NSY2SPX205	23,152
NSY2SPX206	23,152
NSY5G2SP205	439
NSY5G2SP208	439
NSY6G2SP204	433
NSY6G2SP206	433
NSY6G2SP208	433
NSYAC1080	213
NSYAC1120	215
NSYAC280	191
NSYAC320	213
NSYAC360	191,215
NSYAC560	213
NSYAC600	191,215
NSYAC840	213,215
NSYADC16	335,338
NSYADC18	335,338
NSYADG20M	638
NSYADG2M	638
NSYADG3M	638
NSYADG5M	638
NSYADR100	262
NSYADR120	262
NSYADR200	264
NSYADR200D	264
NSYADR60	262
NSYADR80	262
NSYAEBFZ	191,213
NSYAECPFLA10	63,64,280
NSYAECPFLA25	63,64,280
NSYAECPFLA33	63,64,280
NSYAECPFLA7	63,64,280
NSYAECPFLACA14	284
NSYAECPFLACA18	284
NSYAECPFLACA20	284
NSYAECPFLACA30	284
NSYAECPFLAP	284
NSYAECPFLBP	63,65,109,281,317
NSYAECPFLT25	63,65,109,281,317
NSYAECPFLT35	63,65,109,281,317
NSYAECPFLT7	63,65,109,281,317
NSYAECPKFL10	63,66,281
NSYAECPKFL11	63,66,281
NSYAECPKFL7A	63,66,281
NSYAEDDINS3D	58
NSYAEDH120S3D	60,636,638
NSYAEDH120S3HD	646
NSYAEDH180S3D	60,636,638
NSYAEDH20TB	164
NSYAEDH40TB	164
NSYAEDHPLM	643
NSYAEDHPLM108	643
NSYAEDHPLM3025	643
NSYAEDHPLM32	643
NSYAEDHSB	37,40
NSYAEDKTB	162
NSYAEDL1242K31	443,447
NSYAEDL1242K33	434,443,447
NSYAEDL1242S3D	57
NSYAEDL1332S3D	57
NSYAEDL1344S3D	57
NSYAEDL2124S3D	57
NSYAEDL2131S3D	57
NSYAEDL2132S3D	57
NSYAEDL2133S3D	57
NSYAEDL2241S3D	57
NSYAEDL2244S3D	57
NSYAEDL2314S3D	57
NSYAEDL2322S3D	57
NSYAEDL2331S3D	57
NSYAEDL2432S3D	57
NSYAEDL2433S3D	57
NSYAEDL3113S3D	57
NSYAEDL3123S3D	57
NSYAEDL3131AS3D	57,636
NSYAEDL3132S3D	57
NSYAEDL3432S3D	57
NSYAEDL3524S3D	57
NSYAEDL405K31	443,447
NSYAEDL405K33	434,443,447
NSYAEDL405S3D	57
NSYAEDL421S3D	57
NSYAEDL4322S3D	57
NSYAEDL4324S3D	57
NSYAEDL455K31	443,447
NSYAEDL455K33	434,443,447
NSYAEDL455S3D	57
NSYAEDL5124S3D	57
NSYAEDL520S3D	57
NSYAEDL601S3D	57
NSYAEDL610S3D	57
NSYAEDL705S3D	57
NSYAEDLB3MS3D	58
NSYAEDLB3S3D	58
NSYAEDLB5S3D	58
NSYAEDLEDF13K31	443,447
NSYAEDLEDF13K33	434,443,447
NSYAEDLEDF13S3D	59
NSYAEDLEDF14K31	443,447
NSYAEDLEDF14K33	434,443,447
NSYAEDLEDF14S3D	59
NSYAEDLEDF9K31	443,447
NSYAEDLEDF9K33	434,443,447
NSYAEDLEDF9S3D	59
NSYAEDLMETS3D	58
NSYAEDLPADS3D	59
NSYAEDLPADS3DHD	422
NSYAEDLPADS3DK3	443,447
NSYAEDLPSS3D	59
NSYAEDLS3DC	637
NSYAEDLS3DKDB3	57,636,637,645
NSYAEDLS3DRLN	636
NSYAEDLS3HDRL	646
NSYAEDLS3HFDB3	644
NSYAEDLS6S3D	58
NSYAEDLS7S3D	58
NSYAEDLS8S3D	58
NSYAEDLSDS3D	58
NSYAEDLT6S3D	58
NSYAEDLT8S3D	58
NSYAEDPHD	645
NSYAEDPLA001	642
NSYAEDPLA002G	642
NSYAEDPLA003G	642
NSYAEDPLA004	642
NSYAEDPLA005	642
NSYAEDPLM108	643
NSYAEDRS3DPA6	60,302
NSYAEDRSCST	60,143,302
NSYAEDS20TB	162
NSYAEDS40TB	162
NSYAEDS60TB	162
NSYAEDSB520TB	162
NSYAEDSBSB	37,40
NSYAEDST820TB	162
NSYAEDSTSB	37,40
NSYAEFAHLBSC	13,14,47,51
NSYAEFP315S3D	50,53
NSYAEFP32S3D	50,53
NSYAEFP42S3D	50,53
NSYAEFPF40SC	51
NSYAEFPFPTD	528
NSYAEFPFS3DW100	49,52
NSYAEFPFS3DW120	49,52
NSYAEFPFS3DW20	49,52
NSYAEFPFS3DW30	49,52
NSYAEFPFS3DW40	49,52
NSYAEFPFS3DW50	49,52
NSYAEFPFS3DW60	49,52
NSYAEFPFS3DW80	49,52
NSYAEFPFSB	37,40,129
NSYAEFPFSBX	128
NSYAEFPFSC	13,14,47,51
NSYAEFPFSC2	51
NSYAEFPFXSC	14,47,51,422
NSYAEFTB	164
NSYAELYTCRG8	56,445,448
NSYAELYTCRXG8	144

Index of references

N	Page
NSYAELZ	215
NSYAEPZA	213
NSYAEPZM	191
NSYAEUBU41SC	55
NSYAEUBU61SC	55
NSYAEUBUSC	55
NSYAMCSF	12,46,244,271
NSYAMFESTB	166
NSYAMFET154TB	166
NSYAMFET204TB	166
NSYAMFET304TB	166
NSYAMFSB	37,40,129
NSYAMFSTB	165
NSYAMPA1916TB	160,164
NSYAMPA2419TB	160,164
NSYAMPA2924TB	160,164
NSYAMPA3429TB	160,164
NSYAMPM1916TB	160,164
NSYAMPM2419TB	160,164
NSYAMPM2924TB	160,164
NSYAMPM3429TB	160,164
NSYAMRD11155TB	165
NSYAMRD11357TB	165
NSYAMRD15357SB	36,39,128
NSYAMRD16155TB	165
NSYAMRD16357TB	165
NSYAMRD19155TB	165
NSYAMRD19357TB	165
NSYAMRD2030	15
NSYAMRD20357SB	36,39,128
NSYAMRD24155TB	165
NSYAMRD243515TB	165
NSYAMRD24357TB	165
NSYAMRD2530	15
NSYAMRD2540	15
NSYAMRD2550	15
NSYAMRD29155TB	165
NSYAMRD293515TB	165
NSYAMRD29357TB	165
NSYAMRD3030	15
NSYAMRD30357SB	36,39,128
NSYAMRD3040	15
NSYAMRD3050	15
NSYAMRD34155TB	165
NSYAMRD343515TB	165
NSYAMRD34357TB	165
NSYAMRD36	15
NSYAMRD40357SB	36,39,128
NSYAMRD43	15
NSYAMRD48	15
NSYAMRD50357SB	36,39
NSYAMRD54	15
NSYAMRD60357SB	36,39
NSYAMRD64	15
NSYAMRD80357SB	36,39
NSYAPFWM	49
NSYAPLD812	229
NSYAPLD85	229
NSYAPLD86	229
NSYAPLD88	229

N	Page
NSYAS400	344
NSYAS500	344,371,372
NSYAS600	344,371,372,407
NSYAS800	344,371,372,407
NSYAS800L	371,372
NSYASPLA001	642
NSYASPLA002	642
NSYASPLA003	642
NSYASPLM	643
NSYASPLM32	643
NSYATM27	176
NSYATP24DTM	332
NSYATP6DTM	332
NSYATP72G	332
NSYATP72M	332
NSYATPUND	332
NSYAUPG1G	199,211,229,306
NSYAUPG5G	199,211,229,306
NSYAUPGS	199,211,229,306
NSYAVD1U1450	569
NSYAVD1U480	569
NSYAVD1U550M48	569
NSYAVD1U970	569
NSYAVG2U300	569
NSYAZ3PLA	213
NSYAZ4PLA	213
NSYB204	263,270
NSYB404	263,270
NSYB406	263,270
NSYBANPLA53	225
NSYBANPLA54	225
NSYBANPLA56	225
NSYBANPLA73	225
NSYBANPLA74	225
NSYBANPLA76	225
NSYBBH29	353
NSYBBH29C	353
NSYBBH29D	353
NSYBBH29DPC	353
NSYBBH29P	353
NSYBBH30	353
NSYBBH30D	353
NSYBBH31	353
NSYBBH31D	353
NSYBBH32	353
NSYBBH32D	353
NSYBCE10	105
NSYBCE12	105
NSYBCE16	105
NSYBCE4	105
NSYBCE6	105
NSYBCE8	105
NSYBCME	151,197,228
NSYBCPL	197
NSYBE27G	179,185
NSYBF4B3M	412
NSYBF4B4M	412
NSYBF4B5M	412
NSYBF4B6M	412
NSYBF4B8M	412

N	Page
NSYBF4B9M	412
NSYBGN1054HD	221,420
NSYBGN1074HD	221,420
NSYBGN12124HD	221,420
NSYBGN12126HD	221,420
NSYBGN1254HD	221,420
NSYBGN1274HD	221,420
NSYBGN1276HD	221,420
NSYBGN15124HD	221,420
NSYBGN15126HD	221,420
NSYBGN1574HD	221,420
NSYBGN1576HD	221,420
NSYBGN2074HD	221,420
NSYBGN774HD	221,420
NSYBGN776HD	221,420
NSYBHNT500	349
NSYBHNT600	349
NSYBHNT800	349
NSYBHNW600	349
NSYBHNW800	349
NSYBHS500	345,369
NSYBHS600	345,369,406,408
NSYBHS800	345,369,406,408
NSYBICRN	638,644
NSYBL27	179
NSYBLKH123	115
NSYBN204	263,270
NSYBN206	263,270
NSYBN404	263,270
NSYBN406	263,270
NSYBN408	263,270
NSYBN606	263,270
NSYBN608	263,270
NSYBN610	263,270
NSYBP126	20,90
NSYBP128	20,90
NSYBP146	20,90
NSYBP148	20,90
NSYBP166	20,90
NSYBP168	20,90
NSYBP1810	20,90
NSYBP1812	20,90
NSYBP184	20,90
NSYBP186	20,90
NSYBP188	20,90
NSYBP2010	21,91
NSYBP2012	21,91
NSYBP2016	21,91
NSYBP203	21,91,414
NSYBP204	21,91,414
NSYBP206	21,91,413
NSYBP207	639
NSYBP208	21,91,413
NSYBP2210	21,91
NSYBP2212	21,91
NSYBP224	21,91
NSYBP226	21,91
NSYBP228	21,91
NSYBPA7032	306
NSYBPA7035	306

Index of references

N	Page
NSYBPC3	291
NSYBPC5	291
NSYBPCH1016	353
NSYBPCH1050	353
NSYBPCH5120	353
NSYBPCH516	353
NSYBPCH550	353
NSYBPHD12122D	647
NSYBPHD126	647
NSYBPHD128	647
NSYBPHD1612	647
NSYBPHD166	647
NSYBPHD168	647
NSYBPHD208	647
NSYBPI1810	94
NSYBPI2010	94
NSYBPI206	94
NSYBPI208	94
NSYBPI2210	94
NSYBPI228	94
NSYBPLDNG	229
NSYBRF12PLAG	29,219
NSYBRF17PLAG	29,219
NSYBRF21PLAG	29,219
NSYBRF26PLAG	29,219
NSYBRF8PLAG	29,219
NSYBRP11PLAG	29,219
NSYBRP16PLAG	29,219
NSYBRP20PLAG	29,219
NSYBRP25PLAG	29,219
NSYBRP7PLAG	29,219
NSYBS400	342
NSYBS500	342
NSYBS600	342
NSYBS800	342
NSYBSA	345,355,356,358,359,368, 369,371,372,374,406,407,408
NSYBSA70	349
NSYBSC630	342
NSYBTACRNG100	638
NSYBTACRNG120	638
NSYBTACRNG140	638
NSYBTACRNG80	638
NSYBTAS3D100	636,637,645
NSYBTAS3D120	636,637
NSYBTAS3D140	636
NSYBTAS3D60	636,637,645
NSYBTAS3D65	636
NSYBTAS3D70	636,637,645
NSYBTAS3D80	636,637,645
NSYBTAS3D90	636
NSYBTE630TBT	354
NSYBU108PLMG	25,198
NSYBUPLMG	25,198
NSYBVS400	344
NSYBVS500	344,371,372
NSYBVS600	344,371,372,407
NSYBVS800	344,371,372,407
NSYBVS800L	371,372
NSYCAAPV	555,560

N	Page
NSYCAAPVHD	219,425,562
NSYCAC228RMF	575
NSYCAEFPF	51
NSYCAF108	568
NSYCAF125	560
NSYCAF125DG	549,554
NSYCAF125G3DG	549,554
NSYCAF125L55	561,567
NSYCAF125M	560
NSYCAF125O	560
NSYCAF125T	560
NSYCAF190	425,562
NSYCAF223	560
NSYCAF223DG	549,554
NSYCAF223G3DG	549,554
NSYCAF223L55	561,567
NSYCAF223M	560
NSYCAF223O	560
NSYCAF223T	425,560,562
NSYCAF228R	575
NSYCAF291	560
NSYCAF291DG	549,554
NSYCAF291G3DG	549,554
NSYCAF291L55	561,567
NSYCAF291M	560
NSYCAF291O	560
NSYCAF291T	560
NSYCAF92	560
NSYCAF92DG	549,554
NSYCAF92M	560
NSYCAG104X95LM	574
NSYCAG108LP	568
NSYCAG110X46M	574
NSYCAG114LPF	569
NSYCAG125BPC	549,554
NSYCAG125DG	547,554
NSYCAG125DGC	549,554
NSYCAG125LPC	560
NSYCAG125LPF	560,561,567
NSYCAG12LPH1	162,575
NSYCAG12LPH2	162,575
NSYCAG130X110LM	574
NSYCAG170X190LM	574
NSYCAG180X62M	574
NSYCAG19LP	575
NSYCAG216X62M	574
NSYCAG223BPC	549,554
NSYCAG223DG	547,554
NSYCAG223DGC	549,554
NSYCAG223LFHD	425,562
NSYCAG223LPC	560
NSYCAG223LPF	560,561,567
NSYCAG291BPC	549,554
NSYCAG291DG	547,554
NSYCAG291DGC	549,554
NSYCAG291LPC	560
NSYCAG291LPF	560,561,567
NSYCAG317X120M	574
NSYCAG317X91M	574
NSYCAG33LP	575

N	Page
NSYCAG35LP	199,575
NSYCAG38LP	575
NSYCAG417X120M	574
NSYCAG45LP	575
NSYCAG78LPF	569
NSYCAG92BPC	549,554
NSYCAG92DG	547,554
NSYCAG92DGC	549,554
NSYCAG92LPC	560
NSYCAG92LPF	560
NSYCAP125LE	566,572
NSYCAP125LXF	561,566,572
NSYCAP125LZF	561,566,572
NSYCAP223LE	566,572
NSYCAP223LXF	561,566,572
NSYCAP223LZF	561,566,572
NSYCAP291LE	566,572
NSYCAP291LXF	561,566,572
NSYCAP291LZF	561,566,572
NSYCBCMPLAG	218
NSYCBXHCRN	143
NSYCCA100MFST	547,553
NSYCCA150MFST	547,553
NSYCCA200MFST	547,553
NSYCCA300MFST	547,553
NSYCCA400MFST	547,553
NSYCCA500MFST	547,553
NSYCCA50MFST	547,553
NSYCCABLK	549,555
NSYCCAFSDUST	549,555
NSYCCARPM	549,555
NSYCCASTE	615
NSYCCFSBRKIT125	548,553
NSYCCFSBRKIT223	548,553
NSYCCFSBRKIT291	548,553
NSYCCFSBRKIT92	548,553
NSYCCOFR55	547,552
NSYCCOFSEM8U1	547,552
NSYCCOFSEM8U2	547,552
NSYCCOFST30V	547,552
NSYCCOFST90250V	547,552
NSYCCOHY120VID	613,615
NSYCCOHY230VID	613,615
NSYCCOHY30VID	613,615
NSYCCOHYT120VID	613,615
NSYCCOHYT230VID	613,615
NSYCCOHYT30VID	613,615
NSYCCOTH120VID	613,615
NSYCCOTH230VID	613,615
NSYCCOTH30VID	613,615
NSYCCOTHC	612,614
NSYCCOTHCF	612,614
NSYCCOTHD	612,614
NSYCCOTHDF	612,614
NSYCCOTHI	612,614
NSYCCOTHIF	612,614
NSYCCOTHO	612,614
NSYCCOTHOF	612,614
NSYCDL	293
NSYCDP36	113

Index of references

N	Page
NSYCDP38	113
NSYCDRB	293
NSYCDS	293
NSYCEA14E	648
NSYCEA22E	577,648
NSYCEA35W230VL	582
NSYCEA35W230VLE	582
NSYCEA36	577,582,648
NSYCEA50	577,582,648
NSYCEA70W230VL	582
NSYCEA80	577,582,648
NSYCEARTFIT36	582
NSYCEARTFIT80	582
NSYCEFILS	461
NSYCEJ	105
NSYCEJD	282
NSYCEJD11	282
NSYCEJD13	282
NSYCEJD16	282
NSYCEJD18	282
NSYCEJD20	282
NSYCEJD22	282
NSYCEJD24	282
NSYCEJD26	282
NSYCEJD28	282
NSYCEJD3	282
NSYCEJD30	282
NSYCEJD5	282
NSYCEJD7	282
NSYCEJD9	282
NSYCEJDL0	283
NSYCEJDL12	283
NSYCEJDL13	283
NSYCEJDL14	283
NSYCEJDL15	283
NSYCEJDL16	283
NSYCEJDL17	283
NSYCEJDL18	283
NSYCEJDL19	283
NSYCEJDL20	283
NSYCEJDL21	283
NSYCEJDS0	283
NSYCEJDS10	283
NSYCEJDS11	283
NSYCEJDS2	283
NSYCEJDS3	283
NSYCEJDS4	283
NSYCEJDS5	283
NSYCEJDS6	283
NSYCEJDS7	283
NSYCEJDS8	283
NSYCEJDS9	283
NSYCEK	105
NSYCEP	305
NSYCEPLMAG	25,192
NSYCEPLMBG	25,192
NSYCEPLMCG	25,192
NSYCEW10K	580,582,648,649
NSYCEW10K2P4	581,582,648,649
NSYCEW15K	581,582,648,649
NSYCEW15K2P4	581,582,648,649
NSYCEW1K	579,582,648,649
NSYCEW1K8	579,582,648,649
NSYCEW1K8UL	579,582,648,649
NSYCEW1KUL	579,582,648,649
NSYCEW2100W230VL	582
NSYCEW2K5	579,582,648,649
NSYCEW2K5R	581,582,648,649
NSYCEW2K5UL	579,582,648,649
NSYCEW3150W230VL	582
NSYCEW3K5	579,582,648,649
NSYCEW3K5UL	579,582,648,649
NSYCEW4K5	579,582,648,649
NSYCEW4K5UL	579,582,648,649
NSYCEW6K	580,582,648,649
NSYCEW6K2P4	580,582,648,649
NSYCEW6KUL	580,582,648,649
NSYCEWRTFIT2K5	582
NSYCEWRTFIT3K5	582
NSYCEWX10K	580,582,648,649
NSYCEWX10K2P4	581,582,648,649
NSYCEWX15K	581,582,648,649
NSYCEWX15K2P4	581,582,648,649
NSYCEWX1K	579,582,648,649
NSYCEWX1K8	579,582,648,649
NSYCEWX1K8UL	579,582,648,649
NSYCEWX1KUL	579,582,648,649
NSYCEWX2K5	579,582,648,649
NSYCEWX2K5UL	579,582,648,649
NSYCEWX3K5	579,582,648,649
NSYCEWX3K5UL	579,582,648,649
NSYCEWX4K5	579,582,648,649
NSYCEWX4K5UL	579,582,648,649
NSYCEWX6K	580,582,648,649
NSYCEWX6K2P4	580,582,648,649
NSYCEWX6KUL	580,582,648,649
NSYCFP100	288
NSYCFP60	288
NSYCFP80	288
NSYCFS126	288
NSYCFS128	288
NSYCFS96	288
NSYCFS98	288
NSYCGHF12	478
NSYCGHF16	478
NSYCGHF20	478
NSYCGHF25	478
NSYCGHF32	478
NSYCGHF40	478
NSYCGSP16	63,70,130,167,170,287
NSYCGSP20	63,70,130,167,170,287
NSYCGSP25	63,70,130,167,170,287
NSYCGSP32	63,70,130,167,170,287
NSYCGSP40	63,70,130,167,170,287
NSYCGX12	63,71,131,287
NSYCGX12H	63,71,131,287
NSYCGX16	63,71,131,287
NSYCGX16H	63,71,131,287
NSYCGX20	63,71,131,287
NSYCGX20H	63,71,131,287
NSYCGX25	63,71,131,287
NSYCGX25H	63,71,131,287
NSYCGX32	63,71,131,287
NSYCGX32H	63,71,131,287
NSYCGX40	63,71,131,287
NSYCGX40H	63,71,131,287
NSYCL1242ECSX	143
NSYCL27L405	178
NSYCL27M	178
NSYCL405CSX	143
NSYCL610CSX	143
NSYCMACS50	496
NSYCMACS80	496
NSYCMBPT	494
NSYCMT2560110	494
NSYCMT5005	492,495
NSYCMT5010	492,495
NSYCMT5015	492,495
NSYCMT5020	492,495
NSYCMT8005	492,495
NSYCMT8010	492,495
NSYCMT8015	492,495
NSYCMT8020	492,495
NSYCMUCC50	492,496
NSYCMUCC80	492,496
NSYCMUCP50	492,496
NSYCMUCP80	492,496
NSYCMUCPAD87	496
NSYCMUCR50	492,496
NSYCMUCR80	492,496
NSYCMUIA50	492,495
NSYCMUIA80	492,495
NSYCMUMA50	492,495
NSYCMUMA80	492,495
NSYCMUMC50	492,495
NSYCMUMC80	492,495
NSYCMUMR50	492,495
NSYCMUMR80	492,495
NSYCMUTC50	492,496
NSYCMUTC80	492,496
NSYCN20	263,313
NSYCN40	263,313
NSYCN9M625	101,269,468
NSYCNFM6	270
NSYCNFM8	270
NSYCNM6	251,270
NSYCNM8	251,270
NSYCNOH123	115
NSYCNT20	263,313
NSYCNT40	263,313
NSYCOCN80	50,53
NSYCOCNS1400	50,53,142,193,476
NSYCOCNS1800	50,53,142,193,476
NSYCPT17	291
NSYCPT29	291
NSYCPT37	291
NSYCPT50	291
NSYCPTS17	291
NSYCPTS29	291
NSYCPTS37	291

Index of references

N	Page
NSYCPTS50	291
NSYCR100WU1	611
NSYCR100WU1C	610
NSYCR100WU2	611
NSYCR100WU2C	610
NSYCR100WU3	611
NSYCR100WU3C	610
NSYCR10WU1	611
NSYCR10WU1C	610
NSYCR10WU2	611
NSYCR10WU2C	610
NSYCR150WU1	611
NSYCR150WU2	611
NSYCR150WU2C	610
NSYCR150WU3	611
NSYCR170W230VVC	610
NSYCR20WU1	611
NSYCR20WU1C	610
NSYCR20WU2	611
NSYCR20WU2C	610
NSYCR20WU3	611
NSYCR250W115VV	611
NSYCR250W230VV	611
NSYCR400W115VV	611
NSYCR400W230VV	611
NSYCR50WU1C	610
NSYCR50WU2C	610
NSYCR50WU3C	610
NSYCR55WU1	611
NSYCR55WU2	611
NSYCR55WU3	611
NSYCRAF	611
NSYCRAFD	611
NSYCRNCGPSTDSB	638
NSYCRNGSDR	12,46,240,241,243
NSYCRP1W120VTVC	611
NSYCRP1W230VTVC	611
NSYCRS100W120V	607
NSYCRS100W240V	607
NSYCRS10W120V	607
NSYCRS10W240V	607
NSYCRS200W115V	611
NSYCRS200W120V	607
NSYCRS200W230V	611
NSYCRS200W240V	607
NSYCRS25W120V	607
NSYCRS25W240V	607
NSYCRS50W120V	607
NSYCRS50W240V	607
NSYCS200PLM	25,198
NSYCS300PLM	25,198
NSYCS400PLM	25,198
NSYCS500PLM	25,198
NSYCS600PLM	25,198
NSYCS800PLM	25,198
NSYCSH126	334
NSYCSH128	334
NSYCSH146	334
NSYCSH148	334
NSYCSH166	334
NSYCSH168	334
NSYCSH186	334,335
NSYCSH188	334
NSYCSH206	334
NSYCSH208	334
NSYCSHB1410	334
NSYCSHB1412	334
NSYCSHB1610	334
NSYCSHB1612	334
NSYCSHB1810	334,335
NSYCSHB1812	334,335
NSYCSHB2010	334
NSYCSHB2012	334
NSYCSP	94
NSYCSP6G	434
NSYCSSF	639
NSYCSSFHD	647
NSYCTL300DLAG	201
NSYCTL300DLM	331
NSYCTL400DLAG	201
NSYCTL400DLM	331
NSYCTL500DLAG	201
NSYCTL500DLM	331
NSYCTL500DLP2	224,234
NSYCTL500DLPG	224,234
NSYCTL600DLAG	201
NSYCTL600DLM	331
NSYCTL750DLP2	224,234
NSYCTL750DLPG	224,234
NSYCTL800DLAG	201
NSYCTL800DLM	331
NSYCU1050W230VR	601
NSYCU10K3P4	593,600,651,653
NSYCU10K3P460	593,600,651,653
NSYCU1460W230VR	601
NSYCU15K3P4	593,600,651,653
NSYCU15K3P460	593,600,651,653
NSYCU1650W230VL	601
NSYCU1650W230VR	601
NSYCU1800W400VL	601
NSYCU1K	591,600,601,650,652
NSYCU1K2	591,600,650,652
NSYCU1K22P4	591,600,650,652
NSYCU1K2P4	591,600,650,652
NSYCU1K2P4UL	591,600,650,652
NSYCU1K2R	594,600,654,655
NSYCU1K2RUL	594,600,654,655
NSYCU1K2UL	591,600,650,652
NSYCU1K5R	595,600,654,655
NSYCU1K5RUL	595,600,654,655
NSYCU1K6	591,600,650,652
NSYCU1K62P4	591,600,650,652
NSYCU1K62P4UL	591,600,650,652
NSYCU1K6UL	591,600,650,652
NSYCU1KUL	591,600,650,652
NSYCU2000W400VR	601
NSYCU240W230VL	601
NSYCU2450W400VR	601
NSYCU2500W400VL	601
NSYCU2K	591,600,651,653
NSYCU2K3P4	592,600,651,653
NSYCU2K3P4R	595,600,654,655
NSYCU2K3P4RUL	595,600,654,655
NSYCU2K3P4UL	592,600,651,653
NSYCU2KR	595,600,654,655
NSYCU2KUL	591,600,651,653
NSYCU300H	590,600,602,650,652
NSYCU3100W400VR	601
NSYCU370W230VL	601
NSYCU3K3P4	592,600,651,653
NSYCU3K3P4R	595,600,654,655
NSYCU3K3P4RUL	595,600,654,655
NSYCU3K3P4UL	592,600,651,653
NSYCU400	590,600,650,652
NSYCU4000W400VL	601
NSYCU400R	594,600,654,655
NSYCU400RUL	594,600,654,655
NSYCU400UL	590,600,650,652
NSYCU4K3P4	592,600,651,653
NSYCU4K3P4R	595,600,654,655
NSYCU4K3P4RUL	595,600,654,655
NSYCU4K3P4UL	592,600,651,653
NSYCU600	590,600,650,652
NSYCU600UL	590,600,650,652
NSYCU6K3P4	592,600,651,653
NSYCU6K3P460	593,600,651,653
NSYCU760W230VL	601
NSYCU760W230VR	601
NSYCU800	590,600,650,652
NSYCU800R	594,600,654,655
NSYCU800RUL	594,600,654,655
NSYCU800UL	590,600,650,652
NSYCU8K3P4	593,600,651,653
NSYCU8K3P460	593,600,651,653
NSYCUB1100W230S	601
NSYCUB1100W400S	601
NSYCUB1500W230S	601
NSYCUB1500W400S	601
NSYCUB2200W230S	601
NSYCUB2200W400S	601
NSYCUB2700W230S	601
NSYCUB2700W400S	601
NSYCUCN1K2T2KHD	601
NSYCUCN3KT4KHD	601
NSYCUCN400HD	601
NSYCUCN600HD	601
NSYCUCN800T1KHD	601
NSYCUD1K1T1K5	601
NSYCUD1K2T2K	601
NSYCUD3KT4K	601
NSYCUD400	601
NSYCUD600	601
NSYCUD800T1K	601
NSYCUE1100W230L	601
NSYCUE1400W230L	601
NSYCUE1400W230R	601
NSYCUE1400W400L	601
NSYCUE1800W400L	601
NSYCUE1800W400R	601
NSYCUF15K	601

Index of references

N	Page
NSYCUF1K1T2KS	601
NSYCUF1K2T2KR	601
NSYCUF1KT2K	601
NSYCUF3KT4K	601
NSYCUF3KT4KR	601
NSYCUF400	601
NSYCUF400R	601
NSYCUF600	601
NSYCUF6K	601
NSYCUF800R	601
NSYCUF800T1K	601
NSYCUF8KT10K	601
NSYCUFX15K	601
NSYCUFX1K1T2KS	601
NSYCUFX1K2T2K	601
NSYCUFX1K2T2KR	601
NSYCUFX3KT4K	601
NSYCUFX3KT4KR	601
NSYCUFX400	601
NSYCUFX400R	601
NSYCUFX600	601
NSYCUFX6K	601
NSYCUFX800R	601
NSYCUFX800T1K	601
NSYCUFX8KT10K	601
NSYCUHD1K	597,600,656
NSYCUHD1K2P4	597,600,656
NSYCUHD1K6	597,600,656
NSYCUHD1K62P4	597,600,656
NSYCUHD2K3P4	597,600,656
NSYCUHD3K3P4	597,600,656
NSYCUHD400	596,600,656
NSYCUHD4K3P4	597,600,656
NSYCUHD600	596,600,656
NSYCUHD800	596,600,656
NSYCURFT1K2T2K	601
NSYCURFT1K6T2K	601
NSYCURFT3K	601
NSYCURFT3KT4K	601
NSYCURFT400	601
NSYCURFT800R	601
NSYCURFT800T1K	601
NSYCUS1K12P4UL	598,600,657
NSYCUS1K1UL	598,600,657
NSYCUS1K52P4UL	598,600,657
NSYCUS1K5UL	598,600,657
NSYCUS2K3P4UL	599,600,657
NSYCUS2K53P4UL	599,600,657
NSYCUS2K5UL	599,600,605,657
NSYCUS2KUL	599,600,657
NSYCUS3K23P4UL	599,600,657
NSYCUS3K2UL	599,600,657
NSYCUSP0001	650
NSYCUSP0002	650,656
NSYCUSP0003	650,656
NSYCUSP0004	650,656
NSYCUSP0005	650
NSYCUSP0006	650,651,656
NSYCUSP0007	651,656
NSYCUSP0008	654
NSYCUSP0009	654
NSYCUSP0010	654
NSYCUSP0011	654
NSYCUSP0012	654
NSYCUSP0013	650
NSYCUSP0014	650
NSYCUSP0015	650
NSYCUSP0016	650
NSYCUSP0017	650
NSYCUSP0018	650
NSYCUSP0019	650
NSYCUSP0020	651
NSYCUSP0021	651
NSYCUSP0022	651
NSYCUSP0023	654
NSYCUSP0024	654
NSYCUSP0025	654
NSYCUSP0026	654
NSYCUSP0027	654
NSYCUSP0028	654
NSYCUSP0029	654
NSYCUSP0030	648
NSYCUSP0031	648
NSYCUSP0032	648
NSYCUSP0033	648
NSYCUSP0034	648
NSYCUSP0035	648
NSYCUSP0036	648
NSYCUSP0037	648
NSYCUSP0038	648
NSYCUSP0039	648
NSYCUSP0040	648
NSYCUSP0041	648
NSYCUSP0042	648,650,656
NSYCUSP0043	648,650,654,656
NSYCUSP0044	648,650,654,656
NSYCUSP0047	654
NSYCUSP0049	654
NSYCUSP0051	654
NSYCUSP0053	648
NSYCUSP0054	650
NSYCUSP0055	650,656
NSYCUSP0056	650,656
NSYCUSP0057	650,656
NSYCUSP0058	650
NSYCUSP0059	650,654,656,657
NSYCUSP0060	651,654
NSYCUSP0061	651,654,656
NSYCUSP0062	651,654,656,657
NSYCUSP0063	651,654,656,657
NSYCUSP0064	654
NSYCUSP0065	654
NSYCUSP0066	652
NSYCUSP0067	652
NSYCUSP0068	652
NSYCUSP0069	652
NSYCUSP0070	652,653
NSYCUSP0071	653
NSYCUSP0072	655
NSYCUSP0073	655
NSYCUSP0074	655
NSYCUSP0075	655
NSYCUSP0076	648
NSYCUSP0077	648
NSYCUSP0078	648
NSYCUSP0079	648
NSYCUSP0080	648
NSYCUSP0081	648
NSYCUSP0082	648
NSYCUSP0083	648
NSYCUSP0084	648
NSYCUSP0085	652
NSYCUSP0086	652
NSYCUSP0087	652
NSYCUSP0088	652,653
NSYCUSP0089	653
NSYCUSP0090	655
NSYCUSP0091	655
NSYCUSP0092	655
NSYCUSP0093	655
NSYCUSP0094	648
NSYCUSP0095	648
NSYCUSP0096	648
NSYCUSP0097	648
NSYCUSP0098	648
NSYCUSP0099	652,653,655
NSYCUSP0100	648,649,656
NSYCUSP0101	652,656
NSYCUSP0102	652
NSYCUSP0103	652,656
NSYCUSP0104	653,655,656
NSYCUSP0105	653,655,656
NSYCUSP0106	655
NSYCUSP0107	649
NSYCUSP0108	649
NSYCUSP0109	649
NSYCUSP0110	649
NSYCUSP0111	648
NSYCUSP0112	648
NSYCUSP0113	648
NSYCUSP0114	649
NSYCUSP0115	649
NSYCUSP0116	649
NSYCUSP0117	649
NSYCUSP0118	652
NSYCUSP0119	652
NSYCUSP0120	652,653
NSYCUSP0121	655
NSYCUSP0122	655
NSYCUSP0123	655
NSYCUSP0124	649
NSYCUSP0125	649
NSYCUSP0126	652
NSYCUSP0127	652
NSYCUSP0128	653
NSYCUSP0129	655
NSYCUSP0130	657
NSYCUSP0131	657
NSYCUSP0132	657
NSYCUSP0133	657

Index of references

N	Page
NSYCUSP0134	657
NSYCUSP0135	657
NSYCUSP0136	648,650,651,654,656,657
NSYCUSP0137	648,651,654,656,657
NSYCUSP0138	648,650,651,656,657
NSYCUSP0139	651,657
NSYCUSP0140	657
NSYCUSP0141	657
NSYCUSP0142	657
NSYCUSP0143	657
NSYCUSP0144	652,653,655,657
NSYCUSP0145	657
NSYCUSP0146	657
NSYCUSP0147	653,655,657
NSYCUSP0148	653,655,657
NSYCUSP0149	657
NSYCUSP0150	657
NSYCUSP0151	657
NSYCUSP0152	657
NSYCUSP0153	656
NSYCUSP0154	656
NSYCUSP0155	656
NSYCUSP0156	656
NSYCUSP0157	656
NSYCUSP0158	656
NSYCUSP0159	656
NSYCUSP0160	656
NSYCUSP0161	656
NSYCUSP0162	656
NSYCUSP0163	656
NSYCUSP0164	656
NSYCUSP0165	656
NSYCUSP0166	657
NSYCUSP0167	656
NSYCUSP0168	656
NSYCUSP0169	656
NSYCUSP0170	656
NSYCUSP0171	656
NSYCUSP0172	654
NSYCUSP0173	652
NSYCUSP0174	652
NSYCUSP0175	649
NSYCUSP0176	649
NSYCUSP0177	648
NSYCUSP0181	648
NSYCUSP0184	648
NSYCUSX1K12P4UL	598,600,657
NSYCUSX1K1UL	598,600,657
NSYCUSX1K52P4UL	598,600,657
NSYCUSX1K5UL	598,600,657
NSYCUSX2K3P4UL	600,657
NSYCUSX2K53P4UL	600,657
NSYCUSX2K5UL	600,657
NSYCUSX2KUL	600,657
NSYCUSX3K23P4UL	600,657
NSYCUSX3K2UL	600,657
NSYCUX1K	591,600,650,652
NSYCUX1K2	591,600,650,652
NSYCUX1K22P4	591,600,650,652
NSYCUX1K2P4	591,600,650,652
NSYCUX1K2P4UL	591,600,650,652
NSYCUX1K2R	594,600,654,655
NSYCUX1K2UL	591,600,650,652
NSYCUX1K5R	595,600,654,655
NSYCUX1K6	591,600,650,652
NSYCUX1K62P4	591,600,650,652
NSYCUX1K62P4UL	591,600,650,652
NSYCUX1K6UL	591,600,650,652
NSYCUX1KUL	591,600,650,652
NSYCUX2K	591,600,651,653
NSYCUX2K3P4	592,600,651,653
NSYCUX2K3P4R	595,600,654,655
NSYCUX2K3P4UL	592,600,651,653
NSYCUX2KR	595,600,654,655
NSYCUX2KUL	591,600,651,653
NSYCUX3K3P4	592,600,651,653
NSYCUX3K3P4R	595,600,654,655
NSYCUX3K3P4UL	592,600,651,653
NSYCUX400	590,600,650,652
NSYCUX400R	594,600,654,655
NSYCUX4K3P4	592,600,651,653
NSYCUX4K3P4R	595,600,654,655
NSYCUX4K3P4UL	592,600,651,653
NSYCUX600	590,600,650,652
NSYCUX600UL	590,600,650,652
NSYCUX800	590,600,650,652
NSYCUX800R	594,600,654,655
NSYCUX800UL	590,600,650,652
NSYCVA114M	569
NSYCVA78M	569
NSYCVAC100	569
NSYCVF156M115	568
NSYCVF156M230	568
NSYCVF165M115DG	551,553
NSYCVF165M115PF	559
NSYCVF165M230DG	551,553
NSYCVF165M230PF	559,561,567
NSYCVF165M24DPF	559
NSYCVF165M48DPF	559
NSYCVF170M115	569
NSYCVF170M230	569
NSYCVF300M115DG	551,553
NSYCVF300M115PF	559
NSYCVF300M230DG	551,553
NSYCVF300M230PF	559,561,567
NSYCVF300M24DPF	559
NSYCVF300M48DPF	559
NSYCVF35M115	568
NSYCVF35M230	568
NSYCVF38M115DG	551,553,570
NSYCVF38M115PF	559
NSYCVF38M230DG	551,553,570
NSYCVF38M230PF	559,570
NSYCVF38M24DPF	559
NSYCVF38M48DPF	559
NSYCVF54M230MM2	568
NSYCVF550M115FB	425,562
NSYCVF550M230FB	425,562
NSYCVF550M24FB	425,562
NSYCVF550M48FB	425,562
NSYCVF560M115DG	551,553
NSYCVF560M115PF	559,571
NSYCVF560M230DG	551,553
NSYCVF560M230PF	559,561,567,571
NSYCVF570M115MF	568
NSYCVF575M230MF	568
NSYCVF65M115PF	568
NSYCVF65M230PF	568
NSYCVF850M115DG	551,553
NSYCVF850M115PF	559,571
NSYCVF850M230DG	551,553
NSYCVF850M230PF	559,561,567,571
NSYCVF850M400DG	551,553
NSYCVF850M400PF	559
NSYCVF85M115DG	551,553
NSYCVF85M115PF	559
NSYCVF85M230DG	551,553
NSYCVF85M230PF	559,561,567
NSYCVF85M24DPF	559
NSYCVF85M48DPF	559
NSYCW33	304
NSYCW44	304
NSYCW45	304
NSYCW46	304
NSYCW54	304
NSYCW55	304
NSYCW56	304
NSYCW65	304
NSYCW66	304
NSYCW86	304
NSYDB1010M	10,32
NSYDB1510M	10,32
NSYDB2015M	10,32
NSYDB88M	10,32
NSYDBN1010	32
NSYDBN1510	32
NSYDBN2015	32
NSYDBN2520	32
NSYDBN3025	32
NSYDBN88	32
NSYDCD2412	63,65,282
NSYDCD244	63,65,282
NSYDCD248	63,65,282
NSYDCD249	63,65,282
NSYDCE10	105
NSYDCE12	105
NSYDCE168	63,67,282
NSYDCE2410	63,67,282
NSYDCE244	63,67,282
NSYDCE6	105
NSYDCE8	105
NSYDCM20	114,300
NSYDCRN106	638
NSYDCRN108	638
NSYDCRN22	638,644
NSYDCRN23	638,644
NSYDCRN2520	638,644
NSYDCRN3025	638,644
NSYDCRN3045	638,644
NSYDCRN33	638,644

Index of references

N	Page
NSYDCRN34	638,644
NSYDCRN43	638,644
NSYDCRN44	638,644
NSYDCRN46	638,644
NSYDCRN54	638
NSYDCRN55	638,644
NSYDCRN64	638
NSYDCRN65	638
NSYDCRN66	638,644
NSYDCRN68	638,644
NSYDCRN75	638
NSYDCRN86	638,644
NSYDCRN88	638
NSYDCRNG1010T	638
NSYDCRNG105L	638
NSYDCRNG105R	638
NSYDCRNG106	638
NSYDCRNG106L	638
NSYDCRNG106R	638
NSYDCRNG106T	638
NSYDCRNG108	638
NSYDCRNG108T	638
NSYDCRNG125L	638
NSYDCRNG125R	638
NSYDCRNG126	638
NSYDCRNG126L	638
NSYDCRNG126R	638
NSYDCRNG126T	638
NSYDCRNG128	638
NSYDCRNG128T	638
NSYDCRNG145L	638
NSYDCRNG145R	638
NSYDCRNG85L	638
NSYDCRNG85R	638
NSYDCRNG86	638
NSYDCRNG86L	638
NSYDCRNG86R	638
NSYDCRNG86T	638
NSYDCSH1412	334
NSYDCSH1612	334
NSYDCSH1812	334
NSYDCSH1816	334
NSYDCSH2012	334,335
NSYDCSH2016	334,335
NSYDHLT6040	260
NSYDHLT6060	260
NSYDHLT6080	260
NSYDHLT8040	260
NSYDHLT8060	260
NSYDHLT8080	260
NSYDHSF	639,640
NSYDHSM2D	640
NSYDLA112	200
NSYDLA112G	13,47,200,25
NSYDLA234	200
NSYDLA234G	13,25,47,200
NSYDLA24	200
NSYDLA24G	13,25,47,200
NSYDLA48	200
NSYDLA48G	13,25,47,200

N	Page
NSYDLA48P	200
NSYDLA48PG	13,25,47,200
NSYDLA66	200
NSYDLA66G	13,25,47,200
NSYDLA84	200
NSYDLA84G	13,25,47,200
NSYDLA88	200
NSYDLA88G	25,200
NSYDLCR110	332
NSYDLCR135	332
NSYDLCR18	332
NSYDLCR24	332
NSYDLCR36	332
NSYDLCR48	332
NSYDLCR64	332
NSYDLCR88	332
NSYDLLSDF	643
NSYDLM112	12,13,15,22,46,47,140,330,331
NSYDLM168	13,15,47,330,331
NSYDLM24	13,15,22,47,140,330,331
NSYDLM240	13,15,22,47,140,330,331
NSYDLM48	13,15,22,47,140,330,331
NSYDLM48P	13,15,22,47,140,330,331
NSYDLM66	13,15,22,47,140,330,331
NSYDLM84	12,13,15,22,46,47,140,330,331
NSYDLM84P	13,15,22,47,140,330,331
NSYDLM88	15,22,140,330,331
NSYDLP114G	28,222
NSYDLP114PG	28,222
NSYDLP132G	28,222
NSYDLP133G	28,222
NSYDLP152G	28,222
NSYDLP165G	28,222
NSYDLP171G	28,222
NSYDLP198G	28,222
NSYDLP198PG	28,222
NSYDLP231G	28,222
NSYDLP264G	28,222
NSYDLP297G	28,222
NSYDLP57G	28,222
NSYDLP76G	28,222
NSYDLP95G	28,222
NSYDLP99G	28,222
NSYDLPLM18G	25,201
NSYDLS12	173,175
NSYDLS24	175
NSYDLS242	175
NSYDLS36	175
NSYDLS48	175
NSYDPA3	113,300,555
NSYDPA4	113,300,555
NSYDPA44	113,300,555
NSYDPA5	113,300,555
NSYDPHD105P	645
NSYDPHD105R	645
NSYDPHD107P	645
NSYDPHD107R	645
NSYDPHD125LP	645
NSYDPHD125LR	645
NSYDPHD125P	645

N	Page
NSYDPHD125R	645
NSYDPHD127P	645
NSYDPHD127R	645
NSYDPHD155LP	645
NSYDPHD155LR	645
NSYDPHD157P	645
NSYDPHD157R	645
NSYDPHD55P	645
NSYDPHD55R	645
NSYDPHD75P	645
NSYDPHD75R	645
NSYDPHD77P	645
NSYDPHD77R	645
NSYDPLA105G	642
NSYDPLA105HG	642
NSYDPLA107G	642
NSYDPLA107HG	642
NSYDPLA125G	642
NSYDPLA125HG	642
NSYDPLA127G	642
NSYDPLA127HG	642
NSYDPLA155G	642
NSYDPLA155HG	642
NSYDPLA157G	642
NSYDPLA157HG	642
NSYDPLA3	224
NSYDPLA4	224
NSYDPLA55G	642
NSYDPLA55HG	642
NSYDPLA57G	642
NSYDPLA57HG	642
NSYDPLA6	224
NSYDPLA75G	642
NSYDPLA75HG	642
NSYDPLA77G	642
NSYDPLA77HG	642
NSYDPLM108G	643
NSYDPLM108TG	643
NSYDPLM200	25,198,486
NSYDPLM250	25,198,486
NSYDPLM300	25,198,486
NSYDPLM3025G	643
NSYDPLM3025TG	643
NSYDPLM32G	643
NSYDPLM32TG	643
NSYDPLM350	25,198,486
NSYDPLM43G	643
NSYDPLM43TG	643
NSYDPLM54G	643
NSYDPLM54TG	643
NSYDPLM64G	643
NSYDPLM64TG	643
NSYDPLM75G	643
NSYDPLM75TG	643
NSYDPLM86G	643
NSYDPLM86TG	643
NSYDPR100	263
NSYDPR120	263
NSYDPR200	264
NSYDPR200D	264

Index of references

N	Page
NSYDPR200T	264
NSYDPR25	263
NSYDPR35	263
NSYDPR45	263
NSYDPR55	263
NSYDPR60	263
NSYDPR65	263
NSYDPR75	263
NSYDPR80	263
NSYDS3D1010	636
NSYDS3D105L	636
NSYDS3D105R	636
NSYDS3D106	636
NSYDS3D106L	636
NSYDS3D106R	636
NSYDS3D108	636,645
NSYDS3D1210	636
NSYDS3D125L	636
NSYDS3D125R	636
NSYDS3D126	636
NSYDS3D126L	636
NSYDS3D126R	636
NSYDS3D128	636
NSYDS3D145L	636
NSYDS3D145R	636
NSYDS3D32	636,645
NSYDS3D325	636
NSYDS3D33	636,645
NSYDS3D34	636
NSYDS3D43	636,645
NSYDS3D44	636,645
NSYDS3D46	636
NSYDS3D53	636
NSYDS3D54	636,645
NSYDS3D55	636
NSYDS3D64	636,645
NSYDS3D65	636
NSYDS3D66	636,645
NSYDS3D68	636
NSYDS3D75	636,645
NSYDS3D810	636
NSYDS3D85L	636
NSYDS3D85R	636
NSYDS3D86	636,645
NSYDS3D86L	636
NSYDS3D86R	636
NSYDS3D88	636
NSYDS3HD106	646
NSYDS3HD108	646
NSYDS3HD32	646
NSYDS3HD43	646
NSYDS3HD54	646
NSYDS3HD64	646
NSYDS3HD66	646
NSYDS3HD75	646
NSYDS3HD86	646
NSYDS3HD88	646
NSYDS3X1010L	641
NSYDS3X1010LH	641
NSYDS3X1010R	641

N	Page
NSYDS3X1010RH	641
NSYDS3X108	641
NSYDS3X108H	641
NSYDS3X108T	641
NSYDS3X1210L	641
NSYDS3X1210LH	641
NSYDS3X1210R	641
NSYDS3X1210RH	641
NSYDS3X128	641
NSYDS3X128H	641
NSYDS3X32	641
NSYDS3X325	641
NSYDS3X325H	641
NSYDS3X32H	641
NSYDS3X33	641
NSYDS3X33H	641
NSYDS3X43	641
NSYDS3X43H	641
NSYDS3X43T	641
NSYDS3X44	641
NSYDS3X44H	641
NSYDS3X46	641
NSYDS3X46H	641
NSYDS3X54	641
NSYDS3X54H	641
NSYDS3X54T	641
NSYDS3X64	641
NSYDS3X64H	641
NSYDS3X64T	641
NSYDS3X66	641
NSYDS3X66H	641
NSYDS3X75	641
NSYDS3X75H	641
NSYDS3X75T	641
NSYDS3X86	641
NSYDS3X86H	641
NSYDS3X86T	641
NSYDS3X88	641
NSYDS3X88H	641
NSYDSFX1410L	641
NSYDSFX1410R	641
NSYDSFX168	641
NSYDSFX1812L	641,642
NSYDSFX1812LH	641
NSYDSFX1812R	641,642
NSYDSFX1812RH	641
NSYDSFX1816L	641
NSYDSFX1816LH	641
NSYDSFX1816R	641
NSYDSFX1816RH	641
NSYDSFX186	641,642
NSYDSFX188	641,642
NSYDSFX188H	641
NSYDSFX2010L	641,642
NSYDSFX2010LH	641
NSYDSFX2010R	641,642
NSYDSFX2010RH	641
NSYDSFX2012L	641,642
NSYDSFX2012LH	641
NSYDSFX2012R	641,642

N	Page
NSYDSFX2012RH	641
NSYDSFX2016L	641,642
NSYDSFX2016LH	641
NSYDSFX2016R	641,642
NSYDSFX2016RH	641
NSYDSFX206	641,642
NSYDSFX208	641,642
NSYDT16	71,170,287
NSYDT20	71,170,287
NSYDT25	71,170,287
NSYDT32	71,170,287
NSYDT40	71,170,287
NSYDTEF32T	619
NSYE1025	268
NSYE1525	268
NSYE2025	268
NSYEB1510D6	131,305,478
NSYEB1516D8	305,415,478
NSYEB156D6	131,305,478
NSYEB2025D8	305,415,478
NSYEB2050D8	305,415,478
NSYEBMPLAG	218
NSYEC104	18,88,103
NSYEC1041	18,88,104
NSYEC105	18,88,103
NSYEC1051	18,88,104
NSYEC106	18,88,103
NSYEC1061	18,88,104
NSYEC1062	18,88,104
NSYEC108	18,88,103
NSYEC1081	18,88,104
NSYEC1082	18,88,104
NSYEC124	18,88,103
NSYEC1241	18,88,104
NSYEC125	18,88,103
NSYEC1251	18,88,104
NSYEC126	18,88,103
NSYEC1261	18,88,104
NSYEC1262	18,88,104
NSYEC128	18,88,103
NSYEC1281	18,88,104
NSYEC1282	18,88,104
NSYEC164	18,88,103
NSYEC1641	18,88,104
NSYEC165	18,88,103
NSYEC1651	18,88,104
NSYEC166	18,88,103
NSYEC1661	18,88,104
NSYEC1662	18,88,104
NSYEC35	18,88,103
NSYEC351	18,88,104,380
NSYEC36	18,88,103,415
NSYEC361	18,88,104,415
NSYEC381	18,88,380,415
NSYEC44	18,88,103
NSYEC440	461
NSYEC441	18,88,104
NSYEC45	18,88,103
NSYEC451	18,88,104
NSYEC461	18,88,104,415

Index of references

N	Page
NSYEC481	18,88,104,415
NSYEC610	458
NSYEC6101	458
NSYEC6102	459
NSYEC64	18,88,103,415
NSYEC641	18,88,104
NSYEC65	18,88,103
NSYEC651	18,88,104,380
NSYEC66	18,88,103,415,458
NSYEC661	18,88,104,415,458
NSYEC662	18,88,104,415,459
NSYEC68	18,88,103,415,458
NSYEC681	18,88,104,415,458
NSYEC682	18,88,104,415,459
NSYEC7	63,69,167,169,286
NSYEC751	380
NSYEC761	380
NSYEC781	380
NSYEC810	458
NSYEC8101	458
NSYEC8102	459
NSYEC84	18,88,103,415
NSYEC841	18,88,104
NSYEC85	18,88,103
NSYEC851	18,88,104
NSYEC86	18,88,103,415,458
NSYEC861	18,88,104,415,458
NSYEC862	18,88,104,415,459
NSYEC88	18,88,103,415,458
NSYEC881	18,88,104,415,458
NSYEC882	18,88,104,415,459
NSYECA22	267,315
NSYECA42	267,315
NSYECA44	267,315
NSYECAV440	461
NSYECB1M153	131,305
NSYECP440	461
NSYECPC15	63,68,167,168,285
NSYECPC3	63,68,167,168,285
NSYECPC5	63,68,167,168,285
NSYECPC6	63,68,167,168,285
NSYECPC9	63,68,167,168,285
NSYECPLAZ103G	29,211
NSYECPLAZ104G	29,211
NSYECPLAZ123G	29,211
NSYECPLAZ124G	29,211
NSYECPLAZ126G	29,211
NSYECPLAZ53G	29,211
NSYECPLAZ54G	29,211
NSYECPLAZ73G	29,211
NSYECPLAZ74G	29,211
NSYECPLAZ76G	29,211
NSYECVT2440	461
NSYECVT2V440	461
NSYECVT3440	461
NSYECVT3V440	461
NSYEDCME	62
NSYEDCO	252
NSYEDCOC	252
NSYEDCOS	305

N	Page
NSYEDPLA	224
NSYEL136D6	131,305
NSYEL166D6	131,305
NSYEL166D8	131,305,381,415
NSYEL1710D6	131,305
NSYEL2225D8	131,305,415
NSYEL226D13	131,305
NSYEL226D6	131,305
NSYEL2510D6	131,305
NSYEL3525D8	131,305,381,415
NSYEMA20	266,314
NSYEMA40	266,314
NSYEMR	12,46,240,241
NSYEN20	267
NSYEN40	267
NSYEN60	267
NSYETF	252
NSYETU118	268,316
NSYETU48	268,316
NSYETU58	268,316
NSYETU79	268,316
NSYEVA20	266,314
NSYEVA40	266,314
NSYEX1006	268
NSYEX1008	268
NSYEX106	268
NSYEX126	268
NSYEX146	268
NSYEX158	268
NSYEX166	268
NSYEX186	268
NSYEX206	268,460
NSYEX208	268
NSYEX306	268
NSYEX308	268
NSYEX406	268
NSYEX408	268
NSYEX506	268
NSYEX508	268
NSYEX608	268
NSYFB	244
NSYFB45	252,412
NSYFCG100	288
NSYFCG120	288
NSYFCG160	288
NSYFCG60	288
NSYFCG80	288
NSYFCMX	153
NSYFDLSD	643
NSYFECVT440	461
NSYFMPHD	419
NSYFMPLA	211
NSYFNM6	251,271
NSYFNM8	251,271
NSYFPLS1827G	174
NSYFPLS2727G	174
NSYFPLS2736G	174
NSYFPLS2754G	174
NSYFPLS3636G	174
NSYFPLS3654G	174

N	Page
NSYFPLS3672G	174
NSYFPLS5454G	174
NSYFSP27270	176
NSYFSP27360	176
NSYFSP27540	176
NSYFSPLAZ	215
NSYFXMNT60F	348
NSYFXMNT80F	348
NSYFXMNT80W	348
NSYFXMNW80F	348
NSYFXMNW80W	348
NSYFXMNWT60FW	348
NSYFXT6040	259
NSYFXT6050	259
NSYFXT6060	259,514
NSYFXT8040	259
NSYFXT8050	259
NSYFXT8060	259
NSYFXT8080	259
NSYGB140	467
NSYGDD	636
NSYGFR166P	269,468
NSYGFR95M55	269,468
NSYGFR95M63	269,468
NSYGFR95M65	269,468
NSYHLCR40	257,261,434
NSYHLCR50	257,261
NSYHLCR60	257,261,434
NSYHLCR70	257,261
NSYHLCR80	257,261,434
NSYHPF2B3M4	410
NSYHPF2B3M64	410
NSYHPF2B3M65	410
NSYHPF2B3M84	410
NSYHPF2B3M85	410
NSYHS3X	641
NSYHSD	643
NSYHSDF	643
NSYHSMX	642
NSYID166	17,87,111
NSYID168	17,87,111
NSYID1810	17,87,111
NSYID186	17,87,111
NSYID188	17,87,111
NSYID2010	17,87,111
NSYID206	17,87,111
NSYID208	17,87,111
NSYID226	111
NSYID228	111
NSYIN1242E1	116,217,508
NSYIN1242E2	117,217
NSYIN1332E1	116,217,508
NSYIN2124E1	116,217,508
NSYIN2131A1	116,217,508
NSYIN2132A1	116,217,508
NSYIN2331A1	116,217,508
NSYIN2433A1	116,217,508
NSYIN2452E1	116,217,508
NSYIN3113A1	116,217,508
NSYIN3122E1	116,217,508

Index of references

N	Page
NSYIN3123A1	116,217,508
NSYIN3131A1	116,217,508
NSYIN3133A1	116,217,508
NSYIN3422E1	116,217,508
NSYIN3432E1	116,217,508
NSYIN405E1	116,217,508
NSYIN421E1	116,217,508
NSYIN4551	116,217,508
NSYIN6101	116,217,508
NSYINASSA2	117
NSYINBENZ1	116,508
NSYINCW1	116,508
NSYINDB31	116,508
NSYINDB51	116,217,508
NSYINDIN2	117,217
NSYINE11	116,508
NSYINF1301	116,508
NSYINF1401	116,508
NSYINFIAT1	116,508
NSYINH31	116,508
NSYINICHEL8131	116,508
NSYINICHEL8371	116,508
NSYINICHEL8791	116,508
NSYINKBA2	117
NSYINKFAC2	117,217
NSYINKJIS2	117,217
NSYINKR2	117,217
NSYINLCRN	60,300,445,448
NSYINPULS1	116
NSYINPULSD	508
NSYINS61	116,217,508
NSYINS6G1	116,508
NSYINS71	116,217,508
NSYINS81	116,217,508
NSYINS8G1	116,508
NSYINT101	116,508
NSYINT61	116,217,508
NSYINT71	116,508
NSYINT81	116,217,508
NSYINT91	116,508
NSYINUSA1	116,508
NSYJED8122	228
NSYJED8500	228
NSYJED860	228
NSYJED881	228
NSYKPLM	197
NSYLADP	117
NSYLAM1M	296
NSYLAM1MN	296
NSYLAM1MUL	296
NSYLAM1MULN	296
NSYLAM1U	296
NSYLAM3M	296
NSYLAM3MDC	296
NSYLAM3MDCUL	296
NSYLAM3MN	296
NSYLAM3MUL	296
NSYLAM3MULN	296
NSYLAMACF	297
NSYLAMACM	297
NSYLAMDCF	297
NSYLAMDCM	297
NSYLAMLD	296
NSYLAMLDB	296
NSYLAMLDD	296
NSYLAMLDF	296
NSYLAMLDS	296
NSYLAMLDU	296
NSYLAMLDVDC	296
NSYLAMPORTLD	298
NSYLAMT5LD1	298
NSYLAMT5LD1VDC	298
NSYLAMT5LD2	298
NSYLC7	218,415
NSYLC8	218,415
NSYLCK12SF	639,640
NSYLCK14SF	639,640
NSYLCK16SF	639,640
NSYLCK18SF	639,640
NSYLCK20SF	639,640
NSYLCK22SF	639,640
NSYLCKWSF	639,640
NSYLCR40	257
NSYLCR50	257
NSYLCR60	257
NSYLDB5	218,415
NSYLSS3X10	641
NSYLSS3X12	641
NSYLSSDX	644
NSYLSSFX14	641,642
NSYLSSFX16	641,642
NSYLSSFX18	641,642
NSYLSSFX20	641,642
NSYLSUP	257
NSYLT27	178
NSYLT8	218,415
NSYMB106	13,47,241
NSYMB108	13,25,47,195,241
NSYMB1210	13,47,241
NSYMB3025	13,25,47,195,241
NSYMB32	13,25,47,195,241
NSYMB33	13,47,241
NSYMB43	13,25,47,195,241
NSYMB54	13,25,47,195,241
NSYMB64	13,25,47,195,241
NSYMB65	13,47,241
NSYMB75	13,25,47,195,241
NSYMB86	13,25,47,195,241
NSYMBC206	410
NSYMBC208	410
NSYMBHS4	406,408
NSYMBHS5	406,408
NSYMBR19	464
NSYMCDFIX	339
NSYMCOD264	113
NSYMCOD284	113
NSYMD108	13,47,241,486
NSYMD128	13,47,241
NSYMD33	13,47,241,486
NSYMD43	13,47,241,486
NSYMD54	13,47,241,486
NSYMD64	13,47,241,486
NSYMD66	13,47,241,486
NSYMD75	13,47,241,486
NSYMD86	13,47,241,486
NSYMDCM20	114,300
NSYMDVR10	13,15,47,244
NSYMDVR12	12,13,46,47,244
NSYMDVR3	13,15,47,244
NSYMDVR3M	244
NSYMDVR4	13,15,47,244
NSYMDVR5	13,15,47,244
NSYMDVR6	13,15,47,244
NSYMDVR7	13,15,47,244
NSYMDVR8	13,15,47,244
NSYMF1010	12,22,46,140,240
NSYMF106	12,22,46,140,240
NSYMF108	12,22,25,46,140,194,240,485
NSYMF1210	12,22,46,140,240
NSYMF126	12,22,46,140,240
NSYMF128	12,22,46,140,240
NSYMF2PLAZ4	419
NSYMF2PLAZ6	419
NSYMF32	12,22,46,140,240
NSYMF33	12,22,46,140,240,485
NSYMF43	12,22,25,46,140,194,240,485
NSYMF44	12,22,46,140,240,485,502
NSYMF53	12,46,240
NSYMF54	12,22,25,46,140,194,240,485
NSYMF55	12,46,240
NSYMF64	12,22,25,46,140,194,240, 485,502
NSYMF65	12,46,240
NSYMF66	12,22,46,140,240,485
NSYMF75	12,22,25,46,140,194,240,485
NSYMF86	12,22,25,46,140,194,240,485
NSYMF88	12,22,46,140,240
NSYMFB	251
NSYMFP2M6	112,413
NSYMFP2M8	112,413
NSYMFP5M6	112,413
NSYMFP5M8	112,413
NSYMFPLAZ103	29,215
NSYMFPLAZ104	29,215
NSYMFPLAZ123	29,215
NSYMFPLAZ124	29,215
NSYMFPLAZ126	29,215
NSYMFPLAZ53	29,215
NSYMFPLAZ54	29,215
NSYMFPLAZ73	29,215
NSYMFPLAZ74	29,215
NSYMFPLAZ76	29,215
NSYMFS1	339
NSYMFS1D	339
NSYMFSC60	338
NSYMFSC60D	338
NSYMFSC80	338
NSYMFSC80D	338
NSYMIC6	113
NSYMIC8	113

Index of references

N	Page
NSYML23	515
NSYML405SD	507
NSYMLCD23	515
NSYMLS6	515
NSYMLT6	515
NSYMM1010	12,22,46,140,240
NSYMM106	12,15,22,46,140,240,424
NSYMM108	12,15,22,25,46,140,194,240, 424,485
NSYMM11SB	36,38,128
NSYMM1210	12,22,46,140,240
NSYMM1212	12,46,240
NSYMM126	12,22,46,140,240
NSYMM128	12,22,46,140,240
NSYMM12SB	36,38
NSYMM13SB	36,38,128
NSYMM1410	12,46,240
NSYMM14SB	36,38
NSYMM22	240
NSYMM22SB	36,38,128
NSYMM23	240
NSYMM23SB	36,38,128
NSYMM24SB	36,38,128
NSYMM2520	240
NSYMM2540	15,240
NSYMM2550	15,240
NSYMM25SB	36,38
NSYMM26SB	36,38
NSYMM28SB	36,38
NSYMM3025	12,15,22,25,46,140,194, 240,485
NSYMM3045	240
NSYMM32	12,15,22,25,46,140,194,240, 424,485
NSYMM33	12,15,22,46,140,240,485
NSYMM33SB	36,38,128
NSYMM34SB	36,38
NSYMM35SB	36,38
NSYMM36	15,240
NSYMM36SB	36,38
NSYMM38SB	36,38
NSYMM43	12,15,22,25,46,140,194, 240,485
NSYMM44	12,22,46,140,240,485,502
NSYMM44SB	36,38
NSYMM45SB	36,38
NSYMM46SB	36,38
NSYMM48	15,240
NSYMM48SB	36,38
NSYMM53	12,15,46,240
NSYMM54	12,15,22,25,46,140,194,240, 424,485
NSYMM55	12,46,240
NSYMM64	12,15,22,25,46,140,194,240,2 41,424,485,502
NSYMM65	12,15,46,240
NSYMM66	12,15,22,46,140,240,424,485
NSYMM75	12,15,22,25,46,140,194,240, 424,485
NSYMM76	15,240
NSYMM86	12,15,22,25,46,140,194,240, 424,485
NSYMM88	12,22,46,140,240,424
NSYMP1210	17,87,245
NSYMP1212	17,87,245,424
NSYMP124	245,249
NSYMP126	19,20,90,245,424
NSYMP128	17,19,20,87,90,245,424
NSYMP12M6	392,393,395,396,398
NSYMP12M8	392,393,395,396,398
NSYMP1410	17,23,87,152,245,510
NSYMP1412	17,87,245,510
NSYMP144	245,249
NSYMP146	17,19,20,87,90,245
NSYMP148	17,19,20,87,90,245,510
NSYMP1610	17,87,245
NSYMP1612	17,87,245,424
NSYMP164	245,249
NSYMP166	17,19,20,87,90,245,424
NSYMP168	17,19,20,23,87,90,152,245,424
NSYMP16M6	392,395,396,398
NSYMP16M8	392,395,398
NSYMP1810	17,19,20,87,90,245
NSYMP1812	17,19,20,23,87,90,152,245
NSYMP1816	17,23,87,152,245
NSYMP184	19,90,245,249
NSYMP186	17,19,20,23,87,90,152,245
NSYMP188	17,19,20,23,87,90,152,245
NSYMP18M6	392
NSYMP18M8	392
NSYMP2010	17,19,21,23,87,91,152,245
NSYMP2012	17,19,21,23,87,91,152,245
NSYMP2016	17,19,21,23,87,91,152,245
NSYMP204	19,20,91,245,249
NSYMP206	17,19,21,23,87,91,152,245,433
NSYMP208	17,19,21,23,87,91,152,245,4 24,433
NSYMP20M6	392,398
NSYMP20M8	392,398
NSYMP2210	19,21,91,245
NSYMP2212	19,21,91,245
NSYMP224	19,91,245,249
NSYMP226	19,21,91,245
NSYMP228	19,21,91,245
NSYMP24M6	392,398
NSYMP24M8	392,398
NSYMP3M6	392,393,394,395,396
NSYMP3M8	392,393,394,395,396
NSYMP4M6	392,393,394,396,397
NSYMP4M8	392,393,394,396,397
NSYMP5M6	392,396,397
NSYMP5M8	392,396,397
NSYMP6M6	392,393,395
NSYMP6M8	392,393,395
NSYMP8M6	392
NSYMP8M8	392
NSYMP9M6	392,393,395,396,398
NSYMP9M8	392,393,395,396,398
NSYMPB4SD	510
NSYMPB6SD	510
NSYMPBSD	510
NSYMPC156	336
NSYMPC158	336
NSYMPC206	336
NSYMPC208	336
NSYMPC306	336
NSYMPC308	336
NSYMPC406	336
NSYMPC408	336
NSYMPC456	336
NSYMPC458	336
NSYMPC606	336
NSYMPC608	336
NSYMPCH156	336
NSYMPCH158	336
NSYMPCH206	336
NSYMPCH208	336
NSYMPCH306	336
NSYMPCH308	336
NSYMPCH406	336
NSYMPCH408	336
NSYMPCH456	336
NSYMPCH458	336
NSYMPCH606	336
NSYMPCH608	336
NSYMPD106T	112
NSYMPD108T	112
NSYMPD12M6	112,413
NSYMPD12M8	112,413
NSYMPD16M6	112,413
NSYMPD16M8	112,413
NSYMPD18M6	112,413
NSYMPD18M8	112,413
NSYMPD20M6	112,413
NSYMPD20M8	112,413
NSYMPD24M6	112,413
NSYMPD24M8	112,413
NSYMPD26T	112
NSYMPD28T	112
NSYMPD3M6	112,413
NSYMPD3M8	112,413
NSYMPD46T	112
NSYMPD48T	112
NSYMPD4M6	112,413
NSYMPD4M8	112,413
NSYMPD5M6	112,413
NSYMPD5M8	112,413
NSYMPD66T	112
NSYMPD68T	112
NSYMPD6M6	112,413
NSYMPD6M8	112,413
NSYMPD86T	112
NSYMPD88T	112
NSYMPD8M6	112,413
NSYMPD8M8	112,413
NSYMPD9M6	112,413
NSYMPD9M8	112
NSYMPFIX	392,393,394,395,396,397,398
NSYMPLGYFC600	352
NSYMPLGYFC800	352

Index of references

N	Page
NSYMPP108	25,195,241
NSYMPP3025	25,195,241
NSYMPP32	25,195,241
NSYMPP43	25,195,241
NSYMPP54	25,195,241
NSYMPP64	25,195,241
NSYMPP75	25,195,241
NSYMPP86	25,195,241
NSYMPRK10	247
NSYMPRK12	247
NSYMPRK16	247
NSYMPRK8	247
NSYMPS30	339
NSYMPS40	339
NSYMPS50	339
NSYMPS60	339
NSYMPS80	339
NSYMR1010	22,140,240
NSYMR1012	13,47,240
NSYMR106	13,15,22,47,140,240
NSYMR108	13,15,22,25,47,140,195, 240,485
NSYMR1210	13,22,47,140,240
NSYMR126	13,47,240
NSYMR128	13,22,47,140,240
NSYMR1410	13,47,240
NSYMR3025	13,22,25,47,140,195,240,485
NSYMR32	13,22,25,47,140,195,240,485
NSYMR33	13,15,22,47,140,240,485
NSYMR34	13,15,47,240
NSYMR43	13,15,22,25,47,140,195, 240,485
NSYMR44	13,22,47,140,240,502
NSYMR46	13,15,22,47,140,240
NSYMR53	13,47,240
NSYMR54	13,15,22,25,47,140,195, 240,485
NSYMR55	13,47,240
NSYMR64	13,15,22,25,47,140,195,240, 485,502
NSYMR65	13,47,240
NSYMR66	13,15,22,47,140,240,485
NSYMR68	13,47,240
NSYMR75	13,15,22,25,47,140,195, 240,485
NSYMR76	15,240
NSYMR810	13,47,240
NSYMR86	13,15,22,25,47,140,195, 240,485
NSYMR88	13,22,47,140,240
NSYMS43	12,22,25,46,140,194,240,485
NSYMS44	12,22,46,140,240,485
NSYMS53	12,46,240
NSYMS54	12,22,25,46,140,194,240,485
NSYMS55	12,46,240
NSYMS64	12,22,25,46,140,194,240,485
NSYMS66	12,22,46,140,240,485
NSYMS75	12,22,25,46,140,194,240,485
NSYMS86	12,22,25,46,140,194,240,485
NSYMSC202	410
NSYMSC206	410
NSYMTR64	411
NSYMTR65	411
NSYMTR84	411
NSYMTR85	411
NSYMUC156	337
NSYMUC158	337
NSYMUC206	337
NSYMUC208	337
NSYMUC306	335,337
NSYMUC308	335,337
NSYMUC406	337
NSYMUC408	337
NSYMUC456	337
NSYMUC458	337
NSYMUC606	337
NSYMUC608	337
NSYMUCH156	337
NSYMUCH158	337
NSYMUCH206	337
NSYMUCH208	337
NSYMUCH306	337
NSYMUCH308	337
NSYMUCH406	337
NSYMUCH408	337
NSYMUCH456	337
NSYMUCH458	337
NSYMUCH606	337
NSYMUCH608	337
NSYMUPLA103G	210
NSYMUPLA103W	210
NSYMUPLA104G	210
NSYMUPLA104W	210
NSYMUPLA123G	210
NSYMUPLA123W	210
NSYMUPLA124G	210
NSYMUPLA124W	210
NSYMUPLA126G	210
NSYMUPLA126W	210
NSYMUPLA153G	210
NSYMUPLA153W	210
NSYMUPLA154G	210
NSYMUPLA154W	210
NSYMUPLA156G	210
NSYMUPLA156W	210
NSYMUPLA204G	210
NSYMUPLA204W	210
NSYMUPLA53G	210
NSYMUPLA53W	210
NSYMUPLA54G	210
NSYMUPLA54W	210
NSYMUPLA73G	210
NSYMUPLA73W	210
NSYMUPLA74G	210
NSYMUPLA74W	210
NSYMUPLA76G	210
NSYMUPLA76W	210
NSYMW10M	303
NSYMW10MK	303
NSYMW10MR	303
NSYNM4	244,271
NSYNM5	244,271
NSYNM6	244,271
NSYOL6GF	100
NSYPA3025PLMG	25,193
NSYPAP108G	25,193
NSYPAP43G	25,193
NSYPAP54G	25,193
NSYPAP64G	25,193
NSYPAP75G	25,193
NSYPAP86G	25,193
NSYPAPLA105G	28,216
NSYPAPLA107G	28,216
NSYPAPLA125G	28,216
NSYPAPLA127G	28,216
NSYPAPLA155G	28,216
NSYPAPLA157G	28,216
NSYPAPLA55G	28,216
NSYPAPLA57G	28,216
NSYPAPLA75G	28,216
NSYPAPLA77G	28,216
NSYPC100	639,640
NSYPC200	639,640
NSYPCVD126	456
NSYPCVD128	456
NSYPCVD148	456
NSYPCVD168	456
NSYPCVD188	456
NSYPCVD206	456
NSYPCVD208	456
NSYPCVD226	456
NSYPCVD228	456
NSYPCVR124HD	420,426,427,564,565
NSYPCVR126HD	420,426,427,564,565
NSYPCVR54HD	420,426,427,564,565
NSYPCVR74HD	420,426,427,564,565
NSYPCVR76HD	420,426,427,564,565
NSYPF27N	176
NSYPF27X	176
NSYPFC2X	142
NSYPFCX	142
NSYPFPLM32G	25,192
NSYPFPLMG	25,192
NSYPFXPLM	192
NSYPHDT553	418,426,564
NSYPHDT553P	418,426,564
NSYPHDT753	418,426,564
NSYPHDT753P	418,426,564
NSYPHDZT1054	418,426,564
NSYPHDZT1054P	418,426,564
NSYPHDZT1074	418,426,564
NSYPHDZT1074P	418,426,564
NSYPHDZT12124	418,426,564
NSYPHDZT12124P	418,426,564
NSYPHDZT12126	418,426,564
NSYPHDZT12126P	418,426,564
NSYPHDZT1254	418,426,564
NSYPHDZT1254P	418,426,564
NSYPHDZT1274	418,426,564
NSYPHDZT1274P	418,426,564

Index of references

N	Page
NSYPHDZT1276	418,426,564
NSYPHDZT1276P	418,426,564
NSYPHDZT15124	418,426,564
NSYPHDZT15124P	418,426,564
NSYPHDZT15126	418,426,564
NSYPHDZT15126P	418,426,564
NSYPHDZT1574	418,426,564
NSYPHDZT1574P	418,426,564
NSYPHDZT1576	418,426,564
NSYPHDZT1576P	418,426,564
NSYPHDZT2074	418,426,564
NSYPHDZT2074P	418,426,564
NSYPHDZT774	418,426,564
NSYPHDZT774P	418,426,564
NSYPHDZT776	418,426,564
NSYPHDZT776P	418,426,564
NSYPHLT6040	261
NSYPHLT6060	261
NSYPHLT6080	261
NSYPHLT8040	261
NSYPHLT8080	261
NSYPHX200	153,299
NSYPIN	144
NSYPIN106	49,60
NSYPIN108	49,60,144
NSYPIN126	49,60
NSYPIN128	49,60,144
NSYPIN43	49,60,144
NSYPIN54	49,60,144
NSYPIN64	49,60,144
NSYPIN75	49,60,144
NSYPIN86	49,60,144
NSYPLA	232
NSYPLA10103G	26,208
NSYPLA10103TG	26,208
NSYPLA10104G	26,208
NSYPLA10104TG	26,208
NSYPLA10123G	26,208
NSYPLA10123TG	26,208
NSYPLA10124G	26,208
NSYPLA10124TG	26,208
NSYPLA1053G	26,208
NSYPLA1053TG	26,208
NSYPLA1054G	26,208
NSYPLA1054TG	26,208
NSYPLA1073G	26,208
NSYPLA1073TG	26,208
NSYPLA1074G	26,208
NSYPLA1074TG	26,208
NSYPLA12103G	26,208
NSYPLA12103TG	26,208
NSYPLA12104G	26,208
NSYPLA12104TG	26,208
NSYPLA12123G	26,208
NSYPLA12123TG	26,208
NSYPLA12124G	26,208
NSYPLA12124TG	26,208
NSYPLA12126G	26,208
NSYPLA12126TG	26,208
NSYPLA1253G	26,208
NSYPLA1253TG	26,208
NSYPLA1254G	26,208
NSYPLA1254TG	26,208
NSYPLA1273G	26,208
NSYPLA1273TG	26,208
NSYPLA1274G	26,208
NSYPLA1274TG	26,208
NSYPLA1276G	26,208
NSYPLA1276TG	26,208
NSYPLA15103G	26,208
NSYPLA15103TG	26,208
NSYPLA15104G	26,208
NSYPLA15104TG	26,208
NSYPLA15123G	26,208
NSYPLA15123TG	26,208
NSYPLA15124G	26,208
NSYPLA15124TG	26,208
NSYPLA15126G	26,208
NSYPLA15126TG	26,208
NSYPLA1553G	26,208
NSYPLA1553TG	26,208
NSYPLA1554G	26,208
NSYPLA1554TG	26,208
NSYPLA1573G	26,208
NSYPLA1573TG	26,208
NSYPLA1574G	26,208
NSYPLA1574TG	26,208
NSYPLA1576G	26,208
NSYPLA1576TG	26,208
NSYPLA2074G	26,208
NSYPLA2074TG	26,208
NSYPLA5103G	26,208
NSYPLA5103TG	26,208
NSYPLA5104G	26,208
NSYPLA5104TG	26,208
NSYPLA5123G	26,208
NSYPLA5123TG	26,208
NSYPLA5124G	26,208
NSYPLA5124TG	26,208
NSYPLA553G	26,208
NSYPLA553TG	26,208
NSYPLA554G	26,208
NSYPLA554TG	26,208
NSYPLA573G	26,208
NSYPLA573TG	26,208
NSYPLA574G	26,208
NSYPLA574TG	26,208
NSYPLA7103G	26,208
NSYPLA7103TG	26,208
NSYPLA7104G	26,208
NSYPLA7104TG	26,208
NSYPLA7123G	26,208
NSYPLA7123TG	26,208
NSYPLA7124G	26,208
NSYPLA7124TG	26,208
NSYPLA753G	26,208
NSYPLA753TG	26,208
NSYPLA754G	26,208
NSYPLA754TG	26,208
NSYPLA773G	26,208
NSYPLA773TG	26,208
NSYPLA774G	26,208
NSYPLA774TG	26,208
NSYPLA776G	26,208
NSYPLA776TG	26,208
NSYPLAT	232
NSYPLAT10103G	27,209
NSYPLAT10104G	27,209
NSYPLAT10123G	27,209
NSYPLAT10124G	27,209
NSYPLAT1053G	27,209
NSYPLAT1054G	27,209
NSYPLAT1073G	27,209
NSYPLAT1074G	27,209
NSYPLAT12103G	27,209
NSYPLAT12104G	27,209
NSYPLAT12123G	27,209
NSYPLAT12124G	27,209
NSYPLAT12126G	27,209
NSYPLAT1253G	27,209
NSYPLAT1254G	27,209
NSYPLAT1273G	27,209
NSYPLAT1274G	27,209
NSYPLAT1276G	27,209
NSYPLAT15103G	27,209
NSYPLAT15104G	27,209
NSYPLAT15123G	27,209
NSYPLAT15124G	27,209
NSYPLAT15126G	27,209
NSYPLAT1553G	27,209
NSYPLAT1554G	27,209
NSYPLAT1573G	27,209
NSYPLAT1574G	27,209
NSYPLAT1576G	27,209
NSYPLAT2074G	27,209
NSYPLAT5103G	27,209
NSYPLAT5104G	27,209
NSYPLAT5123G	27,209
NSYPLAT5124G	27,209
NSYPLAT553G	27,209
NSYPLAT554G	27,209
NSYPLAT573G	27,209
NSYPLAT574G	27,209
NSYPLAT7103G	27,209
NSYPLAT7104G	27,209
NSYPLAT7123G	27,209
NSYPLAT7124G	27,209
NSYPLAT753G	27,209
NSYPLAT754G	27,209
NSYPLAT773G	27,209
NSYPLAT774G	27,209
NSYPLAT776G	27,209
NSYPLAZ10103G	26,208
NSYPLAZ10104G	26,208
NSYPLAZ10123G	26,208
NSYPLAZ10124G	26,208
NSYPLAZ1053G	26,208
NSYPLAZ1054G	26,208
NSYPLAZ1073G	26,208
NSYPLAZ1074G	26,208

Index of references

N	Page
NSYPLAZ12103G	26,208
NSYPLAZ12104G	26,208
NSYPLAZ12123G	26,208
NSYPLAZ12124G	26,208
NSYPLAZ12126G	26,208
NSYPLAZ1253G	26,208
NSYPLAZ1254G	26,208
NSYPLAZ1273G	26,208
NSYPLAZ1274G	26,208
NSYPLAZ1276G	26,208
NSYPLAZ15103G	26,208
NSYPLAZ15104G	26,208
NSYPLAZ15123G	26,208
NSYPLAZ15124G	26,208
NSYPLAZ15126G	26,208
NSYPLAZ1553G	26,208
NSYPLAZ1554G	26,208
NSYPLAZ1573G	26,208
NSYPLAZ1574G	26,208
NSYPLAZ1576G	26,208
NSYPLAZ2074G	26,208
NSYPLAZ5103G	26,208
NSYPLAZ5104G	26,208
NSYPLAZ5123G	26,208
NSYPLAZ5124G	26,208
NSYPLAZ553G	26,208
NSYPLAZ554G	26,208
NSYPLAZ573G	26,208
NSYPLAZ574G	26,208
NSYPLAZ7103G	26,208
NSYPLAZ7104G	26,208
NSYPLAZ7123G	26,208
NSYPLAZ7124G	26,208
NSYPLAZ753G	26,208
NSYPLAZ754G	26,208
NSYPLAZ773G	26,208
NSYPLAZ774G	26,208
NSYPLAZ776G	26,208
NSYPLAZT10103G	27,209
NSYPLAZT10104G	27,209
NSYPLAZT10123G	27,209
NSYPLAZT10124G	27,209
NSYPLAZT1053G	27,209
NSYPLAZT1054G	27,209
NSYPLAZT1073G	27,209
NSYPLAZT1074G	27,209
NSYPLAZT12103G	27,209
NSYPLAZT12104G	27,209
NSYPLAZT12123G	27,209
NSYPLAZT12124G	27,209
NSYPLAZT12126G	27,209
NSYPLAZT1253G	27,209
NSYPLAZT1254G	27,209
NSYPLAZT1273G	27,209
NSYPLAZT1274G	27,209
NSYPLAZT1276G	27,209
NSYPLAZT15103G	27,209
NSYPLAZT15104G	27,209
NSYPLAZT15123G	27,209
NSYPLAZT15124G	27,209

N	Page
NSYPLAZT15126G	27,209
NSYPLAZT1553G	27,209
NSYPLAZT1554G	27,209
NSYPLAZT1573G	27,209
NSYPLAZT1574G	27,209
NSYPLAZT1576G	27,209
NSYPLAZT2074G	27,209
NSYPLAZT5103G	27,209
NSYPLAZT5104G	27,209
NSYPLAZT5123G	27,209
NSYPLAZT5124G	27,209
NSYPLAZT553G	27,209
NSYPLAZT554G	27,209
NSYPLAZT573G	27,209
NSYPLAZT574G	27,209
NSYPLAZT7103G	27,209
NSYPLAZT7104G	27,209
NSYPLAZT7123G	27,209
NSYPLAZT7124G	27,209
NSYPLAZT753G	27,209
NSYPLAZT754G	27,209
NSYPLAZT773G	27,209
NSYPLAZT774G	27,209
NSYPLAZT776G	27,209
NSYPLD8122G	227,236
NSYPLD8500G	227,236
NSYPLD860G	227,236
NSYPLD881G	227,236
NSYPLHD	419
NSYPLM108BG	190
NSYPLM108G	189,190,203
NSYPLM108G	24
NSYPLM108TG	189,190,203
NSYPLM108TG	24
NSYPLM3025BG	190
NSYPLM3025G	24,189,190
NSYPLM3025PG	190
NSYPLM3025TG	24,189,190
NSYPLM32BG	190
NSYPLM32G	24,189,190
NSYPLM32PG	190
NSYPLM32TG	24,189,190
NSYPLM43BG	190
NSYPLM43G	24,189,190,203
NSYPLM43PG	190
NSYPLM43TG	24,189,190,203
NSYPLM43TVG	24,189,190,203
NSYPLM43VG	24,189,190
NSYPLM54BG	190
NSYPLM54G	24,189,190,203
NSYPLM54PG	190
NSYPLM54TG	24,189,190,203
NSYPLM54TVG	24,189,190,203
NSYPLM54VG	24,189,190
NSYPLM64BG	190
NSYPLM64G	24,189,190,203
NSYPLM64PG	190
NSYPLM64TG	24,189,190,203
NSYPLM64TVG	24,189,190,203
NSYPLM64VG	24,189,190

N	Page
NSYPLM75BG	190
NSYPLM75G	24,189,190,203
NSYPLM75PG	190
NSYPLM75TG	24,189,190,203
NSYPLM75TVG	24,189,190,203
NSYPLM75VG	24,189,190
NSYPLM86BG	190
NSYPLM86G	24,189,190,203
NSYPLM86PG	190
NSYPLM86TG	24,189,190,203
NSYPLM86TVG	24,189,190,203
NSYPLM86VG	24,189,190
NSYPLMRS108GA	189
NSYPLS1827DLS12	173,175
NSYPLS1827G	11,172,174
NSYPLS24	506
NSYPLS2727AG	11,174
NSYPLS2727DLS24	175
NSYPLS2727G	11,174
NSYPLS2736AG	11,174
NSYPLS2736G	11,174
NSYPLS2754AG	11,174
NSYPLS2754G	11,174
NSYPLS30	506
NSYPLS3627DLS24	175
NSYPLS3627DLS36	175
NSYPLS3636G	11,174
NSYPLS3654AG	11,174
NSYPLS3654G	11,174
NSYPLS3672AG	11,174
NSYPLS5427DLS48	175
NSYPLS5427DLS48G	185
NSYPLS5454AG	11,172,174
NSYPLS5454G	11,174
NSYPLS5472AG	11,174
NSYPLSC1827G	11,172,174
NSYPLSC2727AG	11,174
NSYPLSC2727G	11,174
NSYPLSC2736AG	11,174
NSYPLSC2736G	11,174
NSYPLSC2754AG	11,174
NSYPLSC2754G	11,174
NSYPLSC3636G	11,174
NSYPLSC3654AG	11,174
NSYPLSC3654G	11,174
NSYPLSC3672AG	11,174
NSYPLSC5454AG	11,174
NSYPLSC5454G	11,174
NSYPLSC5472AG	11,172,174
NSYPLSP1827G	11,172,174
NSYPLSP2727G	11,174
NSYPLSP2736G	11,174
NSYPLSP2754G	11,174
NSYPLSP3636G	11,174
NSYPLSP3654G	11,174
NSYPLSP5454G	11,174
NSYPMA1010	28,220
NSYPMA1012	28,220
NSYPMA105	28,220
NSYPMA107	28,220

Index of references

N	Page
NSYPMA1210	28,220
NSYPMA1212	28,220
NSYPMA125	28,220
NSYPMA127	28,220
NSYPMA1827G	175
NSYPMA2727G	175
NSYPMA2736G	175
NSYPMA2754G	175
NSYPMA3636G	175
NSYPMA3654G	175
NSYPMA3672G	175
NSYPMA510	28,220
NSYPMA5454G	175
NSYPMA5472G	175
NSYPMA55	28,220
NSYPMA710	28,220
NSYPMA712	28,220
NSYPMA75	28,220
NSYPMA77	28,220
NSYPMB1010	28,220
NSYPMB1012	28,220
NSYPMB105	28,220
NSYPMB107	28,220
NSYPMB1210	28,220
NSYPMB1212	28,220
NSYPMB125	28,220
NSYPMB127	28,220
NSYPMB1510	28,220
NSYPMB1512	28,220
NSYPMB155	28,220
NSYPMB157	28,220
NSYPMB1827	175
NSYPMB2727	175
NSYPMB2736	175
NSYPMB2754	175
NSYPMB3636	175
NSYPMB3654	175
NSYPMB510	28,220
NSYPMB5472	175
NSYPMB55	28,220
NSYPMB710	28,220
NSYPMB712	28,220
NSYPMB75	28,220
NSYPMB77	28,220
NSYPMD1510	10, 33
NSYPMD2015	10, 33
NSYPMD2520	10, 33
NSYPMD3025	10, 33
NSYPMLA103	221
NSYPMLA104	221
NSYPMLA123	221
NSYPMLA124	221
NSYPMLA126	221
NSYPMLA53	221
NSYPMLA54	221
NSYPMLA73	221
NSYPMLA74	221
NSYPMM1010	28,220,233
NSYPMM1012	28,220
NSYPMM105	28,220,420

N	Page
NSYPMM107	28,220,420
NSYPMM1210	28,220
NSYPMM1212	28,220,420
NSYPMM125	28,220,420
NSYPMM127	28,220,420
NSYPMM1510	28,220
NSYPMM1512	28,220,233,420
NSYPMM155	28,220
NSYPMM157	28,220,420
NSYPMM1827	175
NSYPMM207	28,220,420
NSYPMM2727	175
NSYPMM2736	175
NSYPMM2754	175
NSYPMM3636	175
NSYPMM3654	175
NSYPMM3672	175
NSYPMM510	28,220
NSYPMM5454	175
NSYPMM5472	175
NSYPMM55	28,220,420
NSYPMM710	28,220
NSYPMM712	28,220
NSYPMM75	28,220,420
NSYPMM77	28,220,420
NSYPMP300DLM	331
NSYPMP400DLA	201
NSYPMP400DLM	331
NSYPMP45100	509
NSYPMP45120	509
NSYPMP45160	509
NSYPMP4580	509
NSYPMP5002DLP	224,234
NSYPMP500DLA	201
NSYPMP500DLM	331
NSYPMP500DLP	224,234
NSYPMP600DLA	201
NSYPMP600DLM	331
NSYPMP7502DLP	224,234
NSYPMP750DLP	224,234
NSYPMP800DLA	201
NSYPMP800DLM	331
NSYPMP85100	23,509
NSYPMP85120	23,509
NSYPMP85160	509
NSYPMP8560	23,509
NSYPMP8580	23,509
NSYPMR105	28,220
NSYPMR107	28,220
NSYPMR125	28,220
NSYPMR127	28,220
NSYPMR155	28,220
NSYPMR157	28,220
NSYPMR1827	175
NSYPMR2727	175
NSYPMR2736	175
NSYPMR2754	175
NSYPMR3654	175
NSYPMR3672	175
NSYPMR5454	175

N	Page
NSYPMR5472	175
NSYPMR55	28,220
NSYPMR57	28,220
NSYPMR75	28,220
NSYPMR77	28,220
NSYPPC54HD	645
NSYPPC56HD	645
NSYPPC74HD	645
NSYPPC76HD	645
NSYPPCPHDSN	645
NSYPPHLT6040	260
NSYPPHLT8040	260
NSYPPS166	94
NSYPPS168	94
NSYPPS184	94
NSYPPS185	94
NSYPPS186	94
NSYPPS204	94
NSYPPS205	94
NSYPPS206	94
NSYPPS208	94
NSYPPS226	94
NSYPPS228	94
NSYPPSB	37,40,128,129
NSYPS2C27	177,185
NSYPS4C27	177
NSYPTDS1	527,529
NSYPTDS2	527,529
NSYPTDS3	527,529
NSYPTDS4	527,529
NSYPTDS5	527,529
NSYPTZ3	224
NSYPTZ32P	224
NSYPTZ4	29,219,224
NSYPTZ42P	224
NSYPTZ6	224
NSYPTZ62P	224
NSYPUNX	153
NSYRBL216146M	354
NSYRBL216296M	354
NSYRBL21656M	354
NSYRBL21686M	354
NSYRBLZ216146	354
NSYRBLZ216296	354
NSYRBLZ21656	354
NSYRBLZ21686	354
NSYRC12	463
NSYRC14	463
NSYRC16	463
NSYRC18	463
NSYRC1U	467
NSYRC20	463
NSYRC22	463
NSYRCDFIX	467
NSYRCDR12	468
NSYRCDR18	468
NSYRCINT	468
NSYRCK19KIT	463
NSYRCK19KIT6G	434
NSYRCK24	462

Index of references

N	Page
NSYRCK29	462
NSYRCK33	462
NSYRCK38	462
NSYRCK42	434,462
NSYRCK47	462
NSYRCKP12	462
NSYRCKP17	462
NSYRCKP21	462
NSYRCKP26	462
NSYRCKP4	462
NSYRCKP8	462
NSYRCKS10	463
NSYRCKS6	463
NSYRCKS8	463
NSYRCSUP15	467
NSYRCSUP25	467
NSYRE26	108,574
NSYRE60	108,574
NSYRETPLA	216
NSYRETPLAU	216
NSYRP2	501,503
NSYRPX2	501,503
NSYRSF104	639
NSYRSF104L	639
NSYRSF105	639
NSYRSF105L	639
NSYRSF106	639
NSYRSF106L	639
NSYRSF108	639
NSYRSF108L	639
NSYRSF124	639
NSYRSF124L	639
NSYRSF125	639
NSYRSF125L	639
NSYRSF126	639
NSYRSF126L	639
NSYRSF128	639
NSYRSF128L	639
NSYRSF164	639
NSYRSF164L	639
NSYRSF165	639
NSYRSF165L	639
NSYRSF166	639
NSYRSF166L	639
NSYRSF35	639
NSYRSF35L	639
NSYRSF36	639
NSYRSF36L	639
NSYRSF38	639
NSYRSF38L	639
NSYRSF44	639
NSYRSF44L	639
NSYRSF45	639
NSYRSF45L	639
NSYRSF64	639
NSYRSF64L	639
NSYRSF65	639
NSYRSF65L	639
NSYRSF66	639
NSYRSF66L	639
NSYRSF84	639
NSYRSF84L	639
NSYRSF85	639
NSYRSF85L	639
NSYRSF86	639
NSYRSF86L	639
NSYRSF88	639
NSYRSF88L	639
NSYRSFBLR	639
NSYRSW27	17,87,465
NSYRSW31	17,87,465
NSYRSW36	17,87,465
NSYRSW40	17,87,465
NSYRSW45	465
NSYRSW627	465
NSYRSW631	465
NSYRSW636	465
NSYRSW640	465
NSYRSW645	465
NSYRSWC27	17,87,466
NSYRSWC31	17,87,466
NSYRSWC36	17,87,466
NSYRSWC40	17,87,466
NSYRSWC45	466
NSYRSWH180	466
NSYRSWP12	464
NSYRSWP15	464
NSYRSWP18	464
NSYRSWP21	464
NSYRSWP6	464
NSYRSWP9	464
NSYRSWSP6	464
NSYRSWSP8	464
NSYS04	353
NSYS06	353
NSYS10	353
NSYS13M5HS	13,14,47,141,271
NSYS16	353
NSYS16M5HS	141,247,271
NSYS16M6HS	141,271
NSYS2535	353
NSYS3CM303020	492,494,518
NSYS3CM304020	492,494,518
NSYS3CM404020	492,494,518
NSYS3CM406025	492,494,518
NSYS3CM505025	492,494,518
NSYS3CM606020	492,494,518
NSYS3CM608030	492,494,518
NSYS3CM806030	492,494,518
NSYS3CVR64HD	424,426,427,564,565
NSYS3CVR84HD	424,426,427,564,565
NSYS3D101030	12,46
NSYS3D101030D	12,46,75
NSYS3D101030DP	12,46
NSYS3D101030DT	12,46
NSYS3D101030P	12,46
NSYS3D101030T	12,46
NSYS3D101230D	12,46
NSYS3D101230DP	12,46
NSYS3D101240D	12,46
NSYS3D101240DP	12,46
NSYS3D10625	12,46,75,454
NSYS3D10625P	12,46
NSYS3D10625T	12,46,454
NSYS3D10630	12,46,454
NSYS3D10630P	12,46
NSYS3D10630T	12,46,454
NSYS3D10640	12,46,454
NSYS3D10640P	12,46
NSYS3D10640T	12,46,454
NSYS3D10825	12,46,454
NSYS3D10825P	12,46
NSYS3D10825T	12,46,454
NSYS3D10830	12,46,75,454
NSYS3D10830P	12,46
NSYS3D10830T	12,46,454
NSYS3D10840	12,46,454
NSYS3D10840P	12,46
NSYS3D10840T	12,46,454
NSYS3D121030	12,46
NSYS3D121030D	12,46
NSYS3D121030DP	12,46
NSYS3D121030DT	12,46
NSYS3D121030P	12,46
NSYS3D121030T	12,46
NSYS3D121040D	12,46
NSYS3D121040DP	12,46
NSYS3D121230D	12,46
NSYS3D121230DP	12,46
NSYS3D121240D	12,46
NSYS3D121240DP	12,46
NSYS3D12630	12,46
NSYS3D12630P	12,46
NSYS3D12630T	12,46
NSYS3D12640	12,46
NSYS3D12640P	12,46
NSYS3D12640T	12,46
NSYS3D12830	12,46,454
NSYS3D12830P	12,46
NSYS3D12830T	12,46,454
NSYS3D12840	12,46,454
NSYS3D12840P	12,46
NSYS3D12840PK3	447
NSYS3D12840T	12,46,454
NSYS3D141030D	12,46,75
NSYS3D141030DP	12,46
NSYS3D3215	12,46,75
NSYS3D3215P	12,46
NSYS3D32515	12,46
NSYS3D32515P	12,46
NSYS3D32515PK3	447
NSYS3D32515T	12,46
NSYS3D3315	12,46
NSYS3D3315P	12,46
NSYS3D3315T	12,46
NSYS3D3320	12,46
NSYS3D3320P	12,46
NSYS3D3320T	12,46
NSYS3D3415	12,46
NSYS3D3415P	12,46

Index of references

N	Page
NSYS3D3415T	12,46
NSYS3D3420	12,46
NSYS3D3420P	12,46
NSYS3D3420T	12,46
NSYS3D4315	12,46
NSYS3D4315P	12,46
NSYS3D4315T	12,46
NSYS3D4320	12,46
NSYS3D4320P	12,46
NSYS3D4320PK3	447
NSYS3D4320T	12,46
NSYS3D4420	12,46
NSYS3D4420P	12,46
NSYS3D4420T	12,46
NSYS3D4620	12,46,454
NSYS3D4620P	12,46
NSYS3D4620T	12,46,454
NSYS3D4625	12,46,454
NSYS3D4625P	12,46
NSYS3D4625T	12,46,454
NSYS3D5320	12,46,75
NSYS3D5320P	12,46
NSYS3D5320T	12,46
NSYS3D5420	12,46,75
NSYS3D5420P	12,46
NSYS3D5420T	12,46
NSYS3D5425	12,46
NSYS3D5425P	12,46
NSYS3D5425T	12,46
NSYS3D5520	12,46
NSYS3D5520P	12,46
NSYS3D5520T	12,46
NSYS3D5525	12,46
NSYS3D5525P	12,46
NSYS3D5525T	12,46
NSYS3D6420	12,46
NSYS3D6420P	12,46
NSYS3D6420T	12,46
NSYS3D6425	12,46,75
NSYS3D6425P	12,46
NSYS3D6425T	12,46
NSYS3D6525	12,46
NSYS3D6525P	12,46
NSYS3D6525PK3	447
NSYS3D6525T	12,46
NSYS3D6620	12,46,75,454
NSYS3D6620P	12,46
NSYS3D6620T	12,46,454
NSYS3D6625	12,46,454
NSYS3D6625P	12,46
NSYS3D6625T	12,46,454
NSYS3D6630	12,46,454
NSYS3D6630P	12,46
NSYS3D6630T	12,46,454
NSYS3D6640	12,46,454
NSYS3D6640P	12,46
NSYS3D6640T	12,46,454
NSYS3D6830	12,46
NSYS3D6830P	12,46
NSYS3D6830T	12,46
NSYS3D6G12840P	443
NSYS3D6G32515P	443
NSYS3D6G4320P	443
NSYS3D6G6525P	443
NSYS3D6G7525P	443
NSYS3D6G8630P	443
NSYS3D7525	12,46
NSYS3D7525P	12,46
NSYS3D7525PK3	447
NSYS3D7525T	12,46
NSYS3D81030	12,46
NSYS3D81030D	12,46
NSYS3D81030DP	12,46
NSYS3D81030P	12,46
NSYS3D81230D	12,46
NSYS3D81230DP	12,46
NSYS3D8620	12,46,454
NSYS3D8620P	12,46
NSYS3D8620T	12,46,454
NSYS3D8625	12,46,454
NSYS3D8625P	12,46
NSYS3D8625T	12,46,454
NSYS3D8630	12,46,75,454
NSYS3D8630P	12,46
NSYS3D8630PK3	447
NSYS3D8630T	12,46,454
NSYS3D8640	12,46,454
NSYS3D8640P	12,46
NSYS3D8640T	12,46,454
NSYS3D8825	12,46
NSYS3D8825P	12,46
NSYS3D8825T	12,46
NSYS3D8830	12,46
NSYS3D8830P	12,46
NSYS3D8830T	12,46
NSYS3DB25315	14,327
NSYS3DB25415	14,327
NSYS3DB25515	14,327
NSYS3DB3315	14,327
NSYS3DB3415	14,327
NSYS3DB3515	14,327
NSYS3DB3615	14,327
NSYS3DB4315	14,327
NSYS3DB4815	14,327
NSYS3DB5415	14,327
NSYS3DB6415	14,327
NSYS3DCGPSTDSB	636,637,638
NSYS3DCGSB	636,637,638
NSYS3DEX10830	484
NSYS3DEX3215	484
NSYS3DEX3320	484
NSYS3DEX4320	484
NSYS3DEX4420	484
NSYS3DEX5420	484
NSYS3DEX6425	484
NSYS3DEX6625	484
NSYS3DEX7525	484
NSYS3DEX8630	484
NSYS3DLG	636,637,645
NSYS3DM10615T	14,330
NSYS3DM10815T	14,330
NSYS3DM4315T	14,330
NSYS3DM5415T	14,330
NSYS3DM6415T	14,330
NSYS3DM6615T	14,330
NSYS3DM7515T	14,330
NSYS3DM8615T	14,330
NSYS3DTL	636
NSYS3HD10640	421,426,564
NSYS3HD10840	421,426,564
NSYS3HD3215	421
NSYS3HD4320	421
NSYS3HD5420	421
NSYS3HD6425	421
NSYS3HD6630	421
NSYS3HD7525	421
NSYS3HD8630	421,426,564
NSYS3HD8840	421,426,564
NSYS3HF10830P	476
NSYS3HF4320P	476
NSYS3HF6420P	476
NSYS3HF6625P	476
NSYS3HF8630P	476
NSYS3X101030	22,140
NSYS3X101030H	22,140
NSYS3X10830	22,140
NSYS3X10830H	22,140
NSYS3X10830T	22,140
NSYS3X121030	22
NSYS3X121030H	22
NSYS3X12830	22,140
NSYS3X12830H	22,140
NSYS3X302515	22,140
NSYS3X302515H	22,140
NSYS3X3215	22,140
NSYS3X3215H	22,140
NSYS3X3315	22,140
NSYS3X3315H	22,140
NSYS3X4315	22,140
NSYS3X4315H	22,140
NSYS3X4320	22,140
NSYS3X4320H	22,140
NSYS3X4320T	22,140
NSYS3X4420	22,140
NSYS3X4420H	22,140
NSYS3X4620	22,140
NSYS3X4620H	22,140
NSYS3X5420	22,140
NSYS3X5420H	22,140
NSYS3X5420T	22,140
NSYS3X601030	22,140
NSYS3X601230	22,140
NSYS3X6420	22,140
NSYS3X6420H	22,140
NSYS3X6420T	22,140
NSYS3X6625	22,140
NSYS3X6625H	22,140
NSYS3X7525	22,140
NSYS3X7525H	22,140
NSYS3X7525T	22,140

Index of references

N	Page
NSYS3X801030	22,140
NSYS3X801230	22,140
NSYS3X8625	22,140
NSYS3X8625H	22,140
NSYS3X8625T	22,140
NSYS3X8830	22,140
NSYS3X8830H	22,140
NSYS50	353
NSYS5GPC35	382,439
NSYS5GPC38	382,439
NSYS5GPC75	382,439
NSYS5GPC78	382,439
NSYS70	353
NSYS95100	353
NSYSB130	244
NSYSB90	244
NSYSBM151512	10,36,38
NSYSBM15158	10,36,38
NSYSBM152012	10,36,38
NSYSBM15208	10,36,38
NSYSBM153012	10,36,38
NSYSBM15308	10,36,38
NSYSBM154012	10,36,38
NSYSBM15408	10,36,38
NSYSBM202012	10,36,38
NSYSBM20208	10,36,38
NSYSBM203012	10,36,38
NSYSBM20308	10,36,38
NSYSBM204012	10,36,38
NSYSBM20408	10,36,38
NSYSBM205012	10,36,38
NSYSBM20508	10,36,38
NSYSBM206012	10,36,38
NSYSBM20608	10,36,38
NSYSBM208012	10,36,38
NSYSBM303012	10,36,38
NSYSBM304012	10,36,38
NSYSBM305012	10,36,38
NSYSBM306012	10,36,38
NSYSBM308012	10,36,38
NSYSBM404012	10,36,38
NSYSBM405012	10,36,38
NSYSBM406012	10,36,38
NSYSBM408012	10,36,38
NSYSBMABS4	636
NSYSBMABS6	636
NSYSBPLA	225
NSYSBTB	248
NSYSBX15158	10,128,133
NSYSBX15308	10,128,133
NSYSBX20208	10,128,133
NSYSBX20308	10,128,133
NSYSBX204012	10,128,133
NSYSBX303012	10,128,133
NSYSC1030	107
NSYSC1040	107
NSYSC1050	107
NSYSC1060	107
NSYSC1230	107
NSYSC1240	107

N	Page
NSYSC124HD	647
NSYSC1250	107
NSYSC1260	107
NSYSC126HD	647
NSYSC1640	107
NSYSC1650	107
NSYSC1660	107
NSYSC1850	107
NSYSC1860	107
NSYSC2050	107
NSYSC2060	107
NSYSC2450	107
NSYSC2460	107
NSYSC630	107
NSYSC640	107
NSYSC64HD	647
NSYSC650	107
NSYSC660	107
NSYSC66HD	647
NSYSC830	107
NSYSC840	107
NSYSC84HD	647
NSYSC850	107
NSYSC860	107
NSYSC86HD	647
NSYSCCDINLG140	289
NSYSCCDINLG75	289
NSYSCMX10030	151
NSYSCMX10040	151
NSYSCMX12040	151
NSYSCMX12050	151
NSYSCMX16040	151
NSYSCMX16060	151
NSYSCMX6040	151
NSYSCMX8040	151
NSYSCMX8050	151
NSYSCX10060	151
NSYSCX12040	151
NSYSCX12050	151
NSYSCX12060	151
NSYSCX16040	151
NSYSCX16060	151
NSYSCX6040	151
NSYSCX6050	151
NSYSCX8040	151
NSYSCX8060	151
NSYSD10	499,506
NSYSD10R	500,503,504,506
NSYSD12	499,506
NSYSD12R	500,503,504,506
NSYSD6	499,506
NSYSD6R	500,503,504,506
NSYSD8	499,506
NSYSD8R	500,503,504,506
NSYSDC42	501,503
NSYSDC43	501,503
NSYSDC62	501,503
NSYSDC63	501,503
NSYSDCR10	301
NSYSDCR200	22,49,140,243,486

N	Page
NSYSDCR250	22,49,140,243,486
NSYSDCR300	22,49,140,243,486
NSYSDCR4	301
NSYSDCR400	49,243
NSYSDCR5	301
NSYSDCR6	301
NSYSDCR8	301
NSYSDCX42	501,503
NSYSDCX43	501,503
NSYSDCX62	501,503
NSYSDCX63	501,503
NSYSDF1010	499,504,506
NSYSDF108	499,504,506
NSYSDF1210	499,504,506
NSYSDF128	499,504,506
NSYSDF1610	499,504,506
NSYSDF168	499,504,506
NSYSDF810	499,504,506
NSYSDF88	499,504,506
NSYSDFLOCKDB5	643
NSYSDGCR10	289
NSYSDGCR5	289
NSYSDGCR6	289
NSYSDGCR8	289
NSYSDH	507,643
NSYSDP6M	113,300
NSYSDP8M	113,300
NSYSDR100	262
NSYSDR100A	262
NSYSDR120	262
NSYSDR200	264
NSYSDR200B	264
NSYSDR200BD	264
NSYSDR200D	264
NSYSDR30B	262
NSYSDR40B	262
NSYSDR50A	262
NSYSDR60	262
NSYSDR60A	262
NSYSDR80	262
NSYSDR80A	262
NSYSDRC	114
NSYSDRSDCR300	49,243
NSYSDRSDCR400	49,243
NSYSDT5	114,301
NSYSDT6	114,301
NSYSDT8	114,301
NSYSDX10	23,500,503,504,506
NSYSDX12	23,500,503,504,506
NSYSDX6	23,500,503,504,506
NSYSDX8	23,500,503,504,506
NSYSF12640	18,88
NSYSF12640P	18,88
NSYSF12660	18,88
NSYSF12660E	456
NSYSF12660P	18,88
NSYSF12680E	456
NSYSF12840	18,88
NSYSF12840P	18,88
NSYSF12860	18,88

Index of references

N	Page
NSYSF12860E	456
NSYSF12860P	18,88
NSYSF12880E	456
NSYSF14640	18,88
NSYSF14640P	18,88
NSYSF14840	18,88
NSYSF14840P	18,88
NSYSF16660	18,88
NSYSF16660P	18,88
NSYSF16660PC	513
NSYSF16680	18,88
NSYSF16680P	18,88
NSYSF16680PC	513
NSYSF16860	18,88
NSYSF16860P	18,88
NSYSF16880	18,88
NSYSF16880P	18,88
NSYSF181040	18,88
NSYSF1810402D	18,88
NSYSF1810402DP	18,88
NSYSF181040P	18,88
NSYSF181050	18,88
NSYSF181050P	18,88
NSYSF181060	18,88
NSYSF1810602D	18,88
NSYSF1810602DP	18,88
NSYSF181060P	18,88
NSYSF1812402D	18,88
NSYSF1812402DP	18,88
NSYSF1812502D	18,88
NSYSF1812502DP	18,88
NSYSF1812602D	18,88
NSYSF1812602DP	18,88
NSYSF18440	18,88,341
NSYSF18450	18,88,341
NSYSF18460	18,88,341
NSYSF18640	18,88
NSYSF18640P	18,88
NSYSF18640T	18,88
NSYSF18650	18,88
NSYSF18650P	18,88
NSYSF18650T	18,88
NSYSF18660	18,88
NSYSF18660P	18,88
NSYSF18660PC	513
NSYSF18680PC	513
NSYSF18680T	18,88
NSYSF18840	18,88
NSYSF18840P	18,88
NSYSF18840T	18,88
NSYSF18850	18,88
NSYSF18850P	18,88
NSYSF18850T	18,88
NSYSF18860	18,88
NSYSF188602D	18,88
NSYSF188602DP	18,88
NSYSF18860P	18,88
NSYSF18860T	18,88
NSYSF201040	18,88
NSYSF2010402D	18,88
NSYSF2010402DP	18,88
NSYSF201040P	18,88
NSYSF201040T	18,88
NSYSF201050	18,88
NSYSF2010502D	18,88
NSYSF2010502DP	18,88
NSYSF201050P	18,88
NSYSF201050T	18,88
NSYSF201060	18,88
NSYSF2010602D	18,88
NSYSF2010602DP	18,88
NSYSF201060P	18,88
NSYSF201060T	18,88
NSYSF201080	18,88
NSYSF201080P	18,88
NSYSF2012402D	18,88
NSYSF2012402DP	18,88
NSYSF2012502D	18,88
NSYSF2012502DP	18,88
NSYSF2012602D	18,88
NSYSF2012602DP	18,88
NSYSF2012802D	18,88
NSYSF2012802DP	18,88
NSYSF2016402D	18,88
NSYSF2016402DP	18,88
NSYSF2016502D	18,88
NSYSF2016502DP	18,88
NSYSF2016602D	18,88
NSYSF2016602DP	18,88
NSYSF20350	18,88,341,380
NSYSF20360	18,88,341,380,414
NSYSF20380	18,88,341,380,414
NSYSF20440	18,88,341
NSYSF20450	18,88,341
NSYSF20460	18,88,341,414
NSYSF20480	18,88,341,414
NSYSF20640	18,88
NSYSF20640P	18,88
NSYSF20640T	18,88
NSYSF20650	18,88
NSYSF20650P	18,88
NSYSF20650T	18,88
NSYSF20660	18,88
NSYSF20660E	456
NSYSF20660M	413
NSYSF20660P	18,88
NSYSF20680	18,88
NSYSF20680E	456
NSYSF20680M	413
NSYSF20680P	18,88
NSYSF208100E	456
NSYSF20840	18,88
NSYSF20840P	18,88
NSYSF20840T	18,88
NSYSF20850	18,88
NSYSF20850P	18,88
NSYSF20850T	18,88
NSYSF20860	18,88
NSYSF208602D	18,88
NSYSF208602DP	18,88
NSYSF20860E	456
NSYSF20860M	413
NSYSF20860P	18,88
NSYSF20860T	18,88
NSYSF20880	18,88
NSYSF20880E	456
NSYSF20880M	413
NSYSF20880P	18,88
NSYSF20880T	18,88
NSYSF221060	18,88
NSYSF221060P	18,88
NSYSF2212602D	18,88
NSYSF2212602DP	18,88
NSYSF2212802D	18,88
NSYSF2212802DP	18,88
NSYSF22460	18,88,341
NSYSF226100E	456
NSYSF22660	18,88
NSYSF22660E	456
NSYSF22660P	18,88
NSYSF22680	18,88
NSYSF22680E	456
NSYSF22680P	18,88
NSYSF228100E	456
NSYSF22860	18,88
NSYSF22860E	456
NSYSF22860P	18,88
NSYSF22880	18,88
NSYSF22880E	456
NSYSF22880P	18,88
NSYSF22880T	18,88
NSYSF5G20350	439
NSYSF5G20380	439
NSYSF6G20680	433
NSYSF6G20860	433
NSYSF6G20880	433
NSYSFBK	95
NSYSFBK19	23,95,153,381,415
NSYSFBKE	95
NSYSFBKF	95
NSYSFBKR	95
NSYSFBKSH	95
NSYSFC104	20,21,90,91
NSYSFC105	20,21,90,91
NSYSFC106	20,21,90,91
NSYSFC108	20,21,90,91
NSYSFC124	20,21,90,91
NSYSFC125	20,21,90,91
NSYSFC126	20,21,90,91
NSYSFC128	20,21,90,91
NSYSFC164	21,91
NSYSFC165	21,91
NSYSFC166	21,91
NSYSFC35	21,91
NSYSFC36	21,91,414
NSYSFC38	21,91,414
NSYSFC44	20,21,90,91
NSYSFC45	20,21,90,91
NSYSFC46	20,21,90,91,414
NSYSFC48	20,21,90,91,414

Index of references

N	Page
NSYSFC64	20,21,90,91
NSYSFC65	20,21,90,91
NSYSFC66	20,21,90,91,413
NSYSFC68	20,21,90,91,413
NSYSFC84	20,21,90,91
NSYSFC85	20,21,90,91
NSYSFC86	20,21,90,91,413
NSYSFC88	20,21,90,91,413
NSYSFCVR124HD	424,426,427,564,565
NSYSFCVR126HD	424,426,427,564,565
NSYSFCVR64HD	424,426,427,564,565
NSYSFCVR66HD	424,426,427,564,565
NSYSFCVR84HD	424,426,427,564,565
NSYSFCVR86HD	424
NSYSFD126	20,90,92,111
NSYSFD126T	20,90
NSYSFD128	20,90,92,111
NSYSFD128T	20,90
NSYSFD146	20,90,92,111
NSYSFD146T	20,90
NSYSFD148	20,90,92,111
NSYSFD148T	20,90
NSYSFD166	20,90,92,111
NSYSFD166T	20,90
NSYSFD168	20,90,92,111
NSYSFD168T	20,90
NSYSFD1810	20,90
NSYSFD18102D	20,90
NSYSFD1810T	20,90
NSYSFD18122D	20,90
NSYSFD18122DT	20,90
NSYSFD184	20,90,92,111
NSYSFD185	92,111
NSYSFD186	20,90,92,111
NSYSFD186T	20,90
NSYSFD188	20,90,92,111
NSYSFD1882D	20,90
NSYSFD188T	20,90
NSYSFD2010	21,91
NSYSFD20102D	21,91
NSYSFD2010T	21,91
NSYSFD20122D	21,91
NSYSFD20122DT	21,91
NSYSFD20162D	21,91
NSYSFD203	21,91,111,414
NSYSFD204	21,91,92,111,414
NSYSFD205	92,111
NSYSFD206	21,91,92,111
NSYSFD206T	21,91
NSYSFD207	111,639
NSYSFD207T	639
NSYSFD208	21,91,92,111
NSYSFD2082D	21,91
NSYSFD208T	21,91
NSYSFD2210	21,91
NSYSFD2210T	21,91
NSYSFD22122D	21,91
NSYSFD22122DT	21,91
NSYSFD224	21,91,92,111
NSYSFD225	92,111

N	Page
NSYSFD226	21,91,92,111
NSYSFD226T	21,91
NSYSFD228	21,91,92,111
NSYSFD228T	21,91
NSYSFDHD12122D	647
NSYSFDHD126	647
NSYSFDHD128	647
NSYSFDHD16122D	647
NSYSFDHD166	647
NSYSFDHD168	647
NSYSFDHD208	647
NSYSFEB	106,381,415
NSYSFECA64HD	647
NSYSFECA66HD	426,427,564,565,647
NSYSFELB	106,381,415
NSYSFHD1212402D	421,426,564
NSYSFHD1212602D	421,426,564
NSYSFHD12640	421,426,564
NSYSFHD12660	421,426,564
NSYSFHD12840	421,426,564
NSYSFHD12860	421,426,564
NSYSFHD1612402D	421,426,564
NSYSFHD1612602D	421,426,564
NSYSFHD16660	421,426,564
NSYSFHD16840	421,426,564
NSYSFHD16860	421,426,564
NSYSFHD2	117
NSYSFHD20840	421,426,564
NSYSFHD3	117
NSYSFHFBK184	478
NSYSFHFBK186	478
NSYSFHFBK2010	478
NSYSFHFBK204	478
NSYSFHFBK206	478
NSYSFHFBK208	478
NSYSFHFBK226	478
NSYSFHFBK228	478
NSYSFHNTRIM	639,640
NSYSFHPB	115
NSYSFHS1	115,639
NSYSFHS1HD	647
NSYSFLOCK24	118
NSYSFLOCKDB5	118
NSYSFLOCKS6	118
NSYSFLOCKS7	118
NSYSFLOCKS8	118
NSYSFLOCKSG8	118
NSYSFLOCKT6	118
NSYSFLOCKT7	118
NSYSFLOCKT8	118
NSYSFMDR	301
NSYSFNDR	301
NSYSFP20750	380
NSYSFP20750T	380
NSYSFP20760	380
NSYSFP20760T	380
NSYSFP20780	380
NSYSFP20780T	380
NSYSFP300	25,192
NSYSFP400	25,192

N	Page
NSYSFP500	25,192
NSYSFP5G20750	439
NSYSFP5G20780	439
NSYSFP600	25,192
NSYSFPA	380,405
NSYSFPB	248
NSYSFPB6G	434
NSYSFPSC15	36,39
NSYSFPSC20	36,39
NSYSFPSC30	36,39,49,52
NSYSFPSC40	36,39,49,52
NSYSFPSC50	36,39,49,52
NSYSFPSC60	36,39,49,52
NSYSFPSC80	36,39,49,52
NSYSFSPLMG	25,192
NSYSFTB16	106
NSYSFTB18	106
NSYSFTB24	106
NSYSFTB32	106
NSYSFV12	20,90
NSYSFV14	20,90
NSYSFV16	20,90
NSYSFV18	20,90
NSYSFV20	21,91,413,414
NSYSFV22	21,91
NSYSFWFIX	110
NSYSFX181240	23,149
NSYSFX18640	23,149
NSYSFX18840	23,149
NSYSFX201060	23,149
NSYSFX201260	23,149
NSYSFX20650	23,149
NSYSFX20840	23,149
NSYSFX20860	23,149
NSYSFXJG	23,153
NSYSGF	100
NSYSH180NC	114
NSYSHLT6040	260
NSYSHLT6060	260
NSYSHLT6080	260
NSYSHLT8040	260
NSYSHLT8060	260
NSYSHLT8080	260
NSYSIBTB	248
NSYSICR40100	256
NSYSICR40120	256
NSYSICR4030	256
NSYSICR4040	256
NSYSICR4050	256
NSYSICR4060	256
NSYSICR4080	256
NSYSICR65100	256
NSYSICR65120	256
NSYSICR6530	256
NSYSICR6540	256
NSYSICR6550	256
NSYSICR6560	256
NSYSICR6580	256
NSYSICR90100	256
NSYSICR90120	256

Index of references

N	Page
NSYSICR9030	256
NSYSICR9040	256
NSYSICR9050	256
NSYSICR9060	256
NSYSICR9080	256
NSYSIMP12	19,247
NSYSIMP14	19,247
NSYSIMP16	19,247
NSYSIMP18	19,247
NSYSIMP20	19,247
NSYSIMP22	19,247
NSYSLCKP	530,531
NSYSLCKS	530
NSYSLCKS10	531
NSYSLCKS6	531
NSYSLCKS8	531
NSYSLCR40	256
NSYSLCR50	256
NSYSLCR60	256
NSYSLCR80	256
NSYSM10M5HP	293
NSYSM1210302D	16,86
NSYSM1210302DP	16,86
NSYSM1212402D	16,86
NSYSM1212402DP	16,86
NSYSM12830	16,86
NSYSM12830P	16,86
NSYSM1410402D	16,86
NSYSM1410402DP	16,86
NSYSM1412402D	16,86
NSYSM1412402DP	16,86
NSYSM14630	16,86
NSYSM14630P	16,86
NSYSM14640	16,86
NSYSM14640P	16,86
NSYSM14830	16,86
NSYSM14830P	16,86
NSYSM14840	16,86
NSYSM14840P	16,86
NSYSM14840T	16,86
NSYSM1610302D	16,86
NSYSM1610302DP	16,86
NSYSM1610402D	16,86
NSYSM1610402DP	16,86
NSYSM1612302D	16,86
NSYSM1612302DP	16,86
NSYSM1612402D	16,86
NSYSM1612402DP	16,86
NSYSM16630	16,86
NSYSM16630P	16,86
NSYSM16640	16,86
NSYSM16640P	16,86
NSYSM16640T	16,86
NSYSM16830	16,86
NSYSM16830P	16,86
NSYSM16830T	16,86
NSYSM16840	16,86
NSYSM16840P	16,86
NSYSM16840T	16,86
NSYSM181040	16,86
NSYSM1810402D	16,86
NSYSM1810402DP	16,86
NSYSM181040P	16,86
NSYSM1810502D	16,86
NSYSM1810502DP	16,86
NSYSM1812402D	16,86
NSYSM1812402DP	16,86
NSYSM1812502D	16,86
NSYSM1812502DP	16,86
NSYSM1816402D	16,86
NSYSM1816402DP	16,86
NSYSM1816502D	16,86
NSYSM1816502DP	16,86
NSYSM18630	16,86
NSYSM18630P	16,86
NSYSM18640	16,86
NSYSM18640P	16,86
NSYSM18640T	16,86
NSYSM18650	16,86
NSYSM18650P	16,86
NSYSM18830	16,86
NSYSM18830P	16,86
NSYSM18830T	16,86
NSYSM18840	16,86
NSYSM18840P	16,86
NSYSM18840T	16,86
NSYSM18850	16,86
NSYSM18850P	16,86
NSYSM18850T	16,86
NSYSM18860	16,86
NSYSM18860P	16,86
NSYSM2010402D	16,86
NSYSM2010402DP	16,86
NSYSM2010502D	16,86
NSYSM2010502DP	16,86
NSYSM2012402D	16,86
NSYSM2012402DP	16,86
NSYSM2012502D	16,86
NSYSM2012502DP	16,86
NSYSM2012602D	16,86
NSYSM2012602DP	16,86
NSYSM2016402D	16,86
NSYSM2016402DP	16,86
NSYSM2016502D	16,86
NSYSM2016502DP	16,86
NSYSM2016602D	16,86
NSYSM2016602DP	16,86
NSYSM20630	16,86
NSYSM20630P	16,86
NSYSM20640	16,86
NSYSM20640P	16,86
NSYSM20640T	16,86
NSYSM20650	16,86
NSYSM20650P	16,86
NSYSM20830	16,86
NSYSM20830P	16,86
NSYSM20830T	16,86
NSYSM20840	16,86
NSYSM20840P	16,86
NSYSM20840T	16,86
NSYSM20850	16,86
NSYSM20850P	16,86
NSYSM20850T	16,86
NSYSM20860	16,86
NSYSM20860P	16,86
NSYSM20860T	16,86
NSYSMBCE10	105
NSYSMBCE6	105
NSYSMBCE8	105
NSYSMBK	95
NSYSMD12102D	640
NSYSMD12122D	640
NSYSMD14102D	640
NSYSMD14122D	640
NSYSMD16102D	640
NSYSMD16122D	640
NSYSMD18162D	640
NSYSMDR	301
NSYSMEB	106
NSYSMEC103	102
NSYSMEC1031	640
NSYSMEC104	102
NSYSMEC1041	640
NSYSMEC105	102
NSYSMEC1051	640
NSYSMEC63	102
NSYSMEC631	640
NSYSMEC64	102
NSYSMEC641	640
NSYSMEC65	102
NSYSMEC651	640
NSYSMEC66	102
NSYSMEC661	640
NSYSMEC83	102
NSYSMEC831	640
NSYSMEC84	102
NSYSMEC841	640
NSYSMEC85	102
NSYSMEC851	640
NSYSMEC86	102
NSYSMEC861	640
NSYSMHR10	258
NSYSMHR12	258
NSYSMHR16	258
NSYSMHR6	258
NSYSMHR8	258
NSYSMNDR	301
NSYSMP2D4	250
NSYSMP2D5	250,335
NSYSMP2D6	250
NSYSMP2D8	250
NSYSMPB	248,250
NSYSMPFA	247
NSYSMPFB	247
NSYSMPS4	248
NSYSMPS5	248
NSYSMPS6	248
NSYSMPS8	248
NSYSMPSB	248
NSYSMPSE10	249

Index of references

N	Page
NSYSMPSE12	249
NSYSMPSE6	249
NSYSMPSE8	249
NSYSMVR12	258
NSYSMVR14	258
NSYSMVR16	258
NSYSMVR18	258
NSYSMVR20	258
NSYSMWFIX	110
NSYSMX141030	23,149
NSYSMX16660PC	517
NSYSMX16840	23,149
NSYSMX181240	23,149
NSYSMX181240H	23,149
NSYSMX181640	23,149
NSYSMX181640H	23,149
NSYSMX18640	23,149
NSYSMX18660PC	517
NSYSMX18840	23,149
NSYSMX18840H	23,149
NSYSMX201040	23,149
NSYSMX201040H	23,149
NSYSMX201250	23,149
NSYSMX201250H	23,149
NSYSMX201660	23,149
NSYSMX201660H	23,149
NSYSMX20850	23,149
NSYSMXEB	153
NSYSNLPLA	216
NSYSNM6	251,265,270
NSYSNM8	251,265,270
NSYSNSM6	251,265,270
NSYSNSM8	251,265,270
NSYSODS	530,531
NSYSPB6100	99
NSYSPB8100	99
NSYSPBC35	340
NSYSPBC36	340
NSYSPBC38	340
NSYSPC	293
NSYSPCD	293
NSYSPCP	293
NSYSPCR	100
NSYSPF10100	16,19,49,54,86,98,504
NSYSPF10200	17,19,49,54,87,98,457,504
NSYSPF12100	16,19,49,54,86,98,504
NSYSPF12200	17,19,49,54,87,98,504
NSYSPF16100	16,19,86,98,504
NSYSPF16200	17,19,87,98,504
NSYSPF3100	19,98,380,415
NSYSPF3200	19,98,380,415
NSYSPF4100	19,98,415
NSYSPF4200	19,98,415
NSYSPF6100	16,19,49,54,86,89,98,415, 457,504,514
NSYSPF6200	17,19,49,54,87,98,415,457, 504,514
NSYSPF7100	380
NSYSPF7200	380

N	Page
NSYSPF8100	16,19,49,54,86,98,415, 457,504
NSYSPF8200	17,19,49,54,87,98,415,457,504
NSYSPFV6100	99,458
NSYSPFV8100	99,458
NSYSPFVX12200	423,427,565
NSYSPFVX6200	423,427,565
NSYSPFVX8200	423,427,565
NSYSPFX10100	23,141,150,504
NSYSPFX10100H	141,150
NSYSPFX10200	23,141,150,504
NSYSPFX10200H	141,150
NSYSPFX12100	23,150,504
NSYSPFX12100H	150
NSYSPFX12200	23,150,423,504
NSYSPFX12200H	150
NSYSPFX16100	23,150
NSYSPFX16100H	150
NSYSPFX16200	23,150
NSYSPFX16200H	150
NSYSPFX6100	23,150,504,517
NSYSPFX6200	23,150,423,504,517
NSYSPFX8100	23,141,150,504
NSYSPFX8100H	141,150
NSYSPFX8200	23,141,150,423,504
NSYSPFX8200H	141,150
NSYSPLA100	29,219,225,234
NSYSPLA125	29,219,225,234
NSYSPLA150	29,219,225,234
NSYSPLA75	29,219,225,234
NSYSPLD	228
NSYSPLK	101
NSYSPLVX3200	423
NSYSPLVX4200	423,427,565
NSYSPLVX4200SF	423
NSYSPLVX6200	427,565
NSYSPLVX6200SF	423
NSYSPM6	101
NSYSPMP25100	221,246
NSYSPMP25120	246
NSYSPMP2540	246,249
NSYSPMP2560	246
NSYSPMP2575	221,246
NSYSPMP2580	246
NSYSPMP40100	221,246,510
NSYSPMP40120	246,510
NSYSPMP40160	246,510
NSYSPMP4040	246,249
NSYSPMP4060	246
NSYSPMP4080	246,510
NSYSPMP60100	246
NSYSPMP60120	246
NSYSPMP6040	246,249
NSYSPMP6060	246
NSYSPMP6080	246
NSYSPRJ	299
NSYSPS10100	457
NSYSPS3100	16,86,98
NSYSPS3100SD	49,54
NSYSPS3200	17,87,98

N	Page
NSYSPS3200SD	49,54
NSYSPS4100	16,19,86,98
NSYSPS4100SD	49,54,505
NSYSPS4200	17,19,87,98
NSYSPS4200SD	49,54,505
NSYSPS5100	16,19,86,98,380
NSYSPS5100SD	505
NSYSPS5200	17,19,87,98,380
NSYSPS5200SD	505
NSYSPS6100	16,19,86,98,380,415,457,514
NSYSPS6100SD	505
NSYSPS6200	17,19,87,98,380,415,457,514
NSYSPS6200SD	505
NSYSPS8100	19,98,380,415,457,514
NSYSPS8200	19,98,380,415,457,514
NSYSPSJ	299
NSYSPSX3100	23,141,150
NSYSPSX3100H	141,150
NSYSPSX3200	23,141,150,423,427,565
NSYSPSX3200H	141,150
NSYSPSX4100	23,150
NSYSPSX4100H	150
NSYSPSX4100SF	23
NSYSPSX4200	23,150,423
NSYSPSX4200H	150
NSYSPSX4200SF	23,423
NSYSPSX5100	23,150,505
NSYSPSX5100H	150
NSYSPSX5100SF	23
NSYSPSX5200	23,150,505
NSYSPSX5200H	150
NSYSPSX5200SF	23
NSYSPSX6100	23,150,517
NSYSPSX6100H	150
NSYSPSX6100SF	23
NSYSPSX6200	23,150,517
NSYSPSX6200H	150
NSYSPSX6200SF	23,423
NSYSPV6100	99,458
NSYSPV8100	99,458
NSYSQCR12040	639
NSYSQCR12050	639
NSYSQCR12060	639
NSYSQCR12080	639
NSYSQCR40100	255
NSYSQCR40120	255
NSYSQCR4040	255,259
NSYSQCR4050	255,259
NSYSQCR4060	255,259
NSYSQCR4080	255,259
NSYSQCR65100	255
NSYSQCR65120	255
NSYSQCR6540	255
NSYSQCR6550	255
NSYSQCR6560	255
NSYSQCR6580	255
NSYSQCR90100	255
NSYSQCR90120	255
NSYSQCR9040	255
NSYSQCR9050	255

Index of references

N	Page
NSYSQCR9060	255
NSYSQCR9080	255
NSYST30M6	271
NSYST30M6S	271
NSYST40M8	271
NSYSTBR3	250
NSYSTBR4	250
NSYSTBR5	250
NSYSTBR6	250
NSYSTDCSX	143
NSYSTDCX2H	143
NSYSTDCXH	143
NSYSTDNCSX	143
NSYSTMP22100	246
NSYSTMP22120	246
NSYSTMP2260	246
NSYSTMP2280	246
NSYSTMP45100	246
NSYSTMP45120	246
NSYSTMP4560	246
NSYSTMP4580	246
NSYSTMP60100	246,510
NSYSTMP60120	246,510
NSYSTMP6060	246
NSYSTMP6080	246,510
NSYSTMP82100	246
NSYSTMP82120	246
NSYSTMP8260	246
NSYSTMP8280	246
NSYSTW	299
NSYSUCR200WM	56
NSYSUCR250WM	56
NSYSUCR300WM	56
NSYSUCR400WM	56
NSYSUCR40100	254
NSYSUCR40110	101,254
NSYSUCR40120	254
NSYSUCR40140	254
NSYSUCR40160	254
NSYSUCR40180	254
NSYSUCR40200	254,380,405,410
NSYSUCR40220	254
NSYSUCR4030	101,254
NSYSUCR4040	101,254,259
NSYSUCR4050	101,254,259
NSYSUCR4060	254,259,514
NSYSUCR4070	101,254
NSYSUCR4080	254,259,514
NSYSUCR4090	101,254
NSYSUCR65100	254
NSYSUCR65120	254
NSYSUCR65140	254
NSYSUCR65160	254
NSYSUCR65180	254
NSYSUCR65200	254
NSYSUCR65220	254
NSYSUCR6530	254
NSYSUCR6540	254
NSYSUCR6550	254
NSYSUCR6560	254

N	Page
NSYSUCR6580	254
NSYSUCR90100	254
NSYSUCR90110	101,254
NSYSUCR90120	254
NSYSUCR90140	254
NSYSUCR90160	254
NSYSUCR90180	254
NSYSUCR90200	254
NSYSUCR90220	254
NSYSUCR9030	101,254
NSYSUCR9040	101,254
NSYSUCR9050	101,254
NSYSUCR9060	254
NSYSUCR9070	101,254
NSYSUCR9080	254
NSYSUCR9090	101,254
NSYSUPLA3G	210
NSYSUPLA3TG	210
NSYSUPLA4G	210
NSYSUPLA4TG	210
NSYSVR606	108,462
NSYSVR608	108,462
NSYSVR806	108,462
NSYSVR808	108,462
NSYSW	299
NSYSWMBP	636,637,638,645
NSYSWMCH	636,637,638,645
NSYSWMEL	636,637,638,644,645
NSYTBC3105	340
NSYTBC3106	340
NSYTBC3108	340
NSYTBC3125	340
NSYTBC3126	340
NSYTBC3128	340
NSYTBC335	340
NSYTBC336	340
NSYTBC338	340
NSYTBC345	340
NSYTBC346	340
NSYTBC348	340
NSYTBC365	340
NSYTBC366	340
NSYTBC368	340
NSYTBC385	340
NSYTBC386	340
NSYTBC388	340
NSYTBP11116	11,160
NSYTBP1176	11,160
NSYTBP1397	11,160
NSYTBP1397T	11,160
NSYTBP16128	11,160
NSYTBP16128T	11,160
NSYTBP191210H	11,160
NSYTBP191210HT	11,160
NSYTBP19128	11,160
NSYTBP19128T	11,160
NSYTBP191610H	11,160
NSYTBP191610HT	11,160
NSYTBP19168	11,160
NSYTBP19168T	11,160

N	Page
NSYTBP241910	11,160
NSYTBP241910H	11,160
NSYTBP241910HT	11,160
NSYTBP241910T	11,160
NSYTBP241912H	11,160
NSYTBP241912HT	11,160
NSYTBP24198	11,160
NSYTBP24198T	11,160
NSYTBP292412	11,160
NSYTBP292412H	11,160
NSYTBP292412HT	11,160
NSYTBP292412T	11,160
NSYTBP292416H	11,160
NSYTBP292416HT	11,160
NSYTBP29248	11,160
NSYTBP29248T	11,160
NSYTBP342912	11,160
NSYTBP342912T	11,160
NSYTBP342916H	11,160
NSYTBP342916HT	11,160
NSYTBP775	11,160
NSYTBP885	11,160
NSYTBPASBS	167
NSYTBS111113H	11,160
NSYTBS11116	11,160
NSYTBS1176	11,160
NSYTBS1179H	11,160
NSYTBS1397	11,160
NSYTBS1397T	11,160
NSYTBS16128	11,160
NSYTBS16128T	11,160
NSYTBS191210H	11,160
NSYTBS191210HT	11,160
NSYTBS19128	11,160
NSYTBS19128T	11,160
NSYTBS191610H	11,160
NSYTBS191610HT	11,160
NSYTBS19168	11,160
NSYTBS19168T	11,160
NSYTBS241910	11,160
NSYTBS241910H	11,160
NSYTBS241910HT	11,160
NSYTBS241910T	11,160
NSYTBS241912H	11,160
NSYTBS241912HT	11,160
NSYTBS24198	11,160
NSYTBS24198T	11,160
NSYTBS292412	11,160
NSYTBS292412H	11,160
NSYTBS292412HT	11,160
NSYTBS292412T	11,160
NSYTBS292416H	11,160
NSYTBS292416HT	11,160
NSYTBS29248	11,160
NSYTBS29248T	11,160
NSYTBS342912	11,160
NSYTBS342912T	11,160
NSYTBS342916H	11,160
NSYTBS342916HT	11,160
NSYTBS775	11,160

Index of references

N	Page
NSYTBS885	11,160
NSYTC12100	291
NSYTC6CRN	196,415
NSYTC6CSX	143
NSYTC6ME	151,196,228
NSYTC7CRN	196,415,507
NSYTC7CSX	143
NSYTC8CRN	196,415,507
NSYTC8ME	151,196,228
NSYTCD274	178
NSYTCD276	178
NSYTCD278	178
NSYTCL405ME	151,196,228
NSYTCL610ME	151
NSYTCM274	178
NSYTCRE1	638
NSYTCRE12	638
NSYTCSM6PLM	198
NSYTCSPLM	198
NSYTCT274	178
NSYTDB5ME	151,196,228
NSYTDB5PL	197
NSYTDBCRN	415
NSYTDSSF2D	639,640,641,642
NSYTEC6PL	197
NSYTEC7PL	197
NSYTEC8PL	197
NSYTEDB5PL	197
NSYTEL1242EPL	197
NSYTEL405PL	197
NSYTELFACPL	197
NSYTELJISPL	197
NSYTEMPL	197
NSYTERPL	197
NSYTET6PL	197
NSYTET8PL	197
NSYTEX5	199
NSYTEX6	199
NSYTEX8	225,230,231
NSYTEX8PLM	199
NSYTFPCRN10	13,47,62,289
NSYTFPCRN4	13,47,62,289
NSYTFPCRN5	13,47,62,289
NSYTFPCRN6	13,47,62,289
NSYTFPCRN8	13,47,62,289
NSYTHL1242EPLM	196
NSYTHL2331APLM	196
NSYTHL2433APLM	196
NSYTHL3113APLM	196
NSYTHL3131APLM	196
NSYTHL405PLM	196
NSYTHL421PLM	196
NSYTHL455PLM	196
NSYTHPLM	196
NSYTJ10030	49,56
NSYTJ10040	49,56
NSYTJ12030	49,56
NSYTJ12040	49,56
NSYTJ2015	49,56
NSYTJ2015HD	646
NSYTJ2515	49,56
NSYTJ2520	56
NSYTJ3015	49,56
NSYTJ3020	49,56
NSYTJ3020HD	646
NSYTJ4015	49,56
NSYTJ4020	49,56
NSYTJ4020HD	646
NSYTJ4025	49,56
NSYTJ4025HD	646
NSYTJ5015	56
NSYTJ5020	49,56
NSYTJ5025	49,56
NSYTJ5025HD	646
NSYTJ6020	49,56
NSYTJ6025	49,56
NSYTJ6030	49,56
NSYTJ6030HD	646
NSYTJ6040	49,56
NSYTJ6040HD	646
NSYTJ8020	56
NSYTJ8025	49,56
NSYTJ8030	49,56
NSYTJ8040	49,56
NSYTJ8040HD	646
NSYTJIS	196
NSYTJPLA103G	29,211
NSYTJPLA104G	29,211
NSYTJPLA123G	29,211
NSYTJPLA124G	29,211
NSYTJPLA126G	29,211
NSYTJPLA53G	29,211
NSYTJPLA54G	29,211
NSYTJPLA73G	29,211
NSYTJPLA74G	29,211
NSYTJPLA76G	29,211
NSYTL1242EME	151,228
NSYTL220PLM	196
NSYTL27270G	177,185
NSYTL27360G	177
NSYTL405PLM	196
NSYTLA	48,61,72,79
NSYTLA4420G	25,198
NSYTLA6420G	25,198
NSYTLAFL	61,79
NSYTLAU	48,61,79
NSYTLAUHD	646
NSYTLB	48,61,72,79
NSYTLBFL	48,61,79,285,319
NSYTLBU	48,61,79
NSYTLC	48,61,72,79,109
NSYTLCFL	48,61,79,109,285,319
NSYTLCME	48,62,109,280
NSYTLCU	48,61,79,109
NSYTLCUHD	646
NSYTLD	48,61,72,79
NSYTLDFL	48,61,79,285,319
NSYTLDME	48,62,280
NSYTLDU	48,61,79
NSYTLDUHD	646
NSYTLE	48,61,72,79
NSYTLEFL	48,61,79,285,319
NSYTLEME	48,62,280
NSYTLEU	48,61,79
NSYTLEUHD	646
NSYTLF	48,61,72,79
NSYTLF2FL	61,79,285,319
NSYTLFFL	48,61,79,285,319
NSYTLFME	48,62,280
NSYTLFU	48,61,79
NSYTLG	48,61,72,79
NSYTLG2FL	48,61,79,285,319
NSYTLG4FL	61,79,277,285,319
NSYTLGFL	48,61,79,285,319
NSYTLGME	48,62,280
NSYTLGU	48,61,79
NSYTLGUHD	646
NSYTLJISME	151,196,228
NSYTLK2414	63,67,283
NSYTLK2422	63,67,283
NSYTLK2428	63,67,283
NSYTLK2446	63,67,283
NSYTLK24M	63,67,283
NSYTLRME	151,196,228
NSYTMME	151,196
NSYTPLS1827	174
NSYTPLS2727	174
NSYTPLS2727A	175
NSYTPLS2736	174
NSYTPLS2736A	175
NSYTPLS2754	174
NSYTPLS2754A	175
NSYTPLS3636	174
NSYTPLS3654	174
NSYTPLS3654A	175
NSYTPLS3672A	175
NSYTPLS5454	174
NSYTPLS5454A	175
NSYTPLS5472A	175
NSYTPLSC1827G	174
NSYTPLSC2727AG	175
NSYTPLSC2727G	174
NSYTPLSC2736AG	175
NSYTPLSC2736G	174
NSYTPLSC2754AG	175
NSYTPLSC2754G	174
NSYTPLSC3636G	174
NSYTPLSC3654AG	175
NSYTPLSC3654G	174
NSYTPLSC3672AG	175
NSYTPLSC5454AG	175
NSYTPLSC5454G	174
NSYTPLSC5472AG	175
NSYTPLSP1827G	174
NSYTPLSP2727G	174
NSYTPLSP2736G	174
NSYTPLSP2754G	174
NSYTPLSP3636G	174
NSYTPLSP3654G	174
NSYTPLSP5454G	174

Index of references

N	Page
NSYTRAB1010	295
NSYTRAB1020	295
NSYTRAB510	295
NSYTRAB5100	295
NSYTRAB51100	295
NSYTRAB520	295
NSYTRAB530	295
NSYTRAB540	295
NSYTRAB550	295
NSYTRAB590	295
NSYTRAB610	295
NSYTRAB6100	295
NSYTRAB61100	295
NSYTRAB620	295
NSYTRAB630	295
NSYTRAB640	295
NSYTRAB650	295
NSYTRAB690	295
NSYTRAB810	295
NSYTRAB820	295
NSYTRAC162	295
NSYTRAC22	295
NSYTRAC22BL	295
NSYTRAC23	295
NSYTRAC24	295
NSYTRAC952	295
NSYTRACE24	295
NSYTRACP43	295
NSYTRACP44	295
NSYTRACPK22	295
NSYTRACPK23	295
NSYTRACR102	295
NSYTRACR162	295
NSYTRACR22	295
NSYTRACR22BL	295
NSYTRACR23	295
NSYTRACR23BL	295
NSYTRACR24	295
NSYTRACR24BL	295
NSYTRACR42	295
NSYTRACR43	295
NSYTRACR44	295
NSYTRACR62	295
NSYTRACRE24	295
NSYTRACRE44	295
NSYTRACT22	295
NSYTRAL102	295
NSYTRAL1502	295
NSYTRAL162	295
NSYTRAL210	295
NSYTRAL210BL	295
NSYTRAL210GR	295
NSYTRAL22	295
NSYTRAL220	295
NSYTRAL23	295
NSYTRAL24	295
NSYTRAL25	295
NSYTRAL410	295
NSYTRAL410BL	295
NSYTRAL410GR	295
NSYTRAL42	295
NSYTRAL420	295
NSYTRAL43	295
NSYTRAL44	295
NSYTRAL45	295
NSYTRAL610	295
NSYTRAL62	295
NSYTRP22	163,294
NSYTRP22AR	294
NSYTRP22BL	163,294
NSYTRP22PE	163,294
NSYTRP22SC	294
NSYTRP23	294
NSYTRP23AR	294
NSYTRP23BL	294
NSYTRP23PE	294
NSYTRP23SC	294
NSYTRP24	294
NSYTRP24BL	294
NSYTRP24D	294
NSYTRP24DBL	294
NSYTRP24PE	294
NSYTRP42	163,294
NSYTRP42BL	163,294
NSYTRP42PE	163,294
NSYTRP42TB	294
NSYTRP43	294
NSYTRP43BL	294
NSYTRP43PE	294
NSYTRP44	294
NSYTRP44BL	294
NSYTRP44PE	294
NSYTRR102	294
NSYTRR102BL	294
NSYTRR102PE	294
NSYTRR162	294
NSYTRR162BL	294
NSYTRR162PE	294
NSYTRR22	163,294
NSYTRR22AR	294
NSYTRR22BL	163,294
NSYTRR22M	294
NSYTRR22MBL	294
NSYTRR22MF	294
NSYTRR22MFBL	294
NSYTRR22MFF	294
NSYTRR22MP	295
NSYTRR22MPBL	295
NSYTRR22MPE	294
NSYTRR22PE	163,294
NSYTRR22SC	294
NSYTRR22SCAR	294
NSYTRR22TB	294
NSYTRR23	294
NSYTRR23AR	294
NSYTRR23BL	294
NSYTRR23PE	294
NSYTRR23SC	294
NSYTRR23SCAR	294
NSYTRR24	294
NSYTRR24BL	294
NSYTRR24D	294
NSYTRR24DBL	294
NSYTRR24M	294
NSYTRR24MBL	294
NSYTRR24MP	295
NSYTRR24MPBL	295
NSYTRR24PE	294
NSYTRR24SCD	294
NSYTRR42	163,294
NSYTRR42AR	294
NSYTRR42BL	163,294
NSYTRR42PE	163,294
NSYTRR43	294
NSYTRR43BL	294
NSYTRR43PE	294
NSYTRR44	294
NSYTRR44BL	294
NSYTRR44D	294
NSYTRR44DBL	294
NSYTRR44PE	294
NSYTRR62	294
NSYTRR62BL	294
NSYTRR62PE	294
NSYTRV102	294
NSYTRV102BL	294
NSYTRV102PE	294
NSYTRV1502BB	294
NSYTRV162	294
NSYTRV162BL	294
NSYTRV162PE	294
NSYTRV22	163,294
NSYTRV22AR	294
NSYTRV22BL	163,294
NSYTRV22M	294
NSYTRV22MBL	294
NSYTRV22MPE	294
NSYTRV22PE	163,294
NSYTRV24D	294
NSYTRV24DBL	294
NSYTRV42	294
NSYTRV42AR	294
NSYTRV42BL	294
NSYTRV42M	294
NSYTRV42MBL	294
NSYTRV42MPE	294
NSYTRV42PE	294
NSYTRV42SCD	294
NSYTRV42SF5	294
NSYTRV42SF5LA	294
NSYTRV42SF5LD	294
NSYTRV42ST	294
NSYTRV42STAR	294
NSYTRV42TB	294
NSYTRV43	294
NSYTRV43AR	294
NSYTRV43BL	294
NSYTRV43PE	294
NSYTRV44	163,294
NSYTRV44BL	163,294

Index of references

N	Page
NSYTRV44D	294
NSYTRV44DBL	294
NSYTRV44PE	163,294
NSYTRV62	294
NSYTRV62BL	294
NSYTRV62PE	294
NSYTRV62TT	294
NSYTRV62TTD	294
NSYTRV62TTPE	294
NSYTSA2414SE	63,64,281,317
NSYTSA2417SE	63,64,281,317
NSYTSA2422SE	63,64,281,317
NSYTSA2423SE	63,64,281,317
NSYTSA2429SE	63,64,281,317
NSYTSAKFL	63,67,281
NSYTSAM504SE	63,64,280,316
NSYTSAM508SE	63,64,280,316
NSYTSAM6313SE	63,64,280,316
NSYTSAM638SE	63,64,280,316
NSYTSML	143
NSYTSMLS3D	57,143
NSYTSP450	460
NSYTSPC450	460
NSYTSPLA	217
NSYTSPV450	460
NSYTT6CRN	196,415
NSYTT6ME	151,196,228
NSYTT6PL	197
NSYTT7CRN	415
NSYTT7PL	197
NSYTT8CRN	196,415,507
NSYTT8CSX	143
NSYTT8ME	151,196,228
NSYTT8PL	197
NSYTTG40	259
NSYTTG50	259
NSYTTG60	259,514
NSYTUP7032	306
NSYTUP7035	306
NSYTVR10	221,251
NSYTVR12	17,19,87,251
NSYTVR125	221,251
NSYTVR14	17,19,87,153,251,511
NSYTVR15	221,251
NSYTVR16	17,19,87,153,251
NSYTVR18	17,19,87,153,251
NSYTVR20	17,19,87,153,251
NSYTVR22	19,251
NSYTVR7	221,251
NSYTVR8	251,511
NSYTX10030	22,142
NSYTX12030	22,142
NSYTX2015	22,142
NSYTX2515	22,142
NSYTX3015	22,142
NSYTX3020	22,142
NSYTX4020	22,142
NSYTX5025	22,142
NSYTX6020	22,142
NSYTX6025	22,142
NSYTX8030	22,142
NSYUCA22	266,315
NSYUCA44	266,315
NSYUCC270	177,185
NSYUCC360	177
NSYUM27180	177
NSYUM27270	177,185
NSYUM27360	177
NSYUR20	267,315
NSYUR40	267,315
NSYUR60	267,315
NSYUT20	267,315
NSYUT40	267,315
NSYUT60	267,315
NSYUTA22	266,315
NSYUTA42	266,315
NSYUTA44	266,315
NSYUVPLA	210
NSYVA2710M	303
NSYVA2710MA	303
NSYVA2712M	303
NSYVA2712MA	303
NSYVA2716M	303
NSYVA2724M	303
NSYVA272M	303
NSYVA272MA	303
NSYVA274M	303
NSYVA274MA	303
NSYVA276M	303
NSYVA276MA	303
NSYVA278M	303
NSYVA278MA	303
NSYVD2M10U4	14,453,469
NSYVD2M10U5	14,453,469
NSYVD2M14U4	14,453,469
NSYVD2M14U5	14,453,469
NSYVD2M17U4	14,453,469
NSYVD2M17U5	14,453,469
NSYVD2M5U4	14,453,469
NSYVD2M5U5	14,453,469
NSYVD2M8U4	14,453,469
NSYVD2M8U5	14,453,469
NSYVDM10U4F	14,453
NSYVDM11UP	48,269,455
NSYVDM12UF	48,269,455
NSYVDM13U4P	14,453
NSYVDM14U4F	14,453
NSYVDM16U4P	14,453
NSYVDM16UP	48,269,455
NSYVDM17U4F	14,453
NSYVDM17UF	48,269,455
NSYVDM20U8P	48,269,455
NSYVDM20UP	48,269,455
NSYVDM21UF	48,269,455
NSYVDM25U8P	48,269,455
NSYVDM4U4P	14,453
NSYVDM5U4F	14,453
NSYVDM7U4P	14,453
NSYVDM7UP	48,269,455
NSYVDM8U4F	14,453
NSYVDM8UF	48,269,455
NSYVDM9U4P	14,453
NSYVEA9	199
NSYVPF2B4	410
NSYVPHD10	645
NSYVPHD12	645
NSYVPHD15	645
NSYVPHD5	645
NSYVPHD7	645
NSYVPLA10MG	642
NSYVPLA12MG	642
NSYVPLA15MG	642
NSYVPLA5MG	642
NSYVPLA7MG	642
NSYVPLM108	643
NSYVR18	17,19,87,153,251
NSYVR20	17,19,87,153,251
NSYVR22	19,251
NSYWMK33	50,53
NSYWMK34	50,53
NSYWMK43	50,53
NSYWMK44	50,53
NSYZA2103G	29,212
NSYZA2104G	29,212
NSYZA2123G	29,212
NSYZA2124G	29,212
NSYZA2126G	29,212
NSYZA253G	29,212
NSYZA254G	29,212
NSYZA273G	29,212
NSYZA274G	29,212
NSYZA276G	29,212
NSYZD1232G	227,236
NSYZD5300G	227,236
NSYZD630G	227,236
NSYZD831G	227,236
NSYZHPLA103G	29,215
NSYZHPLA104G	29,215
NSYZHPLA123G	29,215
NSYZHPLA124G	29,215
NSYZHPLA53G	29,215
NSYZHPLA54G	29,215
NSYZHPLA73G	29,215
NSYZHPLA74G	29,215
NSYZM253G	25,191
NSYZM263G	25,191
NSYZM283G	25,191
NSYZNPLA103G	29,213
NSYZNPLA104G	29,213
NSYZNPLA123G	29,213
NSYZNPLA124G	29,213
NSYZNPLA53G	29,213
NSYZNPLA54G	29,213
NSYZNPLA73G	29,213
NSYZNPLA74G	29,213
NSYZZ2103G	29,214
NSYZZ2104G	29,214
NSYZZ2123G	29,214
NSYZZ2124G	29,214,419
NSYZZ2124VHD	419,427,565

Index of references

N	Page
NSYZZ2126G	29,214,419
NSYZZ2126VHD	419,427,565
NSYZZ253G	29,214
NSYZZ254G	29,214,419
NSYZZ254VHD	419,427,565
NSYZZ273G	29,214
NSYZZ274G	29,214,419
NSYZZ274VHD	419,427,565
NSYZZ276G	29,214,419
NSYZZ276VHD	419,427,565
NSYZZ5103G	29,214
NSYZZ5104G	29,214
NSYZZ5123G	29,214
NSYZZ5124G	29,214
NSYZZ553G	29,214
NSYZZ554G	29,214
NSYZZ573G	29,214
NSYZZ574G	29,214

U	Page
UE16MK06EN	618

X	Page
XALE2	161
XALE2141	161
XALE3	161
XALE3255	161
XALEK170	161

Life Is On | Schneider Electric

Schneider Electric Industries SAS
35, rue Joseph Monier
CS 30323
92506 Rueil Malmaison Cedex
France

RCS Nanterre 954 503 439
Capital social 896 313 776
se.com

© 2020 Schneider Electric. All Rights Reserved. Life Is On Schneider Electric is a trademark and the property of Schneider Electric SE, its subsidiaries and affiliated companies. All other trademarks are the property of their respective owners. **UEMKCAT001EN** · 11/2020